

April 13, 2006

TO: ALL STATE AGENCIES, SCHOOL DISTRICTS, MUNICIPALITIES, VOLUNTEER
FIRE COMPANIES AND POLITICAL SUBDIVISIONS

FROM: **VICKI MACKLIN**
STATE CONTRACT PROCUREMENT OFFICER
302-857-4553

SUBJECT: **AWARD NOTICE – ADDENDUM #1 EFFECTIVE FEB 12, 2007**
CONTRACT NO. 06-108-JS
CARPET, TILES AND CARPET RECLAMATION

**TABLE OF CONTENTS
OF
KEY CONTRACT INFORMATION**

1. MANDATORY USE CONTRACT:	2
2. CONTRACT PERIOD:	2
3. VENDORS:	2
4. SHIPPING TERMS:	2
5. PRICING:	2
ADDITIONAL TERMS AND CONDITIONS	7

KEY CONTRACT INFORMATION

1. **MANDATORY USE CONTRACT:**

[\(Return to Table of Contents\)](#)

REF: Title 29, Chapter 6911(d) Delaware Code. Every state department and agency within the Executive Branch and Judicial Branch of the state government shall procure all material, equipment and nonprofessional services through the statewide contracts administered by Government Support Services, Office of Management and Budget. Delaware State University, Delaware Technical and Community College, the operations funded by Public School Districts, Delaware Transit Corporation, Department of Elections, the Legislative Branch and the Board of Pension Trustees and their consultants are specifically exempted from the requirements of this subsection.

2. **CONTRACT PERIOD:**

[\(Return to Table of Contents\)](#)

Each Vendors contract shall be valid for a one (1) year period from May 1, 2006 through April 30, 2007. Each contract may be renewed for four (4) additional one (1) year extensions through negotiation between the contractor and Government Support Services. Negotiation must be initiated no later than ninety (90) days prior to the termination of the current agreement.

This contract has been extended and will remain in effect through April 30, 2008.

3. **VENDORS:**

[\(Return to Table of Contents\)](#)

Tri State Carpet, Inc.
2 South Poplar Street
Wilmington, DE 19801
Contact: Tom Hicken
Phone: (302) 654-8193
Email: thicken@tristatecpt.com

4. **SHIPPING TERMS:**

[\(Return to Table of Contents\)](#)

F.O.B. destination.

5. **PRICING:**

[\(Return to Table of Contents\)](#)

Prices will remain firm for the term of the contract year.

PRICE SHEET

CARPET, TILES AND CARPET RECLAMATION

CONTRACT NUMBER: 06-108-JS

COMPANY NAME **Tri-State Carpet Inc.**

SPECIFICATION #1

	<u>UP TO 125 SQ YDS PRICE PER SQ YD</u>	<u>OVER 125 SQ YDS PRICE PER YD</u>	<u>TILE PRICE</u>
GLUE DOWN	\$17.65	\$15.74	
WITH PADDING	\$19.90	\$17.99	
Style/Pattern	Lees Best Regards		
Carpet Tile (If applicable)			n/a
Style/Pattern	n/a		

SPECIFICATION #2

	<u>UP TO 125 SQ YDS PRICE PER SQ YD</u>	<u>OVER 125 SQ YDS PRICE PER YD</u>	<u>TILE PRICE</u>
GLUE DOWN	\$30.71	\$26.62	
WITH PADDING	\$32.95	\$28.87	
Style/Pattern	Lees MBH Collection		
Carpet Tile (If applicable)			\$33.75
Style/Pattern	Lees MBH Collection		

SPECIFICATION #3

	<u>UP TO 125 SQ YDS PRICE PER SQ YD</u>	<u>OVER 125 SQ YDS PRICE PER YD</u>	<u>TILE PRICE</u>
GLUE DOWN	\$27.39	\$23.86	
WITH PADDING	\$29.64	\$26.11	
Style/Pattern	Lees Faculty IV		
Carpet Tile (If applicable)			\$31.45
Style/Pattern	Lees Faculty IV		

SPECIFICATION #4

	<u>UP TO 125 SQ YDS PRICE PER SQ YD</u>	<u>OVER 125 SQ YDS PRICE PER YD</u>	<u>TILE PRICE</u>
GLUE DOWN	\$22.70	\$19.95	
WITH PADDING	\$24.94	\$22.20	
Style/Pattern	Lees Transition		
Carpet Tile (If applicable)			n/a
Style/Pattern	n/a		

SPECIFICATION #5

	<u>UP TO 125 SQ YDS PRICE PER SQ YD</u>	<u>OVER 125 SQ YDS PRICE PER YD</u>	<u>TILE PRICE</u>
GLUE DOWN	\$33.33	\$28.81	
WITH PADDING	\$35.57	\$31.05	
Style/Pattern	Lees Attribute		
Carpet Tile (If applicable)			\$33.75
Style/Pattern	Lees Attribute		

SPECIFICATION #6

	<u>UP TO 125 SQ YDS PRICE PER SQ YD</u>	<u>OVER 125 SQ YDS PRICE PER YD</u>	<u>TILE PRICE</u>
GLUE DOWN	\$23.40	\$20.53	
WITH PADDING	\$25.65	\$22.77	
Style/Pattern	Lees Rivera II		
Carpet Tile (If applicable)			n/a
Style/Pattern	n/a		

SPECIFICATION #7

	<u>UP TO 125 SQ</u> <u>YDS PRICE PER</u> <u>SQ YD</u>	<u>OVER 125 SQ</u> <u>YDS PRICE PER</u> <u>YD</u>	<u>TILE PRICE</u>
GLUE DOWN	\$28.84	\$25.07	
WITH PADDING	\$31.08	\$27.31	
Style/Pattern	Lees Check up		
Carpet Tile (If applicable)			n/a
Style/Pattern	n/a		

SPECIFICATION #8

Carpet Tile		\$34.56
Style/Pattern	Lees Gulfstream II	

Carpet Manufacturer **Lees**

Padding Manufacturer **Invista**

Delivery & Installation **30** Days
A.R.O.

ADDITIONAL:
STATEWIDE

<u>CATEGORY</u>	<u>UP TO 125 SQ</u> <u>YDS</u>	<u>OVER 125 SQ</u> <u>YDS</u>
4" BASEBOARD COVING		
LINEAR FT	<u>\$0.96</u>	<u>\$0.96</u>

<u>CATEGORY</u>	<u>UP TO 125 SQ</u> <u>YDS</u>	<u>OVER 125 SQ</u> <u>YDS</u>
6" BASEBOARD COVING		
LINEAR FT	<u>\$1.28</u>	<u>\$1.28</u>

<u>CATEGORY</u>	<u>UP TO 125 SQ YDS</u>	<u>OVER 125 SQ YDS</u>
LABOR UPCHARGE FOR HOLIDAYS AND WEEKENDS		
SQ. YD.	<u>no additional charge</u>	<u>no additional charge</u>

<u>CATEGORY</u>	<u>UP TO 125 SQ YDS</u>	<u>OVER 125 SQ YDS</u>
LABOR UPCHARGE FOR EVENING HOURS (AFTER 4:30 P.M.)		
SQ. YD.	<u>no additional charge</u>	<u>no additional charge</u>

<u>CATEGORY</u>	<u>UP TO 125 SQ YDS</u>	<u>OVER 125 SQ YDS</u>
FURNITURE REMOVAL AND REPLACEMENT		
PER MAN HOUR	<u>\$49.50</u>	<u>\$49.50</u>

RECLAMATION COST PER SQUARE YD	<u>\$4.45</u>
--------------------------------	---------------

ADDITIONAL TERMS AND CONDITIONS

[\(Return to Table of Contents\)](#)

6. **PRICE ADJUSTMENT:**

If agreement is reached to extend this contract for the second, optional year, Government Support Services shall have the option of offering a determined price adjustment and shall not exceed the current Philadelphia All Urban Consumers Price Index (CPI-U), U.S. City Average. If the CPI-U is used, any increase/decrease shall reflect the change during the previous published twelve (12) month period at the time of renegotiation.

7. **BILLING:**

The successful vendor is required to "Bill as Shipped" to the respective ordering agency(s). Ordering agencies shall provide at a minimum the contract number, ship to and bill to address, contract name and phone number.

8. **PAYMENT:**

The agencies or school districts involved will authorize and process for payment each invoice within thirty (30) days after the date of receipt. The contractor or vendor must accept full payment by procurement (credit) card and/or conventional check and/or other electronic means at the State's option, without imposing any additional fees, costs or conditions.

9. **PRODUCT SUBSTITUTION:**

All items delivered during the life of the contract shall be of the same type and manufacture as specified unless specific approval is given by Government Support Services to do otherwise. Substitutions may require the submission of written specifications and product evaluation prior to any approvals being granted.

10. **ORDERING PROCEDURE:**

Successful contractors are required to have either a local telephone number within the (302) area code, a toll free (800) number, or agree to accept collect calls. Each agency is responsible for placing their orders and may be accomplished by written purchase order, telephone, fax or computer on-line systems. The contractor or vendor must accept full payment by procurement (credit) card and/or conventional check and/or other electronic means at the State's option, without imposing any additional fees, costs or conditions.

11. **HOLD HARMLESS:**

The contractor agrees that it shall indemnify and hold the State of Delaware and all its agencies harmless from and against any and all claims for injury, loss of life, or damage to or loss of use of property caused or alleged to be caused, by acts or omissions of the contractor, its employees, and invitees on or about the premises and which arise out of the contractor's performance, or failure to perform as specified in the Agreement.

12. **NON-PERFORMANCE:**

In the event the contractor does not fulfill its obligations under the terms and conditions of this contract, the ordering agency may purchase equivalent product on the open market. Any difference in cost between the contract prices herein and the price of open market product shall be the responsibility of the contractor. Under no circumstances shall monies be due the contractor in the event open market products can be obtained below contract cost. Any monies charged to the contractor may be deducted from an open invoice.

13. **FORCE MAJEURE:**

Neither the contractor nor the ordering agency shall be held liable for non-performance under the terms and conditions of this contract due, but not limited to, government restriction, strike, flood, fire, or unforeseen catastrophe beyond either party's control. Each party shall notify the other in writing of any situation that may prevent performance under the terms and conditions of this contract.

14. **AGENCY'S RESPONSIBILITIES:**

The Agency shall:

- a. Examine and review in detail all letters, reports, drawings and other documents presented by the Contractor to the Agency and render to the Contractor in writing, findings and decisions pertaining thereto within a reasonable time so as not to delay the services of Contractor.
- b. Give prompt written notice to the Contractor whenever the Agency observes or otherwise becomes aware of any development that affects the scope or timing of the Contractor's services.

15. **INSTALLATION:**

Contractor shall be responsible for installation of carpet in accordance with ANSI A117.1, 1986 - 4.5 Ground and Floor Surfaces and the manufacturer's instructions.

Any damage to existing fixtures, utilities or finished surfaces resulting from the performance of this contract shall be repaired to the User's satisfaction, before final invoice will be paid, at the Contractor's sole expense.

Carpet ordered for direct glue down shall be installed using manufacturer's recommended adhesive, trowel size and application rate. Seam sealer shall be used on all joints and applied as per the manufacturer's recommendations.

Manufacturer must provide carpet tiles to match broadloom.

15. **INSTALLATION - (Continued):**

Carpet ordered for installation over padding shall be installed using proper pad adhesive and pad tape. Carpet shall be seamed using manufacturer's recommended seaming tape and all lengths shall be power stretched.

Carpet shall be laid according to recommendations of manufacturer. Carpet shall be laid flat, level without humps or ripples. Joints shall be subtle and imperceptible. All seams shall be trimmed in a neat and workmanlike manner.

Carpet Edge Guard, Non-metallic: Extruded or molded heavy-duty rubber carpet edge guard; minimum 2" wide anchorage flange; colors to be selected by purchasing agency.

Installed carpet shall be free of spots, dirt or soil, tears and frayed or pulled tufts.

Carpet shall be thoroughly vacuumed immediately after installation.

Comply with manufacturer's recommendation for seam location and direction of carpet. Maintain uniformity in carpet direction, center seams under door. Expansion joints are not to be bridged with continuous carpet to allow for freedom of movement.

16. **MEASUREMENTS:**

Agencies will, in most instances, request that measurements be made prior to the writing of the purchase order. These measurements shall be conducted within 10 days after the Agency's verbal or written request.

17. **DELIVERY:**

Delivery and installation shall be within the following time period after receipt of order unless a longer delivery period is specified on purchase order:

STOCK: 30 Calendar Days
NON-STOCK: 60 Calendar Days

18. **PREVAILING WAGE RATES**

Pursuant to **29 Del.C. 6960**, minimum wages are to be paid various classes of laborers and mechanics which shall be based upon the wages determined by the Delaware Department of Labor, Division of Industrial Affairs, to be prevailing in the county in which the work is to be performed.

RECLAMATION

Bidders must have a comprehensive carpet reclamation program that includes the collection, transportation, processing and reuse of reclaimed carpets. Under no circumstances shall any carpet removed as a result of this contract end up in any landfill. Reclamation must comply with the following procedures:

1. Certification: Reclamation Agency and Carpet Remover shall certify in writing that used carpet was removed and recycled in accordance with the DuPont Carpet Reclamation Program or comparable reclamation program.
2. Adhesive Removal Solvents: Comply with Carpet and Rug Institute Publication 104 subparagraph 6.1.9.
3. Remove used broadloom carpets in large pieces, roll tightly and pack neatly in container. Remove adhesive according to recommendations of the Carpet and Rug Institute (CRI).
4. Deposit only clean, dry used carpets in containers. When available, include scrap and waste from new installation. Clean shall be defined as carpet free from demolition debris or asbestos contamination, garbage, and tack strips.
5. Place used carpet in container supplied by reclamation agency. Place only used commercial carpeting in collection container. Keep container locked or supervised. Maximize the amount of material in the container. Neatly stack carpet tiles or repack in cardboard boxes prior to placing in container.
6. Contaminants from work that occurs within a single room may be contained by sealing doors and other openings with duct tape at head, jamb, and sill. Use window exhaust systems to establish negative pressure in contaminant-producing work area, ensuring continuous flow of air into work area. Seal exhaust system ductwork that might leak into building or mechanical systems.

NOTE

The manufacturer listed is intended to provide bidders with an example of the quality and performance desired and should not be considered restricted to only that manufacturer. Others will be accepted unless it is determined that variances to the specifications are such that there will be an absolute impact on the quality of carpet and extent of warranties.

LEES

CARPET SPECIFICATION #1

BEST REGARD II

BROADLOOM CARPET OR APPROVED EQUAL

Construction:	Tufted
Surface Texture:	Cut Pile
Gauge:	1/8"
Stitches:	9.4
Pile Height:	.265"
Face Yarn:	Antron Legacy by Dupont
Dye System:	Piece Dyed
Face Yarn Weight:	30 oz./sq. yd.
Yarn Count:	2.70/2
Backing Materials:	Action Bac
Primary:	Woven Polypropylene
Secondary:	Woven Polypropylene
Total Weight:	63.70 oz./sq. yd.
Width:	12'
Tile Availability:	Not Available
PERFORMANCE	
Static:	3.0 kv when tested under the Standard AATCC 134-75 Test Method (70°F-20% R.H.)(21°C-20% R.H.)
Flammability:	
DOC-FF-1-70 Pill Test:	Passes
Flame Radiant Panel:	Meets NFPA Class 1 when tested under ASTM-E-648 glue down.
NBS Smoke Chamber NFPA-258:	Less than 450 Flaming Mode
WARRANTIES:	
Wear:	No more than 10% face yarn loss by weight. Normal use ten years

LEES

CARPET SPECIFICATION #2

MBH COLLECTION

BROADLOOM CARPET OR APPROVED EQUAL

Construction:	Tufted
Surface Texture:	Textured Loop Graphics
Gauge:	1/8"
Stitches:	8.8 per inch
Pile Height:	.187"
Face Yarn:	Antron Legacy by Dupont
Dye System:	Yarn Dyed
Fiber Technology:	Duracolor or approved equal
Face Yarn Weight:	26 oz./sq. yd
Yarn Count:	1245/3; 1232/3; 1238/3
Backing Materials:	Unibond or approved equal
Primary:	Woven Polypropylene
Secondary:	Woven Polypropylene
Total Weight:	77.00 oz./sq. yd
Width:	12'
Tile Availability:	DQ582
PERFORMANCE	
Static:	3.0 kv when tested under the Standard Shuffle Test, (70°F - 20% R.H.)(21°C 2% R.H.)
Flammability:	
DOC-FF-1-70 Pill Test:	Passes
Flame Radiant Panel:	Meets NFPA Class 1 when tested under ASTM-E-648 glue down.
NBS Smoke Chamber NFPA-258:	Less than 450 Flaming Mode
WARRANTIES	
Backing Material:	Lifetime of Carpet
Wear:	Lifetime of Carpet. No more than 10% face yarn loss by weight normal use.
Static:	Lifetime of Carpet
Edge Ravel:	Lifetime of Carpet. Guaranteed no edge ravel in normal use (no seam sealers required).
Delamination:	Lifetime of Carpet. Guaranteed no delamination in normal use for (no chair pads required).
Tuft Bind:	Lifetime of Carpet. Guaranteed 20 lbs. average tuft bind, wet or dry, as tested in accordance with ASTM D-1335-67.

LEES

CARPET SPECIFICATION #3

FACULTY IV

BROADLOOM CARPET OR APPROVED EQUAL

Construction:	Tufted
Surface Texture:	Multi-Level Loop
Gauge:	1/8"
Stitches:	8.3
Pile Height:	.156"-218"
Face Yarn:	Antron Legacy BCF Nylon by Dupont
Dye System:	Yarn Duracolor by Lees or approved equal
Face Yarn Weight:	26 oz./sq. yd.
Yarn Count:	1230/4; 1235/4; 1230/2/2
Backing Materials:	Unibond or approved equal
Primary:	Woven Polypropylene
Secondary:	Woven Polypropylene
Total Weight:	76.70 oz./sq. yd.
Width:	12'
Tile Availability:	DK162 18" x 18"
PERFORMANCE	
Static:	3.0 kv when tested under the Standard Shuffle Test (70°F-20% R.H.)(21°C-20% R.H.)
Flammability:	
DOC-FF-1-70 Pill Test:	Passes
Flame Radiant Panel:	Meets NFPA Class 1 when tested under ASTM-E-648 glue down.
NBS Smoke Chamber NFPA-258:	Less than 450 Flaming Mode
WARRANTIES	
Backing Material Warranty:	Lifetime of Carpet.
Wear:	Lifetime of Carpet. No more than 10% face yarn loss by weight in normal use.
Static:	Lifetime of Carpet.
Edge Ravel:	Lifetime of Carpet. Guaranteed no edge ravel in normal use (no seam sealers required)
Delamination:	Lifetime of Carpet. Guaranteed no delamination in normal use for (no chair pads required)
Tuft Bind:	Lifetime of Carpet. Guaranteed 20 lbs. average tuft bind, wet or dry, as tested in accordance with ASTM D-1335-67.

LEES

CARPET SPECIFICATION #4

TRANSITION II

BROADLOOM CARPET OR APPROVED EQUAL

Construction:	Tufted
Surface Texture:	Cut Pile
Gauge:	1/8"
Stitches:	10.7
Pile Height:	.406"
Face Yarn:	Antron Legacy by Dupont
Dye System:	Piece Dyed
Face Yarn Weight:	36 oz./sq. yd.
Yarn Count:	2.70/2
Backing Materials:	Action Bac
Primary:	Woven Polypropylene
Secondary:	Woven Polypropylene
Total Weight:	83.8 oz./sq. yd.
Width:	12'
Tile Availability:	Not Available
PERFORMANCE	
Static:	3.0 kv when tested under the Standard AATCC 134-75 Test Method (70°F-20% R.H.)(21°C-20% R.H.)
Flammability:	
DOC-FF-1-70 Pill Test:	Passes
Flame Radiant Panel:	Meets NFPA Class 1 when tested under ASTM-E-648 glue down.
NBS Smoke Chamber NFPA-258:	Less than 450 Flaming Mode
WARRANTIES:	
Wear:	No more than 10% face yarn loss by weight normal use ten years

LEES

CARPET SPECIFICATION #5

ATTRIBUTE

BROADLOOM CARPET OR APPROVED EQUAL

Construction:	Tufted
Surface Texture:	Loop Graphics
Gauge:	1/10"
Stitches:	11.1
Pile Height:	.187"
Face Yarn:	Antron Legacy by Dupont
Dye System:	Yarn Dyed Duracolor by Lees or approved equal
Face Yarn Weight:	26 oz./sq. yd.
Yarn Count:	1235/2; 1225/2
Backing Materials:	Unibond or approved equal
Primary:	Woven Polypropylene
Secondary:	Woven Polypropylene
Total Weight:	80.70 oz./sq. yd.
Width:	12'
Tile Availability:	DL452 18" x 18"
PERFORMANCE	
Static:	3.0 kv when tested under the Standard Shuffle Test (70°F-20% R.H.)(21°C-20% R.H.)
Flammability:	
DOC-FF-1-70 Pill Test:	Passes
Flame Radiant Panel:	Meets NFPA Class 1 when tested under ASTM-E-648 glue down.
NBS Smoke Chamber NFPA-258:	Less than 450 Flaming Mode
WARRANTIES:	
Backing Material Warranty:	Lifetime of Carpet.
Wear:	Lifetime of Carpet. No more than 10% face yarn loss by weight normal use ten years.
Static:	Lifetime of Carpet.
Edge Ravel:	Lifetime of Carpet. Guaranteed no edge ravel in normal use (no seam sealers required)
Delamination:	Lifetime of Carpet. Guaranteed no delamination in normal use for (no chair pads required)
Tuft Bind:	Lifetime of Carpet. Guaranteed 20 lbs. average tuft bind, wet or dry, as tested in accordance with ASTM D-1335-67.

LEES

CARPET SPECIFICATION #6

RIVERA L1395

BROADLOOM CARPET OR APPROVED EQUAL

Construction:	Tufted
Surface Texture:	Cut Pile Graphics
Gauge:	1/10"
Stitches:	10.5
Pile Height:	.281"
Face Yarn:	Antron Legacy Nylon by Dupont
Dye System:	Piece Dyed
Fiber Technology:	Not Available
Face Yarn Weight:	40 oz./sq. yd.
Yarn Count:	2.90/2; 1232/3
Backing Materials	Action Bac
Primary:	Woven Polypropylene
Secondary:	Woven Polypropylene
Total Weight:	75.80 oz./sq. yd.
Width:	12'
Tile Availability:	Not Available
PERFORMANCE	
Static:	3.0 kv when tested under the Standard Shuffle Test (70°F-20% R.H.)(21°C-20% R.H.)
Flammability:	
DOC-FF-1-70 Pill Test:	Passes
Flame Radiant Panel:	Meets NFPA Class 1 when tested under ASTM-E-648 glue down.
NBS Smoke Chamber NFPA-258:	Less than 450 Flaming Mode
WARRANTIES	
Wear:	No more than 10% face yarn loss by weight normal use ten years.

LEES

CARPET SPECIFICATION #7

CHECK-UP

BROADLOOM CARPET OR APPROVED EQUAL

Construction:	Tufted
Surface Texture:	Multi-Level Loop
Gauge:	5/64"
Stitches:	7.7
Pile Height:	.156"
Face Yarn:	Antron Legacy BCF Nylon by Dupont
Fiber Tech:	Duracolor MD by Lees or approved equal Stain/Bleach Resistant Technology
Face Yarn Weight:	20 oz./sq. yd.
Yarn Count:	1245/2
Backing Materials:	Unibond or approved equal
Primary:	Woven Polypropylene
Secondary:	Woven Polypropylene
Total Weight:	73.7 oz./sq. yd.
Width:	12'
Tile Availability:	DS292 18" x 18"
Broadloom Thermobond:	DS299 6" Width
PERFORMANCE	
Static:	3.0 kv when tested under the Standard Shuffle Test (70°F-20% R.H.)(21°C-20% R.H.)
Flammability:	
DOC-FF-1-70 Pill Test:	Passes
Flame Radiant Panel:	Meets NFPA Class 1 when tested under ASTM-E-648 glue down.
NBS Smoke Chamber NFPA-258:	Less than 450 Flaming Mode
WARRANTIES	
Backing Material Warranty:	Lifetime of Carpet.
Wear:	Lifetime of Carpet. No more than 10% face yarn loss by weight in normal use.
Static:	Lifetime of Carpet
Edge Ravel:	Lifetime of Carpet. Guaranteed no edge ravel in normal use (no seam sealers required)
Delamination:	Lifetime of Carpet. Guaranteed no delamination in normal use for (no chair pads required)
Tuft Bind:	Lifetime of Carpet. Guaranteed 20 lbs. average tuft bind, wet or dry, as tested in accordance with ASTM D-1335-67.

LEES

CARPET SPECIFICATION #8

CARPET TILE

GULFSTREAM II CARPET OR APPROVED EQUAL

Construction:	Tufted
Surface Texture:	Textured Loop Graphics
Gauge:	1/8" (31.5/10 cm)
Stitches:	10.6 per inch
Pile Height:	.167" avg. (41.73/10 cm)
Finished Pile Thickness:	.167" avg. (4.2mm)
Face Yarn:	Antron Legacy Nylon with DuraTech Soil protection by Dupont
Dye System:	Yarn dyed
Fiber Tech:	Duracolor MD by Lees or approved equal Stain Resistant System
Face Yarn Weight:	28 oz./sq. yd.
Backing Materials:	Thermabond Tile
Primary:	Reinforced synthetic
Bonding Agent:	PVC
Secondary:	Fiberglass reinforced, Thermoplastic composite
Total Weight:	148.45 oz./sq. yd. (5033.94gm/m)
Size:	18" x 18" (45.7 c.m x 45.7 cm)
Square Yards/Cartron:	6.00 (5.02m)
PERFORMANCE	
Static:	3.0 kv when tested under the Standard Shuffle Test (70°F-20% R.H.)(21°C-20% R.H.)
Flammability:	
DOC-FF-1-70 Pill Test:	Passes
Flame Radiant Panel:	Meets NFPA Class 1 when tested under ASTM-E-648 glue down.
NBS Smoke Chamber NFPA-258:	Less than 450 Flaming Mode
Construction Materials:	100% man made materials for superior stability. Slight color variation may occur from dye lot to dye lot.
WARRANTIES	
Wear:	Lifetime of Carpet. No more than 10% face yarn loss by weight in normal use.
Static:	Lifetime of Carpet
Edge Ravel:	Lifetime of Carpet. Guaranteed no edge ravel in normal use (no seam sealers required)
Delamination:	Lifetime of Carpet. Guaranteed no delamination in normal use for (no chair pads required)
Tuft Bind:	Lifetime of Carpet.