



KEYSTONE
PURCHASING
NETWORK

Specifications - Door and Hardware Schedule

Door	# Of Leafs	Width	Height	QTY	Description	Manufacturer	Part Number	Finish
1 - Double Door Entry with Vision Panel	2	72"	80"	1	Hollow Metal Door Frame	Steelcraft	DW16 4 5-1/2 3068 A-60 PA. Closer Reinforced. Exit Reinforced. Overhead Stop Reinforced. Installed with (6) Security Anchors	Primed
				2	Hollow Metal Door	Steelcraft	L16 4 3068 N A-60. Closer Reinforced. Exit Reinforced. Overhead Stop Reinforced. Top Cap 3/8" undercut.	Primed
				2	Glass	TBD	23-3/8" x 29-3/4". 1/2" insulated, tempered glass.	Clear
				6	Hinge	Ives	5BB1 4-1/2" x 4-1/2" NRP	US32D
				1	Removable Mullion	Von Duprin	4954. 7"2".	SP28
				1	Exit Device	Von Duprin	CD99NL. 3'. Right hand reverse bevel (RHRB)	US26D
				1	Rim Cylinder	Falcon	C953. 7-pin.	US26D
				2	Mortise Cylinder	Falcon	C987. 7-pin.	US26D
				1	Exit Device	Von Duprin	CD99DT. 3'. Left hand reverse bevel (LHRB).	US26D
				2	Closer	LCN	4111 x MS x ST1631. 1/RH and 1/LH.	689
				2	Overhead Stop	Glynn Johnson	104S ADJ.	US32D
				1	Threshold	Pemko	2005A x 6'	ALUM
				2	Seal	Pemko	2891 AS 3' (Head)	ALUM
				4	Seal	Pemko	2891 AS 6'8" (Jams and Mullion)	ALUM
				2	Kick Plate (Interior Side)	Ives	8400 8" x 34"	US32D
				3	Core	Falcon	C607 CKC. 7-pin. J Keyway.	US26D
				6	Key	Falcon	KB632-2 J VKC.	N/A
				6	Security Anchor	Steelcraft	Model 2509, 2520 or 2511 (Depending upon assembly method)	N/A
2 - Single Door Entry with Vision Panel	1	36"	80"	1	Hollow Metal Door Frame	Steelcraft	DW16 4 5-1/2 3068 A-60 PA. Closer Reinforced. Exit Reinforced. Overhead Stop Reinforced. Installed with (6) Security Anchors	Primed
				1	Hollow Metal Door	Steelcraft	L16 4 3068 N A-60. Closer Reinforced. Exit Reinforced. Overhead Stop Reinforced. Top Cap 3/8" undercut.	Primed
				1	Glass	TBD	6-1/4" x 21-1/4" x 1/2" insulated, tempered glass.	Clear
				3	Hinge	Ives	5BB1 4-1/2" x 4-1/2" NRP	US32D
				1	Exit Device	Von Duprin	22L. 3'. May be right hand reverse bevel (RHRB) or left hand reverse bevel (LHRB).	SP28
				1	Cylinder	Falcon	C987. 7-pin.	US26D
				1	Closer	LCN	4111 x MS x ST1631. May be 1/RH or 1/LH.	689
				1	Overhead Stop	Glynn Johnson	104S ADJ.	US32D
				1	Threshold	Pemko	2005A x 3'	ALUM
				1	Seal	Pemko	2891 AS 3' (Head)	ALUM
				2	Seal	Pemko	2891 AS 6'8" (Jams)	ALUM
				1	Kick Plate (Interior Side)	Ives	8400 8" x 34"	US32D
				1	Core	Falcon	C607 CKC. 7-pin. J Keyway.	US26D
				2	Key	Falcon	KB632-2 J VKC.	N/A
				6	Security Anchor	Steelcraft	Model 2509, 2520 or 2511 (Depending upon assembly method)	N/A

3 - Single Door Entry without Vision Panel	1	36"	80"	1	Hollow Metal Door Frame	Steelcraft	DW16 4 5-1/2 3068 A-60 PA. Closer Reinforced. Exit Reinforced. Overhead Stop Reinforced. Installed with (6) Security Anchors	Primed
				1	Hollow Metal Door	Steelcraft	L16 4 3068 N A-60. Closer Reinforced. Exit Reinforced. Overhead Stop Reinforced. Top Cap 3/8" undercut.	Primed
				3	Hinge	Ives	5BB1 4-1/2" x 4-1/2" NRP	US32D
				1	Exit Device	Von Duprin	22EO x 23OEO. 3'. May be right hand reverse bevel (RHRB) or left hand reverse bevel (LHRB).	SP28
				1	Closer	LCN	1261 RW/PA TBSRT with sex bolts x ST1631	ALUM
				1	Overhead Stop	Glynn Johnson	104S ADJ.	US32D
				1	Threshold	Pemko	2005A x 3'	ALUM
				1	Seal	Pemko	2891 AS 3' (Head)	ALUM
				2	Seal	Pemko	2891 AS 6'8" (Jams)	ALUM
				1	Kick Plate (Interior Side)	Ives	8400 8" x 34"	US32D
				6	Security Anchor	Steelcraft	Model 2509, 2520 or 2511 (Depending upon assembly method)	N/A
4 - 20-minute rated with Vision Panel	1	36"	80"	1	Hollow Metal Frame	Timely	Adjustable Frame with TA-8 standard steel trim. 20-minute rated.	Primed
				1	Wood Door	Jeldwin	36" x 80" slab with 6-7/8" x 21-78" cut out. 20-minute rated.	Imperial Oak
				1	Metal Light Kit	TBD	5" x 20"	Primed
				1	Composite Glass	TBD	6" x 21" x 1/4"	Clear
				3	Hinge	Ives	5BB1 4-1/2" x 4-1/2"	US26D
				1	Lockset	Schlage	ND70BD-RHO	US26D
				1	Closer	LCN	1261 RW/PA TBSRT with sex bolts	ALUM
				1	Wall Stop	Ives	WS407CVX	US32D/Gray
				1	Core	Falcon	C607 CKC. 7-pin. J Keyway.	US26D
				2	Key	Falcon	KB632-2 J VKC.	N/A
5 - Non-rated without Vision Panel	1	36"	80"	1	Hollow Metal Frame	Timely	Adjustable Frame with TA-8 standard steel trim.	Primed
				1	Wood Door	Jeldwin	36" x 80" slab.	Imperial Oak
				3	Hinge	Ives	5BB1 4-1/2" x 4-1/2"	US26D
				1	Lockset	Schlage	ND70BD-RHO	US26D
				1	Wall Stop	Ives	WS407CVX	US32D/Gray
				1	Core	Falcon	C607 CKC. 7-pin. J Keyway.	US26D
				2	Key	Falcon	KB632-2 J VKC.	N/A
6 - 20-minute rated Restroom	1	36"	80"	1	Hollow Metal Frame	Timely	Adjustable Frame with TA-8 standard steel trim. 20-minute rated.	Primed
				1	Wood Door	Jeldwin	36" x 80" slab. 20-minute rated.	Imperial Oak
				3	Hinge	Ives	5BB1 4-1/2" x 4-1/2"	US26D
				1	Lockset	Schlage	ND70BD-RHO	US26D
				1	Closer	LCN	1261 RW/PA TBSRT with sex bolts	ALUM
				1	Wall Stop	Ives	WS407CVX	US32D/Gray
				1	Core	Falcon	C607 CKC. 7-pin. J Keyway.	US26D
				2	Key	Falcon	KB632-2 J VKC.	N/A
7 - 20-minute rated without Vision Panel	1	36"	80"	1	Hollow Metal Frame	Timely	Adjustable Frame with TA-8 standard steel trim. 45-minute rated.	Primed
				1	Wood Door	Jeldwin	36" x 80" slab. 45-minute rated.	Imperial Oak
				3	Hinge	Ives	5BB1 4-1/2" x 4-1/2"	US26D
				1	Lockset	Schlage	ND70BD-RHO	US26D

				1	Closer	LCN	1261 RW/PA TBSRT with sex bolts	ALUM
				1	Wall Stop	Ives	WS407CVX	US32D/Gray
				1	Core	Falcon	C607 CKC. 7-pin. J Keyway.	US26D
				2	Key	Falcon	KB632-2 J VKC.	N/A
8 - Unisex Restroom	1	36"	80"	1	Hollow Metal Frame	Timely	Adjustable Frame with TA-8 standard steel trim. 20-minute rated.	Primed
				1	Wood Door	Jeldwin	36" x 80" slab. 20-minute rated.	Imperial Oak
				3	Hinge	Ives	5BB1 4-1/2" x 4-1/2"	US26D
				1	Lockset	Schlage	ND40S-RHO	US26D
				1	Closer	LCN	1261 RW/PA TBSRT with sex bolts	ALUM
				1	Wall Stop	Ives	WS407CVX	US32D/Gray
9 - Vestibule	1	36"	80"	1	Hollow Metal Frame	Timely	Adjustable Frame with TA-8 standard steel trim.	Primed
				1	Wood Door	Jeldwin	36" x 80" slab with 6-7/8" x 21-78" cut out.	Imperial Oak
				1	Metal Light Kit	TBD	5" x 20"	Primed
				1	Composite Glass	TBD	6" x 21" x 1/4"	Clear
				3	Hinge	Ives	5BB1 4-1/2" x 4-1/2"	US26D
				1	Lockset	Schlage	AL10S-RHO	US26D
				1	Closer	LCN	1261 RW/PA TBSRT with sex bolts	ALUM
10 - Storefront Entry	1	36"	80"	1	Aluminum Door and Frame	Tubelite	Medium stile. Aluminum extrusions alloy 6063-T5. Vertical stile 1-3/4" x 4". Top Rail 1-3/4" x 4" with adjustable setting block. Bottom rail 1-3/4" x 6-1/2".	Class I - Clear Anodized
					Stile and Rail Sections	Tubelite	Minimum .125" wall thickness	Class I - Clear Anodized
					Frame Sections	Tubelite	Minimum .125" wall thickness; including hardware attachment locations.	Class I - Clear Anodized
					Steel Tension Rods	Tubelite	.375" diameter. Run full width of top and bottom rails. Fixed with steel plates and lock nuts	N/A
					Weather Stripping	Tubelite	P1098A.	Felt
				1	Tempered Glass	Tubelite	Insulated 1"	Clear
				3	Hinge	Ives	5BB1 4-1/2" x 4-1/2" NRP	US32D
				1	Exit Device	Von Duprin	CD99NL. 3' x 1409. May be 1/RH or 1/LH.	US26D
				1	Sweep	Tubelite	TBD	N/A
				1	Threshold	Tubelite	E 0019. 1/2" x 4".	TBD
				1	Rim Cylinder	Falcon	C977 7-pin.	US26D
				1	Mortise Cylinder	Falcon	C987. 7-pin.	US26D
				1	Closer	LCN	4111 x MS x ST1631 x 4110-61. May be 1/RH or 1/LH.	689
				1	Overhead Stop	Glynn Johnson	104S ADJ.	US32D
				2	Core	Falcon	C607 CKC. 7-pin. J Keyway.	US26D
				6	Key	Falcon	KB632-2 J VKC.	N/A

The information contained herein is proprietary to the Keystone Purchasing Network (KPN) and it may not be reproduced or shared with any third party without the express written consent of KPN other than for the purposes of responding to this IFB.