

Michael R. Wigley, AIA, LEED AP
Randy B. Duplechain, P.E.
W. Zachary Crouch, P.E.
Michael E. Wheedleton, AIA
Jason P. Loar, P.E.
Ring W. Lardner, P.E.

**FERRIS SCHOOL FOR BOYS NEW PARKING LOT
959 CENTRE ROAD BUILDING #2 WILMINGTON DE 19805
DBF #586B036.A01 □ OMB/DFM# MC3701000049
MAY 11, 2017
ADDENDUM NO. 2**

The following Requests for Information (RFI) were received during the question period. Responses shall become part of the contract documents. Contractor must acknowledge receipt of this addendum on the Bid Form. Failure to do so may subject the Bidder to disqualification.

RFI #1:

"I would like to know if we can substitute the epoxy resin paint with Sherwin Williams traffic paint."

RESPONSE:

After conferring with owner and verifying the paint meets project specifications, it has been determined that this is an acceptable substitution for the striping requirements if a bidder so chooses. Product specifications are attached. Please note that the awarded contractor will be required to provide a 2-year warranty for all work.

Respectfully Submitted,
DAVIS, BOWEN & FRIEDEL, INC.



Ashton N. McLaughlin, P.E.
Civil Engineer

P:\State of Delaware\Ferris School for Boys\Documents\DFM\Bid Support\Addendum 2\0586B036-A01 Addendum 2.dox



Traffic & Zone Products

SETFAST® LOW VOC ACRYLIC TRAFFIC MARKING PAINT

TM5626
TM5627

WHITE
LEAD FREE YELLOW

Revised 9/09

PRODUCT INFORMATION

10.11

PRODUCT DESCRIPTION

SETFAST LOW VOC ACRYLIC TRAFFIC MARKING PAINT is a conventional dry (non-heat applied) **acetone** based paint. Acetone, as the main solvent, has Exempt Status under Federal law and does not contribute harmful VOC's.

This is 100% acrylic, which offers the following outstanding properties:

- Faster dry and hardness development.
- Performance similar to SetFast Chlorinated Rubber Traffic Paint
- Dirt resistant

PRODUCT CHARACTERISTICS

Finish:	Flat
Color:	White, LF Yellow
Volume Solids:	47%, minimum
Weight Solids:	70%, minimum
VOC (EPA Method 24):	<100 g/L; <0.83 lb/gal

Recommended Spreading Rate per coat:

Approximately 320 lineal feet of standard 4" stripe per gallon

	Minimum	Maximum
Wet mils (microns)	15.0	375
Dry mils (microns)	7.5	188
~Coverage sq ft/gal (m ² /L)	110	2.7
Theoretical coverage sq ft/gal (m ² /L) @ 1 mil / 25 microns dft	752	18.4

NOTE: Brush or roll application for small areas only.

If the asphalt is insufficiently cured, applying a thin coat (approximately 1/2 the recommended dft) generally reduces the extent of lifting and cracking.

Drying Schedule @ 15.0 mils wet (375 microns):

@ 77°F/25°C
50% RH

To touch: 5 minutes
No traffic pickup after: 5 minutes

Drying time is temperature, humidity, and film thickness dependent.

Shelf Life:	12 months, unopened Store indoors at 40°F (4.5°C) to 100°F (38°C)
Flash Point:	1°F (-17°C), PMCC
Reducer:	Not recommended
Clean Up:	Acetone, R6K9

RECOMMENDED USES

Developed for use over concrete, asphalt, brick, and other surfaced areas. Serves as a binder for glass beads to make reflective type markings. Do not use this coating over uncured asphalt surfaces such as commonly found on tennis courts, asphalt driveways, and some parking lots.

- Striping contractors
- Shopping centers
- Plant maintenance
- Curbs
- Municipalities
- Parking lots
- Airport runways

PERFORMANCE CHARACTERISTICS

- Abrasion resistant
- Bleed resistant
- High visibility
- Glass beads can be added to make reflective markings
- High hiding
- Fast drying

Federal EPA has added acetone to the list of solvents exempt from the VOC definition. State or local laws may incorporate the federal definitions, or may use their own, and may take precedence over the federal rules. Acetone may or may not be an exempt solvent where state or local regulations are in effect. Consult with your local Sherwin-Williams representative for additional information.



Traffic & Zone Products

SETFAST® LOW VOC ACRYLIC TRAFFIC MARKING PAINT

TM5626
TM5627

WHITE
LEAD FREE YELLOW

PRODUCT INFORMATION

10.11

RECOMMENDED SYSTEMS

Cured Asphalt, Concrete, and Brick:

1 ct. SetFast Low VOC Acrylic Traffic Marking Paint @ 15.0 mils (375 microns) wet and 7.5 mils (188 microns) dft, approximately 320 lineal feet of standard 4" stripe per gallon

The systems listed above are representative of the product's use, other systems may be appropriate.

SURFACE PREPARATION

Surface must be clean, dry, and in sound condition. Remove all oil, dust, grease, dirt, loose rust, and other foreign material to ensure adequate adhesion.

Refer to product Application Bulletin for detailed surface preparation information.

Minimum recommended surface preparation:

Concrete: Cured, clean, dry, sound
Asphalt: Cured, clean, dry, sound
Brick: Cured, clean, dry, sound

Surface Preparation Standards

Condition of Surface	ISO 8501-1 BS7079:A1	Swedish Std. SIS055900	SSPC	NACE
White Metal	Spa 3	Spa 3	SP 5	1
Near White Metal	Spa 2.5	Spa 2.5	SP 10	2
Commercial Blast	Spa 2	Spa 2	SP 6	3
Brush-Off Blast	Spa 1	Spa 1	SP 7	4
Hand Tool Cleaning	CS 2	CS 2	SP 3	-
Pitted & Rusted	CS 2	CS 2	SP 3	-
Rusted	CS 3	CS 3	SP 3	-
Power Tool Cleaning	D St 3	D St 3	SP 3	-

TINTING

May be tinted with up to 4 oz/gal of Blend-A-Color or Maxitoner Colorant. Only exterior grade colorants should be used. Handicap Blue may be obtained by tinting white with 2-3 oz of blue colorant per gallon. Not controlled for tinting strength.

APPLICATION CONDITIONS

Temperature: 40°F (4.5°C) minimum, 90°F (32°C) maximum (air, surface, and material)
At least 5°F (2.8°C) above dew point
Relative humidity: 85% maximum

Refer to product Application Bulletin for detailed application information.

ORDERING INFORMATION

Packaging: 5 gallon (18.9L) containers

Weight:
White: 11.64 ± 0.2 lbs/gal ; 1.40 Kg/L
Lead-free Yellow: 11.48 ± 0.2 lbs/gal ; 1.37 Kg/L

SAFETY PRECAUTIONS

Refer to the MSDS sheet before use.

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams representative for additional technical data and instructions.

WARRANTY

The Sherwin-Williams Company warrants our products to be free of manufacturing defects in accord with applicable Sherwin-Williams quality control procedures. Liability for products proven defective, if any, is limited to replacement of the defective product or the refund of the purchase price paid for the defective product as determined by Sherwin-Williams. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY SHERWIN-WILLIAMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

DISCLAIMER

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Information and Application Bulletin.



Traffic & Zone Products

SETFAST® LOW VOC ACRYLIC TRAFFIC MARKING PAINT

TM5626
TM5627

WHITE
LEAD FREE YELLOW

Revised 9/09

APPLICATION BULLETIN

10.11

SURFACE PREPARATIONS

Surface must be clean, dry, and in sound condition. Remove all oil, dust, grease, dirt, loose rust, and other foreign material to ensure adequate adhesion.

Surfaces should be clean, dry and free from loose or peeling paint. Do not apply when air or surface temperatures are below 40°F (4.5°C), or when the relative humidity exceeds 85%, or when the temperature falls below the dew point.

The presence of concrete sealers or efflorescence of new concrete may interfere with adhesion, and should be removed by extended weathering, etching, or abrasive blasting.

Most previously painted lines may be repainted without additional surface preparation, provided the old paint is tightly adhered to the surface. However, multiple layers of paint will eventually peel and will require removal.

New asphalt surfaces should ideally be allowed to age several months before striping. Solvent based paints may cause bleeding through the paint. Placing an inconspicuous test stripe to determine if the asphalt has aged sufficiently to use solvent paint is recommended. If it is necessary to paint a fresh asphalt surface, use a latex striping paint following the recommended procedures.

Surface Preparation Standards

Condition of Surface	ISO 8501-1 BS7079:A1	Swedish Std. SIS055900	SSPC	NACE
White Metal	Sa 3	Sa 3	SP 5	1
Near White Metal	Sa 2.5	Sa 2.5	SP 10	2
Commercial Blast	Sa 2	Sa 2	SP 6	3
Brush-Off Blast	Sa 1	Sa 1	SP 7	4
Hand Tool Cleaning	Rusted Pitted & Rusted	C St 2 D St 2	SP 2	-
Power Tool Cleaning	Rusted Pitted & Rusted	C St 3 D St 3	SP 3	-

APPLICATION CONDITIONS

Temperature: 40°F (4.5°C) minimum, 90°F (32°C) maximum (air, surface, and material)
At least 5°F (2.8°C) above dew point

Relative humidity: 85% maximum

APPLICATION EQUIPMENT

The following is a guide. Changes in pressures and tip sizes may be needed for proper spray characteristics. Always purge spray equipment before use with listed reducer. Any reduction must be compliant with existing VOC regulations and compatible with the existing environmental and application conditions.

ReducerNot recommended

Clean Up:Acetone, R6K9

Airless Spray Line Striping Equipment

Pressure..... 1500-2000 psi
Hose..... 3/8" ID
Tip015" - .019"
Filter..... 60 mesh

Conventional Spray

Typical fluid tip size is about 0.1" orifice, with a matching fan cap designed for striping application. Working pressures will vary with ambient temperatures. The correct pressure is the lowest pot and atomizing pressure that produces a flat line of the correct thickness. Heated air atomized spray may also be used, allowing improved sprayability but not necessarily dry time. Quick drying application can be expected at ambient temperatures within recommended range.

Brush, small areas only

Brush.....Nylon/Polyester Natural Bristle

Roller, small areas only

Cover 3/8" woven with solvent resistant core

NOTE: Fluid and atomization pressures are dependent on environmental conditions. Use the lowest pressures necessary to achieve a "flat line".

If the striping machine is also used for water based paint, care must be taken to avoid solvent contamination.

If specific application equipment is not listed above, equivalent equipment may be substituted.



Traffic & Zone Products

SETFAST® LOW VOC ACRYLIC TRAFFIC MARKING PAINT

TM5626
TM5627

WHITE
LEAD FREE YELLOW

APPLICATION BULLETIN

10.11

APPLICATION PROCEDURES

Surface preparation must be completed as indicated.

Mixing Instructions: Mix paint thoroughly to a uniform consistency with low speed power agitation prior to use.

Apply paint at the recommended film thickness and spreading rate as indicated below:

Recommended Spreading Rate per coat:

Approximately 320 lineal feet of standard 4" stripe per gallon

	Minimum	Maximum
Wet mils (microns)	15.0	375
Dry mils (microns)	7.5	188
~Coverage sq ft/gal (m ² /L)	110	2.7
Theoretical coverage sq ft/gal (m ² /L) @ 1 mil / 25 microns dft	752	18.4

NOTE: Brush or roll application for small areas only.

If the asphalt is insufficiently cured, applying a thin coat (approximately 1/2 the recommended dft) generally reduces the extent of lifting and cracking.

Drying Schedule @ 15.0 mils wet (375 microns):

@ 77°F/25°C

50% RH

To touch: 5 minutes

No traffic pickup after: 5 minutes

Drying time is temperature, humidity, and film thickness dependent.

Application of coating above maximum or below minimum recommended spreading rate may adversely affect coating performance.

CLEAN UP INSTRUCTIONS

Clean spills and spatters immediately with Acetone, R6K9. Clean tools immediately after use with Acetone, R6K9. Follow manufacturer's safety recommendations when using any solvent.

DISCLAIMER

The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of The Sherwin-Williams Company. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Consult your Sherwin-Williams representative to obtain the most recent Product Data Information and Application Bulletin.

PERFORMANCE TIPS

Spreading rates are calculated on volume solids and do not include an application loss factor due to surface profile, roughness or porosity of the surface, skill and technique of the applicator, method of application, various surface irregularities, material lost during mixing, spillage, overthinning, climatic conditions, and excessive film build.

No reduction of material is recommended as it can affect film build, appearance, and adhesion.

In order to avoid blockage of spray equipment, clean equipment before use or before periods of extended downtime with Acetone, R6K9.

Asphalt surfaces generally require aging prior to painting.

If the asphalt is insufficiently cured, applying a thin coat (approximately 1/2 the recommended dft) generally reduces the extent of lifting and cracking.

Check adhesion by applying a test strip to determine the readiness for painting.

The coating may be made into reflective paint by dropping on glass beads while the paint is still wet.

Painted surfaces can become slippery when wet. Zone Marking paints are not intended for use as floor paints, and should not be used to paint large areas subject to pedestrian traffic. For instance, painting an entire traffic stall is not recommended.

Do not paint on wet surfaces.

Do not paint when the relative humidity is above 85%.

Do not paint when the temperature is below 40°F (4.5°C).

Cool, damp conditions will prolong the drying time.

Refer to Product Information sheet for additional performance characteristics and properties.

SAFETY PRECAUTIONS

Refer to the MSDS sheet before use.

Published technical data and instructions are subject to change without notice. Contact your Sherwin-Williams representative for additional technical data and instructions.

WARRANTY

The Sherwin-Williams Company warrants our products to be free of manufacturing defects in accord with applicable Sherwin-Williams quality control procedures. Liability for products proven defective, if any, is limited to replacement of the defective product or the refund of the purchase price paid for the defective product as determined by Sherwin-Williams. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY SHERWIN-WILLIAMS, EXPRESSED OR IMPLIED, STATUTORY, BY OPERATION OF LAW OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

MATERIAL SAFETY DATA SHEET

TM5626
16 00

DATE OF PREPARATION
Mar 26, 2016

SECTION 1 — PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NUMBER

TM5626

PRODUCT NAME

SETFAST® Low VOC Acrylic Traffic Marking Paint, White

MANUFACTURER'S NAME

THE SHERWIN-WILLIAMS COMPANY
101 Prospect Avenue N.W.
Cleveland, OH 44115

Telephone Numbers and Websites

Product Information	(800) 524-5979 www.sherwin-williams.com
Regulatory Information	(216) 566-2902 www.paintdocs.com
Medical Emergency	(216) 566-2917
Transportation Emergency*	(800) 424-9300
<i>*for Chemical Emergency ONLY (spill, leak, fire, exposure, or accident)</i>	

SECTION 2 — COMPOSITION/INFORMATION ON INGREDIENTS

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
0.4	100-41-4	Ethylbenzene		
		ACGIH TLV	20 PPM	7.1 mm
		OSHA PEL	100 PPM	
		OSHA PEL	125 PPM STEL	
2	1330-20-7	Xylene		
		ACGIH TLV	100 PPM	5.9 mm
		ACGIH TLV	150 PPM STEL	
		OSHA PEL	100 PPM	
		OSHA PEL	150 PPM STEL	
27	67-64-1	Acetone		
		ACGIH TLV	500 PPM	180 mm
		ACGIH TLV	750 PPM STEL	
		OSHA PEL	1000 PPM	
0.2	14808-60-7	Quartz		
		ACGIH TLV	0.025 mg/m3 as Resp. Dust	
		OSHA PEL	0.1 mg/m3 as Resp. Dust	
6	13463-67-7	Titanium Dioxide		
		ACGIH TLV	10 mg/m3 as Dust	
		OSHA PEL	10 mg/m3 Total Dust	
		OSHA PEL	5 mg/m3 Respirable Fraction	

SECTION 3 — HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.
EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.
SKIN: Prolonged or repeated exposure may cause irritation.
INHALATION: Irritation of the upper respiratory system.

HMIS Codes

Health	2*
Flammability	3
Reactivity	0

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.
Prolonged overexposure to hazardous ingredients in Section 2 may cause adverse chronic effects to the following organs or systems:

- the liver
- the urinary system
- the reproductive system

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

SECTION 4 — FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.

INGESTION: Do not induce vomiting. Get medical attention immediately.

SECTION 5 — FIRE FIGHTING MEASURES**FLASH POINT**

1 °F PMCC

LEL

1.0

UEL

12.8

FLAMMABILITY CLASSIFICATION

RED LABEL -- Extremely Flammable, Flash below 21 °F (-6 °C)

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

SECTION 6 — ACCIDENTAL RELEASE MEASURES**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

SECTION 7 — HANDLING AND STORAGE**STORAGE CATEGORY**

DOL Storage Class IB

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Contents are EXTREMELY FLAMMABLE. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively.

During use and until all vapors are gone: Keep area ventilated - Do not smoke - Extinguish all flames, pilot lights, and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally.

Keep out of the reach of children.

SECTION 8 — EXPOSURE CONTROLS/PERSONAL PROTECTION**PRECAUTIONS TO BE TAKEN IN USE**

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist.

Wash hands after using.

This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m³ (total dust), 3 mg/m³ (respirable fraction), OSHA PEL 15 mg/m³ (total dust), 5 mg/m³ (respirable fraction).

VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

SECTION 9 — PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT	11.64 lb/gal	1394 g/l
SPECIFIC GRAVITY	1.40	
BOILING POINT	132 - 292 °F	55 - 144 °C
MELTING POINT	Not Available	
VOLATILE VOLUME	51%	
EVAPORATION RATE	Slower than ether	
VAPOR DENSITY	Heavier than air	
SOLUBILITY IN WATER	Not Available	
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical - As Packaged)		
0.61 lb/gal	73 g/l	Less Water and Federally Exempt Solvents
0.32 lb/gal	38 g/l	Emitted VOC

SECTION 10 — STABILITY AND REACTIVITY**STABILITY — Stable****CONDITIONS TO AVOID**

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

SECTION 11 — TOXICOLOGICAL INFORMATION**CHRONIC HEALTH HAZARDS**

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Ethylbenzene is classified by IARC as possibly carcinogenic to humans (2B) based on inadequate evidence in humans and sufficient evidence in laboratory animals. Lifetime inhalation exposure of rats and mice to high ethylbenzene concentrations resulted in increases in certain types of cancer, including kidney tumors in rats and lung and liver tumors in mice. These effects were not observed in animals exposed to lower concentrations. There is no evidence that ethylbenzene causes cancer in humans.

Crystalline Silica (Quartz, Cristobalite) is listed by IARC and NTP. Long term exposure to high levels of silica dust, which can occur only when sanding or abrading the dry film, may cause lung damage (silicosis) and possibly cancer.

IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

TOXICOLOGY DATA

CAS No.	Ingredient Name			
100-41-4	Ethylbenzene	LC50 RAT	4HR	Not Available
		LD50 RAT		3500 mg/kg
1330-20-7	Xylene	LC50 RAT	4HR	5000 ppm
		LD50 RAT		4300 mg/kg
67-64-1	Acetone	LC50 RAT	4HR	Not Available
		LD50 RAT		5800 mg/kg
14808-60-7	Quartz	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available
13463-67-7	Titanium Dioxide	LC50 RAT	4HR	Not Available
		LD50 RAT		Not Available

SECTION 12 — ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

SECTION 13 — DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

SECTION 14 — TRANSPORT INFORMATION

Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (ocean, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport.

US Ground (DOT)

5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY. (PAINT OR RELATED), ** DO NOT FREEZE **

Larger Containers are Regulated as:

UN1263, PAINT, 3, PG II, (ERG#128), ** DO NOT FREEZE **

DOT (Dept of Transportation) Hazardous Substances & Reportable Quantities

Acetone 5000 lb RQ

Xylenes (mixed isomers) 100 lb RQ

Bulk Containers may be Shipped as (check reportable quantities):

UN1263, PAINT, 3, PG II, (ERG#128), ** DO NOT FREEZE **

Canada (TDG)

UN1263, PAINT, 3, PG II, LIMITED QUANTITY, (ERG#128), ** DO NOT FREEZE **

IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN1263, PAINT, 3, PG II, (-17 C c.c.), EmS F-E, S-E, ** DO NOT FREEZE **

IMO

5 Liters (1.3 Gallons) and Less may be Shipped as Limited Quantity.

UN1263, PAINT, 3, PG II, (-17 C c.c.), EmS F-E, S-E, ** DO NOT FREEZE **

IATA/ICAO

UN1263, PAINT, 3, PG II, ** DO NOT FREEZE **

SECTION 15 — REGULATORY INFORMATION

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No.	CHEMICAL/COMPOUND	% by WT	% Element
100-41-4	Ethylbenzene	0.4	
1330-20-7	Xylene	2	

CALIFORNIA PROPOSITION 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

SECTION 16 — OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.