




SPECIFICATIONS

ISSUE FOR MY MARKETPLACE



240 Continental Drive, Suite 200
Newark, Delaware 19713
Phone: 302.738.7551
Fax: 302.454.5989



HVAC Improvements for
Stokes Elementary School
3874 Upper King Rd.
Dover, DE 19904

Caesar Rodney School District
Contract #: SRS-18-009-Stokesren



200-163183-17001-07



February 6, 2018

NOT FOR BIDDING PURPOSES

**HVAC IMPROVEMENTS
FOR
STOKES ELEMENTARY SCHOOL
CAMDEN, DELAWARE 19934**

PROJECT TEAM

OWNER'S REPRESENTATIVE: State of Delaware
Office of Management and Budget
Division of Facilities Management
Thomas Collins Building, 3rd Floor, Suite 1
540 S. DuPont Highway
Dover, DE 19901

OWNER: Caesar Rodney School District
7 Front Street
PO Box 188
Camden, DE 19934

ARCHITECT: Tetra Tech, Inc.
240 Continental Drive
Suite 200
Newark, DE 19713
Phone: 302-738-7551 Fax: 302-454-5989

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 00 01 10

TABLE OF CONTENTS

- A. Specifications for this project are arranged in accordance with the Construction Specification Institute numbering system and format. Section numbering is discontinuous and all numbers not appearing in the Table of Contents are not used for this Project.
- B. DOCUMENTS BOUND HEREWITH

DIVISION 00 – BIDDING AND CONTRACT REQUIREMENTS

Introductory Information

00 01 01	Project Title Page
00 01 10	Table of Contents
00 01 15	List of Drawings

Procurement Information

00 11 16	Invitation to Bid
00 21 13	Instructions to Bidders
00 41 13	State of DE Bid Form
00 43 13	State of DE Bid Bond

Contracting Information

00 52 13	Standard form of agreement between Owner and Contractor (AIA A101-2007) Sample AIA A101-2007
00 61 13.13	Performance Bond
00 61 13.16	Payment Bond
00 62 76	Miscellaneous AIA Documents Change Order (AIA Document G701-2001) Sample AIA G701-2007 Application and Certificate for Payment (AIA G702-1992) Sample AIA G702-1992 Application for Payment Continuation Sheet (AIA G703-1992) Sample AIA G703-1992 Certificate of Substantial Completion (AIA Document G704-2000) Sample AIA G704-2000 Contractor's Affidavit of Payment of Debts and Claims (AIA Document G706-1994) Sample AIA G706-1994 Contractor's Affidavit of Release of Liens (AIA Document G706A-1994) Sample AIA G706A-1994 Consent of Surety to Final Payment (AIA Document G707-1994) Sample AIA G707-1994 Architect's Supplemental Instructions (AIA Document G710-1992) Sample AIA G710-1992 Construction Change Directive (AIA Document G714-2007)

	Sample AIA G714-2007
	Certificate of Insurance (AIA G715-1991)
	Sample AIA G715-1991
00 72 13	General Conditions of the Construction Contract (AIA A201)
00 73 13	Supplementary Conditions to the Contract
00 73 46	Delaware Prevailing Wage Rates
00 81 13	General Requirements
00 81 14	Drug Testing Forms

DIVISION 01 - GENERAL REQUIREMENTS

01 11 00	Summary
01 23 00	Alternates
01 25 00	Contract Modifications Procedures
01 31 00	Project Management & Coordination
01 31 20	Payroll Reports
01 32 00	Construction Progress
01 33 00	Submittal Procedures
01 33 01	Cadd Release
01 50 00	Temporary Facilities and Controls
01 63 10	Substitutions
01 73 29	Cutting & Patching
01 74 19	Construction Waste Management
01 77 00	Closeout Procedures
01 80 00	Schedule of Special Inspections
01 90 00	Statement of Special Inspections
01 91 13	General Commissioning Requirements
01 91 15	HVAC Commissioning Requirements

DIVISION 02 - EXISTING CONDITIONS

02 41 19	Selective Demolition
----------	----------------------

DIVISION 03 - CONCRETE

03 30 00	Cast-in-Place Concrete
----------	------------------------

DIVISION 05 - METALS


05 12 00	Structural Steel Framing
----------	--------------------------

DIVISION 06 - WOOD, PLASTICS AND COMPOSITES

06 10 53	Miscellaneous Rough Carpentry
----------	-------------------------------

DIVISION 07 - THERMAL AND MOISTURE PROTECTION

07 84 13	Fire Protection, HVAC & Plumbing Penetration Firestopping
----------	---



07 92 00 Joint Sealants

DIVISION 08 – OPENINGS

08 31 13 Access Doors and Frames

DIVISION 09 – FINISHES

09 22 16 Non-Structural Metal Framing
09 29 00 Gypsum Board
09 51 13 Acoustical Panel Ceilings
09 65 13 Resilient Base and Accessories
09 91 23 Interior Painting

DIVISION 11 – EQUIPMENT

11 33 00 Retractable Stairs

DIVISION 21 – FIRE SUPPRESSION

21 05 00 Common Work Results for Fire Protection
21 05 05 Fire Protection Piping, Fittings, and Valves
21 10 03 Water Based Fire Suppression System – Sprinklers and Standpipes

DIVISION 22 – PLUMBING

22 05 00 Common Work Results for Plumbing
22 05 05 Plumbing Piping, Fittings, Valves
22 07 01 Plumbing Insulation
22 40 05 Plumbing Equipment

DIVISION 23 – HEATING, VENTILATING, AND AIR CONDITIONING

23 05 00 Common Work Results for HVAC
23 05 05 HVAC Piping, Fittings, Valves
23 05 48 Vibration Controls for HVAC, Plumbing & Fire Protection Equipment
23 05 93 Testing, Adjusting & Balancing for HVAC & Plumbing
23 06 00 Heating, Ventilating and Air Conditioning Equipment
23 07 01 HVAC Insulation
23 09 00 Instrumentation & Controls of HVAC & Plumbing Systems
23 30 00 HVAC Air Distribution
23 31 20 HVAC Air Distribution System Cleaning
23 81 26 Variable Refrigerant Volume Split Systems with Heat Recovery (Air Cooled Systems)
23 82 22 Packaged Kitchen Hood Ventilation Control System

NOT FOR BIDDING PURPOSES

DIVISION 26 – ELECTRICAL

- 26 05 00 Common Work Results for Electrical
- 26 05 02 Electrical Demolition for Remodeling
- 26 05 19 Low Voltage Electric Power Conductors & Cables
- 26 05 26 Grounding and Bonding for Electrical Systems
- 26 05 28 Electrical Firestopping
- 26 05 29 Hangers & Supports for Electrical Systems
- 26 05 33 Raceways & Boxes for Electrical Systems
- 26 05 53 Identification for Electrical Systems
- 26 24 16 Panelboards
- 26 27 26 Wiring Devices
- 26 28 13 Fuses
- 26 28 16 Enclosed Switches and Circuit Breakers
- 26 29 13 Enclosed Controllers

DIVISION 28 – ELECTRONIC SAFETY AND SECURITY

- 28 31 11 Fire-Alarm System

DIVISION 32 - EXTERIOR IMPROVEMENTS

- 32 31 13 Chain Link Fence and Gates

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 00 01 15

LIST OF DRAWINGS

GENERAL:

G-001 Cover Sheet
PH-121 First Floor Phasing Plan

ARCHITECTURAL:

AD-140 Partial Reflected Ceiling Demolition Plan - Area 'A'
AD-141 Partial Reflected Ceiling Demolition Plan - Area 'B'
A-110 Partial First Floor Plan - Area 'A'
A-120 Partial Mezzanine Floor Plan - Area 'A'
A-121 Partial Mezzanine Floor Plan - Area 'B'
A-130 Roof Plan
A-140 Partial Reflected Ceiling Plan - Area 'A'
A-141 Partial Reflected Ceiling Plan - Area 'B'
A-501 Sections & Details

STRUCTURAL:

S-001 Structural General Notes and Details
S-101 Partial Structural Foundation Plan and Details
S-102 Existing Partial Roof Framing Plan - Area 'A'
S-103 Existing Partial Roof Framing Plan - Area 'B'
S-104 Enlarged Plans and Details
S-501 Structural Existing Truss Profile and Details

MECHANICAL:

M-001 Legend & Abbreviations - HVAC
MD-110 Partial First Floor Demolition Plan - Area 'A' - HVAC
MD-111 Partial First Floor Demolition Plan - Area 'B' - HVAC
MD-120 Partial First Floor Demolition Plan - Area 'A' - HVAC Piping
MD-121 Partial First Floor Demolition Plan - Area 'B' - HVAC Piping
MD-130 Partial Roof Demolition Plan - Area 'A' - HVAC Piping
MD-131 Partial Roof Demolition Plan - Area 'B' - HVAC Piping
MD-210 Demolition Part Plan - HVAC
MD-220 Demolition Part Plan - HVAC
M-110 Partial First Floor Plan - Area 'A' - HVAC
M-111 Partial First Floor Plan - Area 'B' - HVAC
M-120 Partial First Floor Plan - Area 'A' - HVAC Piping
M-121 Partial First Floor Plan - Area 'B' - HVAC Piping
M-130 Partial Roof Plan - Area 'A' - HVAC
M-131 Partial Roof Plan - Area 'B' - HVAC
M-210 Part Plan - HVAC
M-220 Part Plan - HVAC
M-301 Details - HVAC
M-302 Details - HVAC
M-303 Details - HVAC

M-304	Details - HVAC
M-305	Details - HVAC
M-306	Details - HVAC
M-307	Details - HVAC
M-308	Details - HVAC
M-401	Control Diagrams - HVAC
M-402	Control Diagrams - HVAC
M-403	Control Diagrams - HVAC
M-404	Control Diagrams - HVAC
M-405	Control Diagrams - HVAC
M-406	Control Diagrams - HVAC
M-501	Schedules - HVAC
M-502	Schedules - HVAC
M-503	Schedules - HVAC
M-504	Schedules - HVAC

PLUMBING:

P-001	Legend - Plumbing
FPD-110	First Floor Demolition Plan- Fire Protection
FP-110	First Floor Plan - Fire Protection
PD-210	Demolition Part Plan - Plumbing
P-210	Part Plan - Plumbing
P-301	Details - Plumbing
P-302	Details - Plumbing
P-401	Schedules - Plumbing

ELECTRICAL:

E-001	Electrical Legend, Conventions and Abbreviations
ED-110	Partial First Floor Demolition Plan - Area 'A' - Electrical
ED-111	Partial First Floor Demolition Plan - Area 'B' - Electrical
ED-130	Partial Roof Demolition Plan - Area 'A' - Electrical
ED-131	Partial Roof Demolition Plan - Area 'B' - Electrical
E-110	Partial First Floor Plan - Area 'A' - Electrical
E-111	Partial First Floor Plan - Area 'B' - Electrical
E-130	Partial Roof Plan - Area 'A' - Electrical
E-131	Partial Roof Plan - Area 'B' - Electrical
E-301	Schedules and Details
E-401	Schedules

END OF SECTION

INVITATION TO BID

(PLACEHOLDER – TO BE PROVIDED BY DFM)

Sealed bids for OMB/DFM Contract No. _____, will be received by the State of Delaware, Office of Management and Budget, Division of Facilities Management, at the _____ until _____ local time on _____, 20__, at which time they will be publicly opened and read aloud in the Conference Room. Bidder bears the risk of late delivery. Any bids received after the stated time will be returned unopened.

Project involves _____.

Attention is called to construction schedule as detailed in the Bid Documents.

This contract will be awarded on the basis of best value. Attention is called to the Bid Documents which detail the criteria and associated weights which shall be used as the basis of award. (OPTIONAL – Insert Yes No)

A **MANDATORY** Pre-Bid Meeting will be held on _____, 20__, at _____ at the _____ for the purpose of establishing the listing of subcontractors and to answer questions. Representatives of each party to any Joint Venture must attend this meeting. **ATTENDANCE OF THIS MEETING IS A PREREQUISITE FOR BIDDING ON THIS CONTRACT.**

Sealed bids shall be addressed to the Division of Facilities Management _____. The outer envelope should clearly indicate: "OMB/DFM CONTRACT NO. _____ - _____ **SEALED BID - DO NOT OPEN.**"

Contract documents may be obtained at the office of _____ upon receipt of \$ _____ per set/non-refundable. Checks are to be made payable to "_____."

Construction documents will be available for review at the following locations: _____; Delaware Contractors Association; Associated Builders and Contractors.

Bidders will not be subject to discrimination on the basis of race, creed, color, sex, sexual orientation, gender identity or national origin in consideration of this award, and Minority Business Enterprises, Disadvantaged Business Enterprises, Women-Owned Business Enterprises and Veteran-Owned Business Enterprises will be afforded full opportunity to submit bids on this contract. Each bid must be accompanied by a bid security equivalent to ten percent of the bid amount and all additive alternates. The successful bidder must post a performance bond and payment bond in a sum equal to 100 percent of the contract price upon execution of the contract. The Owner reserves the right to reject any or all bids and to waive any informalities therein. The Owner may extend the time and place for the opening of the bids from that described in the advertisement, with not less than two calendar days notice by certified delivery, facsimile machine or other electronic means to those bidders receiving plans.

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

INSTRUCTIONS TO BIDDERS

TABLE OF ARTICLES

1. DEFINITIONS
2. BIDDER'S REPRESENTATION
3. BIDDING DOCUMENTS
4. BIDDING PROCEDURES
5. CONSIDERATION OF BIDS
6. POST-BID INFORMATION
7. PERFORMANCE BOND AND PAYMENT BOND
8. FORM OF AGREEMENT BETWEEN OWNER AND CONTRACTOR

NOT FOR BIDDING PURPOSES

ARTICLE 1: GENERAL

1.1 DEFINITIONS

1.1.1 Whenever the following terms are used, their intent and meaning shall be interpreted as follows:

1.2 STATE: The State of Delaware.

1.3 AGENCY: Contracting State Agency as noted on cover sheet.

1.4 DESIGNATED OFFICIAL: The agent authorized to act for the Agency.

1.5 BIDDING DOCUMENTS: Bidding Documents include the Bidding Requirements and the proposed Contract Documents. The Bidding Requirements consist of the Advertisement for Bid, Invitation to Bid, Instructions to Bidders, Supplementary Instructions to Bidders (if any), General Conditions, Supplementary General Conditions, General Requirements, Special Provisions (if any), the Bid Form (including the Non-collusion Statement), and other sample bidding and contract forms. The proposed Contract Documents consist of the form of Agreement between the Owner and Contractor, as well as the Drawings, Specifications (Project Manual) and all Addenda issued prior to execution of the Contract.

1.6 CONTRACT DOCUMENTS: The Contract Documents consist of the, Instructions to Bidders, Supplementary Instructions to Bidders (if any), General Conditions, Supplementary General Conditions, General Requirements, Special Provisions (if any), the form of agreement between the Owner and the Contractor, Drawings (if any), Specifications (Project Manual), and all addenda.

1.7 AGREEMENT: The form of the Agreement shall be AIA Document A101, Standard Form of Agreement between Owner and Contractor where the basis of payment is a STIPULATED SUM. In the case of conflict between the instructions contained therein and the General Requirements herein, these General Requirements shall prevail.


1.8 GENERAL REQUIREMENTS (or CONDITIONS): General Requirements (or conditions) are instructions pertaining to the Bidding Documents and to contracts in general. They contain, in summary, requirements of laws of the State; policies of the Agency and instructions to bidders.

1.9 SPECIAL PROVISIONS: Special Provisions are specific conditions or requirements peculiar to the bidding documents and to the contract under consideration and are supplemental to the General Requirements. Should the Special Provisions conflict with the General Requirements, the Special Provisions shall prevail.

1.10 ADDENDA: Written or graphic instruments issued by the Owner/Architect prior to the execution of the contract which modify or interpret the Bidding Documents by additions, deletions, clarifications or corrections.

1.11 BIDDER OR VENDOR: A person or entity who formally submits a Bid for the material or Work contemplated, acting directly or through a duly authorized representative who meets the requirements set forth in the Bidding Documents.

1.12 SUB-BIDDER: A person or entity who submits a Bid to a Bidder for materials or labor, or both for a portion of the Work.



STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

- 1.13 BID: A complete and properly executed proposal to do the Work for the sums stipulated therein, submitted in accordance with the Bidding Documents.
- 1.14 BASE BID: The sum stated in the Bid for which the Bidder offers to perform the Work described in the Bidding Documents as the base, to which Work may be added or from which Work may be deleted for sums stated in Alternate Bids (if any are required to be stated in the bid).
- 1.15 ALTERNATE BID (or ALTERNATE): An amount stated in the Bid, where applicable, to be added to or deducted from the amount of the Base Bid if the corresponding change in the Work, as described in the Bidding Documents is accepted.
- 1.16 UNIT PRICE: An amount stated in the Bid, where applicable, as a price per unit of measurement for materials, equipment or services or a portion of the Work as described in the Bidding Documents.
- 1.17 SURETY: The corporate body which is bound with and for the Contract, or which is liable, and which engages to be responsible for the Contractor's payments of all debts pertaining to and for his acceptable performance of the Work for which he has contracted.
- 1.18 BIDDER'S DEPOSIT: The security designated in the Bid to be furnished by the Bidder as a guaranty of good faith to enter into a contract with the Agency if the Work to be performed or the material or equipment to be furnished is awarded to him.
- 1.19 CONTRACT: The written agreement covering the furnishing and delivery of material or work to be performed.
- 1.20 CONTRACTOR: Any individual, firm or corporation with whom a contract is made by the Agency.
- 1.21 SUBCONTRACTOR: An individual, partnership or corporation which has a direct contract with a contractor to furnish labor and materials at the job site, or to perform construction labor and furnish material in connection with such labor at the job site.
- 1.22 CONTRACT BOND: The approved form of security furnished by the contractor and his surety as a guaranty of good faith on the part of the contractor to execute the work in accordance with the terms of the contract.

ARTICLE 2: BIDDER'S REPRESENTATIONS

2.1 PRE-BID MEETING

2.1.1 A pre-bid meeting for this project will be held at the time and place designated. Attendance at this meeting is a pre-requisite for submitting a Bid, unless this requirement is specifically waived elsewhere in the Bid Documents.

2.2 By submitting a Bid, the Bidder represents that:

2.2.1 The Bidder has read and understands the Bidding Documents and that the Bid is made in accordance therewith.

STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

2.2.2 The Bidder has visited the site, become familiar with existing conditions under which the Work is to be performed, and has correlated the Bidder's his personal observations with the requirements of the proposed Contract Documents.

2.2.3 The Bid is based upon the materials, equipment, and systems required by the Bidding Documents without exception.

2.3 JOINT VENTURE REQUIREMENTS

2.3.1 For Public Works Contracts, each Joint Venturer shall be qualified and capable to complete the Work with their own forces.

2.3.2 Included with the Bid submission, and as a requirement to bid, a copy of the executed Joint Venture Agreement shall be submitted and signed by all Joint Venturers involved.

2.3.3 All required Bid Bonds, Performance Bonds, Material and Labor Payment Bonds must be executed by both Joint Venturers and be placed in both of their names.

2.3.4 All required insurance certificates shall name both Joint Venturers.

2.3.5 Both Joint Venturers shall sign the Bid Form and shall submit a copy of a valid Delaware Business License with their Bid.

2.3.6 Both Joint Venturers shall include their Federal E.I. Number with the Bid.

2.3.7 In the event of a mandatory Pre-bid Meeting, each Joint Venturer shall have a representative in attendance.

2.3.8 Due to exceptional circumstances and for good cause shown, one or more of these provisions may be waived at the discretion of the State.

2.4 ASSIGNMENT OF ANTI-TRUST CLAIMS

2.4.1 As consideration for the award and execution by the Owner of this contract, the Contractor hereby grants, conveys, sells, assigns and transfers to the State of Delaware all of its right, title and interests in and to all known or unknown causes of action it presently has or may now or hereafter acquire under the antitrust laws of the United States and the State of Delaware relating to the particular goods or services purchased or acquired by the Owner pursuant to this contract.


ARTICLE 3: BIDDING DOCUMENTS

3.1 COPIES OF BID DOCUMENTS

3.1.1 Bidders may obtain complete sets of the Bidding Documents from the Architectural/Engineering firm designated in the Advertisement or Invitation to Bid in the number and for the deposit sum, if any, stated therein.

3.1.2 Bidders shall use complete sets of Bidding Documents for preparation of Bids. The issuing Agency nor the Architect assumes no responsibility for errors or misinterpretations resulting from the use of incomplete sets of Bidding Documents.

3.1.3 Any errors, inconsistencies or omissions discovered shall be reported to the Architect immediately.



STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

3.1.4 The Agency and Architect may make copies of the Bidding Documents available on the above terms for the purpose of obtaining Bids on the Work. No license or grant of use is conferred by issuance of copies of the Bidding Documents.

3.2 INTERPRETATION OR CORRECTION OF BIDDING DOCUMENTS

3.2.1 The Bidder shall carefully study and compare the Bidding Documents with each other, and with other work being bid concurrently or presently under construction to the extent that it relates to the Work for which the Bid is submitted, shall examine the site and local conditions, and shall report any errors, inconsistencies, or ambiguities discovered to the Architect.

3.2.2 Bidders or Sub-bidders requiring clarification or interpretation of the Bidding Documents shall make a written request to the Architect at least seven days prior to the date for receipt of Bids. Interpretations, corrections and changes to the Bidding Documents will be made by written Addendum. Interpretations, corrections, or changes to the Bidding Documents made in any other manner shall not be binding.

3.2.3 The apparent silence of the specifications as to any detail, or the apparent omission from it of detailed description concerning any point, shall be regarded as meaning that only the best commercial practice is to prevail and only material and workmanship of the first quality are to be used. Proof of specification compliance will be the responsibility of the Bidder.

3.2.4 Unless otherwise provided in the Contract Documents, the Contractor shall provide and pay for all permits, labor, materials, equipment, tools, construction equipment and machinery, water, heat, utilities, transportation, and other facilities and services necessary for the proper execution and completion of the Work.

3.2.5 The Owner will bear the costs for all impact and user fees associated with the project.

3.3 SUBSTITUTIONS

3.3.1 The materials, products and equipment described in the Bidding Documents establish a standard of quality, required function, dimension, and appearance to be met by any proposed substitution. The specification of a particular manufacturer or model number is not intended to be proprietary in any way. Substitutions of products for those named will be considered, providing that the Vendor certifies that the function, quality, and performance characteristics of the material offered is equal or superior to that specified. It shall be the Bidder's responsibility to assure that the proposed substitution will not affect the intent of the design, and to make any installation modifications required to accommodate the substitution.

3.3.2 Requests for substitutions shall be made in writing to the Architect at least ten days prior to the date of the Bid Opening. Such requests shall include a complete description of the proposed substitution, drawings, performance and test data, explanation of required installation modifications due the substitution, and any other information necessary for an evaluation. The burden of proof of the merit of the proposed substitution is upon the proposer. The Architect's decision of approval or disapproval shall be final. The Architect is to notify Owner prior to any approvals.

3.3.3 If the Architect approves a substitution prior to the receipt of Bids, such approval shall be set forth in an Addendum. Approvals made in any other manner shall not be binding.

3.3.4 The Architect shall have no obligation to consider any substitutions after the Contract award.

3.4 ADDENDA

3.4.1 Addenda will be mailed or delivered to all who are known by the Architect to have received a complete set of the Bidding Documents.

3.4.2 Copies of Addenda will be made available for inspection wherever Bidding Documents are on file for that purpose.

3.4.3 No Addenda will be issued later than 4 days prior to the date for receipt of Bids except an Addendum withdrawing the request for Bids or one which extends the time or changes the location for the opening of bids.

3.4.4 Each bidder shall ascertain prior to submitting his Bid that they have received all Addenda issued, and shall acknowledge their receipt in their Bid in the appropriate space. Not acknowledging an issued Addenda could be grounds for determining a bid to be non-responsive.

ARTICLE 4: BIDDING PROCEDURES

4.1 PREPARATION OF BIDS

4.1.1 Submit the bids on the Bid Forms included with the Bidding Documents.

4.1.2 Submit the original Bid Form for each bid. Bid Forms may be removed from the project manual for this purpose.

4.1.3 Execute all blanks on the Bid Form in a non-erasable medium (typewriter or manually in ink).

4.1.4 Where so indicated by the makeup on the Bid Form, express sums in both words and figures, in case of a discrepancy between the two, the written amount shall govern.


4.1.5 Interlineations, alterations or erasures must be initialed by the signer of the Bid.

4.1.6 BID ALL REQUESTED ALTERNATES AND UNIT PRICES, IF ANY. If there is no change in the Base Bid for an Alternate, enter "No Change". The Contractor is responsible for verifying that they have received all addenda issued during the bidding period. Work required by Addenda shall automatically become part of the Contract.

4.1.7 Make no additional stipulations on the Bid Form and do not qualify the Bid in any other manner.

4.1.8 Each copy of the Bid shall include the legal name of the Bidder and a statement whether the Bidder is a sole proprietor, a partnership, a corporation, or any legal entity, and each copy shall be signed by the person or persons legally authorized to bind the Bidder to a contract. A Bid by a corporation shall further give the state of incorporation and have the corporate seal affixed. A Bid submitted by an agent shall have a current Power of Attorney attached, certifying agent's authority to bind the Bidder.

4.1.9 Bidder shall complete the Non-Collusion Statement form included with the Bid Forms and include it with their Bid.



STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

4.1.10 In the construction of all Public Works projects for the State of Delaware or any agency thereof, preference in employment of laborers, workers or mechanics shall be given to bona fide legal citizens of the State who have established citizenship by residence of at least 90 days in the State.

4.1.11 Each bidder shall include in their bid a copy of a valid Delaware Business License.

4.1.12 Each bidder shall include signed Affidavit(s) for the Bidder and each listed Subcontractor certifying compliance with OMB Regulation 4104- "Regulations for the Drug Testing of Contractor and Subcontractor Employees Working on "Large Public Works Projects." "Large Public Works" is based upon the current threshold required for bidding Public Works as set by the Purchasing and Contracting Advisory Council.

4.2 BID SECURITY

4.2.1 All bids shall be accompanied by a deposit of either a good and sufficient bond to the agency for the benefit of the agency, with corporate surety authorized to do business in this State, the form of the bond and the surety to be approved by the agency, or a security of the bidder assigned to the agency, for a sum equal to at least 10% of the bid plus all add alternates, or in lieu of the bid bond a security deposit in the form of a certified check, bank treasurer's check, cashier's check, money order, or other prior approved secured deposit assigned to the State. The bid bond need not be for a specific sum, but may be stated to be for a sum equal to 10% of the bid plus all add alternates to which it relates and not to exceed a certain stated sum, if said sum is equal to at least 10% of the bid. The Bid Bond form used shall be the standard OMB form (attached).

4.2.2 The Agency has the right to retain the Bid security of Bidders to whom an award is being considered until either a formal contract has been executed and bonds have been furnished or the specified time has elapsed so the Bids may be withdrawn or all Bids have been rejected.

4.2.3 In the event of any successful Bidder refusing or neglecting to execute a formal contract and bond within 20 days of the awarding of the contract, the bid bond or security deposited by the successful bidder shall be forfeited.

4.3 SUBCONTRACTOR LIST


4.3.1 As required by Delaware Code, Title 29, section 6962(d)(10)b, each Bidder shall submit with their Bid a completed List of Sub-Contractors included with the Bid Form. NAME ONLY ONE SUBCONTRACTOR FOR EACH TRADE. A Bid will be considered non-responsive unless the completed list is included.

4.3.2 Provide the Name and Address for each listed subcontractor. Addresses by City, Town or Locality, plus State, will be acceptable.

4.3.3 It is the responsibility of the Contractor to ensure that their Subcontractors are in compliance with the provisions of this law. Also, if a Contractor elects to list themselves as a Subcontractor for any category, they must specifically name themselves on the Bid Form and be able to document their capability to act as Subcontractor in that category in accordance with this law.

4.4 EQUALITY OF EMPLOYMENT OPPORTUNITY ON PUBLIC WORKS

4.4.1 During the performance of this contract, the contractor agrees as follows:



- A. The Contractor will not discriminate against any employee or applicant for employment because of race, creed, sex, color, sexual orientation, gender identity or national origin. The Contractor will take affirmative action to ensure the applicants are employed, and that employees are treated during employment, without regard to their race, creed, sex, color, sexual orientation, gender identity or national origin. Such action shall include, but not be limited to, the following: Employment, upgrading, demotion or transfer; recruitment or recruitment advertising; layoff or termination; rates of pay or other forms of compensation; and selection for training, including apprenticeship. The Contractor agrees to post in conspicuous places available to employees and applicants for employment notices to be provided by the contracting agency setting forth this nondiscrimination clause.
- B. The Contractor will, in all solicitations or advertisements for employees placed by or on behalf of the Contractor, state that all qualified applicants will receive consideration for employment without regard to race, creed, sex, color, sexual orientation, gender identity or national origin."

4.5 PREVAILING WAGE REQUIREMENT

4.5.1 Wage Provisions: For renovation and new construction projects whose costs exceed the thresholds contained in Delaware Code, Title 29, Section 6960, the minimum wage rates for various classes of laborers and mechanics shall be as determined by the Department of Labor, Division of Industrial Affairs of the State of Delaware.

4.5.2 The employer shall pay all mechanics and labors employed directly upon the site of work, unconditionally and not less often than once a week and without subsequent deduction or rebate on any account, the full amounts accrued at time of payment, computed at wage rates not less than those stated in the specifications, regardless of any contractual relationship which may be alleged to exist between the employer and such laborers and mechanics.

4.5.3 The scale of the wages to be paid shall be posted by the employer in a prominent and easily accessible place at the site of the work.

4.5.4 Every contract based upon these specifications shall contain a stipulation that sworn payroll information as required by the Department of Labor, be furnished weekly. The Department of Labor shall keep and maintain the sworn payroll information for a period of 6 months from the last day of the work week covered by the payroll.

4.6 SUBMISSION OF BIDS

4.6.1 Enclose the Bid, the Bid Security, and any other documents required to be submitted with the Bid in a sealed opaque envelope. Address the envelope to the party receiving the Bids. Identify with the project name, project number, and the Bidder's name and address. If the Bid is sent by mail, enclose the sealed envelope in a separate mailing envelope with the notation "BID ENCLOSED" on the face thereof. The State is not responsible for the opening of bids prior to bid opening date and time that are not properly marked.

4.6.2 Deposit Bids at the designated location prior to the time and date for receipt of bids indicated in the Advertisement for Bids. Bids received after the time and date for receipt of bids will be marked "LATE BID" and returned.

STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

- 4.6.3 Bidder assumes full responsibility for timely delivery at location designated for receipt of bids.
- 4.6.4 Oral, telephonic or telegraphic bids are invalid and will not receive consideration.
- 4.6.5 Withdrawn Bids may be resubmitted up to the date and time designated for the receipt of Bids, provided that they are then fully in compliance with these Instructions to Bidders.
- 4.7 **MODIFICATION OR WITHDRAW OF BIDS**
- 4.7.1 Prior to the closing date for receipt of Bids, a Bidder may withdraw a Bid by personal request and by showing proper identification to the Architect. A request for withdraw by letter or fax, if the Architect is notified in writing prior to receipt of fax, is acceptable. A fax directing a modification in the bid price will render the Bid informal, causing it to be ineligible for consideration of award. Telephone directives for modification of the bid price shall not be permitted and will have no bearing on the submitted proposal in any manner.
- 4.7.2 Bidders submitting Bids that are late shall be notified as soon as practicable and the bid shall be returned.
- 4.7.3 A Bid may not be modified, withdrawn or canceled by the Bidder during a thirty (30) day period following the time and date designated for the receipt and opening of Bids, and Bidder so agrees in submitting their Bid. Bids shall be binding for 30 days after the date of the Bid opening.

ARTICLE 5: CONSIDERATION OF BIDS

5.1 OPENING/REJECTION OF BIDS

- 5.1.1 Unless otherwise stated, Bids received on time will be publicly opened and will be read aloud. An abstract of the Bids will be made available to Bidders.
- 5.1.2 The Agency shall have the right to reject any and all Bids. A Bid not accompanied by a required Bid Security or by other data required by the Bidding Documents, or a Bid which is in any way incomplete or irregular is subject to rejection.
- 5.1.3 If the Bids are rejected, it will be done within thirty (30) calendar day of the Bid opening.

5.2 COMPARISON OF BIDS

- 5.2.1 After the Bids have been opened and read, the bid prices will be compared and the result of such comparisons will be made available to the public. Comparisons of the Bids may be based on the Base Bid plus desired Alternates. The Agency shall have the right to accept Alternates in any order or combination.
- 5.2.2 The Agency reserves the right to waive technicalities, to reject any or all Bids, or any portion thereof, to advertise for new Bids, to proceed to do the Work otherwise, or to abandon the Work, if in the judgment of the Agency or its agent(s), it is in the best interest of the State.
- 5.2.3 An increase or decrease in the quantity for any item is not sufficient grounds for an increase or decrease in the Unit Price.
- 5.2.4 The prices quoted are to be those for which the material will be furnished F.O.B. Job Site and include all charges that may be imposed during the period of the Contract.

5.2.5 No qualifying letter or statements in or attached to the Bid, or separate discounts will be considered in determining the low Bid except as may be otherwise herein noted. Cash or separate discounts should be computed and incorporated into Unit Bid Price(s).

5.3 DISQUALIFICATION OF BIDDERS

5.3.1 An agency shall determine that each Bidder on any Public Works Contract is responsible before awarding the Contract. Factors to be considered in determining the responsibility of a Bidder include:

- A. The Bidder's financial, physical, personnel or other resources including Subcontracts;
- B. The Bidder's record of performance on past public or private construction projects, including, but not limited to, defaults and/or final adjudication or admission of violations of the Prevailing Wage Laws in Delaware or any other state;
- C. The Bidder's written safety plan;
- D. Whether the Bidder is qualified legally to contract with the State;
- E. Whether the Bidder supplied all necessary information concerning its responsibility; and,
- F. Any other specific criteria for a particular procurement, which an agency may establish; provided however, that, the criteria be set forth in the Invitation to Bid and is otherwise in conformity with State and/or Federal law.

5.3.2 If an agency determines that a Bidder is nonresponsive and/or nonresponsible, the determination shall be in writing and set forth the basis for the determination. A copy of the determination shall be sent to the affected Bidder within five (5) working days of said determination.

5.3.3 In addition, any one or more of the following causes may be considered as sufficient for the disqualification of a Bidder and the rejection of their Bid or Bids.

5.3.3.1 More than one Bid for the same Contract from an individual, firm or corporation under the same or different names.


5.3.3.2 Evidence of collusion among Bidders.

5.3.3.3 Unsatisfactory performance record as evidenced by past experience.

5.3.3.4 If the Unit Prices are obviously unbalanced either in excess or below reasonable cost analysis values.

5.3.3.5 If there are any unauthorized additions, interlineation, conditional or alternate bids or irregularities of any kind which may tend to make the Bid incomplete, indefinite or ambiguous as to its meaning.

5.3.3.6 If the Bid is not accompanied by the required Bid Security and other data required by the Bidding Documents.



- 5.3.3.7 If any exceptions or qualifications of the Bid are noted on the Bid Form.
- 5.4 ACCEPTANCE OF BID AND AWARD OF CONTRACT
- 5.4.1 A formal Contract shall be executed with the successful Bidder within twenty (20) calendar days after the award of the Contract.
- 5.4.2 Per Section 6962(d)(13) a., Title 29, Delaware Code, "The contracting agency shall award any public works contract within thirty (30) days of the bid opening to the lowest responsive and responsible Bidder, unless the Agency elects to award on the basis of best value, in which case the election to award on the basis of best value shall be stated in the Invitation To Bid."
- 5.4.3 Each Bid on any Public Works Contract must be deemed responsive by the Agency to be considered for award. A responsive Bid shall conform in all material respects to the requirements and criteria set forth in the Contract Documents and specifications.
- 5.4.4 The Agency shall have the right to accept Alternates in any order or combination, and to determine the low Bidder on the basis of the sum of the Base Bid, plus accepted Alternates.
- 5.4.5 The successful Bidder shall execute a formal contract, submit the required Insurance Certificate, and furnish good and sufficient bonds, unless specifically waived in the General Requirements, in accordance with the General Requirement, within twenty (20) days of official notice of contract award. The successful Bidder shall provide two business days prior to contract execution, copies of the Employee Drug Testing Program for the Bidder and all listed Subcontractors. Bonds shall be for the benefit of the Agency with surety in the amount of 100% of the total contract award. Said Bonds shall be conditioned upon the faithful performance of the contract. Bonds shall remain in affect for period of one year after the date of substantial completion.
- 5.4.6 If the successful Bidder fails to execute the required Contract, Bond and all required information, as aforesaid, within twenty (20) calendar days after the date of official Notice of the Award of the Contract, their Bid guaranty shall immediately be taken and become the property of the State for the benefit of the Agency as liquidated damages, and not as a forfeiture or as a penalty. Award will then be made to the next lowest qualified Bidder of the Work as advertised, as the Agency may decide.
- 5.4.7 Each bidder shall supply with its bid its taxpayer identification number (i.e., federal employer identification number or social security number) and a copy of its Delaware business license, and should the vendor be awarded a contract, such vendor shall provide to the agency the taxpayer identification license numbers of such subcontractors. Such numbers shall be provided on the later of the date on which such subcontractor is required to be identified or the time the contract is executed. The successful Bidder shall provide to the agency to which it is contracting, within 30 days of entering into such public works contract, copies of all Delaware Business licenses of subcontractors and/or independent contractors that will perform work for such public works contract. However, if a subcontractor or independent contractor is hired or contracted more than 20 days after the Bidder entered the public works contract the Delaware Business license of such subcontractor or independent contractor shall be provided to the agency within 10 days of being contracted or hired.
- 5.4.8 The Bid Security shall be returned to the successful Bidder upon the execution of the formal contract. The Bid Securities of unsuccessful bidders shall be returned within thirty (30) calendar days after the opening of the Bids.

ARTICLE 6: POST-BID INFORMATION

6.1 CONTRACTOR'S QUALIFICATION STATEMENT

6.1.1 Bidders to whom award of a Contract is under consideration shall, if requested by the Agency, submit a properly executed AIA Document A305, Contractor's Qualification Statement, unless such a statement has been previously required and submitted.

6.2 BUSINESS DESIGNATION FORM

6.2.1 Successful bidder shall be required to accurately complete an Office of Management and Budget Business Designation Form for Subcontractors.

ARTICLE 7: PERFORMANCE BOND AND PAYMENT BOND

7.1 BOND REQUIREMENTS

7.1.1 The cost of furnishing the required Bonds, that are stipulated in the Bidding Documents, shall be included in the Bid.

7.1.2 If the Bidder is required by the Agency to secure a bond from other than the Bidder's usual sources, changes in cost will be adjusted as provide in the Contract Documents.

7.1.3 The Performance and Payment Bond forms used shall be the standard OMB forms (attached).

7.2 TIME OF DELIVERY AND FORM OF BONDS

7.2.1 The bonds shall be dated on or after the date of the Contract.

7.2.2 The Bidder shall require the attorney-in-fact who executes the required bonds on behalf of the surety to affix a certified and current copy of the power of attorney.

ARTICLE 8: FORM OF AGREEMENT BETWEEN AGENCY AND CONTRACTOR

8.1 Unless otherwise required in the Bidding Documents, the Agreement for the Work will be written on AIA Document A101, Standard Form of Agreement Between Owner and Contractor Where the Basis of Payment is a Stipulated Sum.

END OF SECTION

NOT FOR BIDDING PURPOSES

HVAC IMPROVEMENTS
STOKES ELEMENTARY SCHOOL
DOVER, DELAWARE

BID FORM

For Bids Due: _____ (DATE) _____

To: Caesar Rodney School District
7 Front Street, PO Box 188
Wyoming, DE 19934

Name of Bidder: _____

Delaware Business License No.: _____ **Taxpayer ID No.:** _____
(A copy of Bidder's Delaware Business License must be attached to this form.)

(Other License Nos.): _____

Phone No.: () _____ - _____ **Fax No.:** () _____ - _____

The undersigned, representing that he has read and understands the Bidding Documents and that this bid is made in accordance therewith, that he has visited the site and has familiarized himself with the local conditions under which the Work is to be performed, and that his bid is based upon the materials, systems and equipment described in the Bidding Documents without exception, hereby proposes and agrees to provide all labor, materials, plant, equipment, supplies, transport and other facilities required to execute the work described by the aforesaid documents for the lump sum itemized below:


\$ _____
(\$ _____)

ALTERNATES

Alternate prices conform to applicable project specification section. Refer to specifications for a complete description of the following Alternates. A "ADD" or "DEDUCT" amount is indicated by the crossed out part that does not apply.

ALTERNATE No. 1: Phasing and Construction Schedule. Work included in documentation to be performed in its entirety in Summer, 2018.

Add/Deduct: \$ _____
(\$ _____)



HVAC IMPROVEMENTS
STOKES ELEMENTARY SCHOOL
DOVER, DELAWARE

BID FORM

I/We acknowledge Addendums numbered _____ and the price(s) submitted include any cost/schedule impact they may have.

This bid shall remain valid and cannot be withdrawn for thirty (30) days from the date of opening of bids (60 days for School Districts and Department of Education), and the undersigned shall abide by the Bid Security forfeiture provisions. Bid Security is attached to this Bid.

The Owner shall have the right to reject any or all bids, and to waive any informality or irregularity in any bid received.

This bid is based upon work being accomplished by the Sub-Contractors named on the list attached to this bid.

Should I/We be awarded this contract, I/We pledge to achieve substantial completion of all the work within _____ calendar days of the Notice to Proceed.

The undersigned represents and warrants that he has complied and shall comply with all requirements of local, state, and national laws; that no legal requirement has been or shall be violated in making or accepting this bid, in awarding the contract to him or in the prosecution of the work required; that the bid is legal and firm; that he has not, directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken action in restraint of free competitive bidding.

Upon receipt of written notice of the acceptance of this Bid, the Bidder shall, within twenty (20) calendar days, execute the agreement in the required form and deliver the Contract Bonds, and Insurance Certificates, required by the Contract Documents.

I am / We are an Individual / a Partnership / a Corporation.

By _____ Trading as _____
(Individual's / General Partner's / Corporate Name)

(State of Corporation)

Business Address: _____


Witness: _____ By: _____
(SEAL) (Authorized Signature)

(Title)

Date: _____

ATTACHMENTS

- Sub-Contractor List
- Non-Collusion Statement
- Affidavit(s) of Employee Drug Testing Program
- Bid Security
- (Others as Required by Project Manuals)



HVAC IMPROVEMENTS
STOKES ELEMENTARY SCHOOL
DOVER, DELAWARE

BID FORM

SUBCONTRACTOR LIST

In accordance with Title 29, Chapter 6962 (d)(10)b Delaware Code, the following sub-contractor listing must accompany the bid submittal. The name and address of the sub-contractor **must be listed for each category** where the bidder intends to use a sub-contractor to perform that category of work. In order to provide full disclosure and acceptance of the bid by the *Owner*, it is **required that bidders list themselves as being the sub-contractor for all categories where he/she is qualified and intends to perform such work**. This form must be filled out completely with no additions or deletions. Note that all subcontractors listed below must have a signed Affidavit of Employee Drug Testing Program included with this bid.

<u>Subcontractor Category</u>	<u>Subcontractor</u>	<u>Address (City & State)</u>	<u>Subcontractors tax payer ID #</u>
1. Concrete	_____	_____	_____
2. Carpentry	_____	_____	_____
3. Insulation	_____	_____	_____
4. Electrical	_____	_____	_____
5. Fire Alarm	_____	_____	_____
6. Fire Protection	_____	_____	_____
7. HVAC	_____	_____	_____
8. Painting	_____	_____	_____
9. Plumbing	_____	_____	_____
10. Metals Fabrication	_____	_____	_____
11. Fencing	_____	_____	_____

NOT FOR BIDDING PURPOSES

HVAC IMPROVEMENTS
STOKES ELEMENTARY SCHOOL
DOVER, DELAWARE

BID FORM
NON-COLLUSION STATEMENT

This is to certify that the undersigned bidder has neither directly nor indirectly, entered into any agreement, participated in any collusion or otherwise taken any action in restraint of free competitive bidding in connection with this proposal submitted this date (to the Office of Management and Budget, Division of Facilities Management).

All the terms and conditions of (Project or Contract Number) have been thoroughly examined and are understood.

NAME OF BIDDER: _____

AUTHORIZED REPRESENTATIVE (TYPED): _____

AUTHORIZED REPRESENTATIVE (SIGNATURE): _____

TITLE: _____

ADDRESS OF BIDDER: _____

E-MAIL: _____

PHONE NUMBER: _____

Sworn to and Subscribed before me this _____ day of _____ 20____.

My Commission expires _____ NOTARY PUBLIC _____.

NOT FOR BIDDING PURPOSES

THIS PAGE MUST BE SIGNED AND NOTARIZED FOR YOUR BID TO BE CONSIDERED.

**AFFIDAVIT
OF
EMPLOYEE DRUG TESTING PROGRAM**

4104 Regulations for the Drug Testing of Contractor and Subcontractor Employees Working on Large Public Works Projects requires that Contractors and Subcontractors implement a program of mandatory drug testing for Employees who work on Large Public Works Contracts funded all or in part with public funds.

We hereby certify that we have in place or will implement during the entire term of the contract a Mandatory Drug Testing Program for our employees on the jobsite that complies with this regulation:

Contractor/Subcontractor Name: _____

Contractor/Subcontractor Address: _____

Authorized Representative (typed or printed): _____

Authorized Representative (signature): _____

Title: _____

Sworn to and Subscribed before me this _____ day of _____ 20____.

My Commission expires _____ NOTARY PUBLIC _____.

THIS PAGE MUST BE SIGNED AND NOTARIZED FOR YOUR BID TO BE CONSIDERED.

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

BID BOND

TO ACCOMPANY PROPOSAL
(Not necessary if security is used)

KNOW ALL MEN BY THESE PRESENTS That: _____ of _____ in the County of _____ and State of _____ as **Principal**, and of _____ in the County of _____ and State of _____ as **Surety**, legally authorized to do business in the State of Delaware ("State"), are held and firmly unto the **State** in the sum of _____ Dollars (\$ _____), or 10% percent not to exceed _____ Dollars (\$ _____) of amount of bid on Contract No. _____, to be paid to the **State** for the use and benefit of _____ State of Delaware Office of Management and Budget for which payment well and truly to be made, we do bind ourselves, our and each of our heirs, executors, administrators, and successors, jointly and severally for and in the whole firmly by these presents.

NOW THE CONDITION OF THIS OBLIGATION IS SUCH that if the above bounden **Principal** who has submitted to the _____ State of Delaware Office of Management and Budget a certain proposal to enter into this contract for the furnishing of certain material and/or services within the **State**, shall be awarded this Contract, and if said **Principal** shall well and truly enter into and execute this Contract as may be required by the terms of this Contract and approved by the _____ State of Delaware Office of Management and Budget this Contract to be entered into within twenty days after the date of official notice of the award thereof in accordance with the terms of said proposal, then this obligation shall be void or else to be and remain in full force and virtue.

Sealed with _____ seal and dated this _____ day of _____ in the year of our Lord two thousand and _____ (20__).

SEALED, AND DELIVERED IN THE
Presence of

Name of Bidder (Organization)

Corporate Seal

By: _____

Authorized Signature

Attest: _____


Title

Name of Surety

Witness: _____

By: _____

Title



PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 00 52 13

STANDARD FORM OF AGREEMENT BETWEEN OWNER AND CONTRACTOR

The Standard Form of Agreement Between Owner and Contractor is as stated in the American Institute of Architects Document AIA A101 (2007 Edition) entitled Standard Form of Agreement Between Owner and Contractor and is part of this project manual as if herein written in full.

Copies of the Document are available through the A/E.

A draft copy of this document is included herein as follows.

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

 **AIA** Document A101™ – 2007

Standard Form of Agreement Between Owner and Contractor where the basis of payment is a Stipulated Sum

AGREEMENT made as of the day of in the year
(In words, indicate day, month and year.)

BETWEEN the Owner:
(Name, legal status, address and other information)

and the Contractor:
(Name, legal status, address and other information)

for the following Project:
(Name, location and detailed description)

test

The Architect:
(Name, legal status, address and other information)

The Owner and Contractor agree as follows.

ADDITIONS AND DELETIONS:
The author of this document has added information needed for its completion. The author may also have revised the text of the original AIA standard form. An *Additions and Deletions Report* that notes added information as well as revisions to the standard form text is available from the author and should be reviewed. A vertical line in the left margin of this document indicates where the author has added necessary information and where the author has added to or deleted from the original AIA text.

This document has important legal consequences. Consultation with an attorney is encouraged with respect to its completion or modification.

AIA Document A201™–2007, General Conditions of the Contract for Construction, is adopted in this document by reference. Do not use with other general conditions unless this document is modified.

NOT FOR BIDDING PURPOSES

Init.

TABLE OF ARTICLES

- 1 THE CONTRACT DOCUMENTS
- 2 THE WORK OF THIS CONTRACT
- 3 DATE OF COMMENCEMENT AND SUBSTANTIAL COMPLETION
- 4 CONTRACT SUM
- 5 PAYMENTS
- 6 DISPUTE RESOLUTION
- 7 TERMINATION OR SUSPENSION
- 8 MISCELLANEOUS PROVISIONS
- 9 ENUMERATION OF CONTRACT DOCUMENTS
- 10 INSURANCE AND BONDS

ARTICLE 1 THE CONTRACT DOCUMENTS

The Contract Documents consist of this Agreement, Conditions of the Contract (General, Supplementary and other Conditions), Drawings, Specifications, Addenda issued prior to execution of this Agreement, other documents listed in this Agreement and Modifications issued after execution of this Agreement, all of which form the Contract, and are as fully a part of the Contract as if attached to this Agreement or repeated herein. The Contract represents the entire and integrated agreement between the parties hereto and supersedes prior negotiations, representations or agreements, either written or oral. An enumeration of the Contract Documents, other than a Modification, appears in Article 9.

ARTICLE 2 THE WORK OF THIS CONTRACT

The Contractor shall fully execute the Work described in the Contract Documents, except as specifically indicated in the Contract Documents to be the responsibility of others.

ARTICLE 3 DATE OF COMMENCEMENT AND SUBSTANTIAL COMPLETION

§ 3.1 The date of commencement of the Work shall be the date of this Agreement unless a different date is stated below or provision is made for the date to be fixed in a notice to proceed issued by the Owner.

(Insert the date of commencement if it differs from the date of this Agreement or, if applicable, state that the date will be fixed in a notice to proceed.)

If, prior to the commencement of the Work, the Owner requires time to file mortgages and other security interests, the Owner's time requirement shall be as follows:

§ 3.2 The Contract Time shall be measured from the date of commencement.

§ 3.3 The Contractor shall achieve Substantial Completion of the entire Work not later than () days from the date of commencement, or as follows:

(Insert number of calendar days. Alternatively, a calendar date may be used when coordinated with the date of commencement. If appropriate, insert requirements for earlier Substantial Completion of certain portions of the Work.)

Init.

Portion of Work

Substantial Completion Date

, subject to adjustments of this Contract Time as provided in the Contract Documents.
(Insert provisions, if any, for liquidated damages relating to failure to achieve Substantial Completion on time or for bonus payments for early completion of the Work.)

ARTICLE 4 CONTRACT SUM

§ 4.1 The Owner shall pay the Contractor the Contract Sum in current funds for the Contractor's performance of the Contract. The Contract Sum shall be (\$), subject to additions and deductions as provided in the Contract Documents.

§ 4.2 The Contract Sum is based upon the following alternates, if any, which are described in the Contract Documents and are hereby accepted by the Owner:
(State the numbers or other identification of accepted alternates. If the bidding or proposal documents permit the Owner to accept other alternates subsequent to the execution of this Agreement, attach a schedule of such other alternates showing the amount for each and the date when that amount expires.)

§ 4.3 Unit prices, if any:
(Identify and state the unit price; state quantity limitations, if any, to which the unit price will be applicable.)

Item	Units and Limitations	Price Per Unit (\$0.00)
------	-----------------------	-------------------------

§ 4.4 Allowances included in the Contract Sum, if any:
(Identify allowance and state exclusions, if any, from the allowance price.)

Item	Price
------	-------

ARTICLE 5 PAYMENTS

§ 5.1 PROGRESS PAYMENTS

§ 5.1.1 Based upon Application for Payment submitted to the Architect by the Contractor and Certificates for Payment issued by the Architect, the Owner shall make progress payments on account of the Contract Sum to the Contractor as provided below and elsewhere in the Contract Documents.

§ 5.1.2 The period covered by each Application for Payment shall be one calendar month ending on the last day of the month, or as follows:

§ 5.1.3 Provided that a valid Application for Payment is received by the Architect that meets all requirements of the contract, payment shall be made by the Owner not later than
(Paragraphs deleted)

30 days after the Owner receives the valid Application for Payment.

§ 5.1.4 Each Application for Payment shall be based on the most recent schedule of values submitted by the Contractor in accordance with the Contract Documents. The schedule of values shall allocate the entire Contract Sum among the various portions of the Work. The schedule of values shall be prepared in such form and supported by such data to substantiate its accuracy as the Architect may require. This schedule, unless objected to by the Architect, shall be used as a basis for reviewing the Contractor's Applications for Payment.

§ 5.1.5 Applications for Payment shall show the percentage of completion of each portion of the Work as of the end of the period covered by the Application for Payment.

§ 5.1.6 Subject to other provisions of the Contract Documents, the amount of each progress payment shall be computed as follows:

- .1 Take that portion of the Contract Sum properly allocable to completed Work as determined by multiplying the percentage completion of each portion of the Work by the share of the Contract Sum allocated to that portion of the Work in the schedule of values, less retainage of percent (%). Pending final determination of cost to the Owner of changes in the Work, amounts not in dispute shall be included as provided in Section 7.3.9 of AIA Document A201™–2007, General Conditions of the Contract for Construction;
- .2 Add that portion of the Contract Sum properly allocable to materials and equipment delivered and suitably stored at the site for subsequent incorporation in the completed construction (or if approved in advance by the Owner, suitably stored off the site at a location agreed upon in writing), less retainage of percent (%);
- .3 Subtract the aggregate of previous payments made by the Owner; and
- .4 Subtract amounts, if any, for which the Architect has withheld or nullified a Certificate for Payment as provided in Section 9.5 of AIA Document A201–2007.

§ 5.1.7 The progress payment amount determined in accordance with Section 5.1.6 shall be further modified under the following circumstances:

- .1 Add, upon Substantial Completion of the Work, a sum sufficient to increase the total payments to the full amount of the Contract Sum, less such amounts as the Architect shall determine for incomplete Work, retainage applicable to such work and unsettled claims, and *(Section 9.8.5 of AIA Document A201–2007 requires release of applicable retainage upon Substantial Completion of Work with consent of surety, if any.)*
- .2 Add, if final completion of the Work is thereafter materially delayed through no fault of the Contractor, any additional amounts payable in accordance with Section 9.10.3 of AIA Document A201–2007.

§ 5.1.8 Reduction or limitation of retainage, if any, shall be as follows:

(If it is intended, prior to Substantial Completion of the entire Work, to reduce or limit the retainage resulting from the percentages inserted in Sections 5.1.6.1 and 5.1.6.2 above, and this is not explained elsewhere in the Contract Documents, insert here provisions for such reduction or limitation.)

§ 5.1.9 Except with the Owner's prior approval, the Contractor shall not make advance payments to suppliers for materials or equipment which have not been delivered and stored at the site.

§ 5.2 FINAL PAYMENT

§ 5.2.1 Final payment, constituting the entire unpaid balance of the Contract Sum, shall be made by the Owner to the Contractor when:

- .1 the Contractor has fully performed the Contract except for the Contractor's responsibility to correct Work as provided in Section 12.2.2 of AIA Document A201–2007, and to satisfy other requirements, if any, which extend beyond final payment; and
- .2 a final Certificate for Payment has been issued by the Architect.

§ 5.2.2 The Owner's final payment to the Contractor shall be made no later than 30 days after the issuance of the Architect's final Certificate for Payment, or as follows:

ARTICLE 6 DISPUTE RESOLUTION

§ 6.1 INITIAL DECISION MAKER

The Architect will serve as Initial Decision Maker pursuant to Section 15.2 of AIA Document A201–2007, unless the parties appoint below another individual, not a party to this Agreement, to serve as Initial Decision Maker.

Init.

(If the parties mutually agree, insert the name, address and other contact information of the Initial Decision Maker, if other than the Architect.)

§ 6.2 BINDING DISPUTE RESOLUTION

For any Claim subject to, but not resolved by, mediation pursuant to Section 15.3 of AIA Document A201-2007, the method of binding dispute resolution shall be as follows:

(Check the appropriate box. If the Owner and Contractor do not select a method of binding dispute resolution here, or do not subsequently agree in writing to a binding dispute resolution method other than litigation, Claims will be resolved by litigation in a court of competent jurisdiction.)

Arbitration pursuant to Section 15.4 of AIA Document A201-2007

Litigation in a court of competent jurisdiction

Other (Specify)

Any remedies available in law or in equity.

ARTICLE 7 TERMINATION OR SUSPENSION

§ 7.1 The Contract may be terminated by the Owner or the Contractor as provided in Article 14 of AIA Document A201-2007.

§ 7.2 The Work may be suspended by the Owner as provided in Article 14 of AIA Document A201-2007.

ARTICLE 8 MISCELLANEOUS PROVISIONS

§ 8.1 Where reference is made in this Agreement to a provision of AIA Document A201-2007 or another Contract Document, the reference refers to that provision as amended or supplemented by other provisions of the Contract Documents.

§ 8.2 Payments due and unpaid under the Contract shall bear interest from the date payment is due at the rate stated below, or in the absence thereof, at the legal rate prevailing from time to time at the place where the Project is located. (Insert rate of interest agreed upon, if any.)

Payments are due 30 days after receipt of a valid Application for Payment. After that 30 day period, interest may be charged at the rate of 1% per month not to exceed 12% per annum

§ 8.3 The Owner's representative:
(Name, address and other information)

§ 8.4 The Contractor's representative:
(Name, address and other information)

§ 8.5 The Contractor's representative shall not be changed without ten days written notice to the Owner..

§ 8.6 Other provisions:

ARTICLE 9 ENUMERATION OF CONTRACT DOCUMENTS

§ 9.1 The Contract Documents, except for Modifications issued after execution of this Agreement, are enumerated in the sections below.

§ 9.1.1 The Agreement is this executed AIA Document A101-2007, Standard Form of Agreement Between Owner and Contractor.

§ 9.1.2 The General Conditions are AIA Document A201-2007, General Conditions of the Contract for Construction.

§ 9.1.3 The Supplementary and other Conditions of the Contract:

Document	Title	Date	Pages
----------	-------	------	-------

§ 9.1.4 The Specifications:

(Either list the Specifications here or refer to an exhibit attached to this Agreement.)

Section	Title	Date	Pages
---------	-------	------	-------

§ 9.1.5 The Drawings:

(Either list the Drawings here or refer to an exhibit attached to this Agreement.)

Number	Title	Date
--------	-------	------

§ 9.1.6 The Addenda, if any:

Number	Date	Pages
--------	------	-------

Portions of Addenda relating to bidding requirements are not part of the Contract Documents unless the bidding requirements are also enumerated in this Article 9.

§ 9.1.7 Additional documents, if any, forming part of the Contract Documents:

.1 AIA Document E201™-2007, Digital Data Protocol Exhibit, if completed by the parties, or the following:

.2 Other documents, if any, listed below:

(List here any additional documents that are intended to form part of the Contract Documents. AIA Document A201-2007 provides that bidding requirements such as advertisement or invitation to bid, Instructions to Bidders, sample forms and the Contractor's bid are not part of the Contract Documents)

Init.

unless enumerated in this Agreement. They should be listed here only if intended to be part of the Contract Documents.)

ARTICLE 10 INSURANCE AND BONDS

The Contractor shall purchase and maintain insurance and provide bonds as set forth in Article 11 of AIA Document A201-2007.

(State bonding requirements, if any, and limits of liability for insurance required in Article 11 of AIA Document A201-2007.)

Type of insurance or bond

Limit of liability or bond amount (\$0.00)

This Agreement entered into as of the day and year first written above.

OWNER (Signature)

CONTRACTOR (Signature)

(Printed name and title)

(Printed name and title)

NOT FOR BIDDING PURPOSES

Init.

STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

PERFORMANCE BOND

Bond Number: _____

KNOW ALL PERSONS BY THESE PRESENTS, that we, _____, as principal (“**Principal**”), and _____, a _____ corporation, legally authorized to do business in the State of Delaware, as surety (“**Surety**”), are held and firmly bound unto the Office of Management and Budget/Division of Facilities Management (“**Owner**”), in the amount of _____ (\$_____), to be paid to **Owner**, for which payment well and truly to be made, we do bind ourselves, our and each and every of our heirs, executors, administrators, successors and assigns, jointly and severally, for and in the whole, firmly by these presents.

Sealed with our seals and dated this _____ day of _____, 20__.


NOW THE CONDITION OF THIS OBLIGATION IS SUCH, that if **Principal**, who has been awarded by **Owner** that certain contract known as Contract No. _____ dated the _____ day of _____, 20__ (the “**Contract**”), which Contract is incorporated herein by reference, shall well and truly provide and furnish all materials, appliances and tools and perform all the work required under and pursuant to the terms and conditions of the Contract and the Contract Documents (as defined in the Contract) or any changes or modifications thereto made as therein provided, shall make good and reimburse **Owner** sufficient funds to pay the costs of completing the Contract that **Owner** may sustain by reason of any failure or default on the part of **Principal**, and shall also indemnify and save harmless **Owner** from all costs, damages and expenses arising out of or by reason of the performance of the Contract and for as long as provided by the Contract; then this obligation shall be void, otherwise to be and remain in full force and effect.

Surety, for value received, hereby stipulates and agrees, if requested to do so by **Owner**, to fully perform and complete the work to be performed under the Contract pursuant to the terms, conditions and covenants thereof, if for any cause **Principal** fails or neglects to so fully perform and complete such work.

Surety, for value received, for itself and its successors and assigns, hereby stipulates and agrees that the obligation of **Surety** and its bond shall be in no way impaired or affected by any extension of time, modification, omission, addition or change in or to the Contract or the work to be performed thereunder, or by any payment thereunder before the time required therein, or by any waiver of any provisions thereof, or by any assignment, subcontracting or other transfer thereof or of any work to be performed or any monies due or to become due thereunder; and **Surety** hereby waives notice of any and all such extensions, modifications, omissions, additions, changes, payments, waivers, assignments, subcontracts and transfers and hereby expressly stipulates and agrees that any and all things done and omitted to be done by and in relation to assignees, subcontractors, and other transferees shall have the same effect as to **Surety** as though done or omitted to be done by or in relation to **Principal**.

Surety hereby stipulates and agrees that no modifications, omissions or additions in or to the terms of the Contract shall in any way whatsoever affect the obligation of **Surety** and its bond.

Any proceeding, legal or equitable, under this Bond may be brought in any court of competent jurisdiction in the State of Delaware. Notices to **Surety** or Contractor may be mailed or delivered to them at their respective addresses shown below.



DIVISION OF FACILITIES MANAGEMENT

STATE OF DELAWARE

IN WITNESS WHEREOF, **Principal** and **Surety** have hereunto set their hand and seals, and such of them as are corporations have caused their corporate seal to be hereto affixed and these presents to be signed by their duly authorized officers, the day and year first above written.

PRINCIPAL

Name: _____

Address: _____

By: _____ (SEAL)

Name:

Title:

Witness or Attest:

Name:

(Corporate Seal)

SURETY

Name: _____

Address: _____

By: _____ (SEAL)

Name:

Title:

Witness or Attest:

Name:

(Corporate Seal)

NOT FOR BIDDING PURPOSES

PAYMENT BOND

Bond Number: _____

KNOW ALL PERSONS BY THESE PRESENTS, that we, _____, as principal (“**Principal**”), and _____, a _____ corporation, legally authorized to do business in the State of Delaware, as surety (“**Surety**”), are held and firmly bound unto the Office of Management and Budget/Division of Facilities Management (“**Owner**”), in the amount of _____ (\$_____), to be paid to **Owner**, for which payment well and truly to be made, we do bind ourselves, our and each and every of our heirs, executors, administrators, successors and assigns, jointly and severally, for and in the whole firmly by these presents.


Sealed with our seals and dated this _____ day of _____, 20__.

NOW THE CONDITION OF THIS OBLIGATION IS SUCH, that if **Principal**, who has been awarded by **Owner** that certain contract known as Contract No. _____ dated the _____ day of _____, 20__ (the “**Contract**”), which Contract is incorporated herein by reference, shall well and truly pay all and every person furnishing materials or performing labor or service in and about the performance of the work under the Contract, all and every sums of money due him, her, them or any of them, for all such materials, labor and service for which **Principal** is liable, shall make good and reimburse **Owner** sufficient funds to pay such costs in the completion of the Contract as **Owner** may sustain by reason of any failure or default on the part of **Principal**, and shall also indemnify and save harmless **Owner** from all costs, damages and expenses arising out of or by reason of the performance of the Contract and for as long as provided by the Contract; then this obligation shall be void, otherwise to be and remain in full force and effect.

Surety, for value received, for itself and its successors and assigns, hereby stipulates and agrees that the obligation of **Surety** and its bond shall be in no way impaired or affected by any extension of time, modification, omission, addition or change in or to the Contract or the work to be performed thereunder, or by any payment thereunder before the time required therein, or by any waiver of any provisions thereof, or by any assignment, subletting or other transfer thereof or of any work to be performed or any monies due or to become due thereunder; and **Surety** hereby waives notice of any and all such extensions, modifications, omissions, additions, changes, payments, waivers, assignments, subcontracts and transfers and hereby expressly stipulates and agrees that any and all things done and omitted to be done by and in relation to assignees, subcontractors, and other transferees shall have the same effect as to **Surety** as though done or omitted to be done by or in relation to **Principal**.

Surety hereby stipulates and agrees that no modifications, omission or additions in or to the terms of the Contract shall in any way whatsoever affect the obligation of **Surety** and its bond.

Any proceeding, legal or equitable, under this Bond may be brought in any court of competent jurisdiction in the State of Delaware. Notices to **Surety** or Contractor may be mailed or delivered to them at their respective addresses shown below.



IN WITNESS WHEREOF, **Principal** and **Surety** have hereunto set their hand and seals, and such of them as are corporations have caused their corporate seal to be hereto affixed and these presents to be signed by their duly authorized officers, the day and year first above written.

PRINCIPAL

Name: _____

Address: _____

By: _____ (SEAL)

Title: _____

Witness or Attest:

Name:

(Corporate Seal)

Name:

SURETY

Name: _____

Address: _____

By: _____ (SEAL)

Name:
Title: _____

Witness or Attest:

Name:

(Corporate Seal)

NOT FOR BIDDING PURPOSES

SECTION 00 62 76

CHANGE ORDER AIA G701-2017

AIA Document G701™CMa–1992 is for implementing changes in the work agreed to by the owner, contractor, construction manager adviser, and architect. Execution of a completed AIA Document G701™–2017 indicates agreement upon all the terms of the change, including any changes in the Contract Sum (or Guaranteed Maximum Price) and Contract Time. It provides space for the signatures of the owner, contractor, construction manager adviser, and architect, and for a complete description of the change. The major difference between AIA Documents G701CMa–1992 and G701–2017 is that the signature of the construction manager adviser, along with those of the owner, architect, and contractor, is required to validate the change order.

A draft copy of this document is included herein as follows

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES



AIA[®]

Document G701[™] – 2001

Change Order

PROJECT <i>(Name and address):</i>	CHANGE ORDER NUMBER:	OWNER: <input type="checkbox"/>
	DATE:	ARCHITECT: <input type="checkbox"/>
TO CONTRACTOR <i>(Name and address):</i>	ARCHITECT'S PROJECT NUMBER:	CONTRACTOR: <input type="checkbox"/>
	CONTRACT DATE:	FIELD: <input type="checkbox"/>
	CONTRACT FOR:	OTHER: <input type="checkbox"/>

THE CONTRACT IS CHANGED AS FOLLOWS:

(Include, where applicable, any undisputed amount attributable to previously executed Construction Change Directives)

The original Contract Sum was	\$	0.00
The net change by previously authorized Change Orders	\$	0.00
The Contract Sum prior to this Change Order was	\$	0.00
The Contract Sum will be by this Change Order in the amount of	\$	0.00
The new Contract Sum including this Change Order will be	\$	0.00
The Contract Time will be by () days.		
The date of Substantial Completion as of the date of this Change Order therefore is		

NOTE: This Change Order does not include changes in the Contract Sum, Contract Time or Guaranteed Maximum Price which have been authorized by Construction Change Directive until the cost and time have been agreed upon by both the Owner and Contractor, in which case a Change Order is executed to supplement the Construction Change Directive.

NOT VALID UNTIL SIGNED BY THE ARCHITECT, CONTRACTOR AND OWNER.

_____ ARCHITECT <i>(Firm name)</i>	_____ CONTRACTOR <i>(Firm name)</i>	_____ OWNER <i>(Firm name)</i>
_____ ADDRESS	_____ ADDRESS	_____ ADDRESS
_____ BY <i>(Signature)</i>	_____ BY <i>(Signature)</i>	_____ BY <i>(Signature)</i>
_____ <i>(Typed name)</i>	_____ <i>(Typed name)</i>	_____ <i>(Typed name)</i>
_____ DATE	_____ DATE	_____ DATE

NOT FOR BIDDING PURPOSES

SECTION 00 62 76

APPLICATION AND CERTIFICATE FOR PAYMENT AIA G702-1992

The Application and Certificate for Payment is as stated in the American Institute of Architects Document AIA G702 (1992 Edition) entitled Application and Certificate for Payment and is part of this project manual as if herein written in full.

A draft copy of this document is included herein as follows

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

Application and Certificate for Payment

TO OWNER: FROM CONTRACTOR:	PROJECT: VIA ARCHITECT:	APPLICATION NO.: PERIOD TO: CONTRACT NO.: CONTRACT DATE: / / PROJECT NO.: / /	Distribution to: OWNER: <input type="checkbox"/> ARCHITECT: <input type="checkbox"/> CONTRACTOR: <input type="checkbox"/> FIELD: <input type="checkbox"/> OTHER: <input type="checkbox"/>
---	--	--	---

CONTRACTOR'S APPLICATION FOR PAYMENT

Application is made for payment, as shown below, in connection with the Contract. Continuation Sheet, AIA Document G703, is attached.

1. ORIGINAL CONTRACT SUM	\$ _____
2. Net change by Change Orders	\$ _____
3. CONTRACT SUM TO DATE (Line 1 ± 2)	\$ _____
4. TOTAL COMPLETED & STORED TO DATE (Column G on G703)	\$ _____
5. RETAINAGE:	
a. _____ % of Completed Work (Column D + E on G703)	\$ _____
b. _____ % of Stored Material (Column F on G703)	\$ _____
Total Retainage (Lines 5a + 5b or Total in Column I of G703)	\$ _____
6. TOTAL EARNED LESS RETAINAGE	\$ _____
(Line 4 Less Line 5 Total)	
7. LESS PREVIOUS CERTIFICATES FOR PAYMENT	\$ _____
(Line 6 from prior Certificate)	
8. CURRENT PAYMENT DUE	\$ _____
9. BALANCE TO FINISH, INCLUDING RETAINAGE	\$ _____
(Line 3 less Line 6)	

CHANGE ORDER SUMMARY	ADDITIONS	DEDUCTIONS
Total changes approved in previous months by owner	\$ _____	\$ _____
Total approved this Month	\$ _____	\$ _____
TOTALS	\$ _____	\$ _____
NET CHANGES by Change Order	\$ _____	

The undersigned Contractor certifies that to the best of the Contractor's knowledge, information and belief the work covered by this Application for Payment has been completed in accordance with the Contract Documents, that all amounts have been paid by the Contractor for Work for which previous Certificates for Payment were issued and payments received from the Owner, and that current payment shown herein is now due.

CONTRACTOR:
 By: _____ Date: _____
 State of: _____
 County of: _____
 Subscribed and sworn to before
 me this _____ day of _____
 Notary Public:
 My Commission expires: _____

ARCHITECT'S CERTIFICATE FOR PAYMENT

In accordance with the Contract Documents, based on on-site observations and the data comprising this application, the Architect certifies to the Owner that to the best of the Architect's knowledge, information and belief the Work has progressed as indicated, the quality of the Work is in accordance with the Contract Documents, and the Contractor is entitled to payment of the AMOUNT CERTIFIED.

AMOUNT CERTIFIED

(Attach explanation if amount certified differs from the amount applied. Initial all figures on this Application and on the Continuation Sheet that are changed to conform with the amount certified.)

ARCHITECT:
 By: _____ Date: _____

This Certificate is not negotiable. The AMOUNT CERTIFIED is payable only to the Contractor named herein. Issuance, payment and acceptance of payment are without prejudice to any rights of the Owner or Contractor under this Contract

SECTION 00 62 76

APPLICATION FOR PAYMENT CONTINUATION SHEET AIA G703 -1992

AIA Document G702, Application and Certificate for Payment, is to be used in conjunction with AIA Document G703, Continuation Sheet. These documents are designed for use on Projects where the Contractor has a direct Agreement with the Owner. Procedures for their use are covered in AIA Document A201, General Conditions of the Contract for Construction.

A draft copy of this document is included herein as follows.

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 00 62 76

CERTIFICATE OF SUBSTANTIAL COMPLETION AIA G704 - 2000

AIA Document G704™-2000 is a standard form for recording the date of substantial completion of the work or a designated portion thereof. The contractor prepares a list of items to be completed or corrected, and the architect verifies and amends this list. If the architect finds that the work is substantially complete, the form is prepared for acceptance by the contractor and the owner, and the list of items to be completed or corrected is attached. In AIA Document G704-2000 the parties agree on the time allowed for completion or correction of the items, the date when the owner will occupy the work or designated portion thereof, and a description of responsibilities for maintenance, heat, utilities and insurance.

A draft copy of this document is included herein as follows.

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES



AIA® Document G704™ – 2000

Certificate of Substantial Completion

PROJECT:
(Name and address):

PROJECT NUMBER: /
CONTRACT FOR:
CONTRACT DATE:

OWNER:
ARCHITECT:
CONTRACTOR:
FIELD:
OTHER:

TO OWNER:
(Name and address):

TO CONTRACTOR:
(Name and address):

PROJECT OR PORTION OF THE PROJECT DESIGNATED FOR PARTIAL OCCUPANCY OR USE SHALL INCLUDE:

The Work performed under this Contract has been reviewed and found, to the Architect's best knowledge, information and belief, to be substantially complete. Substantial Completion is the stage in the progress of the Work when the Work or designated portion is sufficiently complete in accordance with the Contract Documents so that the Owner can occupy or utilize the Work for its intended use. The date of Substantial Completion of the Project or portion designated above is the date of issuance established by this Certificate, which is also the date of commencement of applicable warranties required by the Contract Documents, except as stated below:

Warranty

Date of Commencement

ARCHITECT

BY

DATE OF ISSUANCE

A list of items to be completed or corrected is attached hereto. The failure to include any items on such list does not alter the responsibility of the Contractor to complete all Work in accordance with the Contract Documents. Unless otherwise agreed to in writing, the date of commencement of warranties for items on the attached list will be the date of issuance of the final Certificate of Payment or the date of final payment.

Cost estimate of Work that is incomplete or defective: \$

The Contractor will complete or correct the Work on the list of items attached hereto within () days from the above date of Substantial Completion.

CONTRACTOR

BY

DATE

The Owner accepts the Work or designated portion as substantially complete and will assume full possession at (time) on (date).

OWNER

BY

DATE

The responsibilities of the Owner and Contractor for security, maintenance, heat, utilities, damage to the Work and insurance shall be as follows:

(Note: Owner's and Contractor's legal and insurance counsel should determine and review insurance requirements and coverage.)

SECTION 00 62 76

CONTRACTOR'S AFFIDAVIT OF PAYMENT OF DEBTS AND CLAIMS AIA G706 - 1994

The contractor submits this affidavit with the final request for payment, stating that all payroll bills for materials and equipment, and other indebtedness connected with the work for which the owner might be responsible has been paid or otherwise satisfied. AIA Document G706™-1994 requires the contractor to list any indebtedness or known claims in connection with the construction contract that have not been paid or otherwise satisfied. The contractor may also be required to furnish a lien bond or indemnity bond to protect the owner with respect to each exception.

A draft copy of this document is included herein as follows.

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES



AIA Document G706™ – 1994

Contractor's Affidavit of Payment of Debts and Claims

PROJECT: *(Name and address)*

ARCHITECT'S PROJECT NUMBER:

OWNER:

ARCHITECT:

TO OWNER: *(Name and address)*

CONTRACT FOR:

CONTRACTOR:

CONTRACT DATED:

SURETY:

OTHER:

STATE OF:
COUNTY OF:

The undersigned hereby certifies that, except as listed below, payment has been made in full and all obligations have otherwise been satisfied for all materials and equipment furnished, for all work, labor and services performed, and for all known indebtedness and claims against the Contractor for damages arising in any manner in connection with the performance of the Contract referenced above for which the Owner or Owner's property might in any way be held responsible or encumbered.

EXCEPTIONS:

SUPPORTING DOCUMENTS ATTACHED HERETO:

CONTRACTOR: *(Name and address)*

1. Consent of Surety to Final Payment. Whenever Surety is involved, Consent of Surety is required. AIA Document G707, Consent of Surety, may be used for this purpose

Indicate Attachment Yes No

The following supporting documents should be attached hereto if required by the Owner:

1. Contractor's Release or Waiver of Liens, conditional upon receipt of final payment.
2. Separate Releases or Waivers of Liens from Subcontractors and material and equipment suppliers, to the extent required by the Owner, accompanied by a list thereof.
3. Contractor's Affidavit of Release of Liens (AIA Document G706A).

BY: _____
(Signature of authorized representative)

(Printed name and title)

Subscribed and sworn to before me on this date:

Notary Public:
My Commission Expires:

SECTION 00 62 76

CONTRACTOR'S AFFIDAVIT OF RELEASE OF LIENS AIA G706A - 1994

AIA Document G706A™-1994 supports AIA Document G706™-1994 in the event that the owner requires a sworn statement of the contractor stating that all releases or waivers of liens have been received. In such event, it is normal for the contractor to submit AIA Documents G706-1994 and G706A-1994 along with attached releases or waivers of liens for the contractor, all subcontractors and others who may have lien rights against the owner's property. The contractor is required to list any exceptions to the sworn statement provided in G706A-1994, and may be required to furnish to the owner a lien bond or indemnity bond to protect the owner with respect to such exceptions.

A draft copy of this document is included herein as follows.

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES



AIA[®] Document G706A[™] – 1994

Contractor's Affidavit of Release of Liens

PROJECT: <i>(Name and address)</i>	ARCHITECT'S PROJECT NUMBER:	OWNER: <input type="checkbox"/>
TO OWNER: <i>(Name and address)</i>	CONTRACT FOR: CONTRACT DATED:	ARCHITECT: <input type="checkbox"/> CONTRACTOR: <input type="checkbox"/> SURETY: <input type="checkbox"/> OTHER: <input type="checkbox"/>

STATE OF:
COUNTY OF:

The undersigned hereby certifies that to the best of the undersigned's knowledge, information and belief, except as listed below, the Releases or Waivers of Lien attached hereto include the Contractor, all subcontractors, all suppliers of materials and equipment, and all performers of Work, labor or services who have or may have liens or encumbrances or the right to assert liens or encumbrances against any property of the Owner arising in any manner out of the performance of the Contract referenced above.

EXCEPTIONS:

SUPPORTING DOCUMENTS ATTACHED HERETO: CONTRACTOR: *(Name and address)*

1. Contractor's Release or Waiver of Liens, conditional upon receipt of final payment.
2. Separate Releases or Waivers of Liens from Subcontractors and material and equipment suppliers, to the extent required by the Owner, accompanied by a list thereof.

BY: _____
(Signature of authorized representative)

(Printed name and title)

Subscribed and sworn to before me on this date:

Notary Public:
My Commission Expires:

NOT FOR BIDDING PURPOSES

SECTION 00 62 76

CONSENT OF SURETY TO FINAL PAYMENT AIA G707 - 1994

AIA Document G707™-1994 is intended for use as a companion to AIA Document G706™-1994, Contractor's Affidavit of Payment of Debts and Claims, on construction projects where the contractor is required to furnish a bond. By obtaining the surety's approval of final payment to the contractor and its agreement that final payment will not relieve the surety of any of its obligations, the owner may preserve its rights under the bond.

A draft copy of this document is included herein as follows.

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES



AIA[®]

Document G707™ – 1994

Consent Of Surety to Final Payment

PROJECT: *(Name and address)*

ARCHITECT'S PROJECT NUMBER:

OWNER:

CONTRACT FOR:

ARCHITECT:

TO OWNER: *(Name and address)*

CONTRACT DATED:

CONTRACTOR:

SURETY:

OTHER:

In accordance with the provisions of the Contract between the Owner and the Contractor as indicated above, the
(Insert name and address of Surety)

on bond of
(Insert name and address of Contractor)

, SURETY,

hereby approves of the final payment to the Contractor, and agrees that final payment to the Contractor shall not relieve the
Surety of any of its obligations to
(Insert name and address of Owner)

, CONTRACTOR,

as set forth in said Surety's bond.

, OWNER,

IN WITNESS WHEREOF, the Surety has hereunto set its hand on this date:
(Insert in writing the month followed by the numeric date and year.)

(Surety)

(Signature of authorized representative)

Attest:
(Seal):

(Printed name and title)

NOT FOR BIDDING PURPOSES

SECTION 00 62 76

ARCHITECT'S SUPPLEMENTAL INSTRUCTIONS AIA G710 -1992

AIA Document G710™-1992 is used by the architect to issue additional instructions or interpretations or to order minor changes in the work. It is intended to assist the architect in performing its obligations as interpreter of the contract documents in accordance with the owner/architect agreement and the general conditions of the contract for construction. AIA Document G710-1992 should not be used to change the contract sum or contract time. It is intended to help the architect perform its services with respect to minor changes not involving adjustment in the contract sum or contract time. Such minor changes are authorized under Section 7.4 of AIA Document A201™-2007.

A draft copy of this document is included herein as follows

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES



AIA® Document G710™ – 1992

Architect's Supplemental Instructions

PROJECT (Name and address):

ARCHITECT'S SUPPLEMENTAL INSTRUCTION NO:

OWNER:

ARCHITECT:

CONSULTANT:

CONTRACTOR:

FIELD:

OTHER:

OWNER (Name and address):

DATE OF ISSUANCE:

CONTRACT FOR:

FROM ARCHITECT (Name and address):

CONTRACT DATE:

TO CONTRACTOR (Name and address):

ARCHITECT'S PROJECT NUMBER:

The Work shall be carried out in accordance with the following supplemental instructions issued in accordance with the Contract Documents without change in Contract Sum or Contract Time. Proceeding with the Work in accordance with these instructions indicates your acknowledgment that there will be no change in the Contract Sum or Contract Time.

DESCRIPTION:

ATTACHMENTS:

(Here insert listing of documents that support description.)

ISSUED BY THE ARCHITECT

(Signature)

(Printed name and title)

NOT FOR BIDDING PURPOSES

SECTION 00 62 76

CONSTRUCTION CHANGE DIRECTIVE AIA G714 - 2007

AIA Document G714™-2007 is a directive for changes in the Work for use where the owner and contractor have not reached an agreement on proposed changes in the contract sum or contract time. AIA Document G714-2007 was developed as a directive for changes in the work which, if not expeditiously implemented, might delay the project. Upon receipt of a completed G714-2007, the contractor must promptly proceed with the change in the work described therein. NOTE: G714-2001 expired in 2009.

A draft copy of this document is included herein as follows.

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES



AIA Document G714™ – 2007

Construction Change Directive

PROJECT: <i>(Name and address)</i>	DIRECTIVE NUMBER: 001	OWNER: <input type="checkbox"/>
	DATE:	ARCHITECT: <input type="checkbox"/>
	CONTRACT FOR:	CONSULTANT: <input type="checkbox"/>
TO CONTRACTOR: <i>(Name and address)</i>	CONTRACT DATED:	CONTRACTOR: <input type="checkbox"/>
	ARCHITECT'S PROJECT NUMBER:	FIELD: <input type="checkbox"/>
		OTHER: <input type="checkbox"/>

You are hereby directed to make the following change(s) in this Contract:
(Describe briefly any proposed changes or list any attached information in the alternative.)

PROPOSED ADJUSTMENTS

- The proposed basis of adjustment to the Contract Sum or Guaranteed Maximum Price is:
 - Lump Sum decrease of \$0.00
 - Unit Price of \$ per
 - As provided in Section 7.3.3 of AIA Document A201-2007
 - As follows:
- The Contract Time is proposed to remain unchanged. The proposed adjustment, if any, is (0 days).

When signed by the Owner and Architect and received by the Contractor, this document becomes effective IMMEDIATELY as a Construction Change Directive (CCD), and the Contractor shall proceed with the change(s) described above.

Contractor signature indicates agreement with the proposed adjustments in Contract Sum and Contract Time set forth in this CCD.

_____ ARCHITECT <i>(Firm name)</i>	_____ OWNER <i>(Firm name)</i>	_____ CONTRACTOR <i>(Firm name)</i>
_____ ADDRESS	_____ ADDRESS	_____ ADDRESS
_____ BY <i>(Signature)</i>	_____ BY <i>(Signature)</i>	_____ BY <i>(Signature)</i>
_____ <i>(Typed name)</i>	_____ <i>(Typed name)</i>	_____ <i>(Typed name)</i>
_____ DATE	_____ DATE	_____ DATE

SECTION 00 62 76

ACORD CERTIFICATE OF INSURANCE AIA G715-1991

AIA Document G715™–1991 is intended for use in adopting ACORD Form 25-S to certify the coverage required of contractors under AIA Document A201™–2007, General Conditions of the Contract for Construction. Since the ACORD certificate does not have space to show all the coverages required by AIA Document A201–2007, the Supplemental Attachment form should be completed, signed by the contractor’s insurance representative, and attached to the ACORD certificate.

A draft copy of this document is included herein as follows.

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES



AIA® Document G715™ – 1991

Supplemental Attachment for ACORD Certificate of Insurance 25-S

(This document replaces AIA Document G705, Certificate of Insurance.)

PROJECT (Name and address): _____

INSURED _____

A. General Liability

- | | Yes | No | NA |
|--|--------------------------|--------------------------|--------------------------|
| 1. Does the General Aggregate apply to this Project only? | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 2. Does this policy include coverage for: | | | |
| a. Premises - Operations? | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| b. Explosion, Collapse and Underground Hazards? | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| c. Personal Injury Coverage? | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| d. Products Coverage? | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| e. Completed Operations? | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| f. Contractual Coverage for the Insured's obligations in A201? | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 3. If coverage is written on a claims-made basis, what is the: | | | |
| a. Retroactive Date? | | | |
| b. Extended Reporting Date? | | | |

B. Worker's Compensation

- | | | | |
|---|--------------------------|--------------------------|--------------------------|
| 1. If the Insured is exempt from Worker's Compensation statutes, does the Insured carry the equivalent Voluntary Compensation coverage? | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|---|--------------------------|--------------------------|--------------------------|

C. Final Payment Information

- | | | | |
|---|--------------------------|--------------------------|--------------------------|
| 1. Is this certificate being furnished in connection with the Contractor's request for final payment in accordance with the requirements of Sections 9.10.2 and 11.1.3 of AIA Document A201, General Conditions of the Contract for Construction? | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| 2. If so, and if the policy period extends beyond termination of the Contract for Construction, is Completed Operations coverage for this Project continued for the balance of the policy period? | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |

D. Termination Provisions

- | | | | |
|--|--------------------------|--------------------------|--------------------------|
| 1. Has each policy shown on the certificate and this Supplement been endorsed to provide the holder with 30 days notice of cancellation and/or expiration? List below any policies which do not contain this notice. | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
|--|--------------------------|--------------------------|--------------------------|

E. Other Provisions

Authorized Representative

Date of Issue

SECTION 00 72 13

GENERAL CONDITIONS OF THE CONSTRUCTION CONTRACT

The General Conditions of this Contract are as stated in the American Institute of Architects Document AIA A201 (2007 Edition) entitled General Conditions of the Contract for Construction and is part of this project manual as if herein written in full.

Copies of the Document are available through the Owner.

A draft copy of this document is included herein as follows

NOT FOR BIDDING PURPOSES

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

AIA[®] Document A201[™] – 2007

General Conditions of the Contract for Construction

for the following PROJECT:
(Name and location or address)

THE OWNER:
(Name, legal status and address)

THE ARCHITECT:
(Name, legal status and address)

TABLE OF ARTICLES

- 1 GENERAL PROVISIONS
- 2 OWNER
- 3 CONTRACTOR
- 4 ARCHITECT
- 5 SUBCONTRACTORS
- 6 CONSTRUCTION BY OWNER OR BY SEPARATE CONTRACTORS
- 7 CHANGES IN THE WORK
- 8 TIME
- 9 PAYMENTS AND COMPLETION
- 10 PROTECTION OF PERSONS AND PROPERTY
- 11 INSURANCE AND BONDS
- 12 UNCOVERING AND CORRECTION OF WORK
- 13 MISCELLANEOUS PROVISIONS
- 14 TERMINATION OR SUSPENSION OF THE CONTRACT
- 15 CLAIMS AND DISPUTES

ADDITIONS AND DELETIONS:
The author of this document has added information needed for its completion. The author may also have revised the text of the original AIA standard form. An *Additions and Deletions Report* that notes added information as well as revisions to the standard form text is available from the author and should be reviewed. A vertical line in the left margin of this document indicates where the author has added necessary information and where the author has added to or deleted from the original AIA text.

This document has important legal consequences. Consultation with an attorney is encouraged with respect to its completion or modification.

Init.

INDEX

(Topics and numbers in bold are section headings.)

Acceptance of Nonconforming Work

9.6.6, 9.9.3, **12.3**

Acceptance of Work

9.6.6, 9.8.2, 9.9.3, 9.10.1, 9.10.3, **12.3**

Access to Work

3.16, 6.2.1, 12.1

Accident Prevention

10

Acts and Omissions

3.2, 3.3.2, 3.12.8, 3.18, 4.2.3, 8.3.1, 9.5.1, 10.2.5, 10.2.8, 13.4.2, 13.7, 14.1, 15.2

Addenda

1.1.1, 3.11.1

Additional Costs, Claims for

3.7.4, 3.7.5, 6.1.1, 7.3.7.5, 10.3, 15.1.4

Additional Inspections and Testing

9.4.2, 9.8.3, 12.2.1, **13.5**

Additional Insured

11.1.4

Additional Time, Claims for

3.2.4, 3.7.4, 3.7.5, 3.10.2, 8.3.2, **15.1.5**

Administration of the Contract

3.1.3, 4.2, 9.4, 9.5

Advertisement or Invitation to Bid

1.1.1

Aesthetic Effect

4.2.13

Allowances

3.8, 7.3.8

All-risk Insurance

11.3.1, 11.3.1.1

Applications for Payment

4.2.5, 7.3.9, 9.2, **9.3**, 9.4, 9.5.1, 9.6.3, 9.7, 9.10, 11.1.3

Approvals

2.1.1, 2.2.2, 2.4, 3.1.3, 3.10.2, 3.12.8, 3.12.9, 3.12.10, 4.2.7, 9.3.2, 13.5.1

Arbitration

8.3.1, 11.3.10, 13.7.1, 15.3.2, **15.4**

ARCHITECT

4

Architect, Definition of

4.1.1

Architect, Extent of Authority

2.4.1, 3.12.7, 4.1, 4.2, 5.2, 6.3, 7.1.2, 7.3.7, 7.4, 9.2, 9.5.1, 9.4, 9.5, 9.6.3, 9.8, 9.10.1, 9.10.3, 12.1, 12.2.1, 13.5.1, 13.5.2, 14.2.2, 14.2.4, 15.1.3, 15.2.1

Architect, Limitations of Authority and Responsibility

2.1.1, 3.12.4, 3.12.8, 3.12.10, 4.1.2, 4.2.1, 4.2.2, 4.2.3, 4.2.6, 4.2.7, 4.2.10, 4.2.12, 4.2.13, 5.2.1, 7.4, 9.4.2, 9.5.3, 9.6.4, 15.1.3, 15.2

Architect's Additional Services and Expenses

2.4.1, 11.3.1.1, 12.2.1, 13.5.2, 13.5.3, 14.2.4

Architect's Administration of the Contract

3.1.3, 4.2, 3.7.4, 15.2, 9.4.1, 9.5

Architect's Approvals

2.4.1, 3.1.3, 3.5, 3.10.2, 4.2.7

Architect's Authority to Reject Work

3.5, 4.2.6, 12.1.2, 12.2.1

Architect's Copyright

1.1.7, 1.5

Architect's Decisions

3.7.4, 4.2.6, 4.2.7, 4.2.11, 4.2.12, 4.2.13, 4.2.14, 9.3, 7.3.7, 7.3.9, 8.1.3, 8.3.1, 9.2, 9.4.1, 9.5, 9.8.4, 9.9.1, 13.5.2, 15.2, 15.3

Architect's Inspections

3.7.4, 4.2.2, 4.2.9, 9.4.2, 9.8.3, 9.9.2, 9.10.1, 13.5

Architect's Instructions

3.2.4, 3.3.1, 4.2.6, 4.2.7, 13.5.2

Architect's Interpretations

4.2.11, 4.2.12

Architect's Project Representative

4.2.10

Architect's Relationship with Contractor

1.1.2, 1.5, 3.1.3, 3.2.2, 3.2.3, 3.2.4, 3.3.1, 3.4.2, 3.5, 3.7.4, 3.7.5, 3.9.2, 3.9.3, 3.10, 3.11, 3.12, 3.16, 3.18, 4.2.2, 4.1.3, 4.2, 5.2, 6.2.2, 7, 8.3.1, 9.2, 9.3, 9.4, 9.5, 9.7, 9.8, 9.9, 10.2.6, 10.3, 11.3.7, 12, 13.4.2, 13.5, 15.2

Architect's Relationship with Subcontractors

1.1.2, 4.2.3, 4.2.4, 4.2.6, 9.6.3, 9.6.4, 11.3.7

Architect's Representations

9.4.2, 9.5.1, 9.10.1

Architect's Site Visits

3.7.4, 4.2.2, 4.2.9, 9.4.2, 9.5.1, 9.9.2, 9.10.1, 13.5

Asbestos

10.3.1

Attorneys' Fees

3.18.1, 9.10.2, 10.3.3

Award of Separate Contracts

6.1.1, 6.1.2

Award of Subcontracts and Other Contracts for Portions of the Work

5.2

Basic Definitions

1.1

Bidding Requirements

1.1.1, 5.2.1, 11.4.1

Binding Dispute Resolution

9.7, 11.3.9, 11.3.10, 13.1.1, 15.2.5, 15.2.6.1, 15.3.1, 15.3.2, 15.4.1

Boiler and Machinery Insurance

11.3.2

Bonds, Lien

7.3.7.4, 9.10.2, 9.10.3

Bonds, Performance, and Payment

7.3.7.4, 9.6.7, 9.10.3, 11.3.9, **11.4**

Building Permit

3.7.1

Init.

Capitalization

1.3

Certificate of Substantial Completion

9.8.3, 9.8.4, 9.8.5

Certificates for Payment

4.2.1, 4.2.5, 4.2.9, 9.3.3, 9.4, 9.5, 9.6.1, 9.6.6, 9.7, 9.10.1, 9.10.3, 14.1.1.3, 14.2.4, 15.1.3

Certificates of Inspection, Testing or Approval
13.5.4

Certificates of Insurance

9.10.2, 11.1.3

Change Orders

1.1.1, 2.4.1, 3.4.2, 3.7.4, 3.8.2.3, 3.11.1, 3.12.8, 4.2.8, 5.2.3, 7.1.2, 7.1.3, 7.2, 7.3.2, 7.3.6, 7.3.9, 7.3.10, 8.3.1, 9.3.1.1, 9.10.3, 10.3.2, 11.3.1.2, 11.3.4, 11.3.9, 12.1.2, 15.1.3

Change Orders, Definition of

7.2.1

CHANGES IN THE WORK

2.2.1, 3.11, 4.2.8, 7, 7.2.1, 7.3.1, 7.4, 8.3.1, 9.3.1.1, 11.3.9

Claims, Definition of

15.1.1

CLAIMS AND DISPUTES

3.2.4, 6.1.1, 6.3, 7.3.9, 9.3.3, 9.10.4, 10.3.3, 15, 15.4

Claims and Timely Assertion of Claims

15.4.1

Claims for Additional Cost

3.2.4, 3.7.4, 6.1.1, 7.3.9, 10.3.2, 15.1.4

Claims for Additional Time

3.2.4, 3.7.4.6.1.1, 8.3.2, 10.3.2, 15.1.5

Concealed or Unknown Conditions, Claims for

3.7.4

Claims for Damages

3.2.4, 3.18, 6.1.1, 8.3.3, 9.5.1, 9.6.7, 10.3.3, 11.1.1, 11.3.5, 11.3.7, 14.1.3, 14.2.4, 15.1.5

Claims Subject to Arbitration

15.3.1, 15.4.1

Cleaning Up

3.15, 6.3

Commencement of the Work, Conditions Relating to

2.2.1, 3.2.2, 3.4.1, 3.7.1, 3.10.1, 3.12.6, 5.2.1, 5.2.3, 6.2.2, 8.1.2, 8.2.2, 8.3.1, 11.1, 11.3.1, 11.3.6, 11.4.1, 15.1.4

Commencement of the Work, Definition of

8.1.2

Communications Facilitating Contract

Administration

3.9.1, 14.2.4

Completion, Conditions Relating to

3.4.1, 3.11, 3.15, 4.2.2, 4.2.9, 8.2, 9.4.2, 9.8, 9.9.1, 9.10, 12.2, 13.7, 14.1.2

COMPLETION, PAYMENTS AND

9

Completion, Substantial

4.2.9, 8.1.1, 8.1.3, 8.2.3, 9.4.2, 9.8, 9.9.1, 9.10.3, 12.2, 13.7

Compliance with Laws

1.6.1, 3.2.3, 3.6, 3.7, 3.12.10, 3.13, 4.1.1, 9.6.4, 10.2.2, 11.1, 11.3, 13.1, 13.4, 13.5.1, 13.5.2, 13.6, 14.1.1, 14.2.1.3, 15.2.8, 15.4.2, 15.4.3

Concealed or Unknown Conditions

3.7.4, 4.2.8, 8.3.1, 10.3

Conditions of the Contract

1.1.1, 6.1.1, 6.1.4

Consent, Written

3.4.2, 3.7.4, 3.12.8, 3.14.2, 4.1.2, 9.3.2, 9.8.5, 9.9.1, 9.10.2, 9.10.3, 11.3.1, 13.2, 13.4.2, 15.4.4.2

Consolidation or Joinder

15.4.4

CONSTRUCTION BY OWNER OR BY SEPARATE CONTRACTORS

1.1.4, 6

Construction Change Directive, Definition of
7.3.1

Construction Change Directives

1.1.1, 3.4.2, 3.12.8, 4.2.8, 7.1.1, 7.1.2, 7.1.3, 7.3, 9.3.1.1

Construction Schedule, Contractor's

3.10, 3.12.2, 3.12.2, 6.1.3, 15.1.5.2

Contingent Assignment of Subcontracts

5.4, 14.2.2.2

Continuing Contract Performance

5.1.3

Contract, Definition of

1.1.2

CONTRACT, TERMINATION OR SUSPENSION OF THE

5.4.1.1, 11.3.9, 14

Contract Administration

3.1.3, 4, 9.4, 9.5

Contract Award and Execution, Conditions Relating to

3.7.1, 3.10, 5.2, 6.1, 11.1.3, 11.3.6, 11.4.1

Contract Documents, Copies Furnished and Use of
1.5.2, 2.2.5, 5.3

Contract Documents, Definition of

1.1.1

Contract Sum

3.7.4, 3.8, 5.2.3, 7.2, 7.3, 7.4, 9.1, 9.4.2, 9.5.1.4, 9.6.7, 9.7, 10.3.2, 11.3.1, 14.2.4, 14.3.2, 15.1.4, 15.2.5

Contract Sum, Definition of

9.1

Contract Time

3.7.4, 3.7.5, 3.10.2, 5.2.3, 7.2.1.3, 7.3.1, 7.3.5, 7.4, 8.1.1, 8.2.1, 8.3.1, 9.5.1, 9.7, 10.3.2, 12.1.1, 14.3.2, 15.1.5.1, 15.2.5

Contract Time, Definition of

8.1.1

CONTRACTOR

3

Contractor, Definition of

3.1, 6.1.2

Init.

Contractor's Construction Schedules

3.10, 3.12.1, 3.12.2, 6.1.3, 15.1.5.2

Contractor's Employees

3.3.2, 3.4.3, 3.8.1, 3.9, 3.18.2, 4.2.3, 4.2.6, 10.2, 10.3, 11.1.1, 11.3.7, 14.1, 14.2.1.1

Contractor's Liability Insurance

11.1

Contractor's Relationship with Separate Contractors and Owner's Forces

3.12.5, 3.14.2, 4.2.4, 6, 11.3.7, 12.1.2, 12.2.4

Contractor's Relationship with Subcontractors

1.2.2, 3.3.2, 3.18.1, 3.18.2, 5, 9.6.2, 9.6.7, 9.10.2, 11.3.1.2, 11.3.7, 11.3.8

Contractor's Relationship with the Architect

1.1.2, 1.5, 3.1.3, 3.2.2, 3.2.3, 3.2.4, 3.3.1, 3.4.2, 3.5, 3.7.4, 3.10, 3.11, 3.12, 3.16, 3.18, 4.1.3, 4.2, 5.2, 6.2.2, 7, 8.3.1, 9.2, 9.3, 9.4, 9.5, 9.7, 9.8, 9.9, 10.2.6, 10.3, 11.3.7, 12, 13.5, 15.1.2, 15.2.1

Contractor's Representations

3.2.1, 3.2.2, 3.5, 3.12.6, 6.2.2, 8.2.1, 9.3.3, 9.8.2

Contractor's Responsibility for Those Performing the Work

3.3.2, 3.18, 5.3.1, 6.1.3, 6.2, 9.5.1, 10.2.8

Contractor's Review of Contract Documents

3.2

Contractor's Right to Stop the Work

9.7

Contractor's Right to Terminate the Contract

14.1, 15.1.6

Contractor's Submittals

3.10, 3.11, 3.12.4, 4.2.7, 5.2.1, 5.2.3, 9.2, 9.3, 9.8.2, 9.8.3, 9.9.1, 9.10.2, 9.10.3, 11.1.3, 11.4.2

Contractor's Superintendent

3.9, 10.2.6

Contractor's Supervision and Construction Procedures

1.2.2, 3.3, 3.4, 3.12.10, 4.2.2, 4.2.7, 6.1.3, 6.2.4, 7.1.3, 7.3.5, 7.3.7, 8.2, 10, 12, 14, 15.1.3

Contractual Liability Insurance

11.1.1.8, 11.2

Coordination and Correlation

1.2, 3.2.1, 3.3.1, 3.10, 3.12.2, 6.1.3, 6.2.1

Copies Furnished of Drawings and Specifications

1.5, 2.2.5, 3.11

Copyrights

1.5, 3.17

Correction of Work

2.3, 2.4, 7.3, 9.4.2, 9.8.2, 9.8.3, 9.9.1, 12.1.2, 12.2

Formation and Intent of the Contract Documents

Cost, Definition of

7.3.7

Costs

2.4.1, 3.2.4, 3.7.3, 3.8.2, 3.15.2, 5.4.2, 6.1.1, 6.2.3, 7.3.3.3, 7.3.7, 7.3.8, 7.3.9, 9.10.2, 10.3.2, 10.3.6, 11.3, 12.1.2, 12.2.1, 12.2.4, 13.5, 14

Cutting and Patching

3.14, 6.2.5

Damage to Construction of Owner or Separate Contractors

3.14.2, 6.2.4, 10.2.1.2, 10.2.5, 10.4, 11.1.1, 11.3, 12.2.4

Damage to the Work

3.14.2, 9.9.1, 10.2.1.2, 10.2.5, 10.4.1, 11.3.1, 12.2.4

Damages, Claims for

3.2.4, 3.18, 6.1.1, 8.3.3, 9.5.1, 9.6.7, 10.3.3, 11.1.1, 11.3.5, 11.3.7, 14.1.3, 14.2.4, 15.1.6

Damages for Delay

6.1.1, 8.3.3, 9.5.1.6, 9.7, 10.3.2

Date of Commencement of the Work, Definition of

8.1.2

Date of Substantial Completion, Definition of

8.1.3

Day, Definition of

8.1.4

Decisions of the Architect

3.7.4, 4.2.6, 4.2.7, 4.2.11, 4.2.12, 4.2.13, 15.2, 6.3, 7.3.7, 7.3.9, 8.1.3, 8.2.1, 9.2, 9.4, 9.5.1, 9.8.4, 9.9.1, 13.5.2, 14.2.2, 14.2.4, 15.1, 15.2

Decisions to Withhold Certification

9.4.1, 9.5, 9.7, 14.1.1.3

Defective or Nonconforming Work, Acceptance, Rejection and Correction of

2.4.1, 2.4.1, 3.5, 4.2.6, 6.2.5, 9.5.1, 9.5.2, 9.6.6, 9.8.2, 9.9.3, 9.10.4, 12.2.1

Definitions

1.1, 2.1.1, 3.1.1, 3.5, 3.12.1, 3.12.2, 3.12.3, 4.1.1, 15.1.1, 5.1, 6.1.2, 7.2.1, 7.3.1, 8.1, 9.1, 9.8.1

Delays and Extensions of Time

3.2, 3.7.4, 5.2.3, 7.2.1, 7.3.1, 7.4, 8.3, 9.5.1, 9.7, 10.3.2, 10.4.1, 14.3.2, 15.1.5, 15.2.5

Disputes

6.3, 7.3.9, 15.1, 15.2

Documents and Samples at the Site

3.11

Drawings, Definition of

1.1.5

Drawings and Specifications, Use and Ownership of

3.11

Effective Date of Insurance

8.2.2, 11.1.2

Emergencies

10.4, 14.1.1.2, 15.1.4

Employees, Contractor's

3.3.2, 3.4.3, 3.8.1, 3.9, 3.18.2, 4.2.3, 4.2.6, 10.2, 10.3.3, 11.1.1, 11.3.7, 14.1, 14.2.1.1

Equipment, Labor, Materials or

1.1.3, 1.1.6, 3.4, 3.5, 3.8.2, 3.8.3, 3.12, 3.13.1, 3.15.1, 4.2.6, 4.2.7, 5.2.1, 6.2.1, 7.3.7, 9.3.2, 9.3.3, 9.5.1.3, 9.10.2, 10.2.1, 10.2.4, 14.2.1.1, 14.2.1.2

Execution and Progress of the Work
 1.1.3, 1.2.1, 1.2.2, 2.2.3, 2.2.5, 3.1, 3.3.1, 3.4.1, 3.5,
 3.7.1, 3.10.1, 3.12, 3.14, 4.2, 6.2.2, 7.1.3, 7.3.5, 8.2,
 9.5.1, 9.9.1, 10.2, 10.3, 12.2, 14.2, 14.3.1, 15.1.3
 Extensions of Time
 3.2.4, 3.7.4, 5.2.3, 7.2.1, 7.3, 7.4, 9.5.1, 9.7, 10.3.2,
 10.4.1, 14.3, 15.1.5, 15.2.5
Failure of Payment
 9.5.1.3, 9.7, 9.10.2, 13.6, 14.1.1.3, 14.2.1.2
 Faulty Work
 (See Defective or Nonconforming Work)
Final Completion and Final Payment
 4.2.1, 4.2.9, 9.8.2, 9.10, 11.1.2, 11.1.3, 11.3.1, 11.3.5,
 12.3.1, 14.2.4, 14.4.3
 Financial Arrangements, Owner's
 2.2.1, 13.2.2, 14.1.1.4
 Fire and Extended Coverage Insurance
 11.3.1.1
GENERAL PROVISIONS
1
Governing Law
13.1
 Guarantees (See Warranty)
Hazardous Materials
 10.2.4, 10.3
 Identification of Subcontractors and Suppliers
 5.2.1
Indemnification
 3.17, 3.18, 9.10.2, 10.3.3, 10.3.5, 10.3.6, 11.3.1.2,
 11.3.7
Information and Services Required of the Owner
 2.1.2, 2.2, 3.2.2, 3.12.4, 3.12.10, 6.1.3, 6.1.4, 6.2.5,
 9.6.1, 9.6.4, 9.9.2, 9.10.3, 10.3.3, 11.2, 11.4, 13.5.1,
 13.5.2, 14.1.1.4, 14.1.4, 15.1.3
Initial Decision
15.2
Initial Decision Maker, Definition of
 1.1.8
 Initial Decision Maker, Decision
 14.2.2, 14.2.4, 15.2.1, 15.2.2, 15.2.3, 15.2.4, 15.2.5
 Initial Decision Maker, Extent of Authority
 14.2.2, 14.2.4, 15.1.3, 15.2.1, 15.2.2, 15.2.3, 15.2.4,
 15.2.5
Injury or Damage to Person or Property
10.2.8, 10.4.1
 Inspections
 3.1.3, 3.2.3, 3.7.1, 4.2.2, 4.2.6, 4.2.9, 9.4.2, 9.8.3,
 9.9.2, 9.10.1, 12.2.1, 13.5
 Instructions to Bidders
 1.1
 Instructions to the Contractor
 3.2.4, 3.3.1, 3.8.1, 5.2.1, 7, 8.2.2, 12, 13.5.2
Instruments of Service, Definition of
1.1.7
 Insurance
 3.18.1, 6.1.1, 7.3.7, 9.3.2, 9.8.4, 9.9.1, 9.10.2, 11

Insurance, Boiler and Machinery
11.3.2
Insurance, Contractor's Liability
11.1
 Insurance, Effective Date of
 8.2.2, 11.1.2
Insurance, Loss of Use
11.3.3
Insurance, Owner's Liability
11.2
Insurance, Property
 10.2.5, 11.3
 Insurance, Stored Materials
 9.3.2
INSURANCE AND BONDS
11
 Insurance Companies, Consent to Partial Occupancy
 9.9.1
 Intent of the Contract Documents
 1.2.1, 4.2.7, 4.2.12, 4.3.1, 7.4
Interest
13.6
Interpretation
 1.2.3, 1.4, 4.1.1, 5.1, 6.1.2, 15.1.1
 Interpretations, Written
 4.1.11, 4.1.12, 15.1.4
 Judgment on Final Award
 15.4.2
Labor and Materials, Equipment
 1.1.3, 1.1.6, 3.4, 3.5, 3.8.2, 3.8.3, 3.12, 3.13, 3.15.1,
 4.2.6, 4.2.7, 5.2.1, 6.2.1, 7.3.7, 9.3.2, 9.3.3, 9.5.1.3,
 9.10.2, 10.2.1, 10.2.4, 14.2.1.1, 14.2.1.2
 Labor Disputes
 8.3.1
 Laws and Regulations
 1.5, 3.2.3, 3.6, 3.7, 3.12.10, 3.13.1, 4.1.1, 9.6.4, 9.9.1,
 10.2.2, 11.1.1, 11.3, 13.1.1, 13.4, 13.5.1, 13.5.2,
 13.6.1, 14, 15.2.8, 15.4
 Liens
 2.1.2, 9.3.3, 9.10.2, 9.10.4, 15.2.8
 Limitations, Statutes of
 12.2.5, 13.7, 15.4.1.1
 Limitations of Liability
 2.3.1, 3.2.2, 3.5, 3.12.10, 3.17, 3.18.1, 4.2.6, 4.2.7,
 4.2.12, 6.2.2, 9.4.2, 9.6.4, 9.6.7, 10.2.5, 10.3.3, 11.1.2,
 11.2, 11.3.7, 12.2.5, 13.4.2
 Limitations of Time
 2.1.2, 2.2, 2.4, 3.2.2, 3.10, 3.11, 3.12.5, 3.15.1, 4.2.7,
 5.2, 5.3.1, 5.4.1, 6.2.4, 7.3, 7.4, 8.2, 9.2, 9.3.1, 9.3.3,
 9.4.1, 9.5, 9.6, 9.7, 9.8, 9.9, 9.10, 11.1.3, 11.3.1.5,
 11.3.6, 11.3.10, 12.2, 13.5, 13.7, 14, 15
Loss of Use Insurance
11.3.3
 Material Suppliers
 1.5, 3.12.1, 4.2.4, 4.2.6, 5.2.1, 9.3, 9.4.2, 9.6, 9.10.5
Materials, Hazardous
 10.2.4, 10.3

NOT FOR BIDDING PURPOSES

Materials, Labor, Equipment and
1.1.3, 1.1.6, 1.5.1, 3.4.1, 3.5, 3.8.2, 3.8.3, 3.12, 3.13.1,
3.15.1, 4.2.6, 4.2.7, 5.2.1, 6.2.1, 7.3.7, 9.3.2, 9.3.3,
9.5.1.3, 9.10.2, 10.2.1.2, 10.2.4, 14.2.1.1, 14.2.1.2
Means, Methods, Techniques, Sequences and
Procedures of Construction
3.3.1, 3.12.10, 4.2.2, 4.2.7, 9.4.2
Mechanic's Lien
2.1.2, 15.2.8
Mediation
8.3.1, 10.3.5, 10.3.6, 15.2.1, 15.2.5, 15.2.6, 15.3,
15.4.1
Minor Changes in the Work
1.1.1, 3.12.8, 4.2.8, 7.1, 7.4
MISCELLANEOUS PROVISIONS
13
Modifications, Definition of
1.1.1
Modifications to the Contract
1.1.1, 1.1.2, 3.11, 4.1.2, 4.2.1, 5.2.3, 7, 8.3.1, 9.7,
10.3.2, 11.3.1
Mutual Responsibility
6.2
Nonconforming Work, Acceptance of
9.6.6, 9.9.3, 12.3
Nonconforming Work, Rejection and Correction of
2.3.1, 2.4.1, 3.5, 4.2.6, 6.2.4, 9.5.1, 9.8.2, 9.9.3, 9.10.4,
12.2.1
Notice
2.2.1, 2.3.1, 2.4.1, 3.2.4, 3.3.1, 3.7.2, 3.12.9, 5.2.1, 9.7,
9.10, 10.2.2, 11.1.3, 12.2.2.1, 13.3, 13.5.1, 13.5.2,
14.1, 14.2, 15.2.8, 15.4.1
Notice, Written
2.3.1, 2.4.1, 3.3.1, 3.9.2, 3.12.9, 3.12.10, 5.2.1, 9.7,
9.10, 10.2.2, 10.3, 11.1.3, 11.3.6, 12.2.2.1, 13.3, 14,
15.2.8, 15.4.1
Notice of Claims
3.7.4, 10.2.8, 15.1.2, 15.4
Notice of Testing and Inspections
13.5.1, 13.5.2
Observations, Contractor's
3.2, 3.7.4
Occupancy
2.2.2, 9.6.6, 9.8, 11.3.1.5
Orders, Written
1.1.1, 2.3, 3.9.2, 7, 8.2.2, 11.3.9, 12.1, 12.2.2.1, 13.5.2,
13.3.1
OWNER
2
Owner, Definition of
2.1.1
Owner, Information and Services Required of the
2.1.2, 2.2, 3.2.2, 3.12.10, 6.1.3, 6.1.4, 6.2.5, 9.3.2,
9.6.1, 9.6.4, 9.9.2, 9.10.3, 10.3.3, 11.2, 11.3, 13.5.1,
13.5.2, 14.1.1.4, 14.1.4, 15.1.3

Owner's Authority
1.5, 2.1.1, 2.3.1, 2.4.1, 3.4.2, 3.8.1, 3.12.10, 3.14.2,
4.1.2, 4.1.3, 4.2.4, 4.2.9, 5.2.1, 5.2.4, 5.4.1, 6.1, 6.3,
7.2.1, 7.3.1, 8.2.2, 8.3.1, 9.3.1, 9.3.2, 9.5.1, 9.6.4,
9.9.1, 9.10.2, 10.3.2, 11.1.3, 11.3.3, 11.3.10, 12.2.2,
12.3.1, 13.2.2, 14.3, 14.4, 15.2.7
Owner's Financial Capability
2.2.1, 13.2.2, 14.1.1.4
Owner's Liability Insurance
11.2
Owner's Relationship with Subcontractors
1.1.2, 5.2, 5.3, 5.4, 9.6.4, 9.10.2, 14.2.2
Owner's Right to Carry Out the Work
2.4, 14.2.2
Owner's Right to Clean Up
6.3
**Owner's Right to Perform Construction and to
Award Separate Contract**
6.1
Owner's Right to Stop the Work
2.3
Owner's Right to Suspend the Work
14.3
Owner's Right to Terminate the Contract
14.2
**Ownership and Use of Drawings, Specifications
and Other Instruments of Service**
1.1.1, 1.1.6, 1.1.7, 1.5, 2.2.5, 3.2.2, 3.11.1, 3.17,
4.2.12, 5.3.1
Partial Occupancy or Use
9.6.6, 9.9, 11.3.1.5
Patching, Cutting and
3.14, 6.2.5
Patents
3.17
Payment, Applications for
4.2.5, 7.3.9, 9.2, 9.3, 9.4, 9.5, 9.6.3, 9.7, 9.8.5, 9.10.1,
14.2.3, 14.2.4, 14.4.3
Payment, Certificates for
4.2.5, 4.2.9, 9.3.3, 9.4, 9.5, 9.6.1, 9.6.6, 9.7, 9.10.1,
9.10.3, 13.7, 14.1.1.3, 14.2.4
Payment, Failure of
9.5.1.3, 9.7, 9.10.2, 13.6, 14.1.1.3, 14.2.1.2
Payment, Final
4.2.1, 4.2.9, 9.8.2, 9.10, 11.1.2, 11.1.3, 11.4.1, 12.3.1,
13.7, 14.2.4, 14.4.3
Payment Bond, Performance Bond and
7.3.7.4, 9.6.7, 9.10.3, 11.4
Payments, Progress
9.3, 9.6, 9.8.5, 9.10.3, 13.6, 14.2.3, 15.1.3
PAYMENTS AND COMPLETION
9
Payments to Subcontractors
5.4.2, 9.5.1.3, 9.6.2, 9.6.3, 9.6.4, 9.6.7, 14.2.1.2
PCB
10.3.1

Performance Bond and Payment Bond
 7.3.7.4, 9.6.7, 9.10.3, 11.4
Permits, Fees, Notices and Compliance with Laws
 2.2.2, 3.7, 3.13, 7.3.7.4, 10.2.2
PERSONS AND PROPERTY, PROTECTION OF
10
 Polychlorinated Biphenyl
 10.3.1
Product Data, Definition of
 3.12.2
Product Data and Samples, Shop Drawings
 3.11, 3.12, 4.2.7
Progress and Completion
 4.2.2, 8.2, 9.8, 9.9.1, 14.1.4, 15.1.3
Progress Payments
 9.3, 9.6, 9.8.5, 9.10.3, 13.6, 14.2.3, 15.1.3
Project, Definition of
 1.1.4
 Project Representatives
 4.2.10
Property Insurance
 10.2.5, 11.3
PROTECTION OF PERSONS AND PROPERTY
10
 Regulations and Laws
 1.5, 3.2.3, 3.6, 3.7, 3.12.10, 3.13, 4.1.1, 9.6.4, 9.9.1,
 10.2.2, 11.1, 11.4, 13.1, 13.4, 13.5.1, 13.5.2, 13.6, 14,
 15.2.8, 15.4
 Rejection of Work
 3.5, 4.2.6, 12.2.1
 Releases and Waivers of Liens
 9.10.2
 Representations
 3.2.1, 3.5, 3.12.6, 6.2.2, 8.2.1, 9.3.3, 9.4.2, 9.5.1, 9.8.2,
 9.10.1
 Representatives
 2.1.1, 3.1.1, 3.9, 4.1.1, 4.2.1, 4.2.2, 4.2.10, 5.1.1, 5.1.2,
 13.2.1
 Responsibility for Those Performing the Work
 3.3.2, 3.18, 4.2.3, 5.3.1, 6.1.3, 6.2, 6.3, 9.5.1, 10
 Retainage
 9.3.1, 9.6.2, 9.8.5, 9.9.1, 9.10.2, 9.10.3
Review of Contract Documents and Field
Conditions by Contractor
 3.2, 3.12.7, 6.1.3
 Review of Contractor's Submittals by Owner and
 Architect
 3.10.1, 3.10.2, 3.11, 3.12, 4.2, 5.2, 6.1.3, 9.2, 9.8.2
 Review of Shop Drawings, Product Data and Samples
 by Contractor
 3.12
Rights and Remedies
 1.1.2, 2.3, 2.4, 3.5, 3.7.4, 3.15.2, 4.2.6, 5.3, 5.4, 6.1,
 6.3, 7.3.1, 8.3, 9.5.1, 9.7, 10.2.5, 10.3, 12.2.2, 12.2.4,
 13.4, 14, 15.4
Royalties, Patents and Copyrights
 3.17

Rules and Notices for Arbitration
 15.4.1
Safety of Persons and Property
 10.2, 10.4
Safety Precautions and Programs
 3.3.1, 4.2.2, 4.2.7, 5.3.1, 10.1, 10.2, 10.4
Samples, Definition of
 3.12.3
Samples, Shop Drawings, Product Data and
 3.11, 3.12, 4.2.7
Samples at the Site, Documents and
 3.11
Schedule of Values
 9.2, 9.3.1
 Schedules, Construction
 3.10, 3.12.1, 3.12.2, 6.1.3, 15.1.5.2
 Separate Contracts and Contractors
 1.1.4, 3.12.5, 3.14.2, 4.2.4, 4.2.7.6, 8.3.1, 12.1.2
Shop Drawings, Definition of
 3.12.1
Shop Drawings, Product Data and Samples
 3.11, 3.12, 4.2.7
Site, Use of
 3.13, 6.1.1, 6.3.1
 Site Inspections
 3.1.2, 5.3.1, 3.7.1, 3.7.4, 4.2, 9.4.2, 9.10.1, 13.5
 Site Visits, Architect's
 3.7.4, 4.2.2, 4.2.9, 9.4.2, 9.5.1, 9.9.2, 9.10.1, 13.5
 Special Inspections and Testing
 4.2.6, 12.2.1, 13.5
Specifications, Definition of
 1.1.6
Specifications
 1.1.1, 1.1.6, 1.2.2, 1.5, 3.11, 3.12.10, 3.17, 4.2.14
 Statute of Limitations
 13.7, 15.4.1.1
 Stopping the Work
 2.3, 9.7, 10.3, 14.1
 Stored Materials
 6.2.1, 9.3.2, 10.2.1.2, 10.2.4
Subcontractor, Definition of
 5.1.1
SUBCONTRACTORS
5
 Subcontractors, Work by
 1.2.2, 3.3.2, 3.12.1, 4.2.3, 5.2.3, 5.3, 5.4, 9.3.1.2, 9.6.7
Subcontractual Relations
 5.3, 5.4, 9.3.1.2, 9.6, 9.10, 10.2.1, 14.1, 14.2.1
 Submittals
 3.10, 3.11, 3.12, 4.2.7, 5.2.1, 5.2.3, 7.3.7, 9.2, 9.3, 9.8,
 9.9.1, 9.10.2, 9.10.3, 11.1.3
 Submittal Schedule
 3.10.2, 3.12.5, 4.2.7
Subrogation, Waivers of
 6.1.1, 11.3.7

Substantial Completion

4.2.9, 8.1.1, 8.1.3, 8.2.3, 9.4.2, 9.8, 9.9.1, 9.10.3, 12.2, 13.7

Substantial Completion, Definition of
9.8.1

Substitution of Subcontractors
5.2.3, 5.2.4

Substitution of Architect
4.1.3

Substitutions of Materials
3.4.2, 3.5, 7.3.8

Sub-subcontractor, Definition of
5.1.2

Subsurface Conditions
3.7.4

Successors and Assigns
13.2

Superintendent
3.9, 10.2.6

Supervision and Construction Procedures
1.2.2, 3.3, 3.4, 3.12.10, 4.2.2, 4.2.7, 6.1.3, 6.2.4, 7.1.3, 7.3.7, 8.2, 8.3.1, 9.4.2, 10, 12, 14, 15.1.3

Surety
5.4.1.2, 9.8.5, 9.10.2, 9.10.3, 14.2.2, 15.2.7

Surety, Consent of
9.10.2, 9.10.3

Surveys
2.2.3

Suspension by the Owner for Convenience
14.3

Suspension of the Work
5.4.2, 14.3

Suspension or Termination of the Contract
5.4.1.1, 14

Taxes
3.6, 3.8.2.1, 7.3.7.4

Termination by the Contractor
14.1, 15.1.6

Termination by the Owner for Cause
5.4.1.1, 14.2, 15.1.6

Termination by the Owner for Convenience
14.4

Termination of the Architect
4.1.3

Termination of the Contractor
14.2.2

TERMINATION OR SUSPENSION OF THE CONTRACT
14

Tests and Inspections
3.1.3, 3.3.3, 4.2.2, 4.2.6, 4.2.9, 9.4.2, 9.8.3, 9.9.2, 9.10.1, 10.3.2, 11.4.1.1, 12.2.1, 13.5

TIME
8

Time, Delays and Extensions of
3.2.4, 3.7.4, 5.2.3, 7.2.1, 7.3.1, 7.4, 8.3, 9.5.1, 9.7, 10.3.2, 10.4.1, 14.3.2, 15.1.5, 15.2.5

Time Limits
2.1.2, 2.2, 2.4, 3.2.2, 3.10, 3.11, 3.12.5, 3.15.1, 4.2, 5.2, 5.3, 5.4, 6.2.4, 7.3, 7.4, 8.2, 9.2, 9.3.1, 9.3.3, 9.4.1, 9.5, 9.6, 9.7, 9.8, 9.9, 9.10, 11.1.3, 12.2, 13.5, 13.7, 14, 15.1.2, 15.4

Time Limits on Claims
3.7.4, 10.2.8, 13.7, 15.1.2

Title to Work
9.3.2, 9.3.3

Transmission of Data in Digital Form
1.6

UNCOVERING AND CORRECTION OF WORK
12

Uncovering of Work
12.1

Unforeseen Conditions, Concealed or Unknown
3.7.4, 8.3.1, 10.3

Unit Prices
7.3.3.2, 7.3.4

Use of Documents
1.1.1, 1.5, 2.2.5, 3.12.6, 5.3

Use of Site
3.13, 6.1.1, 6.2.1

Values, Schedule of
9.2, 9.3.1

Waiver of Claims by the Architect
3.4.2

Waiver of Claims by the Contractor
9.10.5, 13.4.2, 15.1.6

Waiver of Claims by the Owner
9.9.3, 9.10.3, 9.10.4, 12.2.2.1, 13.4.2, 14.2.4, 15.1.6

Waiver of Consequential Damages
14.2.4, 15.1.6

Waiver of Liens
9.10.2, 9.10.4

Waivers of Subrogation
6.1.1, 11.3.7

Warranty
3.5, 4.2.9, 9.3.3, 9.8.4, 9.9.1, 9.10.4, 12.2.2, 13.7

Weather Delays
15.1.5.2

Work, Definition of
1.1.3

Written Consent
1.5.2, 3.4.2, 3.7.4, 3.12.8, 3.14.2, 4.1.2, 9.3.2, 9.8.5, 9.9.1, 9.10.2, 9.10.3, 11.4.1, 13.2, 13.4.2, 15.4.4.2

Written Interpretations
4.2.11, 4.2.12

Written Notice
2.3, 2.4, 3.3.1, 3.9, 3.12.9, 3.12.10, 5.2.1, 8.2.2, 9.7, 9.10, 10.2.2, 10.3, 11.1.3, 12.2.2, 12.2.4, 13.3, 14, 15.4.1

Written Orders
1.1.1, 2.3, 3.9, 7, 8.2.2, 12.1, 12.2, 13.5.2, 14.3.1, 15.1.2

ARTICLE 1 GENERAL PROVISIONS

§ 1.1 BASIC DEFINITIONS

§ 1.1.1 THE CONTRACT DOCUMENTS

The Contract Documents are enumerated in the Agreement between the Owner and Contractor (hereinafter the Agreement) and consist of the Agreement, Conditions of the Contract (General, Supplementary and other Conditions), Drawings, Specifications, Addenda issued prior to execution of the Contract, other documents listed in the Agreement and Modifications issued after execution of the Contract. A Modification is (1) a written amendment to the Contract signed by both parties, (2) a Change Order, (3) a Construction Change Directive or (4) a written order for a minor change in the Work issued by the Architect. Unless specifically enumerated in the Agreement, the Contract Documents do not include the advertisement or invitation to bid, Instructions to Bidders, sample forms, other information furnished by the Owner in anticipation of receiving bids or proposals, the Contractor's bid or proposal, or portions of Addenda relating to bidding requirements.

§ 1.1.2 THE CONTRACT

The Contract Documents form the Contract for Construction. The Contract represents the entire and integrated agreement between the parties hereto and supersedes prior negotiations, representations or agreements, either written or oral. The Contract may be amended or modified only by a Modification. The Contract Documents shall not be construed to create a contractual relationship of any kind (1) between the Contractor and the Architect or the Architect's consultants, (2) between the Owner and a Subcontractor or a Sub-subcontractor, (3) between the Owner and the Architect or the Architect's consultants or (4) between any persons or entities other than the Owner and the Contractor. The Architect shall, however, be entitled to performance and enforcement of obligations under the Contract intended to facilitate performance of the Architect's duties.

§ 1.1.3 THE WORK

The term "Work" means the construction and services required by the Contract Documents, whether completed or partially completed, and includes all other labor, materials, equipment and services provided or to be provided by the Contractor to fulfill the Contractor's obligations. The Work may constitute the whole or a part of the Project.

§ 1.1.4 THE PROJECT

The Project is the total construction of which the Work performed under the Contract Documents may be the whole or a part and which may include construction by the Owner and by separate contractors.

§ 1.1.5 THE DRAWINGS

The Drawings are the graphic and pictorial portions of the Contract Documents showing the design, location and dimensions of the Work, generally including plans, elevations, sections, details, schedules and diagrams.

§ 1.1.6 THE SPECIFICATIONS

The Specifications are that portion of the Contract Documents consisting of the written requirements for materials, equipment, systems, standards and workmanship for the Work, and performance of related services.

§ 1.1.7 INSTRUMENTS OF SERVICE

Instruments of Service are representations, in any medium of expression now known or later developed, of the tangible and intangible creative work performed by the Architect and the Architect's consultants under their respective professional services agreements. Instruments of Service may include, without limitation, studies, surveys, models, sketches, drawings, specifications, and other similar materials.

§ 1.1.8 INITIAL DECISION MAKER

The Initial Decision Maker is the person identified in the Agreement to render initial decisions on Claims in accordance with Section 15.2 and certify termination of the Agreement under Section 14.2.2.

§ 1.2 CORRELATION AND INTENT OF THE CONTRACT DOCUMENTS

§ 1.2.1 The intent of the Contract Documents is to include all items necessary for the proper execution and completion of the Work by the Contractor. The Contract Documents are complementary, and what is required by one shall be as binding as if required by all; performance by the Contractor shall be required only to the extent consistent with the Contract Documents and reasonably inferable from them as being necessary to produce the indicated results.

§ 1.2.2 Organization of the Specifications into divisions, sections and articles, and arrangement of Drawings shall not control the Contractor in dividing the Work among Subcontractors or in establishing the extent of Work to be performed by any trade.

§ 1.2.3 Unless otherwise stated in the Contract Documents, words that have well-known technical or construction industry meanings are used in the Contract Documents in accordance with such recognized meanings.

§ 1.3 CAPITALIZATION

Terms capitalized in these General Conditions include those that are (1) specifically defined, (2) the titles of numbered articles or (3) the titles of other documents published by the American Institute of Architects.

§ 1.4 INTERPRETATION

In the interest of brevity the Contract Documents frequently omit modifying words such as "all" and "any" and articles such as "the" and "an," but the fact that a modifier or an article is absent from one statement and appears in another is not intended to affect the interpretation of either statement.

§ 1.5 OWNERSHIP AND USE OF DRAWINGS, SPECIFICATIONS AND OTHER INSTRUMENTS OF SERVICE

§ 1.5.1 The Architect and the Architect's consultants shall be deemed the authors and owners of their respective Instruments of Service, including the Drawings and Specifications, and will retain all common law, statutory and other reserved rights, including copyrights. The Contractor, Subcontractors, Sub-subcontractors and material or equipment suppliers shall not own or claim a copyright in the Instruments of Service. Submittal or distribution to meet official regulatory requirements or for other purposes in connection with this Project shall not be construed as publication in derogation of the Architect's or Architect's consultants' reserved rights.

§ 1.5.2 The Contractor, Subcontractors, Sub-subcontractors and material or equipment suppliers are authorized to use and reproduce the Instruments of Service provided to them solely and exclusively for execution of the Work. All copies made under this authorization shall bear the copyright notice, if any, shown on the Instruments of Service. The Contractor, Subcontractors, Sub-subcontractors, and material or equipment suppliers may not use the Instruments of Service on other projects or for additions to this Project outside the scope of the Work without the specific written consent of the Owner, Architect and the Architect's consultants.

§ 1.6 TRANSMISSION OF DATA IN DIGITAL FORM

If the parties intend to transmit Instruments of Service or any other information or documentation in digital form, they shall endeavor to establish necessary protocols governing such transmissions, unless otherwise already provided in the Agreement or the Contract Documents.

ARTICLE 2 OWNER

§ 2.1 GENERAL

§ 2.1.1 The Owner is the person or entity identified as such in the Agreement and is referred to throughout the Contract Documents as if singular in number. The Owner shall designate in writing a representative who shall have express authority to bind the Owner with respect to all matters requiring the Owner's approval or authorization. Except as otherwise provided in Section 4.2.1, the Architect does not have such authority. The term "Owner" means the Owner or the Owner's authorized representative.

§ 2.1.2 The Owner shall furnish to the Contractor within fifteen days after receipt of a written request, information necessary and relevant for the Contractor to evaluate, give notice of or enforce mechanic's lien rights. Such information shall include a correct statement of the record legal title to the property on which the Project is located, usually referred to as the site, and the Owner's interest therein.

§ 2.2 INFORMATION AND SERVICES REQUIRED OF THE OWNER

§ 2.2.1 Prior to commencement of the Work, the Contractor may request in writing that the Owner provide reasonable evidence that the Owner has made financial arrangements to fulfill the Owner's obligations under the Contract. Thereafter, the Contractor may only request such evidence if (1) the Owner fails to make payments to the Contractor as the Contract Documents require; (2) a change in the Work materially changes the Contract Sum; or (3) the Contractor identifies in writing a reasonable concern regarding the Owner's ability to make payment when due. The Owner shall furnish such evidence as a condition precedent to commencement or continuation of the Work or the

portion of the Work affected by a material change. After the Owner furnishes the evidence, the Owner shall not materially vary such financial arrangements without prior notice to the Contractor.

§ 2.2.2 Except for permits and fees that are the responsibility of the Contractor under the Contract Documents, including those required under Section 3.7.1, the Owner shall secure and pay for necessary approvals, easements, assessments and charges required for construction, use or occupancy of permanent structures or for permanent changes in existing facilities.

§ 2.2.3 The Owner shall furnish surveys describing physical characteristics, legal limitations and utility location for the site of the Project, and a legal description of the site. The Contractor shall be entitled to rely on the accuracy of information furnished by the Owner but shall exercise proper precautions relating to the safe performance of the Work.

§ 2.2.4 The Owner shall furnish information or services required of the Owner by the Contract Documents with reasonable promptness. The Owner shall also furnish any other information or services under the Owner's control and relevant to the Contractor's performance of the Work with reasonable promptness after receiving the Contractor's written request for such information or services.

§ 2.2.5 Unless otherwise provided in the Contract Documents, the Owner shall furnish to the Contractor one copy of the Contract Documents for purposes of making reproductions pursuant to Section 1.5.2.

§ 2.3 OWNER'S RIGHT TO STOP THE WORK

If the Contractor fails to correct Work that is not in accordance with the requirements of the Contract Documents as required by Section 12.2 or repeatedly fails to carry out Work in accordance with the Contract Documents, the Owner may issue a written order to the Contractor to stop the Work, or any portion thereof, until the cause for such order has been eliminated; however, the right of the Owner to stop the Work shall not give rise to a duty on the part of the Owner to exercise this right for the benefit of the Contractor or any other person or entity, except to the extent required by Section 6.1.3.

§ 2.4 OWNER'S RIGHT TO CARRY OUT THE WORK

If the Contractor defaults or neglects to carry out the Work in accordance with the Contract Documents and fails within a ten-day period after receipt of written notice from the Owner to commence and continue correction of such default or neglect with diligence and promptness, the Owner may, without prejudice to other remedies the Owner may have, correct such deficiencies. In such case an appropriate Change Order shall be issued deducting from payments then or thereafter due the Contractor the reasonable cost of correcting such deficiencies, including Owner's expenses and compensation for the Architect's additional services made necessary by such default, neglect or failure. Such action by the Owner and amounts charged to the Contractor are both subject to prior approval of the Architect. If payments then or thereafter due the Contractor are not sufficient to cover such amounts, the Contractor shall pay the difference to the Owner.

ARTICLE 3 CONTRACTOR

§ 3.1 GENERAL

§ 3.1.1 The Contractor is the person or entity identified as such in the Agreement and is referred to throughout the Contract Documents as if singular in number. The Contractor shall be lawfully licensed, if required in the jurisdiction where the Project is located. The Contractor shall designate in writing a representative who shall have express authority to bind the Contractor with respect to all matters under this Contract. The term "Contractor" means the Contractor or the Contractor's authorized representative.

§ 3.1.2 The Contractor shall perform the Work in accordance with the Contract Documents.

§ 3.1.3 The Contractor shall not be relieved of obligations to perform the Work in accordance with the Contract Documents either by activities or duties of the Architect in the Architect's administration of the Contract, or by tests, inspections or approvals required or performed by persons or entities other than the Contractor.

§ 3.2 REVIEW OF CONTRACT DOCUMENTS AND FIELD CONDITIONS BY CONTRACTOR

§ 3.2.1 Execution of the Contract by the Contractor is a representation that the Contractor has visited the site, become generally familiar with local conditions under which the Work is to be performed and correlated personal observations with requirements of the Contract Documents.

§ 3.2.2 Because the Contract Documents are complementary, the Contractor shall, before starting each portion of the Work, carefully study and compare the various Contract Documents relative to that portion of the Work, as well as the information furnished by the Owner pursuant to Section 2.2.3, shall take field measurements of any existing conditions related to that portion of the Work, and shall observe any conditions at the site affecting it. These obligations are for the purpose of facilitating coordination and construction by the Contractor and are not for the purpose of discovering errors, omissions, or inconsistencies in the Contract Documents; however, the Contractor shall promptly report to the Architect any errors, inconsistencies or omissions discovered by or made known to the Contractor as a request for information in such form as the Architect may require. It is recognized that the Contractor's review is made in the Contractor's capacity as a contractor and not as a licensed design professional, unless otherwise specifically provided in the Contract Documents.

§ 3.2.3 The Contractor is not required to ascertain that the Contract Documents are in accordance with applicable laws, statutes, ordinances, codes, rules and regulations, or lawful orders of public authorities, but the Contractor shall promptly report to the Architect any nonconformity discovered by or made known to the Contractor as a request for information in such form as the Architect may require.

§ 3.2.4 If the Contractor believes that additional cost or time is involved because of clarifications or instructions the Architect issues in response to the Contractor's notices or requests for information pursuant to Sections 3.2.2 or 3.2.3, the Contractor shall make Claims as provided in Article 15. If the Contractor fails to perform the obligations of Sections 3.2.2 or 3.2.3, the Contractor shall pay such costs and damages to the Owner as would have been avoided if the Contractor had performed such obligations. If the Contractor performs those obligations, the Contractor shall not be liable to the Owner or Architect for damages resulting from errors, inconsistencies or omissions in the Contract Documents, for differences between field measurements or conditions and the Contract Documents, or for nonconformities of the Contract Documents to applicable laws, statutes, ordinances, codes, rules and regulations, and lawful orders of public authorities.

§ 3.3 SUPERVISION AND CONSTRUCTION PROCEDURES

§ 3.3.1 The Contractor shall supervise and direct the Work, using the Contractor's best skill and attention. The Contractor shall be solely responsible for, and have control over, construction means, methods, techniques, sequences and procedures and for coordinating all portions of the Work under the Contract, unless the Contract Documents give other specific instructions concerning these matters. If the Contract Documents give specific instructions concerning construction means, methods, techniques, sequences or procedures, the Contractor shall evaluate the jobsite safety thereof and, except as stated below, shall be fully and solely responsible for the jobsite safety of such means, methods, techniques, sequences or procedures. If the Contractor determines that such means, methods, techniques, sequences or procedures may not be safe, the Contractor shall give timely written notice to the Owner and Architect and shall not proceed with that portion of the Work without further written instructions from the Architect. If the Contractor is then instructed to proceed with the required means, methods, techniques, sequences or procedures without acceptance of changes proposed by the Contractor, the Owner shall be solely responsible for any loss or damage arising solely from those Owner-requested means, methods, techniques, sequences or procedures.

§ 3.3.2 The Contractor shall be responsible to the Owner for acts and omissions of the Contractor's employees, Subcontractors and their agents and employees, and other persons or entities performing portions of the Work for, or on behalf of, the Contractor or any of its Subcontractors.

§ 3.3.3 The Contractor shall be responsible for inspection of portions of Work already performed to determine that such portions are in proper condition to receive subsequent Work.

§ 3.4 LABOR AND MATERIALS

§ 3.4.1 Unless otherwise provided in the Contract Documents, the Contractor shall provide and pay for labor, materials, equipment, tools, construction equipment and machinery, water, heat, utilities, transportation, and other facilities and services necessary for proper execution and completion of the Work, whether temporary or permanent and whether or not incorporated or to be incorporated in the Work.

§ 3.4.2 Except in the case of minor changes in the Work authorized by the Architect in accordance with Sections 3.12.8 or 7.4, the Contractor may make substitutions only with the consent of the Owner, after evaluation by the Architect and in accordance with a Change Order or Construction Change Directive.

§ 3.4.3 The Contractor shall enforce strict discipline and good order among the Contractor's employees and other persons carrying out the Work. The Contractor shall not permit employment of unfit persons or persons not properly skilled in tasks assigned to them.

§ 3.5 WARRANTY

The Contractor warrants to the Owner and Architect that materials and equipment furnished under the Contract will be of good quality and new unless the Contract Documents require or permit otherwise. The Contractor further warrants that the Work will conform to the requirements of the Contract Documents and will be free from defects, except for those inherent in the quality of the Work the Contract Documents require or permit. Work, materials, or equipment not conforming to these requirements may be considered defective. The Contractor's warranty excludes remedy for damage or defect caused by abuse, alterations to the Work not executed by the Contractor, improper or insufficient maintenance, improper operation, or normal wear and tear and normal usage. If required by the Architect, the Contractor shall furnish satisfactory evidence as to the kind and quality of materials and equipment.

§ 3.6 TAXES

The Contractor shall pay sales, consumer, use and similar taxes for the Work provided by the Contractor that are legally enacted when bids are received or negotiations concluded, whether or not yet effective or merely scheduled to go into effect.

§ 3.7 PERMITS, FEES, NOTICES AND COMPLIANCE WITH LAWS

§ 3.7.1 Unless otherwise provided in the Contract Documents, the Contractor shall secure and pay for the building permit as well as for other permits, fees, licenses, and inspections by government agencies necessary for proper execution and completion of the Work that are customarily secured after execution of the Contract and legally required at the time bids are received or negotiations concluded.

§ 3.7.2 The Contractor shall comply with and give notice required by applicable laws, statutes, ordinances, codes, rules and regulations, and lawful orders of public authorities applicable to performance of the Work.

§ 3.7.3 If the Contractor performs Work knowing it to be contrary to applicable laws, statutes, ordinances, codes, rules and regulations, or lawful orders of public authorities, the Contractor shall assume appropriate responsibility for such Work and shall bear the costs attributable to correction.

§ 3.7.4 **Concealed or Unknown Conditions.** If the Contractor encounters conditions at the site that are (1) subsurface or otherwise concealed physical conditions that differ materially from those indicated in the Contract Documents or (2) unknown physical conditions of an unusual nature, that differ materially from those ordinarily found to exist and generally recognized as inherent in construction activities of the character provided for in the Contract Documents, the Contractor shall promptly provide notice to the Owner and the Architect before conditions are disturbed and in no event later than 21 days after first observance of the conditions. The Architect will promptly investigate such conditions and, if the Architect determines that they differ materially and cause an increase or decrease in the Contractor's cost of, or time required for, performance of any part of the Work, will recommend an equitable adjustment in the Contract Sum or Contract Time, or both. If the Architect determines that the conditions at the site are not materially different from those indicated in the Contract Documents and that no change in the terms of the Contract is justified, the Architect shall promptly notify the Owner and Contractor in writing, stating the reasons. If either party disputes the Architect's determination or recommendation, that party may proceed as provided in Article 15.

§ 3.7.5 If, in the course of the Work, the Contractor encounters human remains or recognizes the existence of burial markers, archaeological sites or wetlands not indicated in the Contract Documents, the Contractor shall immediately suspend any operations that would affect them and shall notify the Owner and Architect. Upon receipt of such notice, the Owner shall promptly take any action necessary to obtain governmental authorization required to resume the operations. The Contractor shall continue to suspend such operations until otherwise instructed by the Owner but shall continue with all other operations that do not affect those remains or features. Requests for adjustments in the Contract Sum and Contract Time arising from the existence of such remains or features may be made as provided in Article 15.

§ 3.8 ALLOWANCES

§ 3.8.1 The Contractor shall include in the Contract Sum all allowances stated in the Contract Documents. Items covered by allowances shall be supplied for such amounts and by such persons or entities as the Owner may direct, but the Contractor shall not be required to employ persons or entities to whom the Contractor has reasonable objection.

§ 3.8.2 Unless otherwise provided in the Contract Documents,

- .1 Allowances shall cover the cost to the Contractor of materials and equipment delivered at the site and all required taxes, less applicable trade discounts;
- .2 Contractor's costs for unloading and handling at the site, labor, installation costs, overhead, profit and other expenses contemplated for stated allowance amounts shall be included in the Contract Sum, but not in the allowances; and
- .3 Whenever costs are more than or less than allowances, the Contract Sum shall be adjusted accordingly by Change Order. The amount of the Change Order shall reflect (1) the difference between actual costs and the allowances under Section 3.8.2.1 and (2) changes in Contractor's costs under Section 3.8.2.2.

§ 3.8.3 Materials and equipment under an allowance shall be selected by the Owner with reasonable promptness.

§ 3.9 SUPERINTENDENT

§ 3.9.1 The Contractor shall employ a competent superintendent and necessary assistants who shall be in attendance at the Project site during performance of the Work. The superintendent shall represent the Contractor, and communications given to the superintendent shall be as binding as if given to the Contractor.

§ 3.9.2 The Contractor, as soon as practicable after award of the Contract, shall furnish in writing to the Owner through the Architect the name and qualifications of a proposed superintendent. The Architect may reply within 14 days to the Contractor in writing stating (1) whether the Owner or the Architect has reasonable objection to the proposed superintendent or (2) that the Architect requires additional time to review. Failure of the Architect to reply within the 14 day period shall constitute notice of no reasonable objection.

§ 3.9.3 The Contractor shall not employ a proposed superintendent to whom the Owner or Architect has made reasonable and timely objection. The Contractor shall not change the superintendent without the Owner's consent, which shall not unreasonably be withheld or delayed.

§ 3.10 CONTRACTOR'S CONSTRUCTION SCHEDULES

§ 3.10.1 The Contractor, promptly after being awarded the Contract, shall prepare and submit for the Owner's and Architect's information a Contractor's construction schedule for the Work. The schedule shall not exceed time limits current under the Contract Documents, shall be revised at appropriate intervals as required by the conditions of the Work and Project, shall be related to the entire Project to the extent required by the Contract Documents, and shall provide for expeditious and practicable execution of the Work.

§ 3.10.2 The Contractor shall prepare a submittal schedule, promptly after being awarded the Contract and thereafter as necessary to maintain a current submittal schedule, and shall submit the schedule(s) for the Architect's approval. The Architect's approval shall not unreasonably be delayed or withheld. The submittal schedule shall (1) be coordinated with the Contractor's construction schedule, and (2) allow the Architect reasonable time to review submittals. If the Contractor fails to submit a submittal schedule, the Contractor shall not be entitled to any increase in Contract Sum or extension of Contract Time based on the time required for review of submittals.

§ 3.10.3 The Contractor shall perform the Work in general accordance with the most recent schedules submitted to the Owner and Architect.

§ 3.11 DOCUMENTS AND SAMPLES AT THE SITE

The Contractor shall maintain at the site for the Owner one copy of the Drawings, Specifications, Addenda, Change Orders and other Modifications, in good order and marked currently to indicate field changes and selections made during construction, and one copy of approved Shop Drawings, Product Data, Samples and similar required submittals. These shall be available to the Architect and shall be delivered to the Architect for submittal to the Owner upon completion of the Work as a record of the Work as constructed.

Init.

§ 3.12 SHOP DRAWINGS, PRODUCT DATA AND SAMPLES

§ 3.12.1 Shop Drawings are drawings, diagrams, schedules and other data specially prepared for the Work by the Contractor or a Subcontractor, Sub-subcontractor, manufacturer, supplier or distributor to illustrate some portion of the Work.

§ 3.12.2 Product Data are illustrations, standard schedules, performance charts, instructions, brochures, diagrams and other information furnished by the Contractor to illustrate materials or equipment for some portion of the Work.

§ 3.12.3 Samples are physical examples that illustrate materials, equipment or workmanship and establish standards by which the Work will be judged.

§ 3.12.4 Shop Drawings, Product Data, Samples and similar submittals are not Contract Documents. Their purpose is to demonstrate the way by which the Contractor proposes to conform to the information given and the design concept expressed in the Contract Documents for those portions of the Work for which the Contract Documents require submittals. Review by the Architect is subject to the limitations of Section 4.2.7. Informational submittals upon which the Architect is not expected to take responsive action may be so identified in the Contract Documents. Submittals that are not required by the Contract Documents may be returned by the Architect without action.

§ 3.12.5 The Contractor shall review for compliance with the Contract Documents, approve and submit to the Architect Shop Drawings, Product Data, Samples and similar submittals required by the Contract Documents in accordance with the submittal schedule approved by the Architect or, in the absence of an approved submittal schedule, with reasonable promptness and in such sequence as to cause no delay in the Work or in the activities of the Owner or of separate contractors.

§ 3.12.6 By submitting Shop Drawings, Product Data, Samples and similar submittals, the Contractor represents to the Owner and Architect that the Contractor has (1) reviewed and approved them, (2) determined and verified materials, field measurements and field construction criteria related thereto or will do so and (3) checked and coordinated the information contained within such submittals with the requirements of the Work and of the Contract Documents.

§ 3.12.7 The Contractor shall perform no portion of the Work for which the Contract Documents require submittal and review of Shop Drawings, Product Data, Samples or similar submittals until the respective submittal has been approved by the Architect.

§ 3.12.8 The Work shall be in accordance with approved submittals except that the Contractor shall not be relieved of responsibility for deviations from requirements of the Contract Documents by the Architect's approval of Shop Drawings, Product Data, Samples or similar submittals unless the Contractor has specifically informed the Architect in writing of such deviation at the time of submittal and (1) the Architect has given written approval to the specific deviation as a minor change in the Work, or (2) a Change Order or Construction Change Directive has been issued authorizing the deviation. The Contractor shall not be relieved of responsibility for errors or omissions in Shop Drawings, Product Data, Samples or similar submittals by the Architect's approval thereof.

§ 3.12.9 The Contractor shall direct specific attention, in writing or on resubmitted Shop Drawings, Product Data, Samples or similar submittals, to revisions other than those requested by the Architect on previous submittals. In the absence of such written notice, the Architect's approval of a resubmission shall not apply to such revisions.

§ 3.12.10 The Contractor shall not be required to provide professional services that constitute the practice of architecture or engineering unless such services are specifically required by the Contract Documents for a portion of the Work or unless the Contractor needs to provide such services in order to carry out the Contractor's responsibilities for construction means, methods, techniques, sequences and procedures. The Contractor shall not be required to provide professional services in violation of applicable law. If professional design services or certifications by a design professional related to systems, materials or equipment are specifically required of the Contractor by the Contract Documents, the Owner and the Architect will specify all performance and design criteria that such services must satisfy. The Contractor shall cause such services or certifications to be provided by a properly licensed design professional, whose signature and seal shall appear on all drawings, calculations, specifications, certifications, Shop Drawings and other submittals prepared by such professional. Shop Drawings and other submittals related to the Work designed or certified by such professional, if prepared by others, shall bear such professional's written approval when submitted to the Architect. The Owner and the Architect shall be entitled to rely upon the adequacy, accuracy and

completeness of the services, certifications and approvals performed or provided by such design professionals, provided the Owner and Architect have specified to the Contractor all performance and design criteria that such services must satisfy. Pursuant to this Section 3.12.10, the Architect will review, approve or take other appropriate action on submittals only for the limited purpose of checking for conformance with information given and the design concept expressed in the Contract Documents. The Contractor shall not be responsible for the adequacy of the performance and design criteria specified in the Contract Documents.

§ 3.13 USE OF SITE

The Contractor shall confine operations at the site to areas permitted by applicable laws, statutes, ordinances, codes, rules and regulations, and lawful orders of public authorities and the Contract Documents and shall not unreasonably encumber the site with materials or equipment.

§ 3.14 CUTTING AND PATCHING

§ 3.14.1 The Contractor shall be responsible for cutting, fitting or patching required to complete the Work or to make its parts fit together properly. All areas requiring cutting, fitting and patching shall be restored to the condition existing prior to the cutting, fitting and patching, unless otherwise required by the Contract Documents.

§ 3.14.2 The Contractor shall not damage or endanger a portion of the Work or fully or partially completed construction of the Owner or separate contractors by cutting, patching or otherwise altering such construction, or by excavation. The Contractor shall not cut or otherwise alter such construction by the Owner or a separate contractor except with written consent of the Owner and of such separate contractor; such consent shall not be unreasonably withheld. The Contractor shall not unreasonably withhold from the Owner or a separate contractor the Contractor's consent to cutting or otherwise altering the Work.

§ 3.15 CLEANING UP

§ 3.15.1 The Contractor shall keep the premises and surrounding area free from accumulation of waste materials or rubbish caused by operations under the Contract. At completion of the Work, the Contractor shall remove waste materials, rubbish, the Contractor's tools, construction equipment, machinery and surplus materials from and about the Project.

§ 3.15.2 If the Contractor fails to clean up as provided in the Contract Documents, the Owner may do so and Owner shall be entitled to reimbursement from the Contractor.

§ 3.16 ACCESS TO WORK

The Contractor shall provide the Owner and Architect access to the Work in preparation and progress wherever located.

§ 3.17 ROYALTIES, PATENTS AND COPYRIGHTS

The Contractor shall pay all royalties and license fees. The Contractor shall defend suits or claims for infringement of copyrights and patent rights and shall hold the Owner and Architect harmless from loss on account thereof, but shall not be responsible for such defense or loss when a particular design, process or product of a particular manufacturer or manufacturers is required by the Contract Documents, or where the copyright violations are contained in Drawings, Specifications or other documents prepared by the Owner or Architect. However, if the Contractor has reason to believe that the required design, process or product is an infringement of a copyright or a patent, the Contractor shall be responsible for such loss unless such information is promptly furnished to the Architect.

§ 3.18 INDEMNIFICATION

§ 3.18.1 To the fullest extent permitted by law the Contractor shall indemnify and hold harmless the Owner, Architect, Architect's consultants, and agents and employees of any of them from and against claims, damages, losses and expenses, including but not limited to attorneys' fees, arising out of or resulting from performance of the Work, provided that such claim, damage, loss or expense is attributable to bodily injury, sickness, disease or death, or to injury to or destruction of tangible property (other than the Work itself), but only to the extent caused by the negligent acts or omissions of the Contractor, a Subcontractor, anyone directly or indirectly employed by them or anyone for whose acts they may be liable, regardless of whether or not such claim, damage, loss or expense is caused in part by a party indemnified hereunder. Such obligation shall not be construed to negate, abridge, or reduce other rights or obligations of indemnity that would otherwise exist as to a party or person described in this Section 3.18.

§ 3.18.2 In claims against any person or entity indemnified under this Section 3.18 by an employee of the Contractor, a Subcontractor, anyone directly or indirectly employed by them or anyone for whose acts they may be liable, the indemnification obligation under Section 3.18.1 shall not be limited by a limitation on amount or type of damages, compensation or benefits payable by or for the Contractor or a Subcontractor under workers' compensation acts, disability benefit acts or other employee benefit acts.

ARTICLE 4 ARCHITECT

§ 4.1 GENERAL

§ 4.1.1 The Owner shall retain an architect lawfully licensed to practice architecture or an entity lawfully practicing architecture in the jurisdiction where the Project is located. That person or entity is identified as the Architect in the Agreement and is referred to throughout the Contract Documents as if singular in number.

§ 4.1.2 Duties, responsibilities and limitations of authority of the Architect as set forth in the Contract Documents shall not be restricted, modified or extended without written consent of the Owner, Contractor and Architect. Consent shall not be unreasonably withheld.

§ 4.1.3 If the employment of the Architect is terminated, the Owner shall employ a successor architect as to whom the Contractor has no reasonable objection and whose status under the Contract Documents shall be that of the Architect.

§ 4.2 ADMINISTRATION OF THE CONTRACT

§ 4.2.1 The Architect will provide administration of the Contract as described in the Contract Documents and will be an Owner's representative during construction until the date the Architect issues the Final Certificate for Payment. The Architect will have authority to act on behalf of the Owner only to the extent provided in the Contract Documents.

§ 4.2.2 The Architect will visit the site at intervals appropriate to the stage of construction, or as otherwise agreed with the Owner, to become generally familiar with the progress and quality of the portion of the Work completed, and to determine in general if the Work observed is being performed in a manner indicating that the Work, when fully completed, will be in accordance with the Contract Documents. However, the Architect will not be required to make exhaustive or continuous on-site inspections to check the quality or quantity of the Work. The Architect will not have control over, charge of, or responsibility for, the construction means, methods, techniques, sequences or procedures, or for the safety precautions and programs in connection with the Work, since these are solely the Contractor's rights and responsibilities under the Contract Documents, except as provided in Section 3.3.1.

§ 4.2.3 On the basis of the site visits, the Architect will keep the Owner reasonably informed about the progress and quality of the portion of the Work completed, and report to the Owner (1) known deviations from the Contract Documents and from the most recent construction schedule submitted by the Contractor, and (2) defects and deficiencies observed in the Work. The Architect will not be responsible for the Contractor's failure to perform the Work in accordance with the requirements of the Contract Documents. The Architect will not have control over or charge of and will not be responsible for acts or omissions of the Contractor, Subcontractors, or their agents or employees, or any other persons or entities performing portions of the Work.

§ 4.2.4 COMMUNICATIONS FACILITATING CONTRACT ADMINISTRATION

Except as otherwise provided in the Contract Documents or when direct communications have been specially authorized, the Owner and Contractor shall endeavor to communicate with each other through the Architect about matters arising out of or relating to the Contract. Communications by and with the Architect's consultants shall be through the Architect. Communications by and with Subcontractors and material suppliers shall be through the Contractor. Communications by and with separate contractors shall be through the Owner.

§ 4.2.5 Based on the Architect's evaluations of the Contractor's Applications for Payment, the Architect will review and certify the amounts due the Contractor and will issue Certificates for Payment in such amounts.

§ 4.2.6 The Architect has authority to reject Work that does not conform to the Contract Documents. Whenever the Architect considers it necessary or advisable, the Architect will have authority to require inspection or testing of the Work in accordance with Sections 13.5.2 and 13.5.3, whether or not such Work is fabricated, installed or completed. However, neither this authority of the Architect nor a decision made in good faith either to exercise or not to exercise such authority shall give rise to a duty or responsibility of the Architect to the Contractor, Subcontractors, material and equipment suppliers, their agents or employees, or other persons or entities performing portions of the Work.

§ 4.2.7 The Architect will review and approve, or take other appropriate action upon, the Contractor's submittals such as Shop Drawings, Product Data and Samples, but only for the limited purpose of checking for conformance with information given and the design concept expressed in the Contract Documents. The Architect's action will be taken in accordance with the submittal schedule approved by the Architect or, in the absence of an approved submittal schedule, with reasonable promptness while allowing sufficient time in the Architect's professional judgment to permit adequate review. Review of such submittals is not conducted for the purpose of determining the accuracy and completeness of other details such as dimensions and quantities, or for substantiating instructions for installation or performance of equipment or systems, all of which remain the responsibility of the Contractor as required by the Contract Documents. The Architect's review of the Contractor's submittals shall not relieve the Contractor of the obligations under Sections 3.3, 3.5 and 3.12. The Architect's review shall not constitute approval of safety precautions or, unless otherwise specifically stated by the Architect, of any construction means, methods, techniques, sequences or procedures. The Architect's approval of a specific item shall not indicate approval of an assembly of which the item is a component.

§ 4.2.8 The Architect will prepare Change Orders and Construction Change Directives, and may authorize minor changes in the Work as provided in Section 7.4. The Architect will investigate and make determinations and recommendations regarding concealed and unknown conditions as provided in Section 3.7.4.

§ 4.2.9 The Architect will conduct inspections to determine the date or dates of Substantial Completion and the date of final completion; issue Certificates of Substantial Completion pursuant to Section 9.8; receive and forward to the Owner, for the Owner's review and records, written warranties and related documents required by the Contract and assembled by the Contractor pursuant to Section 9.10; and issue a final Certificate for Payment pursuant to Section 9.10.

§ 4.2.10 If the Owner and Architect agree, the Architect will provide one or more project representatives to assist in carrying out the Architect's responsibilities at the site. The duties, responsibilities and limitations of authority of such project representatives shall be as set forth in an exhibit to be incorporated in the Contract Documents.

§ 4.2.11 The Architect will interpret and decide matters concerning performance under, and requirements of, the Contract Documents on written request of either the Owner or Contractor. The Architect's response to such requests will be made in writing within any time limits agreed upon or otherwise with reasonable promptness.

§ 4.2.12 Interpretations and decisions of the Architect will be consistent with the intent of, and reasonably inferable from, the Contract Documents and will be in writing or in the form of drawings. When making such interpretations and decisions, the Architect will endeavor to secure faithful performance by both Owner and Contractor, will not show partiality to either and will not be liable for results of interpretations or decisions rendered in good faith.

§ 4.2.13 The Architect's decisions on matters relating to aesthetic effect will be final if consistent with the intent expressed in the Contract Documents.

§ 4.2.14 The Architect will review and respond to requests for information about the Contract Documents. The Architect's response to such requests will be made in writing within any time limits agreed upon or otherwise with reasonable promptness. If appropriate, the Architect will prepare and issue supplemental Drawings and Specifications in response to the requests for information.

ARTICLE 5 SUBCONTRACTORS

§ 5.1 DEFINITIONS

§ 5.1.1 A Subcontractor is a person or entity who has a direct contract with the Contractor to perform a portion of the Work at the site. The term "Subcontractor" is referred to throughout the Contract Documents as if singular in number and means a Subcontractor or an authorized representative of the Subcontractor. The term "Subcontractor" does not include a separate contractor or subcontractors of a separate contractor.

§ 5.1.2 A Sub-subcontractor is a person or entity who has a direct or indirect contract with a Subcontractor to perform a portion of the Work at the site. The term "Sub-subcontractor" is referred to throughout the Contract Documents as if singular in number and means a Sub-subcontractor or an authorized representative of the Sub-subcontractor.

§ 5.2 AWARD OF SUBCONTRACTS AND OTHER CONTRACTS FOR PORTIONS OF THE WORK

§ 5.2.1 Unless otherwise stated in the Contract Documents or the bidding requirements, the Contractor, as soon as practicable after award of the Contract, shall furnish in writing to the Owner through the Architect the names of persons or entities (including those who are to furnish materials or equipment fabricated to a special design) proposed for each principal portion of the Work. The Architect may reply within 14 days to the Contractor in writing stating (1) whether the Owner or the Architect has reasonable objection to any such proposed person or entity or (2) that the Architect requires additional time for review. Failure of the Owner or Architect to reply within the 14-day period shall constitute notice of no reasonable objection.

§ 5.2.2 The Contractor shall not contract with a proposed person or entity to whom the Owner or Architect has made reasonable and timely objection. The Contractor shall not be required to contract with anyone to whom the Contractor has made reasonable objection.

§ 5.2.3 If the Owner or Architect has reasonable objection to a person or entity proposed by the Contractor, the Contractor shall propose another to whom the Owner or Architect has no reasonable objection. If the proposed but rejected Subcontractor was reasonably capable of performing the Work, the Contract Sum and Contract Time shall be increased or decreased by the difference, if any, occasioned by such change, and an appropriate Change Order shall be issued before commencement of the substitute Subcontractor's Work. However, no increase in the Contract Sum or Contract Time shall be allowed for such change unless the Contractor has acted promptly and responsively in submitting names as required.

§ 5.2.4 The Contractor shall not substitute a Subcontractor, person or entity previously selected if the Owner or Architect makes reasonable objection to such substitution.

§ 5.3 SUBCONTRACTUAL RELATIONS

By appropriate agreement, written where legally required for validity, the Contractor shall require each Subcontractor, to the extent of the Work to be performed by the Subcontractor, to be bound to the Contractor by terms of the Contract Documents, and to assume toward the Contractor all the obligations and responsibilities, including the responsibility for safety of the Subcontractor's Work, which the Contractor, by these Documents, assumes toward the Owner and Architect. Each subcontract agreement shall preserve and protect the rights of the Owner and Architect under the Contract Documents with respect to the Work to be performed by the Subcontractor so that subcontracting thereof will not prejudice such rights, and shall allow to the Contractor, unless specifically provided otherwise in the subcontract agreement, the benefit of all rights, remedies and redress against the Contractor that the Contractor, by the Contract Documents, has against the Owner. Where appropriate, the Contractor shall require each Subcontractor to enter into similar agreements with Sub-subcontractors. The Contractor shall make available to each proposed Subcontractor, prior to the execution of the subcontract agreement, copies of the Contract Documents to which the Subcontractor will be bound, and, upon written request of the Subcontractor, identify to the Subcontractor terms and conditions of the proposed subcontract agreement that may be at variance with the Contract Documents. Subcontractors will similarly make copies of applicable portions of such documents available to their respective proposed Sub-subcontractors.

§ 5.4 CONTINGENT ASSIGNMENT OF SUBCONTRACTS

§ 5.4.1 Each subcontract agreement for a portion of the Work is assigned by the Contractor to the Owner, provided that

- 1 assignment is effective only after termination of the Contract by the Owner for cause pursuant to Section 14.2 and only for those subcontract agreements that the Owner accepts by notifying the Subcontractor and Contractor in writing; and
- 2 assignment is subject to the prior rights of the surety, if any, obligated under bond relating to the Contract.

When the Owner accepts the assignment of a subcontract agreement, the Owner assumes the Contractor's rights and obligations under the subcontract.

§ 5.4.2 Upon such assignment, if the Work has been suspended for more than 30 days, the Subcontractor's compensation shall be equitably adjusted for increases in cost resulting from the suspension.

§ 5.4.3 Upon such assignment to the Owner under this Section 5.4, the Owner may further assign the subcontract to a successor contractor or other entity. If the Owner assigns the subcontract to a successor contractor or other entity, the

Owner shall nevertheless remain legally responsible for all of the successor contractor's obligations under the subcontract.

ARTICLE 6 CONSTRUCTION BY OWNER OR BY SEPARATE CONTRACTORS

§ 6.1 OWNER'S RIGHT TO PERFORM CONSTRUCTION AND TO AWARD SEPARATE CONTRACTS

§ 6.1.1 The Owner reserves the right to perform construction or operations related to the Project with the Owner's own forces, and to award separate contracts in connection with other portions of the Project or other construction or operations on the site under Conditions of the Contract identical or substantially similar to these including those portions related to insurance and waiver of subrogation. If the Contractor claims that delay or additional cost is involved because of such action by the Owner, the Contractor shall make such Claim as provided in Article 10.

§ 6.1.2 When separate contracts are awarded for different portions of the Project or other construction or operations on the site, the term "Contractor" in the Contract Documents in each case shall mean the Contractor who executes each separate Owner-Contractor Agreement.

§ 6.1.3 The Owner shall provide for coordination of the activities of the Owner's own forces and of each separate contractor with the Work of the Contractor, who shall cooperate with them. The Contractor shall participate with other separate contractors and the Owner in reviewing their construction schedules. The Contractor shall make any revisions to the construction schedule deemed necessary after a joint review and mutual agreement. The construction schedules shall then constitute the schedules to be used by the Contractor, separate contractors and the Owner until subsequently revised.

§ 6.1.4 Unless otherwise provided in the Contract Documents, when the Owner performs construction or operations related to the Project with the Owner's own forces, the Owner shall be deemed to be subject to the same obligations and to have the same rights that apply to the Contractor under the Conditions of the Contract, including, without excluding others, those stated in Article 3, this Article 6 and Articles 10, 11 and 12.

§ 6.2 MUTUAL RESPONSIBILITY

§ 6.2.1 The Contractor shall afford the Owner and separate contractors reasonable opportunity for introduction and storage of their materials and equipment and performance of their activities, and shall connect and coordinate the Contractor's construction and operations with theirs as required by the Contract Documents.

§ 6.2.2 If part of the Contractor's Work depends for proper execution or results upon construction or operations by the Owner or a separate contractor, the Contractor shall, prior to proceeding with that portion of the Work, promptly report to the Architect apparent discrepancies or defects in such other construction that would render it unsuitable for such proper execution and results. Failure of the Contractor so to report shall constitute an acknowledgment that the Owner's or separate contractor's completed or partially completed construction is fit and proper to receive the Contractor's Work, except as to defects not then reasonably discoverable.

§ 6.2.3 The Contractor shall reimburse the Owner for costs the Owner incurs that are payable to a separate contractor because of the Contractor's delays, improperly timed activities or defective construction. The Owner shall be responsible to the Contractor for costs the Contractor incurs because of a separate contractor's delays, improperly timed activities, damage to the Work or defective construction.

§ 6.2.4 The Contractor shall promptly remedy damage the Contractor wrongfully causes to completed or partially completed construction or to property of the Owner or separate contractors as provided in Section 10.2.5.

§ 6.2.5 The Owner and each separate contractor shall have the same responsibilities for cutting and patching as are described for the Contractor in Section 3.14.

§ 6.3 OWNER'S RIGHT TO CLEAN UP

If a dispute arises among the Contractor, separate contractors and the Owner as to the responsibility under their respective contracts for maintaining the premises and surrounding area free from waste materials and rubbish, the Owner may clean up and the Architect will allocate the cost among those responsible.

ARTICLE 7 CHANGES IN THE WORK

§ 7.1 GENERAL

§ 7.1.1 Changes in the Work may be accomplished after execution of the Contract, and without invalidating the Contract, by Change Order, Construction Change Directive or order for a minor change in the Work, subject to the limitations stated in this Article 7 and elsewhere in the Contract Documents.

§ 7.1.2 A Change Order shall be based upon agreement among the Owner, Contractor and Architect; a Construction Change Directive requires agreement by the Owner and Architect and may or may not be agreed to by the Contractor; an order for a minor change in the Work may be issued by the Architect alone.

§ 7.1.3 Changes in the Work shall be performed under applicable provisions of the Contract Documents, and the Contractor shall proceed promptly, unless otherwise provided in the Change Order, Construction Change Directive or order for a minor change in the Work.

§ 7.2 CHANGE ORDERS

§ 7.2.1 A Change Order is a written instrument prepared by the Architect and signed by the Owner, Contractor and Architect stating their agreement upon all of the following:

- .1 The change in the Work;
- .2 The amount of the adjustment, if any, in the Contract Sum; and
- .3 The extent of the adjustment, if any, in the Contract Time.

§ 7.3 CONSTRUCTION CHANGE DIRECTIVES

§ 7.3.1 A Construction Change Directive is a written order prepared by the Architect and signed by the Owner and Architect, directing a change in the Work prior to agreement on adjustment, if any, in the Contract Sum or Contract Time, or both. The Owner may by Construction Change Directive, without invalidating the Contract, order changes in the Work within the general scope of the Contract consisting of additions, deletions or other revisions, the Contract Sum and Contract Time being adjusted accordingly.

§ 7.3.2 A Construction Change Directive shall be used in the absence of total agreement on the terms of a Change Order.

§ 7.3.3 If the Construction Change Directive provides for an adjustment to the Contract Sum, the adjustment shall be based on one of the following methods:

- .1 Mutual acceptance of a lump sum properly itemized and supported by sufficient substantiating data to permit evaluation;
- .2 Unit prices stated in the Contract Documents or subsequently agreed upon;
- .3 Cost to be determined in a manner agreed upon by the parties and a mutually acceptable fixed or percentage fee; or
- .4 As provided in Section 7.3.7.

§ 7.3.4 If unit prices are stated in the Contract Documents or subsequently agreed upon, and if quantities originally contemplated are materially changed in a proposed Change Order or Construction Change Directive so that application of such unit prices to quantities of Work proposed will cause substantial inequity to the Owner or Contractor, the applicable unit prices shall be equitably adjusted.

§ 7.3.5 Upon receipt of a Construction Change Directive, the Contractor shall promptly proceed with the change in the Work involved and advise the Architect of the Contractor's agreement or disagreement with the method, if any, provided in the Construction Change Directive for determining the proposed adjustment in the Contract Sum or Contract Time.

§ 7.3.6 A Construction Change Directive signed by the Contractor indicates the Contractor's agreement therewith, including adjustment in Contract Sum and Contract Time or the method for determining them. Such agreement shall be effective immediately and shall be recorded as a Change Order.

§ 7.3.7 If the Contractor does not respond promptly or disagrees with the method for adjustment in the Contract Sum, the Architect shall determine the method and the adjustment on the basis of reasonable expenditures and savings of those performing the Work attributable to the change, including, in case of an increase in the Contract Sum, an amount

for overhead and profit as set forth in the Agreement, or if no such amount is set forth in the Agreement, a reasonable amount. In such case, and also under Section 7.3.3.3, the Contractor shall keep and present, in such form as the Architect may prescribe, an itemized accounting together with appropriate supporting data. Unless otherwise provided in the Contract Documents, costs for the purposes of this Section 7.3.7 shall be limited to the following:

- .1 Costs of labor, including social security, old age and unemployment insurance, fringe benefits required by agreement or custom, and workers' compensation insurance;
- .2 Costs of materials, supplies and equipment, including cost of transportation, whether incorporated or consumed;
- .3 Rental costs of machinery and equipment, exclusive of hand tools, whether rented from the Contractor or others;
- .4 Costs of premiums for all bonds and insurance, permit fees, and sales, use or similar taxes related to the Work; and
- .5 Additional costs of supervision and field office personnel directly attributable to the change.

§ 7.3.8 The amount of credit to be allowed by the Contractor to the Owner for a deletion or change that results in a net decrease in the Contract Sum shall be actual net cost as confirmed by the Architect. When both additions and credits covering related Work or substitutions are involved in a change, the allowance for overhead and profit shall be figured on the basis of net increase, if any, with respect to that change.

§ 7.3.9 Pending final determination of the total cost of a Construction Change Directive to the Owner, the Contractor may request payment for Work completed under the Construction Change Directive in applications for Payment. The Architect will make an interim determination for purposes of monthly certification for payment for those costs and certify for payment the amount that the Architect determines, in the Architect's professional judgment, to be reasonably justified. The Architect's interim determination of cost shall adjust the Contract Sum on the same basis as a Change Order, subject to the right of either party to disagree and assert a Claim in accordance with Article 15.

§ 7.3.10 When the Owner and Contractor agree with a determination made by the Architect concerning the adjustments in the Contract Sum and Contract Time, or otherwise reach agreement upon the adjustments, such agreement shall be effective immediately and the Architect will prepare a Change Order. Change Orders may be issued for all or any part of a Construction Change Directive.

§ 7.4 MINOR CHANGES IN THE WORK

The Architect has authority to order minor changes in the Work not involving adjustment in the Contract Sum or extension of the Contract Time and not inconsistent with the intent of the Contract Documents. Such changes will be effected by written order signed by the Architect and shall be binding on the Owner and Contractor.

ARTICLE 8 TIME

§ 8.1 DEFINITIONS

§ 8.1.1 Unless otherwise provided, Contract Time is the period of time, including authorized adjustments, allotted in the Contract Documents for Substantial Completion of the Work.

§ 8.1.2 The date of commencement of the Work is the date established in the Agreement.

§ 8.1.3 The date of Substantial Completion is the date certified by the Architect in accordance with Section 9.8.

§ 8.1.4 The term "day" as used in the Contract Documents shall mean calendar day unless otherwise specifically defined.

§ 8.2 PROGRESS AND COMPLETION

§ 8.2.1 Time limits stated in the Contract Documents are of the essence of the Contract. By executing the Agreement the Contractor confirms that the Contract Time is a reasonable period for performing the Work.

§ 8.2.2 The Contractor shall not knowingly, except by agreement or instruction of the Owner in writing, prematurely commence operations on the site or elsewhere prior to the effective date of insurance required by Article 11 to be furnished by the Contractor and Owner. The date of commencement of the Work shall not be changed by the effective date of such insurance.

§ 8.2.3 The Contractor shall proceed expeditiously with adequate forces and shall achieve Substantial Completion within the Contract Time.

§ 8.3 DELAYS AND EXTENSIONS OF TIME

§ 8.3.1 If the Contractor is delayed at any time in the commencement or progress of the Work by an act or neglect of the Owner or Architect, or of an employee of either, or of a separate contractor employed by the Owner; or by changes ordered in the Work; or by labor disputes, fire, unusual delay in deliveries, unavoidable casualties or other causes beyond the Contractor's control; or by delay authorized by the Owner pending mediation and arbitration; or by other causes that the Architect determines may justify delay, then the Contract Time shall be extended by Change Order for such reasonable time as the Architect may determine.

§ 8.3.2 Claims relating to time shall be made in accordance with applicable provisions of Article 15.

§ 8.3.3 This Section 8.3 does not preclude recovery of damages for delay by either party under other provisions of the Contract Documents.

ARTICLE 9 PAYMENTS AND COMPLETION

§ 9.1 CONTRACT SUM

The Contract Sum is stated in the Agreement and, including authorized adjustments, is the total amount payable by the Owner to the Contractor for performance of the Work under the Contract Documents.

§ 9.2 SCHEDULE OF VALUES

Where the Contract is based on a stipulated sum or Guaranteed Maximum Price, the Contractor shall submit to the Architect, before the first Application for Payment, a schedule of values allocating the entire Contract Sum to the various portions of the Work and prepared in such form and supported by such data to substantiate its accuracy as the Architect may require. This schedule, unless objected to by the Architect, shall be used as a basis for reviewing the Contractor's Applications for Payment.

§ 9.3 APPLICATIONS FOR PAYMENT

§ 9.3.1 At least ten days before the date established for each progress payment, the Contractor shall submit to the Architect an itemized Application for Payment prepared in accordance with the schedule of values, if required under Section 9.2, for completed portions of the Work. Such application shall be notarized, if required, and supported by such data substantiating the Contractor's right to payment as the Owner or Architect may require, such as copies of requisitions from Subcontractors and material suppliers, and shall reflect retainage if provided for in the Contract Documents.

§ 9.3.1.1 As provided in Section 7.3.9, such applications may include requests for payment on account of changes in the Work that have been properly authorized by Construction Change Directives, or by interim determinations of the Architect, but not yet included in Change Orders.

§ 9.3.1.2 Applications for Payment shall not include requests for payment for portions of the Work for which the Contractor does not intend to pay a Subcontractor or material supplier, unless such Work has been performed by others whom the Contractor intends to pay.

§ 9.3.2 Unless otherwise provided in the Contract Documents, payments shall be made on account of materials and equipment delivered and suitably stored at the site for subsequent incorporation in the Work. If approved in advance by the Owner, payment may similarly be made for materials and equipment suitably stored off the site at a location agreed upon in writing. Payment for materials and equipment stored on or off the site shall be conditioned upon compliance by the Contractor with procedures satisfactory to the Owner to establish the Owner's title to such materials and equipment or otherwise protect the Owner's interest, and shall include the costs of applicable insurance, storage and transportation to the site for such materials and equipment stored off the site.

§ 9.3.3 The Contractor warrants that title to all Work covered by an Application for Payment will pass to the Owner no later than the time of payment. The Contractor further warrants that upon submittal of an Application for Payment all Work for which Certificates for Payment have been previously issued and payments received from the Owner shall, to the best of the Contractor's knowledge, information and belief, be free and clear of liens, claims, security interests or

encumbrances in favor of the Contractor, Subcontractors, material suppliers, or other persons or entities making a claim by reason of having provided labor, materials and equipment relating to the Work.

§ 9.4 CERTIFICATES FOR PAYMENT

§ 9.4.1 The Architect will, within seven days after receipt of the Contractor's Application for Payment, either issue to the Owner a Certificate for Payment, with a copy to the Contractor, for such amount as the Architect determines is properly due, or notify the Contractor and Owner in writing of the Architect's reasons for withholding certification in whole or in part as provided in Section 9.5.1.

§ 9.4.2 The issuance of a Certificate for Payment will constitute a representation by the Architect to the Owner based on the Architect's evaluation of the Work and the data comprising the Application for Payment, that, to the best of the Architect's knowledge, information and belief, the Work has progressed to the point indicated and that the quality of the Work is in accordance with the Contract Documents. The foregoing representations are subject to an evaluation of the Work for conformance with the Contract Documents upon Substantial Completion, to results of subsequent tests and inspections, to correction of minor deviations from the Contract Documents prior to completion and to specific qualifications expressed by the Architect. The issuance of a Certificate for Payment will further constitute a representation that the Contractor is entitled to payment in the amount certified. However, the issuance of a Certificate for Payment will not be a representation that the Architect has (1) made exhaustive or continuous on-site inspections to check the quality or quantity of the Work, (2) reviewed construction means, methods, techniques, sequences or procedures, (3) reviewed copies of requisitions received from Subcontractors and material suppliers and other data requested by the Owner to substantiate the Contractor's right to payment, or (4) made examination to ascertain how or for what purpose the Contractor has used money previously paid on account of the Contract Sum.

§ 9.5 DECISIONS TO WITHHOLD CERTIFICATION

§ 9.5.1 The Architect may withhold a Certificate for Payment in whole or in part, to the extent reasonably necessary to protect the Owner, if in the Architect's opinion the representations to the Owner required by Section 9.4.2 cannot be made. If the Architect is unable to certify payment in the amount of the Application, the Architect will notify the Contractor and Owner as provided in Section 9.4.1. If the Contractor and Architect cannot agree on a revised amount, the Architect will promptly issue a Certificate for Payment for the amount for which the Architect is able to make such representations to the Owner. The Architect may also withhold a Certificate for Payment or, because of subsequently discovered evidence, may nullify the whole or a part of a Certificate for Payment previously issued, to such extent as may be necessary in the Architect's opinion to protect the Owner from loss for which the Contractor is responsible, including loss resulting from acts and omissions described in Section 3.3.2, because of

- .1 defective Work not remedied;
- .2 third party claims filed or reasonable evidence indicating probable filing of such claims unless security acceptable to the Owner is provided by the Contractor;
- .3 failure of the Contractor to make payments properly to Subcontractors or for labor, materials or equipment;
- .4 reasonable evidence that the Work cannot be completed for the unpaid balance of the Contract Sum;
- .5 damage to the Owner or a separate contractor;
- .6 reasonable evidence that the Work will not be completed within the Contract Time, and that the unpaid balance would not be adequate to cover actual or liquidated damages for the anticipated delay; or
- .7 repeated failure to carry out the Work in accordance with the Contract Documents.

§ 9.5.2 When the above reasons for withholding certification are removed, certification will be made for amounts previously withheld.

§ 9.5.3 If the Architect withholds certification for payment under Section 9.5.1.3, the Owner may, at its sole option, issue joint checks to the Contractor and to any Subcontractor or material or equipment suppliers to whom the Contractor failed to make payment for Work properly performed or material or equipment suitably delivered. If the Owner makes payments by joint check, the Owner shall notify the Architect and the Architect will reflect such payment on the next Certificate for Payment.

§ 9.6 PROGRESS PAYMENTS

§ 9.6.1 After the Architect has issued a Certificate for Payment, the Owner shall make payment in the manner and within the time provided in the Contract Documents, and shall so notify the Architect.

§ 9.6.2 The Contractor shall pay each Subcontractor no later than seven days after receipt of payment from the Owner the amount to which the Subcontractor is entitled, reflecting percentages actually retained from payments to the Contractor on account of the Subcontractor's portion of the Work. The Contractor shall, by appropriate agreement with each Subcontractor, require each Subcontractor to make payments to Sub-subcontractors in a similar manner.

§ 9.6.3 The Architect will, on request, furnish to a Subcontractor, if practicable, information regarding percentages of completion or amounts applied for by the Contractor and action taken thereon by the Architect and Owner on account of portions of the Work done by such Subcontractor.

§ 9.6.4 The Owner has the right to request written evidence from the Contractor that the Contractor has properly paid Subcontractors and material and equipment suppliers amounts paid by the Owner to the Contractor for subcontracted Work. If the Contractor fails to furnish such evidence within seven days, the Owner shall have the right to contact Subcontractors to ascertain whether they have been properly paid. Neither the Owner nor Architect shall have an obligation to pay or to see to the payment of money to a Subcontractor, except as may otherwise be required by law.

§ 9.6.5 Contractor payments to material and equipment suppliers shall be treated in a manner similar to that provided in Sections 9.6.2, 9.6.3 and 9.6.4.

§ 9.6.6 A Certificate for Payment, a progress payment, or partial or entire use or occupancy of the Project by the Owner shall not constitute acceptance of Work not in accordance with the Contract Documents.

§ 9.6.7 Unless the Contractor provides the Owner with a payment bond in the full total sum of the Contract Sum, payments received by the Contractor for Work properly performed by Subcontractors and suppliers shall be held by the Contractor for those Subcontractors or suppliers who performed Work or furnished materials, or both, under contract with the Contractor for which payment was made by the Owner. Nothing contained herein shall require money to be placed in a separate account and not commingled with money of the Contractor, shall create any fiduciary liability or tort liability on the part of the Contractor for breach of trust or shall entitle any person or entity to an award of punitive damages against the Contractor for breach of the requirements of this provision.

§ 9.7 FAILURE OF PAYMENT

If the Architect does not issue a Certificate for Payment, through no fault of the Contractor, within seven days after receipt of the Contractor's Application for Payment, or if the Owner does not pay the Contractor within seven days after the date established in the Contract Documents the amount certified by the Architect or awarded by binding dispute resolution, then the Contractor may, upon seven additional days' written notice to the Owner and Architect, stop the Work until payment of the amount owing has been received. The Contract Time shall be extended appropriately and the Contract Sum shall be increased by the amount of the Contractor's reasonable costs of shut-down, delay and start-up, plus interest as provided for in the Contract Documents.

§ 9.8 SUBSTANTIAL COMPLETION

§ 9.8.1 Substantial Completion is the stage in the progress of the Work when the Work or designated portion thereof is sufficiently complete in accordance with the Contract Documents so that the Owner can occupy or utilize the Work for its intended use.

§ 9.8.2 When the Contractor considers that the Work, or a portion thereof which the Owner agrees to accept separately, is substantially complete, the Contractor shall prepare and submit to the Architect a comprehensive list of items to be completed or corrected prior to final payment. Failure to include an item on such list does not alter the responsibility of the Contractor to complete all Work in accordance with the Contract Documents.

§ 9.8.3 Upon receipt of the Contractor's list, the Architect will make an inspection to determine whether the Work or designated portion thereof is substantially complete. If the Architect's inspection discloses any item, whether or not included on the Contractor's list, which is not sufficiently complete in accordance with the Contract Documents so that the Owner can occupy or utilize the Work or designated portion thereof for its intended use, the Contractor shall, before issuance of the Certificate of Substantial Completion, complete or correct such item upon notification by the Architect. In such case, the Contractor shall then submit a request for another inspection by the Architect to determine Substantial Completion.

§ 9.8.4 When the Work or designated portion thereof is substantially complete, the Architect will prepare a Certificate of Substantial Completion that shall establish the date of Substantial Completion, shall establish responsibilities of the Owner and Contractor for security, maintenance, heat, utilities, damage to the Work and insurance, and shall fix the time within which the Contractor shall finish all items on the list accompanying the Certificate. Warranties required by the Contract Documents shall commence on the date of Substantial Completion of the Work or designated portion thereof unless otherwise provided in the Certificate of Substantial Completion.

§ 9.8.5 The Certificate of Substantial Completion shall be submitted to the Owner and Contractor for their written acceptance of responsibilities assigned to them in such Certificate. Upon such acceptance and consent of surety, if any, the Owner shall make payment of retainage applying to such Work or designated portion thereof. Such payment shall be adjusted for Work that is incomplete or not in accordance with the requirements of the Contract Documents.

§ 9.9 PARTIAL OCCUPANCY OR USE

§ 9.9.1 The Owner may occupy or use any completed or partially completed portion of the Work at any stage when such portion is designated by separate agreement with the Contractor, provided such occupancy or use is consented to by the insurer as required under Section 11.3.1.5 and authorized by public authorities having jurisdiction over the Project. Such partial occupancy or use may commence whether or not the portion is substantially complete, provided the Owner and Contractor have accepted in writing the responsibilities assigned to each of them for payments, retainage, if any, security, maintenance, heat, utilities, damage to the Work and insurance, and have agreed in writing concerning the period for correction of the Work and commencement of warranties required by the Contract Documents. When the Contractor considers a portion substantially complete, the Contractor shall prepare and submit a list to the Architect as provided under Section 9.8.2. Consent of the Contractor to partial occupancy or use shall not be unreasonably withheld. The stage of the progress of the Work shall be determined by written agreement between the Owner and Contractor or, if no agreement is reached, by decision of the Architect.

§ 9.9.2 Immediately prior to such partial occupancy or use, the Owner, Contractor and Architect shall jointly inspect the area to be occupied or portion of the Work to be used in order to determine and record the condition of the Work.

§ 9.9.3 Unless otherwise agreed upon, partial occupancy or use of a portion or portions of the Work shall not constitute acceptance of Work not complying with the requirements of the Contract Documents.

§ 9.10 FINAL COMPLETION AND FINAL PAYMENT

§ 9.10.1 Upon receipt of the Contractor's written notice that the Work is ready for final inspection and acceptance and upon receipt of a final Application for Payment, the Architect will promptly make such inspection and, when the Architect finds the Work acceptable under the Contract Documents and the Contract fully performed, the Architect will promptly issue a final Certificate for Payment stating that to the best of the Architect's knowledge, information and belief, and on the basis of the Architect's on-site visits and inspections, the Work has been completed in accordance with terms and conditions of the Contract Documents and that the entire balance found to be due the Contractor and noted in the final Certificate is due and payable. The Architect's final Certificate for Payment will constitute a further representation that conditions listed in Section 9.10.2 as precedent to the Contractor's being entitled to final payment have been fulfilled.

§ 9.10.2 Neither final payment nor any remaining retained percentage shall become due until the Contractor submits to the Architect (1) an affidavit that payrolls, bills for materials and equipment, and other indebtedness connected with the Work for which the Owner or the Owner's property might be responsible or encumbered (less amounts withheld by Owner) have been paid or otherwise satisfied, (2) a certificate evidencing that insurance required by the Contract Documents to remain in force after final payment is currently in effect and will not be canceled or allowed to expire until at least 30 days' prior written notice has been given to the Owner, (3) a written statement that the Contractor knows of no substantial reason that the insurance will not be renewable to cover the period required by the Contract Documents, (4) consent of surety, if any, to final payment and (5), if required by the Owner, other data establishing payment or satisfaction of obligations, such as receipts, releases and waivers of liens, claims, security interests or encumbrances arising out of the Contract, to the extent and in such form as may be designated by the Owner. If a Subcontractor refuses to furnish a release or waiver required by the Owner, the Contractor may furnish a bond satisfactory to the Owner to indemnify the Owner against such lien. If such lien remains unsatisfied after payments are made, the Contractor shall refund to the Owner all money that the Owner may be compelled to pay in discharging such lien, including all costs and reasonable attorneys' fees.

§ 9.10.3 If, after Substantial Completion of the Work, final completion thereof is materially delayed through no fault of the Contractor or by issuance of Change Orders affecting final completion, and the Architect so confirms, the Owner shall, upon application by the Contractor and certification by the Architect, and without terminating the Contract, make payment of the balance due for that portion of the Work fully completed and accepted. If the remaining balance for Work not fully completed or corrected is less than retainage stipulated in the Contract Documents, and if bonds have been furnished, the written consent of surety to payment of the balance due for that portion of the Work fully completed and accepted shall be submitted by the Contractor to the Architect prior to certification of such payment. Such payment shall be made under terms and conditions governing final payment, except that it shall not constitute a waiver of claims.

§ 9.10.4 The making of final payment shall constitute a waiver of Claims by the Owner except those arising from:
.1 liens, Claims, security interests or encumbrances arising out of the Contract and unsettled
.2 failure of the Work to comply with the requirements of the Contract Documents; or
.3 terms of special warranties required by the Contract Documents.

§ 9.10.5 Acceptance of final payment by the Contractor, a Subcontractor or material supplier shall constitute a waiver of claims by that payee except those previously made in writing and identified by that payee as unsettled at the time of final Application for Payment.

ARTICLE 10 PROTECTION OF PERSONS AND PROPERTY

§ 10.1 SAFETY PRECAUTIONS AND PROGRAMS

The Contractor shall be responsible for initiating, maintaining and supervising all safety precautions and programs in connection with the performance of the Contract.

§ 10.2 SAFETY OF PERSONS AND PROPERTY

§ 10.2.1 The Contractor shall take reasonable precautions for safety of, and shall provide reasonable protection to prevent damage, injury or loss to

- .1 employees on the Work and other persons who may be affected thereby;
- .2 the Work and materials and equipment to be incorporated therein, whether in storage on or off the site, under care, custody or control of the Contractor or the Contractor's Subcontractors or Sub-subcontractors; and
- .3 other property at the site or adjacent thereto, such as trees, shrubs, lawns, walks, pavements, roadways, structures and utilities not designated for removal, relocation or replacement in the course of construction.

§ 10.2.2 The Contractor shall comply with and give notices required by applicable laws, statutes, ordinances, codes, rules and regulations, and lawful orders of public authorities bearing on safety of persons or property or their protection from damage, injury or loss.

§ 10.2.3 The Contractor shall erect and maintain, as required by existing conditions and performance of the Contract, reasonable safeguards for safety and protection, including posting danger signs and other warnings against hazards, promulgating safety regulations and notifying owners and users of adjacent sites and utilities.

§ 10.2.4 When use or storage of explosives or other hazardous materials or equipment or unusual methods are necessary for execution of the Work, the Contractor shall exercise utmost care and carry on such activities under supervision of properly qualified personnel.

§ 10.2.5 The Contractor shall promptly remedy damage and loss (other than damage or loss insured under property insurance required by the Contract Documents) to property referred to in Sections 10.2.1.2 and 10.2.1.3 caused in whole or in part by the Contractor, a Subcontractor, a Sub-subcontractor, or anyone directly or indirectly employed by any of them, or by anyone for whose acts they may be liable and for which the Contractor is responsible under Sections 10.2.1.2 and 10.2.1.3, except damage or loss attributable to acts or omissions of the Owner or Architect or anyone directly or indirectly employed by either of them, or by anyone for whose acts either of them may be liable, and not attributable to the fault or negligence of the Contractor. The foregoing obligations of the Contractor are in addition to the Contractor's obligations under Section 3.18.

§ 10.2.6 The Contractor shall designate a responsible member of the Contractor's organization at the site whose duty shall be the prevention of accidents. This person shall be the Contractor's superintendent unless otherwise designated by the Contractor in writing to the Owner and Architect.

§ 10.2.7 The Contractor shall not permit any part of the construction or site to be loaded so as to cause damage or create an unsafe condition.

§ 10.2.8 INJURY OR DAMAGE TO PERSON OR PROPERTY

If either party suffers injury or damage to person or property because of an act or omission of the other party, or of others for whose acts such party is legally responsible, written notice of such injury or damage, whether or not insured, shall be given to the other party within a reasonable time not exceeding 21 days after discovery. The notice shall provide sufficient detail to enable the other party to investigate the matter.

§ 10.3 HAZARDOUS MATERIALS

§ 10.3.1 The Contractor is responsible for compliance with any requirements included in the Contract Documents regarding hazardous materials. If the Contractor encounters a hazardous material or substance not addressed in the Contract Documents and if reasonable precautions will be inadequate to prevent foreseeable bodily injury or death to persons resulting from a material or substance, including but not limited to asbestos or polychlorinated biphenyl (PCB), encountered on the site by the Contractor, the Contractor shall, upon recognizing the condition, immediately stop Work in the affected area and report the condition to the Owner and Architect in writing.

§ 10.3.2 Upon receipt of the Contractor's written notice, the Owner shall obtain the services of a licensed laboratory to verify the presence or absence of the material or substance reported by the Contractor and, in the event such material or substance is found to be present, to cause it to be rendered harmless. Unless otherwise required by the Contract Documents, the Owner shall furnish in writing to the Contractor and Architect the names and qualifications of persons or entities who are to perform tests verifying the presence or absence of such material or substance or who are to perform the task of removal or safe containment of such material or substance. The Contractor and the Architect will promptly reply to the Owner in writing stating whether or not either has reasonable objection to the persons or entities proposed by the Owner. If either the Contractor or Architect has an objection to a person or entity proposed by the Owner, the Owner shall propose another to whom the Contractor and the Architect have no reasonable objection. When the material or substance has been rendered harmless, Work in the affected area shall resume upon written agreement of the Owner and Contractor. By Change Order, the Contract Time shall be extended appropriately and the Contract Sum shall be increased in the amount of the Contractor's reasonable additional costs of shut-down, delay and start-up.

§ 10.3.3 To the fullest extent permitted by law, the Owner shall indemnify and hold harmless the Contractor, Subcontractors, Architect, Architect's consultants and agents and employees of any of them from and against claims, damages, losses and expenses, including but not limited to attorneys' fees, arising out of or resulting from performance of the Work in the affected area if in fact the material or substance presents the risk of bodily injury or death as described in Section 10.3.1 and has not been rendered harmless, provided that such claim, damage, loss or expense is attributable to bodily injury, sickness, disease or death, or to injury to or destruction of tangible property (other than the Work itself) except to the extent that such damage, loss or expense is due to the fault or negligence of the party seeking indemnity.

§ 10.3.4 The Owner shall not be responsible under this Section 10.3 for materials or substances the Contractor brings to the site unless such materials or substances are required by the Contract Documents. The Owner shall be responsible for materials or substances required by the Contract Documents, except to the extent of the Contractor's fault or negligence in the use and handling of such materials or substances.

§ 10.3.5 The Contractor shall indemnify the Owner for the cost and expense the Owner incurs (1) for remediation of a material or substance the Contractor brings to the site and negligently handles, or (2) where the Contractor fails to perform its obligations under Section 10.3.1, except to the extent that the cost and expense are due to the Owner's fault or negligence.

§ 10.3.6 If, without negligence on the part of the Contractor, the Contractor is held liable by a government agency for the cost of remediation of a hazardous material or substance solely by reason of performing Work as required by the Contract Documents, the Owner shall indemnify the Contractor for all cost and expense thereby incurred.

Init.

§ 10.4 EMERGENCIES

In an emergency affecting safety of persons or property, the Contractor shall act, at the Contractor's discretion, to prevent threatened damage, injury or loss. Additional compensation or extension of time claimed by the Contractor on account of an emergency shall be determined as provided in Article 15 and Article 7.

ARTICLE 11 INSURANCE AND BONDS

§ 11.1 CONTRACTOR'S LIABILITY INSURANCE

§ 11.1.1 The Contractor shall purchase from and maintain in a company or companies lawfully authorized to do business in the jurisdiction in which the Project is located such insurance as will protect the Contractor from claims set forth below which may arise out of or result from the Contractor's operations and completed operations under the Contract and for which the Contractor may be legally liable, whether such operations be by the Contractor or by a Subcontractor or by anyone directly or indirectly employed by any of them, or by anyone for whose acts any of them may be liable:

- .1 Claims under workers' compensation, disability benefit and other similar employee benefit acts that are applicable to the Work to be performed;
- .2 Claims for damages because of bodily injury, occupational sickness or disease, or death of the Contractor's employees;
- .3 Claims for damages because of bodily injury, sickness or disease, or death of any person other than the Contractor's employees;
- .4 Claims for damages insured by usual personal injury liability coverage;
- .5 Claims for damages, other than to the Work itself, because of injury to or destruction of tangible property, including loss of use resulting therefrom;
- .6 Claims for damages because of bodily injury, death of a person, or property damage arising out of ownership, maintenance or use of a motor vehicle;
- .7 Claims for bodily injury or property damage arising out of completed operations; and
- .8 Claims involving contractual liability insurance applicable to the Contractor's obligations under Section 3.18.

§ 11.1.2 The insurance required by Section 11.1.1 shall be written for not less than limits of liability specified in the Contract Documents or required by law, whichever coverage is greater. Coverages, whether written on an occurrence or claims-made basis, shall be maintained without interruption from the date of commencement of the Work until the date of final payment and termination of any coverage required to be maintained after final payment, and, with respect to the Contractor's completed operations coverage until the expiration of the period for correction of Work or for such other period for maintenance of completed operations coverage as specified in the Contract Documents.

§ 11.1.3 Certificates of insurance acceptable to the Owner shall be filed with the Owner prior to commencement of the Work and thereafter upon renewal or replacement of each required policy of insurance. These certificates and the insurance policies required by this Section 11.1 shall contain a provision that coverages afforded under the policies will not be canceled or allowed to expire until at least 30 days' prior written notice has been given to the Owner. An additional certificate evidencing continuation of liability coverage, including coverage for completed operations, shall be submitted with the final application for Payment as required by Section 9.10.2 and thereafter upon renewal or replacement of such coverage until the expiration of the time required by Section 11.1.2. Information concerning reduction of coverage on account of revised limits or claims paid under the General Aggregate, or both, shall be furnished by the Contractor with reasonable promptness.

§ 11.1.4 The Contractor shall cause the commercial liability coverage required by the Contract Documents to include (1) the Owner, the Architect and the Architect's consultants as additional insureds for claims caused in whole or in part by the Contractor's negligent acts or omissions during the Contractor's operations; and (2) the Owner as an additional insured for claims caused in whole or in part by the Contractor's negligent acts or omissions during the Contractor's completed operations.

§ 11.2 OWNER'S LIABILITY INSURANCE

The Owner shall be responsible for purchasing and maintaining the Owner's usual liability insurance.

§ 11.3 PROPERTY INSURANCE

§ 11.3.1 Unless otherwise provided, the Owner shall purchase and maintain, in a company or companies lawfully authorized to do business in the jurisdiction in which the Project is located, property insurance written on a builder's risk "all-risk" or equivalent policy form in the amount of the initial Contract Sum, plus value of subsequent Contract Modifications and cost of materials supplied or installed by others, comprising total value for the entire Project at the site on a replacement cost basis without optional deductibles. Such property insurance shall be maintained, unless otherwise provided in the Contract Documents or otherwise agreed in writing by all persons and entities who are beneficiaries of such insurance, until final payment has been made as provided in Section 9.10 or until no person or entity other than the Owner has an insurable interest in the property required by this Section 11.3 to be covered whichever is later. This insurance shall include interests of the Owner, the Contractor, Subcontractors and Sub-subcontractors in the Project.

§ 11.3.1.1 Property insurance shall be on an "all-risk" or equivalent policy form and shall include, without limitation, insurance against the perils of fire (with extended coverage) and physical loss or damage including, without duplication of coverage, theft, vandalism, malicious mischief, collapse, earthquake, flood, windstorm, falsework, testing and startup, temporary buildings and debris removal including demolition occasioned by enforcement of any applicable legal requirements, and shall cover reasonable compensation for Architect's and Contractor's services and expenses required as a result of such insured loss.

§ 11.3.1.2 If the Owner does not intend to purchase such property insurance required by the Contract and with all of the coverages in the amount described above, the Owner shall so inform the Contractor in writing prior to commencement of the Work. The Contractor may then effect insurance that will protect the interests of the Contractor, Subcontractors and Sub-subcontractors in the Work, and by appropriate Change Order the cost thereof shall be charged to the Owner. If the Contractor is damaged by the failure or neglect of the Owner to purchase or maintain insurance as described above, without so notifying the Contractor in writing, then the Owner shall bear all reasonable costs properly attributable thereto.

§ 11.3.1.3 If the property insurance requires deductibles, the Owner shall pay costs not covered because of such deductibles.

§ 11.3.1.4 This property insurance shall cover portions of the Work stored off the site, and also portions of the Work in transit.

§ 11.3.1.5 Partial occupancy or use in accordance with Section 9.9 shall not commence until the insurance company or companies providing property insurance have consented to such partial occupancy or use by endorsement or otherwise. The Owner and the Contractor shall take reasonable steps to obtain consent of the insurance company or companies and shall, without mutual written consent, take no action with respect to partial occupancy or use that would cause cancellation, lapse or reduction of insurance.

§ 11.3.2 BOILER AND MACHINERY INSURANCE

The Owner shall purchase and maintain boiler and machinery insurance required by the Contract Documents or by law, which shall specifically cover such insured objects during installation and until final acceptance by the Owner; this insurance shall include interests of the Owner, Contractor, Subcontractors and Sub-subcontractors in the Work, and the Owner and Contractor shall be named insureds.

§ 11.3.3 LOSS OF USE INSURANCE

The Owner, at the Owner's option, may purchase and maintain such insurance as will insure the Owner against loss of use of the Owner's property due to fire or other hazards, however caused. The Owner waives all rights of action against the Contractor for loss of use of the Owner's property, including consequential losses due to fire or other hazards however caused.

§ 11.3.4 If the Contractor requests in writing that insurance for risks other than those described herein or other special causes of loss be included in the property insurance policy, the Owner shall, if possible, include such insurance, and the cost thereof shall be charged to the Contractor by appropriate Change Order.

§ 11.3.5 If during the Project construction period the Owner insures properties, real or personal or both, at or adjacent to the site by property insurance under policies separate from those insuring the Project, or if after final payment

property insurance is to be provided on the completed Project through a policy or policies other than those insuring the Project during the construction period, the Owner shall waive all rights in accordance with the terms of Section 11.3.7 for damages caused by fire or other causes of loss covered by this separate property insurance. All separate policies shall provide this waiver of subrogation by endorsement or otherwise.

§ 11.3.6 Before an exposure to loss may occur, the Owner shall file with the Contractor a copy of each policy that includes insurance coverages required by this Section 11.3. Each policy shall contain all generally applicable conditions, definitions, exclusions and endorsements related to this Project. Each policy shall contain a provision that the policy will not be canceled or allowed to expire, and that its limits will not be reduced, until at least 30 days' prior written notice has been given to the Contractor.

§ 11.3.7 WAIVERS OF SUBROGATION

The Owner and Contractor waive all rights against (1) each other and any of their subcontractors, sub-subcontractors, agents and employees, each of the other, and (2) the Architect, Architect's consultants, separate contractors described in Article 6, if any, and any of their subcontractors, sub-subcontractors, agents and employees, for damages caused by fire or other causes of loss to the extent covered by property insurance obtained pursuant to this Section 11.3 or other property insurance applicable to the Work, except such rights as they have to proceeds of such insurance held by the Owner as fiduciary. The Owner or Contractor, as appropriate, shall require of the Architect, Architect's consultants, separate contractors described in Article 6, if any, and the subcontractors, sub-subcontractors, agents and employees of any of them, by appropriate agreements, written where legally required for validity, similar waivers each in favor of other parties enumerated herein. The policies shall provide such waivers of subrogation by endorsement or otherwise. A waiver of subrogation shall be effective as to a person or entity even though that person or entity would otherwise have a duty of indemnification, contractual or otherwise, did not pay the insurance premium directly or indirectly, and whether or not the person or entity had an insurable interest in the property damaged.

§ 11.3.8 A loss insured under the Owner's property insurance shall be adjusted by the Owner as fiduciary and made payable to the Owner as fiduciary for the insureds, as their interests may appear, subject to requirements of any applicable mortgagee clause and of Section 11.3.10. The Contractor shall pay Subcontractors their just shares of insurance proceeds received by the Contractor, and by appropriate agreements, written where legally required for validity, shall require Subcontractors to make payments to their Sub-subcontractors in similar manner.

§ 11.3.9 If required in writing by a party in interest, the Owner as fiduciary shall, upon occurrence of an insured loss, give bond for proper performance of the Owner's duties. The cost of required bonds shall be charged against proceeds received as fiduciary. The Owner shall deposit in a separate account proceeds so received, which the Owner shall distribute in accordance with such agreement as the parties in interest may reach, or as determined in accordance with the method of binding dispute resolution selected in the Agreement between the Owner and Contractor. If after such loss no other special agreement is made, and unless the Owner terminates the Contract for convenience, replacement of damaged property shall be performed by the Contractor after notification of a Change in the Work in accordance with Article 7.

§ 11.3.10 The Owner as fiduciary shall have power to adjust and settle a loss with insurers unless one of the parties in interest shall object in writing within five days after occurrence of loss to the Owner's exercise of this power; if such objection is made, the dispute shall be resolved in the manner selected by the Owner and Contractor as the method of binding dispute resolution in the Agreement. If the Owner and Contractor have selected arbitration as the method of binding dispute resolution, the Owner as fiduciary shall make settlement with insurers or, in the case of a dispute over distribution of insurance proceeds, in accordance with the directions of the arbitrators.

§ 11.4 PERFORMANCE BOND AND PAYMENT BOND

§ 11.4.1 The Owner shall have the right to require the Contractor to furnish bonds covering faithful performance of the Contract and payment of obligations arising thereunder as stipulated in bidding requirements or specifically required in the Contract Documents on the date of execution of the Contract.

§ 11.4.2 Upon the request of any person or entity appearing to be a potential beneficiary of bonds covering payment of obligations arising under the Contract, the Contractor shall promptly furnish a copy of the bonds or shall authorize a copy to be furnished.

ARTICLE 12 UNCOVERING AND CORRECTION OF WORK

§ 12.1 UNCOVERING OF WORK

§ 12.1.1 If a portion of the Work is covered contrary to the Architect's request or to requirements specifically expressed in the Contract Documents, it must, if requested in writing by the Architect, be uncovered for the Architect's examination and be replaced at the Contractor's expense without change in the Contract Time.

§ 12.1.2 If a portion of the Work has been covered that the Architect has not specifically requested to examine prior to its being covered, the Architect may request to see such Work and it shall be uncovered by the Contractor. If such Work is in accordance with the Contract Documents, costs of uncovering and replacement shall, by appropriate Change Order, be at the Owner's expense. If such Work is not in accordance with the Contract Documents, such costs and the cost of correction shall be at the Contractor's expense unless the condition was caused by the Owner or separate contractor in which event the Owner shall be responsible for payment of such costs.

§ 12.2 CORRECTION OF WORK

§ 12.2.1 BEFORE OR AFTER SUBSTANTIAL COMPLETION

The Contractor shall promptly correct Work rejected by the Architect or failing to conform to the requirements of the Contract Documents, whether discovered before or after Substantial Completion and whether or not fabricated, installed or completed. Costs of correcting such rejected Work, including additional testing and inspections, the cost of uncovering and replacement, and compensation for the Architect's services and expenses made necessary thereby, shall be at the Contractor's expense.

§ 12.2.2 AFTER SUBSTANTIAL COMPLETION

§ 12.2.2.1 In addition to the Contractor's obligations under Section 3.5, if, within one year after the date of Substantial Completion of the Work or designated portion thereof or after the date for commencement of warranties established under Section 9.9.1, or by terms of an applicable special warranty required by the Contract Documents, any of the Work is found to be not in accordance with the requirements of the Contract Documents, the Contractor shall correct it promptly after receipt of written notice from the Owner to do so unless the Owner has previously given the Contractor a written acceptance of such condition. The Owner shall give such notice promptly after discovery of the condition. During the one-year period for correction of Work, if the Owner fails to notify the Contractor and give the Contractor an opportunity to make the correction, the Owner waives the rights to require correction by the Contractor and to make a claim for breach of warranty. If the Contractor fails to correct nonconforming Work within a reasonable time during that period after receipt of notice from the Owner or Architect, the Owner may correct it in accordance with Section 2.4.

§ 12.2.2.2 The one-year period for correction of Work shall be extended with respect to portions of Work first performed after Substantial Completion by the period of time between Substantial Completion and the actual completion of that portion of the Work.

§ 12.2.2.3 The one-year period for correction of Work shall not be extended by corrective Work performed by the Contractor pursuant to this Section 12.2.

§ 12.2.3 The Contractor shall remove from the site portions of the Work that are not in accordance with the requirements of the Contract Documents and are neither corrected by the Contractor nor accepted by the Owner.

§ 12.2.4 The Contractor shall bear the cost of correcting destroyed or damaged construction, whether completed or partially completed, of the Owner or separate contractors caused by the Contractor's correction or removal of Work that is not in accordance with the requirements of the Contract Documents.

§ 12.2.5 Nothing contained in this Section 12.2 shall be construed to establish a period of limitation with respect to other obligations the Contractor has under the Contract Documents. Establishment of the one-year period for correction of Work as described in Section 12.2.2 relates only to the specific obligation of the Contractor to correct the Work, and has no relationship to the time within which the obligation to comply with the Contract Documents may be sought to be enforced, nor to the time within which proceedings may be commenced to establish the Contractor's liability with respect to the Contractor's obligations other than specifically to correct the Work.

§ 12.3 ACCEPTANCE OF NONCONFORMING WORK

If the Owner prefers to accept Work that is not in accordance with the requirements of the Contract Documents, the Owner may do so instead of requiring its removal and correction, in which case the Contract Sum will be reduced as appropriate and equitable. Such adjustment shall be effected whether or not final payment has been made.

ARTICLE 13 MISCELLANEOUS PROVISIONS

§ 13.1 GOVERNING LAW

The Contract shall be governed by the law of the place where the Project is located except that, if the parties have selected arbitration as the method of binding dispute resolution, the Federal Arbitration Act shall govern Section 15.4.

§ 13.2 SUCCESSORS AND ASSIGNS

§ 13.2.1 The Owner and Contractor respectively bind themselves, their partners, successors, assigns and legal representatives to covenants, agreements and obligations contained in the Contract Documents. Except as provided in Section 13.2.2, neither party to the Contract shall assign the Contract as a whole without written consent of the other. If either party attempts to make such an assignment without such consent, that party shall nevertheless remain legally responsible for all obligations under the Contract.

§ 13.2.2 The Owner may, without consent of the Contractor, assign the Contract to a lender providing construction financing for the Project, if the lender assumes the Owner's rights and obligations under the Contract Documents. The Contractor shall execute all consents reasonably required to facilitate such assignment.

§ 13.3 WRITTEN NOTICE

Written notice shall be deemed to have been duly served if delivered in person to the individual, to a member of the firm or entity, or to an officer of the corporation for which it was intended; or if delivered at, or sent by registered or certified mail or by courier service providing proof of delivery to, the last business address known to the party giving notice.

§ 13.4 RIGHTS AND REMEDIES

§ 13.4.1 Duties and obligations imposed by the Contract Documents and rights and remedies available thereunder shall be in addition to and not a limitation of duties, obligations, rights and remedies otherwise imposed or available by law.

§ 13.4.2 No action or failure to act by the Owner, Architect or Contractor shall constitute a waiver of a right or duty afforded them under the Contract, nor shall such action or failure to act constitute approval of or acquiescence in a breach there under, except as may be specifically agreed in writing.

§ 13.5 TESTS AND INSPECTIONS

§ 13.5.1 Tests, inspections and approvals of portions of the Work shall be made as required by the Contract Documents and by applicable laws, statutes, ordinances, codes, rules and regulations or lawful orders of public authorities. Unless otherwise provided, the Contractor shall make arrangements for such tests, inspections and approvals with an independent testing laboratory or entity acceptable to the Owner, or with the appropriate public authority, and shall bear all related costs of tests, inspections and approvals. The Contractor shall give the Architect timely notice of when and where tests and inspections are to be made so that the Architect may be present for such procedures. The Owner shall bear costs of (1) tests, inspections or approvals that do not become requirements until after bids are received or negotiations concluded, and (2) tests, inspections or approvals where building codes or applicable laws or regulations prohibit the Owner from delegating their cost to the Contractor.

§ 13.5.2 If the Architect, Owner or public authorities having jurisdiction determine that portions of the Work require additional testing, inspection or approval not included under Section 13.5.1, the Architect will, upon written authorization from the Owner, instruct the Contractor to make arrangements for such additional testing, inspection or approval by an entity acceptable to the Owner, and the Contractor shall give timely notice to the Architect of when and where tests and inspections are to be made so that the Architect may be present for such procedures. Such costs, except as provided in Section 13.5.3, shall be at the Owner's expense.

§ 13.5.3 If such procedures for testing, inspection or approval under Sections 13.5.1 and 13.5.2 reveal failure of the portions of the Work to comply with requirements established by the Contract Documents, all costs made necessary by

such failure including those of repeated procedures and compensation for the Architect's services and expenses shall be at the Contractor's expense.

§ 13.5.4 Required certificates of testing, inspection or approval shall, unless otherwise required by the Contract Documents, be secured by the Contractor and promptly delivered to the Architect.

§ 13.5.5 If the Architect is to observe tests, inspections or approvals required by the Contract Documents, the Architect will do so promptly and, where practicable, at the normal place of testing.

§ 13.5.6 Tests or inspections conducted pursuant to the Contract Documents shall be made promptly to avoid unreasonable delay in the Work.

§ 13.6 INTEREST

Payments due and unpaid under the Contract Documents shall bear interest from the date payment is due at such rate as the parties may agree upon in writing or, in the absence thereof, at the legal rate prevailing from time to time at the place where the Project is located.

§ 13.7 TIME LIMITS ON CLAIMS

The Owner and Contractor shall commence all claims and causes of action, whether in contract, tort, breach of warranty or otherwise, against the other arising out of or related to the Contract in accordance with the requirements of the final dispute resolution method selected in the Agreement within the time period specified by applicable law, but in any case not more than 10 years after the date of Substantial Completion of the Work. The Owner and Contractor waive all claims and causes of action not commenced in accordance with this Section 13.7.

ARTICLE 14 TERMINATION OR SUSPENSION OF THE CONTRACT

§ 14.1 TERMINATION BY THE CONTRACTOR

§ 14.1.1 The Contractor may terminate the Contract if the Work is stopped for a period of 30 consecutive days through no act or fault of the Contractor or a Subcontractor, Sub-subcontractor or their agents or employees or any other persons or entities performing portions of the Work under direct or indirect contract with the Contractor, for any of the following reasons:

- .1 Issuance of an order of a court or other public authority having jurisdiction that requires all Work to be stopped;
- .2 An act of government, such as a declaration of national emergency that requires all Work to be stopped;
- .3 Because the Architect has not issued a Certificate for Payment and has not notified the Contractor of the reason for withholding certification as provided in Section 9.4.1, or because the Owner has not made payment on a Certificate for Payment within the time stated in the Contract Documents; or
- .4 The Owner has failed to furnish to the Contractor promptly, upon the Contractor's request, reasonable evidence as required by Section 2.2.1.

§ 14.1.2 The Contractor may terminate the Contract if, through no act or fault of the Contractor or a Subcontractor, Sub-subcontractor or their agents or employees or any other persons or entities performing portions of the Work under direct or indirect contract with the Contractor, repeated suspensions, delays or interruptions of the entire Work by the Owner as described in Section 14.3 constitute in the aggregate more than 100 percent of the total number of days scheduled for completion, or 120 days in any 365-day period, whichever is less.

§ 14.1.3 If one of the reasons described in Section 14.1.1 or 14.1.2 exists, the Contractor may, upon seven days' written notice to the Owner and Architect, terminate the Contract and recover from the Owner payment for Work executed including reasonable overhead and profit, costs incurred by reason of such termination, and damages.

§ 14.1.4 If the Work is stopped for a period of 60 consecutive days through no act or fault of the Contractor or a Subcontractor or their agents or employees or any other persons performing portions of the Work under contract with the Contractor because the Owner has repeatedly failed to fulfill the Owner's obligations under the Contract Documents with respect to matters important to the progress of the Work, the Contractor may, upon seven additional days' written notice to the Owner and the Architect, terminate the Contract and recover from the Owner as provided in Section 14.1.3.

§ 14.2 TERMINATION BY THE OWNER FOR CAUSE

§ 14.2.1 The Owner may terminate the Contract if the Contractor

- .1 repeatedly refuses or fails to supply enough properly skilled workers or proper materials;
- .2 fails to make payment to Subcontractors for materials or labor in accordance with the respective agreements between the Contractor and the Subcontractors;
- .3 repeatedly disregards applicable laws, statutes, ordinances, codes, rules and regulations, or lawful orders of a public authority; or
- .4 otherwise is guilty of substantial breach of a provision of the Contract Documents.

§ 14.2.2 When any of the above reasons exist, the Owner, upon certification by the Initial Decision Maker that sufficient cause exists to justify such action, may without prejudice to any other rights or remedies of the Owner and after giving the Contractor and the Contractor's surety, if any, seven days' written notice, terminate employment of the Contractor and may, subject to any prior rights of the surety:

- .1 Exclude the Contractor from the site and take possession of all materials, equipment, tools, and construction equipment and machinery thereon owned by the Contractor;
- .2 Accept assignment of subcontracts pursuant to Section 5.4; and
- .3 Finish the Work by whatever reasonable method the Owner may deem expedient. Upon written request of the Contractor, the Owner shall furnish to the Contractor a detailed accounting of the costs incurred by the Owner in finishing the Work.

§ 14.2.3 When the Owner terminates the Contract for one of the reasons stated in Section 14.2.1, the Contractor shall not be entitled to receive further payment until the Work is finished.

§ 14.2.4 If the unpaid balance of the Contract Sum exceeds costs of finishing the Work, including compensation for the Architect's services and expenses made necessary thereby, and other damages incurred by the Owner and not expressly waived, such excess shall be paid to the Contractor. If such costs and damages exceed the unpaid balance, the Contractor shall pay the difference to the Owner. The amount to be paid to the Contractor or Owner, as the case may be, shall be certified by the Initial Decision Maker, upon application, and this obligation for payment shall survive termination of the Contract.

§ 14.3 SUSPENSION BY THE OWNER FOR CONVENIENCE

§ 14.3.1 The Owner may, without cause, order the Contractor in writing to suspend, delay or interrupt the Work in whole or in part for such period of time as the Owner may determine.

§ 14.3.2 The Contract Sum and Contract Time shall be adjusted for increases in the cost and time caused by suspension, delay or interruption as described in Section 14.3.1. Adjustment of the Contract Sum shall include profit. No adjustment shall be made to the extent:

- .1 that performance was, or would have been so suspended, delayed or interrupted by another cause for which the Contractor is responsible; or
- .2 that an equitable adjustment is made or denied under another provision of the Contract.

§ 14.4 TERMINATION BY THE OWNER FOR CONVENIENCE

§ 14.4.1 The Owner may, at any time, terminate the Contract for the Owner's convenience and without cause.

§ 14.4.2 Upon receipt of written notice from the Owner of such termination for the Owner's convenience, the Contractor shall

- .1 cease operations as directed by the Owner in the notice;
- .2 take actions necessary, or that the Owner may direct, for the protection and preservation of the Work; and
- .3 except for Work directed to be performed prior to the effective date of termination stated in the notice, terminate all existing subcontracts and purchase orders and enter into no further subcontracts and purchase orders.

§ 14.4.3 In case of such termination for the Owner's convenience, the Contractor shall be entitled to receive payment for Work executed, and costs incurred by reason of such termination, along with reasonable overhead and profit on the Work not executed.

ARTICLE 15 CLAIMS AND DISPUTES

§ 15.1 CLAIMS

§ 15.1.1 DEFINITION

A Claim is a demand or assertion by one of the parties seeking, as a matter of right, payment of money, or other relief with respect to the terms of the Contract. The term "Claim" also includes other disputes and matters in question between the Owner and Contractor arising out of or relating to the Contract. The responsibility to substantiate Claims shall rest with the party making the Claim.

§ 15.1.2 NOTICE OF CLAIMS

Claims by either the Owner or Contractor must be initiated by written notice to the other party and to the Initial Decision Maker with a copy sent to the Architect, if the Architect is not serving as the Initial Decision Maker. Claims by either party must be initiated within 21 days after occurrence of the event giving rise to such Claim or within 21 days after the claimant first recognizes the condition giving rise to the Claim, whichever is later.

§ 15.1.3 CONTINUING CONTRACT PERFORMANCE

Pending final resolution of a Claim, except as otherwise agreed in writing or as provided in Section 9.7 and Article 14, the Contractor shall proceed diligently with performance of the Contract and the Owner shall continue to make payments in accordance with the Contract Documents. The Architect will prepare Change Orders and issue Certificates for Payment in accordance with the decisions of the Initial Decision Maker.

§ 15.1.4 CLAIMS FOR ADDITIONAL COST

If the Contractor wishes to make a Claim for an increase in the Contract Sum, written notice as provided herein shall be given before proceeding to execute the Work. Prior notice is not required for Claims relating to an emergency endangering life or property arising under Section 10.4.

§ 15.1.5 CLAIMS FOR ADDITIONAL TIME

§ 15.1.5.1 If the Contractor wishes to make a Claim for an increase in the Contract Time, written notice as provided herein shall be given. The Contractor's Claim shall include an estimate of cost and of probable effect of delay on progress of the Work. In the case of a continuing delay, only one Claim is necessary.

§ 15.1.5.2 If adverse weather conditions are the basis for a Claim for additional time, such Claim shall be documented by data substantiating that weather conditions were abnormal for the period of time, could not have been reasonably anticipated and had an adverse effect on the scheduled construction.

§ 15.1.6 CLAIMS FOR CONSEQUENTIAL DAMAGES

The Contractor and Owner waive Claims against each other for consequential damages arising out of or relating to this Contract. This mutual waiver includes:

- .1 damages incurred by the Owner for rental expenses, for losses of use, income, profit, financing, business and reputation, and for loss of management or employee productivity or of the services of such persons; and
- .2 damages incurred by the Contractor for principal office expenses including the compensation of personnel stationed there, for losses of financing, business and reputation, and for loss of profit except anticipated profit arising directly from the Work.

This mutual waiver is applicable, without limitation, to all consequential damages due to either party's termination in accordance with Article 14. Nothing contained in this Section 15.1.6 shall be deemed to preclude an award of liquidated damages, when applicable, in accordance with the requirements of the Contract Documents.

§ 15.2 INITIAL DECISION

§ 15.2.1 Claims, excluding those arising under Sections 10.3, 10.4, 11.3.9, and 11.3.10, shall be referred to the Initial Decision Maker for initial decision. The Architect will serve as the Initial Decision Maker, unless otherwise indicated in the Agreement. Except for those Claims excluded by this Section 15.2.1, an initial decision shall be required as a condition precedent to mediation of any Claim arising prior to the date final payment is due, unless 30 days have passed after the Claim has been referred to the Initial Decision Maker with no decision having been rendered. Unless the Initial Decision Maker and all affected parties agree, the Initial Decision Maker will not decide disputes between the Contractor and persons or entities other than the Owner.

§ 15.2.2 The Initial Decision Maker will review Claims and within ten days of the receipt of a Claim take one or more of the following actions: (1) request additional supporting data from the claimant or a response with supporting data from the other party, (2) reject the Claim in whole or in part, (3) approve the Claim, (4) suggest a compromise, or (5) advise the parties that the Initial Decision Maker is unable to resolve the Claim if the Initial Decision Maker lacks sufficient information to evaluate the merits of the Claim or if the Initial Decision Maker concludes that, in the Initial Decision Maker's sole discretion, it would be inappropriate for the Initial Decision Maker to resolve the Claim.

§ 15.2.3 In evaluating Claims, the Initial Decision Maker may, but shall not be obligated to, consult with or seek information from either party or from persons with special knowledge or expertise who may assist the Initial Decision Maker in rendering a decision. The Initial Decision Maker may request the Owner to authorize retention of such persons at the Owner's expense.

§ 15.2.4 If the Initial Decision Maker requests a party to provide a response to a Claim or to furnish additional supporting data, such party shall respond, within ten days after receipt of such request, and shall either (1) provide a response on the requested supporting data, (2) advise the Initial Decision Maker when the response or supporting data will be furnished or (3) advise the Initial Decision Maker that no supporting data will be furnished. Upon receipt of the response or supporting data, if any, the Initial Decision Maker will either reject or approve the Claim in whole or in part.

§ 15.2.5 The Initial Decision Maker will render an initial decision approving or rejecting the Claim, or indicating that the Initial Decision Maker is unable to resolve the Claim. This initial decision shall (1) be in writing; (2) state the reasons therefor; and (3) notify the parties and the Architect, if the Architect is not serving as the Initial Decision Maker, of any change in the Contract Sum or Contract Time or both. The initial decision shall be final and binding on the parties but subject to mediation and, if the parties fail to resolve their dispute through mediation, to binding dispute resolution.

§ 15.2.6 Either party may file for mediation of an initial decision at any time, subject to the terms of Section 15.2.6.1.

§ 15.2.6.1 Either party may, within 30 days from the date of an initial decision, demand in writing that the other party file for mediation within 60 days of the initial decision. If such a demand is made and the party receiving the demand fails to file for mediation within the time required, then both parties waive their rights to mediate or pursue binding dispute resolution proceedings with respect to the initial decision.

§ 15.2.7 In the event of a Claim against the Contractor, the Owner may, but is not obligated to, notify the surety, if any, of the nature and amount of the Claim. If the Claim relates to a possibility of a Contractor's default, the Owner may, but is not obligated to, notify the surety and request the surety's assistance in resolving the controversy.

§ 15.2.8 If a Claim relates to or is the subject of a mechanic's lien, the party asserting such Claim may proceed in accordance with applicable law to comply with the lien notice or filing deadlines.

§ 15.3 MEDIATION

§ 15.3.1 Claims, disputes, or other matters in controversy arising out of or related to the Contract except those waived as provided for in Sections 9.10.4, 9.10.5, and 15.1.6 shall be subject to mediation as a condition precedent to binding dispute resolution.

§ 15.3.2 The parties shall endeavor to resolve their Claims by mediation which, unless the parties mutually agree otherwise, shall be administered by the American Arbitration Association in accordance with its Construction Industry Mediation Procedures in effect on the date of the Agreement. A request for mediation shall be made in writing, delivered to the other party to the Contract, and filed with the person or entity administering the mediation. The request may be made concurrently with the filing of binding dispute resolution proceedings but, in such event, mediation shall proceed in advance of binding dispute resolution proceedings, which shall be stayed pending mediation for a period of 60 days from the date of filing, unless stayed for a longer period by agreement of the parties or court order. If an arbitration is stayed pursuant to this Section 15.3.2, the parties may nonetheless proceed to the selection of the arbitrator(s) and agree upon a schedule for later proceedings.

§ 15.3.3 The parties shall share the mediator's fee and any filing fees equally. The mediation shall be held in the place where the Project is located, unless another location is mutually agreed upon. Agreements reached in mediation shall be enforceable as settlement agreements in any court having jurisdiction thereof.

§ 15.4 ARBITRATION

§ 15.4.1 If the parties have selected arbitration as the method for binding dispute resolution in the Agreement, any Claim subject to, but not resolved by, mediation shall be subject to arbitration which, unless the parties mutually agree otherwise, shall be administered by the American Arbitration Association in accordance with its Construction Industry Arbitration Rules in effect on the date of the Agreement. A demand for arbitration shall be made in writing, delivered to the other party to the Contract, and filed with the person or entity administering the arbitration. The party filing a notice of demand for arbitration must assert in the demand all Claims then known to that party on which arbitration is permitted to be demanded.

§ 15.4.1.1 A demand for arbitration shall be made no earlier than concurrently with the filing of a request for mediation, but in no event shall it be made after the date when the institution of legal or equitable proceedings based on the Claim would be barred by the applicable statute of limitations. For statute of limitations purposes, receipt of a written demand for arbitration by the person or entity administering the arbitration shall constitute the institution of legal or equitable proceedings based on the Claim.

§ 15.4.2 The award rendered by the arbitrator or arbitrators shall be final, and judgment may be entered upon it in accordance with applicable law in any court having jurisdiction thereof.

§ 15.4.3 The foregoing agreement to arbitrate and other agreements to arbitrate with an additional person or entity duly consented to by parties to the Agreement shall be specifically enforceable under applicable law in any court having jurisdiction thereof.

§ 15.4.4 CONSOLIDATION OR JOINDER

§ 15.4.4.1 Either party, at its sole discretion, may consolidate an arbitration conducted under this Agreement with any other arbitration to which it is a party provided that (1) the arbitration agreement governing the other arbitration permits consolidation, (2) the arbitrations to be consolidated substantially involve common questions of law or fact, and (3) the arbitrations employ materially similar procedural rules and methods for selecting arbitrator(s).

§ 15.4.4.2 Either party, at its sole discretion, may include by joinder persons or entities substantially involved in a common question of law or fact whose presence is required if complete relief is to be accorded in arbitration, provided that the party sought to be joined consents in writing to such joinder. Consent to arbitration involving an additional person or entity shall not constitute consent to arbitration of any claim, dispute or other matter in question not described in the written consent.

§ 15.4.4.3 The Owner and Contractor grant to any person or entity made a party to an arbitration conducted under this Section 15.4, whether by joinder or consolidation, the same rights of joinder and consolidation as the Owner and Contractor under this Agreement.

SECTION 00 73 13

SUPPLEMENTARY GENERAL CONDITIONS A201-2007

The following supplements modify the "General Conditions of the Contract for Construction," AIA Document A201-2007. Where a portion of the General Conditions is modified or deleted by the Supplementary Conditions, the unaltered portions of the General Conditions shall remain in effect.

TABLE OF ARTICLES

1. GENERAL PROVISIONS
2. OWNER
3. CONTRACTOR
4. ADMINISTRATION OF THE CONTRACT
5. SUBCONTRACTORS
6. CONSTRUCTION BY OWNER OR BY SEPARATE CONTRACTORS
7. CHANGES IN THE WORK
8. TIME
9. PAYMENTS AND COMPLETION
10. PROTECTION OF PERSONS AND PROPERTY
11. INSURANCE AND BONDS
12. UNCOVERING AND CORRECTION OF WORK
13. MISCELLANEOUS PROVISIONS
14. TERMINATION OR SUSPENSION OF THE CONTRACT

ARTICLE 1: GENERAL PROVISIONS

1.1 BASIC DEFINITIONS

1.1.1 THE CONTRACT DOCUMENTS

Delete the last sentence in its entirety and replace with the following:

“The Contract Documents also include Advertisement for Bid, Instructions to Bidder, sample forms, the Bid Form, the Contractor’s completed Bid and the Award Letter.”

Add the following Paragraph:

1.1.2 In the event of conflict or discrepancies among the Contract Documents, the Documents prepared by the State of Delaware, Division of Facilities Management shall take precedence over all other documents.

1.2 CORRELATION AND INTENT OF THE CONTRACT DOCUMENTS

Add the following Paragraphs:

1.2.4 In the case of an inconsistency between the Drawings and the Specifications, or within either document not clarified by addendum, the better quality or greater quantity of work shall be provided in accordance with the Architect’s interpretation.


1.2.5 The word “PROVIDE” as used in the Contract Documents shall mean “FURNISH AND INSTALL” and shall include, without limitation, all labor, materials, equipment, transportation, services and other items required to complete the Work.

1.2.6 The word “PRODUCT” as used in the Contract Documents means all materials, systems and equipment.

1.5 OWNERSHIP AND USE OF DRAWINGS, SPECIFICATIONS AND OTHER INSTRUMENTS OF SERVICE

Delete Paragraph 1.5.1 in its entirety and replace with the following:

“All pre-design studies, drawings, specifications and other documents, including those in electronic form, prepared by the Architect under this Agreement are, and shall remain, the property of the Owner whether the Project for which they are made is executed or not. Such documents may be used by the Owner to construct one or more like Projects without the approval of, or additional compensation to, the Architect. The Contractor, Subcontractors, Sub-subcontractors and Material or Equipment Suppliers are authorized to use and reproduce applicable portions of the Drawings, Specifications and other documents prepared by the



STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

Architect and the Architect's consultants appropriate to and for use in the execution of their Work under the Contract Documents. They are not to be used by the Contractor or any Subcontractor, Sub-subcontractor or Material and Equipment Supplier on other Projects or for additions to this Project outside the scope of the Work without the specific written consent of the Owner, Architect and Architect's consultants.

The Architect shall not be liable for injury or damage resulting from the re-use of drawings and specifications if the Architect is not involved in the re-use Project. Prior to re-use of construction documents for a Project in which the Architect is not also involved, the Owner will remove from such documents all identification of the original Architect, including name, address and professional seal or stamp."

Delete Paragraph 1.5.2 in its entirety.

ARTICLE 2: OWNER

2.2 INFORMATION AND SERVICES REQUIRED OF THE OWNER

To Subparagraph 2.2.3 – Add the following sentence:

"The Contractor, at their expense shall bear the costs to accurately identify the location of all underground utilities in the area of their excavation and shall bear all cost for any repairs required, out of failure to accurately identify said utilities."

Delete Subparagraph 2.2.5 in its entirety and substitute the following:

2.2.5 The Contractor shall be furnished free of charge up to three (3) sets of the Drawings and Project Manuals. Additional sets will be furnished at the cost of reproduction, postage and handling.

ARTICLE 3: CONTRACTOR

3.2 REVIEW OF CONTRACT DOCUMENTS AND FIELD CONDITIONS BY CONTRACTOR

Amend Paragraph 3.2.2 to state that any errors, inconsistencies or omissions discovered shall be reported to the Architect and Owner immediately.

Delete the third sentence in Paragraph 3.2.3.

3.3 SUPERVISION AND CONSTRUCTION PROCEDURES

Add the following Paragraphs:

3.3.2.1 The Contractor shall immediately remove from the Work, whenever requested to do so by the Owner, any person who is considered by the Owner or Architect to be incompetent or disposed to be so disorderly, or

DIVISION OF FACILITIES MANAGEMENT

STATE OF DELAWARE

who for any reason is not satisfactory to the Owner, and that person shall not again be employed on the Work without the consent of the Owner or the Architect.

3.3.4 The Contractor must provide suitable storage facilities at the Site for the proper protection and safe storage of their materials. Consult the Owner and the Architect before storing any materials.

3.3.5 When any room is used as a shop, storeroom, office, etc. by the Contractor or Subcontractor(s) during the construction of the Work, the Contractor making use of these areas will be held responsible for any repairs, patching or cleaning arising from such use.

3.4 LABOR AND MATERIALS

Add the Following Paragraphs:

3.4.4 Before starting the Work, each Contractor shall carefully examine all preparatory Work that has been executed to receive their Work. Check carefully, by whatever means are required, to insure that its Work and adjacent, related Work, will finish to proper contours, planes and levels. Promptly notify the General Contractor/Construction Manager of any defects or imperfections in preparatory Work which will in any way affect satisfactory completion of its Work. Absence of such notification will be construed as an acceptance of preparatory Work and later claims of defects will not be recognized.


3.4.5 Under no circumstances shall the Contractor's Work proceed prior to preparatory Work having been completely cured, dried and/or otherwise made satisfactory to receive this Work. Responsibility for timely installation of all materials rests solely with the Contractor responsible for that Work, who shall maintain coordination at all times.

3.5 WARRANTY

Add the following Paragraphs:

3.5.1 The Contractor will guarantee all materials and workmanship against original defects, except injury from proper and usual wear when used for the purpose intended, for two (2) years after Acceptance by the Owner, and will maintain all items in perfect condition during the period of guarantee.

3.5.2 Defects appearing during the period of guarantee will be made good by the Contractor at his expense upon demand of the Owner, it being required that all work will be in perfect condition when the period of guarantee will have elapsed.



STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

- 3.5.3 In addition to the General Guarantee there are other guarantees required for certain items for different periods of time than the two (2) years as above, and are particularly so stated in that part of the specifications referring to same. The said guarantees will commence at the same time as the General Guarantee.
- 3.5.4 If the Contractor fails to remedy any failure, defect or damage within a reasonable time after receipt of notice, the Owner will have the right to replace, repair, or otherwise remedy the failure, defect or damage at the Contractor's expense.

3.11 DOCUMENTS AND SAMPLES AT THE SITE

Add the following Paragraphs:

- 3.11.1 During the course of the Work, the Contractor shall maintain a record set of drawings on which the Contractor shall mark the actual physical location of all piping, valves, equipment, conduit, outlets, access panels, controls, actuators, including all appurtenances that will be concealed once construction is complete, etc., including all invert elevations.
- 3.11.2 At the completion of the project, the Contractor shall obtain a set of reproducible drawings from the Architect, and neatly transfer all information outlined in 3.11.1 to provide a complete record of the as-built conditions.
- 3.11.3 Provide five (5) prints of these reproducibles, one (1) set for the State Archives, and one (1) set along with the reproducibles themselves and AutoCAD 2006/2010 CD's to Owner. In addition, attach one (1) complete set of prints to each of the Operating and Maintenance Instructions.

- 3.17 In the first sentence of the paragraph, insert "indemnify" between "shall" and "hold".

ARTICLE 4: ADMINISTRATION OF THE CONTRACT

4.2 ADMINISTRATION OF THE CONTRACT

Delete the first sentence of Paragraph 4.2.7 and replace with the following:

The Architect will review and approve or take other appropriate action upon the Contractor's submittals such as Shop Drawings, Product Data and Samples for the purpose of checking for conformance with the Contract Documents.

Delete the second sentence of Paragraph 4.2.7 and replace with the following:

DIVISION OF FACILITIES MANAGEMENT

STATE OF DELAWARE

The Architect’s action will be taken with such reasonable promptness as to cause no delay in the Work in the activities of the Owner, Contractor or separate Contractors, while allowing sufficient time in the Owner’s professional judgment to permit adequate review.

Add the following Paragraph:

4.2.10.1 There will be no full-time project representative provided by the Owner or Architect on this project.

Add to Paragraph 4.2.13 “and in compliance with all local requirements” to the end of the sentence

ARTICLE 5: SUBCONTRACTORS

5.2 AWARD OF SUBCONTRACTS AND OTHER CONTRACTS FOR PORTIONS OF THE WORK

Delete Paragraph 5.2.3 in its entirety and replace with the following:

5.2.3 If the Owner or Architect has reasonable objection to a person or entity proposed by the Contractor, the Contractor shall propose another to whom the Owner or Architect has no reasonable objection, subject to the statutory requirements of 29 Delaware Code § 6962(d)(10)b.3 and 4.

ARTICLE 6: CONSTRUCTION BY OWNER OR BY SEPARATE CONTRACTORS

6.1 OWNER’S RIGHT TO PERFORM CONSTRUCTION AND TO AWARD SEPARATE CONTRACTS

Delete Paragraph 6.1.4 in its entirety.

6.2 MUTUAL RESPONSIBILITY

6.2.3 In the second sentence, strike the word “shall” and insert the word “may”.

ARTICLE 7: CHANGES IN THE WORK


(SEE ARTICLE 7: CHANGES IN WORK IN THE GENERAL REQUIREMENTS)

ARTICLE 8: TIME

8.2 PROGRESS AND COMPLETION

Add the following Paragraphs:

8.2.1.1 Refer to Specification Section SUMMARY OF WORK for Contract time requirements.



STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

8.2.4 If the Work falls behind the Progress Schedule as submitted by the Contractor, the Contractor shall employ additional labor and/or equipment necessary to bring the Work into compliance with the Progress Schedule at no additional cost to the Owner.

8.3 DELAYS AND EXTENSION OF TIME

8.3.1 Strike "arbitration" and insert "remedies at law or in equity"

Add the following Paragraph:

8.3.2.1 The Contractor shall update the status of the suspension, delay, or interruption of the Work with each Application for Payment. (The Contractor shall report the termination of such cause immediately upon the termination thereof.) Failure to comply with this procedure shall constitute a waiver for any claim for adjustment of time or price based upon said cause.

Delete Paragraph 8.3.3 in its entirety and replace with the following:

8.3.3 Except in the case of a suspension of the Work directed by the Owner, an extension of time under the provisions of Paragraph 8.3.1 shall be the Contractor's sole remedy in the progress of the Work and there shall be no payment or compensation to the Contractor for any expense or damage resulting from the delay.

Add the following Paragraph:

8.3.4 By permitting the Contractor to work after the expired time for completion of the project, the Owner does not waive their rights under the Contract.

ARTICLE 9: PAYMENTS AND COMPLETION

9.2 SCHEDULE OF VALUES

Add the following Paragraphs:

9.2.1 The Schedule of Values shall be submitted using AIA Document G702, Continuation Sheet to G703.

9.2.2 The Schedule of Values is to include a line item for Project Closeout Document Submittal. The value of this item is to be no less than 1% of the initial contract amount.

9.3 APPLICATIONS FOR PAYMENT

Add the following Paragraph:

DIVISION OF FACILITIES MANAGEMENT

STATE OF DELAWARE

9.3.1.3 Application for Payment shall be submitted on AIA Document G702 “Application and Certificate for Payment”, supported by AIA Document G703 “Continuation Sheet”. Said Applications shall be fully executed and notarized.

Add the following Paragraphs:

9.3.4 Until Closeout Documents have been received and outstanding items completed the Owner will pay 95% (ninety-five percent) of the amount due the Contractor on account of progress payments.

9.3.5 The Contractor shall provide a current and updated Progress Schedule to the Architect with each Application for Payment. Failure to provide Schedule will be just cause for rejection of Application for Payment.

9.5 DECISIONS TO WITHHOLD CERTIFICATION

Add the following to 9.5.1:

- .8 failure to provide a current Progress Schedule;
- .9 a lien or attachment is filed;
- .10 failure to comply with mandatory requirements for maintaining Record Documents.

9.6 PROGRESS PAYMENTS

Delete Paragraph 9.6.1 in its entirety and replace with the following:

9.6.1 After the Architect has approved and issued a Certificate for Payment, payment shall be made by the Owner within 30 days after Owner’s receipt of the Certificate for Payment.

9.7 FAILURE OF PAYMENT

In first sentence, strike “seven” and insert “thirty (30)”. Also strike “binding dispute resolution” and insert “remedies at law or in equity”.


9.8 SUBSTANTIAL COMPLETION

To Subparagraph 9.8.3- Add the following sentence:

“If the Architect is required to make more than 2 inspections of the same portion of work, the Contractor shall be responsible for all costs associated with subsequent inspections including but not limited to any Architect’s fees.”

9.8.5 In the second sentence, strike “shall” and insert “may”.

ARTICLE 10: PROTECTION OF PERSONS AND PROPERTY



STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

10.1 SAFETY PRECAUTIONS AND PROGRAMS

Add the following Paragraphs:

10.1.1.1 Each Contractor shall develop a safety program in accordance with the Occupational Safety and Health Act of 1970. A copy of said plan shall be furnished to the Owner and Architect prior to the commencement of that Contractor's Work.

10.1.2 Each Contractor shall appoint a Safety Representative. Safety Representatives shall be someone who is on site on a full time basis. If deemed necessary by the Owner or Architect, Contractor Safety meetings will be scheduled. The attendance of all Safety Representatives will be required. Minutes will be recorded of said meetings by the Contractor and will be distributed to all parties as well as posted in all job offices/trailers etc.

10.2 SAFETY OF PERSONS AND PROPERTY

Add the following Paragraph:

10.2.4.1 As required in the Hazardous Chemical Act of June 1984, all vendors supplying any material that may be defined as hazardous must provide Material Safety Data Sheets for those products. Any chemical product should be considered hazardous if it has a caution warning on the label relating to a potential physical or health hazard, if it is known to be present in the work place, and if employees may be exposed under normal conditions or in foreseeable emergency situations. Material Safety Data Sheets shall be provided directly to the Owner, along with the shipping slips that include those products.

10.3 HAZARDOUS MATERIALS

Delete Paragraph 10.3.3 in its entirety.

10.5 Delete Paragraphs 10.3.6 in its entirety.

ARTICLE 11: INSURANCE AND BONDS

11.1 CONTRACTOR'S LIABILITY INSURANCE

11.1.4 Strike "the Owner" immediately following "(1)" and strike "and (2) the Owner as an additional insured for claims caused in whole or in part by the Contractor's negligent acts or omissions during the Contractor's completed operations."

11.2 OWNER'S LIABILITY INSURANCE

DIVISION OF FACILITIES MANAGEMENT

STATE OF DELAWARE

Delete Paragraph 11.2 in its entirety.

11.3 PROPERTY INSURANCE

Delete Paragraph 11.3 in its entirety and replace with the following:

11.3 The State will not provide Builder’s All Risk Insurance for the Project. The Contractor and all Subcontractors shall provide property coverage for their tools and equipment, as necessary. Any mandatory deductible required by the Contractor’s Insurance shall be the responsibility of the Contractor.

11.4 PERFORMANCE BOND AND PAYMENT BOND

Add the following sentence: “The bonds will conform to those forms approved by the Office of Management and Budget.”

ARTICLE 12: UNCOVERING AND CORRECTION OF WORK

12.2.2 AFTER SUBSTANTIAL COMPLETION

Add the following Paragraph:

12.2.2.1.1 At any time during the progress of the Work, or in any case where the nature of the defects will be such that it is not expedient to have corrected, the Owner, at its option, will have the right to deduct such sum, or sums, of money from the amount of the Contract as it considers justified to adjust the difference in value between the defective work and that required under the Contract including any damage to the structure.

12.2.2.1 Strike “one” and insert “two”.

12.2.2.2 Strike “one” and insert “two”.

12.2.2.3 Strike “one” and insert “two”.


12.2.5 In second sentence, strike “one” and insert “two”.

ARTICLE 13: MISCELLANEOUS PROVISIONS

13.1 GOVERNING LAW

Strike “except that, if the parties have selected arbitration as the method of binding dispute resolution, the Federal Arbitration Act shall govern Section 15.4.”

13.6 INTEREST



STATE OF DELAWARE

DIVISION OF FACILITIES MANAGEMENT

Strike “the date payment is due at such rate as the parties may agree upon in writing or, in the absence thereof, at the legal rate prevailing from time to time at the place where the Project is located.” Insert “30 days of presentment of the authorized Certificate of Payment at the annual rate of 12% or 1% per month.

13.7 TIME LIMITS ON CLAIMS

Strike the last sentence.

Add the following Paragraph:

13.8 CONFLICTS WITH FEDERAL STATUTES OR REGULATIONS

13.8.1 If any provision, specifications or requirement of the Contract Documents conflict or is inconsistent with any statute, law or regulation of the government of the United State of America, the Contractor shall notify the Architect and Owner immediately upon discovery.

ARTICLE 14: TERMINATION OR SUSPENSION OF THE CONTRACT

14.4 TERMINATION BY THE OWNER FOR CONVENIENCE

Delete Paragraph 14.4.3 in its entirety and replace with the following:

14.4.3 In case of such termination for the Owner’s convenience, the Contractor shall be entitled to receive payment for Work executed, and cost incurred by reason of such termination along with reasonable overhead.

ARTICLE 15: CLAIMS AND DISPUTES

15.1.2 Throughout the Paragraph strike “21” and insert “45”.

15.1.6 CLAIMS FOR CONSEQUENTIAL DAMAGES


Delete Paragraph 15.1.6 in its entirety.

15.2 INITIAL DECISION

Delete Paragraph 15.2.5 in its entirety and replace with the following:

15.2.5 The Architect will approve or reject Claims by written decision, which shall state the reasons therefore and shall notify the parties of any change in the Contract Sum or Contract Time or both. The approval or rejection of a Claim by the Architect shall be subject to mediation and other remedies at law or in equity.

Delete Paragraph 15.2.6 and its subparagraphs in their entirety.



DIVISION OF FACILITIES MANAGEMENT

STATE OF DELAWARE

15.3 MEDIATION

- 15.3.1 Strike “binding dispute resolution” and insert “any or all remedies at law or in equity”.
- 15.3.2 In the first sentence, delete “administered by the American Arbitration Association in accordance with its Construction Industry Mediation Procedure in effect on the date of the Agreement,” Strike “binding dispute resolution” and insert “remedies at law and in equity”.

15.4 ARBITRATION

Delete Paragraph 15.4 and its sub-sections in its entirety.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 00 52 13

DELAWARE PREVAILING WAGE RATES

State of Delaware, Department of Labor, Prevailing Wages. Provided in accordance with Delaware's Prevailing Wage Regulations.

NOT FOR BIDDING PURPOSES

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

STATE OF DELAWARE
DEPARTMENT OF LABOR
DIVISION OF INDUSTRIAL AFFAIRS
OFFICE OF LABOR LAW ENFORCEMENT
PHONE: (302) 451-3423

Mailing Address:
225 CORPORATE BOULEVARD
SUITE 104
NEWARK, DE 19702

Located at:
225 CORPORATE BOULEVARD
SUITE 104
NEWARK, DE 19702

PREVAILING WAGES FOR BUILDING CONSTRUCTION EFFECTIVE MARCH 15, 2017

CLASSIFICATION	NEW CASTLE	KENT	SUSSEX
ASBESTOS WORKERS	22.86	28.16	40.98
BOILERMAKERS	68.44	34.72	51.05
BRICKLAYERS	51.99	51.99	51.99
CARPENTERS	53.81	53.81	42.77
CEMENT FINISHERS	72.28	46.71	22.17
ELECTRICAL LINE WORKERS	45.47	38.49	29.73
ELECTRICIANS	66.85	66.85	66.85
ELEVATOR CONSTRUCTORS	90.49	90.49	31.94
GLAZIERS	71.20	71.20	56.66
INSULATORS	55.48	55.48	55.48
IRON WORKERS	62.85	62.85	62.85
LABORERS	44.70	44.70	44.70
MILLWRIGHTS	69.18	69.18	55.75
PAINTERS	48.47	48.47	48.47
PILEDRIVERS	75.27	39.35	31.83
PLASTERERS	29.84	29.84	22.12
PLUMBERS/PIPEFITTERS/STEAMFITTERS	65.95	51.49	57.01
POWER EQUIPMENT OPERATORS	67.29	67.29	43.83
ROOFERS-COMPOSITION	24.01	23.70	21.64
ROOFERS-SHINGLE/SLATE/TILE	18.39	21.86	17.19
SHEET METAL WORKERS	67.03	67.03	67.03
SOFT FLOOR LAYERS	51.12	51.12	51.12
SPRINKLER FITTERS	57.29	57.29	57.29
TERRAZZO/MARBLE/TILE FINISHERS	57.72	57.72	47.51
TERRAZZO/MARBLE/TILE SETTERS	66.02	66.02	55.02
TRUCK DRIVERS	28.75	27.44	20.94

CERTIFIED

06/01/2017

BY:

[Signature]
ADMINISTRATOR, OFFICE OF LABOR LAW ENFORCEMENT

NOTE: THESE RATES ARE PROMULGATED AND ENFORCED PURSUANT TO THE PREVAILING WAGE REGULATIONS ADOPTED BY THE DEPARTMENT OF LABOR ON APRIL 3, 1992.

CLASSIFICATIONS OF WORKERS ARE DETERMINED BY THE DEPARTMENT OF LABOR. FOR ASSISTANCE IN CLASSIFYING WORKERS, OR FOR A COPY OF THE REGULATIONS OR CLASSIFICATIONS, PHONE (302) 451-3423.

NON-REGISTERED APPRENTICES MUST BE PAID THE MECHANIC'S RATE.

PROJECT: Door Upgrades - Caesar Rodney SD - Star Hill ES, Stokes ES, Postlethwait MS, Fifer MS, Kent County

NOT FOR BIDDING PURPOSES

PREVAILING WAGE DEBARMENT LIST

The following contractors have been debarred for violations of the prevailing wage law 29Del.C. §6960 or other applicable State statutes.

Therefore, no public construction contract in this State shall be bid on, awarded to, or received by contractors and individuals on this list for a period of (3) three years from the date of the judgment or as deemed by a court of competent jurisdiction.

Contractor	Address	Date of Debarment
Mullen Brothers, Inc. and Daniel Mullen, individually	3375 Garnett Road, Boothwyn, PA 19060	Indefinite/ Civil Contempt
MMR Associates DBA Peninsula Glass and Michael Rooney, individually	679 Horse Pond Road, Dover, DE 19901	1/20/2015
Site Work Safety Supplies, Inc. and Peter Coker, individually	4020 Seven Hickories Road Dover, DE 19904	1/12/2016
Green Granite and Jason Green, individually	604 Heatherbrooke Court Avondale, PA 19311	Indefinite/ Civil Contempt
Pro Image Landscaping, Inc. and Owner(s) individually	23 Commerce Street Wilmington, DE 19801 and/or 2 Cameo Road Claymont, DE 19703	Indefinite/19 Del.C. §108 & 10 Del.C. 542(c)
Liberty Mechanical, LLC and Owner(s), individually	2032 Duncan Road Wilmington, DE 19801	Indefinite/ 19 Del.C. 2374(f)
Integrated Mechanical and Fire Systems Inc. and Allison Sheldon, individually	4601 Governor Printz Boulevard Wilmington, DE 19809	Indefinite/19 Del.C. §108 & 10 Del.C. 542(c)

Updated: May 11, 2017

NOT FOR BIDDING PURPOSES

STATE OF DELAWARE
DEPARTMENT OF LABOR
DIVISION OF INDUSTRIAL AFFAIRS
OFFICE OF LABOR LAW ENFORCEMENT
PHONE: (302) 451-3423


Mailing Address:
4425 North Market St. 3rd FL
Wilmington, DE 19802

Located at:
4425 North Market St. 3rd FL
Wilmington, DE 19802

PREVAILING WAGES FOR BUILDING CONSTRUCTION EFFECTIVE MARCH 15, 2017

CLASSIFICATION	NEW CASTLE	KENT	SUSSEX
ASBESTOS WORKERS	22.86	28.16	40.98
BOILERMAKERS	68.44	34.72	51.05
BRICKLAYERS	51.99	51.99	51.99
CARPENTERS	53.81	53.81	42.77
CEMENT FINISHERS	72.28	46.57	22.17
ELECTRICAL LINE WORKERS	45.47	37.99	29.73
ELECTRICIANS	66.85	66.85	66.85
ELEVATOR CONSTRUCTORS	90.49	64.49	31.94
GLAZIERS	71.20	71.20	56.66
INSULATORS	55.48	55.48	55.48
IRON WORKERS	62.85	62.85	62.85
LABORERS	44.70	44.70	44.70
MILLWRIGHTS	69.18	69.18	55.75
PAINTERS	48.47	48.47	48.47
PILEDRIVERS	75.27	39.35	31.83
PLASTERERS	29.84	29.84	22.12
PLUMBERS/PIPEFITTERS/STEAMFITTERS	65.95	51.49	57.01
POWER EQUIPMENT OPERATORS	67.29	67.29	43.83
ROOFERS-COMPOSITION	24.01	23.70	21.64
ROOFERS-SHINGLE/SLATE/TILE	18.39	21.86	17.19
SHEET METAL WORKERS	67.03	67.03	67.03
SOFT FLOOR LAYERS	51.12	51.12	51.12
SPRINKLER FITTERS	57.29	57.29	57.29
TERRAZZO/MARBLE/TILE FINISHERS	57.72	57.72	47.51
TERRAZZO/MARBLE/TILE SETTERS	66.02	66.02	55.02
TRUCK DRIVERS	28.75	27.44	20.94

CERTIFIED: 4/17/17


BY: 
ADMINISTRATOR, OFFICE OF LABOR LAW ENFORCEMENT

NOTE: THESE RATES ARE PROMULGATED AND ENFORCED PURSUANT TO THE PREVAILING WAGE REGULATIONS ADOPTED BY THE DEPARTMENT OF LABOR ON APRIL 3, 1992.

CLASSIFICATIONS OF WORKERS ARE DETERMINED BY THE DEPARTMENT OF LABOR. FOR ASSISTANCE IN CLASSIFYING WORKERS, OR FOR A COPY OF THE REGULATIONS OR CLASSIFICATIONS, PHONE (302) 761-8200

NON-REGISTERED APPRENTICES MUST BE PAID THE MECHANIC'S RATE.

PROJECT: Stokes Elementary School - HVAC Improvements , Kent County



EMPLOYEE DRUG TESTING REPORT FORM

Period Ending: _____

4104 Regulations for the Drug Testing of Contractor and Subcontractor Employees Working on Large Public Works Projects requires that Contractors and Subcontractors who work on Large Public Works Contracts funded all or in part with public funds submit Testing Report Forms to the Owner no less than quarterly.

Project Number: _____

Project Name: _____

Contractor/Subcontractor Name: _____

Contractor/Subcontractor Address: _____

Number of employees who worked on the jobsite during the report period: _____

Number of employees subject to random testing during the report period: _____

Number of Negative Results _____ Number of Positive Results _____

Action taken on employee(s) in response to a failed or positive random test:

Authorized Representative of Contractor/Subcontractor: _____
(typed or printed)

Authorized Representative of Contractor/Subcontractor: _____
(signature)

Date: _____

NOT FOR BIDDING PURPOSES

**EMPLOYEE DRUG TESTING
REPORT OF POSITIVE RESULTS**

4104 Regulations for the Drug Testing of Contractor and Subcontractor Employees Working on Large Public Works Projects requires that Contractors and Subcontractors who work on Large Public Works Contracts funded all or in part with public funds to notify the Owner in writing of a positive random drug test.

Project Number: _____

Project Name: _____

Contractor/Subcontractor Name: _____

Contractor/Subcontractor Address: _____

Name of employee with positive test result: _____

Last 4 digits of employee SSN: _____

Date test results received: _____

Action taken on employee in response to a positive test result:

Authorized Representative of Contractor/Subcontractor: _____
(typed or printed)

Authorized Representative of Contractor/Subcontractor: _____
(signature)

Date: _____

This form shall be sent by mail to the Owner within 24 hours of receipt of test results.

Enclose this test results form in a sealed envelope with the notation "Drug Testing Form – DO NOT OPEN" on the face thereof and place in a separate mailing envelope.

SECTION 01 11 00

SUMMARY

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:

1. Project information.
2. Work covered by Contract Documents.
3. General requirements of Contract.
4. Owner-furnished products.
5. Access to site.
6. Coordination with occupants.
7. Work restrictions.
8. Phased construction

1.3 DEFINITIONS

- A. Permanent Enclosure: As determined by Architect, the condition at which roofing is insulated and weathertight; exterior walls are insulated and weathertight; all openings are closed with permanent construction; and all exterior joints are sealed.

1.4 PROJECT INFORMATION

- A. Project Identification: HVAC Improvements for Stokes Elementary School

1. Project Location: 3874 Upper King Rd., Dover, DE 19904

- B. Owner's Representative: Ken Starke

1. Address: 7 Front Street, PO Box 188, Wyoming, DE 19934

- C. Owner: Caesar Rodney School District

1. Address: 7 Front Street, PO Box 188, Wyoming, DE 19934

- D. Architect: Tetra Tech Inc.

1. Address: 240 Continental Drive, Suite 200, Newark, DE 19713

E. Building Code in Effect for Project: 2012 IBC

1.5 WORK COVERED BY CONTRACT DOCUMENTS

A. The Work of Project is defined by the Contract Documents and consists of the following:

B. Project consists of HVAC improvements to replace existing system with new system. This includes but is not limited to replacement of chillers; retrofit of ceiling cassette type fan coil units in the entire school; installation of new central station air handling units, exhaust fans, and kitchen hood exhaust fan. ATC system to be upgraded. The Fire Protection system to be replaced. Project also includes work to support HVAC improvements such as ceilings, insulation, access improvements and structural work as further described in Project Documents.

C. Type of Contract: Project will be constructed under a single prime contract.

1.6 GENERAL REQUIREMENTS OF CONTRACT

A. Temporary Heating: Not required for this project.

B. Temporary Ventilation: Not required for this project.

C. Water Service: Water is not required at the Project site.

1.7 USE OF PREMISES

A. Use of the Site: Confine operations at the site to the areas permitted under the Contract. Portions of the site beyond areas on which work is indicated are not to be disturbed. Conform to site rules and regulations affecting the work while engaged in project renovations.

1. Keep drive ways and entrances serving the premises clear and available for the Owner's use at all times. Do not use these areas for parking or storage of materials, except as directed by the Owner's Representative.
2. Do not encumber the site with materials or equipment. Confine stockpiling of materials to the areas directed by the Owner's Representative. If storage is necessary, obtain and pay for such storage beyond the secure perimeter or off site.
3. Lock automotive type vehicles, such as passenger cars and trucks and other mechanized or motorized construction equipment when parked and unattended to prevent unauthorized use. Do not leave such vehicle or equipment unattended with the motor running or the ignition key in place.
4. Parking areas for employees of the Contractor shall be designated in the vicinity of the project, and it shall be the responsibility of the Contractor to require its personnel to park in this designated area and not any area, which may interfere with the Owner's normal operations.

1.8 PROTECTION OF PERSONS AND PROPERTY

- A. The Contractor shall provide ample and approved provisions for the protection of any area, which may be considered a hazard for any persons and vehicles operating in the area. All hazards such as trenches, stored material, work areas, etc., shall be neatly barricaded and lighted.
 - 1. The safeguard measures for this project shall comply, at a minimum, with all applicable sections of the Occupational, Health, and Safety Act, with the latest addenda.

1.9 OWNER'S OCCUPANCY REQUIREMENTS

- A. Full Owner Occupancy: Owner will occupy site and existing building during entire construction period. Cooperate with Owner during construction operations to minimize conflicts and facilitate Owner usage. Perform the Work so as not to interfere with Owner's day-to-day operations. Maintain existing exits, unless otherwise indicated.
 - 1. Maintain access to existing walkways, corridors, and other adjacent occupied or used facilities. Do not close or obstruct walkways, corridors, or other occupied or used facilities without written permission from Owner and authorities having jurisdiction.
 - 2. Provide not less than 72 hours' notice to Owner of activities that will affect Owner's operations.

1.10 WORK RESTRICTIONS

- A. On-Site Work Hours: Work shall be generally performed inside the existing building during normal business working hours of 7:00 a.m. to 3:00 p.m., Monday through Friday, except otherwise indicated.

1.11 COORDINATION

- A. General: The work of this Contract includes coordination of the entire work of the project, including preparation of general coordination drawings, diagrams and schedules, and control of site utilization, from the beginning of the demolition activity through the project closeout and warranty periods.
- B. Copies of governing regulations, which have a bearing on the performance of the work, can be obtained from or reviewed at the local, State, or Federal Agency responsible for the regulation in each case.
- C. Miscellaneous elements of information having a bearing on the performance of the work, such as weather forecasts and reports of general trade union negotiations; copies must be obtained by the Contractor through normal channels of information.
- D. Measurements: Verify dimensions of existing work. Any discrepancy between drawings and / or specifications and existing conditions shall be referred to the Architect in writing for adjustment before the work affected thereby has been performed. In the event of the Contractor's failure to give such notice, he will be held responsible for the results of any discrepancies and cost of rectifying same.

1.12 PHASED CONSTRUCTION

- A. The Work shall be conducted in two phases, with each phase substantially complete as indicated. Phase 1 work to be completed in 2018. Phase 2 work to be complete in 2019. All work will be done over the summer break of the year shown.
- B. Before commencing Work of each phase, submit an updated copy of Contractor's construction schedule showing the sequence, commencement and completion dates for all phases of the Work.

1.13

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION (Not Used)

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 01 23 00

ALTERNATES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes administrative and procedural requirements for alternates.

1.3 DEFINITIONS

- A. Alternate: An amount proposed by bidders and stated on the Bid Form for certain work defined in the bidding requirements that may be added to or deducted from the base bid amount if the Owner decides to accept a corresponding change either in the amount of construction to be completed or in the products, materials, equipment, systems, or installation methods described in the Contract Documents.
 - 1. Alternates described in this Section are part of the Work only if enumerated in the Agreement.
 - 2. The cost or credit for each alternate is the net addition to or deduction from the Contract Sum to incorporate alternates into the Work. No other adjustments are made to the Contract Sum.

1.4 PROCEDURES

- A. Coordination: Revise or adjust affected adjacent work as necessary to completely integrate work of the alternate into Project.
 - 1. Include as part of each alternate, miscellaneous devices, accessory objects, and similar items incidental to or required for a complete installation whether or not indicated as part of alternate.
 - 2. Execute accepted alternates under the same conditions as other work of the Contract.
- C. Schedule: A schedule of alternates is included at the end of this Section. Specification Sections referenced in schedule contain requirements for materials necessary to achieve the work described under each alternate.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION

3.1 SCHEDULE OF ALTERNATES

A. Alternate No. 1: Phasing and construction schedule.

1. Base Bid: Work included in Project Documentation to be performed in two (2) phases. See Drawing PH-121 "First Floor Phasing Plan" for phasing diagrams. Phase #1 will be performed in Summer 2018. Phase #2 will be performed in Summer 2019.
2. Alternate: All work included in Project Documentation to be performed in its entirety in Summer 2018.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 01 25 00

CONTRACT MODIFICATIONS PROCEDURES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section specifies administrative and procedural requirements for handling and processing Contract modifications.

1.3 MINOR CHANGES IN THE WORK

- A. The Architect will issue supplemental instructions authorizing Minor Changes in the Work, not involving adjustment to the Contract Sum or the Contract Time, on AIA Document G710, "Architect's Supplemental Instructions".

1.4 PROPOSAL REQUESTS

- A. Owner-Initiated Proposal Requests: The Architect will issue a detailed description of proposed changes in the Work that may require adjustment to the Contract Sum or the Contract Time. If necessary, the description will include supplemental or revised Drawings and Specifications.
 - 1. Proposal Requests issued by the Architect are for information only. Do not consider them instructions either to stop work in progress or to execute the proposed change.
 - 2. Within time specified in Proposal Request after receipt of Proposal Request, submit a quotation estimating cost adjustments to the Contract Sum and the Contract Time necessary to execute the change. Refer to procedures outlined in the *Supplementary Conditions* of the Contract.
- B. Contractor-Initiated Proposals: If latent or unforeseen conditions require modifications to the Contract, Contractor may propose changes by submitting a request for a change to the Architect. Refer to Procedures outlined in the *Supplementary Conditions* of the Contract.

1.6 CHANGE ORDER PROCEDURES

- A. On Owner's approval of a Proposal Request, the Architect will issue a Change Order for signatures of Owner and Contractor on AIA Document G701.

1.7 CONSTRUCTION CHANGE DIRECTIVE

- A. Work Change Directive: The Architect may issue a Work Change Directive on AIA Document G714. Work Change Directive instructs Contractor to proceed with a change in the Work, for subsequent inclusion in a Change Order.

1. Work Change Directive contains a complete description of change in the Work. It also designates method to be followed to determine change in the Contract Sum or the Contract Time.
- B. Documentation: Maintain detailed records on a time and material basis of work required by the Work Change Directive.
 1. After completion of change, submit an itemized account and supporting data necessary to substantiate cost and time adjustments to the Contract.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION (Not Used)

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 01 31 00

PROJECT MANAGEMENT & COORDINATION

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative provisions for coordinating construction operations on the Project including, but not limited to, the following:
 - 1. General project coordination procedures.
 - 2. Coordination Drawings.
 - 3. Administrative and supervisory personnel.
 - 4. Project meetings.
- B. Each contractor shall participate in coordination requirements. Certain areas of responsibility will be assigned to a specific contractor.
- C. Related Sections: The following Sections contain requirements that relate to this Section:
 - 1. Division 01 Section "Closeout Procedures" for coordinating Contract closeout.

1.3 COORDINATION

- A. Coordination: Coordinate construction operations included in various Sections of the Specifications to ensure efficient and orderly installation of each part of the Work. Coordinate construction operations, included in different Sections that depend on each other for proper installation, connection, and operation.
 - 1. Schedule construction operations in sequence required to obtain the best results where installation of one part of the Work depends on installation of other components, before or after its own installation.
 - 2. Coordinate installation of different components with other contractors to ensure maximum accessibility for required maintenance, service, and repair.
 - 3. Make adequate provisions to accommodate items scheduled for later installation.
- B. If necessary, prepare memoranda for distribution to each party involved, outlining special procedures required for coordination. Include such items as required notices, reports, and list of attendees at meetings.
 - 1. Prepare similar memoranda for the Owner and separate contractors if coordination of their Work is required.
- C. Administrative Procedures: Coordinate scheduling and timing of required administrative procedures with other construction activities and activities of other contractors to avoid conflicts

and to ensure orderly progress of the Work. Such administrative activities include, but are not limited to, the following:

1. Preparation of the Contractor's Construction Schedule.
2. Preparation of the Schedule of Values.
3. Installation and removal of temporary facilities and controls.
4. Delivery and processing of submittals.
5. Progress meetings.
6. Preinstallation conferences.
7. Project closeout activities.

- D. Conservation: Coordinate construction activities to ensure that operations are carried out with consideration given to conservation of energy, water, and materials.

1.4 SUBMITTALS

- A. Coordination Drawings: Prepare Coordination Drawings if limited space availability necessitates maximum utilization of space for efficient installation of different components or if coordination is required for installation of products and materials fabricated by separate entities.

1. Indicate relationship of components shown on separate Shop Drawings.
2. Indicate required installation sequences.

- B. Staff Names: Within 15 days of starting construction operations, submit a list of principal staff assignments, including superintendent and other personnel in attendance at the Project site. Identify individuals and their duties and responsibilities; list addresses and telephone numbers, including home and office telephone numbers. Provide names, addresses, and telephone numbers of individuals assigned as standbys in the absence of individuals assigned to the Project.

1.5 PROJECT MEETINGS

- A. General: Schedule and conduct meetings and conferences at the Project site, unless otherwise indicated.

1. Attendees: Inform participants and others involved, and individuals whose presence is required, of date and time of each meeting. Notify the Owner and the Architect of scheduled meeting dates and times.
2. Agenda: Prepare the meeting agenda. Distribute the agenda to all invited attendees.
3. Minutes: Record significant discussions and agreements achieved. Distribute the meeting minutes to everyone concerned, including the Owner and the Architect, within 3 days of the meeting.

- B. Preconstruction Conference: Schedule a preconstruction conference before starting construction, at a time convenient to the Owner and the Architect, but no later than 15 days after execution of the Agreement. Hold the conference at the Project site or another convenient location. Conduct the meeting to review responsibilities and personnel assignments.

1. Attendees: Authorized representatives of the Owner, the Architect, and their consultants; the Contractor and its superintendent; major subcontractors; manufacturers; suppliers;

and other concerned parties shall attend the conference. All participants at the conference shall be familiar with the Project and authorized to conclude matters relating to the Work.

2. Agenda: Discuss items of significance that could affect progress, including the following:
 - a. Tentative construction schedule.
 - b. Phasing.
 - c. Critical work sequencing.
 - d. Designation of responsible personnel.
 - e. Procedures for processing field decisions and Change Orders.
 - f. Procedures for processing Applications for Payment.
 - g. Distribution of the Contract Documents.
 - h. Submittal procedures.
 - i. Preparation of Record Documents.
 - j. Use of the premises.
 - k. Responsibility for temporary facilities and controls.
 - l. Parking availability.
 - m. Office, work, and storage areas.
 - n. Equipment deliveries and priorities.
 - o. First aid.
 - p. Security.
 - q. Progress cleaning.
 - r. Working hours.
- C. Progress Meetings: Conduct progress meetings at semi-monthly intervals. Coordinate dates of meetings with preparation of payment requests.
 1. Agenda: Review and correct or approve minutes of previous progress meeting. Review other items of significance that could affect progress. Include topics for discussion as appropriate to status of the Project.
 - a. Contractor's Construction Schedule: Review progress since the last meeting. Determine whether each activity is on time, ahead of schedule, or behind schedule, in relation to the Contractor's Construction Schedule. Determine how construction behind schedule will be expedited; secure commitments from parties involved to do so. Discuss whether schedule revisions are required to ensure that current and subsequent activities will be completed within the Contract Time.
 - b. Review present and future needs of each entity present, including the following:
 - 1) Interface requirements.
 - 2) Sequence of operations.
 - 3) Status of submittals.
 - 4) Deliveries.
 - 5) Off-site fabrication.
 - 6) Access.
 - 7) Site utilization.
 - 8) Temporary facilities and controls.
 - 9) Work hours.
 - 10) Hazards and risks.
 - 11) Progress cleaning.
 - 12) Quality and work standards.
 - 13) Change Orders.

- 14) Documentation of information for payment requests.
2. Reporting: Distribute minutes of the meeting to each party present and to parties who should have been present. Include a brief summary, in narrative form, of progress since the previous meeting and report.
 - a. Schedule Updating: Revise the Contractor's Construction Schedule after each progress meeting where revisions to the schedule have been made or recognized. Issue revised schedule concurrently with the report of each meeting.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION (Not Used)

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 01 31 20
PAYROLL REPORTS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for schedules and reports required for proper performance of the Work, including:
 - 1. State of Delaware Payroll Reports.
- B. Related Sections: The following Sections contain requirements that relate to this Section:
 - 1. Division 00 Section "Supplementary General Conditions A201-2007" specifies requirements for submittal of the Schedule of Values.
 - 2. Division 01 Section "Project Management & Coordination" specifies requirements for submittal and distribution of meeting and conference minutes.

1.3 SUBMITTAL PROCEDURES

- A. Coordination: Coordinate preparation and processing of schedules and reports with performance of other construction activities.

1.4 PAYROLL REPORTS

- A. State of Delaware Payroll Reports: As required by the State of Delaware, Section 6960, Title 29, of the Delaware Code, payroll wages shall be reported weekly to the Delaware Department of Labor, Division of Industrial Affairs, 4425 North Market Street, Wilmington, DE 19802, phone 302-761-8200. Forms shall be available at the above address. A sample copy of the form is attached under contract forms, State of Delaware Payroll Report.

PART 2 - PRODUCTS (Not Applicable)

PART 3 - EXECUTION (Not Applicable)

END OF SECTION

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 01 32 00

CONSTRUCTION PROGRESS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for documenting the progress of construction during performance of the Work, including the following:

1. Preliminary Construction Schedule.
2. Contractor's Construction Schedule.
3. Submittals Schedule.
4. Daily construction reports.
5. Material location reports.
6. Field condition reports.
7. Construction photographs.

- B. Related Sections include the following:

1. Division 00 Section "Supplementary General Conditions A201-2007" for submitting the Schedule of Values.
2. Division 01 Section "Project Management and Coordination" for submitting and distributing meeting and conference minutes.
3. Division 01 Section "Submittal Procedures" for submitting schedules and reports.
4. Division 01 Section "Closeout Procedures" for submitting photographic negatives as Project Record Documents at Project closeout.

1.3 DEFINITIONS

- A. Activity: A discrete part of a project that can be identified for planning, scheduling, monitoring, and controlling the construction project. Activities included in a construction schedule consume time and resources.

- 1. Critical activities are activities on the critical path. They must start and finish on the planned early start and finish times.

- 2. Predecessor activity is an activity that must be completed before a given activity can be started.

- B. CPM: Critical path method, which is a method of planning and scheduling a construction project where activities are arranged based on activity relationships. Network calculations determine when activities can be performed and the critical path of Project.

- C. Critical Path: The longest continuous chain of activities through the network schedule that establishes the minimum overall Project duration and contains no float.

- D. Event: The starting or ending point of an activity.
- E. Float: The measure of leeway in starting and completing an activity.
 - 1. Float time is not for the exclusive use or benefit of either Owner or Contractor, but is a jointly owned, expiring Project resource available to both parties as needed to meet schedule milestones and Contract completion date.
 - 2. Free float is the amount of time an activity can be delayed without adversely affecting the early start of the following activity.
 - 3. Total float is the measure of leeway in starting or completing an activity without adversely affecting the planned Project completion date.
- F. Major Area: A story of construction, a separate building, or a similar significant construction element.
- G. Milestone: A key or critical point in time for reference or measurement.
- H. Network Diagram: A graphic diagram of a network schedule, showing activities and activity relationships.

1.4 SUBMITTALS

- A. Qualification Data: For firms and persons specified in "Quality Assurance" Article and in-house scheduling personnel to demonstrate their capabilities and experience. Include lists of completed projects with project names and addresses, names and addresses of architects and owners, and other information specified.
- B. Submittals Schedule: Submit three copies of schedule. Arrange the following information in a tabular format:
 - 1. Scheduled date for first submittal.
 - 2. Specification Section number and title.
 - 3. Submittal category (action or informational).
 - 4. Name of subcontractor.
 - 5. Description of the Work covered.
- C. Contractor's Construction Schedule: Submit three printed copies of initial schedule, one a reproducible print and one a blue- or black-line print, large enough to show entire schedule for entire construction period.
- D. CPM Reports: Concurrent with CPM schedule, submit three printed copies of each of the following computer-generated reports. Format for each activity in reports shall contain activity number, activity description, original duration, remaining duration, early start date, early finish date, late start date, late finish date, and total float.
 - 1. Activity Report: List of all activities sorted by activity number and then early start date, or actual start date if known.
 - 2. Logic Report: List of preceding and succeeding activities for all activities, sorted in ascending order by activity number and then early start date, or actual start date if known.
 - 3. Total Float Report: List of all activities sorted in ascending order of total float.

- E. Daily Construction Reports: Submit two copies at weekly intervals.
- F. Material Location Reports: Submit two copies at weekly intervals.
- G. Field Condition Reports: Submit two copies at weekly intervals.

1.5 QUALITY ASSURANCE

- A. Scheduling Consultant Qualifications: An experienced specialist in CPM scheduling and reporting.

1.6 COORDINATION

- A. Coordinate preparation and processing of schedules and reports with performance of construction activities and with scheduling and reporting of separate contractors.
- B. Coordinate Contractor's Construction Schedule with the Schedule of Values, list of subcontracts, Submittals Schedule, progress reports, payment requests, and other required schedules and reports.
 - 1. Secure time commitments for performing critical elements of the Work from parties involved.
 - 2. Coordinate each construction activity in the network with other activities and schedule them in proper sequence.

PART 2 - PRODUCTS

2.1 SUBMITTALS SCHEDULE

- A. Preparation: Submit a schedule of submittals, arranged in chronological order by dates required by construction schedule. Include time required for review, resubmittal, ordering, manufacturing, fabrication, and delivery when establishing dates.
 - 1. Coordinate Submittals Schedule with list of subcontracts, the Schedule of Values, and Contractor's Construction Schedule.
 - 2. Final Submittal: Submit concurrently with the first complete submittal of Contractor's Construction Schedule.

2.2 CONTRACTOR'S CONSTRUCTION SCHEDULE (CPM SCHEDULE)

- A. CPM Schedule: Prepare Contractor's Construction Schedule using a CPM network analysis diagram.
 - 1. Develop network diagram in sufficient time to submit CPM schedule so it can be accepted for use no later than 15 days after date established for the Notice to Proceed.
 - 2. Establish procedures for monitoring and updating CPM schedule and for reporting progress. Coordinate procedures with progress meeting and payment request dates.
 - 3. Use "one workday" as the unit of time.
- B. CPM Schedule Preparation: Prepare a list of all activities required to complete the Work. Using the preliminary network diagram, prepare a skeleton network to identify probable critical paths.

1. Activities: Indicate the estimated time duration, sequence requirements, and relationship of each activity in relation to other activities. Include estimated time frames for the following activities:
 - a. Preparation and processing of submittals.
 - b. Purchase of materials.
 - c. Delivery.
 - d. Fabrication.
 - e. Installation.
2. Processing: Process data to produce output data or a computer-drawn, time-scaled network. Revise data, reorganize activity sequences, and reproduce as often as necessary to produce the CPM schedule within the limitations of the Contract Time.
3. Format: Mark the critical path. Locate the critical path near center of network; locate paths with most float near the edges.
 - a. Subnetworks on separate sheets are permissible for activities clearly off the critical path.

2.3 REPORTS

- A. Daily Construction Reports: Prepare a daily construction report recording the following information concerning events at Project site:
 1. List of subcontractors at Project site.
 2. List of separate contractors at Project site.
 3. Approximate count of personnel at Project site.
 4. High and low temperatures and general weather conditions.
 5. Accidents.
 6. Meetings and significant decisions.
 7. Unusual events (refer to special reports).
 8. Stoppages, delays, shortages, and losses.
 9. Meter readings and similar recordings.
 10. Emergency procedures.
 11. Orders and requests of authorities having jurisdiction.
 12. Change Orders received and implemented.
 13. Construction Change Directives received.
 14. Services connected and disconnected.
 15. Equipment or system tests and startups.
 16. Partial Completions and occupancies.
 17. Substantial Completions authorized.
- B. Material Location Reports: At monthly intervals, prepare a comprehensive list of materials delivered to and stored at Project site. List shall be cumulative, showing materials previously reported plus items recently delivered. Include with list a statement of progress on and delivery dates for materials or items of equipment fabricated or stored away from Project site.
- C. Field Condition Reports: Immediately on discovery of a difference between field conditions and the Contract Documents, prepare a detailed report. Submit with a request for information. Include a detailed description of the differing conditions, together with recommendations for changing the Contract Documents.

PART 3 - EXECUTION (not used)

END OF SECTION

SECTION 01 33 00

SUBMITTAL PROCEDURES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for submitting Shop Drawings, Product Data, Samples, and other miscellaneous submittals.
- B. Related Sections include the following:
 - 1. Division 01 Section "Project Management and Coordination" for submitting Coordination Drawings.

1.3 DEFINITIONS

- A. Action Submittals: Written and graphic information that requires the Architect's responsive action.
- B. Informational Submittals: Written information that does not require the Architect's approval. Submittals may be rejected for not complying with requirements.

1.4 SUBMITTAL PROCEDURES

- A. General: Architect will provide electronic copies of CADD drawings of the Contract Drawings for Contractor's use in preparing submittals.
 - 1. Upon request contractor shall sign a release form provided by the Architect and payment of the processing fee for each consultant's CADD files. Only plan drawings and backgrounds to be provided.
- B. Coordination: Coordinate preparation and processing of submittals with performance of construction activities.
 - 1. Coordinate each submittal with fabrication, purchasing, testing, delivery, other submittals, and related activities that requires sequential activity.
 - 2. Coordinate transmittal of different types of submittals for related parts of the Work so processing will not be delayed because of need to review submittals concurrently for coordination.
 - a. The Architect reserves the right to withhold action on a submittal requiring coordination with other submittals until related submittals are received.

- C. Submittals Schedule: Comply with requirements in Division 1 Section "Construction Progress Documentation" for list of submittals and time requirements for scheduled performance of related construction activities.
- D. Processing Time: Allow enough time for submittal review, including time for resubmittals, as follows. Time for review shall commence on the Architect's receipt of submittal.
1. Initial Review: Allow 15 days for initial review of each submittal. Allow additional time if processing must be delayed to permit coordination with subsequent submittals. The Architect will advise the Contractor when a submittal being processed must be delayed for coordination.
 2. Concurrent Review: Where concurrent review of submittals by the Architect, Architect's consultants, the Owner, or other parties is required, allow 21 days for initial review of each submittal.
- E. Identification: Place a permanent label or title block on each submittal for identification.
1. Indicate name of firm or entity that prepared each submittal on label or title block.
 2. Provide a space approximately 4 by 5 inches (100 by 125 mm) on label or beside title block to record the Contractor's review and approval markings and action taken by the Architect.
 3. Include the following information on label for processing and recording action taken:
 - a. Project name.
 - b. Date.
 - c. Name and address of Architect.
 - d. Name and address of Contractor.
 - e. Name and address of subcontractor.
 - f. Name and address of supplier.
 - g. Name of manufacturer.
 - h. Number and title of appropriate Specification Section.
 - i. Drawing number and detail references, as appropriate.
- F. Deviations: Highlight, encircle, or otherwise identify deviations from the Contract Documents on submittals.
- G. Additional Copies: Unless additional copies are required for final submittal, and unless the Architect observes noncompliance with provisions of the Contract Documents, initial submittal may serve as final submittal.
1. Submit one copy of submittal to concurrent reviewer in addition to specified number of copies to the Architect.
 2. Additional copies submitted for maintenance manuals will not be marked with action taken and will be returned.
- H. Transmittal: Package each submittal individually and appropriately for transmittal and handling. Transmit each submittal using a transmittal form. The Architect will return submittals received from sources other than the Contractor.
1. On an attached separate sheet, prepared on the Contractor's letterhead, record relevant information, requests for data, revisions other than those requested by the Architect on previous submittals, and deviations from requirements of the Contract Documents,

- including minor variations and limitations. Include the same label information as the related submittal.
- 2. Include the Contractor's certification stating that information submitted complies with requirements of the Contract Documents.
- I. Use for Construction: Use only final submittals with mark indicating action taken by the Architect in connection with construction.

PART 2 - PRODUCTS

2.1 ACTION SUBMITTALS

- A. General: Prepare and submit Action Submittals required by individual Specification Sections.
 - 1. Number of Copies: Submit five copies of each submittal, unless otherwise indicated. The Architect will return two copies. Mark up and retain one returned copy as a Project Record Document.
- B. Product Data: Collect information into a single submittal for each element of construction and type of product or equipment.
 - 1. If information must be specially prepared for submittal because standard printed data are not suitable for use, submit as Shop Drawings, not as Product Data.
 - 2. Mark each copy of each submittal to show which products and options are applicable.
 - 3. Include the following information, as applicable:
 - a. Manufacturer's written recommendations.
 - b. Manufacturer's product specifications.
 - c. Manufacturer's installation instructions.
 - d. Standard color chart.
 - e. Manufacturer's catalog cuts.
 - f. Wiring diagrams showing factory-installed wiring.
 - g. Printed performance curves.
 - h. Operational range diagrams.
 - i. Mill reports.
 - j. Standard product operating and maintenance manuals.
 - k. Compliance with recognized trade association standards.
 - l. Compliance with recognized testing agency standards.
 - m. Application of testing agency labels and seals.
 - n. Notation of coordination requirements.
- C. Shop Drawings: Prepare Project-specific information, drawn accurately to scale. Do not base Shop Drawings on reproductions of the Contract Documents or standard printed data.
 - 1. Preparation: Include the following information, as applicable:
 - a. Dimensions.
 - b. Identification of products.
 - c. Fabrication and installation drawings.
 - d. Roughing-in and setting diagrams.

- e. Wiring diagrams showing field-installed wiring, including power, signal, and control wiring.
- f. Shop work manufacturing instructions.
- g. Templates and patterns.
- h. Schedules.
- i. Design calculations.
- j. Compliance with specified standards.
- k. Notation of coordination requirements.
- l. Notation of dimensions established by field measurement.
2. Number of Copies: Submit one correctable, translucent, reproducible print and six blue- or black-line print of each submittal. The Architect will return the reproducible print.
- D. Samples: Prepare physical units of materials or products, including the following:
1. Samples for Verification: Submit full-size units or Samples of size indicated, prepared from the same material to be used for the Work, cured and finished in manner specified, and physically identical with the product proposed for use, and that show full range of color and texture variations expected. Samples include, but are not limited to, the following: partial sections of manufactured or fabricated components; small cuts or containers of materials; complete units of repetitive used materials; swatches showing color, texture, and pattern; color range sets; and components used for independent testing and inspection.
 2. Submit Samples for review of kind, color, pattern, and texture for a final check of these characteristics with other elements and for a comparison of these characteristics between final submittal and actual component as delivered and installed.
 - a. If variation in color, pattern, texture, or other characteristic is inherent in the product represented by a Sample, submit at least two sets of paired units that show approximate limits of the variations.
 - b. Refer to individual Specification Sections for requirements for Samples that illustrate workmanship, fabrication techniques, details of assembly, connections, operation, and similar construction characteristics.
 3. Disposition: Maintain sets of approved Samples at Project site, available for quality-control comparisons throughout the course of construction activity. Sample sets may be used to determine final acceptance of construction associated with each set.
 - a. Samples that may be incorporated into the Work are indicated in individual Specification Sections. Such Samples must be in an undamaged condition at time of use.
- E. Product Schedule or List: Prepare a written summary indicating types of products required for the Work and their intended location. Include the following information in tabular form:
1. Type of product. Include unique identifier for each product.
 2. Number and name of room or space.
 3. Location within room or space.
- F. Submittals Schedule: Comply with requirements in Division 1 Section "Construction Progress Documentation."

- G. Application for Payment: Comply with requirements in Division 1 Section “Payment Procedures.”
- H. Schedule of Values: Comply with requirements in Division 1 Section “Payment Procedures.”

2.2 INFORMATIONAL SUBMITTALS

- A. General: Prepare and submit Informational Submittals required by other Specification Sections.
 - 1. Number of Copies: Submit one copies of each submittal, unless otherwise indicated. The Architect will not return copies.
 - 2. Certificates and Certifications: Provide a notarized statement that includes signature of entity responsible for preparing certification. Certificates and certifications shall be signed by an officer or other individual authorized to sign documents on behalf of that entity.
 - 3. Test and Inspection Reports: Comply with requirements in Division 1 Section “Quality Requirements.”
- B. Qualification Data: Prepare written information that demonstrates capabilities and experience of firm or person. Include lists of completed projects with project names and addresses, names and addresses of architects and owners, and other information specified.
- C. Product Certificates: Prepare written statements on manufacturer’s letterhead certifying that product complies with requirements.
- D. Welding Certificates: Prepare written certification that welding procedures and personnel comply with requirements. Submit record of Welding Procedure Specification (WPS) and Procedure Qualification Record (PQR) or AWS forms. Include names of firms and personnel certified.
- E. Installer Certificates: Prepare written statements on manufacturer’s letterhead certifying that Installer complies with requirements and, where required, is authorized for this specific Project.
- F. Manufacturer Certificates: Prepare written statements on manufacturer’s letterhead certifying that manufacturer complies with requirements. Include evidence of manufacturing experience where required.
- G. Material Certificates: Prepare written statements on manufacturer’s letterhead certifying that material complies with requirements.
- H. Material Test Reports: Prepare reports written by a qualified testing agency, on testing agency’s standard form, indicating and interpreting test results of material for compliance with requirements.
- I. Preconstruction Test Reports: Prepare reports written by a qualified testing agency, on testing agency’s standard form, indicating and interpreting results of tests performed before installation of product, for compliance with performance requirements.
- J. Compatibility Test Reports: Prepare reports written by a qualified testing agency, on testing agency’s standard form, indicating and interpreting results of compatibility tests performed before installation of product. Include written recommendations for primers and substrate preparation needed for adhesion.

- K. Field Test Reports: Prepare reports written by a qualified testing agency, on testing agency's standard form, indicating and interpreting results of field tests performed either during installation of product or after product is installed in its final location, for compliance with requirements.
- L. Product Test Reports: Prepare written reports indicating current product produced by manufacturer complies with requirements. Base reports on evaluation of tests performed by manufacturer and witnessed by a qualified testing agency, or on comprehensive tests performed by a qualified testing agency.
- M. Research/Evaluation Reports: Prepare written evidence, from a model code organization acceptable to authorities having jurisdiction, that product complies with building code in effect for Project. Include the following information:
1. Name of evaluation organization.
 2. Date of evaluation.
 3. Time period when report is in effect.
 4. Product and manufacturers' names.
 5. Description of product.
 6. Test procedures and results.
 7. Limitations of use.
- N. Maintenance Data: Prepare written and graphic instructions and procedures for operation and normal maintenance of products and equipment. Comply with requirements in Division 1 Section "Closeout Procedures".
- O. Design Data: Prepare written and graphic information, including, but not limited to, performance and design criteria, list of applicable codes and regulations, and calculations. Include list of assumptions and other performance and design criteria and a summary of loads. Include load diagrams if applicable. Provide name and version of software, if any, used for calculations. Include page numbers.
- P. Manufacturer's Instructions: Prepare written or published information that documents manufacturer's recommendations, guidelines, and procedures for installing or operating a product or equipment. Include name of product and name, address, and telephone number of manufacturer. Include the following, as applicable:
1. Preparation of substrates.
 2. Required substrate tolerances.
 3. Sequence of installation or erection.
 4. Required installation tolerances.
 5. Required adjustments.
 6. Recommendations for cleaning and protection.
- Q. Manufacturer's Field Reports: Prepare written information documenting factory-authorized service representative's tests and inspections. Include the following, as applicable:
1. Name, address, and telephone number of factory-authorized service representative making report.
 2. Statement on condition of substrates and their acceptability for installation of product.
 3. Statement that products at Project site comply with requirements.
 4. Summary of installation procedures being followed, whether they comply with requirements and, if not, what corrective action was taken.

5. Results of operational and other tests and a statement of whether observed performance complies with requirements.
 6. Statement whether conditions, products, and installation will affect warranty.
 7. Other required items indicated in individual Specification Sections.
- R. Insurance Certificates and Bonds: Prepare written information indicating current status of insurance or bonding coverage. Include name of entity covered by insurance or bond, limits of coverage, amounts of deductibles, if any, and term of the coverage.

PART 3 - EXECUTION

3.1 CONTRACTOR'S REVIEW

- A. Review each submittal and check for compliance with the Contract Documents. Note corrections and field dimensions. Mark with approval stamp before submitting to the Architect.
- B. Approval Stamp: Stamp each submittal with a uniform, approval stamp. Include Project name and location, submittal number, Specification Section title and number, name of reviewer, date of the Contractor's approval, and statement certifying that submittal has been reviewed, checked, and approved for compliance with the Contract Documents.

3.2 ARCHITECT'S ACTION

- A. General: The Architect will not review submittals that do not bear the Contractor's approval stamp and will return them without action.
- B. Action Submittals: The Architect will review each submittal, make marks to indicate corrections or modifications required, and return it. The Architect will stamp each submittal with an action stamp and will mark stamp appropriately to indicate action taken, as follows:
- C. Informational Submittals: The Architect will review each submittal and will not return it, or will reject and return it if it does not comply with requirements. The Architect will forward each submittal to appropriate party.
- D. Submittals not required by the Contract Documents will not be reviewed and may be discarded.

END OF SECTION

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 01 33 01

CADD RELEASE

Use and Indemnification Agreement - INSTRUCTIONS

USE AND INDEMNIFICATION AGREEMENT

Please be aware that Tetra Tech charges contractor(s) for electronic files (this applies to files in AutoCAD (or similar) format).

PDF's, which are simply an electronic scan of the drawings, do not require the use of the indemnification form; however we charge \$50 per PDF to cover our expenses. Tetra Tech must receive the contractor's check prior to sending PDF's.

For AutoCAD type files, the cost is \$100. The Use and Indemnification Agreement is to be signed by the Prime Contractor. Should a subcontractor, such as a steel fabricator, ductwork detailer, desire electronic files, they would need to pursue this request through their Prime Contractor who has the contract with the Client.

Due to the inherent value to the company of our typical details and our other standards, we limit the drawings types that we will release via this indemnification form to plan type drawings. Typical detail sheets are not to be released in the form of an electronic AutoCAD drawing file.

In addition, our internal individual Base Plans will not be released; we limit what the contractor can purchase to the actual individual contract drawings.

After the Prime Contractor has determined the number of drawings that they will need, fill out the following two pages. The second page of the form, marked Use and Indemnification Agreement – Business Office, needs to be sent to the Business Office with the Contractor check made out to Tetra Tech. We will not release electronic files until we receive this form and the check.



240 Continental Drive, Suite 200
Newark, Delaware 19713
Tel. (302) 738-7551
Fax (302) 454-5980

Use and Indemnification Agreement

Re: HVAC Improvements for Stokes Elementary School

Tt Project No. 200-163183-17001-07

Whereas, _____ (hereinafter the "Contractor"), acknowledges that it has requested certain electronic files and/or media of Drawings and/or Specifications for the above-referenced Project which are the property of Tetra Tech Engineers, Architects & Landscape Architects, P.C. d/b/a Tetra Tech Architects & Engineers (hereinafter "Tetra Tech").

Whereas, Contractor further acknowledges all requests for electronic files require a pre-payment of \$100, regardless of the number of files requested, prior to receiving said files from Tetra Tech.

Now, therefore, Contractor hereby warrants and covenants that it will abide by the following provisions:

A. Indemnification

- In consideration of permission to use electronic files or media, including but not limited to electronic files of drawings created by use of computer, for the Work of this Project only, and which the Contractor has requested from Tetra Tech, the Contractor, to the fullest extent permitted by law, hereby agrees to indemnify and hold harmless Tetra Tech, its agents, employees, officers, directors and consultants from and against any and all claims, damages, losses and expenses, including any attorneys' fees, arising out of, resulting from or in connection with any and all use of said electronic materials, but only if such claim, damage, loss or expense is caused in whole or in part by the Contractor, its employees, agents, officers, directors, or any other party directly or indirectly employed by any of them or any party for whose acts any of them may be liable, regardless of whether or not it is caused by a party indemnified hereunder. Such obligation shall not be construed to reduce or negate any other right or obligation of indemnification that would otherwise exist as to any party hereto. This indemnification shall not apply to the liability of the indemnitee arising out of its own negligence. This indemnification shall not be limited in any way because of any limitation on damages, compensation or benefits under any statute, law or governmental requirement of any sort.
- The following shall be included within the definition of "expenses" herein: (a) any time expended by the indemnified party of its employees, agents, officers and directors at their usual and customary billing rates, as well as all out-of-pocket expenses such as long-distance telephone calls, costs of reproduction, expenses of travel and lodging; (b) all costs and expenses of experts, consultants, engineers, and any other party retained by the indemnified party reasonably required to defend the claim; (c) all costs, including reasonable attorneys' fees, incurred in bringing any action to enforce the provisions of this indemnification. The following shall be included within the definition of "action" herein: any case brought in any state or federal court, any arbitration, any mediation, and any similar forum for resolution of any dispute herein, and shall also include any counterclaim or third-party action in any such forum.

B. Use and Compatibility

- Tetra Tech' instruments of service are furnished without guarantee of compatibility with the Contractor's software or hardware, and Tetra Tech' sole responsibility for the electronic media is to furnish a replacement for defective disks within thirty (30) days after delivery to Contractor.
- Because data stored on electronic media can deteriorate undetected or be modified without Tetra Tech' knowledge, the Contractor agrees that Tetra Tech will not be held liable for the completeness or correctness of the electronic media after an acceptance period of thirty (30) days after delivery of the electronic files. Tetra Tech does confirm the accuracy of the final sealed hard copy drawings, previously submitted pursuant to the Prime Agreement for this Project.
- The electronic files are submitted to the Contractor for a thirty (30) day acceptance period. During this period, the Contractor may review and examine these files and any errors detected during this time will be corrected by Tetra Tech. Any changes requested after the acceptance period will be considered additional services to be performed on a time and materials basis, at Tetra Tech's standard cost plus terms and conditions.
- Tetra Tech retains ownership of the printed hard copy Drawings and Specifications and the electronic media. The Contractor is granted a license for their use, but only in the operation and maintenance of the Project. Use of these materials for modification, extension, or expansion of this Project or on any other project, unless under the direction of Tetra Tech, shall be without liability to Tetra Tech and Tetra Tech's consultants.

IN WITNESS WHEREOF:

Contractor: _____
Signed name: _____
Printed Name: _____
Title: _____
Date: _____

If transmission is not received as noted, kindly notify us at once.



Use and Indemnification Agreement – Business Office

.....
Electronic Drawing Files

Prime Contractor Name

Prime Contractor Address

Contact to Receive Invoices

Project Name HVAC Improvements - Stokes Elementary School

Project Number 200-163183-17001-07

Number of Drawing Files (Each individual drawing in the set of Contract Documents represents 1 file)

List each Drawing # Requested

Contractor Signature _____

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 01 50 00

TEMPORARY FACILITIES AND CONTROLS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes requirements for temporary facilities and controls including temporary utilities, support facilities, and security and protection facilities.

- B. Temporary utilities include, but are not limited to, the following:

1. Sewers and drainage.
2. Water service and distribution.
3. Sanitary facilities, including toilets, wash facilities, and drinking-water facilities.
4. Heating and cooling facilities.
5. Ventilation.
6. Electric power service.
7. Lighting.
8. Telephone service.

- C. Support facilities include, but are not limited to, the following:

1. Temporary roads and paving.
2. Dewatering facilities and drains.
3. Project identification and temporary signs.
4. Waste disposal facilities.
5. Field offices.
6. Storage and fabrication sheds.
7. Lifts and hoists.
8. Temporary elevator usage.
9. Temporary stairs.
10. Construction aids and miscellaneous services and facilities.

- D. Security and protection facilities include, but are not limited to, the following:

1. Environmental protection.
2. Storm water control.
3. Tree and plant protection.
4. Pest control.
5. Site enclosure fence.
6. Security enclosure and lockup.
7. Barricades, warning signs, and lights.
8. Covered walkways.
9. Temporary enclosures.

10. Temporary partitions.
11. Fire protection.

E. Related Sections include the following:

1. Division 01 Section "Submittal Procedures" for procedures for submitting copies of implementation and termination schedule and utility reports.

1.3 USE CHARGES

- A. Temporary water and electric will be provided by the Owner.

1.4 QUALITY ASSURANCE

- A. Standards: Comply with ANSI A10.6, NECA's "Temporary Electrical Facilities," and NFPA 241.
1. Trade Jurisdictions: Assigned responsibilities for installation and operation of temporary utilities are not intended to interfere with trade regulations and union jurisdictions.
 2. Electric Service: Comply with NECA, NEMA, and UL standards and regulations for temporary electric service. Install service to comply with NFPA 70.
- B. Tests and Inspections: Arrange for authorities having jurisdiction to test and inspect each temporary utility before use. Obtain required certifications and permits.

1.5 PROJECT CONDITIONS

- A. Temporary Utilities: At earliest feasible time, when acceptable to the Owner, change over from use of temporary service to use of permanent service.
1. Temporary Use of Permanent Facilities: Installer of each permanent service shall assume responsibility for operation, maintenance, and protection of each permanent service during its use as a construction facility before the Owner's acceptance, regardless of previously assigned responsibilities.
- B. Conditions of Use: The following conditions apply to use of temporary services and facilities by all parties engaged in the Work:
1. Keep temporary services and facilities clean and neat.
 2. Relocate temporary services and facilities as required by progress of the Work.


PART 2 - PRODUCTS

2.1 MATERIALS

- A. General: Provide new materials. Undamaged, previously used materials in serviceable condition may be used if approved by the Architect. Provide materials suitable for use intended.

2.2 EQUIPMENT

- A. General: Provide equipment suitable for use intended.



- B. Fire Extinguishers: Hand carried, portable, UL rated. Provide class and extinguishing agent as indicated or a combination of extinguishers of NFPA-recommended classes for exposures.
 - 1. Comply with NFPA 10 and NFPA 241 for classification, extinguishing agent, and size required by location and class of fire exposure.
- C. Self-Contained Toilet Units: Single-occupant units of chemical, aerated recirculation or combustion type; vented; fully enclosed with a glass-fiber-reinforced polyester shell or similar nonabsorbent material.
- D. Heating Equipment: Unless the Owner authorizes use of permanent heating system, provide vented, self-contained, liquid-propane-gas or fuel-oil heaters with individual space thermostatic control.
 - 1. Use of gasoline-burning space heaters, open-flame heaters, or salamander-type heating units is prohibited.
 - 2. Heating Units: Listed and labeled, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use for type of fuel being consumed.
- E. Electrical Outlets: Properly configured, NEMA-polarized outlets to prevent insertion of 110- to 120-V plugs into higher-voltage outlets; equipped with ground-fault circuit interrupters, reset button, and pilot light.
- F. Power Distribution System Circuits: Where permitted and overhead and exposed for surveillance, wiring circuits, not exceeding 125-V ac, 20-A rating, and lighting circuits may be nonmetallic sheathed cable.

PART 3 - EXECUTION

3.1 INSTALLATION, GENERAL

- A. Locate facilities where they will serve the Project adequately and result in minimum interference with performance of the Work. Relocate and modify facilities as required.
- B. Provide each facility ready for use when needed to avoid delay. Maintain and modify as required. Do not remove until facilities are no longer needed or are replaced by authorized use of completed permanent facilities.

3.2 TEMPORARY UTILITY INSTALLATION

- A. Water Service: Use of the Owner's existing water service facilities will be permitted, as long as facilities are cleaned and maintained in a condition acceptable to the Owner. At Substantial Completion, restore these facilities to condition existing before initial use.
 - 1. Provide rubber hoses as necessary to serve the Project site.
 - 2. Where installations below an outlet might be damaged by spillage or leakage, provide a drip pan of suitable size to minimize water damage. Drain accumulated water promptly from pans.
- B. Sanitary Facilities: Provide temporary toilets, wash facilities, and drinking-water fixtures. Comply with regulations and health codes for type, number, location, operation, and maintenance of fixtures and facilities.

1. Disposable Supplies: Provide toilet tissue, paper towels, paper cups, and similar disposable materials for each facility. Maintain adequate supply. Provide covered waste containers for disposal of used material.
 2. Toilets: Use of the Owner's existing toilet facilities will not be permitted, as long as facilities are cleaned and maintained in a condition acceptable to the Owner. At Substantial Completion, restore these facilities to condition existing before initial use.
- C. Heating and Cooling: Provide temporary heating and cooling required by construction activities for curing or drying of completed installations or for protecting installed construction from adverse effects of low temperatures or high humidity. Select equipment from that specified that will not have a harmful effect on completed installations or elements being installed.
1. Maintain a minimum temperature of 50 deg F (10 deg C) in permanently enclosed portions of building for normal construction activities, and 65 deg F (18.3 deg C) for finishing activities and areas where finished Work has been installed.
- D. Electric Power Service: Use of the Owner's existing electric power service will be permitted, as long as equipment is maintained in a condition acceptable to the Owner.
- E. Electric Distribution: Provide receptacle outlets adequate for connection of power tools and equipment.
1. Provide waterproof connectors to connect separate lengths of electrical power cords if single lengths will not reach areas where construction activities are in progress. Do not exceed safe length-voltage ratio.
- F. Telephone Service:
1. Provide a portable cellular telephone for superintendent's use in making and receiving telephone calls when away from field office.
- G. Waste Disposal Facilities: Provide waste collection containers in sizes adequate to handle waste from construction operations. Containerize and clearly label hazardous, dangerous, or unsanitary waste materials separately from other waste.
1. If required by authorities having jurisdiction, provide separate containers, clearly labeled, for each type of waste material to be deposited.
- 3.3 OPERATION, TERMINATION, AND REMOVAL
- A. Termination and Removal: Remove each temporary facility when need for its service has ended, when it has been replaced by authorized use of a permanent facility, or no later than Substantial Completion. Complete or, if necessary, restore permanent construction that may have been delayed because of interference with temporary facility. Repair damaged Work, clean exposed surfaces, and replace construction that cannot be satisfactorily repaired.
1. Materials and facilities that constitute temporary facilities are the property of the Contractor. The Owner reserves right to take possession of the Project identification signs.
 2. At Substantial Completion, clean and renovate permanent facilities used during construction period. Comply with final cleaning requirements in Division 1 Section "Closeout Procedures."

END OF SECTION

SECTION 01 63 10

SUBSTITUTIONS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Requests for substitution must be made ten days prior to bid. This specification section applies to extra-ordinary conditions that could not be requested during the bidding period.
- B. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for handling requests for substitutions made after award of the Contract, but no later than 60 days after commencement of the Work.
- B. Related Sections: The following Divisions contain requirements that relate to this Section:
 - 1. Division 01 specifies the applicability of industry standards to products specified.
 - 2. Division 01 specifies requirements for submitting the Contractor's Construction Schedule and the Submittal Schedule.
 - 3. Division 01 specifies requirements governing the Contractor's selection of products and product options.

1.3 DEFINITIONS

- A. Definitions in this Article do not change or modify the meaning of other terms used in the Contract Documents.
- B. Substitutions: Changes in products, materials, equipment, and methods of construction required by the Contract Documents proposed by the Contractor after award of the Contract are considered to be requests for substitutions. The following are not considered to be requests for substitutions:
 - 1. Substitutions requested during the bidding period, and accepted by Addendum prior to award of the Contract, are included in the Contract Documents and are not subject to requirements specified in this Section for substitutions.
 - 2. Revisions to the Contract Documents requested by the Owner or Architect.
 - 3. Specified options of products and construction methods included in the Contract Documents.
 - 4. The Contractor's determination of and compliance with governing regulations and orders issued by governing authorities.

1.4 SUBMITTALS

- A. Substitution Request Submittal: Substitution requests will only be considered during the bidding period. Substitutions will not be considered after the bids are accepted.

1. Submit three copies of each request for substitution for consideration. Submit requests in the form and according to procedures required for change-order proposals. The Contractor is solely responsible for obtaining the required forms to submit before the stated time period expires.
2. Identify the product or the fabrication or installation method to be replaced in each request. Include related Specification Section and Drawing numbers.
3. Provide complete documentation showing compliance with the requirements for substitutions, and the following information, as appropriate:
 - a. Coordination information, including a list of changes or modifications needed to other parts of the Work and to construction performed by the Owner and separate contractors that will be necessary to accommodate the proposed substitution.
 - b. A detailed comparison of significant qualities of the proposed substitution with those of the Work specified. Significant qualities may include elements, such as performance, weight, size, durability, and visual effect.
 - c. Product Data, including Drawings and descriptions of products and fabrication and installation procedures.
 - d. Samples, where applicable or requested.
 - e. A statement indicating the substitution's effect on the Contractor's Construction Schedule compared to the schedule without approval of the substitution. Indicate the effect of the proposed substitution on overall Contract Time.
 - f. Cost information, including a proposal of the net change, if any in the Contract Sum.
 - g. The Contractor's certification that the proposed substitution conforms to requirements in the Contract Documents in every respect and is appropriate for the applications indicated.
 - h. The Contractor's waiver of rights to additional payment or time that may subsequently become necessary because of the failure of the substitution to perform adequately.
4. Architect's Action: If necessary, the Architect will request additional information or documentation for evaluation within one week of receipt of a request for substitution. The Architect will notify the Contractor of acceptance or rejection of the substitution within two weeks of receipt of the request, or one week of receipt of additional information or documentation, whichever is later.
 - a. Use the product specified if the Architect cannot make a decision on the use of a proposed substitute within the time allocated.

PART 2 PRODUCTS

2.1 SUBSTITUTIONS

- A. Conditions: The Architect will receive and consider the Contractor's request for substitution when the following conditions are satisfied, as determined by the Architect. If the following conditions are not satisfied, the Architect will return the requests without action except to record noncompliance with these requirements.
 1. Revisions to the Contract Documents are not required.
 2. Proposed changes are in keeping with the general intent of the Contract Documents.
 3. The request is timely, fully documented, and properly submitted.
 4. The specified product or method of construction cannot be provided within the Contract Time. The Architect will not consider the request if the product or method cannot be

provided as a result of failure to pursue the Work promptly or coordinate activities properly.

5. The requested substitution offers the Owner a substantial advantage, in cost, time, energy conservation, or other considerations, after deducting additional responsibilities the Owner must assume. The Owner's additional responsibilities may include compensation to the Architect for redesign and evaluation services, increased cost of other construction by the Owner, and similar considerations.
 6. The specified product or method of construction cannot receive necessary approval by a governing authority, and the requested substitution can be approved.
 7. The specified product or method of construction cannot be provided in a manner that is compatible with other materials and where the Contractor certifies that the substitution will overcome the incompatibility.
 8. The specified product or method of construction cannot be coordinated with other materials and where the Contractor certifies that the proposed substitution can be coordinated.
- B. The Contractor's submittal and the Architect's acceptance of Shop Drawings, Product Data, or Samples for construction activities not complying with the Contract Documents do not constitute an acceptable or valid request for substitution, nor do they constitute approval.

PART 3 - EXECUTION (Not Applicable)

END OF SECTION

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 01 73 29
CUTTING & PATCHING

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes procedural requirements for cutting and patching.
- B. Related Sections include the following:
 - 1. Divisions 02 through 07 Sections for specific requirements and limitations applicable to cutting and patching individual parts of the Work.

1.3 DEFINITIONS

- A. Cutting: Removal of in-place construction necessary to permit installation or performance of other Work.
- B. Patching: Fitting and repair work required to restore surfaces to original conditions after installation of other Work.

1.4 QUALITY ASSURANCE

- A. Structural Elements: Do not cut and patch structural elements in a manner that could change their load-carrying capacity or load-deflection ratio.
- B. Operational Elements: Do not cut and patch operating elements and related components in a manner that results in reducing their capacity to perform as intended or that result in increased maintenance or decreased operational life or safety. Operating elements include the following: List below is an example only. Revise to suit Project's operating systems. With advice of counsel, delete below if Architect's approval is not required. If list is deleted, delete option in paragraph above.
 - 1. Fire-suppression systems.
 - 2. Mechanical systems piping and ducts.
 - 3. Control systems.
 - 4. Communication systems.
 - 5. Conveying systems.

6. Electrical wiring systems.
 - C. Visual Requirements: Do not cut and patch construction in a manner that results in visual evidence of cutting and patching. Do not cut and patch construction exposed on the exterior or in occupied spaces in a manner that would, in Architect's opinion, reduce the building's aesthetic qualities. Remove and replace construction that has been cut and patched in a visually unsatisfactory manner.
 - D. Cutting and Patching Conference: Before proceeding, meet at Project site with parties involved in cutting and patching, including mechanical and electrical trades. Review areas of potential interference and conflict. Coordinate procedures and resolve potential conflicts before proceeding.

PART 2 - PRODUCTS

2.1 MATERIALS

- A. General: Comply with requirements specified in other Sections.
- B. In-Place Materials: Use materials identical to in-place materials. For exposed surfaces, use materials that visually match in-place adjacent surfaces to the fullest extent possible.
 1. If identical materials are unavailable or cannot be used, use materials that, when installed, will match the visual and functional performance of in-place materials.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine surfaces to be cut and patched and conditions under which cutting and patching are to be performed.
 1. Compatibility: Before patching, verify compatibility with and suitability of substrates, including compatibility with in-place finishes or primers.
 2. Proceed with installation only after unsafe or unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Temporary Support: Provide temporary support of Work to be cut.
- B. Protection: Protect in-place construction during cutting and patching to prevent damage. Provide protection from adverse weather conditions for portions of Project that might be exposed during cutting and patching operations.

- C. Adjoining Areas: Avoid interference with use of adjoining areas or interruption of free passage to adjoining areas.
- D. Existing Utility Services and Mechanical/Electrical Systems: Where existing services/systems are required to be removed, relocated, or abandoned, bypass such services/systems before cutting to prevent interruption to occupied areas.

3.3 PERFORMANCE

- A. General: Employ skilled workers to perform cutting and patching. Proceed with cutting and patching at the earliest feasible time, and complete without delay.
 - 1. Cut in-place construction to provide for installation of other components or performance of other construction, and subsequently patch as required to restore surfaces to their original condition.
- B. Cutting: Cut in-place construction by sawing, drilling, breaking, chipping, grinding, and similar operations, including excavation, using methods least likely to damage elements retained or adjoining construction. If possible, review proposed procedures with original Installer; comply with original Installer's written recommendations.
 - 1. In general, use hand or small power tools designed for sawing and grinding, not hammering and chopping. Cut holes and slots as small as possible, neatly to size required, and with minimum disturbance of adjacent surfaces. Temporarily cover openings when not in use.
 - 2. Finished Surfaces: Cut or drill from the exposed or finished side into concealed surfaces.
 - 3. Concrete or Masonry: Cut using a cutting machine, such as an abrasive saw or a diamond-core drill.
 - 4. Mechanical and Electrical Services: Cut off pipe or conduit in walls or partitions to be removed. Cap, valve, or plug and seal remaining portion of pipe or conduit to prevent entrance of moisture or other foreign matter after cutting.
 - 5. Proceed with patching after construction operations requiring cutting are complete.
- C. Patching: Patch construction by filling, repairing, refinishing, closing up, and similar operations following performance of other Work. Patch with durable seams that are as invisible as possible. Provide materials and comply with installation requirements specified in other Sections.
 - 1. Inspection: Where feasible, test and inspect patched areas after completion to demonstrate integrity of installation.
 - 2. Exposed Finishes: Restore exposed finishes of patched areas and extend finish restoration into retained adjoining construction in a manner that will eliminate evidence of patching and refinishing.
 - a. Clean piping, conduit, and similar features before applying paint or other finishing materials.
 - b. Restore damaged pipe covering to its original condition.
 - 3. Floors and Walls: Where walls or partitions that are removed extend one finished area into another, patch and repair floor and wall surfaces in the new space. Provide an even

surface of uniform finish, color, texture, and appearance. Remove in-place floor and wall coverings and replace with new materials, if necessary, to achieve uniform color and appearance.

- a. Where patching occurs in a painted surface, apply primer and intermediate paint coats over the patch and apply final paint coat over entire unbroken surface containing the patch. Provide additional coats until patch blends with adjacent surfaces.
 4. Ceilings: Patch, repair, or rehang in-place ceilings as necessary to provide an even-plane surface of uniform appearance.
 5. Exterior Building Enclosure: Patch components in a manner that restores enclosure to a weathertight condition.
- D. Cleaning: Clean areas and spaces where cutting and patching are performed. Completely remove paint, mortar, oils, putty, and similar materials.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 01 74 19

CONSTRUCTION WASTE MANAGEMENT

PART 1 – GENERAL

1.1 SUMMARY

- A. Section includes: Administrative and procedural requirements for construction waste management activities.

1.2 DEFINITIONS

- A. Construction, Demolition, and Land clearing (CDL) Waste: Includes all non-hazardous solid wastes resulting from construction, remodeling, alterations, repair, demolition and land clearing. Includes material that is recycled, reused, salvaged or disposed as garbage.
- B. Salvage: Recovery of materials for on-site reuse, sale or donation to a third party.
- C. Reuse: Making use of a material without altering its form. Materials can be reused on-site or reused on other projects off-site. Examples include, but are not limited to the following: Crushing or grinding of concrete for use as sub-base material. Chipping of land clearing debris for use as mulch.
- D. Recycling: The process of sorting, cleaning, treating, and reconstituting materials for the purpose of using the material in the manufacture of a new product.
- E. Source-Separated CDL Recycling: The process of separating recyclable materials in separate containers as they are generated on the job-site. The separated materials are hauled directly to a recycling facility or transfer station.
- F. Co-mingled CDL Recycling: The process of collecting mixed recyclable materials in one container on-site. The container is taken to a material recovery facility where materials are separated for recycling.
- G. Approved Recycling Facility: Any of the following:
 - 1. A facility that can legally accept CDL waste materials for the purpose of processing the materials into an altered form for the manufacture of a new product.
 - 2. Material Recovery Facility: A general term used to describe a waste-sorting facility. Mechanical, hand-separation, or a combination of both procedures, are used to recover recyclable materials.

1.3 SUBMITTALS

- A. Contractor shall develop a Waste Management Plan: Submit 3 copies of plan within 14 days of date established for the **Notice to Proceed**.
- B. Contractor shall provide Waste Management Report: Concurrent with each Application for Payment, submit 3 copies of report.

1.4 PERFORMANCE REQUIREMENTS

- A. General: Divert a minimum of **75%** CDL waste, by weight, from the landfill by one, or a combination of the following activities:
 - 1. Salvage
 - 2. Reuse
 - 3. Source-Separated CDL Recycling
 - 4. Co-mingled CDL Recycling

- B. CDL waste materials that can be salvaged, reused or recycled include, but are not limited to, the following:
 - 1. Acoustical ceiling tiles
 - 2. Asphalt
 - 3. Asphalt shingles
 - 4. Cardboard packaging
 - 5. Carpet and carpet pad
 - 6. Concrete
 - 7. Drywall
 - 8. Fluorescent lights and ballasts
 - 9. Land clearing debris (vegetation, stumpage, dirt)
 - 10. Metals
 - 11. Paint (through hazardous waste outlets)
 - 12. Wood
 - 13. Plastic film (sheeting, shrink wrap, packaging)
 - 14. Window glass
 - 15. Wood
 - 16. Field office waste, including office paper, aluminum cans, glass, plastic, and office cardboard.

1.4 QUALITY ASSURANCE

- A. Waste Management Coordinator Qualifications: Experienced firm, with a record of successful waste management coordination of projects with similar requirements, that employs a LEED Accredited Professional, certified by the USGBC as waste management coordinator.

- B. Regulatory Requirements: Conduct construction waste management activities in accordance with hauling and disposal regulations of all authorities having jurisdiction and all other applicable laws and ordinances.

- C. Preconstruction Conference: Schedule and conduct meeting at Project site prior to construction activities.
 - 1. Attendees: Inform the following individuals, whose presence is required, of date and time of meeting.
 - a. Owner
 - b. Architect
 - c. Contractor's superintendent

NOT FOR BIDDING PURPOSES

- d. Major subcontractors
 - e. Waste Management Coordinator
 - f. Other concerned parties.
2. Agenda Items: Review methods and procedures related to waste management including, but not limited to, the following:
 - a. Review and discuss waste management plan including responsibilities of Waste Management Coordinator.
 - b. Review requirements for documenting quantities of each type of waste and its disposition.
 - c. Review and finalize procedures for materials separation and verify availability of containers and bins needed to avoid delays.
 - d. Review procedures for periodic waste collection and transportation to recycling and disposal facilities.
 - e. Review waste management requirements for each trade.
 3. Minutes: Record discussion. Distribute meeting minutes to all participants.
Note: If there is a Project Architect, they will perform this role.
- 1.5 WASTE MANAGEMENT PLAN – Contactor shall develop and document the following:
- A. Develop a plan to meet the requirements listed in this section at a minimum. Plan shall consist of waste identification, waste reduction plan and cost/revenue analysis. Distinguish between demolition and construction waste. Indicate quantities by weight throughout the plan.
 - B. Indicate anticipated types and quantities of demolition, site-cleaning and construction waste generated by the project. List all assumptions made for the quantities estimates.
 - C. List each type of waste and whether it will be salvaged, recycled, or disposed of in an landfill. The plan should include the following information:
 1. Types and estimated quantities, by weight, of CDL waste expected to be generated during demolition and construction.
 2. Proposed methods for CDL waste salvage, reuse, recycling and disposal during demolition including, but not limited to, one or more of the following:
 - a. Contracting with a deconstruction specialist to salvage materials generated,
 - b. Selective salvage as part of demolition contractor's work,
 - c. Reuse of materials on-site or sale or donation to a third party.
 3. Proposed methods for salvage, reuse, recycling and disposal during construction including, but not limited to, one or more of the following:
 - a. Requiring subcontractors to take their CDL waste to a recycling facility;
 - b. Contracting with a recycling hauler to haul recyclable CDL waste to an approved recycling or material recovery facility;
 - c. Processing and reusing materials on-site;
 - d. Self-hauling to a recycling or material recovery facility.

- 4. Name of recycling or material recovery facility receiving the CDL wastes.
- 5. Handling and Transportation Procedures: Include method that will be used for separating recyclable waste including sizes of containers, container labeling, and designated location on project site where materials separation will be located.
- D. Cost/Revenue Analysis: Indicate total cost of waste disposal as if there was no waste management plan and net additional cost or net savings resulting from implementing waste management plan. Include the following:
 - 1. Total quantity of waste.
 - 2. Estimated cost of disposal (cost per unit). Include hauling and tipping fees and cost of collection containers for each type of waste.
 - 3. Total cost of disposal (with no waste management).
 - 4. Revenue from salvaged materials.
 - 5. Revenue from recycled materials.
 - 6. Savings in hauling and tipping fees by donating materials.
 - 7. Savings in hauling and tipping fees that are avoided.
 - 8. Handling and transportation costs. Including cost of collection containers for each type of waste.
 - 9. Net additional cost or net savings from waste management plan.

PART 2 - PRODUCTS (Not Used)


PART 3 – EXECUTION

3.1 CONSTRUCTION WASTE MANAGEMENT, GENERAL

- A. Provide containers for CDL waste that is to be recycled clearly labeled as such with a list of acceptable and unacceptable materials. The list of acceptable materials must be the same as the materials recycled at the receiving material recovery facility or recycling processor.
- B. The collection containers for recyclable CDL waste must contain no more than 10% non-recyclable material, by volume.
- C. Provide containers for CDL waste that is disposed in a landfill clearly labeled as such.
- D. Use detailed material estimates to reduce risk of unplanned and potentially wasteful cuts.
- E. To the greatest extent possible, include in material purchasing agreements a waste reduction provision requesting that materials and equipment be delivered in packaging made of recyclable material, that they reduce the amount of packaging, that packaging be taken back for reuse or recycling, and to take back all unused product. Insure that subcontractors require the same provisions in their purchase agreements.
- F. Conduct regular visual inspections of dumpsters and recycling bins to remove contaminants.

3.2 SOURCE SEPARATION

- A. General: Contractor shall separate recyclable materials from CDL waste to the maximum extent possible.



Separate recyclable materials by type.

1. Provide containers, clearly labeled, by type of separated materials or provide other storage method for managing recyclable materials until they are removed from Project site.
2. Stockpile processed materials on-site without intermixing with other materials. Place, grade, and shape stockpiles to drain surface water and to minimize pest attraction. Cover to prevent windblown dust.
3. Stockpile materials away from demolition area. Do not store within drip line of remaining trees.
4. Store components off the ground and protect from weather.

3.3 CO-MINGLED RECYCLING

- A. General: Do not put CDL waste that will be disposed in a landfill into a co-mingled CDL waste recycling container.

REMOVAL OF CONSTRUCTION WASTE MATERIALS

- A. Remove CDL waste materials from project site on a regular basis. Do not allow CDL waste to accumulate on-site.
- B. Transport CDL waste materials off Owner's property and legally dispose of them.
- C. Burning of CDL waste is not permitted.

NOT FOR BIDDING PURPOSES

WASTE MANAGEMENT PROGRESS REPORT				
MATERIAL CATEGORY	DISPOSED IN MUNICIPAL SOLID WASTE LANDFILL	DIVERTED FROM LANDFILL BY RECYCLING, SALVAGE OR REUSE		
		Recycled	Salvaged	Reused
1. Acoustical Ceiling Tiles				
2. Asphalt				
3. Asphalt Shingles				
4. Cardboard Packaging				
5. Carpet and Carpet Pad				
6. Concrete				
7. Drywall				
8. Fluorescent Lights and Ballasts				
9. Land Clearing Debris (vegetation, stumpage, dirt)				
10. Metals				
11. Paint (through hazardous waste outlets)				
12. Wood				
13. Plastic Film (sheeting, shrink wrap, packaging)				
14. Window Glass				
15. Field Office Waste (office paper, aluminum cans, glass, plastic, and coffee cardboard)				
16. Other (insert description)				
17. Other (insert description)				
Total (In Weight)		(TOTAL OF ALL ABOVE VALUES – IN WEIGHT)		
		Percentage of Waste Diverted	(TOTAL WASTE DIVIDED BY TOTAL DIVERTED)	

NOT FOR BIDDING PURPOSES

END OF SECTION

SECTION 01 77 00

CLOSEOUT PROCEDURES

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 1 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes administrative and procedural requirements for contract closeout, including, but not limited to, the following:

1. Inspection procedures.
2. Project Record Documents.
3. Operation and maintenance manuals.
4. Warranties.
5. Instruction of the Owner's personnel.
6. Final cleaning.

1.3 SUBSTANTIAL COMPLETION

- A. Preliminary Procedures: Before requesting inspection for determining date of Substantial Completion, complete the following. List items below that are incomplete in request.

1. Prepare a list of items to be completed and corrected (punch list), the value of items on the list, and reasons why the Work is not complete.
2. Advise the Owner of pending insurance changeover requirements.
3. Submit specific warranties, workmanship bonds, maintenance service agreements, final certifications, and similar documents.
4. Obtain and submit releases permitting the Owner unrestricted use of the Work and access to services and utilities. Include occupancy permits, operating certificates, and similar releases.
5. Prepare and submit Project Record Documents, operation and maintenance manuals, Final Completion construction photographs, damage or settlement surveys, property surveys, and similar final record information.
6. Deliver tools, spare parts, extra materials, and similar items to location designated by the Owner. Label with manufacturer's name and model number where applicable.
7. Make final changeover of permanent locks and deliver keys to the Owner. Advise the Owner's personnel of changeover in security provisions.
8. Complete startup testing of systems.
9. Submit test/adjust/balance records.
10. Terminate and remove temporary facilities from Project site, along with mockups, construction tools, and similar elements.
11. Advise the Owner of changeover in heat and other utilities.
12. Submit changeover information related to the Owner's occupancy, use, operation, and maintenance.

13. Complete final cleaning requirements, including touchup painting.
14. Touch up and otherwise repair and restore marred exposed finishes to eliminate visual defects.

B. Inspection: Submit a written request for inspection for Substantial Completion. On receipt of request, the Architect will either proceed with inspection or notify the Contractor of unfulfilled requirements. The Architect will prepare the Certificate of Substantial Completion after inspection or will notify the Contractor of items, either on the Contractor's list or additional items identified by the Architect that must be completed or corrected before certificate will be issued.

1. Reinspection: Request reinspection when the Work identified in previous inspections as incomplete is completed or corrected.
2. Results of completed inspection will form the basis of requirements for Final Completion.

1.4 FINAL COMPLETION

A. Preliminary Procedures: Before requesting final inspection for determining date of Final Completion, complete the following:

1. Submit a final Application for Payment according to Division 00 Section "Supplementary General Conditions A201-2007."
2. Submit certified copy of the Architect's Substantial Completion inspection list of items to be completed or corrected (punch list), endorsed and dated by the Architect. The certified copy of the list shall state that each item has been completed or otherwise resolved for acceptance.
3. Submit evidence of final, continuing insurance coverage complying with insurance requirements.
4. Instruct the Owner's personnel in operation, adjustment, and maintenance of products, equipment, and systems.

B. Inspection: Submit a written request for final inspection for acceptance. On receipt of request, the Architect will either proceed with inspection or notify the Contractor of unfulfilled requirements. The Architect will prepare a final Certificate for Payment after inspection or will notify the Contractor of construction that must be completed or corrected before certificate will be issued.

1. Reinspection: Request reinspection when the Work identified in previous inspections as incomplete is completed or corrected.

1.5 LIST OF INCOMPLETE ITEMS (PUNCH LIST)

A. Preparation: Submit three copies of list. Include name and identification of each space and area affected by construction operations for incomplete items and items needing correction including, if necessary, areas disturbed by the Contractor that are outside the limits of construction.

1. Organize list of spaces in sequential order.
2. Organize items applying to each space by major element, including categories for ceiling, individual walls, floors, equipment, and building systems.
3. Include the following information at the top of each page:

- a. Project name.
- b. Date.
- c. Name of Architect.
- d. Name of Contractor.
- e. Page number.

1.6 PROJECT RECORD DOCUMENTS

- A. General: Do not use Project Record Documents for construction purposes. Protect Project Record Documents from deterioration and loss. Provide access to Project Record Documents for the Architect's reference during normal working hours.
- B. Record Drawings:
 1. Maintain and submit one set of blue- or black-line white prints of Contract Drawings and Shop Drawings and submit digital scanned copies of all the Record Drawings; format to be .JPG or .TIF.
 2. The Contractor shall be responsible for updating the bid documents (CADD drawings and specifications) with the as-built changes. All changes shall be clouded and tagged as "as-built" revisions. The drawings shall also have a new "as-built" date.
 3. Deliverables: One review set of bond prints, two final sets (one in bond and one in Mylar).
 4. Drawings that replace the original bid drawings shall be cross referenced to the original bid drawing files.
 5. Mark Record Prints to show the actual installation where installation varies from that shown originally. Require individual of entity who obtained record data, whether individual or entity is Installer, sub contractor, or similar entity, to prepare the marked-up Record Prints.
 - a. Give particular attention to information on concealed elements that cannot be readily identified and recorded later.
 - b. Accurately record information in an understandable drawing technique.
 - c. Record data as soon as possible after obtaining it. Record and check the markup before enclosing concealed installations.
 - d. Mark Contract Drawings or Shop Drawings, whichever is most capable of showing actual physical conditions, completely and accurately. Where Shop Drawings are marked, show cross-reference on Contract Drawings.
 6. Mark record sets with erasable, red-colored pencil. Use other colors to distinguish between changes for different categories of the Work at the same location.
 7. Mark important additional information that was either shown schematically or omitted from original Drawings.
 8. Note Construction Change Directive numbers, Change Order numbers, alternate numbers, and similar identification where applicable.
 9. Identify and date each Record Drawing; include the designation "PROJECT RECORD DRAWING" in a prominent location. Organize into manageable sets; bind each set with durable paper cover sheets. Include identification on cover sheets.
- C. Record Specifications: Submit one copy of Project's Specifications, including addenda and contract modifications. Mark copy to indicate the actual product installation where installation varies from that indicated in Specifications, addenda, and contract modifications.

1. Give particular attention to information on concealed products and installations that cannot be readily identified and recorded later.
 2. Mark copy with the proprietary name and model number of products, materials, and equipment furnished, including substitutions and product options selected.
 3. Note related Change Orders, Record Drawings, and Product Data, where applicable.
- D. Record Product Data: Submit one copy of each Product Data submittal. Mark one set to indicate the actual product installation where installation varies substantially from that indicated in Product Data.
1. Give particular attention to information on concealed products and installations that cannot be readily identified and recorded later.
 2. Include significant changes in the product delivered to Project site and changes in manufacturer's written instructions for installation.
 3. Note related Change Orders, Record Drawings, and Record Specifications, where applicable.
- E. Miscellaneous Record Submittals: Assemble miscellaneous records required by other Specification Sections for miscellaneous record keeping and submittal in connection with actual performance of the Work. Bind or file miscellaneous records and identify each, ready for continued use and reference.

1.7 OPERATION AND MAINTENANCE MANUALS

- A. Assemble three (3) complete sets of operation and maintenance data indicating the operation and maintenance of each system, subsystem, and piece of equipment not part of a system. Include operation and maintenance data required in individual Specification Sections and as follows:
1. Operation Data:
 - a. Emergency instructions and procedures.
 - b. System, subsystem, and equipment descriptions, including operating standards.
 - c. Operating procedures, including startup, shutdown, seasonal, and weekend operations.
 - d. Description of controls and sequence of operations.
 - e. Piping diagrams.
 2. Maintenance Data:
 - a. Manufacturer's information, including list of spare parts.
 - b. Name, address, and telephone number of Installer or supplier.
 - c. Maintenance procedures.
 - d. Maintenance and service schedules for preventive and routine maintenance.
 - e. Maintenance record forms.
 - f. Sources of spare parts and maintenance materials.
 - g. Copies of maintenance service agreements.
 - h. Copies of warranties and bonds.
- B. Organize operation and maintenance manuals into suitable sets of manageable size. Bind and index data in heavy-duty, 3-ring, vinyl-covered, loose-leaf binders, in thickness necessary to accommodate contents, with pocket inside the covers to receive folded oversized sheets.

Identify each binder on front and spine with the printed title "OPERATION AND MAINTENANCE MANUAL," Project name, and subject matter of contents.

1.8 WARRANTIES

- A. Submittal Time: Submit written warranties on request of the Architect for designated portions of the Work where commencement of warranties other than date of Substantial Completion is indicated.
- B. Partial Occupancy: Submit properly executed warranties within 15 days of completion of designated portions of the Work that are completed and occupied or used by the Owner during construction period by separate agreement with the Contractor.
- C. Organize warranty documents into an orderly sequence based on the table of contents of the Project Manual.
 - 1. Bind warranties and bonds in heavy-duty, 3-ring, vinyl-covered, loose-leaf binders, thickness as necessary to accommodate contents, and sized to receive 8-1/2-by-11-inch (115-by-280-mm) paper.
 - 2. Provide heavy paper dividers with plastic-covered tabs for each separate warranty. Mark tab to identify the product or installation. Provide a typed description of the product or installation, including the name of the product and the name, address, and telephone number of Installer.
 - 3. Identify each binder on the front and spine with the typed or printed title "WARRANTIES," Project name, and name of the Contractor.
- D. Provide additional copies of each warranty to include in operation and maintenance manuals.

PART 2 - PRODUCTS

2.1 MATERIALS

- A. Cleaning Agents: Use cleaning materials and agents recommended by manufacturer or fabricator of the surface to be cleaned. Do not use cleaning agents that are potentially hazardous to health or property or that might damage finished surfaces.

PART 3 - EXECUTION

3.1 DEMONSTRATION AND TRAINING

- A. Instruction: Instruct the Owner's personnel to adjust, operate, and maintain systems, subsystems, and equipment not part of a system.
 - 1. Provide instructors experienced in operation and maintenance procedures.
 - 2. Provide instruction at mutually agreed-on times. For equipment that requires seasonal operation, provide similar instruction at the start of each season.
 - 3. Schedule training with the Owner, through the Architect with at least seven days' advance notice.
 - 4. Coordinate instructors, including providing notification of dates, times, length of instruction, and course content.

- B. Program Structure: Develop an instruction program that includes individual training modules for each system and equipment not part of a system, as required by individual Specification Sections. For each training module, develop a learning objective and teaching outline. Include instruction for the following:

1. System design and operational philosophy.
2. Review of documentation.
3. Operations.
4. Adjustments.
5. Troubleshooting.
6. Maintenance.
7. Repair.

3.2 FINAL CLEANING

- A. General: Provide final cleaning. Conduct cleaning and waste-removal operations to comply with local laws and ordinances and Federal and local environmental and antipollution regulations.
- B. Cleaning: Employ experienced workers or professional cleaners for final cleaning. Clean each surface or unit to condition expected in an average commercial building cleaning and maintenance program. Comply with manufacturer's written instructions.
1. Complete the following cleaning operations before requesting inspection for certification of Substantial Completion for entire Project or for a portion of Project:
 - a. Clean Project site, yard, and grounds, in areas disturbed by construction activities, including landscape development areas, of rubbish, waste material, litter, and other foreign substances.
 - b. Sweep paved areas broom clean. Remove petrochemical spills, stains, and other foreign deposits.
 - c. Rake grounds that are neither planted nor paved to a smooth, even-textured surface.
 - d. Remove tools, construction equipment, machinery, and surplus material from Project site.
 - e. Remove snow and ice to provide safe access to building.
 - f. Clean exposed exterior and interior hard-surfaced finishes to a dirt-free condition, free of stains, films, and similar foreign substances. Avoid disturbing natural weathering of exterior surfaces. Restore reflective surfaces to their original condition.
 - g. Remove debris and surface dust from limited access spaces, including roofs, plenums, shafts, trenches, equipment vaults, manholes, attics, and similar spaces.
 - h. Sweep concrete floors broom clean in unoccupied spaces.
 - i. Vacuum carpet and similar soft surfaces, removing debris and excess nap; shampoo if visible soil or stains remain.
 - j. Clean transparent materials, including mirrors and glass in doors and windows. Remove glazing compounds and other noticeable, vision-obscuring materials. Replace chipped or broken glass and other damaged transparent materials. Polish mirrors and glass, taking care not to scratch surfaces.
 - k. Remove labels that are not permanent.

- l. Touch up and otherwise repair and restore marred, exposed finishes and surfaces. Replace finishes and surfaces that cannot be satisfactorily repaired or restored or that already show evidence of repair or restoration.
 - 1) Do not paint over "UL" and similar labels, including mechanical and electrical nameplates.
 - m. Wipe surfaces of mechanical and electrical equipment and similar equipment. Remove excess lubrication, paint and mortar droppings, and other foreign substances.
 - n. Replace parts subject to unusual operating conditions.
 - o. Clean plumbing fixtures to a sanitary condition, free of stains, including stains resulting from water exposure.
 - p. Replace disposable air filters and clean permanent air filters. Clean exposed surfaces of diffusers, registers, and grills.
 - q. Clean ducts, blowers, and coils if units were operated without filters during construction.
 - r. Clean light fixtures, lamps, globes, and reflectors to function with full efficiency. Replace burned-out bulbs, and those noticeably dimmed by hours of use, and defective and noisy starters in fluorescent and mercury vapor fixtures to comply with requirements for new fixtures.
 - s. Leave Project clean and ready for occupancy.
- C. Comply with safety standards for cleaning. Do not burn waste materials. Do not bury debris or excess materials on the Owner's property. Do not discharge volatile, harmful, or dangerous materials into drainage systems. Remove waste materials from Project site and dispose of lawfully.

3.3 SUMMARY OF CLOSEOUT DOCUMENTS

- A. Contractor's Affidavit of Payment of Debts and Claims (AIA Document G706)
- B. Contractor's Consent of Surety Company to Final Payment (AIA Document G707) (one copy)
- C. Contractor's Affidavit of Release of Liens (AIA Document G706A) (one copy)
- D. Copy of Letter of Guarantee and Warranty Information (three copies)
- E. Subcontractor's Release of Liens had been submitted with each previous Application of Payment (AIA Document G706A) (one copy)
- F. Operation and Maintenance Manuals
- G. Record Shop Drawings and Submittals
- H. As-built Drawings: All construction changes should be clouded and marked.
 1. Updated CAD files to reflect changes and as-built conditions.
 2. Two hard copies and one CD-Rom with digital Image (scanned) files of As-builts
 3. Mylar prints of As-builts revised CAD file

- I. Affidavit of Discharge of State Tax Liability
- J. Punch List Closeout Letter

END OF SECTION

NOT FOR BIDDING PURPOSES

SCHEDULE OF SPECIAL INSPECTIONS

P – Perform these Special Inspections tasks for each welded joint or member. (AISC 360 & AISC 341)

O – Observe these Special Inspections items on a random daily basis. Operations need not be delayed pending these inspections. (AISC 360 & AISC 341)

D – Document, with a report, that the work has been performed in accordance with the contract documents. (AISC 341)

C – Continuous Special Inspections is the constant monitoring of specific tasks by a special inspector. These inspections must be carried out continuously over the duration of the particular tasks. (IBC)

P – Periodic Special Inspections is Special Inspections by the special inspector who is intermittently present where the work to be inspected has been or is being performed. (IBC)

STRUCTURAL STEEL

PRIOR TO WELDING (Table N5.4-1, AISC 360-10 & TABLE J6-1, AISC 341-10)				
Required	Task	Perform	Observe	Description
<input checked="" type="checkbox"/>	1. Verify welding procedures (WPS) and consumable certificates	P	-	
<input checked="" type="checkbox"/>	2. Material identification (Type/Grade)	-	O	
<input checked="" type="checkbox"/>	3. Welder identification system	-	O	A system shall be maintained by which a welder who has welded a joint or member can be identified. Stamps, if used, shall be the low-stress dye type.
<input checked="" type="checkbox"/>	4. Fit-up groove welds (including joint geometry)	-	O	<ul style="list-style-type: none"> • Joint preparation • Dimensions (alignment, root opening, root face, bevel) • Cleanliness (condition of steel surfaces) • Tacking (tack weld quality and location) • Backing type and fit (if applicable)
<input checked="" type="checkbox"/>	5. Configuration and finish of access holes	-	O	
<input checked="" type="checkbox"/>	6. Fit-up of fillet welds	-	O	<ul style="list-style-type: none"> • Dimensions (alignment, gaps at root) • Cleanliness (condition of steel surfaces) • Tacking (tack weld quality and location)

STRUCTURAL STEEL

DURING WELDING (Table N5.4-2, AISC 360-10 & TABLE J6-2, AISC 341-10)				
Required	Task	Perform	Observe	Description
<input checked="" type="checkbox"/>	1. Use of qualified welders	-	0	
<input checked="" type="checkbox"/>	2. Control and handling of welding consumables	-	0	<ul style="list-style-type: none"> • Packaging • Exposure control.
<input checked="" type="checkbox"/>	3. No welding over cracked tack welds	-	0	
<input checked="" type="checkbox"/>	4. Environmental conditions	-	0	<ul style="list-style-type: none"> • Wind speed within limits • Precipitation and temperature
<input checked="" type="checkbox"/>	5. WPS followed	-	0	<ul style="list-style-type: none"> • Settings on welding equipment • Travel speed • Selected welding materials • Shielding gas type/flow rate • Pre-heat applied • Interpass temperature maintained (min./max.) • Proper position (F, V, H, OH) • Intermix of filler metals avoided unless approved
<input checked="" type="checkbox"/>	6. Welding techniques	-	0	<ul style="list-style-type: none"> • Interpass and final cleaning • Each pass within profile limitations • Each pass meets quality requirements

NOT FOR BIDDING PURPOSES

STRUCTURAL STEEL

AFTER WELDING (TABLE N5.4-3, AISC 360-10 & TABLE J6-3, AISC 341-10):				
Required	Task	Perform	Observe	Description
<input checked="" type="checkbox"/>	1. Welds cleaned	-	O	
<input checked="" type="checkbox"/>	2. Size, length, and location of welds	P	-	
<input checked="" type="checkbox"/>	3. Welds meet visual acceptance criteria	P	-	<ul style="list-style-type: none"> • Crack prohibition • Weld/base-metal fusion • Crater cross section • Weld profiles • Weld size • Undercut • Porosity
<input checked="" type="checkbox"/>	4. Arc strikes	P	-	
<input checked="" type="checkbox"/>	5. k-area	P	-	When welding of doubler plates, continuity plates or stiffeners has been performed in the k-area, visually inspect the web k-area for cracks within 3 in. of the weld.
<input checked="" type="checkbox"/>	6. Backing removed and weld tabs removed (if required)	P	-	
<input checked="" type="checkbox"/>	7. Backing removed, weld tabs removed and finished, and fillet welds added (if required)	P/D	-	
<input checked="" type="checkbox"/>	8. Placement of reinforcing or contouring fillet welds (if required)	P/D	-	
<input checked="" type="checkbox"/>	9. Repair activities	P	-	
<input checked="" type="checkbox"/>	10. Document acceptance or rejection of welded joint/member	P	-	

NOT FOR BIDDING PURPOSES

STRUCTURAL STEEL

NONDESTRUCTIVE TESTING (SECTION N5.5, AISC 360-10 & SECTION J6.2, AISC 341-10):				
Required	Task	Perform	Observe	Description
<input type="checkbox"/>	1. CJP welds (Risk Cat. II)	-	0	Ultrasonic testing shall be performed on 10% of CJP groove welds in butt, T- and corner joints subject to transversely applied tension loading in materials 5/16-inch thick or greater. Test rate must be increased if > 5% of welds tested have unacceptable defects.
<input checked="" type="checkbox"/>	2. CJP welds (Risk Cat. III, IV or V)	-	0	Ultrasonic testing shall be performed on all CJP groove welds in butt, T- and corner joints subject to transversely applied tension loading in materials 5/16-inch thick or greater.
<input checked="" type="checkbox"/>	3. CJP welds	-	0	Ultrasonic testing shall be performed on 100% of CJP groove welds in materials 5/16-inch or greater. Magnetic particle testing shall be performed on 25% of all beam-to-column CJP groove welds.
<input checked="" type="checkbox"/>	4. Access holes (flange > 2")	-	0	Thermally cut surfaces of access holes shall be MT or PT when the flange thickness exceeds 2 in. for rolled shapes, or when the web thickness exceeds 2 in. for built-up shapes. Any cracks shall be deemed unacceptable regardless of size or location.
<input checked="" type="checkbox"/>	5. Welded joints subject to fatigue	-	0	Radiographic or Ultrasonically inspect welded joints identified on the contract documents to be subject to fatigue per sections 5.1, 5.2, 5.3, 5.4, 6.1, 6.2, and 6.3 of Table A-3.1, AISC 360-10.

NOT FOR BIDDING PURPOSES

STRUCTURAL STEEL

NONDESTRUCTIVE TESTING (SECTION N5.5, AISC 360-10 & SECTION J6.2, AISC 341-10):				
Required	Task	Perform	Observe	Description
<input checked="" type="checkbox"/>	6. K-area NDT	P	-	Where welding of doubler plates, continuity plates or stiffeners has been performed in the k-area, the web shall be tested for cracks using magnetic particle testing (MT). The MT inspection area shall include the k-area base metal within 3-inches of the weld. The MT shall be performed no sooner than 48 hours following completion of the welding.
<input checked="" type="checkbox"/>	7. Base metal NDT for lamellar tearing and laminations	-	O	After joint completion, base metal thicker than 1 1/2 in. loaded in tension in the through-thickness direction in tee and corner joints, where the connected material is greater than 3/4 in. and contains CJP groove welds, shall be ultrasonically tested for discontinuities behind and adjacent to the fusion line of such welds.
<input checked="" type="checkbox"/>	8. Beam cope and access hole	-	O	At welded splices and connections, thermally cut surfaces of beam copes and access holes shall be tested using magnetic particle testing or penetrant testing, when the flange thickness exceeds 1 1/2 in. for rolled shapes, or when the web thickness exceeds 1 1/2 in. for built-up shapes.
<input checked="" type="checkbox"/>	9. Reduced beam section repair	-	O	Magnetic particle testing shall be performed on any weld and adjacent area of the reduced beam section (RBS) cut surface that has been repaired by welding, or on the base metal of the RBS cut surface if a sharp notch has been removed by grinding.
<input checked="" type="checkbox"/>	10. Weld tab removal sites	-	O	At the end of welds where weld tabs have been removed, magnetic particle testing shall be performed on the same beam-to-column joints receiving UT.

NOT FOR BIDDING PURPOSES

STRUCTURAL STEEL

PRIOR TO BOLTING (TABLE N5.6-1, AISC 360-10 & TABLE J7-1, AISC 341-10):				
Required	Task	Perform	Observe	Description
<input checked="" type="checkbox"/>	1. Manufacture's certification available for fastener materials	P	-	
<input checked="" type="checkbox"/>	2. Fasteners marked in accordance with ASTM requirements	-	O	
<input checked="" type="checkbox"/>	3. Proper fasteners selected for joint detail (grade, type, bolt length if threads are to be excluded from shear plane)	-	O	
<input checked="" type="checkbox"/>	4. Proper bolting procedure selected for joint detail	-	O	
<input checked="" type="checkbox"/>	5. Connecting elements, including appropriate faying surface condition and hole preparation, if specified, meet applicable requirements	-	O	
<input checked="" type="checkbox"/>	6. Pre-installation verification testing by installation personnel observed and documented for fastener assemblies and methods used	-	O/D***	
<input checked="" type="checkbox"/>	7. Proper storage provided for bolts, nuts, washers, and other fastener components	-	O	

NOT FOR BIDDING PURPOSES

STRUCTURAL STEEL

DURING BOLTING (TABLE N5.6-2, AISC 360-10 & TABLE J7-2, AISC 341-10):				
Required	Task	Perform	Observe	Description
<input checked="" type="checkbox"/>	1. Fastener assemblies of suitable condition, paced in all holes and washers (if required) are positioned as required	-	O	
<input checked="" type="checkbox"/>	2. Joint brought to the snug-tight condition prior to pretensioning operations	-	O	
<input checked="" type="checkbox"/>	3. Fastener component not turned by the wrench prevented from rotating	-	O	
<input checked="" type="checkbox"/>	4. Fasteners are pretensioned in accordance with RCSC Specification, progressing systematically from the most rigid point toward the free edges	-	O	
AFTER BOLTING (TABLE N5.6-3, AISC 360-10 & TABLE J7-3, AISC 341-10):				
Required	Task	Perform	Observe	Description
<input checked="" type="checkbox"/>	Document acceptance or rejection of bolted connections	P	-	
OTHER STEEL INSPECTIONS (SECTION 5.7, AISC 360-10):				
Required	Task	Perform	Observe	Description
<input checked="" type="checkbox"/>	1. Anchor rods and other embedments supporting structural steel	P	-	Verify the diameter, grade, type, and length of the anchor rod or embedded item, and the extent or depth of embedment prior to placement of concrete.
<input checked="" type="checkbox"/>	2. Fabricated steel or erected steel frame	-	O	Verify compliance with the details shown on the construction documents, such as braces, stiffeners, member locations and proper application of joint details at each connection.

NOT FOR BIDDING PURPOSES

STRUCTURAL STEEL

OTHER STEEL INSPECTIONS (Tables J8-1 & J10-1, AISC 341-10):				
Required	Task	Perform	Observe	Description
<input checked="" type="checkbox"/>	1. Reduced beam sections (RBS)	P/D	-	<ul style="list-style-type: none"> • Contour and finish • Dimensional tolerances
<input checked="" type="checkbox"/>	2. Protected zones	P/D	-	No holes or unapproved attachments made by fabricator or erector
<input type="checkbox"/>	3. H-piles	P/D	-	No holes or unapproved attachments made by the responsible contractor

NOT FOR BIDDING PURPOSES

STEEL CONSTRUCTION OTHER THAN STRUCTURAL STEEL

STEEL ROOF AND FLOOR DECKS (IBC TABLE 1705.2.2):				
Required	Task	Continuous	Periodic	Description
<input checked="" type="checkbox"/>	1. Material verification of cold-formed steel deck	-	P	Confirm that identification markings are provided to conform to ASTM standards specified on approved construction documents. Verify material with manufacturer's certified test reports.
<input checked="" type="checkbox"/>	2. Floor and roof deck welds	-	P	Visual inspection to confirm that welds meet acceptance criteria of AWS D1.3 and verify welder qualifications.
WELDING OF REINFORCING STEEL (IBC TABLE 1705.2.2):				
Required	Task	Continuous	Periodic	Description
<input checked="" type="checkbox"/>	1. Verification of weldability	-	P	Verify weldability of reinforcing steel, other than ASTM A 706 based upon carbon equivalent and in accordance with AWS D1.4.
<input checked="" type="checkbox"/>	2. Reinforcing steel resisting flexural and axial forces in intermediate or special moment frames, and boundary elements of special structural walls	C	-	Visually inspect all welds in accordance with AWS D1.4.
<input checked="" type="checkbox"/>	3. Shear reinforcement	C	-	Visually inspect all welds in accordance with AWS D1.4.
<input checked="" type="checkbox"/>	4. Other reinforcing steel	-	P	Visually inspect all welds in accordance with AWS D1.4.

NOT FOR BIDDING PURPOSES

CONCRETE CONSTRUCTION

IBC TABLE 1705.3, 1705.12.1:				
Required	Task	Continuous	Periodic	Description
<input checked="" type="checkbox"/>	1. Reinforcing steel, including prestressing tendons	-	P	Verify prior to placing concrete that reinforcing is of specified type, grade and size; that it is free of oil, dirt and rust; that it is located and spaced properly; that hooks, bends, ties, stirrups and supplemental reinforcement are placed correctly; that lap lengths, stagger and offsets are provided; and that all mechanical connections are installed per the manufacturer's instructions and/or evaluation report.
<input checked="" type="checkbox"/>	2. Anchors cast in concrete	-	P	Verify prior to placing concrete that cast in anchors have proper embedment, spacing and edge distance.
<input checked="" type="checkbox"/>	3. Post-installed anchors or dowels	C	-	Inspect all post-installed anchors/dowels as required by the approved ICC-ES report.
<input checked="" type="checkbox"/>	4. Use of required mix design	-	P	Verify that all mixes used comply with the approved construction documents
<input checked="" type="checkbox"/>	5. Concrete slump, air content, and temperature	C	-	At the time fresh concrete is sampled to fabricate specimens for strength test verify these tests are performed.
<input checked="" type="checkbox"/>	6. Concrete & shotcrete placement	C	-	Verify proper application techniques are used during concrete conveyance and depositing avoids segregation or contamination. Verify that concrete is properly consolidated.
<input checked="" type="checkbox"/>	7. Curing temperature and techniques	-	P	Inspect curing, cold weather protection and hot weather protection procedures.
<input type="checkbox"/>	8. Pre-stressed concrete	C	-	Verify application of prestressing forces and grouting of bonded prestressing tendons in the seismic force-resisting system.

CONCRETE CONSTRUCTION

IBC TABLE 1705.3, 1705.12.1:				
Required	Task	Continuous	Periodic	Description
<input type="checkbox"/>	9. Erection of precast concrete	-	P	Verify that all precast elements are lifted, assembled and braced in accordance with the approved construction documents.
<input checked="" type="checkbox"/>	10. In-situ concrete strength verification	-	P	Prior to the removal of shores and forms or the stressing of post-tensioned tendons verify that adequate strength has been achieved.
<input checked="" type="checkbox"/>	11. Formwork	-	P	Inspect the forms to ensure that they are placed plumb and conform to the shape, lines, and dimensions of the members as required by the approved construction documents.
<input checked="" type="checkbox"/>	12. Reinforcement complying with ASTM A 615 in special moment frames, special structural walls and coupling beams	-	P	Verify that ASTM A 615 reinforcing steel used in these areas complies with ACI 318: 21.1.5.2 by means of certified mill test reports. If this reinforcing steel is to be welded chemical tests shall be performed in accordance with ACI 318: 3.5.2.
<input type="checkbox"/>	13. Reinforcement placement within progressive collapse resisting system (#)	C	-	Visual inspect reinforcing steel placement with a particular emphasis on reinforcing steel anchorages, laps and other details within the progressive collapse resisting system, including horizontal tie force elements, vertical tie force elements and bridging elements.

NOT FOR BIDDING PURPOSES

WOOD CONSTRUCTION

IBC 1705.5, 1705.10.1 & 1705.11.2				
Required	Task	Continuous	Periodic	Description
<input type="checkbox"/>	1. High-load diaphragms	-	P	Verify thickness and grade of sheathing, size of framing members at panel edges, nail/staple diameters and length, and the number of fastener lines and fastener spacing are per approved plans.
<input type="checkbox"/>	2. Metal-plate-connected wood trusses spanning 60 feet or greater	-	P	Verify that temporary and permanent truss bracing is installed in accordance with approved truss package.
<input checked="" type="checkbox"/>	3. Field Gluing (*, **)	C	-	Inspect all field gluing of structural wood element within the main wind-force resisting system.
<input checked="" type="checkbox"/>	4. Nailing, bolting, anchoring and other fastening of components (*, **)	-	P	If fasteners within the main wind-force resisting system are spaced less than 4-inches, verify that proper nailing, bolting, anchoring and other fastening of shear walls, diaphragms, drag struts, braces, and holdowns.
<input type="checkbox"/>	5. Nailing, bolting, anchoring and other fastening of components (#)		P	Verify proper nailing, bolting, anchoring, and other fastening components within the progressive collapse resisting system, including horizontal tie force elements, vertical tie force elements and bridging elements.

NOT FOR BIDDING PURPOSES

SOILS CONSTRUCTION

IBC TABLE 1705.6				
Required	Task	Continuous	Periodic	Description
<input checked="" type="checkbox"/>	1. Foundation bearing capacity	-	P	Verify the materials below foundations are adequate to achieve the design bearing capacity.
<input checked="" type="checkbox"/>	2. Excavations	-	P	Verify the excavations are extended to the proper depth and have reached proper material.
<input checked="" type="checkbox"/>	3. Perform classification and testing of compacted fill materials	-	P	
<input checked="" type="checkbox"/>	4. Compacted fill material	C	-	Verify the use of proper materials, densities and lift thicknesses during placement and compaction of compacted fill.
<input checked="" type="checkbox"/>	5. Subgrade	-	P	Prior to placement of compacted fill, observe sub-grade and verify that site has been prepared properly.

NOT FOR BIDDING PURPOSES

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

Statement of Special Inspections

Project: HVAC Improvements
Location: Stokes Elementary School
Owner: Caesar Rodney School District

Design Professional in Responsible Charge:

This *Statement of Special Inspections* is submitted as a condition for permit issuance in accordance with the Special Inspection and Structural Testing requirements of the Building Code. It includes a schedule of Special Inspection services applicable to this project as well as the name of the Special Inspection Coordinator and the identity of other approved agencies to be retained for conducting these inspections and tests. This *Statement of Special Inspections* encompass the following disciplines:

- Structural Mechanical/Electrical/Plumbing
 Architectural Other: _____

The Special Inspection Coordinator shall keep records of all inspections and shall furnish inspection reports to the Building Official and the Registered Design Professional in Responsible Charge. Discovered discrepancies shall be brought to the immediate attention of the Contractor for correction. If such discrepancies are not corrected, the discrepancies shall be brought to the attention of the Building Official and the Registered Design Professional in Responsible Charge. The Special Inspection program does not relieve the Contractor of his or her responsibilities.

Interim reports shall be submitted to the Building Official and the Registered Design Professional in Responsible Charge.

A *Final Report of Special Inspections* documenting completion of all required Special Inspections, testing and correction of any discrepancies noted in the inspections shall be submitted prior to issuance of a Certificate of Use and Occupancy.

Job site safety and means and methods of construction are solely the responsibility of the Contractor.

Interim Report Frequency: _____ or per attached schedule.

Prepared by:

Andrew T. Coats, PE
(type or print name)



Signature _____ Date _____

Owner's Authorization:

Building Official's Acceptance:

Signature _____ Date _____

Signature _____ Date _____

Schedule of Inspection and Testing Agencies

This Statement of Special Inspections / Quality Assurance Plan includes the following building systems:

- | | |
|--|--|
| <input checked="" type="checkbox"/> Soils and Foundations | <input type="checkbox"/> Spray Fire Resistant Material |
| <input checked="" type="checkbox"/> Cast-in-Place Concrete | <input checked="" type="checkbox"/> Wood Construction |
| <input type="checkbox"/> Precast Concrete | <input type="checkbox"/> Exterior Insulation and Finish System |
| <input type="checkbox"/> Masonry | <input type="checkbox"/> Mechanical & Electrical Systems |
| <input checked="" type="checkbox"/> Structural Steel | <input type="checkbox"/> Architectural Systems |
| <input type="checkbox"/> Cold-Formed Steel Framing | <input type="checkbox"/> Special Cases |

Special Inspection Agencies	Firm	Address, Telephone e-mail
1. Special Inspection Coordinator		
2. Inspector		
3. Inspector		
4. Testing Agency		
5. Testing Agency		
6. Other		

Note: The inspectors and testing agencies shall be engaged by the Owner or the Owner's Agent, and not by the Contractor or Subcontractor whose work is to be inspected or tested. Any conflict of interest must be disclosed to the Building Official, prior to commencing work.

SECTION 019113

GENERAL COMMISSIONING REQUIREMENTS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes general requirements that apply to implementation of commissioning without regard to systems, subsystems, and equipment being commissioned.

- B. Related Sections include the following:

1. Division 01 Section "*HVAC Commissioning Requirements*" for specific requirements for commissioning HVAC systems.
2. Division 01 Section "*Electrical Commissioning Requirements*" for specific requirements for commissioning electrical systems.
3. Division 01 Section "*Plumbing System Commissioning Requirements*" for specific requirements for commissioning Plumbing systems.
4. Division 01 Section "*Contract Closeout*" for specific requirements for closeout at substantial and final completion.
5. Division 01 Section "*Contract Closeout*" for Specific Requirements for training and demonstration of systems to Owner.
6. Division 01 Section "*Contract Closeout*" for Specific Requirements related to the Preparation of systems operation and maintenance manuals.

1.3 DEFINITIONS

- A. CxA: Commissioning Authority.
- B. OPR: Owner's Project Requirements.
- C. Systems, Subsystems, and Equipment: Where these terms are used together or separately, they shall mean "as-built" systems, subsystems, and equipment.
- D. TAB: Testing, Adjusting, and Balancing.

1.4 COMMISSIONING TEAM

- A. Members Appointed by Contractor(s): Individuals, each having authority to act on behalf of the entity he or she represents, explicitly organized to implement the commissioning process through coordinated actions. The commissioning team shall consist of, but not be limited to, representatives of Contractor, including Project superintendent and subcontractors, installers, suppliers, and specialists deemed appropriate by the CxA.
- B. Members Appointed by Owner:
1. CxA: The designated person, company, or entity that plans, schedules, and coordinates the commissioning team to implement the commissioning process. Owner will engage the CxA under a separate contract. The CxA for this project shall be performed by Gipe Associates, Inc., 8719 Brooks Drive, Easton, Maryland 21601, (410) 822-8688 - telephone, (410) 822-6306 – fax.
 2. All contractor commissioning requirements and costs associated with commissioning the project shall be included in the base bid.
 3. Representatives of the facility user and operation and maintenance personnel.
 4. Architect and Engineering design professionals.

1.5 OWNER'S RESPONSIBILITIES

- A. Assign operation and maintenance personnel and schedule them to participate in commissioning team activities including, but not limited to the following:
1. Coordination meetings.
 2. Training in operation and maintenance of systems, subsystems, and equipment.
 3. Testing meetings.
 4. Demonstration of operation of systems, subsystems, and equipment.

1.6 CONTRACTOR'S RESPONSIBILITIES

- A. Provide utility services required for the commissioning process.
- B. Contractor shall assign representatives with expertise and authority to act on behalf of the Contractor and schedule them to participate in and perform commissioning team activities including, but not limited to, the following:
1. Participate in commissioning and construction-phase coordination meetings.
 2. Participate in maintenance orientation and inspection.
 3. Participate in operation and maintenance training sessions.
 4. Participate in final review at acceptance meeting.
 5. Certify that Work is complete and systems are operational according to the Contract Documents, including calibration of instrumentation and controls.
 6. Evaluate performance deficiencies identified in test reports and, in collaboration with entity responsible for system and equipment installation, recommend corrective action.
 7. Review and approve final commissioning documentation.

8. Certify that all pre-test work and pre-testing of functional performance tests are complete and operational prior to scheduling performed testing by CxA. Submit completed functional performance test forms with data from pre-testing.
 9. During functional performance testing, a representative from the mechanical contractor, controls contractor, and test/balance engineer must be present and participate in testing.
- C. Subcontractors shall assign representatives with expertise and authority to act on behalf of subcontractors and schedule them to participate in and perform commissioning team activities including, but not limited to, the following:
1. Pre-test all systems/equipment prior to engaging CxA for Functional Performance Testing.
 2. Participate in commissioning and construction-phase coordination meetings.
 3. Participate in maintenance orientation and inspection.
 4. Participate in procedures meeting for testing.
 5. Participate in final review at acceptance meeting.
 6. Provide schedule for operation and maintenance data submittals, equipment startup, and testing to CxA for incorporation into the commissioning plan. Update schedule on a weekly basis throughout the construction period.
 7. Provide information to the CxA for developing construction-phase commissioning plan.
 8. Participate in training sessions for Owner's operation and maintenance personnel.
 9. Provide updated Project Record Documents to the CxA on a daily basis.
 10. Gather and submit operation and maintenance data for systems, subsystems, and equipment to the CxA, as specified in Division 01 Section "Operation and Maintenance Data."
 11. Provide technicians who are familiar with the construction and operation of installed systems and who shall develop specific test procedures and participate in testing of installed systems, subsystems, and equipment.
 12. The test/balance subcontractor, mechanical contractor, and automatic temperature controls subcontractor must be on-site and provide assistance during all functional performance testing.

1.7 CxA'S RESPONSIBILITIES

- A. Organize and lead the commissioning team.
- B. Prepare a construction-phase commissioning plan. Collaborate with Contractor and with subcontractors to develop test and inspection procedures. Include design changes and scheduled commissioning activities coordinated with overall Project schedule. Identify commissioning team member responsibilities, by name, firm, and trade specialty, for performance of each commissioning task.
- C. Convene commissioning team meetings for the purpose of coordination, communication, and conflict resolution; discuss progress of the commissioning processes. Responsibilities include arranging for facilities, preparing agenda and attendance lists, and notifying participants. The CxA shall prepare and distribute minutes to commissioning team members and attendees within five workdays of the commissioning meeting.
- D. At a mutually agreed upon time, conduct an initial construction-phase coordination meeting for the purpose of reviewing the commissioning activities and establishing tentative schedules for

operation and maintenance submittals; operation and maintenance training sessions; TAB Work; and Project completion.

- E. Observe and inspect construction and report progress and deficiencies. In addition to compliance with the Contract Documents, inspect systems and equipment installation for adequate accessibility for maintenance and component replacement or repair.
- F. Prepare Project-specific test and inspection procedures and checklists.
- G. Schedule, direct, witness, and document tests, inspections, and systems startup.
- H. Compile test data, inspection reports, and certificates and include them in the systems manual and commissioning report.
- I. Certify date of acceptance and startup for each item of equipment for start of warranty periods.
- J. Review Project Record Documents for accuracy. Request revisions from Contractor to achieve accuracy. Project Record Documents requirements are specified in Division 01 Section "Project Record Documents."
- K. Review and comment on operation and maintenance documentation and systems manual outline for compliance with the Contract Documents. Operation and maintenance documentation requirements are specified in Division 01 Section "Operation and Maintenance Data."
- L. Assemble the final commissioning documentation, including the commissioning report and Project Record Documents.

1.8 COMMISSIONING DOCUMENTATION

- A. Commissioning Plan: A document, prepared by CxA, that outlines the schedule, allocation of resources, and documentation requirements of the commissioning process, and shall include, but is not limited to the following:
 1. Plan for delivery and review of submittals, systems manuals, and other documents and reports. Identification of the relationship of these documents to other functions and a detailed description of submittals that are required to support the commissioning processes. Submittal dates shall include the latest date approved submittals must be received without adversely affecting commissioning plan.
 2. Description of the organization, layout, and content of commissioning documentation (including systems manual) and a detailed description of documents to be provided along with identification of responsible parties.
 3. Identification of systems and equipment to be commissioned.
 4. Description of schedules for testing procedures along with identification of parties involved in performing and verifying tests.
 5. Identification of items that must be completed before the next operation can proceed.
 6. Description of responsibilities of commissioning team members.
 7. Description of observations to be made.
 8. Description of requirements for operation and maintenance training, including required training materials.
 9. Description of expected performance for systems, subsystems, equipment, and controls.

10. Schedule for commissioning activities with specific dates coordinated with overall construction schedule.
 11. Identification of installed systems, subsystems, and equipment, including design changes that occurred during the construction phase.
 12. Process and schedule for documenting changes on a continuous basis to appear in Project Record Documents.
 13. Process and schedule for completing prestart and startup checklists for systems, subsystems, and equipment to be verified and tested.
 14. Step-by-step procedures for testing systems, subsystems, and equipment, with descriptions for methods of verifying relevant data, recording the results obtained, and listing parties involved in performing and verifying tests.
- B. Test Checklists: CxA, with assistance of Contractor and Subcontractors, shall develop test checklists for each system, subsystem, or equipment including interfaces and interlocks, and include a separate entry, with space for comments, for each item to be tested. Prepare separate checklists for each mode of operation and provide space to indicate whether the mode under test responded as required. Provide space for testing personnel to sign off on each checklist. Specific checklist content requirements are specified in Division 01 Section "HVAC Commissioning Requirements", "Electrical Commissioning Requirements" and "Plumbing System Commissioning Requirements". Test checklists will be jointly developed as the project progresses. Each checklist, regardless of system, subsystem, or equipment being tested, shall include, but not be limited to, the following:
1. Name and identification code of tested item.
 2. Test number.
 3. Time and date of test.
 4. Indication of whether the record is for a first test or retest following correction of a problem or issue.
 5. Dated signatures of the person performing test and of the witness, if applicable.
 6. Individuals present for test.
 7. Deficiencies.
 8. Issue number, if any, generated as the result of test.
- C. Certificate of Readiness: Certificate of Readiness shall be signed by Contractor, Subcontractor(s), Installer(s), and CxA certifying that systems, subsystems, equipment, and associated controls are ready for testing. Completed test checklists signed by the responsible parties shall accompany this certificate.
- D. Test and Inspection Reports: CxA shall record test data, observations, and measurements on test checklists. Photographs, forms, and other means appropriate for the application shall be included with data. CxA shall compile test and inspection reports and test and inspection certificates and include them in systems manual and commissioning report.
- E. Corrective Action Documents: CxA shall document corrective action taken for systems and equipment that fail tests. Include required modifications to systems and equipment and revisions to test procedures, if any. Retest systems and equipment requiring corrective action and document retest results.
- F. Issues Log: CxA shall prepare and maintain an issues log that describes design, installation, and performance issues that are at variance with the Contract Documents. Identify and track issues as they are encountered, documenting the status of unresolved and resolved issues.

1. Creating an Issues Log Entry:
 - a. Identify the issue with unique numeric or alphanumeric identifier by which the issue may be tracked.
 - b. Assign a descriptive title of the issue.
 - c. Identify date and time of the issue.
 - d. Identify test number of test being performed at the time of the observation, if applicable, for cross-reference.
 - e. Identify system, subsystem, and equipment to which the issue applies.
 - f. Identify location of system, subsystem, and equipment.
 - g. Include information that may be helpful in diagnosing or evaluating the issue.
 - h. Note recommended corrective action.
 - i. Identify commissioning team member responsible for corrective action.
 - j. Identify expected date of correction.
 - k. Identify person documenting the issue.

2. Documenting Issue Resolution:
 - a. Log date correction is completed or the issue is resolved.
 - b. Describe corrective action or resolution taken. Include description of diagnostic steps taken to determine root cause of the issue, if any.
 - c. Identify changes to the Contract Documents that may require action.
 - d. State that correction was completed and system, subsystem, and equipment is ready for retest, if applicable.
 - e. Identify person(s) who corrected or resolved the issue.
 - f. Identify person(s) documenting the issue resolution.

3. Issues Log Report: On a periodic basis, but not less than for each commissioning team meeting, CxA shall prepare a written narrative for review of outstanding issues and a status update of the issues log. As a minimum, CxA shall include the following information in the issues log and expand it in the narrative:
 - a. Issue number and title.
 - b. Date of the identification of the issue.
 - c. Name of the commissioning team member assigned responsibility for resolution.
 - d. Expected date of correction.

G. Commissioning Report: CxA shall document results of the commissioning process including unresolved issues and performance of systems, subsystems, and equipment. The commissioning report shall indicate whether systems, subsystems, and equipment have been completed and are performing according to the Contract Documents. The commissioning report shall include, but is not limited to, the following:

1. Lists and explanations of substitutions; compromises; variances in the Contract Documents; record of conditions; and, if appropriate, recommendations for resolution. This report shall be used to evaluate systems, subsystems, and equipment and shall serve as a future reference document during Owner occupancy and operation. It shall describe components and performance that exceed requirements of the Contract Documents and those that do not meet requirements of the Contract Documents. It may also include a recommendation for accepting or rejecting systems, subsystems, and equipment.
2. Commissioning plan.

3. Testing plans and reports.
4. Corrective modification documentation.
5. Issues log.
6. Completed test checklists.
7. Listing of off-season test(s) not performed and a schedule for their completion.
8. All commissioning documents must be submitted to the building Owner within 90 days of the date of receipt of the Certificate of Occupancy.

- H. Systems Manual: CxA shall gather required information and compile systems manual. Systems manual shall include, but is not limited to, the following:
1. Project Record Documents as specified in Division 01 Section "Project Record Documents."
 2. Final commissioning plan.
 3. Commissioning report.
 4. Operation and maintenance data as specified in Division 01 Section "Operation and Maintenance Data."

1.9 SUBMITTALS

- A. Test Checklists and Report Forms: CxA shall submit sample checklists and forms to Contractor quality-control manager and subcontractors for review and comment. Submit two copies of each checklist and report form.
- B. Test and Inspection Reports: CxA shall submit test and inspection reports.
- C. Corrective Action Documents: CxA shall submit corrective action documents.

1.10 QUALITY ASSURANCE

- A. Instructor Qualifications: Factory-authorized service representatives, experienced in training, operation, and maintenance procedures for installed systems, subsystems, and equipment.
- B. Test Equipment Calibration: Comply with test equipment manufacturer's calibration procedures and intervals. Recalibrate test instruments immediately whenever instruments have been repaired following damage or dropping. Affix calibration tags to test instruments. Instruments shall have been calibrated within six months prior to use.

1.11 COORDINATION

- A. Coordinating Meetings: CxA shall conduct coordination meetings of the commissioning team to review progress on the commissioning plan, to discuss scheduling conflicts, and to discuss upcoming commissioning process activities.
- B. Pretesting Meetings: CxA shall conduct pretest meetings of the commissioning team to review startup reports, pretest inspection results, testing procedures, testing personnel and instrumentation requirements, and manufacturers' authorized service representative services for each system, subsystem, equipment, and component to be tested.

- C. Testing Coordination: CxA shall coordinate sequence of testing activities to accommodate required quality-assurance and -control services with a minimum of delay and to avoid necessity of removing and replacing construction to accommodate testing and inspecting.
 - 1. Schedule times for tests, inspections, obtaining samples, and similar activities.
- D. Manufacturers' Field Services: CxA and Contractor shall coordinate services of manufacturers' field services.

1.12 ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION

3.1 OPERATION AND MAINTENANCE TRAINING REQUIREMENTS

- A. Training Preparation Conference: Before operation and maintenance training, CxA shall convene a training preparation conference to include Owner's operation and maintenance personnel, Contractor, and subcontractors. In addition to requirements specified in Division 01 Section "Demonstration and Training," perform the following:
 - 1. Review installed systems, subsystems, and equipment.
 - 2. Review instructor qualifications.
 - 3. Review instructional methods and procedures.
 - 4. Review training module outlines and contents.
 - 5. Review course materials (including operation and maintenance manuals).
 - 6. Inspect and discuss locations and other facilities required for instruction.
 - 7. Review and finalize training schedule and verify availability of educational materials, instructors, audiovisual equipment, and facilities needed to avoid delays.
 - 8. For instruction that must occur outside, review weather and forecasted weather conditions and procedures to follow if conditions are unfavorable.
- B. Training Modules: Develop an instruction program that includes individual training modules for each system, subsystem, and equipment as specified in Division 01 Section "Demonstration and Training."

END OF SECTION

SECTION 01 91 15

HVAC COMMISSIONING REQUIREMENTS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes requirements for commissioning the HVAC system and its subsystems and equipment. This Section supplements the general requirements specified in Division 01 Section "General Commissioning Requirements."

- B. Related Sections include the following:

1. Division 01 Section "General Commissioning Requirements" for general requirements for commissioning processes that apply to this Section.

- C. The following systems and/or equipment shall be commissioned:

1. 100% Outside Air Units
2. Air Flow Monitoring Stations.
3. Automatic Temperature Control System.
4. Boilers and burners.
5. Chilled water system/chiller.
6. Condensate overflow alarms.
7. Condensate pumps.
8. Duct detectors.
9. Ductless heat pumps and air conditioning units.
10. Electric Heaters/Radiant Heat Panels.
11. Exhaust Fans and ventilation fans.
12. Fan coil systems.
13. Flow measuring stations.
14. Flow Switches.
15. Freeze protection pumps.
16. High temperature alarms.
17. Hot water systems.
18. HVAC controls and sequences of operation.
19. Kitchen ventilation system.
20. Pumps.
21. Supply air systems, including steam humidifiers.
22. Variable frequency drives.
23. Variable refrigerant volume systems (indoor and outdoor units).
24. Variable refrigerant volume system ATC interface and systems integration.

1.3 DEFINITIONS

- A. Architect: Includes Architect identified in the Contract for Construction between Owner and Contractor, plus consultant/design professionals responsible for design of HVAC, electrical, communications, controls for HVAC systems, and other related systems.
- B. CxA: Commissioning Authority.
- C. Systems, Subsystems, and Equipment: Where these terms are used together or separately, they shall mean "as-built" systems, subsystems, and equipment.
- D. TAB: Testing, Adjusting, and Balancing.

1.4 CONTRACTOR'S RESPONSIBILITIES

- A. The following responsibilities are in addition to those specified in Division 01 Section "General Commissioning Requirements."
- B. Contractor:
 - 1. Attend procedures meeting for TAB Work.
 - 2. Certify that TAB Work is complete.
 - 3. Assist performing functional performance tests.
- C. Mechanical Contractor:
 - 1. Attend TAB verification testing.
 - 2. Provide measuring instruments and logging devices to record test data, and data acquisition equipment to record data for the complete range of testing for the required test period.
 - 3. Assist performing functional performance tests.
- D. HVAC Instrumentation and Control Contractor: With the CxA, review control designs for compliance with the Contract Documents, controllability with respect to actual equipment to be installed, and recommend adjustments to control designs and sequence of operation descriptions.
- E. TAB Subcontractor:
 - 1. Contract Documents Review: With the CxA, review the Contract Documents before developing TAB procedures.
 - a. Verify the following:
 - 1) Accessibility of equipment and components required for TAB Work.
 - 2) Adequate number and placement of duct balancing dampers to allow proper balancing while minimizing sound levels in occupied spaces.
 - 3) Adequate number and placement of balancing valves to allow proper balancing and recording of water flow.

- 4) Adequate number and placement of test ports and test instrumentation to allow reading and compilation of system and equipment performance data needed to conduct both TAB and commissioning testing.
 - 5) Air and water flow rates have been specified and compared to central equipment output capacities.
- b. Identify discontinuities and omissions in the Contract Documents.
 - c. This review of the Contract Documents by the TAB Subcontractor satisfies requirements for a design review report as specified in Division 23 Section "Testing Adjusting & Balancing for HVAC & Plumbing."
 - d. Assist performing functional performance tests.
2. Additional Responsibilities: Participate in tests specified in Division 23 Sections "Instrumentation & Controls of HVAC & Plumbing Systems."
- F. Electrical Contractor:
1. With the Mechanical Contractor, coordinate installations and connections between and among electrical and HVAC systems, subsystems, and equipment.
 2. Attend TAB verification testing.

1.5 COMMISSIONING DOCUMENTATION

- A. The following are in addition to documentation specified in Division 01 Section "General Commissioning Requirements."
- B. Test Checklists: CxA with assistance of Contractor shall develop test checklists for HVAC systems, subsystems, and equipment, including interfaces and interlocks with other systems. CxA shall prepare separate checklists for each mode of operation and provide space to indicate whether the mode under test responded as required. In addition to the requirements specified in Division 01 Section "General Commissioning Requirements," checklists shall include, but not be limited to, the following:
1. Calibration of sensors and sensor function.
 2. Testing conditions under which test was conducted, including (as applicable) ambient conditions, set points, override conditions, and status and operating conditions that impact the results of test.
 3. Control sequences for HVAC systems.
 4. Strength of control signal for each set point at specified conditions.
 5. Responses to control signals at specified conditions.
 6. Sequence of response(s) to control signals at specified conditions.
 7. Electrical demand or power input at specified conditions.
 8. Power quality and related measurements.
 9. Expected performance of systems, subsystems, and equipment at each step of test.
 10. Narrative description of observed performance of systems, subsystems, and equipment. Notation to indicate whether the observed performance at each step meets the expected results.
 11. Interaction of auxiliary equipment.
 12. Issues log.

1.6 SUBMITTALS

- A. The following submittals are in addition to those specified in Division 01 Section "General Commissioning Requirements."
- B. Testing Procedures: CxA shall submit detailed testing plan, procedures, and checklists for each series of tests. Submittals shall include samples of data reporting sheets that will be part of the reports.
- C. Certificate of Readiness: CxA shall compile certificates of readiness from Contractor certifying that systems, subsystems, equipment, and associated controls are ready for testing.
- D. Certificate of Completion of Installation, Prestart, and Startup: CxA shall certify that installation, prestart, and startup activities have been completed. Certification shall include completed checklists provided by TAB Subcontractor as specified in Division 23 Section "Testing Adjusting & Balancing for HVAC & Plumbing."
- E. Test and Inspection Reports: CxA shall compile and submit test and inspection reports and certificates, and shall include them in systems manual and commissioning report.
- F. Corrective Action Documents: CxA shall submit corrective action documents.
- G. Certified TAB Reports: CxA shall submit verified, certified TAB reports.

1.7 ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION

3.1 TESTING PREPARATION

- A. Prerequisites for Testing:

1. Certify that HVAC systems, subsystems, and equipment have been completed, calibrated, and started; are operating according to the Contract Documents; and that Certificates of Readiness are signed and submitted.
2. Certify that HVAC instrumentation and control systems have been completed and calibrated; are operating according to the Contract Documents; and that pretest set points have been recorded.
3. Certify that TAB procedures have been completed, and that TAB reports have been submitted, discrepancies corrected, and corrective work approved.
4. Test systems and intersystem performance after approval of test checklists for systems, subsystems, and equipment.

5. Set systems, subsystems, and equipment into operating mode to be tested (e.g., normal shut down, normal auto position, normal manual position, unoccupied cycle, emergency power, and alarm conditions).
6. Verify each operating cycle after it has been running for a specified period and is operating in a steady-state condition.
7. Inspect and verify the position of each device and interlock identified on checklists. Sign off each item as acceptable, or failed. Repeat this test for each operating cycle that applies to system being tested.
8. Check safety cutouts, alarms, and interlocks with duct detectors and life-safety systems during each mode of operation.
9. Annotate checklist or data sheet when a deficiency is observed.
10. Verify equipment interface with monitoring and control system and TAB criteria, include the following:
 - a. All temperature alarms.
 - b. All pump status alarms.
 - c. Supply and return flow rates for VAV and constant volume systems in each operational mode.
 - d. Minimum outdoor-air intake in each operational mode and at minimum and maximum airflows.
 - e. Total exhaust airflow and total outdoor-air intake.
 - f. Supply and return flow rates for water to air geothermal heat pump systems in each operational mode.
 - g. 100% outside air units.
 - h. Minimum outdoor-air intake in each operational mode and at minimum and maximum airflows.
 - i. Supply, outside air, exhaust and return air flow rates for ERVs in each operating mode.
 - j. Kitchen ventilation supply and exhaust air flow rates and temperatures, including optical and exhaust sensors.
 - k. Pump flow rates, pressure and amperage at each operating mode.
 - l. 100% outside air unit air and water flow rates and temperatures in each operating mode.
 - m. Sequences of operation of all HVAC equipment.
 - n. Ductless heat pumps and air conditioning units with air flow rates, fluid flow rates, and temperatures.
 - o. Variable speed drive parameters at each operated mode.
 - p. Electric heating equipment volts, amps, and temperature rise.
 - q. Boiler temperatures, flow rates, low water cut-off interlock, flame failure interlocks, and amperage.
 - r. Supply and return air flow rates for all HVAC equipment.
 - s. Operation/Accuracy of flow measuring stations at various flow rates.
 - t. Operation of variable refrigerant flow systems in all modes.
 - u. Chiller flow rates, temperatures, set points, and safeties.
 - v. Fluid flow rates and temperature for all water cooled equipment.
 - w. Set point and operation of "high temperature" alarms.
 - x. Test operation and air temperatures of hot gas re-heat coils.
 - y. Set point and operation of high temperature alarms.
 - z. Test freeze protection pumps.

11. Verify proper responses of monitoring and control system controllers and sensors to include the following:
 - a. For each controller or sensor, record the indicated monitoring and control system reading and the test instrument reading. If initial test indicates that the test reading is outside of the control range of the installed device, check calibration of the installed device and adjust as required. Retest malfunctioning devices and record results on checklist or data sheet.
 - b. Report deficiencies and prepare an issues log entry.
 12. Verify that HVAC equipment field quality-control testing has been completed and approved. CxA shall direct, witness, and document field quality-control tests, inspections, and startup specified in individual Division 23 Sections.
- B. Testing Instrumentation: Install measuring instruments and logging devices to record test data for the required test period. Instrumentation shall monitor and record full range of operating conditions and shall allow for calculation of total capacity of system for each mode of operation. For individual room cooling tests, provide temporary heaters to impose a cooling load. Operational modes include the following:
1. Heating/Cooling Mode.
 2. Occupied and unoccupied.
 3. Warm up and cool down.
 4. Life-safety and safety systems.
 5. Duct detectors.
 6. Fire safety.
 7. Temporary upset of system operation.
 8. Partial occupancy conditions.
 9. Special cycles.
 10. Variable refrigerant volume units in heating/cooling modes.
 11. Lead/standby modes where redundant equipment is indicated.
 12. All alarms.
 13. Kitchen make-up air unit and exhaust air fan at full, partial, and minimum air flow rates.
 14. Flow switch shut-down and alarm.
 15. Condensate overflow safety switch shut-down and alarm.
 16. Condensate pump operation.

3.2 TAB VERIFICATION

- A. TAB Subcontractor shall coordinate with CxA for work required in Division 23 Section "Testing Adjusting & Balancing for HVAC & Plumbing." TAB Subcontractor shall copy CxA with required reports, sample forms, checklists, and certificates.
- B. Contractor, HVAC Contractor, and CxA shall witness TAB Work.
- C. TAB Preparation:
 1. TAB Subcontractor shall provide CxA with data required for "Pre-Field TAB Engineering Reports" specified in Division 23 Section "Testing Adjusting & Balancing for HVAC & Plumbing."

- a. CxA shall use this data to certify that prestart and startup activities have been completed for systems, subsystems, and equipment installation.

D. Verification of Final TAB Report:

1. CxA shall select, at random, 10 percent of report for field verification.
2. CxA shall notify TAB Subcontractor 10 days in advance of the date of field verification; however, notice shall not include data points to be verified. The TAB Subcontractor shall use the same instruments (by model and serial number) that were used when original data were collected.
3. Failure of an item is defined as follows:
 - a. For all readings a deviation of more than 10 percent.
4. Failure of more than 10 percent of selected items shall result in rejection of final TAB report.

- E. If deficiencies are identified during verification testing, CxA shall notify the HVAC Contractor and Architect, and shall take action to remedy the deficiency. Architect shall review final tabulated checklists and data sheets to determine if verification is complete and that system is operating according to the Contract Documents.

- F. CxA shall certify that TAB Work has been successfully completed.

3.3 TESTING

- A. Test systems and intersystem performance after test checklists for systems, subsystems, and equipment have been approved.

- B. Perform tests using design conditions whenever possible.

1. Simulate conditions by imposing an artificial load when it is not practical to test under design conditions and when written approval for simulated conditions is received from CxA. Before simulating conditions, calibrate testing instruments. Set and document simulated conditions and methods of simulation. After tests, return settings to normal operating conditions.
2. Alter set points when simulating conditions is not practical and when written approval is received from CxA.
3. Alter sensor values with a signal generator when design or simulating conditions and altering set points are not practical. Do not use sensor to act as signal generator to simulate conditions or override values.

- C. Scope of HVAC Contractor Testing:

1. Testing scope shall include entire HVAC installation, from central equipment for heat generation and refrigeration through distribution systems to each conditioned space. It shall include measuring capacities and effectiveness of operational and control functions.
2. Test all operating modes, interlocks, control responses, responses to abnormal or emergency conditions, and verify proper response of building automation system controllers and sensors.

- D. Detailed Testing Procedures: CxA, with HVAC Contractor, TAB Subcontractor, and HVAC Instrumentation and Control Contractor, shall prepare detailed testing plans, procedures, and checklists for HVAC systems, subsystems, and equipment.
- E. HVAC Instrumentation and Control System Testing:
1. Field testing plans and testing requirements are specified in Division 23 Section "Instrumentation & Controls of HVAC & Plumbing Systems". The CxA, HVAC Contractor, Equipment Provider/Manufacturer and the HVAC Instrumentation and Control Contractor shall collaborate to prepare testing plans.
 2. CxA shall convene a meeting of appropriate entities to review test report of HVAC instrumentation and control systems.
- F. Energy Supply System Testing: HVAC Contractor shall prepare a testing plan to verify performance of gas systems and equipment. Plan shall include the following:
1. Sequence of testing and testing procedures for each equipment item and pipe section to be tested, identified by pipe zone or sector identification marker. Markers shall be keyed to Drawings for each pipe sector showing the physical location of each designated pipe test section. Drawings keyed to pipe zones or sectors shall be formatted to allow each section of piping to be physically located and identified when referred to in system testing plan.
 2. Tracking checklist for managing and ensuring that all pipe sections have been tested.
- G. Heat-Generation System Testing: HVAC Contractor shall prepare a testing plan to verify performance of air handling units, condensate receivers, and auxiliary equipment, variable refrigerant volume units, unit heaters, radiant heat panels, radiant heat panels, kitchen make-up air units, 100% outside air units, and hot gas re-heat coils. Plan shall include the following:
1. Sequence of testing and testing procedures for each item of equipment and section of pipe to be tested, identified by identification marker. Markers shall be keyed to Drawings for each pipe sector showing the physical location of each item of equipment and pipe test section. Drawings shall be formatted to allow each item of equipment and section of piping to be physically located and identified when referred to in the system testing plan.
 2. Tracking checklist for managing and ensuring that all pipe sections have been tested.
 3. Variable refrigerant flow equipment volts, amps, temperatures, and modes of operation.
- H. Refrigeration System Testing: HVAC Contractor shall prepare a testing plan to verify performance of chillers, refrigerant compressors, condensers, variable refrigerant volume systems, ductless units, and other refrigeration systems. Plan shall include the following:
1. Sequence of testing and testing procedures for each item of equipment and section of pipe to be tested, identified by identification marker. Markers shall be keyed to Drawings showing the physical location of each item of equipment and pipe test section. Drawings shall be formatted to allow each item of equipment and section of piping to be physically located and identified when referred to in the system testing plan.
 2. Tracking checklist for managing and ensuring that all pipe sections have been tested.
 3. Variable refrigerant flow equipment volts, amps, temperatures, and modes of operation.
- I. HVAC Distribution System Testing: HVAC Contractor shall prepare a testing plan to verify performance of air, air handling units, and hydronic distribution systems, special exhaust

kitchen ventilation systems, and other distribution systems. Include HVAC terminal equipment and unitary equipment. Plan shall include the following:

1. Sequence of testing and testing procedures for each item of equipment and section of pipe to be tested, identified by identification marker. Markers shall be keyed to Drawings showing the physical location of each item of equipment and pipe test section. Drawings shall be formatted to allow each item of equipment and section of piping to be physically located and identified when referred to in the system testing plan.
2. Tracking checklist for managing and ensuring that all pipe sections have been tested.
3. Equipment, air flow rates, air temperatures, fluid flow rates, safeties, freeze protection pump operation, and demand controlled ventilation.

J. Deferred Testing:

1. If tests cannot be completed because of a deficiency outside the scope of the HVAC system, the deficiency shall be documented and reported to Owner. Deficiencies shall be resolved and corrected by appropriate parties and test rescheduled.
2. If the testing plan indicates specific seasonal testing, appropriate initial performance tests shall be completed and documented and additional tests scheduled.

K. Testing Reports:

1. Reports shall include measured data, data sheets, and a comprehensive summary describing the operation of systems at the time of testing.
2. Include data sheets for each controller to verify proper operation of the control system, the system it serves, the service it provides, and its location. For each controller, provide space for recording its readout, the reading at the controller's sensor(s), plus comments. Provide space for testing personnel to sign off on each data sheet.
3. Prepare a preliminary test report. Deficiencies will be evaluated by Architect to determine corrective action. Deficiencies shall be corrected and test repeated.

END OF SECTION

SECTION 02 41 19

SELECTIVE DEMOLITION

PART 1 - GENERAL

1.1 SUMMARY

A. Section Includes:

1. Demolition and removal of selected portions of building or structure.
2. Salvage of existing items to be reused or recycled.

1.2 MATERIALS OWNERSHIP

- A. Unless otherwise indicated on the drawings, demolition waste becomes property of Contractor.

1.3 INFORMATIONAL SUBMITTALS

- A. Engineering Survey: Submit engineering survey of condition of building.
- B. Proposed Protection Measures: Submit report, including Drawings, that indicates the measures proposed for protecting individual and property, for dust control and for noise control. Indicate proposed locations and construction of barriers.
- C. Schedule of selective demolition activities with starting and ending dates for each activity.
- D. Predemolition photographs or video.
- E. Statement of Refrigerant Recovery: Signed by refrigerant recovery technician.

1.4 QUALITY ASSURANCE

- A. Refrigerant Recovery Technician Qualifications: Certified by an EPA-approved certification program.

1.5 FIELD CONDITIONS

- A. Owner will occupy portions of building immediately adjacent to selective demolition area. Conduct selective demolition so Owner's operations will not be disrupted.
- B. Conditions existing at time of inspection for bidding purpose will be maintained by Owner as far as practical.

- C. Notify Architect of discrepancies between existing conditions and Drawings before proceeding with selective demolition.
- D. Hazardous Materials: It is not expected that hazardous materials will be encountered in the Work.
 - 1. If suspected hazardous materials are encountered, do not disturb; immediately notify Architect and Owner. Hazardous materials will be removed by Owner under a separate contract.
- E. Storage or sale of removed items or materials on-site is not permitted.
- F. Utility Service: Maintain existing utilities indicated to remain in service and protect them against damage during selective demolition operations.
 - 1. Maintain fire-protection facilities in service during selective demolition operations.
- G. Arrange selective demolition schedule so as not to interfere with Owner's operations.

1.6 WARRANTY

- A. Existing Warranties: Remove, replace, patch, and repair materials and surfaces cut or damaged during selective demolition, by methods and with materials and using approved contractors so as not to void existing warranties.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. Regulatory Requirements: Comply with governing EPA notification regulations before beginning selective demolition. Comply with hauling and disposal regulations of authorities having jurisdiction.
- B. Standards: Comply with ASSE A10.6 and NFPA 241.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Verify that utilities have been disconnected and capped before starting selective demolition operations.
- B. Perform an engineering survey of condition of building to determine whether removing any element might result in structural deficiency or unplanned collapse of any portion of structure or adjacent structures during selective building demolition operations.

NOT FOR BIDDING PURPOSES

3.2 PREPARATION

- A. Refrigerant: Before starting demolition, remove refrigerant from mechanical equipment according to 40 CFR 82 and regulations of authorities having jurisdiction.

3.3 UTILITY SERVICES AND MECHANICAL/ELECTRICAL SYSTEMS

- A. Existing Services/Systems to Remain: Maintain services/systems indicated to remain and protect them against damage.
- B. Existing Services/Systems to Be Removed, Relocated, or Abandoned: Locate, identify, disconnect, and seal or cap off utility services and mechanical/electrical systems serving areas to be selectively demolished.
 - 1. Owner will arrange to shut off indicated services/systems when requested by Contractor.
 - 2. Arrange to shut off utilities with utility companies.
 - 3. If services/systems are required to be removed, relocated, or abandoned, provide temporary services/systems that bypass area of selective demolition and that maintain continuity of services/systems to other parts of building.
 - 4. Disconnect, demolish, and remove fire-suppression systems, plumbing, and HVAC systems, equipment, and components indicated on Drawings to be removed.
 - a. Piping to Be Removed: Remove portion of piping indicated to be removed and cap or plug remaining piping with same or compatible piping material.
 - b. Piping to Be Abandoned in Place: Drain piping and cap or plug piping with same or compatible piping material and leave in place.
 - c. Equipment to Be Removed: Disconnect and cap services and remove equipment.
 - d. Equipment to Be Removed and Reinstalled: Disconnect and cap services and remove, clean, and store equipment; when appropriate, reinstall, reconnect, and make equipment operational.
 - e. Equipment to Be Removed and Salvaged: Disconnect and cap services and remove equipment and deliver to Owner.
 - f. Ducts to Be Removed: Remove portion of ducts indicated to be removed and plug remaining ducts with same or compatible ductwork material.
 - g. Ducts to Be Abandoned in Place: Cap or plug ducts with same or compatible ductwork material and leave in place.

3.4 PROTECTION

- A. Temporary Protection: Provide temporary barricades and other protection required to prevent injury to people and damage to adjacent buildings and facilities to remain.
- B. Temporary Shoring: Design, provide, and maintain shoring, bracing, and structural supports as required to preserve stability and prevent movement, settlement, or collapse of construction and finishes to remain, and to prevent unexpected or uncontrolled movement or collapse of construction being demolished.
- C. Remove temporary barricades and protections where hazards no longer exist.

3.5 SELECTIVE DEMOLITION

- A. General: Demolish and remove existing construction only to the extent required by new construction and as indicated. Use methods required to complete the Work within limitations of governing regulations and as follows:
1. Neatly cut openings and holes plumb, square, and true to dimensions required. Use cutting methods least likely to damage construction to remain or adjoining construction. Use hand tools or small power tools designed for sawing or grinding, not hammering and chopping. Temporarily cover openings to remain.
 2. Cut or drill from the exposed or finished side into concealed surfaces to avoid marring existing finished surfaces.
 3. Do not use cutting torches.
 4. Locate selective demolition equipment and remove debris and materials so as not to impose excessive loads on supporting walls, floors, or framing.
 5. Dispose of demolished items and materials promptly.
- B. Site Access and Temporary Controls: Conduct selective demolition and debris-removal operations to ensure minimum interference with roads, streets, walks, walkways, and other adjacent occupied and used facilities.
- C. Removed and Salvaged Items:
1. Clean salvaged items.
 2. Pack or crate items after cleaning. Identify contents of containers.
 3. Store items in a secure area until delivery to Owner.
 4. Transport items to Owner's storage area off-site.
 5. Protect items from damage during transport and storage.
- D. Removed and Reinstalled Items:
1. Clean and repair items to functional condition adequate for intended reuse.
 2. Pack or crate items after cleaning and repairing. Identify contents of containers.
 3. Protect items from damage during transport and storage.
 4. Reinstall items in locations indicated. Comply with installation requirements for new materials and equipment. Provide connections, supports, and miscellaneous materials necessary to make item functional for use indicated.
- E. Existing Items to Remain: Protect construction indicated to remain against damage and soiling during selective demolition. When permitted by Architect, items may be removed to a suitable, protected storage location during selective demolition and cleaned and reinstalled in their original locations after selective demolition operations are complete.

3.6 CLEANING

- A. Remove demolition waste materials from Project site and dispose of them in an EPA-approved construction and demolition waste landfill acceptable to authorities having jurisdiction.
1. Do not allow demolished materials to accumulate on-site.

2. Remove and transport debris in a manner that will prevent spillage on adjacent surfaces and areas.
 3. Remove debris from elevated portions of building by chute, hoist, or other device that will convey debris to grade level in a controlled descent.
 4. Comply with requirements specified in Section 01 74 19 "Construction Waste Management and Disposal."
- B. Burning: Do not burn demolished materials.
- C. Clean adjacent structures and improvements of dust, dirt, and debris caused by selective demolition operations. Return adjacent areas to condition existing before selective demolition operations began.

END OF SECTION

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 03 30 00

CAST-IN-PLACE CONCRETE

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes cast-in-place concrete, including formwork, reinforcement, concrete materials, mixture design, placement procedures, and finishes.
- B. Related Requirements:
 - 1. See Civil Drawings General Notes, Section "Earth Moving" for drainage fill under slabs-on-grade.
 - 2. See Civil Drawings General Notes, Section "Concrete Paving" for concrete pavement and walks.

1.3 DEFINITIONS

- A. Cementitious Materials: Portland cement alone or in combination with one or more of the following: blended hydraulic cement, fly ash, and other pozzolans, materials subject to compliance with requirements.
- B. W/C Ratio: The ratio by weight of water to cementitious materials.

1.4 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.
 - 1. Before submitting design mixtures, review concrete design mixture and examine procedures for ensuring quality of concrete materials. Require representatives of each entity directly concerned with cast-in-place concrete to attend, including the following:
 - a. Contractor's superintendent.
 - b. Independent testing agency responsible for concrete design mixtures.
 - c. Ready-mix concrete manufacturer.
 - d. Concrete Subcontractor.
 - e. Special concrete finish Subcontractor.

2. Review special inspection and testing and inspecting agency procedures for field quality control, concrete finishes and finishing, cold- and hot-weather concreting procedures, curing procedures, construction contraction and isolation joints, and joint-filler strips, semi-rigid joint fillers, forms and form removal limitations, shoring and reshoring procedures, vapor-barrier installation, anchor rod and anchorage device installation tolerances, steel reinforcement installation, methods for achieving specified floor and slab flatness and levelness floor and slab flatness and levelness measurement, concrete repair procedures, and concrete protection.

1.5 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Design Mixtures: For each concrete mixture. Submit alternate design mixtures when characteristics of materials, Project conditions, weather, test results or other circumstances warrant adjustments.
 1. Indicate amounts of mixing water to be withheld for later addition at Project site.
- C. Steel Reinforcement Shop Drawings: Placing Drawings that detail fabrication, bending, and placement. Include bar sizes, lengths, material, grade, bar schedules, stirrup spacing, bent bar diagrams, bar arrangement, splices and laps, mechanical connections, tie spacing, hoop spacing, and supports for concrete reinforcement.
- D. Construction Joint Layout: Indicate proposed construction joints required to construct the structure.
 1. Location of construction joints is subject to approval of the Architect.
- E. Slab on Grade Contraction Control Joint Layout: Indicate proposed Slab on Grade Control Joints which meet specified requirements.
 1. Location of all Slab on Grade Control Joint are subject to approval of the Architect.
 2. Provide dimensions to all Slab on Grade Control Joint locations.
 3. Submittals to indicate all items associated with Slab on Grade Control Joints, such as:
 - a. Second-Pour "Diamonds" around all column pier locations inside Column Isolation Joints.
 - b. Additional rebar at mid-depth of slab at re-entrant corners, door openings, slab opening, etc.
 - c. Housekeeping pad layout

1.6 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For Installer, manufacturer and testing agency.
- B. Welding certificates.
- C. Material Certificates: For each of the following, signed by manufacturers:

1. Cementitious materials.
2. Admixtures.
3. Form materials and form-release agents.
4. Steel reinforcement and accessories.
5. Fiber reinforcement.
6. Curing compounds.
7. Floor and slab treatments.
8. Bonding agents.
9. Adhesives.
10. Vapor barrier.
11. Semirigid joint filler.
12. Joint-filler strips.
13. Repair materials.

D. Material Test Reports: For the following, from a qualified testing agency.

1. Aggregates

E. Formwork Shop Drawings: Prepared by or under the supervision of a qualified professional engineer, detailing fabrication, assembly, and support of formwork.

1. Shoring and Reshoring: Indicate proposed schedule and sequence of stripping formwork, shoring removal, and reshoring installation and removal.

F. Floor surface flatness and levelness measurements indicating compliance with specified tolerances.

G. Field quality-control reports.

H. Minutes of preinstallation conference.

1.7 QUALITY ASSURANCE

A. Installer Qualifications: A qualified installer who employs on Project personnel qualified as ACI-certified Flatwork Technician and Finisher and a supervisor who is an ACI-certified Concrete Flatwork Technician.

B. Manufacturer Qualifications: A firm experienced in manufacturing ready-mixed concrete products and that complies with ASTM C 94 requirements for production facilities and equipment.

1. Manufacturer certified according to NRMCA's "Certification of Ready Mixed Concrete Production Facilities."

C. Testing Agency Qualifications: An independent agency, qualified according to ASTM C 1077 and ASTM E 329 for testing indicated.

1. Personnel conducting field tests shall be qualified as ACI Concrete Field Testing Technician, Grade 1, according to ACI CP-1 or an equivalent certification program.

2. Personnel performing laboratory tests shall be ACI-certified Concrete Strength Testing Technician and Concrete Laboratory Testing Technician, Grade I. Testing agency laboratory supervisor shall be an ACI-certified Concrete Laboratory Testing Technician, Grade II.

D. Welding Qualifications: Qualify procedures and personnel according to AWS D1.4.

1.8 PRECONSTRUCTION TESTING

- A. Preconstruction Testing Service: Engage a qualified testing agency to perform preconstruction testing on concrete mixtures.

1.9 DELIVERY, STORAGE, AND HANDLING

- A. Steel Reinforcement: Deliver, store, and handle steel reinforcement to prevent bending and damage. Avoid damaging coatings on steel reinforcement.

1.10 FIELD CONDITIONS

- A. Cold-Weather Placement: Comply with ACI 308.1 and as follows. Protect concrete work from physical damage or reduced strength that could be caused by frost, freezing actions, or low temperatures.

1. When average high and low temperature is expected to fall below 40 deg F for three successive days, maintain delivered concrete mixture temperature within the temperature range required by ACI 308.1.
2. Do not use frozen materials or materials containing ice or snow. Do not place concrete on frozen subgrade or on subgrade containing frozen materials.
3. Do not use calcium chloride, salt, or other materials containing antifreeze agents or chemical accelerators unless otherwise specified and approved in mixture designs.

- B. Hot-Weather Placement: Comply with ACI 301 and as follows:

1. Maintain concrete temperature below 90 deg F at time of placement. Chilled mixing water or chopped ice may be used to control temperature, provided water equivalent of ice is calculated to total amount of mixing water. Using liquid nitrogen to cool concrete is Contractor's option.
2. Fog-spray forms, steel reinforcement, and subgrade just before placing concrete. Keep subgrade uniformly moist without standing water, soft spots, or dry areas.

PART 2 - PRODUCTS

2.1 CONCRETE, GENERAL

- A. ACI Publications: Comply with the following unless modified by requirements in the Contract Documents:

1. ACI 301.
2. ACI 117.

2.2 FORM-FACING MATERIALS

- A. Smooth-Formed Finished Concrete: Form-facing panels that provide continuous, true, and smooth concrete surfaces. Furnish in largest practicable sizes to minimize number of joints.
1. Plywood, metal, or other approved panel materials.
 2. Exterior-grade plywood panels, suitable for concrete forms, complying with BOAC PS 1, and as follows:
 - a. High-density overlay, Class 1 or better.
 - b. Medium-density overlay, Class 1 or better; mill-release agent treated and edge sealed.
 - c. Structural 1, B-B or better; mill oiled and edge sealed.
 - d. B-B (Concrete Form), Class 1 or better; mill oiled and edge sealed.
 3. Overlaid Finnish birch plywood.
- B. Rough-Formed Finished Concrete: Plywood, lumber, metal, or another approved material. Provide lumber dressed on at least two edges and one side for tight fit.
- C. Pan-Type Forms: Glass-fiber-reinforced plastic or formed steel, stiffened to resist plastic concrete loads without detrimental deformation.
- D. Chamfer Strips: Wood, metal, PVC, or rubber strips, 3/4 by 3/4 inch, minimum.
- E. Rustication Strips: Wood, metal, PVC, or rubber strips, kerfed for ease of form removal.
- F. Form-Release Agent: Commercially formulated form-release agent that does not bond with, stain, or adversely affect concrete surfaces and does not impair subsequent treatments of concrete surfaces.
1. Formulate form-release agent with rust inhibitor for steel form-facing materials.
- G. Form Ties: Factory-fabricated, removable or snap-off glass-fiber-reinforced plastic or metal form ties designed to resist lateral pressure of fresh concrete on forms and to prevent spalling of concrete on removal.
1. Furnish units that leave no corrodible metal closer than 1 inch to the plane of exposed concrete surface.

2.3 STEEL REINFORCEMENT

- A. Reinforcing Bars: ASTM A 615, Grade 60, deformed.
- B. Galvanized Reinforcing Bars: ASTM A 615, Grade 60, deformed bars, ASTM A 767, Class I zinc coated after fabrication and bending.

- C. Plain-Steel Wire: ASTM A 1064/A 1064M, as drawn.
- D. Deformed-Steel Wire: ASTM A 1064/A 1064M.

2.4 REINFORCEMENT ACCESSORIES

- A. Joint Dowel Bars: ASTM A 615, Grade 60, plain-steel bars, cut true to length with ends square and free of burrs.
- B. Zinc Repair Material: ASTM A 780.
- C. Bar Supports: Bolsters, chairs, spacers, and other devices for spacing, supporting, and fastening reinforcing bars in place precast concrete according to CRSI's "Manual of Standard Practice," of greater compressive strength than concrete and as follows:
 1. For concrete surfaces exposed to view, where legs of wire bar supports contact forms, use CRSI Class 1 plastic-protected steel wire or CRSI Class 2 stainless-steel bar supports.
 2. For zinc-coated reinforcement, use galvanized wire or dielectric-polymer-coated wire bar supports.

2.5 CONCRETE MATERIALS

- A. Source Limitations: Obtain each type or class of cementitious material of the same brand from the same manufacturer's plant, obtain aggregate from single source, and obtain admixtures from single source from single manufacturer.
- B. Cementitious Materials:
 1. Portland Cement: ASTM C 150, Type I; Type II or Type I/II gray.
 2. Fly Ash: ASTM C 418, Class F or C.
 3. Blended Hydraulic Cement: ASTM C 595, Type IS, portland blast-furnace slag, Type IP, portland-pozzolan, Type IL, portland-limestone, or Type IT, ternary blended cement.
- C. Normal-Weight Aggregates: ASTM C 33, Class 3S coarse aggregate or better, graded. Provide aggregates from a single source with documented service record data of at least 10 years' satisfactory service in similar applications and service conditions using similar aggregates and cementitious materials. ASTM C33, Class 4S coarse aggregate or better, graded, for exterior concrete.
 1. Maximum Coarse-Aggregate Size:
 - a. 1-1/2 inches nominal, for slabs on grade.
 - b. All other concrete: 1 inch nominal.
 2. Fine Aggregate: Free of materials with deleterious reactivity to alkali in cement.
- D. Air-Entraining Admixture: ASTM C 260.
- E. Chemical Admixtures: Certified by manufacturer to be compatible with other admixtures and that do not contribute water-soluble chloride ions exceeding those permitted in hardened concrete. Do not use calcium chloride or admixtures containing calcium chloride.

1. Water-Reducing Admixture: ASTM C 494/C 494M, Type A.
2. Retarding Admixture: ASTM C 494/C 494M, Type B.
3. Water-Reducing and Retarding Admixture: ASTM C 494/C 494M, Type D.
4. High-Range, Water-Reducing Admixture: ASTM C 494/C 494M, Type F.
5. High-Range, Water-Reducing and Retarding Admixture: ASTM C 494/C 494M, Type G.
6. Plasticizing and Retarding Admixture: ASTM C 1017/C 1017M, Type II.

F. Water: ASTM C 94 and potable.

2.6 FIBER REINFORCEMENT

- A. Synthetic Macro-Fiber: Polyolefin macro-fibers engineered and designed for use in concrete, complying with ASTM C 1116, Type III, 1 to 2-1/4 inches long.

2.7 VAPOR BARRIER

- A. Vapor Barrier: Water-vapor transmission rate (permeance) less than 0.015 perms (gr/ft²/hr/in-Hg), in accordance with ASTM E 1745. The product must meet water-vapor transmission rate (0.01 perms) requirement for both the new material and the ASTM E 1745 mandatory conditioning test (ASTM E 1745; paragraph 7.12 through 7.15.) Provide all manufacturers' accessories required for complete installation including mastic and seam tape. Seam tape to be provided with a water-vapor transmission rate of 0.3 perms or lower.

1. Products: Subject to compliance with requirements, provide one of the following:

- a. Layfield Construction Materials; VaporFlex 15.
- b. Reef Industries, Inc.; Griffon Vaproguard.
- c. Stego Industries, LLC; Stego Wrap 15 mil Class A.

2.8 LIQUID FLOOR TREATMENTS

- A. Penetrating Liquid Floor Treatment: Clear, chemically reactive, waterborne solution of inorganic silicate or silicate materials and proprietary components; odorless; that penetrates, hardens, and densifies concrete surfaces.

2.9 CURING MATERIALS

- A. Evaporation Retarder: Waterborne, monomolecular film forming, manufactured for application to fresh concrete.
- B. Moisture-Retaining Cover: ASTM C 171, polyethylene film or white burlap-polyethylene sheet.
- C. Water: Potable.
- D. Clear, Waterborne, Membrane-Forming Curing Compound: ASTM C 309, Type 1, Class B, nondissipating, certified by curing compound manufacturer to not interfere with bonding of floor covering.

- E. Clear, Waterborne, Membrane-Forming Curing and Sealing Compound: ASTM C 1315, Type 1, Class A.

2.10 RELATED MATERIALS

- A. Expansion- and Isolation-Joint-Filler Strips: ASTM D 1751, asphalt-saturated cellulosic fiber or ASTM D 1752, cork or self-expanding cork.
- B. Bonding Agent: ASTM C 1059, Type II, nonredispersible, acrylic emulsion or styrene butadiene.
- C. Epoxy Bonding Adhesive: ASTM C 881, two-component epoxy resin, capable of humid curing and bonding to damp surfaces, of class suitable for application temperature and of grade to suit requirements, and as follows:
 - 1. Types I and II, nonload bearing or Types IV and V, load bearing, for bonding hardened or freshly mixed concrete to hardened concrete.
- D. Reglets: Fabricate reglets of not less than 0.022-inch-thick, galvanized-steel sheet. Temporarily fill or cover face opening of reglet to prevent intrusion of concrete or debris.
- E. Dovetail Anchor Slots: Hot-dip galvanized-steel sheet, not less than 0.034 inch thick, with bent tab anchors. Temporarily fill or cover face opening of slots to prevent intrusion of concrete or debris.

2.11 REPAIR MATERIALS

- A. Repair Underlayment: Cement-based, polymer-modified, self-leveling product that can be applied in thicknesses from 1/8 inch and that can be feathered at edges to match adjacent floor elevations.
 - 1. Cement Binder: ASTM C 150, portland cement or hydraulic or blended hydraulic cement as defined in ASTM C 219.
 - 2. Primer: Product of underlayment manufacturer recommended for substrate, conditions, and application.
 - 3. Aggregate: Well-graded, washed gravel, 1/8 to 1/4 inch or coarse sand as recommended by underlayment manufacturer.
 - 4. Compressive Strength: Not less than 4100 psi at 28 days when tested according to ASTM C 109/C 109M.
- B. Repair Overlayment: Cement-based, polymer-modified, self-leveling product that can be applied in thicknesses from 1/4 inch and that can be filled in over a scarified surface to match adjacent floor elevations.
 - 1. Cement Binder: ASTM C 150, portland cement or hydraulic or blended hydraulic cement as defined in ASTM C 219.
 - 2. Primer: Product of topping manufacturer recommended for substrate, conditions, and application.

3. Aggregate: Well-graded, washed gravel, 1/8 to 1/4 inch or coarse sand as recommended by topping manufacturer.
4. Compressive Strength: Not less than 5000 psi at 28 days when tested according to ASTM C 109/C 109M.

2.12 CONCRETE MIXTURES, GENERAL

- A. Prepare design mixtures for each type and strength of concrete, proportioned on the basis of laboratory trial mixture or field test data, or both, according to ACI 301.
 1. Use a qualified independent testing agency for preparing and reporting proposed mixture designs based on laboratory trial mixtures.
- B. Cementitious Materials: Use fly ash, and pozzolan, as needed to reduce the total amount of portland cement, which would otherwise be used, by not less than 40 percent. Limit percentage, by weight, of cementitious materials other than portland cement in concrete as follows:
 1. Fly Ash: 25 percent.
 2. Combined Fly Ash and Pozzolan: 25 percent.
- C. Admixtures: Use admixtures according to manufacturer's written instructions.
 1. Use water-reducing, high-range water-reducing or plasticizing admixture in concrete, as required, for placement and workability.
 2. Use water-reducing and -retarding admixture when required by high temperatures, low humidity, or other adverse placement conditions.
 3. Use water-reducing admixture in pumped concrete, and concrete with a w/c ratio below 0.50.
 4. Use corrosion-inhibiting admixture in concrete mixtures where indicated.

2.13 CONCRETE MIXTURES FOR BUILDING ELEMENTS

- A. Footings and Foundation Walls: Normal-weight concrete.
 1. Minimum Compressive Strength 4,000 psi at 28 days.
 2. Maximum W/C Ratio: 0.50.
 3. Slump Limit: 4 inches, 8 inches for concrete with verified slump of 2 to 4 inches before adding high-range water-reducing admixture or plasticizing admixture plus or minus 1 inch.
 4. Air Content: 6 percent, plus or minus 1.5 percent at point of delivery for 1-inch nominal maximum aggregate size.
- B. Slabs-on-Grade: Normal-weight concrete.
 1. Minimum Compressive Strength: 4,000 psi at 28 days.
 2. Maximum W/C Ratio: 0.50.
 3. Minimum Cementitious Materials Content: 470 lb/cu. yd..
 4. Slump Limit: 4 inches plus or minus 1 inch.
 5. Air Content: Do not allow air content of trowel-finished floors to exceed 3 percent.

C. Suspended Slabs: Normal-weight concrete.

1. Minimum Compressive Strength: 4000 psi.
2. Maximum W/C Ratio: 0.45.
3. Minimum Cementitious Materials Content: 520 lb/cu. yd..
4. Slump Limit: 4 inches, 8 inches for concrete with verified slump of 2 to 4 inches before adding high-range water-reducing admixture or plasticizing admixture, plus or minus 1 inch.
5. Air Content: Do not allow air content of trowel-finished floors to exceed 3 percent.
6. Synthetic Macro-Fiber: Uniformly disperse in concrete mixture at manufacturer's recommended rate, but not less than a rate of 3.0 lb/cu. yd..

2.14 FABRICATING REINFORCEMENT

- A. Fabricate steel reinforcement according to CRSI's "Manual of Standard Practice."

2.15 CONCRETE MIXING

- A. Ready-Mixed Concrete: Measure, batch, mix, and deliver concrete according to ASTM C 94 and ASTM C 1116, and furnish batch ticket information.
1. When air temperature is between 85 and 90 deg F, reduce mixing and delivery time from 1-1/2 hours to 75 minutes; when air temperature is above 90 deg F, reduce mixing and delivery time to 60 minutes.

PART 3 - EXECUTION

3.1 FORMWORK INSTALLATION

- A. Design, erect, shore, brace, and maintain formwork, according to ACI 301, to support vertical, lateral, static, and dynamic loads, and construction loads that might be applied, until structure can support such loads.
- B. Construct formwork so concrete members and structures are of size, shape, alignment, elevation, and position indicated, within tolerance limits of ACI 117.
- C. Limit concrete surface irregularities, designated by ACI 347 as abrupt or gradual, as follows:
1. Class A, 1/8 inch for smooth-formed finished surfaces.
 2. Class B, 1/4 inch for rough-formed finished surfaces.
- D. Construct forms tight enough to prevent loss of concrete mortar.
- E. Construct forms for easy removal without hammering or prying against concrete surfaces. Provide crush or wrecking plates where stripping may damage cast-concrete surfaces. Provide top forms for inclined surfaces steeper than 1.5 horizontal to 1 vertical.
1. Install keyways, reglets, recesses, and the like, for easy removal.

2. Do not use rust-stained steel form-facing material.
- F. Set edge forms, bulkheads, and intermediate screed strips for slabs to achieve required elevations and slopes in finished concrete surfaces. Provide and secure units to support screed strips; use strike-off templates or compacting-type screeds.
- G. Provide temporary openings for cleanouts and inspection ports where interior area of formwork is inaccessible. Close openings with panels tightly fitted to forms and securely braced to prevent loss of concrete mortar. Locate temporary openings in forms at inconspicuous locations.
- H. Chamfer exterior corners and edges of permanently exposed concrete.
- I. Form openings, chases, offsets, sinkages, keyways, reglets, blocking, screens, and bulkheads required in the Work. Determine sizes and locations from trades providing such items.
- J. Clean forms and adjacent surfaces to receive concrete. Remove chips, wood, sawdust, dirt, and other debris just before placing concrete.
- K. Retighten forms and bracing before placing concrete, as required, to prevent mortar leaks and maintain proper alignment.
- L. Coat contact surfaces of forms with form-release agent, according to manufacturer's written instructions, before placing reinforcement.

3.2 EMBEDDED ITEM INSTALLATION

- A. Place and secure anchorage devices and other embedded items required for adjoining work that is attached to or supported by cast-in-place concrete. Use setting drawings, templates, diagrams, instructions, and directions furnished with items to be embedded.
 1. Install anchor rods accurately located, to elevations required and complying with tolerances in Section 05 of AISC 303.
 2. Install dowel anchor slots in concrete structures as indicated.

3.3 REMOVING AND REUSING FORMS

- A. General: Formwork for sides of beams, walls, columns, and similar parts of the Work that does not support weight of concrete may be removed after cumulatively curing at not less than 50 deg F for 24 hours after placing concrete. Concrete has to be hard enough to not be damaged by form-removal operations, and curing and protection operations need to be maintained.
 1. Remove forms only if shores have been arranged to permit removal of forms without loosening or disturbing shores.
- B. Clean and repair surfaces of forms to be reused in the Work. Split, frayed, delaminated, or otherwise damaged form-facing material are not acceptable for exposed surfaces. Apply new form-release agent.
- C. When forms are reused, clean surfaces, remove fins and laitance, and tighten to close joints. Align and secure joints to avoid offsets. Do not use patched forms for exposed concrete surfaces unless approved by Architect.

3.4 SHORING AND RESHORING INSTALLATION

- A. Comply with ACI 318 and ACI 301 for design, installation, and removal of shoring and reshoring.
 - 1. Do not remove shoring or reshoring until measurement of slab tolerances is complete.
- B. In multistory construction, extend shoring or reshoring over a sufficient number of stories to distribute loads in such a manner that no floor or member will be excessively loaded or will induce tensile stress in concrete members without sufficient steel reinforcement.
- C. Plan sequence of removal of shores and reshore to avoid damage to concrete. Locate and provide adequate reshoring to support construction without excessive stress or deflection.

3.5 VAPOR-BARRIER INSTALLATION

- A. Sheet Vapor Barriers: Place, protect, and repair sheet vapor barrier according to ASTM E 1643 and manufacturer's written instructions.
 - 1. Lap joints 6 inches and seal with manufacturer's recommended tape.

3.6 STEEL REINFORCEMENT INSTALLATION

- A. General: Comply with CRSI's "Manual of Standard Practice" for fabricating, placing, and supporting reinforcement.
 - 1. Do not cut or puncture vapor barrier. Repair damage and reseal vapor barrier before placing concrete.
- B. Clean reinforcement of loose rust and mill scale, earth, ice, and other foreign materials that reduce bond to concrete.
- C. Accurately position, support, and secure reinforcement against displacement. Locate and support reinforcement with bar supports to maintain minimum concrete cover. Do not tack weld crossing reinforcing bars.
 - 1. Weld reinforcing bars according to AWS D1.4/D 1.4M, where indicated.
- D. Set wire ties with ends directed into concrete, not toward exposed concrete surfaces.
- E. Zinc-Coated Reinforcement: Repair cut and damaged zinc coatings with zinc repair material according to ASTM A 780/A 780M. Use galvanized-steel wire ties to fasten zinc-coated steel reinforcement.

3.7 JOINTS

- A. General: Construct joints true to line with faces perpendicular to surface plane of concrete.

- B. Construction Joints: Install so strength and appearance of concrete are not impaired, at locations indicated or as approved by Architect.
1. Place joints perpendicular to main reinforcement. Continue reinforcement across construction joints unless otherwise indicated. Do not continue reinforcement through sides of strip placements of floors and slabs.
 2. Form keyed joints as indicated. Embed keys at least 1-1/2 inches into concrete.
 3. Locate horizontal joints in walls and columns at the top of footings or floor slabs.
 4. Space vertical joints in walls as indicated. Locate joints beside piers integral with walls near corners, and in concealed locations where possible.
 5. Use a bonding agent at locations where fresh concrete is placed against hardened or partially hardened concrete surfaces.
 6. Use epoxy-bonding adhesive at locations where fresh concrete is placed against hardened or partially hardened concrete surfaces.
- C. Contraction/Control Joints in Slabs-on-Grade: Form weakened-plane contraction/control joints, sectioning concrete into areas as approved in Contractor Finished Slab on Grade Contraction/Control Joint Layout Shop Drawings. Construct contraction/control joints for a depth equal to at least one-fourth of concrete thickness as follows:
1. Grooved Joints: Form contraction/control joints after initial floating by grooving and finishing each edge of joint to a radius of 1/8 inch. Repeat grooving of contraction/control joints after applying surface finishes. Eliminate groover tool marks on concrete surfaces.
 2. Sawed Joints: Form contraction/control joints with power saws equipped with shatterproof abrasive or diamond-tipped blades. Cut 1/8-inch-wide joints into concrete when cutting action does not tear, abrade, or otherwise damage surface and before concrete develops random contraction cracks.
 3. Install Contraction/Control Joints at maximum 15 feet in on center in both directions. Install on column lines wherever possible.
- D. Isolation Joints in Slabs-on-Grade: After removing formwork, install joint-filler strips at slab junctions with vertical surfaces, such as column pedestals, foundation walls, grade beams, and other locations as indicated.
1. Extend joint-filler strips full width and depth of joint, terminating flush with finished concrete surface unless otherwise indicated.
 2. Terminate full-width joint-filler strips not less than 1/2 inch or more than 1 inch below finished concrete surface where joint sealants, specified in Section 07 92 00 "Joint Sealants," are indicated.
 3. Install joint-filler strips in lengths as long as practicable. Where more than one length is required, lace or clip sections together.
- E. Doweled Joints: Install dowel bars and support assemblies at joints where indicated. Lubricate or asphalt coat one-half of dowel length to prevent concrete bonding to one side of joint.

3.8 CONCRETE PLACEMENT

- A. Before placing concrete, verify that installation of formwork, reinforcement, and embedded items is complete and that required inspections are completed.

- B. Do not add water to concrete during delivery, at Project site, or during placement unless approved by Architect.
- C. Before test sampling and placing concrete, water may be added at Project site, subject to limitations of ACI 301.
1. Do not add water to concrete after adding high-range water-reducing admixtures to mixture.
- D. Deposit concrete continuously in one layer or in horizontal layers of such thickness that no new concrete is placed on concrete that has hardened enough to cause seams or planes of weakness. If a section cannot be placed continuously, provide construction joints as indicated. Deposit concrete to avoid segregation.
1. Deposit concrete in horizontal layers of depth not to exceed formwork design pressures and in a manner to avoid inclined construction joints.
 2. Consolidate placed concrete with mechanical vibrating equipment according to ACI 301.
 3. Do not use vibrators to transport concrete inside forms. Insert and withdraw vibrators vertically at uniformly spaced locations to rapidly penetrate placed layer and at least 6 inches into preceding layer. Do not insert vibrators into lower layers of concrete that have begun to lose plasticity. At each insertion, limit duration of vibration to time necessary to consolidate concrete and complete embedment of reinforcement and other embedded items without causing mixture constituent to segregate.
- E. Deposit and consolidate concrete for floors and slabs in a continuous operation, within limits of construction joints, until placement of a panel or section is complete.
1. Consolidate concrete during placement operations, so concrete is thoroughly worked around reinforcement and other embedded items and into corners.
 2. Maintain reinforcement in position on chairs during concrete placement.
 3. Screed slab surfaces with a straightedge and strike off to correct elevations.
 4. Slope surfaces uniformly to drains where required.
 5. Begin initial floating using bull floats or darbies to form a uniform and open-textured surface plane, before excess bleedwater appears on the surface. Do not further disturb slab surfaces before starting finishing operations.

3.9 FINISHING FORMED SURFACES

- A. Rough-Formed Finish: As-cast concrete texture imparted by form-facing material with tie holes and defects repaired and patched. Remove fins and other projections that exceed specified limits on formed-surface irregularities.
1. Apply to concrete surfaces not exposed to public view.
- B. Smooth-Formed Finish: As-cast concrete texture imparted by form-facing material, arranged in an orderly and symmetrical manner with a minimum of seams. Repair and patch tie holes and defects. Remove fins and other projections that exceed specified limits on formed-surface irregularities.

1. Apply to concrete surfaces exposed to public view; to receive a rubbed finish; or to be covered with a coating or covering material applied directly to concrete.
- C. Rubbed Finish: Apply the following to smooth-formed-finished as-cast concrete where indicated:
1. Smooth-Rubbed Finish: Not later than one day after form removal, moisten concrete surfaces and rub with carborundum brick or another abrasive until producing a uniform color and texture. Do not apply cement grout other than that created by the rubbing process.
- D. Related Unformed Surfaces: At tops of walls, horizontal offsets, and similar unformed surfaces adjacent to formed surfaces, strike off smooth and finish with a texture matching adjacent formed surfaces. Continue final surface treatment of formed surfaces uniformly across adjacent unformed surfaces unless otherwise indicated.

3.10 FINISHING FLOORS AND SLABS

- A. General: Comply with ACI 302.1R recommendations for screeding, restraigthening, and finishing operations for concrete surfaces. Do not wet concrete surfaces.
- B. Scratch Finish: While still plastic, texture concrete surface that has been screeded and bull-floated or darbied. Use stiff brushes, brooms, or rakes to produce a profile amplitude of 1/4 inch in one direction.
1. Apply scratch finish to surfaces to receive concrete floor toppings.
- C. Trowel Finish: After applying float finish, apply first troweling and consolidate concrete by hand or power-driven trowel. Continue troweling passes and restraighthen until surface is free of trowel marks and uniform in texture and appearance. Grind smooth any surface defects that would telegraph through applied coatings or floor coverings.
1. Apply a trowel finish to surfaces exposed to view or to be covered with resilient flooring, carpet, ceramic or quarry tile set over a cleavage membrane, paint, or another thin-film-finish coating system.
 2. Finish surfaces to the following tolerances, according to ASTM E 1155, for a randomly trafficked floor surface:
 1. Specified overall values of flatness, F(F) 35; and of levelness, F(L) 25; with minimum local values of flatness, F(F) 24; and of levelness, F(L) 17; for slabs-on-grade.
- D. Broom Finish: Apply a broom finish to exterior concrete platforms, steps, ramps, and elsewhere as indicated.
1. Immediately after float finishing, slightly roughen trafficked surface by brooming with fiber-bristle broom perpendicular to main traffic route. Coordinate required final finish with Architect before application.

3.11 MISCELLANEOUS CONCRETE ITEM INSTALLATION

- A. Filling In: Fill in holes and openings left in concrete structures after work of other trades is in place unless otherwise indicated. Mix, place, and cure concrete, as specified, to blend with in-place construction. Provide other miscellaneous concrete filling indicated or required to complete the Work.
- B. Curbs: Provide monolithic finish to interior curbs by stripping forms while concrete is still green and by steel-troweling surfaces to a hard, dense finish with corners, intersections, and terminations slightly rounded.
- C. Equipment Bases and Foundations:
1. Coordinate sizes and locations of concrete bases with actual equipment provided.
 2. Construct concrete bases 6 inches high unless otherwise indicated, and extend base not less than 6 inches in each direction beyond the maximum dimensions of supported equipment unless otherwise indicated or unless required for seismic anchor support.
 3. Minimum Compressive Strength: 4000 psi at 28 days.
 4. Install dowel rods to connect concrete base to concrete floor. Unless otherwise indicated, install dowel rods on 18-inch centers around the full perimeter of concrete base.
 5. For supported equipment, install epoxy-coated anchor bolts that extend through concrete base and anchor into structural concrete substrate.
 6. Prior to pouring concrete, place and secure anchorage devices. Use setting drawings, templates, diagrams, instructions, and directions furnished with items to be embedded.
 7. Cast anchor-bolt insert into bases. Install anchor bolts to elevations required for proper attachment to supported equipment.

3.12 CONCRETE PROTECTING AND CURING

- A. General: Protect freshly placed concrete from premature drying and excessive cold or hot temperatures. Comply with ACI 306.1 for cold-weather protection and ACI 301 for hot-weather protection during curing.
- B. Evaporation Retarders: Apply evaporation retarder to unformed concrete surfaces if hot, dry, or windy conditions cause moisture loss approaching 0.2 lb/sq. ft. x h before and during finishing operations. Apply according to manufacturer's written instructions after placing, screeding, and bull floating or darbying concrete, but before float finishing.
- C. Formed Surfaces: Cure formed concrete surfaces. If forms remain during curing period, moist cure after loosening forms. If removing forms before end of curing period, continue curing for remainder of curing period.
- D. Unformed Surfaces: Begin curing immediately after finishing concrete. Cure unformed surfaces, including floors and slabs, concrete floor toppings, and other surfaces.
- E. Cure concrete according to ACI 308.1, by one or a combination of the following methods:
1. Moisture Curing: Keep surfaces continuously moist for not less than seven days with the following materials:

- a. Water.
 - b. Continuous water-fog spray.
 - c. Absorptive cover, water saturated, and kept continuously wet. Cover concrete surfaces and edges with 12-inch lap over adjacent absorptive covers.
2. Moisture-Retaining-Cover Curing: Cover concrete surfaces with moisture-retaining cover for curing concrete, placed in widest practicable width, with sides and ends lapped at least 12 inches, and sealed by waterproof tape or adhesive. Cure for not less than seven days. Immediately repair any holes or tears during curing period, using cover material and waterproof tape.
- a. Moisture cure or use moisture-retaining covers to cure concrete surfaces to receive floor coverings.
 - b. Moisture cure or use moisture-retaining covers to cure concrete surfaces to receive penetrating liquid floor treatments.
 - c. Cure concrete surfaces to receive floor coverings with either a moisture-retaining cover or a curing compound that the manufacturer certifies does not interfere with bonding of floor covering used on Project.
3. Curing Compound: Apply uniformly in continuous operation by power spray or roller according to manufacturer's written instructions. Recoat areas subjected to heavy rainfall within three hours after initial application. Maintain continuity of coating and repair damage during curing period.
- a. Removal: After curing period has elapsed, remove curing compound without damaging concrete surfaces by method recommended by curing compound manufacturer unless manufacturer certifies curing compound does not interfere with bonding of floor covering used on Project.
4. Curing and Sealing Compound: Apply uniformly to floors and slabs indicated in a continuous operation by power spray or roller according to manufacturer's written instructions. Recoat areas subjected to heavy rainfall within three hours after initial application. Repeat process 24 hours later and apply a second coat. Maintain continuity of coating and repair damage during curing period.

3.13 LIQUID FLOOR TREATMENT APPLICATION

- A. Penetrating Liquid Floor Treatment: Prepare, apply, and finish penetrating liquid floor treatment according to manufacturer's written instructions.
 1. Remove curing compounds, sealers, oil, dirt, laitance, and other contaminants and complete surface repairs.
 2. Apply liquid until surface is saturated, scrubbing into surface until a gel forms; rewet; and repeat brooming or scrubbing. Rinse with water; remove excess material until surface is dry. Apply a second coat in a similar manner if surface is rough or porous.
- B. Sealing Coat: Uniformly apply a continuous sealing coat of curing and sealing compound to hardened concrete by power spray or roller according to manufacturer's written instructions.

3.14 JOINT FILLING

- A. Prepare, clean, and install joint filler according to manufacturer's written instructions.
 - 1. Defer joint filling until concrete has aged at least two month(s). Do not fill joints until construction traffic has permanently ceased.
- B. Remove dirt, debris, saw cuttings, curing compounds, and sealers from joints; leave contact faces of joints clean and dry.
- C. Install semirigid joint filler full depth in saw-cut joints and at least 2 inches deep in formed joints. Overfill joint and trim joint filler flush with top of joint after hardening.

3.15 CONCRETE SURFACE REPAIRS

- A. Defective Concrete: Repair and patch defective areas when approved by Architect. Remove and replace concrete that cannot be repaired and patched to Architect's approval.
- B. Patching Mortar: Mix dry-pack patching mortar, consisting of 1 part portland cement to 2-1/2 parts fine aggregate passing a No. 16 sieve, using only enough water for handling and placing.
- C. Repairing Formed Surfaces: Surface defects include color and texture irregularities, cracks, spalls, air bubbles, honeycombs, rock pockets, fins and other projections on the surface, and stains and other discolorations that cannot be removed by cleaning.
 - 1. Immediately after form removal, cut out honeycombs, rock pockets, and voids more than 1/2 inch in any dimension in solid concrete. Limit cut depth to 3/4 inch. Make edges of cuts perpendicular to concrete surface. Clean, dampen with water, and brush-coat holes and voids with bonding agent. Fill and compact with patching mortar before bonding agent has dried. Fill form face voids with patching mortar or cone plugs secured in place with bonding agent.
 - 2. Repair defects on surfaces exposed to view by blending white portland cement and standard portland cement so that, when dry, patching mortar matches surrounding color. Patch a test area at inconspicuous locations to verify mixture and color match before proceeding with patching. Compact mortar in place and strike off slightly higher than surrounding surface.
 - 3. Repair defects on concealed formed surfaces that affect concrete's durability and structural performance as determined by Architect.
- D. Repairing Unformed Surfaces: Test unformed surfaces, such as floors and slabs, for finish and verify surface tolerances specified for each surface. Correct low and high areas. Test surfaces sloped to drain for trueness of slope and smoothness; use a sloped template.
 - 1. Repair finished surfaces containing defects. Surface defects include spalls, popouts, honeycombs, rock pockets, crazing and cracks in excess of 0.01 inch wide or that penetrate to reinforcement or completely through unreinforced sections regardless of width, and other objectionable conditions.
 - 2. After concrete has cured at least 14 days, correct high areas by grinding.

3. Correct localized low areas during or immediately after completing surface finishing operations by cutting out low areas and replacing with patching mortar. Finish repaired areas to blend into adjacent concrete.
 4. Correct other low areas scheduled to receive floor coverings with a repair underlayment. Prepare, mix, and apply repair underlayment and primer according to manufacturer's written instructions to produce a smooth, uniform, plane, and level surface. Feather edges to match adjacent floor elevations.
 5. Correct other low areas scheduled to remain exposed with a repair topping. Cut out low areas to ensure a minimum repair topping depth of 1/4 inch to match adjacent floor elevations. Prepare, mix, and apply repair topping and primer according to manufacturer's written instructions to produce a smooth, uniform, plane, and level surface.
 6. Repair defective areas, except random cracks and single holes 1 inch or less in diameter, by cutting out and replacing with fresh concrete. Remove defective areas with clean, square cuts and expose steel reinforcement with at least a 3/4-inch clearance all around. Dampen concrete surfaces in contact with patching concrete and apply bonding agent. Mix patching concrete of same materials and mixture as original concrete, except without coarse aggregate. Place, compact, and finish to blend with adjacent finished concrete. Cure in same manner as adjacent concrete.
 7. Repair random cracks and single holes 1 inch or less in diameter with patching mortar. Groove top of cracks and cut out holes to sound concrete and clean off dust, dirt, and loose particles. Dampen cleaned concrete surfaces and apply bonding agent. Place patching mortar before bonding agent has dried. Compact patching mortar and finish to match adjacent concrete. Keep patched area continuously moist for at least 72 hours.
- E. Perform structural repairs of concrete, subject to Architect's approval, using epoxy adhesive and patching mortar.
- F. Repair materials and installation not specified above may be used, subject to Architect's approval.
- 3.16 FIELD QUALITY CONTROL
- A. Special Inspection: Owner will engage a special inspector and qualified testing and inspecting agency to perform field tests and inspections and prepare test reports.
- B. Testing Agency: Engage a qualified testing and inspecting agency to perform tests and inspections and to submit reports.
- C. Inspections:
1. Steel reinforcement placement.
 2. Steel reinforcement welding.
 3. Headed bolts and studs.
 4. Verification of use of required design mixture.
 5. Concrete placement, including conveying and depositing.
 6. Curing procedures and maintenance of curing temperature.
 7. Verification of concrete strength before removal of shores and forms from beams and slabs.

D. Concrete Tests: Testing of composite samples of fresh concrete obtained according to ASTM C 172 shall be performed according to the following requirements:

1. Testing Frequency: Obtain one composite sample for each day's pour of each concrete mixture exceeding 5 cu. yd., but less than 25 cu. yd., plus one set for each additional 50 cu. yd. or fraction thereof.
2. Testing Frequency: Obtain at least one composite sample for each 100 cu. yd. or fraction thereof of each concrete mixture placed each day.
 - a. When frequency of testing provides fewer than five compressive-strength tests for each concrete mixture, testing shall be conducted from at least five randomly selected batches or from each batch if fewer than five are used.
3. Slump: ASTM C 143; one test at point of placement for each composite sample, but not less than one test for each day's pour of each concrete mixture. Perform additional tests when concrete consistency appears to change.
4. Concrete Temperature: ASTM C 1064; one test hourly when air temperature is 40 deg F and below or 80 deg F and above, and one test for each composite sample.
5. Compression Test Specimens: ASTM C 31.
 - a. Cast and laboratory cure two sets of two standard cylinder specimens for each composite sample.
 - b. Cast and field cure two sets of two standard cylinder specimens for each composite sample.
6. Compressive-Strength Tests: ASTM C 39/C 39M; test one set of two laboratory-cured specimens at 7 days and one set of two specimens at 28 days.
 - a. Test one set of two field-cured specimens at 7 days and one set of two specimens at 28 days.
 - b. A compressive-strength test shall be the average compressive strength from a set of two specimens obtained from same composite sample and tested at age indicated.
7. When strength of field-cured cylinders is less than 85 percent of companion laboratory-cured cylinders, Contractor shall evaluate operations and provide corrective procedures for protecting and curing in-place concrete.
8. Strength of each concrete mixture will be satisfactory if every average of any three consecutive compressive-strength tests equals or exceeds specified compressive strength and no compressive-strength test value falls below specified compressive strength by more than 500 psi.
9. Test results shall be reported in writing to Architect, concrete manufacturer, and Contractor within 48 hours of testing. Reports of compressive-strength tests shall contain Project identification name and number, date of concrete placement, name of concrete testing and inspecting agency, location of concrete batch in Work, design compressive strength at 28 days, concrete mixture proportions and materials, compressive breaking strength, and type of break for both 7- and 28-day tests.
10. Nondestructive Testing: Impact hammer, sonoscope, or other nondestructive device may be permitted by Architect but will not be used as sole basis for approval or rejection of concrete.
11. Additional Tests: Testing and inspecting agency shall make additional tests of concrete when test results indicate that slump, air entrainment, compressive strengths, or other

requirements have not been met, as directed by Architect. Testing and inspecting agency may conduct tests to determine adequacy of concrete by cored cylinders complying with ASTM C 42 or by other methods as directed by Architect.

12. Additional testing and inspecting, at Contractor's expense, will be performed to determine compliance of replaced or additional work with specified requirements.
13. Correct deficiencies in the Work that test reports and inspections indicate do not comply with the Contract Documents.

- E. Measure floor and slab flatness and levelness according to ASTM E 1155 within 24 hours of finishing.

3.17 PROTECTION OF LIQUID FLOOR TREATMENTS

- A. Protect liquid floor treatment from damage and wear during the remainder of construction period. Use protective methods and materials, including temporary covering, recommended in writing by liquid floor treatments installer.

END OF SECTION

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 05 12 00

STRUCTURAL STEEL FRAMING

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

A. Section Includes:

- 1. Structural steel.
- 2. Grout.

B. Related Requirements:

- 1. Section 05 50 00 "Metal Fabrications" for steel lintels and shelf angles not attached to structural-steel frame, miscellaneous steel fabrications and other steel items not defined as structural steel.
- 2. Section 09 91 13 "Exterior Painting" and Section 09 91 23 "Interior Painting" and for surface-preparation and priming requirements.

1.3 DEFINITIONS

- A. Structural Steel: Elements of the structural frame indicated on Drawings and as described in AISC 303, "Code of Standard Practice for Steel Buildings and Bridges."

1.4 COORDINATION

- A. Coordinate selection of shop primers with topcoats to be applied over them. Comply with paint and coating manufacturers' written recommendations to ensure that shop primers and topcoats are compatible with one another.
- B. Coordinate installation of anchorage items to be embedded in or attached to other construction without delaying the Work. Provide setting diagrams, sheet metal templates, instructions, and directions for installation.

1.5 PREINSTALLATION MEETINGS

- A. Preinstallation Conference: Conduct conference at Project site.

1.6 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Shop Drawings: Show fabrication of structural-steel components.
 - 1. Include details of cuts, connections, splices, camber, holes, and other pertinent data.
 - 2. Include embedment Drawings.
 - 3. Indicate welds by standard AWS symbols, distinguishing between shop and field welds and show size, length, and type of each weld. Show backing bars that are to be removed and supplemental fillet welds where backing bars are to remain.
 - 4. Indicate type, size, and length of bolts, distinguishing between shop and field bolts. Identify pretensioned and slip-critical, high-strength bolted connections.
- C. Welding Procedure Specifications (WPSs) and Procedure Qualification Records (PQRs): Provide according to AWS D1.1/D1.1M, "Structural Welding Code - Steel," for each welded joint whether prequalified or qualified by testing, including the following:
 - 1. Power source (constant current or constant voltage)
 - 2. Electrode manufacturer and trade name, for demand critical welds.
- D. Delegated-Design Submittal: For structural-steel connections indicated to comply with design loads, include analysis data signed and sealed by the qualified professional engineer licensed in the State of Delaware, responsible for their preparation.

1.7 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For Installer fabricator and testing agency.
- B. Welding certificates.
- C. Paint Compatibility Certificates: From manufacturers of topcoats applied over shop primers, certifying that shop primers are compatible with topcoats.
- D. Mill test reports for structural steel, including chemical and physical properties.
- E. Product Test Reports: For the following:
 - 1. Bolts, nuts, and washers including mechanical properties and chemical analysis.
 - 2. Direct-tension indicators.
 - 3. Tension-control, high-strength, bolt-nut-washer assemblies.
 - 4. Shop primers.
 - 5. Nonshrink grout.
- F. Survey of existing conditions.
- G. Source quality-control reports.
- H. Field quality-control and special inspection reports.

1.8 QUALITY ASSURANCE

- A. Fabricator Qualifications: A qualified fabricator that participates in the AISC Quality Certification Program and is designated an AISC-Certified Plant, Category STD.
- B. Installer Qualifications: A qualified installer who participates in the AISC Quality Certification Program and is designated an AISC-Certified Erector, Category ACSE.
- C. Shop-Painting Applicators: Qualified according to AISC's Sophisticated Paint Endorsement P1 and Endorsement P2 or to SSPC-QP 3, "Standard Procedure for Evaluating Qualifications of Shop Painting Applicators."
- D. Welding Qualifications: Qualify procedures and personnel according to AWS D1.1/D1.1M, "Structural Welding Code - Steel."
 - 1. Welders and welding operators performing work on bottom flange, demand-critical welds shall pass the supplemental welder qualification testing, as required by AWS D1.8/D1.8M. FCAW-S and FCAW-G shall be considered separate processes for welding personnel qualification.
- E. Comply with applicable provisions of the following specifications and documents:
 - 1. AISC 303.
 - 2. AISC 341 and AISC 341s1.
 - 3. AISC 360.
 - 4. RCSC's "Specification for Structural Joints Using ASTM A 325 or A 490 Bolts."

1.9 DELIVERY, STORAGE, AND HANDLING

- A. Store materials to permit easy access for inspection and identification. Keep steel members off ground and spaced by using pallets, dunnage, or other supports and spacers. Protect steel members and packaged materials from corrosion and deterioration.
 - 1. Do not store materials on structure in a manner that might cause distortion, damage, or overload to members or supporting structures. Repair or replace damaged materials or structure as directed.
- B. Store fasteners in a protected place in sealed containers with manufacturer's labels intact.
 - 1. Fasteners may be repackaged provided Owner's testing and inspecting agency observes repackaging and seals containers.
 - 2. Clean and relubricate bolts and nuts that become dry or rusty before use.
 - 3. Comply with manufacturers' written recommendations for cleaning and lubricating ASTM F 1852 fasteners and for retesting fasteners after lubrication.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. Connections: Provide details of connections required by the Contract Documents to be selected or completed by structural-steel fabricator, including comprehensive engineering analysis by a qualified professional engineer, to withstand loads indicated and comply with other information and restrictions indicated.
1. Select and complete connections using schematic details indicated and AISC 360.
 2. Use Allowable Stress Design; data are given at service-load level.
- B. Moment Connections: Type PR, partially restrained.
- C. Construction: Combined system of moment frame and braced frame.

2.2 STRUCTURAL-STEEL MATERIALS

- A. W-Shapes: ASTM A 992/A 992M.
- B. Channels, Angles: ASTM A 572/A 572M, Grade 50.
- C. Plate and Bar: ASTM A 36/A 36M.
- D. Cold-Formed Hollow Structural Sections: ASTM A 500/A 500M, Grade C, structural tubing.
- E. Welding Electrodes: Comply with AWS requirements.

2.3 BOLTS, CONNECTORS AND ANCHORS

- A. High-Strength Bolts, Nuts, and Washers: ASTM A 325, Type 1, heavy-hex steel structural bolts; ASTM A 563, Grade C, heavy-hex carbon-steel nuts; and ASTM F 436, Type 1, hardened carbon-steel washers; all with plain finish.
1. Direct-Tension Indicators: ASTM F 959, Type 325, compressible-washer type with plain finish.
- B. High-Strength Bolts, Nuts, and Washers: ASTM A 490, Type 1, heavy-hex steel structural bolts; ASTM A 563, Grade DH, heavy-hex carbon-steel nuts; and ASTM F 436, Type 1, hardened carbon-steel washers with plain finish.
1. Direct-Tension Indicators: ASTM F 959, Type 490, compressible-washer type with plain finish.
- C. Tension-Control, High-Strength Bolt-Nut-Washer Assemblies: ASTM F 1852, Type 1, heavy-hex head assemblies consisting of steel structural bolts with splined ends, heavy-hex carbon-steel nuts, and hardened carbon-steel washers.
1. Finish: Plain.

D. Unheaded Anchor Rods: ASTM F 1554, Grade 55, weldable.

1. Configuration: Straight.
2. Nuts: ASTM A 563 heavy-hex carbon steel.
3. Plate Washers: ASTM A 36/A 36M carbon steel.
4. Washers: ASTM F 436, Type 1, hardened carbon steel.
5. Finish: Plain.

E. Headed Anchor Rods: ASTM F 1554, Grade 55, weldable, straight.

1. Nuts: ASTM A 563 heavy-hex carbon steel.
2. Plate Washers: ASTM A 36/A 36M carbon steel.
3. Washers: ASTM F 436, Type 1, hardened carbon steel.
4. Finish: Plain.

F. Threaded Rods: ASTM A 36/A 36M.

1. Nuts: ASTM A 563 heavy-hex carbon steel.
2. Washers: ASTM F 436, Type 1, hardened carbon steel.
3. Finish: Plain.

G. Clevises and Turnbuckles: Made from cold finished carbon steel bars, ASTM A 108, Grade 1035.

2.4 PRIMER

A. Primer: SSPC-Paint 25, Type I, zinc oxide, alkyd, linseed oil primer and compatible with topcoat.

2.5 GROUT

A. Nonmetallic, Shrinkage Resistant Grout: ASTM C 1107/C 1107M, factory-packaged, nonmetallic aggregate grout, noncorrosive and nonstaining, mixed with water to consistency suitable for application and a 30-minute working time.

2.6 FABRICATION

A. Structural Steel: Fabricate and assemble in shop to greatest extent possible. Fabricate according to AISC 303, "Code of Standard Practice for Steel Buildings and Bridges," and to AISC 360.

1. Camber structural-steel members where indicated.
2. Fabricate beams with rolling camber up.
3. Identify high-strength structural steel according to ASTM A 6/A 6M and maintain markings until structural steel has been erected.
4. Mark and match-mark materials for field assembly.
5. Complete structural-steel assemblies, including welding of units, before starting shop-priming operations.

B. Thermal Cutting: Perform thermal cutting by machine to greatest extent possible.

1. Plane thermally cut edges to be welded to comply with requirements in AWS D1.1/D1.1M.
- C. Bolt Holes: Cut, drill or punch standard bolt holes perpendicular to metal surfaces.
- D. Finishing: Accurately finish ends of columns and other members transmitting bearing loads.
- E. Cleaning: Clean and prepare steel surfaces that are to remain unpainted according to SSPC-SP 3, "Power Tool Cleaning."
- F. Steel Wall-Opening Framing: Select true and straight members for fabricating steel wall-opening framing to be attached to structural-steel frame. Straighten as required to provide uniform, square, and true members in completed wall framing. Build up welded framing, weld exposed joints continuously, and grind smooth.
- G. Welded Door Frames: Build up welded door frames attached to structural-steel frame. Weld exposed joints continuously and grind smooth. Plug-weld fixed steel bar stops to frames. Secure removable stops to frames with countersunk machine screws, uniformly spaced not more than 10 inches o.c. unless otherwise indicated.
- H. Holes: Provide holes required for securing other work to structural steel and for other work to pass through steel members.
 1. Cut, drill, or punch holes perpendicular to steel surfaces. Do not thermally cut bolt holes or enlarge holes by burning.
 2. Baseplate Holes: Cut, drill, mechanically thermal cut, or punch holes perpendicular to steel surfaces.
 3. Weld threaded nuts to framing and other specialty items indicated to receive other work.

2.7 SHOP CONNECTIONS

- A. High-Strength Bolts: Shop install high-strength bolts according to RCSC's "Specification for Structural Joints Using ASTM A 325 or A 490 Bolts" for type of bolt and type of joint specified.
 1. Joint Type: Snug tightened or Pretensioned.
- B. Weld Connections: Comply with AWS D1.1/D1.1M for tolerances, appearances, welding procedure specifications, weld quality, and methods used in correcting welding work.

2.8 SHOP PRIMING

- A. Shop prime steel surfaces except the following:
 1. Surfaces embedded in concrete or mortar. Extend priming of partially embedded members to a depth of 2 inches.
 2. Surfaces to be field welded.
 3. Surfaces of high-strength bolted, slip-critical connections.

- B. Surface Preparation: Clean surfaces to be painted. Remove loose rust and mill scale and spatter, slag, or flux deposits. Prepare surfaces according to the following specifications and standards:
 - 1. SSPC-SP 3, "Power Tool Cleaning."
- C. Priming: Immediately after surface preparation, apply primer according to manufacturer's written instructions and at rate recommended by SSPC to provide a minimum dry film thickness of 1.5 mils. Use priming methods that result in full coverage of joints, corners, edges, and exposed surfaces.
 - 1. Stripe paint corners, crevices, bolts, welds, and sharp edges.
 - 2. Apply two coats of shop paint to surfaces that are inaccessible after assembly or erection. Change color of second coat to distinguish it from first.
- D. Painting: Prepare steel and apply a one-coat, nonasphaltic primer complying with SSPC-PS Guide 7.00, "Painting System Guide 7.00: Guide for Selecting One-Coat Shop Painting Systems," to provide a dry film thickness of not less than 1.5 mils.

2.9 SOURCE QUALITY CONTROL

- A. Testing Agency: Owner will engage a qualified testing agency to perform shop tests and inspections.
 - 1. Provide testing agency with access to places where structural-steel work is being fabricated or produced to perform tests and inspections.
- B. Bolted Connections: Inspect and test shop-bolted connections according to RCSC's "Specification for Structural Joints Using ASTM A 325 or A 490 Bolts."
- C. Welded Connections: Visually inspect shop-welded connections according to AWS D1.1/D1.1M and the following inspection procedures, at testing agency's option:
 - 1. Liquid Penetrant Inspection: ASTM E 165.
 - 2. Magnetic Particle Inspection: ASTM E 709; performed on root pass and on finished weld. Cracks or zones of incomplete fusion or penetration are not accepted.
 - 3. Ultrasonic Inspection: ASTM E 164.
 - 4. Radiographic Inspection: ASTM E 94.
- D. Prepare test and inspection reports.

PART 7 - EXECUTION

7.1 EXAMINATION

- A. Verify, with certified steel erector present, elevations of concrete- and masonry-bearing surfaces and locations of anchor rods, bearing plates, and other embedments for compliance with requirements.

1. Prepare a certified survey of existing conditions. Include bearing surfaces, anchor rods, bearing plates, and other embedments showing dimensions, locations, angles, and elevations.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Provide temporary shores, guys, braces, and other supports during erection to keep structural steel secure, plumb, and in alignment against temporary construction loads and loads equal in intensity to design loads. Remove temporary supports when permanent structural steel, connections, and bracing are in place unless otherwise indicated.

3.3 ERECTION

- A. Set structural steel accurately in locations and to elevations indicated and according to AISC 303 and AISC 360.
- B. Baseplates and Leveling Plates: Clean concrete- and masonry-bearing surfaces of bond-reducing materials, and roughen surfaces prior to setting plates. Clean bottom surface of plates.
 1. Set plates for structural members on wedges, shims, or setting nuts as required.
 2. Weld plate washers to top of baseplates.
 3. Snug-tighten anchor rods after supported members have been positioned and plumbed. Do not remove wedges or shims but, if protruding, cut off flush with edge of plate before packing with grout.
 4. Promptly pack grout soundly between bearing surfaces and plates so no voids remain. Neatly finish exposed surfaces; protect grout and allow to cure. Comply with manufacturer's written installation instructions for shrinkage-resistant grouts.
- C. Maintain erection tolerances of structural steel within AISC 303, "Code of Standard Practice for Steel Buildings and Bridges."
- D. Align and adjust various members that form part of complete frame or structure before permanently fastening. Before assembly, clean bearing surfaces and other surfaces that are in permanent contact with members. Perform necessary adjustments to compensate for discrepancies in elevations and alignment.
 1. Level and plumb individual members of structure.
 2. Make allowances for difference between temperature at time of erection and mean temperature when structure is completed and in service.
- E. Splice members only where indicated.
- F. Do not use thermal cutting during erection.
- G. Do not enlarge unfair holes in members by burning or using drift pins. Ream holes that must be enlarged to admit bolts.

3.4 FIELD CONNECTIONS

- A. High-Strength Bolts: Install high-strength bolts according to RCSC's "Specification for Structural Joints Using ASTM A 325 or A 490 Bolts" for type of bolt and type of joint specified.
 - 1. Joint Type: Snug tightened or Pretensioned.
- B. Weld Connections: Comply with AWS D1.1/D1.1M for tolerances, appearances, welding procedure specifications, weld quality, and methods used in correcting welding work.
 - 1. Comply with AISC 303 and AISC 360 for bearing, alignment, adequacy of temporary connections, and removal of paint on surfaces adjacent to field welds.
 - 2. Remove backing bars or runoff tabs, back gouge, and grind steel smooth.

3.5 FIELD QUALITY CONTROL

- A. Special Inspections: Owner will engage a qualified special inspector to perform the following special inspections:
 - 1. Verify structural-steel materials and inspect steel frame joint details.
 - 2. Verify weld materials and inspect welds.
 - 3. Verify connection materials and inspect high-strength bolted connections.
- B. Testing Agency: Owner will engage a qualified testing agency to perform tests and inspections.
- C. Bolted Connections: Inspect and test bolted connections according to RCSC's "Specification for Structural Joints Using ASTM A 325 or A 490 Bolts."
- D. Welded Connections: Visually inspect field welds according to AWS D1.1/D1.1M.
 - 1. In addition to visual inspection, test and inspect field welds according to AWS D1.1/D1.1M and the following inspection procedures, at testing agency's option:
 - a. Liquid Penetrant Inspection: ASTM E 165.
 - b. Magnetic Particle Inspection: ASTM E 709; performed on root pass and on finished weld. Cracks or zones of incomplete fusion or penetration are not accepted.
 - c. Ultrasonic Inspection: ASTM E 164.
 - d. Radiographic Inspection: ASTM E 94.

3.6 REPAIRS AND PROTECTION

- A. Touchup Painting: Immediately after erection, clean exposed areas where primer is damaged or missing and paint with the same material as used for shop painting to comply with SSPC-PA 1 for touching up shop-painted surfaces.
 - 1. Clean and prepare surfaces by SSPC-SP 2 hand-tool cleaning or SSPC-SP 3 power-tool cleaning.

- B. Touchup Painting: Cleaning and touchup painting are specified in Section 09 91 13 "Exterior Painting" and Section 09 91 23 "Interior Painting."
- C. Touchup Priming: Cleaning and touchup priming are specified in Section 09 96 00 "High-Performance Coatings."

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 06 10 53

MISCELLANEOUS ROUGH CARPENTRY

PART 1 - GENERAL

1.1 SUMMARY

A. Section Includes:

1. Wood blocking, cants, and nailers.
2. Plywood backing panels.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of process and factory-fabricated product.

1.3 INFORMATIONAL SUBMITTALS

- A. Evaluation Reports: For the following, from ICC-ES.

1. Preservative-treated wood.
2. Fire-retardant-treated wood.
3. Power-driven fasteners.

PART 2 - PRODUCTS

2.1 WOOD PRODUCTS, GENERAL

- A. Lumber: DOC PS 20 and applicable rules of grading agencies indicated. If no grading agency is indicated, provide lumber that complies with the applicable rules of any rules-writing agency certified by the ALSC Board of Review. Provide lumber graded by an agency certified by the ALSC Board of Review to inspect and grade lumber under the rules indicated.

1. Factory mark each piece of lumber with grade stamp of grading agency.
2. Dress lumber, S4S, unless otherwise indicated.

- B. Maximum Moisture Content of Lumber: 15 percent unless otherwise indicated.

2.2 WOOD-PRESERVATIVE-TREATED MATERIALS

- A. Preservative Treatment by Pressure Process: AWPA U1; Use Category UC2 for interior construction not in contact with ground, Use Category UC3b for exterior construction not in contact with ground, and Use Category UC4a for items in contact with ground.

1. Preservative Chemicals: Acceptable to authorities having jurisdiction and containing no arsenic or chromium.
- B. Kiln-dry lumber after treatment to a maximum moisture content of 19 percent. Do not use material that is warped or does not comply with requirements for untreated material.
- C. Mark lumber with treatment quality mark of an inspection agency approved by the ALSC Board of Review.
- D. Application: Treat all miscellaneous carpentry unless otherwise indicated.

2.3 FIRE-RETARDANT-TREATED MATERIALS

- A. Fire-Retardant-Treated Lumber and Plywood by Pressure Process: Product with a flame-spread index of 25 or less when tested according to ASTM E 84, and with no evidence of significant progressive combustion when the test is extended an additional 20 minutes, and with the flame front not extending more than 10.5 feet beyond the centerline of the burners at any time during the test.
 1. Exterior Type: Treated materials shall comply with requirements specified above for fire-retardant-treated lumber and plywood by pressure process after being subjected to accelerated weathering according to ASTM D 2898. Use for exterior locations and where indicated.
 2. Interior Type A: Treated materials shall have a moisture content of 28 percent or less when tested according to ASTM D 3201 at 92 percent relative humidity. Use where exterior type is not indicated.
 3. Design Value Adjustment Factors: Treated lumber shall be tested according to ASTM D 5664, and design value adjustment factors shall be calculated according to ASTM D 6841. For enclosed roof framing, framing in attic spaces, and where high-temperature fire-retardant treatment is indicated, provide material with adjustment factors of not less than 0.25 modulus of elasticity and 0.75 for extreme fiber in bending for Project's climatic regional zone.
- B. Kiln-dry lumber after treatment to a maximum moisture content of 19 percent. Kiln-dry plywood after treatment to a maximum moisture content of 15 percent.
- C. Identify fire-retardant-treated wood with appropriate classification marking of qualified testing agency.
- D. Application: Treat all miscellaneous carpentry unless otherwise indicated.
 1. Framing for raised platforms.
 2. Concealed blocking.
 3. Roof framing and blocking.
 4. Wood cants, nailers, curbs, equipment support bases, blocking, and similar members in connection with roofing.
 5. Plywood backing panels.

2.4 DIMENSION LUMBER FRAMING

- A. Non-Load-Bearing Interior Partitions: Construction or No. 2 grade of any species.
- B. Other Framing: No. 2 grade of any of the following species:
 - 1. Hem-fir (north); NLGA.
 - 2. Southern pine; SPIB.
 - 3. Douglas fir-larch; WCLIB or WWPA.
 - 4. Southern pine or mixed southern pine; SPIB.
 - 5. Spruce-pine-fir; NLGA.
 - 6. Douglas fir-south; WWPA.
 - 7. Hem-fir; WCLIB or WWPA.
 - 8. Douglas fir-larch (north); NLGA.
 - 9. Spruce-pine-fir (south); NeLMA, WCLIB, or WWPA.

2.5 MISCELLANEOUS LUMBER

- A. General: Provide miscellaneous lumber indicated and lumber for support or attachment of other construction, including the following:
 - 1. Blocking.
 - 2. Nailers.
 - 3. Rooftop equipment bases and support curbs.
 - 4. Cants.
 - 5. Furring.
 - 6. Grounds.
 - 7. Utility shelving.
- B. Dimension Lumber Items: Construction or No. 2 grade lumber of any species.
- C. Concealed Boards: 15 percent maximum moisture content of any of the following species and grades:
 - 1. Mixed southern pine or southern pine, No. 2 grade; SPIB.
 - 2. Eastern softwoods, No. 2 Common grade; NELMA.
 - 3. Northern species, No. 2 Common grade; NLGA.
 - 4. Western woods, Construction or No. 2 Common grade; WCLIB or WWPA.

2.6 PLYWOOD BACKING PANELS

- A. Equipment Backing Panels: Plywood, DOC PS 1, Exterior, A-C, fire-retardant treated, in thickness indicated or, if not indicated, not less than 3/4-inch nominal thickness.

2.7 FASTENERS

- A. General: Provide fasteners of size and type indicated that comply with requirements specified in this article for material and manufacture.

1. Where carpentry is exposed to weather, in ground contact, pressure-preservative treated, or in area of high relative humidity, provide fasteners with hot-dip zinc coating complying with ASTM A 153/A 153M.
- B. Screws for Fastening to Metal Framing: ASTM C 1002, length as recommended by screw manufacturer for material being fastened.
- C. Power-Driven Fasteners: Fastener systems with an evaluation report acceptable to authorities having jurisdiction, based on ICC-ES AC70.

PART 3 - EXECUTION

3.1 INSTALLATION, GENERAL

- A. Framing Standard: Comply with AF&PA's WCD 1, "Details for Conventional Wood Frame Construction," unless otherwise indicated.
- B. Set carpentry to required levels and lines, with members plumb, true to line, cut, and fitted. Fit carpentry accurately to other construction. Locate nails, blocking, and similar supports to comply with requirements for attaching other construction.
- C. Install plywood backing panels by fastening to studs; coordinate locations with utilities requiring backing panels.
- D. Do not splice structural members between supports unless otherwise indicated.
- E. Comply with AWPAC M4 for applying field treatment to cut surfaces of preservative-treated lumber.
- F. Securely attach carpentry work to substrate by anchoring and fastening as indicated, complying with the following:
 1. Table 2304.4.1, "Fastening Schedule," in ICC's International Building Code.
 2. Table R602.3(1), "Fastener Schedule for Structural Members," and Table R602.3(2), "Alternate Attachments," in ICC's International Residential Code for One- and Two-Family Dwellings.
 3. ICC-ES evaluation report for fastener.

3.2 PROTECTION

- A. Protect wood that has been treated with inorganic boron (SBX) from weather. If, despite protection, inorganic boron-treated wood becomes wet, apply EPA-registered borate treatment. Apply borate solution by spraying to comply with EPA-registered label.

END OF SECTION

SECTION 07 84 13

FIRE PROTECTION, HVAC & PLUMBING PENETRATION FIRESTOPPING

PART 1 GENERAL

1.1 SUMMARY

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- B. Section includes:
 - 1. Through-penetration firestopping in fire rated construction.
 - 2. Through-penetration smoke-stopping in smoke partitions.
- C. Related items:
 - 1. Fire dampers and manufactured devices. Refer to Division 23 Section *HVAC Air Distribution*.
 - 2. Smoke dampers and combination fire/smoke dampers. Refer to Division 23 Section *HVAC Air Distribution*.

1.2 REFERENCES

- A. Underwriters Laboratories
 - 1. UL Fire Resistance Directory
 - a. Through-penetration firestop devices (XHCR)
 - b. Fire resistance rating (BXUV)
 - c. Through-penetration firestop systems (XHEZ)
 - d. Fill, void, or cavity material (XHHW)
- B. American Society for Testing and Materials Standards:
 - 1. ASTM E 814-88: Standard Test Method for Fire Tests of Through-Penetration Firestops.

DEFINITIONS

- A. Assembly: Particular arrangement of materials specific to given type of construction described or detailed in referenced documents.
- B. Barriers: Time-rated fire walls, smoke barrier walls, time-rated ceiling/floor assemblies and structural floors.

- C. Firestopping: Methods and materials applied in penetrations and unprotected openings to limit spread of heat, fire, gasses and smoke.
- D. Penetration: Opening or foreign material passing through or into barrier or structural floor such that full thickness of rated materials is not obtained.
- E. System: Specific products and applications, classified and numbered by Underwriters Laboratories, Inc. to close specific barrier penetrations.
- F. Sleeve: Metal fabrication or pipe section extended through thickness of barrier and used to permanently guard penetration. Sleeves are described as part of penetrating system in other sections and may or may not be required.

1.4 SYSTEM DESCRIPTION

- A. Design Requirements
 - 1. Fire-rated construction: Maintain barrier and structural floor fire resistance ratings including resistance to cold smoke at all penetrations.
 - 2. Smoke barrier construction: Maintain barrier and structural floor resistance to cold smoke at all penetrations.

1.5 SUBMITTALS

- A. Submit in accordance with Division 01 Section *Submittal Procedures*, unless otherwise indicated.
- B. Product data: Manufacturer's specifications and technical data including the following:
 - 1. Detailed specification of construction and fabrication.
 - 2. Manufacturer's installation instructions.
- C. Shop drawings: Indicate dimensions, description of materials and finishes, general construction, specific modifications, component connections, anchorage methods, hardware, and installation procedures, plus the following specific requirements.
 - 1. Details of each proposed assembly identifying intended products and applicable UL system number, or UL classified devices.
 - 2. Manufacturer or manufacturer's representative shall provide qualified engineering judgment and drawings relating to non-standard applications as needed.
- D. Quality control submittals:
 - 1. Statement of qualifications.
- E. Applicators' qualifications statement:

1. List past projects indicating required experience.

1.6 QUALITY ASSURANCE

- A. Installer's qualifications: Fire experienced in installation or application of systems similar in complexity to those required for this project, plus the following:
 1. Acceptable to or licensed by manufacturer, State or local authority where applicable.
 2. At least 2 years experience with systems.
 3. Successfully completed at least 5 comparable scale projects using this system.
- B. Local and State regulatory requirements: Submit forms for acceptance for proposed assemblies not conforming to specific UL Firestop System numbers, or UL classified devices.
- C. Materials shall have been tested to provide fire rating at least equal to that of the construction.

1.7 DELIVERY, STORAGE, AND HANDLING

- A. Packing and shipping:
 1. Deliver products in original unopened packaging with legible manufacturer's identification.
 2. Coordinate delivery with scheduled installation date, allow minimum storage at site.
- B. Storage and protection: Store materials in a clean, dry, ventilated location. Protect from soiling, abuse, moisture and freezing when required. Follow manufacturer's instructions.

1.8 PROJECT CONDITIONS

- A. Existing condition:
 1. Verify existing conditions and substrates before starting work. Correct unsatisfactory conditions before proceeding.
 2. Proceed with installation only after penetrations of the substrate and supporting brackets have been installed.
- B. Environmental requirements:
 1. Furnish adequate ventilation if using solvent.
 2. Furnish forced air ventilation during installation if required by manufacturer.

3. Keep flammable materials away from sparks or flame.
4. Provide masking and drop cloths to prevent contamination of adjacent surfaces by firestopping materials.

1.9 WARRANTY

- A. Submit copies of written warranty agreeing to repair or replace joint sealers which fail in joint adhesion, extrusion resistance, migration resistance, or general durability or appear to deteriorate in any other manner not clearly specified by submitted manufacturer's data as an inherent quality of the material for the exposure indicated. The warranty period shall be two (2) years from date of substantial completion unless otherwise noted.

PART 2 PRODUCTS

2.1 THROUGH-PENETRATION FIRESTOPPING OF FIRE-RATED CONSTRUCTION

- A. Systems of devices listed in the UL Fire Resistance Directory under categories XHCR and XHEZ may be used, providing that it conforms to the construction type, penetrant type, annular space requirements and fire rating involved in each separate instance, and that the system be symmetrical for wall applications. Systems or devices must be asbestos-free.
 1. Additional requirements: Withstand the passage of cold smoke either as an inherent property of the system, or by the use of a separate product included as a part of the UL system or device and designed to perform this function.
 2. Acceptable manufacturers and products.
 - a. Those listed in the UL Fire Resistance directory for the UL System involved and as further defined in the System and Applications Schedule in Part 3.6 of this section.
 3. All firestopping products must be from a single manufacturer. All trades shall use products from the same manufacturer unless otherwise noted.

2.2 SMOKE-STOPPING AT SMOKE PARTITIONS

- A. Through-penetration smoke-stopping: Any system complying with the requirements for through-penetration firestopping in fire-rated construction, as specified in The Systems and Applications Schedule in Part 3.6 of this section, is acceptable, provided that the system includes the specified smoke seal or will provide a smoke seal. The length of time of the fire resistance may be disregarded.

ACCESSORIES

- A. Fill, void or cavity materials: As classified under category XHHW in the UL Fire Resistance Directory.
- B. Forming materials: As classified under category XHKU in the UL Fire Resistance Directory.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Verification of conditions: Examine areas and conditions under which work is to be performed and identify conditions detrimental to proper or timely completion.
 - 1. Verify barrier penetrations are properly sized and in suitable condition for application of materials.
 - 2. Do not proceed until unsatisfactory conditions have been corrected.
- B. Coordinate an inspection of all Mechanical Firestopping systems with the Fire Marshal prior to installation of ceilings, walls, etc.

3.2 PREPARATION

- A. Clean surfaces to be in contact with penetration seal materials of dirt, grease, oil, loose materials, rust, or other substances that may affect proper fitting, adhesion, or the required fire resistance.

3.3 INSTALLATION

- A. Install penetration seal materials in accordance with printed instructions of the UL Fire Resistance Directory and in accordance with manufacturer's instruction.
- B. Seal holes or voids made by penetrations to ensure an effective smoke barrier.
- C. Protect materials from damage on surfaces subject to traffic.
- D. When large openings are created in walls or floors to permit installation of pipes, ducts, or other items, close unused portions of opening with firestopping materials tested for the application. See UL Fire Resistance Directory or Section 3.6 of this document.
- E. Install smoke stopping as specified for firestopping.

3.4 FIELD QUALITY CONTROL

- A. Examine penetration sealed areas to ensure proper installation before concealing or enclosing areas.
- B. Keep areas of work accessible until inspection by applicable code authorities.
- C. Perform under this section patching and repairing of firestopping caused by cutting or penetration by other trades.

3.5 ADJUSTING AND CLEANING

- A. Clean up spills of liquid components.

- B. Neatly cut and trim materials as required.
- C. Remove equipment, materials and debris, leaving area in undamaged, clean condition.

3.6 SYSTEMS AND APPLICATION SCHEDULES*

PENETRATING ITEM	CONCRETE	GYPSUM	WOOD FLOOR/CEILING
Metal Pipe	CAJ1001 CP25S/L, CP25N/S	WL1001 CP 25	FC1002 CP 25
	CAJ1006 CS-195+, FS-195+	WL1002 FS-195+	FC1003 2000,2000+,20003
	CAJ1007 FS-195+, 1-inch& 2-inch Wide	WL1003 CP 25WB+,CP 25N/S	FC1006 CP 25WB+
	CAJ1009 2000, 2000+, 2003	WL1008 2000+	
	CAJ1010 2000, 2000+, 2003	WL1009 2000+	
	CAJ1012 2000, 2000+, 2003	WL1010 2000+	
	CAJ1013 2000, 2000+, 2003	WL1016 CP 25WB+	
	CAJ1014 2000, 2000+, 2003	WL1017 CP 25WB+,CP 25N/S	
	CAJ1015 2000, 2000+, 2003	WL1032 CP 25WB+,CP 25N/S	
	CAJ1017 FD 150	WL1036 FD 150	
	CAJ1021 FD 150	WL1037 CS-195+,FS-195+	
	CAJ1027 MPS-2+	WL1067 CP 25N/S	
	CAJ1044 CP 25WB+	WL1073 CP 25WB+	
	CAJ1052 CP 25S/L, CP 25N/S	WL1080 MPS2+	
	CAJ1058 2000, 2000+, 2003	WL1082 2000+	
	CAJ1060 2000, 2000+, 2003		
	CAJ1063 2000, 2000+, 2003		
	CAJ1066 CP 25N/S,CP 25S/L, CP 25WB+		
	CAJ1091 CP 25N/S,CP 25S/L, CP 25WB+		
	CAJ1092 CP 25WB+		
	CAJ1112 FS-195+		
	CAJ1160 CP 25S/L, CP 25N/S		
	CAJ1175 CP 25WB+		
	CAJ1176 CP 25WB+		
	CAJ1188 2000+		
	CBJ1020 CS-195+, FS-195+		
	CBJ1021 CS-195+, MPS-2+		
	CBJ1031 2001		
	CBJ1032 2001		
	FA1002 CP 25WB+		
	WJ1010 CP 25WB+		
	WJ1023 2001		

NOT FOR BIDDING PURPOSES

HVAC IMPROVEMENTS
STOKES ELEMENTARY SCHOOL

200-163183-17001-07

PENETRATING ITEM	CONCRETE	GYPSUM	WOOD FLOOR/CEILING
Non-Metallic	CAJ2001 FS-195+, 1-inch& 2-inch WIDE, PPD'S CAJ2002 FS-195+ CAJ2003 CS-195+, FS-195+ CAJ2005 FS-195 CAJ2006 FS-195+ CAJ2013 FS-195+ CAJ2019 2000, 2000+, 2003 CAJ2027 FS-195+, CP 25N/S, CP 25S/L, CP 25WB+ CAJ2028 FS-195, MPS-2+ CAJ2029 FS-195+, PPD'S CAJ2030 CS-195+, FS-195+ CAJ2040 FS-195+, CP 25WB+ CAJ2044 FS-195+, CP 25N/S, CP 25S/L CP 25 WB+ CAJ2090 FS-195+ CAJ2177 FS-195+, PPD'S FA2001 FS-195+, PPD'S FS2002 CS-195+, FS-195+, MPS-2+, PPD'S FA2011 FS-195+ WJ2012 FS-195+ 1-inch WIDE	WL2002 FS-195+, PPD'S WL2003 FS-195+ WL2004 FS-195+ WL2005 FS-195+ 4' WIDE WL2006 FS-195+ WL2013 FS-195+ WL2031 CS-195+, FS-195+ WL2032 CS-195+, FS-195+ WL2033 FS-195+ WL2073 FS-195+ 1-inch WIDE	FC2002 FS-195+, PPD'S FC2007 FS-195+, PPD'S FC2008 FS-195+ FC2009 FS-195+, PPD'S FC2024 FS-195 FC2026 FS-195+ FC2028 FS-195, 1' & 2-inch WIDE, PPD'S
Insulated Metallic Pipe	CAJ5001 CP 25N/S, CP 25S/L, CP 25WB+ CAJ5002 FS-195+ CAJ5003 FS-195+ CAJ5005 MPS-2+ CAJ5009 2000+, 2003 CAJ5017 FS-195+, CP 25 CAJ5022 FS-195+ CAJ5024 FS-195+ CAJ5030 CS-195+, FS-195+ CAJ5041 2000, 2000+, 2003 CAJ5060 CP 25WB+ CAJ5074 2000+ CBJ5002 CP 25 CBJ5003 FS-195+ FA5001 FS-195+ CP 25WB+	WL5001 FS-195+ WL5002 FS-195+ WL5009 FS-195+ WL5010 FS-195+ WL5011 CP 25WB+ WL5032 2000+ WL5038 CP 25WB+ WL5039 CP 25WB+ WL5040 CP 25WB+ WL5045 CP 25WB+ WL5053 2000+	FC5002 FS-195+ FC5008 FS-195+
Miscellaneous Mechanical HVAC Ducts	CAJ7001 CP 25N/S CP 25S/L CAJ7003 CP 25WB+ CAJ7009 DUCT WRAP, BULK PUTTY		FC7001 CP 25S/L, CP 25N/S
Mixed Penetrating Items Combos	CAJ8001 CS-195+ FS-195 CAJ8003 2000, 2000+, 20003 CAJ8004 2000, 2000+, 20003 CAJ8006 2001 CAJ8013 FS-195+, CP 25 CBJ8004 CS-195, FS-195+ CBJ8005 CS-195+, MPS-2+ CBJ8008 2001 FA8001 FS-195+, CP 25WB+	WL8002 CS-195+, FS-195+	

* Underwriter's Laboratories, Inc., Fire Resistance Directory.

END OF SECTION

SECTION 07 92 00

JOINT SEALANTS

PART 1 - GENERAL

1.1 SUMMARY

A. Section Includes:

1. Silicone joint sealants.
2. Mildew-resistant joint sealants.
3. Latex joint sealants.

1.2 ACTION SUBMITTALS

- A. Product Data: For each joint-sealant product.
- B. Samples: For each kind and color of joint sealant required.

1.3 INFORMATIONAL SUBMITTALS

- A. Product test reports.
- B. Preconstruction laboratory test reports.
- C. Sample warranties.

1.4 WARRANTY

- A. Special Installer's Warranty: Installer agrees to repair or replace joint sealants that do not comply with performance and other requirements specified in this Section within specified warranty period.
 1. Warranty Period: Two years from date of Substantial Completion.
- B. Special Manufacturer's Warranty: Manufacturer agrees to furnish joint sealants to repair or replace those joint sealants that do not comply with performance and other requirements specified in this Section within specified warranty period.
 1. Warranty Period: Five years from date of Substantial Completion.

PART 2 - PRODUCTS

2.1 JOINT SEALANTS, GENERAL

- A. Colors of Exposed Joint Sealants: As selected by Architect from manufacturer's full range.

2.2 SILICONE JOINT SEALANTS

- A. Silicone, S, NS, 50, NT: Single-component, nonsag, plus 50 percent and minus 50 percent movement capability, nontraffic-use, neutral-curing silicone joint sealant; ASTM C 920, Type S, Grade NS, Class 50, Use NT.

1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
- a. GE Construction Sealants; Momentive Performance Materials Inc.
 - b. May National Associates, Inc.; a subsidiary of Sika Corporation.
 - c. Pecora Corporation.

2.3 MILDEW-RESISTANT JOINT SEALANTS

- A. Mildew-Resistant Joint Sealants: Formulated for prolonged exposure to humidity with fungicide to prevent mold and mildew growth.

- B. Silicone, Mildew Resistant, Acid Curing, S, NS, 25, NT: Mildew-resistant, single-component, nonsag, plus 25 percent and minus 25 percent movement capability, nontraffic-use, acid-curing silicone joint sealant; ASTM C 920, Type S, Grade NS, Class 25, Use NT.

1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
- a. GE Construction Sealants; Momentive Performance Materials Inc.
 - b. Pecora Corporation.
 - c. Tremco Incorporated.

- C. Acrylic Latex: Acrylic latex or siliconized acrylic latex, ASTM C 834, Type OP, Grade NF.

1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
- a. May National Associates, Inc.; a subsidiary of Sika Corporation.
 - b. Pecora Corporation.
 - c. Sherwin-Williams Company (The).

2.4 JOINT-SEALANT BACKING

- A. Cylindrical Sealant Backings: ASTM C 1330, Type C (closed-cell material with a surface skin), and of size and density to control sealant depth and otherwise contribute to producing optimum sealant performance.
- B. Bond-Breaker Tape: Polyethylene tape or other plastic tape recommended by sealant manufacturer.

2.5 MISCELLANEOUS MATERIALS

- A. Primer: Material recommended by joint-sealant manufacturer where required for adhesion of sealant to joint substrates indicated, as determined from preconstruction joint-sealant-substrate tests and field tests.
- B. Cleaners for Nonporous Surfaces: Chemical cleaners acceptable to manufacturers of sealants and sealant backing materials.
- C. Masking Tape: Nonstaining, nonabsorbent material compatible with joint sealants and surfaces adjacent to joints.

PART 3 - EXECUTION

3.1 PREPARATION

- A. Surface Cleaning of Joints: Clean out joints immediately before installing joint sealants to comply with joint-sealant manufacturer's written instructions and the following requirements:
 - 1. Remove laitance and form-release agents from concrete.
 - 2. Clean nonporous joint substrate surfaces with chemical cleaners or other means that do not stain, harm substrates, or leave residues capable of interfering with adhesion.
- B. Joint Priming: Prime joint substrates where recommended by joint-sealant manufacturer or as indicated by preconstruction joint-sealant-substrate tests or prior experience.
- C. Masking Tape: Use masking tape where required to prevent contact of sealant or primer with adjoining surfaces.

3.2 INSTALLATION OF JOINT SEALANTS

- A. General: Comply with ASTM C 1193 and joint-sealant manufacturer's written installation instructions for products and applications indicated, unless more stringent requirements apply.
- B. Install sealant backings of kind indicated to support sealants during application and at position required to produce cross-sectional shapes and depths of installed sealants relative to joint widths that allow optimum sealant movement capability.
- C. Install bond-breaker tape behind sealants where sealant backings are not used between sealants and backs of joints.

- D. Install sealants using proven techniques that comply with the following and at the same time backings are installed:
1. Place sealants so they directly contact and fully wet joint substrates.
 2. Completely fill recesses in each joint configuration.
 3. Produce uniform, cross-sectional shapes and depths relative to joint widths that allow optimum sealant movement capability.
- E. Tooling of Nonsag Sealants: Immediately after sealant application and before skinning or curing begins, tool sealants to form smooth, uniform beads of configuration indicated. Use tooling agents that are approved in writing by sealant manufacturer and that do not discolor sealants or adjacent surfaces.
1. Provide concave joint profile per Figure 8A in ASTM C 1193 unless otherwise indicated.

3.3 JOINT-SEALANT SCHEDULE

- A. Joint-Sealant Application: Exterior joints in vertical surfaces and horizontal nontraffic surfaces.
1. Joint Locations:
 - a. Joints in between trim and brick work.
 2. Joint Sealant: Silicone, nonstaining, S, NS, 50, NT.
 3. Joint-Sealant Color: As selected by Architect from manufacturer's full range of colors.
- B. Joint-Sealant Application: Interior joints in vertical surfaces and horizontal nontraffic surfaces not subject to significant movement.
1. Joint Locations:
 - a. Perimeter joints between interior wall surfaces and frames of interior doors and windows.
 - b. Other joints as required.
 2. Joint Sealant: Acrylic latex.
 3. Joint-Sealant Color: As selected by Architect from manufacturer's full range of colors.
- C. Joint-Sealant Application: Mildew-resistant interior joints in vertical surfaces and horizontal nontraffic surfaces.
1. Joint Locations:
 - a. Joints between plumbing fixtures and adjoining walls, floors, and counters.
 2. Joint Sealant: Silicone, mildew resistant, acid curing, S, NS, 25, NT.
 3. Joint-Sealant Color: As selected by Architect from manufacturer's full range of colors.

END OF SECTION

SECTION 08 31 13

ACCESS DOORS AND FRAMES

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes access doors and frames for walls and ceilings.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Samples: For each type of access door and frame and for each finish specified.
- C. Product Schedule: For access doors and frames.

PART 2 - PRODUCTS

2.1 ACCESS DOORS AND FRAMES

- A. Flush Access Doors with Concealed Flanges:

1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 - a. Larsen's Manufacturing Company.
 - b. Milnor; Commercial Products Group of Hart & Cooley, Inc.
 - c. Williams Bros. Corporation of America (The).
2. Description: Face of door flush with frame; with concealed flange for gypsum board installation and concealed hinge.
3. Locations: Wall and ceiling.
4. Uncoated Steel Sheet for Door: Nominal 0.060 inch, 16 gage, factory primed.
5. Frame Material: Same material and thickness as door.
6. Latch and Lock: Cam latch, screwdriver operated.

2.2 MATERIALS

- A. Steel Plates, Shapes, and Bars: ASTM A 36/A 36M.

- B. Steel Sheet: Uncoated or electrolytic zinc coated, ASTM A 879/A 879M, with cold-rolled steel sheet substrate complying with ASTM A 1008/A 1008M, Commercial Steel (CS), exposed.
- C. Frame Anchors: Same material as door face.
- D. Inserts, Bolts, and Anchor Fasteners: Hot-dip galvanized steel according to ASTM A 153/A 153M or ASTM F 2329.

2.3 FABRICATION

- A. Metal Surfaces: For metal surfaces exposed to view in the completed Work, provide materials with smooth, flat surfaces without blemishes. Do not use materials with exposed pitting, seam marks, roller marks, rolled trade names, or roughness.
- B. Doors and Frames: Grind exposed welds smooth and flush with adjacent surfaces. Furnish mounting holes, attachment devices and fasteners of type required to secure access doors to types of supports indicated.
- C. Latch and Lock Hardware:
 - 1. Quantity: Furnish number of latches and locks required to hold doors tightly closed.
 - 2. Keys: Furnish two keys per lock and key all lock alike.

2.4 FINISHES

- A. Painted Finishes: Comply with coating manufacturer's written instructions for cleaning, conversion coating, and applying and baking finish.
 - 1. Factory Primed: Apply manufacturer's standard, lead- and chromate-free, universal primer immediately after surface preparation and pretreatment.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Comply with manufacturer's written instructions for installing access doors and frames.
- B. Adjust doors and hardware, after installation, for proper operation.

END OF SECTION

SECTION 09 22 16

NON-STRUCTURAL METAL FRAMING

PART 1 - GENERAL

1.1 SUMMARY

A. Section Includes:

1. Non-load-bearing steel framing systems for interior partitions.
2. Suspension systems for interior ceilings and soffits.

1.2 ACTION SUBMITTALS

A. Product Data: For each type of product.

1.3 INFORMATIONAL SUBMITTALS

- A. Product Certificates: For each type of code-compliance certification for studs and tracks.
- B. Evaluation reports for firestop tracks or post-installed anchors and power-actuated fasteners from ICC-ES or other qualified testing agency acceptable to authorities having jurisdiction.

1.4 QUALITY ASSURANCE

- A. Code-Compliance Certification of Studs and Tracks: Provide documentation that framing members are certified according to the product-certification program of the Certified Steel Stud Association, the Steel Framing Industry Association or the Steel Stud Manufacturers Association.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. Fire-Test-Response Characteristics: For fire-resistance-rated assemblies that incorporate non-load-bearing steel framing, provide materials and construction identical to those tested in assembly indicated, according to ASTM E 119 by an independent testing agency.
- B. STC-Rated Assemblies: For STC-rated assemblies, provide materials and construction identical to those tested in assembly indicated on Drawings, according to ASTM E 90 and classified according to ASTM E 413 by an independent testing agency.

2.2 FRAMING SYSTEMS

- A. Framing Members, General: Comply with ASTM C 754 for conditions indicated.
1. Steel Sheet Components: Comply with ASTM C 645 requirements for metal unless otherwise indicated.
- B. Studs and Tracks: ASTM C 645.
1. Steel Studs and Tracks:
 - a. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
 - 1) Phillips Manufacturing Co.
 - 2) SCAFCO Steel Stud Company.
 - 3) Steel Construction Systems.
 - 4) Steel Network, Inc. (The).
 - b. Minimum Base-Metal Thickness: 0.0329 inch (20 gauge).
 - c. Depth: As indicated on Drawings.
- C. Slip-Type Head Joints: Where indicated, provide one of the following:
1. Deflection Track: Steel sheet top track manufactured to prevent cracking of finishes applied to interior partitions resulting from deflection of structure above; in thickness not less than indicated for studs and in width to accommodate depth of studs.
- D. Cold-Rolled Channel Bridging: Steel, 0.0538-inch minimum base-metal thickness, with minimum 1/2-inch-wide flanges.
1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
 - a. ClarkDietrich Building Systems.
 - b. MarinoWARE.
 - c. MRI Steel Framing, LLC.
 - d. SCAFCO Steel Stud Company.
 - e. Steel Construction Systems.
 2. Depth: 1-1/2 inches.
 3. Clip Angle: Not less than 1-1/2 by 1-1/2 inches, 0.068-inch-thick, galvanized steel.

2.3 SUSPENSION SYSTEMS

- A. Tie Wire: ASTM A 641/A 641M, Class 1 zinc coating, soft temper, 0.062-inch-diameter wire, or double strand of 0.048-inch-diameter wire.

2.4 AUXILIARY MATERIALS

- A. General: Provide auxiliary materials that comply with referenced installation standards.
 - 1. Fasteners for Steel Framing: Of type, material, size, corrosion resistance, holding power, and other properties required to fasten steel members to substrates.
- B. Isolation Strip at Exterior Walls: Provide the following:
 - 1. Foam Gasket: Adhesive-backed, closed-cell vinyl foam strips that allow fastener penetration without foam displacement, 1/8 inch thick, in width to suit steel stud size.

PART 3 - EXECUTION

3.1 INSTALLATION, GENERAL

- A. Installation Standard: ASTM C 754.
 - 1. Gypsum Board Assemblies: Also comply with requirements in ASTM C 840 that apply to framing installation.
- B. Install framing and accessories plumb, square, and true to line, with connections securely fastened.
- C. Install supplementary framing, and blocking to support fixtures, equipment services, heavy trim, grab bars, toilet accessories, furnishings, or similar construction.
- D. Install bracing at terminations in assemblies.
- E. Do not bridge building control and expansion joints with non-load-bearing steel framing members. Frame both sides of joints independently.

3.2 INSTALLING FRAMED ASSEMBLIES

- A. Install framing system components according to spacings indicated, but not greater than spacings required by referenced installation standards for assembly types.
- B. Where studs are installed directly against exterior masonry walls or dissimilar metals at exterior walls, install isolation strip between studs and exterior wall.
- C. Install studs so flanges within framing system point in same direction.

- D. Install tracks at floors and overhead supports. Extend framing full height to structural supports or substrates above suspended ceilings except where partitions are indicated to terminate at suspended ceilings. Continue framing around ducts that penetrate partitions above ceiling.
1. Slip-Type Head Joints: Where framing extends to overhead structural supports, install to produce joints at tops of framing systems that prevent axial loading of finished assemblies.
 2. Other Framed Openings: Frame openings other than door openings the same as required for door openings unless otherwise indicated. Install framing below sills of openings to match framing required above door heads.
 3. Fire-Resistance-Rated Partitions: Install framing to comply with fire-resistance-rated assembly indicated and support closures and to make partitions continuous from floor to underside of solid structure.
 - a. Firestop Track: Where indicated, install to maintain continuity of fire-resistance-rated assembly indicated.
 4. Sound-Rated Partitions: Install framing to comply with sound rated assembly indicated.

END OF SECTION

SECTION 09 29 00

GYPSUM BOARD

PART 1 - GENERAL

1.1 SUMMARY

A. Section Includes:

1. Interior gypsum board.

1.2 ACTION SUBMITTALS

A. Product Data: For each type of product.

B. Samples: For each texture finish indicated on same backing indicated for Work.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. Fire-Resistance-Rated Assemblies: For fire-resistance-rated assemblies, provide materials and construction identical to those tested in assembly indicated according to ASTM E 119 by an independent testing agency.

2.2 GYPSUM BOARD, GENERAL

- A. Size: Provide maximum lengths and widths available that will minimize joints in each area and that correspond with support system indicated.

2.3 INTERIOR GYPSUM BOARD

A. Gypsum Board, Type X: ASTM C 1396/C 1396M.

1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
 - a. CertainTeed Corporation.
 - b. Georgia-Pacific Gypsum LLC.
 - c. National Gypsum Company.
 - d. USG Corporation.

2. Thickness: 5/8 inch.
3. Long Edges: Tapered.

2.4 TRIM ACCESSORIES

A. Interior Trim: ASTM C 1047.

1. Material: Galvanized or aluminum-coated steel sheet, rolled zinc, plastic, or paper-faced galvanized-steel sheet.
2. Shapes:
 - a. Cornerbead.
 - b. LC-Bead: J-shaped; exposed long flange receives joint compound.
 - c. L-Bead: L-shaped; exposed long flange receives joint compound.
 - d. Expansion (control) joint.

2.5 JOINT TREATMENT MATERIALS

A. General: Comply with ASTM C 475/C 475M.

B. Joint Tape:

1. Interior Gypsum Board: Paper.

C. Joint Compound for Interior Gypsum Board: For each coat, use formulation that is compatible with other compounds applied on previous or for successive coats.

1. Prefilling: At open joints, rounded or beveled panel edges, and damaged surface areas, use setting-type taping compound.
2. Embedding and First Coat: For embedding tape and first coat on joints, fasteners, and trim flanges, use setting-type taping compound.
 - a. Use setting-type compound for installing paper-faced metal trim accessories.
3. Fill Coat: For second coat, use drying-type, all-purpose compound.
4. Finish Coat: For third coat, use drying-type, all-purpose compound.
5. Skim Coat: For final coat of Level 5 finish, use drying-type, all-purpose compound.

2.6 AUXILIARY MATERIALS

A. General: Provide auxiliary materials that comply with referenced installation standards and manufacturer's written instructions.

B. Steel Drill Screws: ASTM C 1002 unless otherwise indicated.

1. Use screws complying with ASTM C 954 for fastening panels to steel members from 0.033 to 0.112 inch thick.

2. For fastening cementitious backer units, use screws of type and size recommended by panel manufacturer.
- C. Acoustical Sealant: Manufacturer's standard nonsag, paintable, nonstaining latex sealant complying with ASTM C 834. Product effectively reduces airborne sound transmission through perimeter joints and openings in building construction as demonstrated by testing representative assemblies according to ASTM E 90.
 1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
 - a. Pecora Corporation; AC-20 FTR.
 - b. USG Corporation; sheet rock acoustical sealant.

PART 3 - EXECUTION

3.1 APPLYING AND FINISHING PANELS

- A. Examine panels before installation. Reject panels that are wet, moisture damaged, and mold damaged.
- B. Comply with ASTM C 840.
- C. Isolate perimeter of gypsum board applied to non-load-bearing partitions at structural abutments. Provide 1/4- to 1/2 inch wide spaces at these locations and trim edges with edge trim where edges of panels are exposed. Seal joints between edges and abutting structural surfaces with acoustical sealant.
- D. For trim with back flanges intended for fasteners, attach to framing with same fasteners used for panels. Otherwise, attach trim according to manufacturer's written instructions.
- E. Prefill open joints, rounded or beveled edges, and damaged surface areas.
- F. Apply joint tape over gypsum board joints, except for trim products specifically indicated as not intended to receive tape.
- G. Gypsum Board Finish Levels: Finish panels to levels indicated below and according to ASTM C 840:
 1. Level 1: Ceiling plenum areas, concealed areas, and where indicated.
 2. Level 2: Where indicated on Drawings.
 3. Level 3: Where indicated on Drawings.
 4. Level 4: At panel surfaces that will be exposed to view unless otherwise indicated.

3.2 PROTECTION

- A. Protect installed products from damage from weather, condensation, direct sunlight, construction, and other causes during remainder of the construction period.
- B. Remove and replace panels that are wet, moisture damaged, and mold damaged.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 09 51 13

ACOUSTICAL PANEL CEILINGS

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes acoustical panels and exposed suspension systems for interior ceilings.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Samples: For each exposed product and for each color and texture specified.
- C. Delegated-Design Submittal: For seismic restraints for ceiling systems.
 - 1. Include design calculations for seismic restraints including analysis data signed and sealed by the qualified professional engineer responsible for their preparation.

1.3 INFORMATIONAL SUBMITTALS

- A. Coordination Drawings: Reflected ceiling plans, drawn to scale, and coordinated with each other, using input from installers of the items involved.
- B. Product test reports.
- C. Research reports.
- D. Field quality-control reports.

1.4 CLOSEOUT SUBMITTALS

- A. Maintenance data.

PART 2 - PRODUCTS

2.1 PERFORMANCE REQUIREMENTS

- A. Delegated Design: Engage a qualified professional engineer, as defined in Section 01 40 00 "Quality Requirements," to design seismic restraints for ceiling systems.

- B. Seismic Performance: Suspended ceilings shall withstand the effects of earthquake motions determined according to ASCE/SEI 7.
- C. Surface-Burning Characteristics: Comply with ASTM E 84; testing by a qualified testing agency. Identify products with appropriate markings of applicable testing agency.
 - 1. Flame-Spread Index: Class A according to ASTM E 1264.
 - 2. Smoke-Developed Index: 450 or less.

2.2 ACOUSTICAL PANELS - TYPE A1

- A. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
 - 1. Armstrong World Industries, Inc.; School Zone – Fine Fissured, 824, white
- B. Acoustical Panel Standard: Manufacturer's standard panels according to ASTM E 1264.
- C. Classification: Provide panels complying with ASTM E 1264 for type, form, and pattern as follows:
 - 1. Type and Form: Type IV, mineral base with membrane-faced overlay; Form 2, water felted; with vinyl overlay on face, back, and sealed edges.
 - 2. Pattern: As indicated by manufacturer's designation.
- D. Color: White.
- E. Light Reflectance (LR): Not less than 85.
- F. Ceiling Attenuation Class (CAC): Not less than 35.
- G. Noise Reduction Coefficient (NRC): Not less than 0.70.
- H. Edge/Joint Detail: Regular.
- I. Thickness: 3/4 inch.
- J. Modular Size: 24 by 48 inches.

2.3 ACOUSTICAL PANELS - TYPE A2

- A. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
 - 1. Armstrong World Industries, Inc.; School Zone – Fine Fissured, 1714, white.
- B. Acoustical Panel Standard: Manufacturer's standard panels according to ASTM E 1264.
- C. Classification: Provide panels complying with ASTM E 1264 for type, form, and pattern as follows:

1. Type and Form: Type IV, mineral base with membrane-faced overlay; Form 2, water felted; with vinyl overlay on face, back, and sealed edges.
2. Pattern: As indicated by manufacturer's designation.

D. Color: White.

E. Light Reflectance (LR): Not less than .85.

F. Ceiling Attenuation Class (CAC): Not less than 40.

G. Noise Reduction Coefficient (NRC): Not less than 0.70.

H. Edge/Joint Detail: Square.

I. Thickness: 3/4 inch.

J. Modular Size: 24 by 48 inches.

2.4 ACOUSTICAL PANELS - TYPE A3

A. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:

1. Armstrong World Industries, Inc.; School Zone – Fine Fissured, 1713, white

B. Acoustical Panel Standard: Manufacturer's standard panels according to ASTM E 1264.

C. Classification: Provide panels complying with ASTM E 1264 for type, form, and pattern as follows:

1. Type and Form: Type IV, mineral base with membrane-faced overlay; Form 2, water felted; with vinyl overlay on face, back, and sealed edges.
2. Pattern: As indicated by manufacturer's designation.

D. Color: White.

E. Light Reflectance (LR): Not less than .85.

F. Ceiling Attenuation Class (CAC): Not less than 35.

G. Noise Reduction Coefficient (NRC): Not less than 0.70.

H. Edge/Joint Detail: Square.

I. Thickness: 3/4 inch.

J. Modular Size: 24 by 24 inches.

2.5 METAL SUSPENSION SYSTEM

- A. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
1. Armstrong Prelude XL 15/16" Exposed Tee.
- B. Metal Suspension-System Standard: Manufacturer's standard, direct-hung, metal suspension system and accessories according to ASTM C 635/C 635M.
- C. Wide-Face, Capped, Double-Web, Steel Suspension System: Main and cross runners roll formed from cold-rolled steel sheet; prepainted, electrolytically zinc coated, or hot-dip galvanized, G30 coating designation; with prefinished 15/16-inch-wide metal caps on flanges.
1. Structural Classification: Intermediate-duty system.
 2. End Condition of Cross Runners: Override (stepped) type.
 3. Face Design: Flat, flush.
 4. Cap Material: Cold-rolled steel.
 5. Cap Finish: Painted white.

2.6 ACCESSORIES

- A. Attachment Devices: Size for five times the design load indicated in ASTM C 635/C 635M, Table 1, "Direct Hung," unless otherwise indicated. Comply with seismic design requirements.
- B. Hold-Down Clips: Manufacturer's standard hold-down.
- C. Impact Clips: Manufacturer's standard impact-clip system designed to absorb impact forces against acoustical panels.
- D. Seismic Clips: Manufacturer's standard seismic clips designed to secure acoustical panels in place during a seismic event.

2.7 METAL EDGE MOLDINGS AND TRIM

- A. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
1. Armstrong.
- B. Roll-Formed, Sheet-Metal Edge Moldings and Trim: Type and profile indicated or, if not indicated, manufacturer's standard moldings for edges and penetrations that comply with seismic design requirements; formed from sheet metal of same material, finish, and color as that used for exposed flanges of suspension-system runners.
- C. External Aluminum Panel Trim: Basis of Design Product.
1. Armstrong Axion Classic Trim, Height as indicated on Drawings.

PART 3 - EXECUTION

3.1 PREPARATION

- A. Measure each ceiling area and establish layout of acoustical panels to balance border widths at opposite edges of each ceiling. Avoid using less-than-half-width panels at borders unless otherwise indicated.
- B. Layout openings for penetrations centered on the penetrating items.

3.2 INSTALLATION

- A. Install acoustical panel ceilings according to ASTM C 636/C 636M and manufacturer's written instructions.
- B. Install edge moldings and trim of type indicated at perimeter of acoustical ceiling area and where necessary to conceal edges of acoustical panels.
 - 1. Apply acoustical sealant in a continuous ribbon concealed on back of vertical legs of moldings before they are installed.
 - 2. Do not use exposed fasteners, including pop rivets, on moldings and trim.
 - 3. Arrange directionally patterned acoustical panels as follows:
 - a. As indicated on reflected ceiling plans.
 - b. Install panels with pattern running in one direction parallel to long axis of space.
 - 4. Install hold-down clips in areas indicated; space according to panel manufacturer's written instructions unless otherwise indicated.

3.3 FIELD QUALITY CONTROL

- A. Special Inspection. Owner will engage a qualified special inspector to perform inspections.
 - 1. Periodic inspection during the installation of suspended ceiling grids according to AIA/CES/SI 7.

END OF SECTION

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 09 65 13

RESILIENT BASE AND ACCESSORIES

PART 1 - GENERAL

1.1 SUMMARY

- A. Section Includes:
 - 1. Thermoplastic-rubber base.

1.2 ACTION SUBMITTALS

- A. Product Data: For each type of product.
- B. Samples: For each exposed product and for each color and texture specified.

PART 2 - PRODUCTS

2.1 THERMOSET-RUBBER BASE

- A. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to the following:
 - 1. Johnsonite; a Tarkett company.
- B. Product Standard: ASTM F 1861, Type TS (rubber, vulcanized thermoset), Group I (solid, homogeneous).
 - 1. Style and Location:
 - 2. Style B, Cove: Provide in areas with resilient floor coverings.
- C. Thickness: 0.125 inch.
- D. Height: 4 inches.
- E. Lengths: Cut lengths 48 inches long or coils in manufacturer's standard length.
- F. Outside Corners: Job formed or preformed.
- G. Inside Corners: Job formed or preformed.
- H. Colors: To match existing base.

2.2 INSTALLATION MATERIALS

- A. Trowelable Leveling and Patching Compounds: Latex-modified, portland-cement-based or blended hydraulic-cement-based formulation provided or approved by resilient-product manufacturer for applications indicated.
- B. Adhesives: Water-resistant type recommended by resilient-product manufacturer for resilient products and substrate conditions indicated.

PART 3 - EXECUTION

3.1 PREPARATION

- A. Prepare substrates according to manufacturer's written instructions to ensure adhesion of resilient products.
- B. Fill cracks, holes, and depressions in substrates with trowelable leveling and patching compound; remove bumps and ridges to produce a uniform and smooth substrate.
- C. Do not install resilient products until materials are the same temperature as space where they are to be installed.
- D. Immediately before installation, sweep and vacuum clean substrates to be covered by resilient products.

3.2 RESILIENT BASE INSTALLATION

- A. Comply with manufacturer's written instructions for installing resilient base.
- B. Apply resilient base to walls, columns, pilasters, casework and cabinets in toe spaces, and other permanent fixtures in rooms and areas where base is required.
- C. Install resilient base in lengths as long as practical without gaps at seams and with tops of adjacent pieces aligned.
- D. Tightly adhere resilient base to substrate throughout length of each piece, with base in continuous contact with horizontal and vertical substrates.
- E. Do not stretch resilient base during installation.
- F. On masonry surfaces or other similar irregular substrates, fill voids along top edge of resilient base with manufacturer's recommended adhesive filler material.
- G. Preformed Corners: Install preformed corners before installing straight pieces.
- H. Job-Formed Corners:
 - 1. Outside Corners: Use straight pieces of maximum lengths possible and form with returns not less than 3 inches in length.

- a. Form without producing discoloration (whitening) at bends.
2. Inside Corners: Use straight pieces of maximum lengths possible and form with returns not less than 3 inches in length.
 - a. Miter or cope corners to minimize open joints.

3.3 RESILIENT ACCESSORY INSTALLATION

- A. Comply with manufacturer's written instructions for installing resilient accessories.

3.4 CLEANING AND PROTECTION

- A. Comply with manufacturer's written instructions for cleaning and protecting resilient products.

END OF SECTION

NOT FOR BIDDING PURPOSES

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 09 91 23
INTERIOR PAINTING

PART 1 - GENERAL

1.1 SUMMARY

- A. Section includes surface preparation and the application of paint systems on the following interior substrates:
1. Concrete masonry units (CMUs).
 2. Gypsum board.

1.2 DEFINITIONS

- A. MPI Gloss Level 1: Not more than five units at 60 degrees and 10 units at 85 degrees, according to ASTM D 523.
- B. MPI Gloss Level 2: Not more than 10 units at 60 degrees and 10 to 35 units at 85 degrees, according to ASTM D 523.
- C. MPI Gloss Level 3: 10 to 25 units at 60 degrees and 10 to 35 units at 85 degrees, according to ASTM D 523.
- D. MPI Gloss Level 4: 20 to 35 units at 60 degrees and not less than 35 units at 85 degrees, according to ASTM D 523.
- E. MPI Gloss Level 5: 35 to 70 units at 60 degrees, according to ASTM D 523.
- F. MPI Gloss Level 6: 70 to 85 units at 60 degrees, according to ASTM D 523.
- G. MPI Gloss Level 7: More than 85 units at 60 degrees, according to ASTM D 523.

1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product. Include preparation requirements and application instructions.
1. Include Printout of current "MPI Approved Products List" for each product category specified, with the proposed product highlighted.
- B. Samples: For each type of paint system and in each color and gloss of topcoat.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
1. Benjamin Moore & Co.
 2. Glidden Professional.
 3. PPG Paints.
 4. Sherwin-Williams Company (The).
- B. Products: Subject to compliance with requirements, provide products listed in the Interior Painting Schedule for the paint category indicated.


2.2 PAINT, GENERAL

- A. MPI Standards: Products shall comply with MPI standards indicated and shall be listed in its "MPI Approved Products Lists."
- B. Material Compatibility:
1. Materials for use within each paint system shall be compatible with one another and substrates indicated, under conditions of service and application as demonstrated by manufacturer, based on testing and field experience.
 2. For each coat in a paint system products shall be recommended in writing by topcoat manufacturers for use in paint system and on substrate indicated.
- C. Colors: To match existing surrounding surfaces.
1. Ten percent of surface area will be painted with deep tones.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates and conditions, with Applicator present, for compliance with requirements for maximum moisture content and other conditions affecting performance of the Work.
- B. Maximum Moisture Content of Substrates: When measured with an electronic moisture meter as follows:
1. Masonry (Clay and CMUs): 12 percent.
 2. Gypsum Board: 12 percent.
- C. Verify suitability of substrates, including surface conditions and compatibility with existing finishes and primers.



- D. Proceed with coating application only after unsatisfactory conditions have been corrected.
 - 1. Application of coating indicates acceptance of surfaces and conditions.

3.2 PREPARATION

- A. Comply with manufacturer's written instructions and recommendations in "MPI Architectural Painting Specification Manual" applicable to substrates and paint systems indicated.
- B. Remove hardware, covers, plates, and similar items already in place that are removable and are not to be painted. If removal is impractical or impossible because of size or weight of item, provide surface-applied protection before surface preparation and painting.
 - 1. After completing painting operations, use workers skilled in the trades involved to reinstall items that were removed. Remove surface-applied protection if any.

3.3 APPLICATION

- A. Apply paints according to manufacturer's written instructions and recommendations in "MPI Architectural Painting Specification Manual."
- B. Apply paints to produce surface films without cloudiness, spotting, holidays, laps, brush marks, roller tracking, runs, sags, ropiness, or other surface imperfections. Cut in sharp lines and color breaks.

3.4 INTERIOR PAINTING SCHEDULE

A. CMU Substrates:

- 1. Institutional Low-Odor/VOC Latex System MPI INT 4.2E:
 - a. Block Filler: Block filler, latex, interior/exterior, MPI #4.
 - 1) Basis of Design: Sherwin Williams.
 - b. Intermediate Coat: Latex, interior, institutional low odor/VOC, matching topcoat.
 - c. Topcoat: Latex, interior, institutional low odor/VOC (MPI Gloss Level 4), MPI #146.
 - 1) Basis of Design: Sherwin Williams.

B. Gypsum Board Substrates:

- 1. Institutional Low-Odor/VOC Latex System MPI INT 9.2M:
 - a. Prime Coat: Primer sealer, interior, institutional low odor/VOC, MPI #149.
 - 1) Basis of Design: Sherwin Williams.
 - b. Topcoat: Latex, interior, institutional low odor/VOC (MPI Gloss Level 4), MPI #146.

- 1) Basis of Design: Sherwin Williams.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 11 33 00
RETRACTABLE STAIRS

PART 1 - GENERAL

1.1 SECTIONS INCLUDES

- A. Manual disappearing stairways.

1.2 REFERENCES

- A. ANSI A14.9: Safety Requirements for Ceiling Mounted Disappearing Climbing Systems.

1.3 SUBMITTALS

- A. Submit under provisions of Section 01 33 00.
- B. Manufacturer's data sheets on each product to be used, including:
 - 1. Preparation instructions and recommendations.
 - 2. Storage and handling requirements and recommendations.
 - 3. Installation methods.
- C. Shop Drawings for Stairs:
 - 1. Plan and section of stair installation.
 - 2. Indicate rough opening dimensions for ceiling and/or roof openings.

1.4 DELIVERY, STORAGE AND HANDLING

- A. Store stairway until installation inside under cover in manufacturer's unopened packaging. If stored outside, under a tarp or suitable cover.

1.5 WARRANTY

- A. Limited Warranty: One year against defective material and workmanship, covering parts only. Defective parts, as deemed by the manufacturer, will be replaced at no charge, freight excluded, upon inspection at manufacturer's plant.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Basis of Design Manufacturer: Precision Ladders, LLC, P. O. Box 2279; Morristown, TN 37816-2279; Tel: 423-586-2265; Fax: 423-586-2091; www.PrecisionLadders.com

2.2 MANUAL DISAPPEARING STAIRWAYS

- A. Manual Disappearing Stairway.

1. Standard Model: Super Simplex Disappearing Stairway as manufactured by Precision Ladders LLC. Stairs for ceiling heights 7'-0" – 12'-0": Model 1000 (ceiling height in inches). Stairs for ceiling heights 12'-1" – 13'-6": Model 2000 (ceiling height in inches).

- B. Performance Standard: Unit shall comply with ANSI A14.9, Commercial Type, for rough openings between 27 inches to 39 inches. Stairway capacity shall be rated at 500 lbs.

- C. Accessories:

1. Steel pole to aid opening and closing stairways.
2. Stairs for ceiling heights 9'-10" – 12'-0" shall be equipped with a patented Precision Fold Assist to aid in folding and unfolding of sections. Stairs for ceiling heights 12'-1" – 13'-6" shall be equipped with 2 Fold Assists. Precision Fold-Assist is optional on stairways for ceiling heights of 9' and below.

- D. COMPONENTS

1. Ceiling Opening:

- a. Ceiling height of 9'-9" or less requires an opening of 30" x 54"
b. Ceiling heights from 9'-10" – 12'-0" require opening of 30" x 64"
c. Ceiling heights from 12'-1" – 13'-6" require opening of 22 1/2" x 72"

2. Stairway Stringer: 6005-T5 Extruded aluminum channel 5" x 1" x 1/8"; tri-fold design; steel blade type hinges; adjustable feet with plastic Mar-guard. Pitch shall be 63°.

3. Stairway Tread: 6005-T5 extruded aluminum channel 5 3/16 inches by 1 1/4 inches by 1/8 inch. Depth is 5 3/16 inches. Deeply serrated top surface. Riser Height: 9-1/2 inches. Clear Tread Width for Standard Width: 18 inches.

4. Railing: Aluminum bar handrail riveted to stringers, upper section only.

5. Frame:

- a. If ceiling to floor (or roof deck) above is under 12", frame shall be 1/8" steel formed channel, box.
b. When ceiling to floor (or roof deck) above is 12" or greater, the frame shall be 1/8" steel, 63° (with built-in steps) on the hinge end, 90° on the other end, custom depth to fill distance from ceiling to floor above. This custom frame will require a longer opening in the floor above than is required at the ceiling level.

6. Door Panel
 - a. Standard (non-fire rated) door shall be constructed of 1/8 inch (3 mm) aluminum sheet attached to stairway frame with a steel piano hinge. Door overlaps bottom flange of frame. Eye bolt accommodates pole for opening and closing door.
7. Hardware:
 - a. Steel blade type hinge connecting stringer sections. Zinc plated and chromate sealed.
 - b. Steel operating arms, both sides. Zinc coat with clear trivalent chromate.
 - c. Double acting steel springs and cable, both sides.
 - d. Rivets rated at 1100 lb (499 kg) shear strength each.
 - e. Steel section alignment clips at stringer section joints.
 - f. Molded rubber guards at corners of aluminum door panel.
8. Finishes: Mill finish on aluminum stairway components. Prime coat on frame.

2.3 FABRICATION

- A. Completely fabricate ladder ready for installation before shipment to the site.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Do not begin installation until rough opening and structural support have been properly prepared. Layout opening for penetrations centered on the penetrating items.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.
- C. Examine materials upon arrival at site. Notify the carrier and manufacturer of any damage.

3.2 INSTALLATION

- A. Install in accordance with manufacturer's instructions.

3.3 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.

END OF SECTION

PAGE

INTENTIONALLY

LEFT

BLANK

NOT FOR BIDDING PURPOSES

SECTION 21 05 00

COMMON WORK RESULTS FOR FIRE PROTECTION

PART 1. GENERAL

1.1. SUMMARY

- A. All work under Division 21 is subject to the Division 01, *General Conditions* and *Special Requirements* for the entire contract.
- B. Provide all labor, materials, equipment, and services necessary for and incidental to the complete installation and operation of all mechanical work.
- C. Unless otherwise specified, all submissions shall be made to, and acceptances and approvals made by the Architect and the Engineer.
- D. Contract Drawings are generally diagrammatic and all offsets, fittings, transitions and accessories are not necessarily shown. Furnish and install all such items as may be required to fit the work to the conditions encountered. Arrange piping, equipment, and other work generally as shown on the contract drawings, providing proper clearance and access. Where departures are proposed because of field conditions or other causes, prepare and submit detailed shop drawings for approval in accordance with *Submittals* specified below. The right is reserved to make reasonable changes in location of equipment, and piping up to the time of rough-in or fabrication.
- E. Conform to the requirements of all rules, regulations and codes of local, state and federal authorities having jurisdiction.
- F. Coordinate the work under Division 21 with the work of all other construction trades.
- G. Be responsible for all construction means, methods, techniques, procedures, and phasing sequences used in the work. Furnish all tools, equipment and materials necessary to properly perform the work in first class, substantial, and workmanlike manner, in accordance with the full intent and meaning of the contract documents.
- H. The existing fire protection system shall be removed and a new fire protection system installed as indicated on the Contract Drawings.

1.2. PERMITS AND FEES

- A. Obtain all permits and pay taxes, fees and other costs in connection with the work. File necessary plans, prepare documents, give proper notices and obtain necessary approvals. Deliver inspection and approval certificates to Owner prior to final acceptance of the work.
- B. Permits and fees shall comply with the Division 01, *General Requirements* of the specification.

1.3. EXAMINATION OF SITE

- A. Examine the site, determine all conditions and circumstances under which the work must be done, and make all necessary allowances for same. No additional cost to the Owner will be permitted for contractor's failure to do so.
- B. Examine and verify specific conditions described in individual specifications sections.
- C. Verify that utility services are available, of the correct characteristics, and in the correct locations.

1.4. CONTRACTOR QUALIFICATION

- A. Any Contractor or Subcontractor performing work under Division 21 shall be fully qualified and acceptable to the Architect and Owner. Submit the following evidence when requested:
 - 1. A list of not less than five comparable projects which the Contractor completed.
 - 2. Letter of reference from not less than three registered professional engineers, general contractors or building owners.
 - 3. Local and/or State License, where required.
 - 4. Membership in trade or professional organizations where required.
- B. A Contractor is any individual, partnership or corporation, performing work by contract or subcontract on this project.
- C. Acceptance of a Contractor or Subcontractor will not relieve the Contractor or subcontractor of any contractual requirements or his responsibility to supervise and coordinate the work of various trades.

1.5. MATERIALS AND EQUIPMENT

- A. Materials and equipment installed as a permanent part of the project shall be new, unless otherwise indicated or specified, and of the specified type and quality. Existing items of equipment are being relocated under another Division of these specifications. The Contractor shall be responsible for connecting all utilities as shown on the drawings, to equipment identified as existing.
- B. Where material or equipment is identified by proprietary name, model number and/or manufacturer, furnish named item, or its equal, subject to approval by Engineer. Substituted items shall be equal or better in quality and performance and must be suitable for available space, required arrangement, and application. Submit all data necessary to determine suitability of substituted items, for approval.
- C. The suitability of named item only has been verified. Where more than one item is named, only the first named item has been verified as suitable. Substituted items, including items other than first named shall be equal or better in quality and performance to that of specified items, and must be suitable for available space, required arrangement and application. Contractor, by providing other than the first named manufacturer, assumes responsibility for all necessary adjustments and modifications necessary for a

satisfactory installation. Adjustments and modifications shall include but not be limited to electrical, structural, support, and architectural work.

- D. Substitution will not be permitted for specified items of material or equipment where noted.
- E. All items of equipment furnished shall have a service record of at least five (5) years.

1.6. FIRE SAFE MATERIALS


- A. Unless otherwise indicated, materials and equipment shall conform to UL, NFPA and ASTM standards for fire safety with smoke and fire hazard rating not exceeding flame spread of 25 and smoke developed of 50.

1.7. REFERENCED STANDARDS, CODES AND SPECIFICATIONS

- A. Specifications, Codes and Standards listed below are included as part of this specification, latest edition.
- B. ASTM - American Society for Testing and Materials
- C. FM - Factory Mutual
- D. IBC - International Building Code
- E. IEEE - Institute of Electrical and Electronics Engineers
- F. MSSP - Manufacturers Standards Society of the Valve and Fittings Industry
- G. NEC - National Electrical Code
- H. NEMA - National Electrical Manufacturers Association
- I. NFPA - National Fire Protection Association
- J. UL - Underwriters' Laboratories
- K. State of Delaware Fire Protection Requirements.
- L. All equipment, materials, piping and installation shall comply with the codes and standards listed in the enforceable edition of the Applicable National Fire Protection Association Pamphlets.
- M. Fire Protection Systems design, equipment and installation shall comply with the Delaware State Fire Prevention Regulations, latest edition including all Annexes and Addendums.

1.8. SUBMITTALS, REVIEW AND ACCEPTANCE

- A. Equipment, materials, installation, workmanship and arrangement of work are subject to review and acceptance. No substitution will be permitted after acceptance of equipment or materials except where such substitution is considered by the Architect to be in best interest of Owner.
- B. After acceptance of Material and Equipment List, submit six (6) copies or more as required under General Conditions of complete descriptive data for all items. Data shall consist of specifications, data sheets, samples, capacity ratings, performance curves, operating characteristics, catalog cuts, dimensional drawings, wiring diagrams, installation instructions, and any other information necessary to indicate complete compliance with Contract Documents. Edit submittal data specifically for application to



this project.

- C. Thoroughly review and stamp all submittals to indicate compliance with contract requirements prior to submission. Coordinate installation requirements and any electrical requirements for equipment submitted. Contractor shall be responsible for correctness of all submittals.
- D. Submittals will be reviewed for general compliance with design concept in accordance with contract documents, but dimensions, quantities, or other details will not be verified.
- E. Identify submittals, indicating intended application, location and service of submitted items. Refer to specification sections or paragraphs and drawings where applicable. Clearly indicate exact type, model number, style, size and special features of proposed item. Submittals of a general nature will not be acceptable. For substituted items, clearly list on the first page of the submittal all differences between the specified item and the proposed item. The contractor shall be responsible for corrective action and maintaining the specification requirements if differences have not been clearly indicated in the submittal.
- F. Submit actual operating conditions or characteristic for all equipment where required capacities are indicated. Factory order forms showing only required capacities will not be acceptable. Call attention, in writing, to deviation from contract requirements.
- G. Acceptance will not constitute waiver of contract requirements unless deviations are specifically indicated and clearly noted. Use only final or corrected submittals and data prior to fabrication and/or installation.
- H. For any submittal requiring more than two (2) reviews by the Engineer (including those caused by a change in subcontractor or supplier) the Owner will withhold contractor's funds by a change order to the contract to cover the cost of additional reviews. One review is counted for each action including rejection or return of any reason.
- I. For resubmissions, the Contractor must address in writing all of the Engineer's comments on the original submission to verify compliance.

1.9. SHOP DRAWINGS

- A. Prepare and submit shop drawings for all mechanical equipment, specially fabricated items, modifications to standard items, specially designed systems where detailed design is not shown on the contract drawings, or where the proposed installation differs from that shown on contract drawings.
- B. Submit data and shop drawings including but not limited to the list below, in addition to provisions of the paragraph above. Identify all shop drawings by the name of the item and system and the applicable specification paragraph number and drawing number.
- C. Every submittal including, but not limited to the list below, shall be forwarded with its own transmittal as a separate, distinct shop drawing. Grouping of items/systems that are not related shall be unacceptable.
- D. Items and Systems

Access Doors/Panels including layout and location
Alarm Check Valves
Backflow Preventers
Coordinated Drawings
Drip Pans
Exterior Equipment/Piping Supports
Fire Protection System including Hydraulic Calculations, Equipment and Devices
Fire Stopping - Methods and Materials
Flowmeter and Primary Elements (Flow Fittings)
Gongs
Hose Valve Cabinets and Hose Valves
Identification System
Material and Equipment List
Operations and Maintenance Manuals
Pipe Materials Including Itemized Schedule
Preliminary Pipe Pressure Tests
Pressure Relief Valves
Pressure Gauges
Strainers
Test Certificates
Valves
Weatherproof Assembly Components
Wiring Diagrams, Flow Diagrams and Operating Instructions
Zone Valve Assemblies and Wire Mesh Enclosures

- E. Contractor, additionally, shall submit for review any other shop drawings as required by the Architect. No item shall be delivered to the site, or installed, until the Contractor has received a submittal from the Engineer marked *Reviewed* or *Comments Noted*. After the proposed materials have been reviewed, no substitution will be permitted except where approved by the Architect.
- F. For any shop drawing requiring more than two (2) reviews by the Engineer (including those caused by a change in subcontractor or supplier) the Owner will withhold contractor's funds by a change order to the contract to cover the cost of additional reviews. One review is counted for each action including rejection or return of any reason.

1.10. SUPERVISION AND COORDINATION

- A. Provide complete supervision, direction, scheduling, and coordination of all work under the Contract, including that of subcontractors.
- B. Coordinate rough-in of all work and installation of sleeves, anchors, and supports for piping, equipment, and other work performed under Division 21.
- C. Arrange for pipe spaces, chases, slots, and openings in building structure during progress of construction to allow for fire protection installations.
- D. Coordinate electrical work required under Division 21 with that under Division 26. Coordinate all work under Division 21 with work under all other Divisions.

- E. Supply services of an experienced (10 years minimum) and competent Project Manager to be in constant charge of work at site.
- F. Where a discrepancy exists within the specifications or drawings or between the specifications and drawings, the more stringent (or costly) requirement shall apply until clarification can be obtained from the Engineer. Failure to clarify such discrepancies with the Engineer will not relieve the Contractor of the responsibility of conforming to the requirements of the Contract.
- G. Failure of contractor to obtain a full and complete set of contract documents (either before or after bidding) will not relieve the contractor of the responsibility of complying with the intent of the contract documents.

1.11. CUTTING AND PATCHING

- A. Accomplish all cutting and patching necessary for the installation of work under Division 21. Damage resulting from this work to other work already in place, shall be repaired at Contractor's expense. Where cutting is required, perform work in neat and workmanlike manner. Restore disturbed work to match and blend with existing construction and finish, using materials compatible with the original. Use mechanics skilled in the particular trades required.
- B. Do not cut structural members without approval from the Architect or Structural Engineer.

1.12. PENETRATION OF WATERPROOF CONSTRUCTION

- A. Coordinate the work to minimize penetration of waterproof construction, including roofs, exterior walls, and interior waterproof construction. Where such penetrations are necessary, furnish and install all necessary curbs, sleeves, flashings, fittings and caulking to make penetrations absolutely watertight.
- B. Where pipes penetrate roofs, flash pipe with Stoneman *Stormtite*, Pate or approved equal, roof flashing assemblies with skirt and caulked counter flashing sleeve.
- C. Furnish and install pitch pockets or weather tight curb assemblies where required.
- D. Furnish and install curbs, specifically designed for application to the particular roof construction, and install in accordance with the manufacturer's instructions. The Contractor shall be responsible for sleeve sizes and locations. All roof penetrations shall be installed in accordance with manufacturer's instructions, the National Roofing Contractors Association, SMACNA, and as required by other divisions of these specifications.

1.13. CONNECTIONS AND ALTERATIONS TO EXISTING WORK

- A. Unless otherwise noted on the drawings, where existing fire protection work is removed, pipes, valves, etc., shall be removed, including hangers, to a point below finished floors or behind finished walls and capped. Such point shall be far enough behind finished surfaces to allow for installation of normal thickness of required finish material.

- B. Where work specified in Division 21 connects to existing equipment and piping, etc., Contractor shall perform all necessary alterations, cuttings, fittings, etc., of existing work as may be necessary to make satisfactory connections between new and existing work, and to leave completed work in a finished and workmanlike condition.
- C. Where the work specified under Division 21, or under other Divisions, requires relocation of existing equipment, piping, etc., Contractor shall perform all work and make necessary changes to existing work as may be required to leave completed work in a finished and workmanlike condition.
- D. Where the relocation of existing equipment is required for access or the installation of new equipment, the contractor shall temporarily remove and/or relocate and re-install as required to leave the existing and new work in a finished and workmanlike condition.

1.14. DEMOLITION

- A. Unless otherwise noted all existing equipment, piping, etc. shall remain.
- B. Where existing equipment is indicated to be removed, all associated piping, conduit, power, controls, insulation, hangers, supports and housekeeping pads, etc. Patch, paint and repair walls/roof/floor to match existing and/or new finishes.
- C. Provide necessary piping, valves, temporary feeds, etc., as required. Drain and refill piping systems as often as necessary to accommodate phasing and to minimize time lengths of outages.
- D. The Contractor shall be responsible for visiting the site and determining the existing conditions in which the work is to be performed.
- E. Where any abandoned pipes in existing floors, walls, pipe tunnels, ceilings, etc., conflict with new work, remove abandoned pipes as necessary to accommodate new work.
- F. The location of all existing equipment, piping, etc., indicated is approximate only and shall be checked and verified. Install all new fire protection work to connect to or clear existing work as applicable.
- G. Maintain egress at all times. Coordinate egress requirements with the State Fire Marshal, the Owner and the authorities having jurisdiction.
- H. Make provisions and include in bid all costs associated with confined entry/space requirements in crawl spaces and all other applicable OSHA regulations.
- I. Where required to maintain the existing systems in operation, temporarily backfeed existing systems from new equipment. Contractor shall temporarily extend existing piping systems to new piping systems with the appropriate shut-off valves and tamper switches.
- J. At completion of project all temporary piping, valves, controls, etc., shall be removed in their entirety.
- K. Existing piping, equipment, materials, etc., not required for re-use or re-installation in

this project, shall be removed from the project site.

- L. Deliver to the Owner, on the premises where directed, existing equipment and materials which are removed and which are desired by the Owner or are indicated to remain the property of the Owner.
- M. All other materials and equipment which are removed shall become property of the Contractor and shall be promptly removed, from the premises, and disposed of by the Contractor, in an approved manner.
- N. Where piping is removed, remove all pipe hangers which were supporting the removed piping. Patch the remaining penetration voids with like materials and paint to match existing construction.
- O. Where required, provide and coordinate removal and reinstallation of existing equipment. Take care to protect materials and equipment indicated for reuse. Contractor shall repair or replace items which are damaged. Contractor shall have Owner's representative present to confirm condition of equipment prior to demolition.
- P. Before demolition begins, and in the presence of the Owner's representative, test and note all deficiencies in all existing systems affected by demolition but not completely removed by demolition. Provide a copy of the list of system deficiencies to the Owner and the Engineer. Videotape existing conditions in each space prior to beginning demolition work.
- Q. The Owner shall have the first right of refusal for all devices and equipment removed by the Contractor.
- R. All devices and equipment designated by the Owner to remain the property of the Owner shall be moved and stored by the Contractor at a location on site as designated by the Owner. It shall be the Contractor's responsibility to store all devices and equipment in a safe manner to prevent damage while stored.
- S. All existing equipment refused by the Owner shall become the property of the Contractor and shall be removed from the site by the Contractor in a timely manner and disposed of in a legal manner.
- T. Work Abandoned in Place: cut and remove underground pipe a minimum of 2 inches beyond face of adjacent construction. Cap and patch surface to match existing finish.
- U. Temporary Disconnection: Remove, store, clean, reinstall, reconnect, and make operational equipment indicated for relocation.
- V. Terminate services and utilities in accordance with local laws, ordinances, rules and regulations.

1.15. ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

1.16. DEFINITIONS

- A. *Approve* - to permit use of material, equipment or methods conditional upon compliance with contract documents requirements.
- B. *Furnish and install* or *provide* means to supply, erect, install, and connect to complete for readiness for regular operation, the particular work referred to.
- C. *Contractor* means the mechanical contractor and any of his subcontractors, vendors, suppliers, or fabricators.
- D. *Piping* includes pipe, all fittings, valves, hangers, insulation, identification, and other accessories relative to such piping.
- E. *Concealed* means hidden from sight in chases, formed spaces, shafts, hung ceilings, embedded in construction or in crawl space.
- F. *Exposed* means not installed underground or *concealed* as defined above.
- G. *Invert Elevation* means the elevation of the inside bottom of pipe.
- H. *Finished Spaces*: Spaces other than mechanical and electrical equipment rooms, furred spaces, pipe and duct shafts, unheated spaces immediately below roof, spaces above ceiling, unexcavated spaces, crawl spaces, and tunnels.
- I. *Review* - limited observation or checking to ascertain general conformance with design concept of the work and with information given in contract documents. Such action does not constitute a waiver or alteration of the contract requirements.
- J. *Building Line*: Exterior wall of building.

PART 2. ELECTRICAL REQUIREMENTS

2.1. GENERAL MOTOR AND ELECTRICAL REQUIREMENTS

- A. Furnish and install control and interlock wiring for the equipment furnished. In general, power wiring and motor starting equipment will be provided under Division 26. Carefully review the contract documents to coordinate the electrical work under Division 21 with the work under Division 26. Where the electrical requirements of the equipment furnished differ from the provisions made under Division 26, make the necessary allowances under Division 21. Where no electrical provisions are made under Division 26, include all necessary electrical work under Division 21.
- B. All electrical work performed under Division 21 shall conform to the applicable requirements of Division 26 and conforming to the National Electrical Code. All wiring, conduit, etc., installed in ceiling plenums must be plenum rated per NFPA and the IBC.
- C. Provide wiring diagrams with electrical characteristics and connection requirements.
- D. Test Reports: Indicate test results verifying nominal efficiency and power factor for three phase motors larger than five (5) horsepower.

- E. Protect motors stored on site from weather and moisture by maintaining factory covers and suitable weatherproof covering. For extended outdoor storage, remove motors from equipment and store separately.
- F. All motors shall be furnished with visible nameplate indicating motor horsepower, voltage, phase, cycles, RPM, full load amps, locked rotor amps, frame size, manufacturer's name and model number, service factor, power factor and efficiency.
- G. Nominal efficiency and power factor shall be as scheduled at full load and rated voltage when tested in accordance with IEEE 112.
- H. Brake horsepower load requirement at specified duty shall not exceed 85 percent of nameplate horsepower times NEMA service factor for motors with 1.0 and 1.15 service factors.
- I. All single phase motors shall be provided with thermal protection: Internal protection shall automatically open power supply circuit to motor when winding temperature exceeds a safe value calibrated to temperature rating of motor insulation. Thermal protection device shall automatically reset when motor temperature returns to normal range, unless otherwise indicated.

2.2. MOTORS AND CONTROLS

- A. Motors and controls shall conform to the latest requirements of IEEE, NEMA, NFPA-70 and shall be UL listed. Motor sizes are specified with the driven equipment. Motor starting and control equipment is specified either with the motor which is controlled or in an electrical specification section. The Contractor is advised to consult all specification sections to determine responsibility for motors and controls.
- B. Motors shall be designed, built and tested in accordance with the latest revision of NEMA Standard MG.
- C. Motors shall be suitable for use under the conditions and with the equipment to which applied, and designed for operation on the electrical systems specified or indicated.
 - 1. Motor capacities shall be such that the horsepower rating and the rated full-load current will not be exceeded while operating under the specified operating conditions. Under no condition shall the motor current exceed that indicated on the nameplates.
 - 2. Motor sizes noted in the individual equipment specifications are minimum requirements only. It is the responsibility of the equipment manufacturers and of the Contractor to furnish motors, electrical circuits and equipment of ample capacity to operate the equipment without overloading, exceeding the rated full-load current, or overheating at full-load capacity under the most severe operating service of this equipment. Motors shall have sufficient torque to accelerate the total WR^2 of the driven equipment to operating speed.
 - 3. Motors shall be continuous duty type and shall operate quietly at all speeds and loads.

4. Motors shall be designed for operation on 60 hertz power service. Unless otherwise specified or shown, motors less than ½ horsepower shall be single phase, and motors ½ horsepower and larger shall be 3 phase unless otherwise noted.
 5. Motors shall be mounted so that the motor can be removed without removing the entire driven unit.
- D. Single phase motors, smaller than 1/20 horsepower shall be ball or sleeve bearing; drip-proof, totally enclosed or explosion proof, as specified; 120 volts; permanent-split capacitor or shaded pole type. These motors shall not be used for general power purposes, and shall only be provided as built-in components. When approved by the Engineer, deviations from the specifications will be permitted as follows:
1. Open motors may be installed as part of an assembly where enclosure within a cabinet provides protection against moisture.
 2. Motors used in conjunction with low voltage control systems may have a voltage rating less than 115 volts.
- E. Single phase motors, greater than 1/20 horsepower and less than ½ horsepower shall be ball bearing; drip-proof, totally enclosed or explosion proof, as specified, with Class A or B insulation, as standard with the motor manufacturer; 115 or 120/208/240 volts as required; capacitor start-induction run, permanent split capacitor, or repulsion start-induction run type with minimum efficiency of 70 percent and a minimum full load power of 77 percent.
- F. Except as otherwise specified in the various specification sections, 3 phase motors 60 horsepower and smaller shall be NEMA design B squirrel cage induction type meeting the requirements of this paragraph. Motors shall be drip-proof, totally enclosed or explosion proof, as specified or indicated. Insulation shall be Class B or F, at 40 degrees C ambient temperature. Drip-proof motors shall have a 1.15 service factor and totally enclosed and explosion proof motors shall have a service factor of 1.00 or higher. Motors specified for operation at 480, 240, and 208 volts shall be nameplated 460, 230, 209 volts, respectively. Efficiencies and percent power factor at full load for three phase motors shall be not less than the values listed below for premium efficiency motors:

MOTOR NAMEPLATE	MINIMUM EFFICIENCY AT NOMINAL SPEED AND RATED LOAD	PERCENT AT	MINIMUM POWER FACTOR
1HP and above to	85.5 percent		84 percent
1-½ HP	86.5 percent		85 percent
2HP	86.5 percent		85 percent
3HP	89.5 percent		86 percent
5HP	89.5 percent		87 percent

7½ HP	91 percent	86 percent
10HP	91.7 percent	85 percent
15HP	93.0 percent	85 percent
20HP	93.0 percent	86 percent
25HP	93.6 percent	85 percent
50HP and above	94.5 percent	88 percent
60 HP	95.0 percent	90 percent
75HP	95.0 percent	90 percent
100 HP	95.4 percent	90 percent
125 HP	95.8 percent	95 percent
150 HP and above	96.0 percent	95 percent

- G. Three phase motors ½ HP or greater shall be the Duty Master XE by Reliance Electric Company, Super-E Premium Efficiency of Baldor Motor and Drives, E-plus Efficient Standard Duty Motor of the Electric Motor Division of Gould, Inc., the MAC II High Efficiency motor of Westinghouse Electric Corp., the equivalent product of General Electric, or approved equal.
- H. Motor frames shall be NEMA Standard T-Frames of steel, aluminum, or cast iron with end brackets of cast-iron or aluminum with steel inserts.

2.3. MOTOR INSTALLATION

- A. Install in accordance with manufacturer's instructions.
- B. Install securely on firm foundation. Mount ball bearing motors to support shaft regardless of shaft position.
- C. Check line voltage and phase and ensure agreement with nameplate. Check that proper thermal overloads have been installed prior to operating motors.

2.4. WIRING DIAGRAMS

- A. The Contractor is responsible for obtaining and submitting wiring diagrams for all major items of equipment.
- B. Wiring diagrams shall be provided with shop drawings for all equipment requiring electric power.

PART 3. EXECUTION

3.1. EQUIPMENT INSTALLATION - COMMON REQUIREMENTS

- A. Install equipment to provide maximum possible headroom, if mounting heights are not indicated.
- B. Install equipment according to approved submittal data. Portions of the work are shown only in diagrammatic form. Refer conflicts to Architect.
- C. Install equipment level and plumb, parallel and perpendicular to other building systems and components in exposed interior spaces, unless otherwise indicated.
- D. Install fire protection equipment to facilitate service, maintenance, and repair or replacement of components. Connect equipment for ease of disconnecting, with minimum interference to other installations. Extend grease fittings to accessible locations.
- E. Install equipment giving right of way to piping installed at required slope.
- F. Install flexible connectors on equipment side of shutoff valves, horizontally and parallel to equipment shafts if possible.
- G. Do not install equipment or piping over electrical gear, electrical panels, motor controllers, and similar electrical equipment. Install equipment and piping to maintain clear space above and in front of all electrical components per the National Electric Code.

3.2. SUPPORTS, HANGERS AND FOUNDATIONS

- A. Provide supports, hangers, braces, attachments and foundations required for the work. Support and set the work in a thoroughly substantial and workmanlike manner without placing strains on materials, equipment, or building structure, submit shop drawings for approval. Coordinate all work with the requirements of the structural division.
- B. Supports, hangers, braces, and attachments shall be standard manufactured items or fabricated structural steel shapes. All interior hangers shall be galvanized or steel with rust inhibiting paint. For un-insulated copper piping provide copper hanger to prevent contact of dissimilar metals. All exterior hangers shall be constructed of galvanized steel utilizing galvanized rods, nuts, washers, bolts, etc. At contractor's option stainless steel may be utilized for exterior hangers, rods, nuts, washers, bolts, etc.

3.3. DEMONSTRATION AND TRAINING VIDEO RECORDINGS

- A. General: Record demonstration and training video recordings. Record each training module separately.
 - 1. At beginning of each training module, record each chart containing learning objective and lesson outline.
- B. Video Recording Format: Provide high-quality color video recordings with menu navigation in format acceptable to Engineer
- C. Recording: Mount camera on tripod before starting recording, unless otherwise necessary to show area of demonstration and training. Display continuous running time.

- D. Narration: Describe scenes on video recording by audio narration by microphone while video recording is recorded. Include description of items being viewed.
- E. Transcript: Provide a transcript of the narration. Display images and running time captured from videotape opposite the corresponding narration segment.

3.4. PROVISIONS FOR ACCESS

- A. The contractor shall provide access panels and doors for all concealed equipment, valves, strainers, controls, control devices, and other devices requiring maintenance, service, adjustment, balancing or manual operation.
- B. Where access doors are necessary, furnish and install manufactured painted steel door assemblies consisting of hinged door, key locks, and frame designed for the particular wall or ceiling construction. Properly locate each door. Door sizes shall be a 12 inches x 12 inches for hand access, 18 inches x 18 inches for shoulder access and 24 inches x 24 inches for full body access where required. Review locations and sizes with Architect prior to fabrication. Provide U.L. approved and labeled access doors where installed in fire rated walls or ceilings. Doors shall be Milcor Metal Access Doors as manufactured by Inland-Ryerson, Mifab, or approved equal.
 - 1. Acoustical or Cement Plaster: Style B
 - 2. Hard Finish Plaster: Style K or L
 - 3. Masonry or Dry Wall: Style M
- C. Where access is by means of liftout ceiling tiles or panels, mark each ceiling grid using small color-coded and numbered tabs. Provide a chart or index for identification. Place markers within ceiling grid net on ceiling tiles.
- D. Access panels, doors, etc. described herein shall be furnished under the section of specifications providing the particular service and to be turned over to the pertinent trade for installation. Coordinate installation with installing contractor. All access doors shall be painted in baked enamel finish to match ceiling or wall finish.
- E. Submit shop drawings indicating the proposed location of all access panels/doors. Access doors in finished spaces shall be coordinated with air devices, lighting and sprinkler to provide a neat and symmetrical appearance.
- F. Where access doors are installed in wet locations (i.e. shower rooms, toilet rooms, kitchens, dishwasher rooms, can wash rooms, and similar spaces, etc.) provide aluminum access doors/frames.

3.5. PAINTING AND FINISHES

- A. Provide protective finishes on all materials and equipment. Use coated or corrosion-resistant materials, hardware and fittings throughout the work. Paint bare, untreated ferrous surfaces with rust-inhibiting paint. All exterior components including supports, hangers, nuts, bolts, washers, vibration isolators, etc. shall be stainless steel.
- B. Clean surfaces prior to application of insulation, adhesives, coatings, paint, or other finishes.

- C. Provide factory-applied finishes where specified. Unless otherwise indicated factory-applied paints shall be baked enamel with proper pretreatment.
- D. Protect all finishes and restore any finishes damaged as a result of work under Division 21 to their original condition.
- E. The preceding requirements apply to all work, whether exposed or concealed.
- F. Remove all construction marking and writing from exposed equipment, piping and building surfaces. Do not paint manufacturer's labels or tags.
- G. All exposed piping, equipment, etc. shall be painted. Colors shall be as stated in this division or as selected by the Architect and conform to ANSI Standards.
- H. All exposed piping, equipment, etc. in finished spaces shall be painted. Colors shall be as selected by the Architect and conform to ANSI Standards.

3.6. CLEANING OF SYSTEMS

- A. Thoroughly clean systems after satisfactory completion of pressure tests and before permanently connecting equipment, and other accessory items. Blow out and flush piping until interior surfaces are free of foreign matter.
- B. Flush piping to remove cutting oil, excess pipe joint compound, solder slag and other foreign materials. Do not use system pumps until after cleaning and flushing has been accomplished to the satisfaction of the Engineer. Employ chemical cleaners, including a non-foaming detergent, not harmful to system components. After cleaning operation, final flushing and refilling, the residual alkalinity shall not exceed 300 parts per million. Submit a certificate of completion to Engineer stating name of service company used.
- C. Pay for labor and materials required to locate and remove obstructions from systems that are clogged with construction refuse after acceptance. Replace and repair work disturbed during removal of obstructions.
- D. Leave systems clean, and in complete running order.

3.7. COLOR SELECTION

- A. Color of finishes shall be as selected by the Architect.
- B. Submit color of factory-finished equipment for acceptance prior to ordering.

3.8. PROTECTION OF WORK

- A. Protect work, material and equipment from weather and construction operations before and after installation. Properly store and handle all materials and equipment.
- B. Cover temporary openings in piping and equipment to prevent the entrance of water, dirt, debris, or other foreign matter. Deliver pipes and tubes with factory applied end caps.

- C. Cover or otherwise protect all finishes.
- D. Replace damaged materials, devices, finishes and equipment.
- E. Protect stored pipes and tubes from moisture and dirt. Elevate above grade. Do not exceed structural capacity of floor, where stored inside.

3.9. OPERATION OF EQUIPMENT

- A. Clean all systems and equipment prior to initial operation for testing, or other purposes. Lubricate, adjust, and test all equipment in accordance with manufacturer's instructions. Do not operate equipment unless all proper safety devices or controls are operational. Provide all maintenance and service for equipment that is authorized for operation during construction.
- B. Where specified, or otherwise required, provide the services of the manufacturer's factory-trained servicemen or technicians to start up the equipment. Where factory start-up of equipment is not specified, provide field start-up by qualified technician.
- C. Submit factory start-up sheets or field start-up sheets for all equipment.

3.10. IDENTIFICATIONS, FLOW DIAGRAMS, ELECTRICAL DIAGRAMS AND OPERATING INSTRUCTIONS

- A. Contractor shall submit for approval working fire protection drawings of each piping system installed in the building. Diagrams shall indicate the location and the identification number of each valve in the particular system. Following approval by all authorities, the diagrams shall be framed, mounted under safety glass and hung in each Mechanical Room where directed. Contractor shall deliver the tracing or sepia from which the diagrams were reproduced to the Owner.
- B. All valves shall be plainly tagged. For any bypass valves, install sign indicating valve position as "Normally Open" or "Normally Closed" as required.
- C. All items of equipment, including motor starters, fire pump controllers, jockey pump controllers and disconnects shall be furnished with white on black plastic permanent identification cards. Lettering shall be a minimum of ¼ inch high. Identification plates shall be secured, affixed to each piece of equipment, starters, disconnects, panels by screw or adhesive (tuff bond #TB2 or as approved equal). Equipment identification and room name or area served shall be on each label.
- D. Provide six (6) copies of operating and maintenance instructions for all principal items of equipment furnished. This material shall be bound as a volume of the *Operation and Maintenance Booklet* as hereinafter specified.
- E. All piping installed under this contract shall be stenciled with *direction of flow* arrows and with stenciled letters naming each pipe and service. Refer to Division 21 Section, "Fire Protection Piping, Fittings, Valves, Etc". Color code all direction of flow arrows and labels. In finished spaces omit labeling and direction of flow arrows. Paint in color as selected by Architect.

- F. Submit list of wording, symbols, letter size, and color coding for fire protection identification. Submit samples of equipment identification cards, piping labels, and valve tags to Engineer for review prior to installation.
- G. Provide at least four (4) hours of straight time instruction to the operating personnel. Time of instruction shall be designated by the Owner.
- H. Contractor shall demonstrate Sequences of Operation of all fire protection equipment in presence of Owner's representative, and Fire Marshal.

3.11. WALL AND FLOOR PENETRATION

- A. All penetrations of partitions, ceilings, roofs and floors by piping or conduit under Division 21 shall be sleeved, sealed, and caulked airtight for sound and air transfer control.
- B. All penetration of fire rated assemblies shall be sleeved, sealed, caulked and protected to maintain the rating of the wall, roof, or floor. Fire Marshal approved U.L. assemblies shall be utilized. See Division 07 Section, "Fire Protection, HVAC and Plumbing Protection Firestopping".
- C. Where piping extends through exterior walls or below grade, provide waterproof pipe penetration seals, as specified in another division of these specifications.
- D. Provide pipe escutcheons for sleeved pipes in finished areas.
- E. Piping sleeves:
 - 1. Galvanized steel pipe, standard weight where pipes are exposed and roofs and concrete and masonry walls. On exterior walls provide anchor flange welded to perimeter.
 - 2. Twenty-two (22) gauge galvanized steel elsewhere.
- F. Extend all floor sleeves through floor at least 2-inches above finished floor, caulk sleeve through entire depth and furnish and install floor plate.
- G. Sleeves for penetrations in kitchen and hood service areas shall finish .375 inches above floor or flush with wall surfaces and be neatly pointed up to fit snugly against floor or wall material.

3.12. RECORD DRAWINGS

- A. Upon completion of the mechanical installations, the Contractor shall deliver to the Architect one complete set of prints of the fire protection drawings which shall be legibly marked in red pencil to show all changes and departures of the installation as compared with the original design. They shall be suitable for use in preparation of Record Drawings.
- B. Contractor shall incorporate all sketches, addendums, value engineering, change orders, etc., into record drawings prior to delivering to Architect.

3.13. WARRANTY

- A. Contractor's attention is directed to warranty obligations contained in the GENERAL CONDITIONS.
- B. The above shall not in any way void or abrogate equipment manufacturer's guarantee or warranty. Certificates of equipment manufacturer's warranties shall be included in the operations and maintenance manuals.
- C. The contractor guarantees for a two year period from the time of final acceptance by the Owner.
 - 1. That the work contains no faulty or imperfect material or equipment or any imperfect, careless, or unskilled workmanship.
 - 2. That all work, equipment, machines, devices, etc. shall be adequate for the use to which they are intended, and shall operate with ordinary care and attention in a satisfactory and efficient manner.
 - 3. That the contractor will re-execute, correct, repair, or remove and replace with proper work, without cost to the Owner, any work found to be deficient. The contractor shall also make good all damages caused to their work or materials in the process of complying with this section.
 - 4. That the entire work shall be water-tight and leak-proof.

3.14. LUBRICATION

- A. All bearings, motors, and all equipment requiring lubrication shall be provided with accessible fittings for same. Before turning over the equipment to the Owner, the Contractor shall fully lubricate each item of equipment, shall provide one year's supply of lubricant for each and shall provide Owner with complete written lubricating instructions, together with diagram locating the points requiring lubrication. Include this information in the *Operations and Maintenance Booklet*.
- B. In general, all motors and equipment shall be provided with grease lubricated roller or ball bearings with Alemite or equal accessible or extended grease fittings and drain plugs.

3.15. OPERATION AND MAINTENANCE MANUALS

- A. The Contractor shall have prepared six (6) hardcopies and one (1) electronic copy of the Operation and Maintenance Manuals and deliver these copies of the manuals to the Owner. The manuals shall be as specified herein. The manuals must be approved and will not be accepted as final until so stamped.
- B. The manuals shall be bound in a three-ring loose-leaf binder similar to National No. 3881 with the following title lettered on the front: *Operations and Maintenance Manuals – Nellie Stokes Elementary School – Fire Protection*. No sheets larger than 8-1/2 inches x 11 inches shall be used, except sheets that are neatly folded to 8-1/2 inches x 11 inches and used as a pull-out. Provide divider tabs and table of contents for organizing and

separating information.

C. Provide the following data in the booklet:

1. As first entry, an approved letter indicating the starting/ending time of Contractor's warranty period.
2. Maintenance operation and lubrication instructions on each piece of equipment furnished.
3. Manufacturer's extended limited warranties on equipment.
4. Chart form indicating frequency and type of routine maintenance for all fire protection equipment. The chart shall also indicate model number of equipment, location and service.
5. Provide sales and authorized service representatives names, address, and phone numbers of all equipment and subcontractors.
6. Provide supplier and subcontractor's names, address, and phone number.
7. Catalog data of all equipment, valves, etc. shall include wiring diagrams, parts list and assembly drawing.
8. Provide and install in locations as directed by the Owner, valve charts including valve tag number, valve type, valve model number, valve manufacturer, style, service and location. Each valve chart shall be enclosed in a durable polymer based frame with a cover safety glass.
9. Access panel charts with index illustrating the location and purpose of access panels.
10. Approved Fire Protection Certificates.
11. Start-up reports for equipment.

D. Submit *Operations and Maintenance Manuals* prior to anticipated date of substantial completion for Engineer review and approval. Substantial completion requires that *Operations and Maintenance Manuals* be reviewed and approved.

3.16. INSTALLATION AND COORDINATION DRAWINGS

- A. Prepare, submit, and use composite installation and coordination drawings to assure proper coordination and installation of work. Drawings shall include, but not be limited, to the following:
 1. Complete Plumbing, Sprinkler and HVAC Piping Drawings showing coordination with lights, electrical equipment, HVAC equipment and structural amenities.
- B. Draw plans to a scale not less than 3/8-inch equals one foot. Include plans, sections, and elevations of proposed work, showing all equipment, and piping in areas involved. Fully dimension all work including lighting fixtures, conduits, pullboxes, panelboards, and other electrical work, walls, doors, ceilings, columns, beams, joists and other architectural and structural work.
- C. Identify all equipment and devices on wiring diagrams and schematics. Where field connections are shown to factory-wired terminals, include manufacturer's literature showing internal wiring.

3.17. PIPING SYSTEMS TESTING

- A. The entire new fire protection piping systems shall be tested hydrostatically before insulation covering is applied and proven tight under the following gauge pressures for a duration of four (4) hours. Testing to be witnessed by Owner's representative and documented in writing.


SYSTEM	TEST PRESSURE
Fire Protection (Refer to NFPA)	200 psi

- B. Testing and acceptance thereof shall be in accordance with local requirements and shall meet approval of authority having jurisdiction. Submit certificates and approved permits and insert one (1) copy in the *Operations and Maintenance Manuals*.

3.18. PHASING

- A. Refer to Architectural Specifications and contract drawings for any required phasing.
- B. Maintain building egress and traffic ways at all times. Coordinate egress requirements with the State Fire Marshal, the Owner and Authorities having jurisdiction.
- C. Provide dust barriers/partitions, penetration closures, etc. to ensure safety of building occupants and protection of existing surroundings.
- D. The Building shall remain watertight at all times.
- E. Refer to phasing plans for additional requirements.
- F. Provide necessary piping, valves, etc. as required. Drain and refill piping systems as often as necessary to accommodate phasing and to minimize time length of outages. Temporarily feed new systems with existing system where required.
- G. Within thirty days of Award of Contract, the Contractor shall submit a minimum of six (6) copies of the proposed Phasing Plan (Drawings and detailed written description) to the Architect for review and approval based on the general and specific requirements indicated on the Drawings and Specifications. The phasing plan shall reflect the work of all trades. The phasing plan shall be updated as often as needed (i.e. major deviations and/or modified sequence of events) and reviewed during each progress meeting so the facility and Architect can be aware of the areas of construction and progress as it relates to the approved schedule.
- H. Due to phased construction, some systems must be operated until later phases are completed.
- I. While work is in progress, except for designated short intervals during which connections are made, continuity of service shall be maintained to all existing systems. Interruptions shall be coordinated with the Owner as to time and duration. The contractor shall be responsible for any interruptions to service and shall repair any damages to existing systems caused by his operations.

3.19. OUTAGES



- A. Provide a minimum of fourteen (14) days notice to schedule outages. The Contractor shall include in their bid outages and/or work in occupied areas to occur on weekends, holidays, or at night. Coordinate and get approval of all outages with the Owner.
- B. Submit *Outage Request form*, attached at end of this Section, to Owner for approval.

END OF SECTION

NOT FOR BIDDING PURPOSES

OUTAGE REQUEST

DATE APPLIED: _____ BY: _____

DATE FOR OUTAGE: _____ FIRM: _____

START OUTAGE-TIME: _____ DATE: _____

END OUTAGE -- TIME: _____ DATE: _____

AREAS AND ROOMS: _____

FLOOR(S): _____

AREA(S): _____

ROOM(S): _____

WORK TO BE PERFORMED: _____

SYSTEM(S): _____

REQUEST APPROVED BY: _____

(FOREMAN OR OTHER PERSON IN CHARGE)

(FOR OWNER'S USE ONLY):

APPROVED: _____

YES ___ NO ___ BY: _____ DATE: _____

DATE/TIME-AS REQUESTED: _____ OTHER : _____

OWNER'S PRESENCE REQUIRED: _____

YES: ___ NO: ___ NAME: _____

POINT OF CONTACT: _____ PHONE: _____

NOT FOR BIDDING PURPOSES

SECTION 21 05 05

FIRE PROTECTION PIPING, FITTINGS AND VALVES

PART 1. GENERAL

1.1. SUMMARY

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2. SYSTEM DESCRIPTION CONDITIONS

- A. Provide all labor and materials necessary to furnish and install all piping systems on this project as herein specified and/or shown on the drawings.
- B. All piping and insulation installed in ceiling plenums must be plenum rated and comply with NFPA and the authority having jurisdiction.
- C. Where more than one piping system material is specified, ensure system components are compatible and joined to ensure the integrity of the system is not jeopardized. Provide necessary joining fittings. Ensure flanges, union, and couplings for servicing are consistently provided.
- D. Use unions, flanges, and couplings downstream of valves and at equipment or apparatus connections. Do not use direct welded or threaded connections to valves, equipment or other apparatus.
- E. Use non-conducting dielectric connections whenever jointing dissimilar metals in open systems.
- F. Provide pipe hangers and supports in accordance with ASTM B31.9, MSS SP69 and NFPA-13 unless indicated otherwise.
- G. Use 3/4 inch (20 mm) ball valves with cap and chain for drains at main shut-off valves, low points of piping, bases of vertical risers, and at equipment. Pipe to nearest floor drain.

1.3. QUALITY ASSURANCE

- A. Valves: Manufacturer's name and pressure rating marked on valve body.
- B. To assure uniformity and compatibility of piping components in grooved piping systems, all grooved products utilized shall be supplied by a single manufacturer. Grooving tools shall be of the same manufacturer as the grooved components.
- C. If the product is available domestically it shall be supplied as such.

1.4. DELIVERY, STORAGE AND HANDLING

- A. Deliver, store, protect and handle products to site under as hereinbefore specified.
- B. Accept valves on site in shipping containers with labeling in place. Inspect for damage.
- C. Provide temporary protective coating on cast iron and steel valves.
- D. Provide temporary end caps and closures on piping and fittings. Maintain in place until installation.
- E. Protect piping systems from entry of foreign materials by temporary covers, completing sections of the work, and isolating parts of completed systems.

1.5. EXTRA MATERIALS

- A. Provide one (1) repacking kit for each size valve.

1.6. ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

PART 2. PRODUCTS

2.1. PIPE MATERIALS

- A. All materials, unless otherwise specified, shall be new and of the best quality of their respective kinds, and shall conform to the requirements and ordinances of local, state and insurance authorities having jurisdiction.
 - 1. Fire Protection Piping (NFPA-13):
 - a). Piping Above Grade (Inside): Steel, schedule 40, ASTM A53, black pipe. Piping 4 inches and smaller shall be ASTM A120, black steel pipe. Sizes 4-inches and above shall be standard weight, black, cast iron with screwed fittings, schedule 10 steel piping shall be acceptable when approved by the authority having jurisdiction.
 - b). Piping Above Grade (Outside): Galvanized Steel
 - c). Wet Pipe Fittings: Steel fittings shall be ASME B16.9, wrought steel, butt welded. Cast iron fittings shall be ASME 16.1, flanges and flanged fittings. Malleable iron fittings shall be ASME B16.3, threaded fittings. Mechanical grooved couplings shall be malleable iron housing clamps to engage and lock C shaped elastomeric sealing gasket, steel bolts, nuts, and washers; galvanized for galvanized pipe. Mechanical formed fittings shall be carbon steel housing with integral pipe stop and O-ring and O-ring uniformity compressed into permanent mechanical engagement onto pipe.
 - d). Dry Pipe Fittings: UL listed for dry pipe service.

- e). Victaulic, Grinnell, or approved equal, grooved end fittings and mechanical couplings shall be used for wet pipe and dry pipe systems 2" and larger. Couplings and fitting shall be UL listed and FM approved. Fittings shall be ASTM A536 ductile iron, ASTM A234 forged steel or ASTM A53 fabricated steel with factory grooved ends designed to accept Victaulic couplings.
- f). Victaulic, Grinnell, or approved equal mechanical couplings shall consist of two ASTM A536 ductile iron housings, pressure-responsive synthetic rubber gasket and plated steel bolts and nuts.
 - i. Rigid Type: Housings shall be cast with offsetting, angle-pattern bolt pads to provide system rigidity and support and hanging in accordance with NFPA-13. Tongue and recess rigid type couplings shall only be used if the contractor uses a torque wrench for installation. Required torque shall be in accordance with the manufacturer's latest recommendation.
 - 1.) 1-1/4" through 8": "Installation Ready" stab-on rigid coupling, designed for direct 'stab' installation onto grooved end pipe without prior field disassembly and no loose part. Victaulic FireLock EZ Style 009H (1-1/4" – 4") and Victaulic QuickVic Style 107H (2"-8").
 - 2.) 2" and Larger: Standard rigid coupling design. Victaulic Style 07 Zero-Flex.
 - ii. Flexible Type: Use in seismic areas and where required by NFPA-13.
 - 1.) 2" through 8": "Installation Ready" stab-on flexible coupling, designed for direct 'stab' installation onto grooved end pipe without prior field disassembly and no loose parts. Victaulic QuickVic Style 177.
 - 2.) 2" and Larger: Standard flexible coupling design. Victaulic Style 75 or 77.
 - iii.

Fire Protection Service	Temperature Range	Gasket Recommendation
Freezer Applications	-30°F to 0°F (-34°C to 17°C)	Grade L Silicone FlushSeal® Design
Water/Wet Systems	Ambient	Grade EPDM, Type A-C Shaped, FireLock EZ, or QuickVic Design

- g). Gate Valves: 2-1/2 inches & larger - listed 175 lb. OS&Y, flanged. 2 inches & smaller - UL/FM listed 175 lb., bronze, screwed. Furnish all sprinkler control valves with slow close manual operator and position indicator. Tamper switches furnish under Division 21.
- h). Grooved End Gate Valves: 2-1/2inches and Larger – UL listed/FM

approved, 250 psi maximum pressure rating, OS&Y, ductile iron body, bronze mounted, grooved ends. Victaulic FireLock Series 771.

- i). Grooved End Butterfly Valves: 2 inches & Larger: UL listed/FM approved, up to 365 psi maximum pressure rating, ductile iron body, nickel-plated ductile iron disc, Nitrile seat, weather-proof actuator with two pre-wired supervisory switches. Victaulic FireLock Series 765 or Series 705.
 - j). Globe Valves: 2 inches & smaller - 175 lb., bronze, screwed, UL/FM listed.
 - k). Check Valves: 2-1/2 inches & smaller - UL/FM listed 175 lb., flanged swing check. 2 inches & smaller - listed 175 lb., bronze swing check, screwed.
 - l). Grooved End Check Valves: 2 inches and Larger: UL listed/FM approved, up to 365 psi maximum pressure rating, ductile iron body, spring-loaded stainless steel or EPDM coated ductile iron disc, nickel-plated or welded-in nickel seat. Victaulic FireLock Series 717H or Series 717.
 - m). Finish: All exposed fire protection piping shall be primed and painted with epoxy red paint. White letters shall indicate pipe and indicate direction of flow. Painting shall be provided under Division 09.
 - n). Special Requirements: All fire protection piping, valves, fittings and joints shall comply with applicable National Fire Protection Pamphlets (NFPA) local codes, building codes, Fire Marshal, Owner's Insurance Underwriter, and the authority having jurisdiction.
- B. Steel pipe shall be similar and equal to National Allied Tube or Wheatland black or zinc-coated (galvanized) as hereinafter specified. Pipe shall be free from all defects which may affect the durability for the intended use. Each length of pipe shall be stamped with the manufacturer's name.
 - C. Copper pipe shall be Revere, Anaconda or Chase with approved solder fittings.
 - D. Welding fittings for steel pipe shall meet the requirements of ASTM Standard A-23 and shall be standard catalog products. Fittings fabricated by metering and notching pipe will not be accepted.

2.2. PIPE HANGERS

- A. All hangers for metallic piping shall be adjustable, wrought clevis type, or adjustable malleable split ring swivel type, having rods with machine threads. Hangers shall be Grinnell Company's Figure 260 for pipe 3/4-inch and larger, and Figure 65 for pipe 2-inches and smaller, or approved equal. Adjustable pipe stanchion with U-bolt shall be Grinnell Company's Figure 191. Pipe roller supports shall be Grinnell's Figure 181 or Figure 271. Exterior pipe hangers shall be galvanized or stainless steel construction. For copper piping in direct contact with the hanger, hanger construction shall be copper coated to prevent contact of dissimilar metals similar to Grinnell's Figure CT-65. Hanger spacing and rod sizes for steel and copper pipe shall not be less than the following:

NOMINAL PIPE SIZE IN	STD. STEEL PIPE	MAXIMUM SPAN FT. COPPER TUBE	MINIMUM ROD DIAMETER INCHES OF ASTM A36 STEEL THREADED RODS
3/4 & 1	6	5	3/8
1 - 1/2	6	8	3/8
2	8	8	3/8
2 - 1/2	10	9	1/2
3	12	10	1/2
4	14	12	5/8
5	14	12	5/8
6	16	14	3/4
8	18	16	7/8
10	20	18	7/8
12	20	18	7/8

- B. Anchors, guides, and pipe supports shall be installed in accordance with the contract drawings and manufacturer's recommendations to provide pipe support and control pipe movement for all piping systems. Anchors and guides shall be securely attached to the pipe support structure. Submit shop drawing for proposed pipe support structure for guides and anchors for approval of the Structural Engineer. Pipe alignment guides shall be Fig. 255 Grinnell, or as approved equal. Guides shall be sized to accommodate the pipe with insulation. Guides shall be steel factory fabricated, with bolted two section outer cylinder and base for alignment of piping and two section guiding spider for bolting to pipe.
- C. Hangers for pipe sizes 1/2 to 1 1/2 inch (13 to 38 mm): Carbon steel, adjustable swivel, split ring, comply with NFPA-13.
- D. Hangers for pipe sizes 2 to 4 inches (50 to 100 mm): Carbon steel, adjustable, clevis. Comply with NFPA-13.
- E. Hangers for cold pipe sizes 6 inches (150 mm) and over: adjustable steel yoke, cast iron roll, double hanger, comply with NFPA-13.
- F. Multiple or Trapeze hangers: Steel channels with welded spacers and hanger rods.
- G. Wall support for pipe sizes to 3 inches (76 mm): cast iron hook, comply with NFPA-13.
- H. Wall support for pipe sizes 4 inches (100 mm) and over: Welded steel bracket and wrought

steel clamp, comply with NFPA-13.

- I. Wall support for pipe sizes 6 inches (150 mm) and over: welded steel bracket and wrought steel clamp with adjustable steel yoke and cast iron roll, comply with NFPA-13..
- J. Vertical Support: Steel riser clamp, comply with NFPA-13.
- K. Floor support for pipe: Cast iron adjustable pipe saddle, lock nut, nipple, floor flange, and concrete pier or steel support, comply with NFPA-13.
- L. Copper pipe support: Carbon steel ring, adjustable, copper plated, comply with NFPA-13.
- M. Hanger rods: Mild steel threaded both ends, threaded one end, or continuous threaded, comply with NFPA-13.
- N. Inserts: Malleable iron case of galvanized steel shell and expansion plug for threaded connection with lateral adjustment, top slot for reinforcing rods, lugs for attaching to forms; size inserts to suit threaded hanger rods.
- O. Victaulic Style 009H, 107H, and 07, Grinnell, or approved equal, rigid couplings may be used with IPS steel piping systems, which meet the support and hanging requirements of NFPA-13. An adequate number of Victaulic Style 177, 75, and 77, Grinnell, or approved equal, flexible couplings shall also be used to compensate for thermal expansion/contraction of the pipe.

2.3. VALVES

- A. Provide parts list and assembly drawings (exploded view) for all valves in shop drawing submittals. Provide valves of the same type by the same manufacturer. All valves shall be provided with tamper switches and coordinated with Division 28.

2.4. PRESSURE GAUGES

- A. Unless otherwise indicated, pressure gauges shall be the bronze bourdon tube type, 4-1/2-inch dial, stem mounting, cast aluminum adjustable pointer, 1 percent accuracy over middle half of scale range, 1-1/2 percent over balance: Terice Model 600C; Weksler Instruments, Ernst Gage Co., Miljoco, or as approved equal.
- B. Gauges shall have pressure, vacuum, compound, or retard ranges as required, select ranges so that the normal readings are at the approximate midpoint and maximum system pressures do not exceed full scale.
- C. Furnish and install a gauge valve at each pressure gauge. Gauge valves shall be Crane Model No. 88, Needle Valve, Ernst Gage Co. FLG 200, Wexler Instrument Corp. Type BBV4, or approved equal, rated for pressure intended.
- D. Gauge connections for pressure gauges, thermometers, or control instruments shall be made using tee fittings, except that gauge connections up to 1-inch size in steel may be using threaded extra heavy pipe couplings welded directly to the main, provided that the main is at least 2-inch size for 2-inch connections, 3-inch size for 3/4-inch connections, and 4-inch size

for 1-inch connections. Minimum gauge connection shall be 2-inch ips.

- E. Provide snubbers on all gauges. Snubbers shall be No. 872 by Trerice, RS1/RS6 by Wexler Instruments, Miljoco, or as approved equal.

2.5. ESCUTCHEONS

- A. Provide chromium plated escutcheons properly fitted and secured with set screws on all exposed piping which passes through walls, floors or ceilings of finished spaces.
- B. All escutcheon plates shall be chrome plated spun brass of plain pattern, and shall be set tight on the pipe and to the building surface. Plastic escutcheon plates will not be accepted.

2.6. DIELECTRIC CONNECTIONS:

- A. Furnish and install electrically insulated dielectric waterway fittings, unions or flanges, as manufactured by EPCO Sales, Inc., or Victaulic Co. at the following locations:
 - 1. Where steel piping systems join copper piping.
 - 2. Avoid the installation of steel nipples, cast iron or steel valves and specialties, or other ferrous components in predominantly copper piping systems. Where such installation is necessary, isolate the component with dielectric connections. Do not mix steel pipe and copper tube in the same run of pipe or in the same section of a piping system.

2.7. SLEEVES

- A. Sleeves shall be provided around all pipes through walls, floors, ceilings, partitions, roof structure members or other building parts. Sleeves shall be standard weight galvanized iron pipe two sizes larger than the pipe or insulation so that pipe or insulation shall pass through masonry or concrete walls or floors. Provide 20 gauge galvanized steel sheet or galvanized pipe sleeves for all piping passing through frame walls.
- B. Sleeves through floors shall be flush with the floor except for sleeves passing through Equipment Rooms which shall extend 3/4-inch above the floor. Space between the pipe and sleeve shall be caulked. Escutcheon plates shall be constructed to conceal the ends of sleeves. Each trade shall be responsible for drilling existing floors and walls for necessary sleeve holes. Drilling methods and tools shall be as hereinbefore specified.
- C. Sleeves through walls and floors shall be sealed with with a waterproof caulking compound.
- D. Firestop at sleeves that penetrate smoke barriers smoke partitions and/or rated walls/floors.

2.8. WATER PROOF PIPE PENETRATION SEALS

- A. Provide and install waterproof pipe penetration seals at all pipes that enter the building below grade or through exterior wall.
- B. Link seals are to be Metraflex Metraseals, Model MS, Linkseal, or approved equal, black

EPDM seal material, glass reinforced plastic pressure plates, zinc plated nuts and bolts, seals are to be resistant to sunlight and ozone, pressure rated to make a hydrostatic seal of up to 20 psig and up to 40 feet of head, temperature rated from -40 degrees F to 250 degrees F.

PART 3. EXECUTION

3.1. GENERAL PIPING INSTALLATION REQUIREMENTS

- A. All pipes shall be cut accurately to measurements established at the building, and shall be worked into place without springing or forcing, properly clearing all windows, doors and other openings. Excessive cutting or other weakening of the building structure to facilitate piping installation will not be permitted. All pipes shall be so installed as to permit free expansion and contraction without causing damage. All open ends of pipe lines, equipment, etc., shall be properly capped or plugged during installation to keep dirt or other foreign material out of the system. All pipes shall be run parallel with the lines of the building and as close to walls, columns and ceilings as may be practical, with proper pitch. All piping shall be arranged so as not to interfere with removal of other equipment on devices not to block access to doors, windows, manholes, or other access openings. Flanges or unions, as applicable for the type of piping specified, shall be provided in the piping at connections to all items of equipment, and installed so that there will be no interference with the installation of the equipment. All valves and specialties shall be placed to permit easy operation and access and all valves shall be regulated, packed and glands adjusted at the completion of the work before final acceptance. All piping shall be installed so as to avoid air or liquid pockets throughout the work. Ends of pipe shall be reamed so as to remove all burrs.
- B. All piping shall be run to provide a minimum clearance of 2-inches between finished covering on such piping and all adjacent work. Group piping wherever practical at common elevations.
- C. All valves and other fittings shall be readily accessible.
- D. Drain valves with hose connections shall be provided at low points for drainage of piping systems. Blow down valves shall be provided at the ends of all mains and branches so as to properly clean by blowing down the lines throughout in the direction of normal flow.
- E. Spring clamp plates (escutcheons) shall be provided where pipes are exposed in the building and run through walls, floors, or ceilings. Plates shall be chrome plated spun brass of plain pattern, and shall be set tight on the pipe and to the building surface.
- F. Install all valves with stem upright or horizontal, not inverted.
- G. Where pipe support members are welded to structural building framing, scrape, brush clean, weld and apply one coat of zinc rich primer.
- H. Protect piping systems from entry of foreign materials by temporary covers, completing sections of the work, and isolating parts of completed system.
- I. All water containing pipes shall be routed clear of combustion air dampers and louvers to prevent freezing condition when dampers are open.

- J. Where zone valve assemblies are installed in stairwells, install primed and painted 18 gauge removable mesh screen. Color of paint shall be as selected by Architect.

3.2. PRESSURE GAGE INSTALLATION REQUIREMENTS.

- A. Install pressure gages in piping tees with pressure-gage valve located on a pipe at most readable location.
- B. Adjust faces of gages to proper angle for best visibility.
- C. Clean windows of gages and clean factory-finished surfaces. Replace cracked and broken window, and repair scratched and marred surfaces with manufacturer's touch up paint.

3.3. VALVE INSTALLATION REQUIREMENTS

- A. Examine piping system for compliance with requirements for installation tolerances and other conditions affecting performance of valves. Do not proceed with installation until unsatisfactory conditions have been corrected.
- B. Examine valve interior for cleanliness, freedom from foreign matter, and corrosion. Remove special packing materials, such as blocks, used to prevent disc movement during shipping and handling.
- C. Operate valves from fully open to fully closed positions. Examine guides and seats made accessible by such operation.
- D. Examine threads on valve and mating pipe for form and cleanliness.
- E. Examine mating flange faces for conditions that might cause leakage. Check bolting for proper size, length, and material. Check gasket material for proper size, material composition suitable for service, and freedom from defects and damage.
- F. Do not attempt to repair defective valves; replace with new valves.
- G. Install valves as indicated, according to manufacturer's written instructions.
- H. Piping installation requirements are specified in other Division 21 Sections. Drawings indicate the general arrangement of piping, fittings, and specialties.
 - I. Install valves with unions or flanges at each piece of equipment arranged to allow servicing, maintenance, and equipment removal without system shutdown.
- J. Locate valves for easy access and provide separate support where necessary.
- K. Install valves in horizontal piping with stem at or above the center of the pipe.
- L. Install valves in a position to allow full stem movement.
- M. Adjust or replace packing after piping systems have been tested and put into service, but before final adjusting and balancing. Replace valves if leak persists.

3.4. PIPE JOINTS INSTALLATION REQUIREMENTS

- A. Screwed Joints: All screwed joints shall be made with tapered threads properly cut. Screwed joints shall be made perfectly tight with a stiff mixture of graphite and oil, applied with a brush to the male threads on the fittings.
- B. Grooved Joints: Install in accordance with the manufacturer's (Victaulic, Grinnell or approved equal) guidelines and recommendations. All grooved couplings, fittings, valves, and specialties shall be the products of a single manufacturer. Grooving tools shall be of the same manufacturer as the grooved components. The gasket style and elastomeric material (grade) shall be verified as suitable for the intended service as specified. Gaskets shall be molded and produced by Victaulic. Grooved end shall be clean and free from indentations, projections, and roll marks in the area from pipe end to groove for proper gasket sealing. A Victaulic factory-trained field representative shall provide on-site training for contractor's field personnel in the proper use of grooving tools and installation of grooved piping products. Factory-trained representative shall periodically review the product installation. Contractor shall remove and replace any improperly installed products.
- C. Soldered Joints and Copper Piping: Joints in copper piping shall conform to the following minimum standards.
1. The pipes shall be cut to a length making certain that the ends are square, using a fins hacksaw blade or tube cutter. The ends of all pipes shall be reamed and all burrs removed.
 2. The outside end of the pipe and the cut end of the fitting shall be cleaned with steel wool, sand cloth or steel wire brush. All dark spots shall be removed.
 3. The flux shall be applied evenly and sparingly to the outside end of the pipe and the inside of the outer end of the fitting until all surfaces to be jointed are completely covered. The piping and fitting shall be slipped together and reworked several times to insure an even distribution of the flux.
 4. The correct amount of solder per joint for each size pipe shall be used in accordance with the manufacturer's recommendations.
 5. Solder joints shall be made by using a direct flame from a torch.
 6. On pipe sizes larger than ¼-inch, the fittings and valves in the pipe shall be moved or tapped with a hammer when the solder starts to melt to insure an even distribution of the solder.
 7. The excess solder shall be removed while it is still in the plastic state leaving a fillet around the cup of the fitting.
 8. Solder joints shall be suitable for working pressure of 100 psig and for working temperature of not less than 250 degrees F. The type of solder and flux used will be submitted for approval. Type 95-5 shall be the minimum standard.

- D. Where copper piping joins steel piping, approved bronze adapters shall be used.
- E. Prohibited Connections: No direct weld, soldered, or brazed connections, without unions or flanges, shall be made to valves, strainers, apparatus, or related equipment. Right and left couplings, long threads, or caulking of pipe threads or gasket joints will not be permitted.

3.5. HANGERS AND SUPPORTS INSTALLATION REQUIREMENTS

- A. General: All hangers shall be of an approved type arranged to maintain the required grading and pitching of lines to prevent vibration and to provide for expansion and contraction. Saddles shall be Grinnells Figure 173/273 or approved equal. Provide approved spacers between saddles and pipe where flexible insulation is specified. Provide insulation protection shields for insulated piping without saddles. Shield shall be Grinnell Figure 167 or as approved equal. Comply with NFPA-13.
- B. Spacing: Regardless of spacing, hangers shall be provided at or near all changes in direction, both vertical and horizontal, for all piping.
- C. Vertical Lines: Shall be supported at their bases, using either a suitable hanger placed in a horizontal line near the riser, or a base type fitting set on a pedestal, foundation or support. All vertical lines extending through more than one floor level shall be supported at each floor with a riser clamp. Riser clamp shall be Grinnell Co.'s Figure 261, or approved equal. All vertical drops to pump suction elbows shall be supported by floor posts.
- D. Racks and Brackets: All horizontal piping on vertical walls shall be properly supported by suitable racks securely anchored into the wall construction. Where not practical to obtain ceiling anchorage, all piping near walls shall be supported by approved brackets securely anchored into the wall construction. Washer plates (Fib. 60, 60L) and other miscellaneous attachments, fasteners, etc., shall be Grinnell or as approved equal. All exterior hanger and bracket systems in their entirety shall be galvanized.
- E. Pipe Hangers and supports shall be attached to the panel point at the top chord of bar joist or at a location approved by the structural engineer.
- F. Select hangers and components for loads imposed. Secure rods with double nuts.
- G. Support of horizontal piping shall allow for vertical adjustment after installation of piping.
- H. Support overhead piping with clevis hangers.
- I. Do not support all parallel piping from the same joist. Stagger all supports in accordance with the structural engineer's recommendations.
- J. Fabricate and install steel anchors by welding steel shapes, plates, and bars to piping and to structure. Comply with ASME B31.9 and AWS D1.1.
- K. Construct concrete anchors of poured-in-place concrete of dimensions indicated and include embedded fasteners.
- L. Refer to structural documents for appropriate connection/attachment materials to building.

3.6. PIPING IDENTIFICATION INSTALLATION REQUIREMENTS

- A. All piping shall be identified with painted background marked with the name of the service with arrows to indicate flow direction. Color code and system identification shall comply with ANSI Standards and piping identification system shall comply with ASME A13.1-81, scheme for the identification of piping systems and ASHRAE Fundamentals Handbook, latest edition.
- B. Markings shall be plain block letters, stenciled on pipes, and shall be located near each branch connection, near each valve, and at least every 10 feet on straight runs of pipe. Where pipes are adjacent to each other, markings shall be neatly lined up. All markings shall be located in such manner as to be easily legible from the floor. Pipe identification schedule shall be as follows:

OUTSIDE DIAMETER OF PIPE OR COVERING (INCHES)	LENGTH OF COLOR FIELD (INCHES)	SIZE OF LETTERS (INCHES)
½ to 1 ¼	8	½
1-½ to 2	8	¾
2 ½ to 6	12	1 ¼
8 to 10	24	2 ½
Over 10	32	3 ½

3.7. VALVE IDENTIFICATION REQUIREMENTS

- A. All valves shall be tagged with a numbered tag.
- B. The tags shall be made of 1-inch diameter brass tags fastened to the valve by means of brass chains. Numbers shall agree with valve numbers on diagrammatic herein before specified.
- C. Provide a minimum of six (6) valve charts with valve numbers indicating valve type, size, manufacturer and service.
- D. Additional valve charts shall be mounted behind glazed wooden frames and be hung in the main fire protection riser room. Additional copies shall be provided in each copy of the O&M manuals.

END OF SECTION

SECTION 21 10 03

WATER BASED FIRE SUPPRESSION SYSTEM - SPRINKLERS & STANDPIPES

PART 1. GENERAL

1.1. REFERENCE

- A. The conditions of the Contract and General Requirements apply to the work specified in this section. All work under this section shall also be subject to the requirements of Division 21 Section, *Common Work Results for Fire Protection* and Division 01 Section, *General Requirements*.
- B. Submit complete shop drawings of all equipment utilized with the system in accordance with Division 21 Section, *Common Work Results for Fire Protection*. Submittals shall include but not be limited to the following fire protection system and accessories:
- Ball Drip Valves
 - Fire Department Siamese Connection
 - Pressure Sensing Devices, Valves
 - Alarm Check Valves
 - Pressure/Vacuum Gauges
 - Inspector's Test Station
 - Eccentric Reducers
 - Pressure Switches
 - Valves and Piping
 - Backflow Preventers
 - Standpipe Valves
 - Flow Switches
 - Tamper Switches
 - Hose Valve Cabinets
 - Main Drains
 - Auxiliary Drains
 - Blind Flange with Escutcheon
 - Hose valves/Cabinets
- C. Provide sprinklers, piping and associated equipment complete and ready for operation. Equipment materials, installation, workmanship, fabrication, assembly, erection, examination, inspection, and testing shall be in accordance with NFPA-13, NFPA-70, NFPA-14, NFPA-72E, and NFPA-101 . Devices and equipment for fire protection service shall be U.L listed or FM approved.
- D. All of the equipment and devices shall be included within the project Operations and Maintenance Manuals.
- E. Refer to Division 21 Section, *Fire Protection Pipes, Valves, and Fittings* for pipe materials.
- F. Fire Protection Systems design, equipment and installation shall comply with the Delaware State Fire Prevention Regulations, latest edition including all Annexes and Addendums.

1.2. DESCRIPTION

- A. Provide all facilities, labor, materials, tools, equipment, appliances, transportation, supervision, and related work necessary to complete the work specified in this Section and as shown on the drawings. The work shall be performed by a licensed sprinkler contractor only. All equipment, piping, devices, and valves shall be sized based on hydraulic calculations. Include a 10 psig safety factor with hydraulic calculations.
- B. Layout sprinkler system complete and size all fire protection piping in accordance with requirements of the National Fire Protection Association and the State Fire Marshal. System shall be designed for occupancy as required by applicable codes. Conceal fire protection piping in finished spaces unless indicated otherwise. System drains and inspector's test shall not be located in finished spaces.
- C. Sprinkler equipment and work shall conform to requirements of National Fire Protection Association Standard No. 13, No.14, and No. 24. In addition, all work shall conform to requirements of all codes and regulations of authorities having jurisdiction over this work, including, but not limited to, State Fire Marshal, County Fire Marshal, Life Safety Codes and International Code, and Insurance Underwriter.
- D. Preliminary Shop Drawing: Prior to preparing detailed working drawings for submission to State Fire Marshal, submit preliminary sprinkler system layout to the Architect for review and approval. Show all finished ceilings, light fixtures, air diffusers and other ceiling mounted devices. Coordinate sprinkler head types and locations with ceiling types. All sprinkler heads in acoustic tile ceilings shall be centered in the tile.
- E. The fire protection contractor shall prepare dimensioned and detailed working drawings, specifications, and hydraulic calculations and submit same to the State Fire Marshal and/or County Fire Marshal for review and approval. Prior to submission to the Fire Marshal, the Fire Protection Contractor shall have all fire protection drawings, submittals, calculations reviewed and approved by a registered Fire Protection Engineer or a level III Nicet Technician. One set of these approved documents shall be provided to the Engineer for record purposes. All costs related to changes required to obtain the Fire Marshal's or Insurance Underwriters' approval shall be the responsibility of the contractor.
- F. Manufactured equipment and materials shall be submitted to the Engineer for review and approval, in accordance with the requirements of Division 21 Section, *Common Work Results for Fire Protection*.
- G. Hydraulic calculations should be based on an available water supply as follows:

Static Pressure =	51 psig
Residual Pressure =	34 psig
Flow =	750 gpm
Existing Pipe Material	For Hydraulic Calculations Assume Roughness Coefficient C factor = 100 for all Exterior Piping.

- H. Hydraulic calculations shall include a 10 psig safety factor to account for pipe aging and deterioration of water supply.
- I. For small areas subject to freezing (loading dock, exterior canopy, etc.), Contractor shall provide and install freeze proof heads, piping, control valves, tamper switches, test stations, (backflow preventers, expansion chambers, fill cup, drain valve) etc., as required by NFPA-13 and the authority having jurisdiction. Glycol loops shall be acceptable at contractor's option subject to the approval of the Authority having jurisdiction.
- J. All stage/platforms shall be fully sprinklered/protected per the requirements of N.F.P.A.-13, N.F.P.A.-101, and the International Building Code. Provide and install Hose Valves on both sides of stages/platforms in addition to sprinkler protection. Hose connections shall be 1 ½ inch with sufficient 1 ½ inch hose to provide fire protection for the stage/platform area. The hose connections shall be equipped with approved adjustable fog nozzles and be mounted in a cabinet.
- K. Where combustible construction materials are located above ceilings, provide above ceiling fire protection in accordance with N.F.P.A.-13.

1.3. DELIVERY, STORAGE AND PROTECTION

- A. Refer to Division 01 Section, *General Requirements*: Transport, handle, store, and protect products.
- B. Accept equipment and devices on site in factory packing. Inspect for damage. Comply with manufacturer's rigging and installation instructions for all equipment.
- C. Protect components from physical damage including effects of weather, water, and construction debris.
- D. Provide temporary inlet and outlet caps, and maintain in place until installation.

1.4. EXTRA MATERIALS

- A. Provide extra sprinklers under provisions of NFPA-13. Provide suitable wrenches for each sprinkler type and metal storage cabinet.

1.5. PERMITS FROM THE AUTHORITY HAVING JURISDICTION AND FEES

- A. Pay all permits, fees, and charges required for this work.

1.6. HYDRANT FLOW TESTS

- A. The Fire Protection Contractor shall perform a hydrant flow test.
- B. The hydrant flow test shall be performed by the Fire Protection Contractor in the vicinity of each building at no additional cost to the Owner.
- C. Where practical, tests shall be performed between 9:00 a.m. and 5:00 p.m. on a normal working day during summer. If conducting the test is impractical during these hours,

then a local Fire Department representative shall be present to "observe" the test during "off peak" hours and to acknowledge the correctness of results.

- D. The tests shall be submitted for review prior to submitting any hydraulic calculations. The test data shall contain the following:

1. Date of the test
2. Who performed the test and who was present.
3. Site plan indicating locations and diameters of water mains and locations of the hydrants tests.
4. Grade elevation of the hydrant tests
5. Static pressure in psig
6. Flow in GPM
7. Residual pressure in psig
8. Hydrant butt size in inches
9. Hydrant coefficient

1.7. ALTERNATES

- A. Refer to Division 01 Section, *Alternates* - Alternates for description of work under this section affected by alternates.

PART 2. PRODUCTS

2.1. SPECIALTIES

- A. All sprinkler heads shall be U.L. listed and shall be of the same manufacturer throughout the building.
- B. Piping shall be in accordance with Division 21 Section, *Fire Protection Piping, Fittings, and Valves, etc.* All exposed fire protection piping in unfinished areas shall be painted with red epoxy paint. White letters shall identify piping and indicate direction of flow. Exposed fire protection piping within finished areas shall be painted in color as determined by the Architect/Engineer.
- C. Shut-off valves shall be UL approved O.S. and Y. double disc gate valves or UL/FM approved grooved end butterfly valves.
- D. Check valves shall be swing check type or spring-loaded type UL approved for the application.
- E. Fire department connection shall be Potter-Roemer 5750 Series, or approved equal, with individual drop clapper valves, plugs, and chains on each connection. Exposed parts shall be polished chrome plated. Threads shall match local Fire Department specifications. Where required by local Fire Department, provide Storz type Fire department connection. Escutcheon shall be lettered "AUTO SPRINKLER", "AUTO SPRINKLER - STANDPIPE", as required. Locate as shown on drawings and connect to main fire line through check valve with ball drip. Discharge ball drip drain line as indicated on contract drawings.
- F. Coordinate the fire protection systems with the fire alarm system specified under

Division 26. Provide alarm initiating devices with proper contact arrangement. All electrical wiring shall be furnished and installed under Division 26.

- G. Flow control valve, alarm switches and valve supervision shall be furnished and installed under this Division. All wiring shall be accomplished by the electrical contractor, under Division 26. Provide any additional flow control valves, alarm switches, tamper switches and flow switches required by NFPA-13 but not indicated on contract drawings. Coordinate with the alarm system and electrical subcontractor.
- H. Pipe and fittings shall meet the requirements of NFPA 13 and NFPA-24.
- I. Wet pipe alarm check valve shall be Victaulic FireLock Series 750, or approved equal. Valve shall be UL listed and FM approved for sprinkler systems with 175 psig maximum working pressure. Provide complete valve trim package including all necessary valves, gauges, fittings, nipples and alarm test. Valve internal components shall be replaceable without removing the valve from the installed position. Valve shall be installed in the vertical position only.
- J. Retard Chamber shall be Victaulic Series 752. Retard Chamber shall be UL listed and FM approved. Chamber shall prevent false alarms with ordinary city water pressure surges.
- K. Water motor alarm shall be Victaulic Series 710. Alarm shall be UL listed and FM approved. Alarm shall be hydraulically driven and tested 100 percent at low flow, 5 psig. Gong assembly and motor housing shall be finished with corrosion resistant, red enamel. Furnish unit with nylon bearings and inlet strainer. At contractor's option install electric gong. Provide power and control wiring under this Division of specifications.
- L. Stage/platform standpipe angle valves shall be Potter-Roemer 2500 series 1 ½ inch angle valve, brass body, brass mounting, inside screw rising stem, red handle, cap and chain. Provide unit with 30' hose length, 1 ½ inch valve size, and 1 ½ inch diameter polyflex hose. Provide each unit with fog nozzle as required. Valve cabinet shall be Potter-Roemer series fully recessed fire hose cabinet, 20 gauge white glossy polyester coated steel box, 20 gauge tubular steel door with 18 gauge frame. Door and frame finished with white prime polyester coating. Provide with break glass steel door, cam catch, identify decal, recessed or surface mounted unit as indicated.

2.2. SPRINKLER HEADS

- A. Suspended or Drywall Ceilings:
 - 1. Manufacturer: Victaulic, Viking, Grinnell, Reliable, or approved equal.
 - 2. All sprinkler heads installed in suspended ceilings and drywall ceilings including bulkheads shall be Victaulic Model V38 concealed quick response sprinkler or approved equal. Cover plate shall be finished with a polyester baked enamel finish. Color selection by Architect. Provide cover assembly with each head. Frangible glass bulb shall be temperature rated for specific area hazard.
 - 3. Sprinkler heads in all other areas with finished ceilings shall be Victaulic Model

V27 or approved equal. These sprinklers shall be standard pendant type with matching screw on escutcheon plate. Sprinkler and escutcheon plate finish shall be chrome plated. Fusible link shall be temperature rated for specific area hazard.

B. Exposed Area Type:

1. Manufacturers: Victaulic, Viking, Grinnell, Reliable, or approved equal.
2. Sprinkler heads in unfinished or exposed areas shall be Victaulic Model V27 or approved equal. These sprinklers shall be standard, ½ inch upright, pendant or conventional where required. Provide guards where hereinafter indicated. Sprinklers shall be brass with frangible glass bulb temperature rated for specific area hazard. Provide standard brass, screw on flat escutcheon plate.

C. Sidewall type:

1. Manufacturers: Victaulic, Viking, Grinnell, Reliable, or approved equal.
2. Sidewall sprinklers shall be Victaulic Model V27 semi-recessed horizontal sidewall type with matching screw on escutcheon plate. Sprinkler and escutcheon plate finish shall be chrome plated. Frangible glass bulb shall be temperature rated for specific area hazard.

D. Dry Sprinklers:

1. Manufacturers: Victaulic, Viking, Grinnell, Reliable, or approved equal.
2. Sprinkler heads for areas subject to freezing (walk-in boxes), and similar spaces shall be Victaulic Model V36 dry sprinkler or approved equal. Dry sprinkler shall be standard or expose pendant type with matching escutcheon plate. Sprinkler and escutcheon plate shall be chrome plated. Frangible glass bulb shall be temperature rated for specific area hazard. Length of heads shall be as required to suit field conditions. Provide adjustable surface mounted escutcheon plate with each head. Provide flush ceiling plate. For small systems, per NFPA-13, glycol loops shall be acceptable at Contractor's option, subject to the approval of the authority having jurisdiction.

E. Attic Sprinklers:

1. Manufacturers: Victaulic, Viking, Grinnell, Reliable.
2. Sprinkler heads for attic areas shall be Central Attic type or approved equal wet or dry sprinkler specifically listed for attic applications. Model and deflection type shall be as required to accommodate dual directional, single directional, back to back, and hip applications. Sprinklers and escutcheon shall be Natural Brass finish. Fusible links shall be temperature rated for specific application. Fast response glass bulb or fusible link shall be furnished.

F. Quick Response Type:

1. Manufacturers: Victaulic, Viking, Grinnell, Reliable or approved equal.
 2. Sprinkler heads shall be listed quick response sprinklers in accordance with NFPA-13 and NFPA-101. Quick response sprinklers shall be Victaulic Model V27 or approved equal. Model and deflector style shall be as required to accommodate upright, pendant, sidewall or recessed mounting. Sprinklers and escutcheon plates shall be chrome plated. Frangible glass bulb shall be temperature rated for specific area hazard.
- G. The temperature rating of the sprinklers shall be as required by N.F.P.A.-13 and of the authority having jurisdiction.
- H. All sprinkler heads installed in lay-in ceiling tiles shall be located in the center of the tile to provide a symmetrical, aesthetic and neat appearance. All sprinkler heads installed in bulkheads, recesses, and soffits shall be centered to provide a symmetrical, aesthetic and neat appearance.
- I. Provide extended escutcheons in rooms with surface mounted lighting fixtures.
- J. Additional heads shall be furnished as required by NFPA-13. The heads shall be in a cabinet designed to hold the heads and include one sprinkler head wrench for each type of sprinkler. Cabinet shall be mounted where indicated in the field.
- K. Head guards shall be provided in mechanical spaces, penthouses, janitors' closets, electrical rooms, storage areas, gymnasiums, and auxiliary gymnasiums. Finish for head guards in finished spaces shall be selected by Architect.
- L. Sprinkler escutcheons and guards shall be listed, supplied, and approved for use with the sprinkler, by the sprinkler manufacturer.
- M. Provide high temperature sprinkler heads for use adjacent to skylights, heaters, lights, or other high temperature areas.

2.3. FLEXIBLE SPRINKLER DROPS

A. Stainless Steel Sprinkler Fittings

1. Manufacturer: Victaulic AquaFlex®
2. In lieu of rigid pipe offsets for concealed locations only, or return bends for sprinkler drops, the Victaulic AquaFlex® stainless steel, multiple-use, sprinkler fitting system may be used to locate sprinklers as required by final finished ceiling tiles and walls. The drop system shall consist of a braided or unbraided (corrugated) type 304 stainless steel flexible tube, a zinc-plated steel 1" NPT male threaded nipple for connection to branch-line piping, and a zinc-plated steel reducer with 1/2" or 3/4" NPT female thread for connection to the sprinkler head. Union joints shall be provided for ease of installation. The flexible drop shall attach to the ceiling grid using a one-piece open gate bracket. The braided drop system is FM approved for sprinkler services to 200 psi and can be installed without the use of tools, and the unbraided system is UL listed for sprinkler services to 175 psi.

2.4. SIGNS

- A. Provide 9 inch x 7 inch signs suspended from control valves which indicate the purpose of the valve and its normal position, Central Type A or approved equal.
- B. All control, drain, and test connection valves shall be provided with signs indicating purpose.
- C. Signs shall be fabricated of an approved material, painted red with white lettering.
- D. Signs shall have typed labels. Handwritten labels shall not be acceptable.

2.5. DRAINS

- A. The sprinkler systems shall be arranged to be completely drainable. Means of drainage shall be provided with adequate protection from freezing.
- B. Drain valve may be combined with sprinkler alarm test valve and sight glass, G/J Innovations Sure-Test or approved equal. Valve shall be UL listed with positive off handle for off, test or drain, integral sight glass, orifice size equal to smallest sprinkler orifice and full 1 inch drain.

2.6. ALARM DEVICES

- A. Approved water flow switches shall be installed to activate the fire alarm, and annunciate sprinkler flow at a minimum on each floor, each system riser, where indicated on the contract documents and where required by N.F.P.A. or the authority having jurisdiction. Conductors shall be provided under the electric division to provide fire alarm, and annunciation. Activation of the sprinkler system by one sprinkler or equivalent test shall cause the fire alarm system to activate, and the appropriate lamp(s) to activate on the annunciator. An approved test shall be provided for each water flow switch.
- B. All valves controlling water supply for sprinklers shall be electrically supervised in accordance with requirements of NFPA 13 and 72A, and provided under this Division. Provide separate valve chart for all fire protection valve indicating valve type, normal position, size, location and type of supervision insert in O&M manual and mount additional copies in fire pump room and mechanical rooms.
- C. Valve tamper switches shall be Model OSY2 as manufactured by System Sensor or Model OSYSU-A2 as manufactured by Potter Electric Signal Company or approved equal. The valve tamper switches shall monitor the open position of all OS&Y gate valves. Each tamper switches shall contain two sets of single pole double throw, Form C contacts. All valve tamper switches shall have tamper resistant covers that upon removal of the cover will cause the switches to operate. Tamper switches shall be suitable for 125/250 VAC @ 15 AMPS. All tamper switches shall be U.L. listed and F.M. approved.
- D. Pressure type flow switches shall be Model EPS10 as manufactured by System Sensor or Model PS10-2 as manufactured by Potter Electric Signal Company or approved equal. Each pressure type flow switch shall contain two sets of single pole double throw switch contacts. All pressure type flow switches shall have tamper resistant covers that upon

removal of the cover will cause the switches to operate. Pressure type flow switches shall be suitable for 125/250 VAC @ 10 AMPS. All pressure type flow switches shall be U.L. listed and F.M. approved.

- E. Vane Type waterflow switch with retard shall be WFD Series as manufactured by System Sensor or Model VSR-F as manufactured by Potter Electric Signal Company or approved equal. The VAC type waterflow switches shall contain two single pole, double throw form C, snap return switches. All Vane type waterflow switches shall have tamper resistant covers that upon removal of the cover will cause the switches to operate. Vane type waterflow switches shall be suitable for 125/250 VAC @ 10 AMPS. All vane type waterflow switches shall be U.L. listed and F.M. approved.

2.7. GAUGES

- A. A listed 3 ½ inch dial spring pressure gauge shall be connected to the top of each standpipe. Gauges shall be located in a suitable place to prevent freezing. Each gauge shall be controlled by a valve having arrangement for draining.
- B. Listed pressure gauges with connections not smaller than ¼ inch shall be installed at the system main drain, at each main drain associated with a floor control valve, and above and below each alarm check-valve.
- C. All pressure gauges shall be listed and shall have a maximum limit not less than twice the normal working pressure at the point where installed. They shall be installed to permit removal and shall be located where they will not be subject to freezing.

2.8. DOUBLE DETECTOR CHECK VALVE BACKFLOW PREVENTER (FIRE PROTECTION SYSTEM)

- A. The sprinkler system backflow preventer shall be provided under this Division and coordinated with Plumbing Contractor. Backflow preventer shall be sized for sprinkler demand to limit pressure drop to 5 psig.
- B. Backflow preventers for Fire Protection Systems shall be ASSE/AWWA-1015 approved, double detector check-valve backflow preventer assemblies at sprinkler system water service connections. Units shall be specifically listed for Fire Protection use. Units shall be double detector check valve as manufactured by Watts 709 DCDA, Ames, Conbraco, Wilkens, or approved equal with OS&Y Gate valves, U.L. listed, F.M. approved, NSF-61 approved. Units shall be suitable for minimum 175 psi working pressure. Backflow preventers shall be factory tested at two (2) times the working pressure encountered or as required by N.F.P.A. Backflow preventer shall be capable of withstanding test pressures per N.F.P.A.
- C. Backflow preventer shall be factory finished with epoxy coated paint or shall be 304 stainless steel.
- D. Pipe any discharge openings full size, through air gap fittings, to nearest floor drain. Maintain clearances for servicing as required by Plumbing Code and authority having jurisdiction. Discharge piping shall be Type L copper pipe.
- E. Provide and install tamper switches on all backflow preventers OS&Y gate valves or

butterfly valves. Backflow preventer shall be installed between 12 inches and 60 inches above finished floor. Provide 18 inch clearance around backflow preventer for service and maintenance.

- F. Unit shall include auxiliary piping with approval backflow preventer and water meter. Meter shall indicate flow in gallons per minute.

2.9. AUTOMATIC BALL DRIP VALVES

- A. Provide and install automatic ball drip valves at the Fire Department connection. Discharge ball drip valves to closest floor drain or building exterior as required with suitable air gap. Automatic ball drip valves shall be ITT-AC Pump or approved equal.

2.10. VALVES

- A. Provide and install control valves as indicated on contract drawings and as required by N.F.P.A.-13. Gate valves shall be listed O.S. & Y. type. All control valves shall be supervised open. Supervision shall be as required by N.F.P.A.-13. Victaulic Series 705 and 765 grooved end butterfly valves shall be supervised in the open position and Victaulic Series 707 and 766 shall be supervised closed, for fire pump metering test lines for NFPA-20 and rooftop test units, as well as pressure reducing valve by-pass lines per NFPA-14.

2.11. BLIND FLANGE FOR FORWARD FLOW TESTING OF BACKFLOW PREVENTER

- A. A blind flange with normally closed control valve shall be provided for use in forward flow testing of backflow preventer. Blind flange shall be sized to flow entire system demand in accordance with NFPA-13 and NFPA-25, latest edition. Control valve shall be monitored with tamper switch.
- B. Identify and label blind flange "Backflow Preventer Test Connection" to differentiate fitting on exterior wall from Fire Department connection.
- C. Install ball drip in test pipe to allow drainage and prevent freezing.

PART 3. EXECUTION

3.1. GENERAL INSTALLATION REQUIREMENTS

- A. Install equipment in accordance with manufacturer's instructions.
- B. Where required, install buried shut-off valves in valve box. Provide post indicator.
- C. Provide approved double check valve assembly at sprinkler system water source connection.
- D. Locate fire department connection with sufficient clearance from walls, obstructions, or adjacent Siamese connectors to allow full swing of fire department wrench handle.
- E. Locate outside alarm gong on building wall.

- F. Place pipe runs to minimize obstruction to other work.
- G. Place piping in concealed spaces above finished ceilings.
- H. Center sprinklers in two directions in ceiling tile and provided piping offsets as required.
- I. Apply masking tape or paper cover to ensure concealed sprinklers, cover plates, and sprinkler escutcheons do not receive field paint finish. Remove after painting. Replace painted sprinklers.
- J. Flush entire piping system of foreign matter.
- K. Install guards on sprinklers where subject to abuse and where specified.
- L. Hydrostatically test entire system.
- M. Test must be witnessed by Fire Marshal/authority having jurisdiction/ Owner's insurance underwriter/ Architect/Engineer.
- N. Refer to plumbing floor plans for approximate locations of sprinkler zones control valve assemblies and routing of fire protection mains.
- O. Locate inspectors test stations for sprinkler zones per NFPA-13. Provide and install drain piping from all approved terminations. Provide splash blocks for terminations outside. Splash block locations shall be approved by the Architects.
- P. The fire protection contractor shall hydraulically prove the most remote area per NFPA-13.
- Q. Coordinate locations of sprinkler heads with lights, diffusers, ceiling types, etc.
- R. Hydrostatically test system at 200 PSI for 4 hours, per NFPA-13.
- S. Provide and install class III standpipe hose valves on each side of stage/platform per NFPA-13, NFPA-101, NFPA-14 and the BOCA Building Code provide indicating control valve for each hose valve.
- T. Provide dry pipe sprinklers at all walk-in freezers, etc., as required by NFPA-13.
- U. The sprinkler bulb protector must remain in place until the sprinkler is completely installed and before the system is placed in service. Remove bulb protectors carefully by hand after installation. Do not use any tools to remove bulb protectors.
- V. Refer to Architectural Drawings for exact location and extent of all fire rated walls and smoke barriers.
- W. Grooved joint piping systems shall be installed in accordance with the manufacturer's (Victaulic) guidelines and recommendations. All grooved couplings, fittings, valves, and specialties shall be the products of a single manufacturer. Grooving tools shall be of the same manufacturer as the grooved components. The gasket style and elastomeric material (grade) shall be verified as suitable for the intended service as specified.

Gaskets shall be molded and produced by Victaulic. Grooved end shall be clean and free from indentations, projections, and roll marks in the area from pipe end to groove for proper gasket sealing.

3.2. INTERFACE WITH OTHER PRODUCTS

- A. Ensure required devices are installed and connected as required to fire alarm system.

3.3. LAYOUT

- A. Coordinate layout and installation of fire protection system with all other buildings structural, mechanical and electrical work. Locate sprinkler heads symmetrically with respect to ceiling tiles, lighting fixtures, registers, grilles, diffusers, etc. Provide piping offsets as required to maintain symmetry. Note that a preliminary sprinkler layout is to be submitted for review. Contractor is cautioned that sprinkler heads must be located to prevent conflict with other work and in any case, sprinkler contractor shall be responsible for coordination of his work with work of other trades.
- B. Unless otherwise indicated, the entire building shall be protected throughout with a wet pipe sprinkler system.

3.4. WET PIPE SPRINKLER SYSTEM

- A. System components shall include, but not be limited to flow control valves, electrical connections to central fire alarm system, Siamese fire department connection, check valves, main piping, branch piping, inspector's test, drains, sprinkler heads, hose valves and cabinet, ball drip valves, signs, standpipes, etc. and all other incidental appurtenances as required.

3.5. VALVE INSTALLATION

- A. Gate Valves: Install fire-protection-service valves supervised-open, located to control sources of water supply except from fire department connections. Provide permanent identification signs indicating portion of system controlled by each valve.
- B. Install check valve in each water-supply connection. Install backflow preventers instead of check valves in potable-water supply sources.
- C. Alarm Check Valves: Install valves in vertical position for proper direction of flow, including bypass check valve and retard chamber drain-line connection.

3.6. CONNECTIONS

- A. Connect water supplies to standpipes and sprinklers. Include backflow preventers.
- B. Install ball drip valves at each check valve for fire department connection. Drain to floor drain or outside building.
- C. Connect piping to specialty valves, specialties, fire department connections, and accessories.

- D. Connect alarm devices to fire alarm.

3.7. COMMISSIONING

- A. Verify that specialty valves, trim, fittings, controls, and accessories are installed and operate correctly.
- B. Verify that specified tests of piping are complete.
- C. Verify that damaged sprinklers and sprinklers with paint or coating not specified are replaced with new, correct type.
- D. Verify that sprinklers are correct types, have correct finishes and temperature ratings, and have guards as required for each application.
- E. Verify that potable-water supplies have correct types of backflow preventers.
- F. Verify that fire department connections have threads compatible with local fire department equipment
- G. Fill wet-pipe sprinkler piping with water.
- H. Energize circuits to electrical equipment and devices.
- I. Adjust operating controls and pressure settings.
- J. Coordinate with fire alarm tests. Operate as required.

3.8. DRAINS

- A. The sprinkler system shall be arranged to be completely drainable. Means of drainage shall be provided with adequate protection from freezing.

3.9. TESTS

- A. The sprinkler systems installation shall be hydrostatically tested, inspected, and approved in accordance with NFPA Standard No. 13, NFPA Standard No. 14, and NFPA Standard No. 25. Test certificate shall be forwarded to the Office of the State Fire Marshal and the Architect as proof of compliance.
- B. Tests shall be performed in accordance with the requirements of the Office of the State Fire Marshal and shall prove the systems to be adequate and satisfactory in every respect. All tests shall be performed in the presence of the State Fire Marshal or his representative.
- C. Any deficiencies revealed by these tests shall be corrected and the systems shall be retested until acceptable results are obtained.

3.10. AS-BUILT DRAWINGS & PROJECT CLOSEOUT

- A. Provide separate as-built drawings of all fire protection systems meeting requirements of General Mechanical Requirements hereinbefore specified.

- B. At the completion of the work, provide a sealed plan of the building indicating the locations of all control valves, low point drains, flow switches, and Inspectors Test Stations. The plan shall be neatly drawn and color coded to indicate the portion of the building protected by each system, framed under glass and permanently mounted on the wall adjacent to the system header.
- C. Include manufacturers literature, cleaning procedures, replacement parts, lists, and repair data for equipment.
- D. Include manufacturers' instructions, start-up data, troubleshooting, checklists for all equipment.

3.11. WARRANTY

- A. The Contractor's attention is directed to the warranty obligations contained in the Article of the General Conditions of the specifications entitled "warranty".

3.12. OWNER TRAINING

- A. Upon completion of the project, furnish a complete copy of NFPA-25 to Owner. Provide correspondence indicating that the pamphlet has been turned over to the Owner.
 - 1. Contractor shall provide at least four (4) hours of training to the Owner on the proper inspection, testing, and maintenance of the installed fire protection system.
 - 2. Schedule training with the Owner through the Architect and/or Engineer with at least seven (7) days prior notice.
 - 3. A Victaulic factory-trained field representative shall provide on-site training for contractor's field personnel in the proper use of grooving tools and installation of grooved piping products. Factory-trained representative shall periodically review the product installation. Contractor shall remove and replace any improperly installed products.

END OF SECTION

SECTION 22 05 00

COMMON WORK RESULTS FOR PLUMBING

PART 1 GENERAL

1.1 SUMMARY

- A. All work under Division 22 is subject to the Division 01, *General Requirements, the General Conditions and Supplementary Conditions*.
- B. Provide all labor, materials, equipment, and services necessary for and incidental to the complete installation and operation of all plumbing work.
- C. Unless otherwise specified, all submissions shall be made to, and acceptances and approvals made by the Architect and the Engineer.
- D. Contract Drawings are generally diagrammatic and all offsets, fittings, transitions and accessories are not necessarily shown. Furnish and install all such items as may be required to fit the work to the conditions encountered. Arrange piping, equipment, and other work generally as shown on the contract drawings, providing proper clearance and access. Where departures are proposed because of field conditions or other causes, prepare and submit detailed shop drawings for approval in accordance with *Submittals* specified below. The right is reserved to make reasonable changes in location of equipment, piping, up to the time of rough-in or fabrication.
- E. Conform to the requirements of all rules, regulations and codes of local, state and federal authorities having jurisdiction.
- F. Coordinate the work under Division 22 with the work of all other construction trades.
- G. Be responsible for all construction means, methods, techniques, procedures, and phasing sequences used in the work. Furnish all tools, equipment and materials necessary to properly perform the work in first class, substantial, and workmanlike manner, in accordance with the full intent and meaning of the contract documents.

1.2 PERMITS AND FEES

- A. Obtain all permits and pay taxes, fees and other costs in connection with the work. File necessary plans, prepare documents, give proper notices and obtain necessary approvals. Deliver inspection and approval certificates to Owner prior to final acceptance of the work.
- B. Permits and fees shall comply with the Division 01, *General Requirements* of the specification.

1.3 EXAMINATION OF SITE

- A. Examine the site, determine all conditions and circumstances under which the work must be done, and make all necessary allowances for same. No additional cost to the Owner will be permitted for contractors failure to do so.

- B. Examine and verify specific conditions described in individual specifications sections.
- C. Verify that utility services are available, of the correct characteristics, and in the correct locations.

1.4 CONTRACTOR QUALIFICATION

- A. Any Contractor or Subcontractor performing work under Division 22 shall be fully qualified and acceptable to the Architect and Owner. Submit the following evidence when requested:
 - 1. A list of not less than five comparable projects which the Contractor completed.
 - 2. Letter of reference from not less than three registered professional engineers, general contractors or building owners.
 - 3. Local and/or State License, where required.
 - 4. Membership in trade or professional organizations where required.
- B. A Contractor is any individual, partnership, or corporation, performing work by contract or subcontract on this project.
- C. Acceptance of a Contractor or Subcontractor will not relieve the Contractor or subcontractor of any contractual requirements or his responsibility to supervise and coordinate the work, of various trades.

1.5 MATERIALS AND EQUIPMENT

- A. Materials and equipment installed as a permanent part of the project shall be new, unless otherwise indicated or specified, and of the specified type and quality. Existing items of equipment are being relocated under another Division of these specifications. The Contractor shall be responsible for connecting all utilities as shown on the drawings, to equipment identified as existing.
- B. Where material or equipment is identified by proprietary name, model number and/or manufacturer, furnish named item, or its equal, subject to approval by Engineer. Substituted items shall be equal or better in quality and performance and must be suitable for available space, required arrangement, and application. Submit all data necessary to determine suitability of substituted items, for approval.
- C. The suitability of named item only has been verified. Where more than one item is named, only the first named item has been verified as suitable. Substituted items, including items other than first named shall be equal or better in quality and performance to that of specified items, and must be suitable for available space, required arrangement and application. Contractor, by providing other than the first named manufacturer, assumes responsibility for all necessary adjustments and modifications necessary for a satisfactory installation. Adjustments and modifications shall include but not be limited to electrical, structural, support, and architectural work.

- D. Substitution will not be permitted for specified items of material or equipment where noted.
- E. All items of equipment furnished shall have a service record of at least five (5) years.

1.6 FIRE SAFE MATERIALS

- A. Unless otherwise indicated, materials and equipment shall conform to UL, NFPA and ASTM standards for fire safety with smoke and fire hazard rating not exceeding flame spread of 25 and smoke developed of 50.

1.7 REFERENCED STANDARDS, CODES AND SPECIFICATIONS

- A. Specifications, Codes and Standards listed below are included as part of this specification, latest edition.
- B. ASHRAE - American Society of Heating, Refrigerating and Air Conditioning Engineers
- C. ASME - American Society of Mechanical Engineers
- D. ASPE - American Society of Plumbing Engineers
- E. ASTM - American Society for Testing and Materials
- F. AWWA - American Water Works Association
- G. ASME CSD-1 - American Society of Mechanical Engineers Controls and Safety Devices for Automatically Fired Boilers
- H. CS - Commercial Standard
- I. CSD - Control and Safety Devices
- J. DNREC - Delaware Department of Natural Resources and Environmental Control
- K. EPA - Environmental Protection Agency
- L. FDA - Food and Drug Administration
- M. FM - Factory Mutual
- N. IBC - International Building Code
- O. IEEE - Institute of Electrical and Electronics Engineers
- P. MSSP - Manufacturers Standards Society of the Valve and Fittings Industry
- Q. NEC - National Electrical Code
- R. NEMA - National Electrical Manufacturers Association
- S. NSF - National Sanitation Foundation
- T. TEMA - Tubular Exchanger Manufacturers Association
- U. UL - Underwriters' Laboratories

All plumbing equipment and materials shall comply with the codes and standards listed in the latest edition of ASHRAE HVAC Applications Handbook, Chapter entitled *Codes and Standards*.

1.8 SUBMITTALS, REVIEW AND ACCEPTANCE

- A. Equipment, materials, installation, workmanship and arrangement of work are subject to review and acceptance. No substitution will be permitted after acceptance of equipment or materials except where such substitution is considered by the Architect to be in best interest of Owner.

- B. After acceptance of Material and Equipment List, submit six (6) copies or more as required under General Conditions of complete descriptive data for all items. Data shall consist of specifications, data sheets, samples, capacity ratings, performance curves, operating characteristics, catalog cuts, dimensional drawings, wiring diagrams, installation instructions, and any other information necessary to indicate complete compliance with Contract Documents. Edit submittal data specifically for application to this project.
- C. Thoroughly review and stamp all submittals to indicate compliance with contract requirements prior to submission. Coordinate installation requirements and any electrical requirements for equipment submitted. Contractor shall be responsible for correctness of all submittals.
- D. Submittals will be reviewed for general compliance with design concept in accordance with contract documents, but dimensions, quantities, or other details will not be verified.
- E. Identify submittals, indicating intended application, location and service of submitted items. Refer to specification sections or paragraphs and drawings where applicable. Clearly indicate exact type, model number, style, size and special features of proposed item. Submittals of a general nature will not be acceptable. For substituted items, clearly list on the first page of the submittal all differences between the specified item and the proposed item. The contractor shall be responsible for corrective action and maintaining the specification requirements if differences have not been clearly indicated in the submittal.
- F. Submit actual operating conditions or characteristics for all equipment where required capacities are indicated. Factory order forms showing only required capacities will not be acceptable. Call attention, in writing, to deviation from contract requirements.
- G. Acceptance will not constitute waiver of contract requirements unless deviations are specifically indicated and clearly noted. Use only final or corrected submittals and data prior to fabrication and/or installation.
- H. For any submittal requiring more than two (2) reviews by the Engineer (including those caused by a change in subcontractor or supplier) the Owner will withhold contractor's funds by a change order to the contract to cover the cost of additional reviews. One review is counted for each action including rejection or return of any reason.
- I. For resubmissions, the Contractor must address in writing all of the Engineer's comments on the original submission to verify compliance.

1.2 SHOP DRAWINGS

- A. Prepare and submit shop drawings for all plumbing equipment, specially fabricated items, modifications to standard items, specially designed systems where detailed design is not shown on the contract drawings, or where the proposed installation differs from that shown on contract drawings.
- B. Submit data and shop drawings including but not limited to the list below, in addition to provisions of the paragraph above. Identify all shop drawings by the name of the item and system and the applicable specification paragraph number and drawing number.

- C. Every submittal including, but not limited to the list below, shall be forwarded with its own transmittal as a separate, distinct shop drawing. Grouping of items/systems that are not related shall be unacceptable.

D. Items and Systems

Access Doors/Panels including layout and location
Automatic Temperature Control System and Equipment as it relates to plumbing system
Backflow Preventers
Coordinated Drawings
Drain Valves
Drip Pans
Equipment Rails
Fire Stopping - Methods and Materials
Gas Pressure Regulating Valves
Gas Quick Disconnect Valves
Gas Solenoid Valves and Valve Boxes
Hose Bibbs and Wall Hydrants
Identification System
Material and Equipment List
Operations and Maintenance Manuals
Pipe Materials Including Itemized Schedule
Plumbing Fixtures & Trim
Preliminary Testing and Balancing Report
Pressure/Temperature Relief Valves
Pressure Regulating Valves
Roof Curbs
Strainers
Test Certificates
Thermal Insulation Materials Include Table Summary
Thermometers and Gauges
Vacuum Breakers
Valves
Vibration Isolation Materials
Weatherproof Assembly Components
Wiring Diagrams, Flow Diagrams and Operating Instructions

- E. Contractor, additionally, shall submit for review any other shop drawings as required by the Architect. No item shall be delivered to the site, or installed, until the Contractor has received a submittal from the Engineer marked *Reviewed* or *Comments Noted*. After the proposed materials have been reviewed, no substitution will be permitted except where approved by the Architect.

1.0 SUPERVISION AND COORDINATION

- A. Provide complete supervision, direction, scheduling, and coordination of all work under the Contract, including that of subcontractors.
- B. Coordinate rough-in of all work and installation of sleeves, anchors, and supports for piping, equipment, and other work performed under Division 22.

- C. Arrange for pipe spaces, chases, slots, and openings in building structure during progress of construction to allow for mechanical installations.
- D. Coordinate electrical work required under Division 22 with that under Division 26. Coordinate all work under Division 22 with work under all other Divisions.
- E. Supply services of an experienced (10 years minimum) and competent Project Manager to be in constant charge of work at site.
- F. Where a discrepancy exists within the specifications or drawings or between the specifications and drawings, the more stringent (or costly) requirement shall apply until clarification can be obtained from the Engineer. Failure to clarify such discrepancies with the Engineer will not relieve the Contractor of the responsibility of conforming to the requirements of the Contract.
- G. Failure of contractor to obtain a full and complete set of contract documents (either before or after bidding) will not relieve the contractor of the responsibility of complying with the intent of the contract documents.
- H. Coordinate installation of large equipment requiring positioning before closing in building.

1.11 CUTTING AND PATCHING

- A. Accomplish all cutting and patching necessary for the installation of work under Division 22. Damage resulting from this work to other work already in place, shall be repaired at Contractor's expense. Where cutting is required, perform work in neat and workmanlike manner. Restore disturbed work to match and blend with existing construction and finish, using materials compatible with the original. Use mechanics skilled in the particular trades required.
- B. Do not cut structural members without approval from the Architect or Engineer.

1.12 PENETRATION OF WATERPROOF CONSTRUCTION

- A. Coordinate the work to minimize penetration of waterproof construction, including roofs, exterior walls, and interior waterproof construction. Where such penetrations are necessary, furnish and install all necessary curbs, sleeves, flashings, fittings and caulking to make penetrations absolutely watertight.
- B. Where plumbing vents or other pipes penetrate roofs, flash pipe with Stoneman *Stormtite*, Pate or approved equal, roof flashing assemblies with skirt and caulked counter flashing sleeve.
- C. Furnish and install pitch pockets or weather tight curb assemblies where required.
- D. Furnish and install roof drains, curbs, and vent assemblies specifically designed for application to the particular roof construction, and install in accordance with the manufacturer's instructions. The Contractor shall be responsible for sleeve sizes and locations. All roof penetrations shall be installed in accordance with manufacturer's

instructions, the National Roofing Contractors Association, SMACNA, and as required by other divisions of these specifications.

- E. All work associated with the existing roof shall be performed so as to maintain the existing roof warranty.

1.13 CONCRETE AND MASONRY WORK

- A. Furnish and install concrete and masonry work for equipment foundations, supports pads, and other items required under Division 22. Perform work in accordance with requirements of other applicable Divisions of these specifications.
- B. Concrete shall test not less than 3,000 psi compressive strength after 28 days.
- C. Grout shall be non-shrink, high strength mortar, free of iron oxides and suitable for use in contact with all metals, without caps or other protective finishes. Apply in accordance with manufacturer's instructions and standard grouting practices.

1.14 CONNECTIONS AND ALTERATIONS TO EXISTING WORK

- A. Unless otherwise noted on the drawings, where existing plumbing work is removed all pipes, valves, etc., shall be removed, including hangers, to a point below finished floors or behind finished walls and capped. Such point shall be far enough behind finished surfaces to allow for installation of normal thickness of required finish material.
- B. Where work specified in Division 22 connects to existing equipment, piping, etc., Contractor shall perform all necessary alterations, cuttings, fittings, etc., of existing work as may be necessary to make satisfactory connections between new and existing work, and to leave completed work in a finished and workmanlike condition.
- C. Where the work specified under Division 22, or under other Divisions, requires relocation of existing equipment, piping, etc., Contractor shall perform all work and make necessary changes to existing work as may be required to leave completed work in a finished and workmanlike condition. Where existing insulation is disturbed, replace insulation where removed or damaged equal to existing, in type, thickness, density, finish and thermal resistance (R-value) value.
- D. Where the relocation of existing equipment is required for access or the installation of new equipment, the contractor shall temporarily remove and/or relocate and re-install as required to leave the existing and new work in a finished and workman like condition.

1.15 DEMOLITION

- A. Unless otherwise noted all existing equipment, piping, etc., shall remain.
- B. Where existing equipment is indicated to be removed, all associated piping, conduit, power, controls, insulation, hangers, supports and housekeeping pads, etc., patch, paint and repair walls/roof/floor to match existing and/or new finishes.
- C. Provide necessary piping, valves, traps, temporary feeds, etc., as required. Drain and refill piping systems as often as necessary to accommodate phasing and to minimize time

lengths of outages.

- D. The Contractor shall be responsible for visiting the site and determining the existing conditions in which the work is to be performed.
- E. Refer to phasing plans for additional requirements.
- F. Where any abandoned pipes in existing floors, walls, pipe tunnels, ceilings, etc., conflict with new work, remove abandoned pipes as necessary to accommodate new work.
- G. The location of all existing equipment, piping, etc., indicated is approximate only and shall be checked and verified. Install all new plumbing work to connect to or clear existing work as applicable.
- H. Maintain egress at all times. Coordinate egress requirements with the State Fire Marshal, the Owner and the authorities having jurisdiction.
- I. When applicable, make provisions and include in bid all costs associated with confined entry/space requirements in crawl spaces, tunnels, and all other applicable OSHA and MOSH regulations.
- J. Where required to maintain the existing systems in operation, temporarily backfeed existing systems from new equipment. Contractor shall temporarily extend existing piping systems to new piping systems with the appropriate shut-off valves.
- K. At completion of project all temporary piping, valves, controls, etc., shall be removed in their entirety.
- L. Existing piping, equipment, materials, etc., not required for re-use or re-installation in this project, shall be removed from the project site.
- M. Deliver to the Owner, on the premises where directed, existing equipment and materials which are removed and which are desired by the Owner or are indicated to remain the property of the Owner.
- N. All other materials and equipment which are removed shall become property of the Contractor and shall be promptly removed, from the premises, and disposed of by the Contractor, in an approved manner. Contractor shall be responsible for proper disposal of all removed equipment containing refrigerants. Contractor shall include in his bid all cost associated with the evacuation, removal and disposal of all existing equipment containing refrigerants in accordance with EPA and Health Department requirements.
- O. Where piping is removed, remove all pipe hangers which were supporting the removed piping. Patch the remaining penetration voids with like materials and paint to match existing construction.
- P. Where required, provide and coordinate removal and re-installation of existing equipment. Take care to protect materials and equipment indicated for reuse. Contractor shall repair or replace items which are damaged. Contractor shall have Owner's representative present to confirm condition of equipment prior to demolition.

- Q. Before demolition begins, and in the presence of the Owners representative, test and note all deficiencies in all existing systems affected by demolition but not completely removed by demolition. Provide a copy of the list of system deficiencies to the Owner and the Engineer. Videotape existing conditions in each space prior to beginning demolition work.
- R. The Owner shall have the first right of refusal for all plumbing fixtures, devices and equipment removed by the Contractor.
- S. All plumbing fixtures, devices and equipment designated by the Owner to remain the property of the Owner shall be moved and stored by the Contractor at a location on site as designated by the Owner. It shall be the Contractor's responsibility to store all plumbing fixtures, devices and equipment in a safe manner to prevent damage while stored.
- T. All existing equipment refused by the Owner shall become the property of the Contractor and shall be removed from the site by the Contractor in a timely manner and disposed of in a legal manner.
- U. Work Abandoned in Place: cut and remove underground pipe a minimum of 2 inches beyond face of adjacent construction. Cap and patch surface to match existing finish.
- V. Temporary Disconnection: Remove, store, clean, reinstall, reconnect, and make operational equipment indicated for relocation.
- W. Terminate services and utilities in accordance with local laws, ordinances, rules and regulations.

1.16 EXCAVATION AND BACKFILLING

A. GENERAL

- 1. Perform all necessary excavation, or installation of work under Division 22, in whatever materials or conditions encountered, using suitable methods and equipment.
- 2. Accurately establish required lines and grades and properly locate the work.
- 3. Determine the locations of all existing utilities before commencing the work.

B. Excavation: (Refer also to other portions of the specifications)

- 1. Excavate only the required elevations. If excavation is carried below the foundation lines or other required limits, backfill the excess with concrete.
- 2. Keep banks of trenches as nearly vertical as possible, and provide sheeting and/or shoring as required for protection of work and safety of personnel. Follow local, State, OSHA, Guidelines.
- 3. Keep excavations dry. Protect excavations from freezing.

C. Backfilling: (Refer also to other portions of the specifications)

1. Backfill excavations to the required elevations and restore surfaces to their original or required conditions.
2. Backfill shall be similar material, free from objectionable matter such as rubbish, roots, stumps, brush, rocks and other sharp objects. Unless otherwise indicated, suitable material from the excavation may be used for backfill.
3. Carefully place and mechanically tamp backfill in layers not exceeding 12 inches loose thickness. Compact to 95 percent minimum.
4. Do not backfill against frozen material. Do not use frozen material for backfill.

1.17 DRIVE GUARDS

- A. Provide safety guards on all exposed belt drives, motor couplings, and other rotating machinery. Provide fully enclosed guards where machinery is exposed from more than one direction.
- B. When available, guards shall be factory fabricated and furnished with the equipment. Otherwise fabricate guards of heavy gauge steel, rigidly braced, removable, and finish to match equipment served. Provide openings for tachometers. Guards shall meet local, State and O.S.H.A. requirements.

1.18 VIBRATION ISOLATION

- A. Furnish and install vibration isolators, flexible connections, supports, anchors and/or foundations required to prevent transmission of vibration from equipment, or piping to building structure. See Division 23 Section, *Vibration Controls for HVAC, Plumbing and Fire Protection*.

1.19 ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

1.20 FASTENERS

- A. All fasteners located in public spaces including classrooms, corridors, lobbies, etc., shall be provided with tamper proof fasteners. Provide Pin Phillips hardware as manufactured by Challenge Industries or approved equal.

1.21 DEFINITIONS

- A. *Approve* - to permit use of material, equipment or methods conditional upon compliance with contract documents requirements.
- B. *Furnish and install* or *provide* means to supply, erect, install, and connect to complete for readiness for regular operation, the particular work referred to.
- C. *Contractor* means the mechanical contractor and any of his subcontractors, vendors,

suppliers, or fabricators.

- D. *Piping* includes pipe, all fittings, valves, hangers, insulation, identification, and other accessories relative to such piping.
- E. *Concealed* means hidden from sight in chases, formed spaces, shafts, hung ceilings, embedded in construction or in crawl space.
- F. *Exposed* means not installed underground or *concealed* as defined above.
- G. *Invert Elevation* means the elevation of the inside bottom of pipe.
- H. *Finished Spaces*: Spaces other than mechanical and electrical equipment rooms, furred spaces, pipe and duct shafts, unheated spaces immediately below roof, spaces above ceiling, unexcavated spaces, crawl spaces, and tunnels.
- I. *Review* - limited observation or checking to ascertain general conformance with design concept of the work and with information given in contract documents. Such action does not constitute a waiver or alteration of the contract requirements.
- J. *ECM*: Electronically Commutating Motor.
- K. *Building Line*: Exterior wall of building.

1.22 MINIMUM EFFICIENCY REQUIREMENTS

- A. All plumbing equipment shall be manufactured to provide the minimum efficiency requirements as specified in ASHRAE Standard 90.1, latest edition.
- B. All piping and equipment insulation shall comply with ASHRAE Standard 90.1, latest edition.
- C. All service water heating equipment shall be manufactured to provide the minimum efficiency requirements as specified in ASHRAE Standard 90.1, latest edition.
- D. All plumbing devices, controls, accessories, and components shall be manufactured to provide the minimum efficiency requirements as specified in ASHRAE Standard 90.1, latest edition.

1.23 SYSTEM INTEGRATION

- A. For all plumbing equipment specified to be provided with packaged controls and interfaced with the automatic temperature control system, provide system integration between the equipment manufacturer and the automatic temperature control subcontractor.
- B. Plumbing equipment submittals requiring system integration as defined above must identify all required system integration points.
- C. Plumbing equipment manufacturers must coordinate with ATC subcontractor regarding system integration prior to submitting on the equipment.

- D. A system integration meeting must be arranged by the Mechanical Contractor and include, but not be limited to the systems integrator for the plumbing equipment manufacturer and the ATC Subcontractor. This portion of systems integration must occur prior to plumbing equipment being delivered to the project.
- E. Once the plumbing equipment is on site, a second systems integration meeting must be arranged by the Mechanical Contractor to coordinate the packaged controls with the ATC system. The plumbing equipment manufacturer's representative familiar with system integration and the ATC subcontractor familiar with programming must be present.
- F. A final system integrations meeting shall occur once all equipment is in place and ready for operation. The Mechanical Contractor, the plumbing equipment systems integrator, and the ATC Subcontractor shall meet on site to jointly program schedule, verify points, interlock devices, and fully set up all systems integration components.
- G. All systems integration coordination, programming, and graphics must be completed prior to requesting commissioning and/or inspections by the Engineer of Record.

1.24 LEAD FREE REQUIREMENTS

- A. All plumbing fixtures, equipment, and devices that contact potable water must be lead free per the State requirements. Potable water systems shall also comply with NSF 61 – Annex G and NSF-372.

PART 2 ELECTRICAL REQUIREMENTS

2.1 WIRING DIAGRAMS

- A. The Contractor is responsible for obtaining and submitting wiring diagrams for all major items of equipment.
- B. Wiring diagrams shall be provided with shop drawings for all equipment requiring electric power.
- C. Provide wiring diagrams for all major plumbing items of equipment to electrical contractor and ATC subcontractor for coordination.

PART 3 EXECUTION

3.1 EQUIPMENT INSTALLATION - COMMON REQUIREMENTS

- A. Install equipment to provide maximum possible headroom, if mounting heights are not indicated.
- B. Install equipment according to approved submittal data. Portions of the work are shown only in diagrammatic form. Refer conflicts to the Architect.
- C. Install equipment level and plumb, parallel and perpendicular to other building systems and components in exposed interior spaces, unless otherwise indicated.

- D. Install plumbing equipment to facilitate service, maintenance, and repair or replacement of components. Connect equipment for ease of disconnecting, with minimum interference to other installations. Extend grease fittings to accessible locations.
- E. Install equipment giving right of way to piping installed at required slope.
- F. Install flexible connectors on equipment side of shutoff valves, horizontally and parallel to equipment shafts if possible.
- G. Do not install equipment or piping over electrical gear, electrical panels, motor controllers, and similar electrical equipment. Install equipment and piping to maintain clear space above and in front of all electrical components per the National Electric Code.

3.2 SUPPORTS, HANGERS AND FOUNDATIONS

- A. Provide supports, hangers, braces, attachments and foundation required for the work. Support and set the work in a thoroughly substantial and workmanlike manner without placing strains on materials, equipment, or building structure; submit shop drawings for approval. Coordinate all work with the requirements of the structural division.
- B. Supports, hangers, braces, and attachments shall be standard manufactured items or fabricated structural steel shapes. All interior hangers shall be galvanized or steel with rust inhibiting paint. For un-insulated copper piping provide copper hanger to prevent contact of dissimilar metals. All exterior hangers shall be constructed of stainless steel utilizing stainless steel rods, nuts, washers, bolts, etc.
- C. Concrete housekeeping pads and foundations shall be not less than 4 inches high and shall extend a minimum of 6 inches beyond equipment bases. Provide wire-mesh reinforcement; chamfer exposed edges and corners; and finish exposed surfaces smooth.
- D. Where new concrete housekeeping pads are placed on existing concrete, saw cut the existing concrete to the perimeter dimension of the new pad to a depth of $\frac{1}{2}$ inch. Break out the top $\frac{1}{2}$ inch area of the existing concrete. Add *stubs* of #4 rebar angled into the existing concrete at a depth of approximately 50 percent of the existing slab thickness. The top portion of the rebar *stub* shall extend into the new pad by approximately 50 percent of its thickness. Furnish one rebar *stub* per every two square feet of new pad. Chemically bond the new concrete to the existing concrete.

3.3 DEMONSTRATION AND TRAINING VIDEO RECORDINGS

- A. General: Record demonstration and training video recordings. Record each training module separately.
 - 1. At beginning of each training module, record each chart containing learning objective and lesson outline.
- B. Video Recording Format: Provide high-quality color video recordings with menu navigation in format acceptable to Engineer
- C. Recording: Mount camera on tripod before starting recording, unless otherwise necessary to show area of demonstration and training. Display continuous running time.

- D. Narration: Describe scenes on video recording by audio narration by microphone while video recording is recorded. Include description of items being viewed.
- E. Transcript: Provide a transcript of the narration. Display images and running time captured from videotape opposite the corresponding narration segment.

3.4 PROVISIONS FOR ACCESS

- A. The contractor shall provide access panels and doors for all concealed equipment, valves, strainers, dampers, filters, controls, control devices, cleanouts, traps, and other devices requiring maintenance, service, adjustment, balancing or manual operation.
- B. Where access doors are necessary, furnish and install manufactured painted steel door assemblies consisting of hinged door, key locks, and frame designed for the particular wall or ceiling construction. Properly locate each door. Door sizes shall be a 12 inches x 12 inches for hand access, 18 inches x 18 inches for shoulder access and 24 inches x 24 inches for full body access where required. Review locations and sizes with Architect prior to fabrication. Provide U.L. approved and labeled access doors where installed in fire rated walls or ceilings. Doors shall be Mild Steel Metal Access Doors as manufactured by Inland-Ryerson, Mifab, or approved equal.
 1. Acoustical or Cement Plaster: Style B
 2. Hard Finish Plaster: Style K or L
 3. Masonry or Dry Wall: Style M
- C. Where access is by means of lift out ceiling tiles or panels, mark each ceiling grid using small color-coded and numbered tabs. Provide a chart or index for identification. Place markers within ceiling grid not on ceiling tiles.
- D. Access panels, doors, etc. described herein shall be furnished under the section of specifications providing the particular service and to be turned over to the pertinent trade for installation. Coordinate installation with installing contractor. All access doors shall be painted in baked enamel finish to match ceiling or wall finish.
- E. Submit shop drawings indicating the proposed location of all access panels/doors. Access doors in finished spaces shall be coordinated with air devices, lighting and sprinklers to provide a neat and symmetrical appearance.
- F. Where access doors are installed in wet locations (i.e. shower rooms, toilet rooms, kitchen rooms, kitchens, dishwasher rooms, can wash rooms, and similar spaces, etc.) provide aluminum access doors/frame.

3.5 PAINTING AND FINISHES

- A. Provide protective finishes on all materials and equipment. Use coated or corrosion-resistant materials, hardware and fittings throughout the work. Paint bare, untreated ferrous surfaces with rust-inhibiting paint. All exterior components including supports, hangers, nuts, bolts, washers, vibration isolators, etc. shall be stainless steel.
- B. Clean surfaces prior to application of insulation, adhesives, coatings, paint, or other

finishes.

- C. Provide factory-applied finishes where specified. Unless otherwise indicated factory-applied paints shall be baked enamel with proper pretreatment.
- D. Protect all finishes and restore any finishes damaged as a result of work under Division 22 to their original condition.
- E. The preceding requirements apply to all work, whether exposed or concealed.
- F. Remove all construction marking and writing from exposed equipment, piping and building surfaces. Do not paint manufacturer's labels or tags.
- G. All exposed piping, equipment, etc. shall be painted. Colors shall be as stated in this division or as selected by the Architect and conform to ANSI Standards.
- H. All exterior roof mounted equipment, piping and vents shall be painted to match roof in color as selected by Architect.
- I. All exposed piping, equipment, etc. in finished spaces shall be painted. Colors shall be as selected by the Architect and conform to ANSI Standards.
- J. All exposed piping, equipment, etc., in Mechanical Rooms, Penthouses, Fire Pump Rooms, Mezzanines, Crawlspace, and Storage where PVC jacketed shall not require painting. Label and identify and color code as specified.

3.6 CLEANING OF SYSTEMS

- A. Thoroughly clean systems after satisfactory completion of pressure tests and before permanently connecting fixtures, equipment, traps, strainers, and other accessory items. Blow out and flush piping until interior surfaces are free of foreign matter.
- B. Flush piping in recirculating water systems to remove cutting oil, excess pipe joint compound, solder slag and other foreign materials. Do not use system pumps until after cleaning and flushing has been accomplished to the satisfaction of the Engineer. Employ chemical cleaners, including a non-foaming detergent, not harmful to system components. After cleaning operation, final flushing and refilling, the residual alkalinity shall not exceed 300 parts per million. Submit a certificate of completion to Engineer stating name of service company used.
- C. Maintain strainers and dirt pockets in clean condition.
- D. Pay for labor and materials required to locate and remove obstructions from systems that are clogged with construction refuse after acceptance. Replace and repair work disturbed during removal of obstructions.
- E. Leave systems clean, and in complete running order.

3.7 COLOR SELECTION

- A. Color of finishes shall be as selected by the Architect.

- B. Submit color of factory-finished equipment for acceptance prior to ordering.

3.8 PROTECTION OF WORK

- A. Protect work, material and equipment from weather and construction operations before and after installation. Properly store and handle all materials and equipment.
- B. Cover temporary openings in piping and equipment to prevent the entrance of water, dirt, debris, or other foreign matter. Deliver pipes and tubes with factory applied end caps.
- C. Cover or otherwise protect all finishes.
- D. Replace damaged materials, devices, finishes and equipment.
- E. Protect stored pipes and tubes from moisture and dirt. Elevate above grade. Do not exceed structural capacity of floor, where stored inside.

3.9 OPERATION OF EQUIPMENT

- A. Clean all systems and equipment prior to initial operation for testing, balancing, or other purposes. Lubricate, adjust, and test all equipment in accordance with manufacturer's instructions. Do not operate equipment unless all proper safety devices or controls are operational. Provide all maintenance and service for equipment that is authorized for operation during construction.
- B. Where specified, or otherwise required, provide the services of the manufacturer's factory-trained servicemen or technicians to start up the equipment. Where factory start-up of equipment is not specified, provide field start-up by qualified technician.
- C. Submit factory start-up sheets or field start-ups sheets for all equipment prior to the commencement of testing and balancing work. Testing and balancing work shall not commence until start-up reports have been completed, reviewed by Engineer and forwarded to Testing and Balancing Agency.
- D. Do not use plumbing systems for temporary services or temporary conditioning during construction. Refer to Division 01 section "*Temporary Facilities and Controls*" for temporary plumbing during construction.
- E. Upon completion of work, clean and restore all equipment to new conditions; replace expendable items such as filters.

3.10 IDENTIFICATIONS, FLOW DIAGRAMS, ELECTRICAL DIAGRAMS AND OPERATING INSTRUCTIONS

- A. Contractor shall submit for approval schematic piping diagrams of each piping system installed in the building. Diagrams shall indicate the location and the identification number of each valve in the particular system. Following approval by all authorities, the diagrams shall be framed, mounted under safety glass and hung in each Mechanical Room where directed. Contractor shall deliver the tracing or sepia from which the diagrams were reproduced to the Owner.

- B. All valves shall be plainly tagged. For any bypass valves, install sign indicating valve position as “Normally Open” or “Normally Closed” as required.
- C. All items of equipment, including motor starters and disconnects shall be furnished with white on black plastic permanent identification cards. Lettering shall be a minimum of 1/4 inch high. Identification plates shall be secured, affixed to each piece of equipment (starters, disconnects, panels by screw or adhesive (tuff bond #TB2 or as approved equal). Equipment identification and room name or area served shall be on each panel.
- D. Provide six (6) copies of operating and maintenance instructions for all principal items of equipment furnished. This material shall be bound as a volume of the *Operations and Maintenance Manuals* as hereinafter specified.
- E. All lines piping installed under this contract shall be stenciled with *direction of flow* arrows and with stenciled letters naming each pipe and service. Refer to Division 22 Section, *Plumbing Piping, Fittings, Valves, Etc.* Color code all direction of flow arrows and labels. In finished spaces omit labeling and direction of flow arrows. Paint in color as selected by Architect.
- F. Submit list of wording, symbols, letter size, and color coding for plumbing identification. Submit samples of equipment identification cards, piping labels, labels, and valve tags to Engineer for review prior to installation.
- G. Provide at least 16 hours of straight time instruction to the operating personnel. Time of instruction shall be designated by the Owner. Additional instruction time for the automatic temperature control (ATC) system is specified in Division 23 Section, *Instrumentation and Controls of HVAC and Plumbing Systems.*
- H. Contractor shall demonstrate Sequences of Operation of all plumbing equipment in presence of Owner's representative, Engineer, and ATC subcontractor.

3.11 WALL AND FLOOR PENETRATION

- A. All penetrations of partitions, ceilings, roofs and floors by piping or conduit under Division 22 shall be sleeved, sealed, and caulked airtight for sound and air transfer control. Penetrations of mechanical room partitions, ceilings, and floors shall be as specified in Division 07 Section, *Fire Protection, HVAC and Plumbing Penetration Firestopping.*
- B. All penetration of fire rated assemblies shall be sleeved, sealed, caulked and protected to maintain the rating of the wall, roof, or floor. Fire Marshal approved U.L. assemblies shall be utilized. See Division 07 Section, *Fire Protection, HVAC and Plumbing Penetration Firestopping.*
- C. Where piping extends through exterior walls or below grade, provide waterproof pipe penetration seals, as specified in another division of these specifications.
- D. Provide pipe escutcheons and duct flanges for sleeved pipes and ducts in finished areas.
- E. Piping sleeves:

1. Galvanized steel pipe, standard weight where pipes are exposed and roofs and concrete and masonry walls. On exterior walls provide anchor flange welded to perimeter.
 2. Twenty-two (22) gauge galvanized steel elsewhere.
- F. Extend all floor sleeves through floor at least 2-inches above finished floor, caulk sleeve the entire depth and furnish and install floor plate.
- G. Sleeves for penetrations in kitchen and food service areas shall finish .375 inches above floor or flush with wall surfaces and be neatly pointed up to fit snugly against floor or wall material.

3.12 RECORD DRAWINGS

- A. Upon completion of the mechanical installations, the Contractor shall deliver to the Architect one complete set of prints of the mechanical contract drawings which shall be legibly marked in red pencil to show all changes and departures of the installation as compared with the original design. They shall be suitable for use in preparation of Record Drawings.
- B. Contractor shall incorporate all sketches, addendums, value engineering, change orders, etc., into record drawings prior to delivering to Architect.

3.13 WARRANTY

- A. Contractor's attention is directed to warranty obligations contained in the *General Conditions and Supplementary Conditions*.
- B. The above shall not in any way void or abrogate equipment manufacturer's guarantee or warranty. Certificates of equipment manufacturer's warranties shall be included in the operations and maintenance manuals.
- C. The contractor guarantees for a two year period from the time of final acceptance by the Owner.
1. That the work contains no faulty or imperfect material or equipment or any imperfect, careless, or unskilled workmanship.
 2. That all work, equipment, machines, devices, etc. shall be adequate for the use to which they are intended, and shall operate with ordinary care and attention in a satisfactory and efficient manner.
 3. That the contractor will re-execute, correct, repair, or remove and replace with proper work, without cost to the Owner, any work found to be deficient. The contractor shall also make good all damages caused to their work or materials in the process of complying with this section.
 4. That the entire work shall be water-tight and leak-proof.

3.14 LUBRICATION

- A. All bearings, motors, and all equipment requiring lubrication shall be provided with accessible fittings for same. Before turning over the equipment to the Owner, the Contractor shall fully lubricate each item of equipment, shall provide one year's supply of lubricant for each, and shall provide Owner with complete written lubricating instructions, together with diagram locating the points requiring lubrication. Include this information in the *Operations and Maintenance Manuals*.
- B. In general, all motors and equipment shall be provided with grease lubricated roller or ball bearings with Alemite or equal accessible or extended grease fittings and drain plugs.

3.15 OPERATIONS AND MAINTENANCE MANUALS

- A. The Contractor shall have prepared six (6) hardcopies and one (1) electronic copy of the *Operations and Maintenance Manuals* and deliver these copies of the manuals to the Owner. The manuals shall be as specified herein. The manuals must be approved and will not be accepted as final until so stamped.
- B. The manuals shall be bound in a three-ring loose leaf binder similar to National No. 3881 with the following title lettered on the front: *Operations and Maintenance Manual Nellie Stokes Elementary School – Plumbing Systems*. No sheets larger than 8-1/2 inches x 11 inches shall be used, except sheets that are neatly folded to 8-1/2 inches x 11 inches and used as a pull-out. Provide divider tabs and table of contents for organizing and separating information.
- C. Provide the following data in the booklet:
 - 1. As first entry, an approved letter indicating the starting/ending time of Contractor's warranty period.
 - 2. Catalog data on each piece of plumbing equipment furnished.
 - 3. Maintenance operation and lubrication instructions on each piece of plumbing equipment furnished.
 - 4. Complete catalog data on each piece of plumbing equipment furnished including approved shop drawing.
 - 5. Manufacturer's extended limited warranties on equipment including but not limited to water heaters.
 - 6. Chart form indicating frequency and type of routine maintenance for all plumbing equipment. The chart shall also indicate model number of equipment, location and service.
 - 7. Provide sales and authorized service representatives names, address, and phone numbers of all equipment and subcontractors.
 - 8. Provide supplier and subcontractor's names, address, and phone number.
 - 9. Catalog data of all equipment, valves, etc. shall include wiring diagrams, parts list and assembly drawing.
 - 10. Provide and install in locations as directed by the Owner, valve charts including valve tag number, valve type, valve model number, valve manufacturer, style, service and location. Each valve chart shall be enclosed in a durable polymer based frame with a cover safety glass.
 - 11. Copy of the approved balancing report for plumbing equipment/system.
 - 12. Access panel charts with index illustrating the location and purpose of access

- panels.
- 13. Approved Health and Plumbing and Electrical Certificates.
- 14. Start-up reports for equipment.
- 15. Insert color graphic with embedded parameters for ATC system into Record and Information Booklet.

D. Submit *Operations and Maintenance Manuals* prior to the anticipated date of substantial completion for Engineer review and approval. Substantial completion requires that *Operations and Maintenance Manuals* reviewed and approved.

3.16 INSTALLATION AND COORDINATION DRAWINGS

- A. Prepare, submit, and use composite installation and coordination drawings to assure proper coordination and installation of work. Drawings shall include but not be limited, to the following:
 - 1. Complete Plumbing, Sprinkler and HVAC Piping Drawings showing coordination with lights, electrical equipment HVAC equipment and structural amenities.
- B. Draw plans to a scale not less than 3/8-inch equals one foot. Include plans, sections, and elevations of proposed work, showing all equipment, and piping in areas involved. Fully dimension all work including lighting fixtures, conduits, pullboxes, panelboards, and other electrical work, walls, doors, ceilings, columns, beams, joists and other architectural and structural work.
- C. Identify all equipment and devices on wiring diagrams and schematics. Where field connections are shown to factory-wired terminals, include manufacturer’s literature showing internal wiring.

3.17 PIPING SYSTEMS TESTING


A. The entire new plumbing piping systems shall be tested hydrostatically before insulation covering is applied and proven tight under the following gauge pressures for a duration of four (4) hours. Testing to be witnessed by Owner’s representative and documented in writing.

SYSTEM	TEST PRESSURE
Domestic Water & Coil Drain Piping	100 psi
Sanitary & Storm Water Piping	As specified below

B. All gas piping shall be pressure tested in accordance with NFPA-54. Gas piping systems shall be proven tight under the following gauge pressures for a duration of four(4) hours:

SYSTEM	TEST PRESSURE
Gas Piping	100 psig

C. All storm, waste, vent and water piping shall be tested by the Contractor and approved by



the Engineer before acceptance. All storm, soil, and waste piping, located underground, shall be tested before backfilling. The costs of all equipment required for tests are to be included in the contract price.

- D. The entire new drainage system and venting system shall have all necessary openings plugged and filled with water to the level of the highest stack above or at the roof. The system shall hold this water for thirty (30) minutes without showing a drop greater than 1/4 inch. Where a portion of the system is to be tested, the test shall be conducted in the same manner as described for the entire system, except a vertical stack 10 feet above the highest horizontal line to be tested may be installed and filled with water to maintain sufficient pressure, or a pump may be used to supply the required pressure. The pressure shall be maintained for thirty (30) minutes. All testing shall be in accordance with the local Plumbing Code and witnessed by the Plumbing Inspector or authority having jurisdiction.
- E. Upon completion of roughing-in and before setting equipment and fixtures, the entire new water piping system shall be tested at a hydrostatic pressure of not less than one hundred (100) pounds per square inch gauge and proven tight at this pressure. Where a portion of the water piping system is to be concealed before completion, this portion shall be tested separately in a manner described for the entire system.
- F. Testing and acceptance thereof shall be in accordance with local requirements and shall meet approval of authority having jurisdiction. Submit certificates and approved permits and insert one (1) copy in the *Operations and Maintenance Manuals*.

3.18 EQUIPMENT BY OTHERS

- A. This Contractor shall make all system connections required to equipment furnished and installed under other divisions or furnished by the Owner. Connections shall be complete in all respects to render this equipment functional to its fullest intent.
- B. It shall be the responsibility of the supplier of this equipment to furnish complete instructions for connections. Failure to do so will not relieve this contractor of any responsibility for improper equipment operation.

3.19 PHASING

- A. Refer to Architectural Specifications and contract drawings for any required phasing.
- B. Maintain building egress and traffic ways at all times. Coordinate egress requirements with the State Fire Marshal, the Owner and Authorities having jurisdiction.
- C. Provide dust barriers/partitions, penetration closures, etc, to ensure safety of building occupants and protection of existing surroundings.
- D. The Building shall remain watertight at all times.
- E. Refer to phasing plans for additional requirements.
- F. Provide necessary piping, valves, etc. as required. Drain and refill piping systems as often as necessary to accommodate phasing and to minimize time length of outages.

Provide valves, to maintain existing systems in operation until all equipment is connected. Temporarily feed new systems with existing system where required or shown on contract drawings.

- G. Within thirty days of Award of Contract, the Contractor shall submit a minimum of six (6) copies of the proposed Phasing Plan (Drawings and detailed written description) to the Architect for review and approval based on the general and specific requirements indicated on the Drawings and Specifications. The phasing plan shall reflect the work of all trades. The phasing plan shall be updated as often as needed (i.e. major deviations and/or modified sequence of events) and reviewed during each progress meeting so the facility and Architect can be aware of the areas of construction and progress as it relates to the approved schedule.
- H. Due to phased construction, some systems must be operated at part load conditions until later phases are completed.
- I. While work is in progress, except for designated short intervals during which connections are made, continuity of service shall be maintained to all existing systems. Interruptions shall be coordinated with the Owner as to time and duration. The contractor shall be responsible for any interruptions to service and shall repair any damages to existing systems caused by his operations.

3.20 OUTAGES

- A. Provide a minimum of fourteen (14) day notice to schedule outages. The Contractor shall include in their bid outages and/or work in occupied areas to occur on weekends, holidays, or at night. Coordinate and get approval of all outages with the Owner.
- B. Submit *Outage Request form*, attached at end of this Section, to Owner for approval.

END OF SECTION

OUTAGE REQUEST

DATE APPLIED: _____ BY: _____

DATE FOR OUTAGE: _____ FIRM: _____

START OUTAGE-TIME: _____ DATE: _____

END OUTAGE -- TIME: _____ DATE: _____

AREAS AND ROOMS: _____

FLOOR(S): _____

AREA(S): _____

ROOM(S): _____

WORK TO BE PERFORMED: _____

SYSTEM(S): _____

REQUEST APPROVED BY: _____

(FOREMAN OR OTHER PERSON IN CHARGE)

(FOR OWNER'S USE ONLY):

APPROVED: _____

YES ___ NO ___ BY: _____ DATE: _____

DATE/TIME-AS REQUESTED: _____ OTHER : _____

OWNER'S PRESENCE REQUIRED: _____

YES: ___ NO: ___ NAME: _____

POINT OF CONTACT: _____ PHONE: _____

NOT FOR BIDDING PURPOSES

SECTION 22 05 05

PLUMBING PIPING, FITTINGS AND VALVES

PART 1. GENERAL

1.1. SUMMARY

- A. The conditions of the contract and other general requirements apply to the work specified in this section. All work under this section shall also be subject to the requirements of Division 22 Section, Common Work Results for Plumbing and Division 01, *General Requirements*.
- B. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2. SYSTEM DESCRIPTION CONDITIONS

- A. Provide all labor and materials necessary to furnish and install all piping systems on this project as herein specified and/or shown on the drawings. Final connections to equipment furnished in other sections of the specifications shall be included under this section.
- B. All piping and insulation installed in ceiling plenums must be plenum rated and comply with NFPA and International Building Code (IBC).
- C. Where more than one piping system material is specified, ensure system components are compatible and joined to ensure the integrity of the system is not jeopardized. Provide necessary joining fittings. Ensure flanges, union, and couplings for servicing are consistently provided.
- D. Use unions, flanges, and couplings downstream of valves and at equipment or apparatus connections. Do not use direct welded or threaded connections to valves, equipment or other apparatus.
- E. Use non-conducting dielectric connections whenever jointing dissimilar metals in open systems.
- F. Provide pipe hangers and supports in accordance with ASTM B31.9 and MSS SP69 unless indicated otherwise.
- G. Use spring loaded "silent" check valves on discharge of all pumps.
- H. Use 3/4 inch (20 mm) ball valves with cap and chain for drains at main shut-off valves, low points of piping, bases of vertical risers, and at equipment. Pipe to nearest floor drain.
- I. At all runout piping serving equipment, use swing joints with elbows to prevent excessive movement of piping due to expansion.

1.3. QUALITY ASSURANCE

- A. Valves: Manufacturer's name and pressure rating marked on valve body.

- B. Welding Materials and Procedures: Conform to ASME Code and applicable state labor regulation. Provide certificate of compliance from authority having jurisdiction indicating approval of welders.
- C. Welders Certification: In accordance with ASME Section 9.
- D. All grooved joint couplings, fittings, valves, and specialties shall be the products of a single manufacturer. Grooving tools shall be of the same manufacturer as the grooved components.
- E. All castings used for coupling housings, fittings, and valve bodies shall be date stamped for quality assurance and traceability.
- F. Maintain one copy of each document on site.

1.4. DELIVERY, STORAGE AND HANDLING

- A. Deliver, store, protect and handle products to site under as hereinbefore specified.
- B. Accept valves on site in shipping containers with labeling in place. Inspect for damage.
- C. Provide temporary protective coating on cast iron and steel valves.
- D. Provide temporary end caps and closures on piping and fittings. Maintain in place until installation.
- E. Protect piping systems from entry of foreign materials by temporary covers, completing sections of the work, and insulating parts of completed systems.

1.5. ENVIRONMENTAL REQUIREMENTS

- A. Do not install underground piping when bedding is wet or frozen.

1.6. EXTRA MATERIALS

- A. Provide one (1) repacking kit for each size valve.

1.7. ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

1.8. LEAD FREE REQUIREMENTS

- A. All plumbing fixtures, equipment, and devices that contact potable water must be lead free per the State requirements.

1.9. PLASTIC PIPE PENETRATIONS

- A. Install UL listed collars, sealing methods, and firestopping at all plastic pipe penetrations of

smoke walls and fire rated walls per NFPA.

PART 2. PRODUCTS

2.1. PIPE MATERIALS

A. All materials, unless otherwise specified, shall be new and of the best quality of their respective kinds, and shall conform to the requirements and ordinances of local, state and insurance authorities having jurisdiction.

1. Sanitary Underground - Within Building to 5 Feet Outside of Foundation Wall:

a). Pipe & Fittings: Cast iron soil pipe, Hubless cast iron soil pipe and fittings must be marked with the collective trademark of the Cast Iron Soil Pipe Institute and listed by NSF International as compliant with CISPI 301.

b). Hubless pipe and fittings shall be joined using Heavy Duty Shielding Coupling, ASTM C 1540 Type 304 Stainless Steel corrugated shield and bands, and polychloroprene (neoprene) based rubber sleeve conforming to ASTM C564.

i. Approved Manufacturers:

- 1) Husky SL 4000
- 2) Clamp All 125
- 3) MG

c). Service Weight pipe and fittings must be marked with the Cast Iron Soil Pipe Institute collective trademark and listed by NSF International as compliant with ASTM A 74. Gaskets must be polychloroprene (neoprene) based rubber Service Weight type conforming to ASTM C564.

Approved manufacturers:

- 1) AB&I
- 2) Charlotte
- 3) Tyler

2. Sanitary and Vents Above Floor Inside Building:

a). Pipe & Fittings: Cast iron *No-Hub* pipe and fittings shall be marked with the collective trademark of the Cast Iron Soil Pipe Institute and listed by NSF International as compliant with CISPI 301, ASTM C564. Installation and support shall be in accordance with Cast Iron Soil Pipe Institute recommendation. Joints shall be made with neoprene gaskets and 304 stainless steel clamp and shield assemblies. Sealing sleeve shall be polychloroprene (neoprene) based rubber sleeve conforming to ASTM C564.

b). Hubless Cast Iron Soil Pipe and Fittings

i. Hubless pipe and fittings must be listed by NSF International as compliant with CISPI 301.

- ii. Manufacturers:
- 1) AB&I
 - 2) Charlotte
 - 3) Tyler
- c). Medium Duty Shielding Coupling, ASTM C 1540, Type 304 Stainless Steel corrugated shield and bands, and polychloroprene (neoprene) based rubber sleeve conforming to ASTM C564.
- i. Approved manufacturers:
- 1) Clamp-All
 - 2) Mission Rubber Company
 - 3) Husky HD 2000
3. Indirect Waste Piping:
- a). Pipe & Fittings: Hard drawn Type L copper piping with cast brass drainage fittings. ASTM B88-78 and ANSI B16.1877. All exposed indirect waste piping shall be chrome plated or primed and painted with silver paint.
4. Storm Water Below Grade or Under Building to Point 5 Feet from Building Line:
- a). PVC Pipe: Schedule 40 DWV or cellular core. Fittings: Schedule 40 PVC, ASTM D 2665 or ASTM F891 socket fittings. Joints: ASTM D2855, solvent weld with ASTM D2564 solvent cement.
- b). Downspout Boots with Cleanout Tees:
Smith, Zurn, Josam, Neenah or approved equal cast iron body downspout boot with trap. Furnish unit with cast holes and galvanized flat head bolts. Refer to the Architectural Contract documents for exact size. Downspout boots shall discharge into coated cast iron cleanout tee with bronze plug. All components shall be painted in color as selected by Architect.
- c). Perforated Elevator Pit & Foundation Drain Piping: Advanced drainage system, Certain-Teed Corp. or approved equal. Perforated, polyethylene (PE) pipe and fittings: ASTM F 405, corrugated, for coupled joints. Couplings shall be manufacturer's standard band type.
5. Storm Water Above Floor Inside Building:
- a). PVC Pipe: Schedule 40 DWV or cellular core. Fittings: Schedule 40 PVC, ASTM D 2665 or ASTM F891 socket fittings. Joints: ASTM D2855, solvent weld with ASTM D2564 solvent cement.
6. Domestic Cold Water Outside of Building Below Ground or Under Building to Point 5 Feet from Building Line:
- a). Pipe: 2-1/2 inches & smaller, soft temper type K. ASTM B88 - No joints below grade except as approved by the Engineer.
- 3 inches & larger, ductile iron pipe for water, ANSI 21.50 & 21.51 with

double thickness cement mortar lining, ANSI 21.4.

- b). Fittings & Joints: wrought copper solder joint fittings, ANSI B16.22. Joints for copper piping shall be ASTM B32, SOLDER, grade 95TA.

Cast iron pressure fittings, ANSI 21.10, Class 250. Mechanical specification for mechanical joint for cast iron pressure pipe & fittings, ANSI A21.11. Joints for ductile iron pipe shall be AWWA C111 rubber gasket with 3/4 inch diameter rods.

7. Domestic Hot, Cold, and Recirc., Water Piping Inside Buildings, Above Grade:

- a). Pipe or Tubing: 2 inches & smaller, all water lines soft temper Type K copper tubing below ground, hard temper Type L copper tubing above ground, ASTM B88, or Type 304/304L, Schedule 10S, stainless steel to ASTM A312.

2-1/2 inches & larger, hot dipped galvanized steel A120, ASTM A53, Grade B, Schedule 40 steel, or hard copper tube, Type L with copper-tube dimensioned grooved ends; copper ground - end fittings; copper tubing, keyed couplings; and grooved joints. (Flaring of tube or fitting ends to accommodate alternate sized couplings is not permitted.)

Provide dielectric fittings between steel and copper. Victaulic Style 47 or approved equal.

- b). Fittings & Joints: Copper tubing fittings and joints shall be solder type wrought copper -95-5 silver solder or braze (lead and antimony based solders are prohibited). Galvanized steel pipe fittings and joints shall be ANSI B16.12 hot dipped galvanized threaded ends and 125 lb. galvanized cast iron fittings or 150 lb. galvanized malleable iron.

Stainless steel fittings shall be Vic-Press or approved equal for Schedule 10S pipe. Fittings shall be precision, cold drawn, stainless steel with EPDM O-ring seals. (Seals shall be UL classified in accordance with ANSI/NSF61 for Potable Water service.) Fittings rated for working pressures to 500-psi.

- ii. Grooved joint couplings shall consist of two ductile iron housing segments cast with offsetting angle pattern bolt pads, FlushSeal elastomer gasket, and ASTM A449 electroplated steel bolts and nuts. (Gasket shall be UL classified in accordance with ANSI/NSF61 for Potable Water service, and shall meet the lead content requirements of NSF-372.) Installation-Ready, for direct stab installation without field disassembly. Victaulic Style 607H or approved equal.
- iii. Installation-Ready™ fittings for grooved end copper tubing shall be manufactured to copper-tube dimensions. Fittings shall be ductile iron conforming to ASTM A-536, Grade 65-45-12, with Installation-Ready™ ends, complete with PVDF (Poly Vinylidene Fluoride) and Grade “EHP” EPDM-HP (Grade ‘T’ Nitrile) gasket; and ASTM A449 electroplated steel bolts and nuts. System shall

be rated to 300 psi (2065 kPa) with Type K or L Copper Tubing.

- 1) UL classified in accordance with NSF-61 for potable water service. The system shall meet the low-lead requirements of NSF-372.
- c). Gate Valves: 2-1/2 inches & larger - OS&Y, IBBM flanged, 125 lb. standard solid wedge.
2 inches & smaller - bronze solder end, bronze body, solid wedge, rising stem, 200 lb. w.o.g. non-shock. However, use brass valve only on all copper pipe.
- d). Butterfly Valves: Cast brass body to UNS C87850, elastomer pressure responsive seat, aluminum-bronze disc with stainless steel stem. Stem shall be offset from the disc centerline to provide complete 360-degree circumferential seating. Copper-tube dimensioned grooved ends, suitable for working pressures to 300-psig CWP Victaulic Style 608N or approved equal.
- e). Ball Valves: Shut-off valves 2-inches and smaller shall be ball valves. Ball valves shall be 150 lbs, brass or bronze body, standard port, 2 piece body, TFE seats with bronze trim. Ball valves shall be threaded end or solder end, or Vic-Press end as required to accommodate piping. Ball valves shall be as manufactured by Victaulic, Conbraco, Crane, Apollo, Nibco, Watts or engineer approved equal.
- f). Unions: 2-1/2 inches & larger - 150 lb. brass companion flanges.
2 inches & smaller - wrought copper, ground joint solder ends; threaded hexagonal stainless steel union with Vic-Press ends, Victaulic P589 or approved equal.
- g). Check Valves: 2-1/2 inches & larger - IBBM, 125 lb. std. flanged bronze swing check, with metal disc; 2-inches and smaller - 125 lb. std. screwed or solder ends.
- h). Globe Valves: 2 inches and smaller, bronze body, bronze trim, rising stem, hand wheel, inside screw, renewable composition disc, solder ends, 150 lb, with back seating capacity.
2 inches & larger: IBBM, 150 lb, bronze trim, rising stem, handwheel OS&Y, plug type disc, flanged ends, renewable seat and disc.
Globe valves shall be Conbraco, Crane, Nibco, Milwaukee, Watts or approved equal.
- i). Combination Shut-off/Balancing Valves:
Victaulic/TA Hydronics, Taco Circuit Setter, Bell & Gossett Circuit Setter Plus, Flowset Accuset, Gerand, or engineer approved equal, 1/2 inch-3 inches

300 psi rated globe type or ball valve with DZR brass Ametal (copper-alloy) or bronze body/brass ball construction with glass and carbon filled TFE seats, in-line flow meter and balancing and shut-off valve with built in ball valve for flow adjustment. Valve shall have memory stop, calibrated nameplate, Schrader valve connections and preformed molded insulation. Valves shall be leaktight at full rated working pressure. Balance valve size shall be selected based on manufacturer's acceptable flow range and design flow rate. Pressure drop through combination shut off balance valves shall not exceed 5 feet of head at design flow rate.

- j). Extended Valve Stems: Provide and install round collar type extended valve stems on all valves installed in insulated piping. Valve stem and collar shall be selected to suit insulation thickness and maintain valve handles outside of insulation.
- k). (Alternate): At contractor's option, Viega ProPress pressure seal mechanical fittings may be utilized.
 - i. Viega, ProPress Pressure Seal Fittings: Bronze, or copper shall conform to ASME B16.31, ICC LC 1002, IAPMO PS 117, NSF 61, and NSF 61-G or NSF 372. ProPress fittings ½-inch thru 4-inch for use with ASTM B88 copper tube type L and ½-inch up to 1-1/4-inch annealed copper tube. ProPress fittings shall have an EPDM sealing element grip ring, PBT separator ring, EPDM sealing element and Smart Connect (SC) feature.

8. Gas Piping:

- a). Pipe: Inside Building Above Ground: Schedule 40 uncoated black steel pipe, ASTM A 53 or A120.
- b). Outside Building, Below Ground: Copper type *L* tubing, ASTM B88 Below Ground.
- c). Outside building above grade/roof: Schedule 40 black steel pipe, ASTM A53 or A120.
- d). Fittings & Joints: 150 lb. screwed malleable iron ASTM B16.3 with joints sealed with litharge and glycerin. Piping 2 ½ inches and larger and any concealed piping within walls must be welded, ASTM A24 forged steel welded type joints shall be threaded or welded to ANSI B31.1 or ASME Sec. 1.
- e). Plug Valves: 2- ½ inches & larger ASME B16.38 and MSS SP-78 cast iron lubricated plug valves with 125 psig pressure rating, 3 turn type. Gas valves are prohibited above ceilings.
- f). Cocks: 2 inches & smaller - bronze, Crane 270. AGA certified bronze body, plug type with bronze plug, ball type with chrome plated brass ball, for 5 psig or less gas. Include AGA stamp, flat or square head or lever

handle, and threaded ends conforming to ASME B1.20.1

- g). Ball Valves: Full flow, double seal, ball type with bronze body, Buna-N seals and O-ring packing, chrome plated brass ball and designed for working pressures up to 175 psig. Valves shall be 3 turn type. MSS SP-78, class 175 WOG.
- h). Kitchen Equipment Gas Solenoid Valve:
The main gas supply to the kitchen equipment shall be furnished with a new automatic solenoid gas valve. Valve shall be U.L. listed and interlocked with hood suppression system. Coordinate with Food Service Documents.
- i). Gas Vents: Install vent piping for gas pressure regulators and gas trains, extend outside building to a non-hazardous location away from any potential source of ignition, and vent to atmosphere. Pipe material shall be identical to gas piping here-in before specification. Terminate vents with turned down, reducing elbow fittings with corrosion-resistant insect screen in large end.
- j). Finish: All gas piping downstream of regulator, installed exposed in a kitchen, or piping installed on a roof shall be primed and finished with two coats of rust resistant paint with newter gray finish. Paint shall be two part epoxy-exterior paint as manufactured by Pittsburgh Paint, Themeco, or approved equal. Painting shall be provided under another Section of these Specifications.

- B. Steel pipe shall be similar and equal to National Tube Company, Grinnell, Republic, or Bethlehem black or zinc-coated (galvanized) as hereinafter specified. Pipe shall be free from all defects which may affect the durability for the intended use. Each length of pipe shall be stamped with the manufacturer's name.
- C. Copper pipe shall be Bevere, Anaconda or Chase with approved solder fittings.
- D. Welding fittings for steel pipe shall meet the requirements of ASTM Standard A-23 and shall be standard catalog products. Fittings fabricated by metering and notching pipe will not be accepted.

2.2. PIPE HANGERS, ROLLER SUPPORTS, ANCHORS, GUIDES, AND SADDLES

- A. All hangers for metallic piping shall be adjustable, wrought clevis type, or adjustable malleable split ring swivel type, having rods with machine threads. Hangers shall be Grinnell Company's Figure 260, Carpenter and Patterson, or approved equal for pipe ¾-inch and larger, and Figure 65 for pipe 2-inches and smaller, or approved equal. Adjustable pipe stanchion with U-bolt shall be Grinnell Company's Figure 191. Pipe roller supports shall be Grinnell's Figure 181 or Figure 271. Exterior pipe hangers shall be galvanized or stainless steel construction. For copper piping in direct contact with the hanger, hanger construction shall be copper coated to prevent contact of dissimilar metals similar to Grinnell's Figure CT-65. Hanger spacing and rod sizes for steel and copper pipe shall not be less than the following:

NOMINAL PIPE SIZE IN	STD. STEEL PIPE	MAXIMUM SPAN FT. COPPER TUBE	MINIMUM ROD DIAMETER INCHES OF ASTM A36 STEEL THREADED RODS
3/4 & 1	6	5	3/8
1 - 1/2	6	8	3/8
2	8	8	3/8
2 - 1/2	10	9	1/2
3	12	10	1/2
4	14	12	5/8
5	14	12	5/8
6	16	14	3/4
8	18	16	7/8
10	20	18	7/8
12	20	18	7/8

B. Install hangers for cast-iron and storm water soil piping with the following maximum horizontal spacing and minimum rod diameters:

1. NPS 1-1/2 and NPS 2 (DN 40 and DN 50): 60 inches (1500 mm) with 3/8-inch (10-mm) rod.
 2. NPS 3 (DN 80): 60 inches (1500 mm) with 1/2-inch (13-mm) rod.
 3. NPS 4 and NPS 5 (DN 100 and DN 125): 60 inches (1500 mm) with 5/8-inch (16-mm) rod.
 4. NPS 6 (DN 150): 60 inches (1500 mm) with 3/4-inch (19-mm) rod.
 5. NPS 8 to NPS 12 (DN 200 to DN 300): 60 inches (1500 mm) with 7/8-inch (22-mm) rod.
 6. NPS 15 (DN 375): 60 inches (1500 mm) with 1-inch (25-mm) rod.
- Spacing for 10-foot (3-m) lengths may be increased to 10 feet (3 m). Spacing for fittings is limited to 60 inches (1500 mm).

C. Install supports for vertical cast-iron soil piping every 15 feet (4.5 m).

D. Anchors, guides, and roller supports shall be installed in accordance with the contract drawings and manufacturer's recommendations to provide pipe support and control pipe movement for all piping systems. Anchors and guides shall be securely attached to the pipe support structure. Submit shop drawing for proposed pipe support structure for guides and anchors for approval of the Structural Engineer. Pipe alignment guides shall be Fig. 255 Grinnell, or as approved equal. Guides shall be sized to accommodate the pipe with insulation. Guides shall be steel factory, fabricated, with bolted two section outer cylinder

and base for alignment of piping and two section guiding spider for bolting to pipe.

- E. Hangers for pipe sizes ½ to 1 ½ inch (13 to 38 mm): Carbon steel, adjustable swivel, split ring.
- F. Hangers for cold pipe sizes 2 inches (50 mm) and over: Carbon steel, adjustable, clevis.
- G. Hangers for cold pipe sizes 2 to 4 inches (50 to 100 mm): Carbon steel, adjustable, clevis.
- H. Hangers for cold pipe sizes 6 inches (150 mm) and over: adjustable steel yoke, cast iron roll, double hanger.
- I. Multiple or Trapeze hangers: Steel channels with welded spacers and hanger rods.
- J. Multiple or Trapeze hangers for hot pipe sizes 6 inches (150 mm) and over: Steel channels with welded spacers and hanger rod, cast iron roll.
- K. Wall support for pipe sizes to 3 inches (76 mm): cast iron hook
- L. Wall support for pipe sizes 4 inches (100 mm) and over: Welded steel bracket and wrought steel clamp.
- M. Wall support for hot pipe sizes 6 inches (150 mm) and over: welded steel bracket and wrought steel clamp with adjustable steel yoke and cast iron roll.
- N. Vertical Support: Steel riser clamp.
- O. Floor support for cold pipe: Cast iron adjustable pipe saddle, lock nut, nipple, floor flange, and concrete pier or steel support.
- P. Floor support for hot pipe sizes to 4 inches (100 mm): Cast iron adjustable pipe saddle, lock nut, nipple, floor flange, and concrete pier or steel support.
- Q. Floor support for hot pipe sizes 6 inches (150 mm) and over: Adjustable cast iron roll and stand, steel screws, and concrete pier or steel support.
- R. Copper pipe support: Carbon steel ring, adjustable, copper plated.
- S. Hanger rods: Mild steel threaded both ends, threaded one end, or continuous threaded.
- T. Inserts: Malleable iron case of galvanized steel shell and expander plug for threaded connection with lateral adjustment, top slot for reinforcing rods, lugs for attaching to forms; size inserts to suit threaded hanger rods.

2.3. VALVES

- A. Provide parts list and assembly drawings (exploded view) for all valves in shop drawing submittals. Provide valves of the same type by the same manufacturer.
- B. Check valves in base mounted pump discharges shall be of the vertical type and shall be

Miller "non-slam" check valves or approved equal suitable for service intended. Check valves in circulator discharges shall be horizontal type.

- C. Provide at each base mounted pump a suction diffuser of size and type shown on drawings. Units shall consist of a cast iron angle type body with inlet vanes, magnetic insert, and blowdown connection tapped gauge post, 125 psi ANSI flange and a combination stainless steel diffuser strainer with 3/16-inch diameter opening for pump protection. Unit shall be equipped with a disposable fine mesh start up strainer which shall be removable after 30 days. Flow direction shall be from inside the strainer to outside for ease of service and cleaning. The body shall fit the pump and connecting pipe size. The unit shall be provided with an adjustable support foot to relieve piping strains from the pump suction. Suction diffuser shall be Taco "SD" Series Catalog 300-4.1, Bell and Gossett Model FLG, Armstrong, or approved equal.
- D. Multi-purpose valve (non-slam check valve, throttling valve, shut-off valves and calibrated balancing valve) shall be provided at discharge side of each constant speed pump. The valve shall be of heavy-duty cast iron construction with standard ANSI flanged connections and rated for a maximum working pressure of 175 psig at 240°F. The valve shall be fitted with a stainless steel stem or stem sleeve and brass seat with "O" ring seal. Valve shall be Taco "Plus One" Number 300-4.2, Bell and Gossett 3DS Triple Duty Valve, Armstrong, or as approved equal, and shall have check and plug valve features plus a memory stop with pointer and scale. Provide additional shut-off valve to allow servicing of check valve if a multipurpose valve is utilized in lieu of separate check, shut-off, and balance valve. Provide additional shut-off valve downstream of multi-purpose valve to allow servicing of multi-purpose check valve feature. Provide pre-manufactured, removable insulation covers for all multipurpose valves.

2.4. STRAINERS

- A. Strainers shall be of the basket or "Y" type and shall be heavy and durable, constructed of best grade gray iron with the bottoms drilled and plugged. Bodies shall have arrows clearly cast on the sides to show flow direction. Strainers shall be equipped with easily removable covers and brass sediment baskets made of brass not less than #22 gauge in thickness. Total area of basket perforations shall be not less than four times the cross section of the entering pipe. Flow shall be into basket, and then out through the perforations. Strainers shall be suitable for water or the intended fluid. Strainers 2 inches and smaller shall have threaded or solder ends, 2 inches and larger shall have flanged ends.
- B. Strainer screens shall be stainless steel with perforations and shall be 1/16-inch for pipe sizes 5 inches and less, 1/8-inch (40 percent open area) perforations for pipe sizes 6-inch and greater.
- C. Provide valved and capped (with chain) blowdowns in each strainer. Blowdown valves shall be Appolo 78-100/200 series or as approved equal.
- D. Strainers shall be manufactured by Watts, Mueller, Armstrong, Yarway, Spirax/Sarco or as approved equal.

2.5. UNIONS, FLANGES, AND COUPLINGS

- A. Unions in steel pipe 2-inches and smaller shall be malleable iron with brass inserted seats designed for a working pressure of 150 psig.
- B. Unions in copper pipe 2-inches and smaller shall be sweat fittings with bronze seats designed for a working pressure of 125 psig.
- C. Flanges for steel pipe over 2 inches shall be 150 psig, forged steel, slip on. Gaskets shall be 1/16 inch thick pre-formed neoprene.
- D. Flanges for copper pipe over 2 inches shall be bronze. Gaskets shall be 1/16 inch thick preformed neoprene.

2.6. MANUAL AIR VENTS

- A. Manual air vents shall be similar to the hereinafter specified gate valves. Provide 1/4-inch size on 3/4-inch pipe and smaller, 1/2 -inch size on 1-inch pipe and larger. Install at all high points of piping. Valves shall be Crane No. 88, or as approved equal, with threaded ends, bronze body, bronze or brass bonnet and bronze stem.

2.7. THERMOMETERS

- A. Unless otherwise indicated, thermometers shall be ASTM E1, in a glass type, organic filled, 9-inch scale size, corrosion-resistant metal case, with "any-angle" mounting with positive locking device. Terice Industrial Thermometers, Weksler Instruments, Ernst Gage Co., Miljoco, or approved equal. Insertion stem length shall suite the pipe size and configuration. Thermometer wells shall be brass with brass union hubs in copper and in ferrous piping. Where piping is insulated or otherwise covered, use wells with lagging extension. Where wells are installed in pipes, use 1/2 inch diameter, increase pipe size so that well does not restrict flow. Accuracy shall be 2 percent.
- B. Unless otherwise indicated, thermometer ranges shall be as follows:
 1. Domestic cold water: 0 degrees F to 100 degrees F, 1 degrees F Division.
 2. Domestic hot and hot water recirculating: 30 degrees F to 180 degrees F, 2 degrees F Division.
- C. Provide heat conducting compound in wells.
- D. At Contractor's option, light powered thermometers may be utilized in lieu of organic filled thermometers.

2.8. PRESSURE GAUGES

- A. Unless otherwise indicated, pressure gauges shall be the bronze bourdon tube type, 4-1/2-inch dial, stem mounting, cast aluminum adjustable pointer, 1 percent accuracy over middle half of scale range, 1-1/2 percent over balance: Terice Model 600C; Weksler Instruments, Ernst Gage Co., Miljoco, or as approved equal.
- B. Gauges shall have pressure, vacuum, compound, or retard ranges as required, select ranges so that the normal readings are at the approximate midpoint and maximum system pressures

do not exceed full scale.

- C. Furnish and install a gauge valve at each pressure gauge. Gauge valves shall be Crane Model No. 88, Needle Valve, Ernst Gage Co. FLG 200, Wexler Instrument Corp. Type BBV4, or approved equal, rated for pressure intended.
- D. Gauge connections for pressure gauges, thermometers, or control instruments shall be made using tee fittings, except that gauge connections up to 1-inch size in steel may be using threaded extra heavy pipe couplings welded directly to the main, provided that the main is at least 2-inch size for 2-inch connections, 3-inch size for 3/4-inch connections, and 4-inch size for 1-inch connections. Minimum gauge connection shall be 2-inch ips.
- E. Provide snubbers on all gauges. Snubbers shall be No. 872 by Trerico, R-1/RS by Wexler Instruments, Miljoco or as approved equal.

2.9. PIPING SPECIALTIES

- A. Furnish and install flexible pipe connections, as specified and/or shown on the drawings, at suction and discharge connections of all base mounted and vertical in-line pumps, all vibrating equipment and elsewhere as shown. Pump flexible connections shall be utilized at all pumps. Refer to Division 23 Section, *Vibration Control for HVAC, Plumbing and Fire Protection Equipment* for specifications.
- B. Pressure relief valves shall be provided in the number and sizes required to relieve 110 percent of the full input to the system. Valves shall be rated; and installed in accordance with ASME, and CSD-1 including all amendments. Pipe discharge full size to floor drain, (with union) and support discharge pipe to prevent exerting any strain on relief valve body, piping to be Type-L copper. Water safety relief valves shall be Watts Series 740, Conbraco, Series 154A, Bell and Gossett, or approved equal. Provide pressure gauge adjacent to all safety relief valves.
- C. Gas relief valve piping shall be sized and installed in accordance with the latest edition of ASME Boiler & Pressure Vessel Code, CSD-1 including amendments. Pipe material shall be as specified for gas piping. Gas relief valve piping material shall be the same as hereinbefore specified for gas piping.

2.10. ESCUTCHEONS

- A. Provide chromium plated escutcheons properly fitted and secured with set screws on all exposed piping which passes through walls, floors or ceilings of finished spaces.
- B. All escutcheon plates shall be chrome plated spun brass of plain pattern, and shall be set tight on the pipe and to the building surface. Plastic escutcheon plates will not be accepted.

2.11. DIELECTRIC CONNECTIONS:

- A. Furnish and install electrically insulated dielectric unions, waterway fittings, or flanges, as manufactured by Victaulic Company, EPCO Sales, Inc., at the following locations:
 - 1. Where steel piping systems join copper piping.

2. Where copper tube connects to domestic water storage tanks, water heaters, heat exchangers, expansion tanks, and other steel vessels.
3. Avoid the installation of steel nipples, cast iron or steel valves and specialties, or other ferrous components in predominately copper piping systems. Where such installation is necessary, isolate the component with dielectric connections. Do not mix steel pipe and copper tube in the same run of pipe or in the same section of a piping system.
4. Dielectric Waterway: Copper silicon casting conforming to UNS C8785 with grooved and/or threaded ends. UL classified in accordance with NSF-61 for potable water service, and shall meet the low lead requirements of NSF-372. Basis of Design: Victaulic Series 647.

2.12. SLEEVES

- A. Sleeves shall be provided around all pipes through walls, floors, ceilings, partitions, roof structure members or other building parts. Sleeves shall be standard weight galvanized iron pipe two sizes larger than the pipe or insulation so that pipe or insulation shall pass through masonry or concrete walls or floors. Provide 20 gauge galvanized steel sheet or galvanized pipe sleeves for all piping passing through frame walls.
- B. Sleeves through floors shall be flush with the floor except for sleeves passing through Equipment Rooms which shall extend 3/4-inch above the floor. Refer to Division 23 Section, *Vibration Controls for HVAC, Plumbing and Fire Protection Equipment* for mechanical equipment room penetration's additional requirements. Space between the pipe and sleeve shall be caulked. Escutcheon plates shall be constructed to conceal the ends of sleeves. Each trade shall be responsible for drilling existing floors and walls for necessary sleeve holes. Drilling methods and tools shall be as hereinbefore specified.
- C. Sleeves through walls and floors shall be sealed with a waterproof caulking compound.
- D. Firestop at sleeves that penetrate smoke barriers smoke partitions and/or rated walls/floors.

2.13. PRESSURE REDUCING VALVES

- A. Provide pressure reducing valves as indicated, of size and capacity selected by the installer to maintain operating pressure on the system. Body shall be cast-iron or bronze construction, renewable stainless steel seat, non-corrosive disc, water tight cage assembly, adjustable pressure ranges and inlet strainer Watts Regulator Model 223-S, Armstrong, Bell and Gossett or as approved equal.
- B. Provide pressure gauge adjacent to all pressure reducing valves to verify proper set point.

2.14. WATER PROOF PIPE PENETRATION SEALS

- A. Provide and install waterproof pipe penetration seals at all pipes that enter the building below grade or through exterior wall.

- B. Link seals are to be Metraflex Metraseals, Model MS, Linkseal, or approved equal, black EPDM seal material, glass reinforced plastic pressure plates, zinc plated nuts and bolts, seals are to be resistant to sunlight and ozone, pressure rated to make a hydrostatic seal of up to 20 psig and up to 40 feet of head, temperature rated from -40 degrees F to 250 degrees F.

2.15. GAS PRESSURE REGULATORS

- A. Gas pressure regulators shall be as manufactured by Equimeter, Inc., Maxitrol Co., Rockwell, Fisher Controls, American Meter Co., or approved equal. Gas pressure regulator shall maintain a constant downstream pressure with a variable inlet pressure.
- B. Gas pressure regulators shall comply with ANSI Z21.18 and shall be single stage, steel jacketed, corrosion-resistant type. Include atmospheric vent, elevation compensator, with threaded ends conforming to ASME B1.20.1 for 2 inch NPS and smaller and flanged ends for 2 ½ inch NPS and larger.
- C. Each pressure regulator shall have an identification stamped on diaphragm cover and shall be painted AGA grey. Regulator inlet and outlet pressures and flow volume in cubic feet per hour of specified gas are as indicated on the contract drawings.
- D. Regulators installed exposed on roof or outside shall be designed and listed for outside installation.

2.16. FLEXIBLE GAS PIPE CONNECTIONS

- A. Description: Comply with AGA LC-1 and include the following:
 - 1. Tubing: Corrugated stainless steel with plastic jacket or coating.
 - 2. Fittings: Copper alloy with ends made to fit corrugated tubing. Include ends with threads according to ASME B1.20.1 if connection to threaded pipe or fittings is required.
 - 3. Striker Plates: Steel, designed to protect tubing from penetrations.
 - 4. Manifolds: malleable iron or steel with protective coating. Include threaded connections according to ASME B1.20.1 for pipe inlet and corrugated tubing outlets.
 - 5. Available Manufacturers:
 - a). OmegaFlex, Inc.
 - b). Titeflex Corp.
 - c). Tru-Flex Metal Hose Corp.
 - d). Ward Industries, Inc.

2.17. TRANSITION FITTINGS

- A. General Requirements:
 - 1. Same size as pipes to be joined.

2. Pressure rating at least equal to pipes to be joined.
 3. End connections compatible with pipes to be joined.
- B. Fitting-Type Transition Couplings: Manufactured piping coupling or specified piping system fitting.
- C. Plastic-to-Metal Transition Fittings:
1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a). Charlotte Pipe and Foundry Company.
 - b). Harvel Plastics, Inc.
 - c). Spears Manufacturing Company.
 2. Description: PVC or CPVC one-piece fitting with manufacturer's Schedule 80 equivalent dimensions; one end with threaded brass insert and one solvent-cement-socket end.
- D. Plastic-to-Metal Transition Unions:
1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a). Colonial Engineering, Inc.
 - b). NIBCO INC.
 - c). Spears Manufacturing Company.
 2. Description: PVC or CPVC four-part union. Include brass threaded end, solvent-cement-joint plastic end, rubber O-ring, and union nut.

2.18. ROOFTOP GAS PIPING SUPPORTS/BASES

- A. Furnish and install rooftop gas piping supports for all piping installed on the roof. Entire system shall be as manufactured by Eberl Iron Works or approved equal.
- B. Bases: The base supports shall be the non-penetrating type preventing need for additional barriers. Base material shall be heavy duty rubber manufactured from 100% recycled ground crumb rubber.
- C. Pipe Supports: The pipe supports shall be elevated pipe roller supports. To allow for expansion and contraction the supports shall include pipe rollers, threaded rods, and supporting hardware. All supports shall be type 304 stainless steel with stainless steel hardware. Furnish with pipe straps to restrain pipes on the rollers.

PART 3. EXECUTION

3.1. GENERAL PIPING INSTALLATION REQUIREMENTS

- A. All pipes shall be cut accurately to measurements established at the building, and shall be worked into place without springing or forcing, properly clearing all windows, doors and other openings. Excessive cutting or other weakening of the building structure to facilitate piping installation will not be permitted. All pipes shall be so installed as to permit free expansion and contraction without causing damage. All open ends of pipe lines, equipment, etc., shall be properly capped or plugged during installation to keep dirt or other foreign material out of the system. All pipes shall be run parallel with the lines of the building and as close to walls, columns and ceilings as may be practical, with proper pitch. All piping shall be arranged so as not to interfere with removal of other equipment or devices not to block access to doors, windows, manholes, or other access openings. Flanges or unions, as applicable for the type of piping specified, shall be provided in the piping at connections to all items of equipment, coils, etc., and installed so that there will be no interference with the installation of the equipment, ducts, etc. All valves and specialties shall be placed to permit easy operation and access and all valves shall be regulated, packed and glands adjusted at the completion of the work before final acceptance. All piping shall be installed so as to avoid air or liquid pockets throughout the work. Ends of pipe shall be reamed so as to remove all burrs.
- B. All piping shall be graded to convey entrained air to high points where automatic air vents shall be provided. The size of supply and return pipes for each piece of equipment shall in no case be smaller than the outlets in the equipment.
- C. All piping shall be run to provide a minimum clearance of 2-inches between finished covering on such piping and all adjacent work. Group piping wherever practical at common elevations.
- D. All valves, strainers, caps, and other fittings shall be readily accessible.
- E. Rough-in and final connections are required to all equipment and fixtures provided under this Contract.
- F. Drain valves with hose connections shall be provided at low points for drainage of piping system. Blow down valves shall be provided at the ends of all mains and branches so as to properly clean by blowing down the lines throughout in the direction of normal flow.
- G. Discharge lines from all relief valves shall be piped to within 4-inches of floor and extend to floor drains wherever floors are not pitched to drains. Pitch the relief valve piping away from the relief valve to insure that no fluid can be trapped in valve discharge. Support all relief valve piping to prevent exerting strain on the relief valve body. The end of the relief valve discharge piping shall not be threaded to prevent capping or plugging.
- H. All branches from water mains shall be taken from the top of the supply mains at an angle of forty-five (45) degrees above the horizontal, unless otherwise directed. Branches feeding down shall be taken from the side or bottom of the main on water mains only. All connections shall be carefully made to insure unrestricted circulation, eliminate air pockets or trapped condensate, and permit the complete drainage of the system.
- I. Cutoff valves shall be provided on each branch line from the mains on all plumbing lines.

- J. Shut-off valves shall be installed at the inlet and outlet of each piece of equipment to permit isolation for maintenance and repair.
- K. Balancing valves shall be installed in all domestic re-circulating systems and at all pumps, and where indicated on the drawings.
- L. Unions shall be installed on all bypasses, at all connections to equipment, where shown on drawings or where required to facilitate removal of equipment whether shown or not.
- M. Spring clamp plates (escutcheons) shall be provided where pipes are exposed in the building and run through walls, floors, or ceilings. Plates shall be chrome plated spun brass or plain pattern, and shall be set tight on the pipe and to the building surface.
- N. If the size of any piping is not clearly evident in the drawings, the Contractor shall request instructions for the Engineer as to the proper sizing. Any changes resulting from the Contractor's failure to request clarification shall be at his expense. Where pipe size discrepancies or conflicts exist in the drawings, the larger pipe size shall govern.
- O. Install all valves with stem upright or horizontal, not inverted.
- P. Where pipe support members are welded to structural building framing, scrape, brush clean, weld and apply one coat of zinc rich primer.
- Q. Provide clearance for installation of insulation and access to valves and fittings.
- R. Protect piping systems from entry of foreign materials by temporary covers, completing sections of the work, and isolating parts of completed system.
- S. All water containing pipes shall be routed clear of combustion air dampers and louvers to prevent freezing conditions when dampers are open.
- T. Provide manual air vents at top of piping systems.
- U. Where access doors are required, install piping so that valves can be grouped together to minimize the quantity of access doors.
- V. Install manufactured U.L. listed firestop collars at all floor/wall penetrations for all PVC and CPVC pipe penetrations.

3.2. THERMOMETER AND PRESSURE GAGE INSTALLATION REQUIREMENTS.

- A. Install thermometers and adjust vertical and tilted positions.
- B. Install separable sockets in vertical position in piping tees where fixed thermometers are indicated.
 1. Install with socket extending to one-third diameter of pipe.
 2. Fill sockets with oil or graphite and secure caps.

- C. Install pressure gages in piping tees with pressure-gage valve located on a pipe at most readable location.
- D. Adjust faces of thermometer and gages to proper angle for best visibility.
- E. Clean windows of thermometer and gauges and clean factory-finished surfaces. Replace cracked and broken window, and repair scratched and marred surfaces with manufacturer's touch up paint.

3.3. VALVE INSTALLATION REQUIREMENTS

- A. Examine piping system for compliance with requirements for installation tolerances and other conditions affecting performance of valves. Do not proceed with installation until unsatisfactory conditions have been corrected.
- B. Examine valve interior for cleanliness, freedom from foreign matter, and corrosion. Remove special packing materials, such as blocks, used to prevent disc movement during shipping and handling.
- C. Operate valves from fully open to fully closed positions. Examine guides and seats made accessible by such operation.
- D. Examine threads on valve and mating pipe for form and cleanliness.
- E. Examine mating flange faces for conditions that might cause leakage. Check bolting for proper size, length, and material. Check gasket material for proper size, material composition suitable for service, and freedom from defects and damage.
- F. Examine grooved ends for form and cleanliness. Grooved ends shall be clean and free from indentations, projections, and roll marks in the area from pipe end to groove.
- G. Do not attempt to repair defective valves; replace with new valves.
- H. Install valves as indicated, according to manufacturer's written instructions.
- I. Piping installation requirements are specified in other Division 22 Sections. Drawings indicate the general arrangement of piping, fittings, and specialties.
- J. Install valves with unions or flanges at each piece of equipment arranged to allow servicing, maintenance, and equipment removal without system shutdown.
- K. Locate valves for easy access and provide separate support where necessary.
- L. Install valves in horizontal piping with stem at or above the center of the pipe.
- M. Install valves in a position to allow full stem movement.
- N. Adjust or replace packing after piping systems have been tested and put into service, but before final adjusting and balancing. Replace valves if leak persists.

3.4. WASTE AND VENT PIPING INSTALLATION REQUIREMENTS

- A. Each pipe shall be laid true to line and grade and in such manner as to form a close concentric joint with the adjoining pipe and to prevent sudden offsets of the flow line. All pipe when laid shall rest on the full length of the barrel and bell holes shall be dug in trench bottoms to make joints. Pipe shall not be adjusted to grade by use of block or wedges. Where rock or old foundations are encountered, trenches shall be excavated 6-inches below grade and crusher run limestone shall be used as a bedding material to support barrel of pipe.
- B. As the work progresses, the interior of the sewer shall be cleared of all dirt and surplus materials of every description.
- C. Trenches shall be kept free from water until the pipe jointing material has set and pipe shall not be laid when the conditions of the trench or the weather is unsuitable for such work. At all times, when work is not in progress, all open ends of pipe and fittings shall be securely closed to the satisfaction of the Engineer, so that no trench water, earth or other substance will enter the pipe or fittings.
- D. Slip joints will be permitted only in trap seals or on the inlet side of the trap. Unions on the sewer side of the trap shall be ground faced, and shall not be concealed or enclosed. Install bell and spigot pipe with bell end upstream.
- E. Threaded joints shall be American Standard taper screw threads with permacel joint compound applied to the male thread. Connections between threaded pipe and cast iron pipe shall have a ring or half coupling screwed on to form a spigot end on the threaded pipe.
- F. Establish invert elevations, slopes for drainage to 1/8 inch per foot. Maintain gradients.

3.5. PIPE JOINTS INSTALLATION REQUIREMENTS

- A. Welded Joints: Joints in piping 2-1/2-inches and larger shall be fusion welded. Welding shall be in accordance with recommendations of the American Welding Society. Welding fittings shall conform in physical and chemical properties to the latest revisions of the American Society for Testing Materials.
- B. Qualify welding procedures, welders and operators in accordance with ASME B31.1, or ASME B31.9 as applicable, for shop and project site welding of piping work. Certify welding of piping work using Standard Procedure Specifications by, and welders tested under supervision of, National Certified Pipe Welding Bureau (NCPWB). Submit welders qualifications for approval.
- C. Grooved Joints: Grooved joint shall be installed in accordance with the manufacturer's written recommendations. Grooved ends shall be clean and free from indentations, projections, or roll marks. The gasket shall be molded and produced by the coupling manufacturer of an elastomer suitable for the intended service. The coupling manufacturer's factory trained representative shall provide on-site training for the contractor's field personnel in the use of grooving tools and installation of product. The representative shall periodically visit the job site to ensure best practices in grooved product installation are being followed. (A distributor's representative is not considered qualified to conduct the training.)

- D. Screwed Joints: All screwed joints shall be made with tapered threads properly cut. Screwed joints shall be made perfectly tight with a stiff mixture of graphite and oil, applied with a brush to the male threads on the fittings.
- E. Soldered Joints and Copper Piping: Joints in copper piping shall conform to the following minimum standards.
1. The pipes shall be cut to a length making certain that the ends are square, using a fine hacksaw blade or tube cutter. The ends of all pipes shall be reamed and all burrs removed.
 2. The outside end of the pipe and the cut end of the fitting shall be cleaned with steel wool, sand cloth, or steel wire brush. All dark spots shall be removed.
 3. The flux shall be applied evenly and sparingly to the outside end of the pipe and the inside of the outer end of the fitting until all surfaces to be jointed are completely covered. The piping and fitting shall be slipped together and reworked several times to insure an even distribution of the flux.
 4. The correct amount of solder per joint for each size pipe shall be used in accordance with the manufacturer's recommendations.
 5. Solder joints shall be made by using a direct flame from a torch.
 6. On pipe sizes larger than 1/4 inch, the fittings and valves in the pipe shall be moved or tapped with a hammer when the solder starts to melt to insure an even distribution of the solder.
 7. The excess solder shall be removed while it is still in the plastic state leaving a fillet around the top of the fitting.
 8. Solder joints shall be suitable for working pressure of 100 psig and for working temperature of not less than 250 degrees F. The type of solder and flux used will be submitted for approval. Type 95-5 shall be the minimum standard.
 9. Lead and antimony-based solders shall not be used for potable water systems. Brazing and silver solders are acceptable.
- F. Where copper piping joins steel piping, approved bronze adapters shall be used.
- G. Prohibited Connections: No direct weld, soldered, or brazed connections, without unions or flanges, shall be made to valves, strainers, apparatus, or related equipment. Right and left couplings, long threads, or caulking of pipe threads or gasket joints will not be permitted.
- H. Mechanical specification for mechanical joint for cast iron pressure pipe & fittings, ANSI A21.11.
- I. When installing gas piping which is to be concealed (i.e., in walls), unions, tube fittings, running threads, right- and left-hand couplings, bushings, and swing joints made by

combination of fittings shall not be used. All concealed piping within walls shall be welded.

1. Gas Piping
2. Final Gas Connections: Unless otherwise specified herein, final connections shall be made with rigid metallic pipe and fittings.
3. Pipe Joints:
 - a). Pipe joints shall be designed and installed to effectively sustain the longitudinal pull-out forces caused by contraction of the piping or superimposed loads.
 - b). Threaded Metallic Joints: Threaded joints in metallic pipe shall have tapered threads evenly cut and shall be made with an approved graphite joint sealing compound for gas service. After cutting and before threading, pipe shall be reamed and burrs shall be removed. Caulking of threaded joints to stop or prevent leaks shall not be permitted.
 - c). Welded Metallic Joints: Beveling, alignment, heat treatment, and inspection of welds shall conform to ASME B31.2. Weld defects shall be removed and repairs made to the weld, or the weld joints shall be entirely removed and rewelded. After filler metal has been removed from its original package, it shall be protected or stored so that its characteristics or welding properties are not affected adversely. Electrodes that have been wetted or have lost any of their coating shall not be used.
 - d). Thermoplastic Joints: Jointing procedures shall conform to AGA 01. Solvent cement or heat of fusion joints shall not be made between different kinds of plastics.
 - e). Joining Thermoplastic to Metallic Piping: When compression-type mechanical joints are used, the gasket material in the fittings shall be compatible with the plastic piping and with the gas in the system. An internal tubular rigid stiffener shall be used in conjunction with the fitting, and the stiffener shall be flush with the end of the pipe or tubing and shall extend at least to the outside end of the compression fitting when installed. The stiffener shall be free of rough or sharp edges and shall not be a force fit in the plastic. A split tubular stiffener shall not be used.
 - f). Special Requirements; Drips, grading of the lines, freeze protection, and branch outlet locations shall be as shown and shall comply with NFPA 54 and/or NFPA-58.
 - g). Install containment conduits for gas piping below slabs, within building, in gastight conduits extending minimum of 4 inches (100mm) outside building, and vented to atmosphere. Terminate vents with turned-down, reducing-elbow fittings with corrosion-resistant insect screens in large end. Prepare and paint outside of conduits with coal-tar epoxy-polyamide paint according to SSPC-Paint 16.

- h). Install gas meter per manufacturer's requirements.
 - i). Install metal shut-off valves upstream and downstream of gas meter with full size normally closed bypass valve.
 - j). Install strainer on inlet of gas meter.
4. Install concrete filled, steel, schedule 40, painted pipe bollards around gas meter and regulator.
- J. Plastic piping solvent cement joints: Clean and dry joining surfaces. Join pipe and fittings according to the following:
- 1. Comply with ASTM F 402 for safe handling practices of cleaners, primers, and solvent cements. Apply primer.
 - 2. PVC Piping: Join according to ASTM D2855.
 - 3. CPVC Piping: Join according to ASTM D2846/D 2845M Appendix.

3.6. HANGERS AND SUPPORTS INSTALLATION REQUIREMENTS

- A. General: All hangers shall be of an approved type arranged to maintain the required grading and pitching of lines to prevent vibration and to provide for expansion and contraction. Provide protection saddles between hangers and insulation on heating water insulated pipe. Saddles shall be Grinnells Figure 173/275 or approved equal. Provide approved spacers between saddles and pipe where flexible insulation is specified. Provide insulation protection shields for insulated piping without saddles. Shield shall be Grinnell Figure 167 or as approved equal.
- B. Spacing: Regardless of spacing, hangers shall be provided at or near all changes in direction, both vertical and horizontal, for all piping. For cast iron soil pipe, one hanger shall be placed at each hub or bell.
- C. Vertical Lines: Shall be supported at their bases, using either a suitable hanger placed in a horizontal line near the riser, or a base type fitting set on a pedestal, foundation or support. All vertical lines extending through more than one floor level shall be supported at each floor with a riser clamp. Riser clamp shall be Grinnell Co.'s Figure 261, or approved equal. All vertical drops to pump suction elbows shall be supported by floor posts.
- D. Racks and Brackets: All horizontal piping on vertical walls shall be properly supported by suitable racks securely anchored into the wall construction. Where not practical to obtain ceiling anchorage, all piping near walls shall be supported by approved brackets securely anchored into the wall construction. Washer plates (Fib. 60, 60L) and other miscellaneous attachments, fasteners, etc., shall be Grinnell or as approved equal. All exterior hanger and bracket systems in their entirety shall be galvanized.
- E. Pipe Hangers and supports shall be attached to the panel point at the top chord of bar joist or at a location approved by the structural engineer.
- F. Select hangers and components for loads imposed. Secure rods with double nuts.

- G. Support of horizontal piping shall allow for vertical adjustment after installation of piping.
- H. Support overhead piping with clevis hangers.
- I. Do not support all parallel piping from the same joist. Stagger all supports in accordance with the structural engineer's recommendations.
- J. Refer to structural documents for appropriate connection/attachment materials to building.

3.7. AIR VENTING INSTALLATION REQUIREMENTS

- A. The top of each plumbing piping system and other points as indicated, where necessary for the removal of air from the system or equipment, shall be vented using an approved type of manual air vent.
- B. In addition to manual air vents at high points of system, each item of water heat transfer equipment shall be manually vented using an approved type manual air vent. All air vents shall be accessible.

3.8. DIRT POCKETS INSTALLATION

- A. Dirt pockets shall be installed at the base of all risers and ahead of all gas equipment and as indicated on the drawings.

3.9. EXPANSION LOOPS AND SWING CONNECTION INSTALLATION REQUIREMENTS

- A. Install expansion fittings according to manufacturer's written instructions.
- B. Install expansion fittings in sizes matching pipe size in which they are installed.
- C. Align expansion fittings to avoid end-loading and torsional stress.
- D. Install pipe bends and loops cold-sprung in tension or compression as required to partly absorb tension or compression produced during anticipated change in temperature.
- E. Attach pipe bends and loops to anchors.
 - 1. Steel Anchors: Attach by welding. Comply with ASME B31.9 and ASME Boiler and Pressure Vessel Code: Section IX, "Welding and Brazing Qualifications."
 - 2. Concrete Anchors: Attach by fasteners. Follow fastener manufacturer's written instructions.
- F. Connect risers and branch connections to mains with at least five pipe fittings, including tee in main.
- G. Connect risers and branch connections to plumbing equipment with at least four pipe fittings, including tee in riser.
- H. Connect mains and branch connections to plumbing equipment with at least four pipe

fittings, including tee in main.

3.10. PIPING IDENTIFICATION REQUIREMENTS

- A. All piping shall be identified with painted background marked with the name of the service with arrows to indicate flow direction. Color code and system identification shall comply with ANSI Standards and piping identification system shall comply with ASME A13.1-87 scheme for the identification of piping systems and ASHRAE Fundamentals Handbook, latest edition.
- B. Markings shall be plain block letters, stenciled on pipes, and shall be located near each branch connection, near each valve, and at least every 10 feet on straight runs of pipe. Where pipes are adjacent to each other, markings shall be neatly lined up. All markings shall be located in such manner as to be easily legible from the floor. Pipe identification schedule shall be as follows:

OUTSIDE DIAMETER OF PIPE OR COVERING (INCHES)	LENGTH OF COLOR FIELD (INCHES)	SIZE OF LETTERS (INCHES)
½ to 1 ¼	8	½
1-½ to 2	8	¾
2 ½ to 6	12	1 ¼
8 to 10	24	2 ½
Over 10	32	3 ½

3.11. VALVE IDENTIFICATION REQUIREMENTS

- A. All valves shall be tagged with a numbered tag.
- B. The tags shall be made of 1-inch diameter brass tags fastened to the valve by means of brass chains. Numbers shall agree with valve numbers on diagrammatic herein before specified.
- C. Provide a minimum of six (6) valve charts with valve numbers indicating valve type, size, manufacturer and service.
- D. Additional valve charts shall be mounted behind glazed wooden frames and be hung in each mechanical equipment room including each air handling unit mechanical equipment room. Additional copies shall be provided in each copy of the O&M manuals.

3.12. CLEANING PIPING AND EQUIPMENT

- A. All water, plumbing piping, and pumped condensate systems shall be cleaned by filling with a solution of one (1) pound of trisodium phosphate to each 50 gallons of water and circulating this solution for a period of six (6) hours during which time the system shall reach operating temperature. The systems shall then be flushed with fresh water and refilled with fresh water purged of all air.

- B. All water, plumbing, and pumped condensate piping system shall be flushed clean with fresh water. See Division 22 Sections, *Plumbing Fixture* and *Plumbing Equipment* for domestic potable water cleaning and sterilization.

3.13. PRESSURE SEAL FITTING INSTALLATION REQUIREMENTS

- A. Viega, ProPress Pressure Seal bronze, or copper fittings: Sealing element shall be verified for the intended use. Tube ends shall be cut on a right angle (square) to the tube. Tube end shall be reamed and chamfered, all grease oil or dirt shall be removed from the tube end with a clean rag. Visually examine the fitting sealing element to ensure there is no damage and it is properly seated into the fitting. Utilizing a Viega Insertion Depth Inspection Gauge mark the tube wall, with a felt tip pen, at the appropriate location, or insert the tube fully into the fitting and mark the tube wall at the face of the fitting. Always examine the tube to ensure it is fully inserted into the fitting prior to pressing the joint. ProPress fittings shall be installed according to the most current edition of the Viega installation guidelines. Installers shall attend a Viega ProPress installation training class.
- B. After ProPress Pressure seal fittings have been installed a "two step test" shall be followed. Pressurize the system with application appropriate test medium, water between 15 and 85 psi, or air/dry nitrogen between .5 and 45 psi. Check the pressure gauge for pressure loss. If the system does not hold pressure, walk the system and check for un-pressed fittings. Should you identify an un-pressed ensure the tube is fully inserted into the fitting and properly marked, prior to pressing the joint. After appropriate repairs have been made, retest the system per local code, or specification requirements, not to exceed 600 psi with water or 200 psi when using air.

END OF SECTION

SECTION 22 07 01

PLUMBING INSULATION

PART 1. GENERAL

1.1. REFERENCE

- A. The Conditions of the Contract and other General Requirements apply to the work specified in this Section. All work under this Section shall be subject to the requirements of Division 22 Section, *Common Work Results for Plumbing*.
- B. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2. DESCRIPTION

- A. All piping and equipment installed under this Contract shall be covered as specified.

1.3. SCOPE

- A. The work covered by this specification consists of furnishing all labor, equipment, materials and accessories, and performing all operations required, for the correct fabrication and installation of thermal insulation applied to all piping, equipment, and systems, in accordance with applicable project specifications and drawings, subject to the terms and conditions of the contract.

1.4. STANDARDS

- A. Thermal insulation materials shall meet the property requirements of one or more of the following specifications as applicable to the specific product or use:
 - 1. American Society for Testing of Materials Specifications:
 - a). ASTM C 547, "Standard Specification for Mineral Fiber Preformed Pipe Insulation".
 - b). ASTM C 533, "Standard Specification for Calcium Silicate Pipe & Block Insulation".
 - c). ASTM C 55, "Standard Specification for Mineral Fiber Blanket and Felt Insulation".
 - d). ASTM E 96, "Standard Test Methods for Water Vapor Transmission of Materials".
 - e). ASTM C 585, "Recommended Practice for Inner and Outer Diameters of Rigid Pipe Insulation for Nominal Sizes of Pipe and Tubing (NPS System)".

- f). ASTM C 612, "Standard Specification for Mineral Fiber Block and Board Thermal Insulation".
 - g). ASTM C 1136, "Standard Specification for Barrier Material, Vapor, "Type 1 or 2 (Jacket only).
 - h). ASHRAE 90.1 "Energy efficient design of new buildings except low-rise residential buildings", latest edition.
- B. Insulation materials, including all weather and vapor barrier materials, closures, hangers, supports, fitting covers, and other accessories, shall be furnished and installed in strict accordance with project drawings, plans, and specifications.

1.5. SYSTEM PERFORMANCE

- A. Insulation materials furnished and installed hereunder should meet the minimum economic insulation thickness requirements of the North American Insulation Manufacturers' Association (NAIMA) (formerly known as TIMA), to ensure cost-effective energy conservation performance. Alternatively, materials should meet the minimum thickness requirements of National Voluntary Consensus Standard 90.1, (latest edition) and "Energy Efficient Design of New Buildings," of the American Society of Heating, Refrigeration, and Air-Conditioning Engineers (ASHRAE), latest edition. However, if other factors such as condensation control or personnel protection are to be considered, the selection of the thickness of insulation should satisfy the controlling factor. As minimum, all insulation thicknesses shall be as hereinafter specified.
- B. Insulation materials furnished and installed hereunder shall meet the fire hazard requirements of any one of the following specifications:
- | | | |
|----|---|-----------|
| 1. | American Society for Testing of Materials | ASTM E 84 |
| 2. | Underwriters' Laboratories, Inc. | UL 723 |
| 3. | National Fire Protection Association | NFPA 255 |
- C. Calcium silicate products shall include a visual identification system to permit positive field determination of their asbestos-free characteristics.

1.6. QUALITY ASSURANCE

- A. Insulation materials and accessories furnished and installed hereunder shall, where required, be accompanied by manufacturers' current submittal or data sheets showing compliance with applicable specifications listed in Section 1.4 above.
- B. Insulation materials and accessories shall be installed in a workmanlike manner by skilled and experienced workers who are regularly engaged in commercial insulation work.

1.7. DELIVERY AND STORAGE OF MATERIALS

- A. All of the insulation materials and accessories covered by this specification shall be delivered to the job site and stored in a safe, dry place with appropriate labels and/or other product identification.
- B. The Contractor shall use whatever means are necessary to protect the insulation materials and accessories before, during, and after installation. No insulation material shall be installed that has become damaged in any way. The Contractor shall also use all means necessary to protect work and materials installed by other trades.
- C. If any insulation material has become wet because of transit or job site exposure to moisture or water, the Contractor shall not install such material, and shall remove it from the job site. An exception may be allowed in cases where the Contractor is able to demonstrate that wet insulation when fully dried out (either before installation, or afterward following exposure to system operating temperatures) will provide installed performance that is equivalent in all respects to new, completely dry insulation. In such cases, consult the insulation manufacturer in writing for technical assistance.
- D. Maintain ambient temperatures and conditions required by manufacturers of adhesives, mastics, and insulation cements. Protect all insulation from water, construction traffic, dirt, chemical and mechanical damage.

1.8. ALTERNATES

- A. Refer to Division 01 Section, *Alternates* for description of work under this section affected by alternates.

PART 2. PRODUCTS

2.1. GENERAL

- A. All materials to be insulated shall be thoroughly cleaned, after completion of successful tests, and shall be covered as specified below. Fiberglass insulation shall be Owens-Corning, Manville, Armstrong, or P.P.G, or as approved equal.

2.2. PIPE INSULATION MATERIALS

- A. Unless otherwise noted, insulation shall be one piece or half sectional molded fibrous glass with "K" rating of .23 at 75 degrees F mean temperature, for service temperatures between 60 degrees F and +450 degrees F with all service poly-encapsulated jacket. Pipe insulation shall be fiberglass ASJmax SSL II with double closure system as manufactured by Owens Corning, Johns Manville, Knauf or approved equal.
- B. Unless otherwise noted, pipe insulation jacket shall be factory-applied vinyl coated, embossed and reinforced vapor barrier laminate, with a perm rating of not more than 0.02 perms. All hot and cold, concealed and exposed butt strips shall be of the same material as the jacket. Jacket and butt strips shall be sealed with field-applied Foster 85-20/85-50 or Childers CP-82 (5 gallon cans only) adhesive. Jacket and butt strips shall be off-white color and shall be equivalent to Owens-Corning Fiberglass 25-ASJ.

- C. For fittings on all piping, valves, and flanges, apply fiberglass molded or segmented insulation equal in thickness to the adjoining insulation and securely fasten in place using wire. Cold piping: Apply a tack coat of vapor barrier coating and reinforcing mesh. After ½ hour, apply second coat of same vapor barrier coating, UL labeled, Type C, for cold water piping. Hot piping Type H for hot water piping: Apply tack of breather mastic. Wrap fitting with fiberglass reinforcing cloth overlapping adjoining sections of pipe insulation by 2-inches. Apply a second coat of breather mastic over the reinforcing cloth, working it to a smooth finish. As an option to the above hot fittings, a polyvinyl chloride fitting cover may be supplied.
- D. All pipe insulation, jackets, or facings, and adhesives used to adhere jacket or facing to the insulation, including fittings and butt strips, shall have non-combustible fire and smoke hazard system rating and label as tested by ASTM E-84, NFPA 225, and UL 73, not exceeding Flame Spread 25, Fuel Contributed 50, Smoke Developed 50. Accessories such as adhesives, mastic cements, tapes and cloth for fittings shall have the same ratings as listed above. All products or their shipping cartons shall bear the manufacturer's label indicating that flame and smoke ratings do not exceed the above criteria.
- E. For piping having a vapor barrier insulation and for an insulated piping requiring supports, hangers and supports shall be installed outside the insulation. Wherever hangers and supports are installed outside the insulation, pipe insulation protecting shields shall be provided. Where insulation is a load bearing material, of sufficient strength to support the weight of the piping, pipe shields one third the circumference of the insulation and of a length not less than three times the diameter of the insulation (maximum length 24-inches) shall be provided. Insulation of 7-1/4 pound or greater density will be considered as load bearing for pipe sizes up to and including 2-inches. Where insulation is not of sufficient strength to support the weight of the piping, a half section of high density fiberglass or foam inserts, shall be provided. Vapor barrier and finish shall be applied as required to match adjoining insulation. In addition, shields shall be furnished as specified above.
- F. For piping located outside of the building, a corrugated aluminum weatherproof jacketing system shall be provided. This system shall be Micro-Lot ML as manufactured by Manville, Polyweld by Pabco Metals Corp., Childers, or as approved equal, and installed per the manufacturer's recommendations. Where outdoor piping is receiving electric heat tape, the insulation shall be oversized so that the heat tape is not compressed tightly to the pipe. Pipe jacketing shall be corrugated (3/16-inch) deep aluminum, .016-inch thickness of H-14 temper with aluminum strapping of .75-inch width and .020 inch thickness with moisture barrier. Aluminum jacketing elbows shall be smooth, .016-inch thickness and 1100 alloy. All jacketing shall have an integrally bonded moisture barrier over the entire surface in contact with the insulation. Longitudinal joints shall be applied so they will shed water and shall be sealed completely and shall be sealed completely with metal jacketing sealant. Sealant shall be Foster 95-44 or Childers CP-76. Circumferential joints shall be closed using preformed butt strips following manufacturer's recommendations for securement. Jacket seams shall be located on the bottom side of the horizontal piping.
- G. All disturbed piping insulation in existing areas shall be re-insulated with insulation type, density, and thickness as specified for new piping. Insulation damaged due to new work and demolition only shall be replaced unless otherwise noted.

- H. On cold systems such as domestic cold water, vapor barrier performance is extremely important. All penetrations and seams of the ASJ and exposed ends of insulation must be sealed with vapor barrier coating. The ASJ must be protected with either a vapor barrier coating or a suitable vapor retarding outer jacket. Vapor seals at butt joints shall be applied at every fourth pipe section joint and at each fitting to provide isolation of water incursion. Vapor Barrier Coating: Foster 30-65; Childers CP-34 or Vimasco 749. Permeance shall be 0.03 perms or less at 45 mils dry at test by ASTM E96.
- I. Fittings and valves shall be insulated with pre-formed fiberglass fittings, fabricated sections of Fiberglass pipe insulation, Fiberglass pipe and tank insulation, Fiberglass blanket insulation, or insulating cement. Thickness shall be equal to adjacent pipe insulation. Finish shall be with pre-formed PVC fitting covers or as otherwise specified on contract drawings. Where applicable, Victaulic PVC fitting valve and coupling covers shall be utilized. Victaulic PVC covers shall be installed with matching pipe insulation jacketing material, vinyl tape, solvent weld adhesive and appropriate fasteners.
1. Flanges, couplings and valve bonnets shall be covered with an oversized pipe insulation section sized to provide the same insulation thickness as on the main pipe section. An oversized insulation section shall be used to form a collar between the two insulation sections with low density blanket insulation being used to fill gaps. Jacketing shall match that used on straight pipe sections. Rough cut ends shall be coated with a suitable weather or vapor resistant mastic as dictated by the system location and service. Finish valve installation with a Tyvac jacket with ends that secure to adjacent piping.
 2. On hot systems where fittings are to be left exposed, insulation ends should be beveled away from bolts for easy access.
 3. On cold systems, particular care must be given to vapor sealing the fitting cover or finish to the pipe insulation vapor barrier. All valve stems must be sealed with caulking which allows free movement of the stem but provides a seal against moisture incursion. All gauge and thermometer penetrations and extensions shall be correctly sealed and insulated to prevent surface condensation.
- J. All piping shall be supported in such a manner that neither the insulation or the vapor/weather barrier is compromised by the hanger or the effects of the hanger. In all cases, hanger spacing must be such that the circumferential joint may be made outside the hanger. On cold systems, vapor barrier must be continuous, including material covered by the hanger saddle.
1. Piping systems 3-inches (7.5cm) in diameter or less, insulated with Fiberglass insulation, may be supported by placing saddles of the proper length and spacing, as designated in Owens-Corning Pub. 1-IN-12534, under the insulation. Hangers saddles shall be minimum 16 gauge with a saddle arc of 120 degrees minimum.
 2. For hot or cold piping systems larger than 3-inches (7.5 cm) in diameter, operating at temperatures less than +200 degrees F (93 degrees C) and insulated with fiber glass, high density inserts such as foam with sufficient compressive strength shall be used to support the weight of the piping system. At temperatures exceeding +200

degrees F (93 degrees C), Owens-Corning Pink or IIG, Calcium Silicate pipe insulation shall be used for high density inserts.

3. Owens-Corning Pink Calcium Silicate pipe insulation may be used to support the entire weight of the piping system provided the hanger saddle is designed so the maximum compressive load does not exceed 100 psi (7kg/cm).
4. Where pipe shoes and roller supports are required, insulation shall be inserted in the pipe shoe to minimize pipe heat loss. Where possible, the pipe shoe shall be sized to be flush with the outer pipe insulation diameter.
5. Thermal expansion and contraction of the piping and insulation system shall generally be taken care of by utilizing double layers of insulation and staggering both longitudinal and circumferential joints. Where long runs are encountered, expansion joints may be required where single layers of insulation are being used and should be so noted on the contract drawings.
6. On vertical runs, insulation support rings shall be used.

2.3. PIPING INSULATION THICKNESSES SCHEDULE

- A. All piping shall be insulated with pipe insulation of the thicknesses indicated below:

PIPING INSULATION THICKNESSES SCHEDULE SERVICES	THICKNESS
All Drain Piping from Cooling Coils/Evaporators	½-inch thickness
All Domestic Hot and Cold Water Piping , including Re-circulating Piping	1-inch thickness
Above Grade Air Priming Lines	½ -inch thickness

2.4. EQUIPMENT INSULATION MATERIALS AND THICKNESSES

- A. The following equipment shall be insulated with Fiberglass Rigid Board Insulation or Foam Plastic Insulation:

1. Domestic Water Meters.
2. Backflow Preventer Valve Bodies.
3. Plumbing Pumps.
4. All Pump Volutes and Strainers.
5. Make-up Water Valve Bodies

- B. Insulation for cold surfaces shall be 1-1/2-inch thickness, 6 lb. density, 705 FRK with a "K" rating of .23 at 75 degrees F mean temperature. Insulation for hot surfaces except as

otherwise noted shall be 1-1/2-inch thickness, 6 lb. density, 705 with a "K" rating of .23 at 75 degrees F mean temperature. Insulation shall be applied with staggered joints firmly butted and joined. The insulation shall be held in place by steel bands. Bands shall be 1-inch by 25 gauge galvanized steel spaced on not over 12-inch centers. All joints and voids shall be filled with Owens-Corning #110 cement, well troweled into openings. For 705 FRK insulation, all joints and voids shall be FRK taped and vapor sealed. There shall be applied over the insulation surface 1-inch galvanized wire netting laced together at all edges and wired to the steel bands with 16 gauge soft annealed wire. Over this shall be applied 2-inch thick layer of Owens-Corning #110 cement applied in two layers. Install metal corner beads at all corners and edges in order to provide a permanent installation. Onto the dry cement surface apply a brush coat of Foster Sealfas 30-36 or Childers CP-50AMV1 lagging adhesive at the rate of 60-70 square feet per gallon. Embed into wet coating a layer of 8 ounce canvas smoothed out to avoid wrinkles and lap all seams a minimum of 2-inches. Apply a second brush coat of Sealfas 30-36 or Childers CP-50 AMV1 lagging adhesive to the entire surface at the rate of 60-70 square feet per gallon. Cleanouts, nameplates, and manholes shall not be insulated, and the insulation on surrounding surfaces shall be neatly beveled off at such openings.

C. Insulation Installation on Pumps:

1. Fabricate metal boxes lined with insulation. Fit boxes around pumps and coincide box joints with splits in pump casings. Fabricate joints with outward bolted flanges. Bolt flanges on 6-inch (150-mm) centers, starting at corners. Install 3/8-inch- (10-mm-) diameter fasteners with wing nuts. Alternatively, secure the box sections together using a latching mechanism.
2. Fabricate boxes from aluminum at least 0.040 inch (1.0 mm) thick.
3. For below ambient services, install a vapor barrier coating at seams, joints, and penetrations. Seal between flanges with replaceable gasket material to form a vapor barrier.

D. Mechanical fasteners shall be utilized to hold insulation to surface with bands as required to hold the curvature of the material.

E. Support rings shall be provided to support the top head insulation where required.

F. Outdoor installations require a weather barrier mastic for protection of the insulation jacketing.

G. Insulation types materials shall be suitable for temperatures encountered by each item of equipment.

2.5. ACCESSORY MATERIALS

A. Accessory materials installed as part of insulation work under this section shall include, but not be limited to:

1. Closure Materials - Butt strips, bands, wires, staples, mastics, adhesives; pressure-sensitive tapes.

2. Field-applied jacketing materials - sheet metal, plastic, canvas, fiber glass cloth, insulating cement; PVC fitting covers, PVC jacketing.
 3. Support Materials - Hanger straps, hanger rods, saddles.
 4. Fasteners, weld pins/studs, speed clips, insulation washers.
 5. Metal mesh or expanded metal lagging.
- B. All accessory materials shall be installed in accordance with project drawings and specifications, manufacturer's instructions, and/or in conformance with the current edition of the Midwest Insulation Contractors Association (MICA) "Commercial & Industrial Insulation Standards."

2.6. FIELD-APPLIED JACKET

- A. Field-applied jackets shall comply with ASTM C 921, Type I unless otherwise indicated.
- B. PVC Jacket: High-impact-resistant, UV-resistant PVC complying with ASTM D 1784, Class 16354-C; thickness as scheduled; roll stock ready for shop or field cutting and forming. Thickness is indicated in field-applied jacket schedules.
1. Products: Subject to compliance with requirements, available products that may be incorporated into the Work include, but are not limited to, the following:
 - a). Johns Manville; Zexon.
 - b). P.I.C. Plastics, Inc; FG Series.
 - c). Proto PVC Corporation; LoSmoke.
 - d). Speedline Corporation; SmokeSafe.
 2. Adhesive: As recommended by jacket material manufacturer. VOC content not to exceed 250 g/l.
 3. Color: High Gloss White
 4. Factory-fabricated fitting covers to match jacket if available; otherwise, field fabricate.
 - a). Shapes: 45- and 90-degree, short- and long-radius elbows, tees, valves, flanges, unions, reducers, end caps, soil-pipe hubs, traps, mechanical joints, and P-trap and supply covers for lavatories.
 5. Factory-fabricated tank heads and tank side panels.

PART 3. EXECUTION

3.1. WORKMANSHIP

- A. The Contractor shall take special care to prevent soiling equipment below or adjacent to areas being insulated. He shall be completely responsible for removing insulation cement splashes and smears and all surfaces that he mars or otherwise soils or defaces, and he will be

totally responsible for restoring these damaged surfaces to their like-new condition when delivered to the site.

3.2. SITE INSPECTION

- A. Before starting work under this section, carefully inspect the site and installed work of other trades and verify that such work is complete to the point where installation of materials and accessories under this section can begin.
- B. Verify that all materials and accessories can be installed in accordance with project drawings and specifications and material manufacturers' recommendations.
- C. Verify, by inspecting product labeling, submittal data, and/or certifications which may accompany the shipments, that all materials and accessories to be installed on the project comply with applicable specifications and standards and meet specified thermal and physical properties.

3.3. PREPARATION

- A. Ensure that all pipe and equipment surfaces over which insulation is to be installed are clean and dry.
- B. Ensure that insulation is clean, dry, and in good mechanical condition with all factory-applied vapor or weather barriers intact and undamaged. Wet, dirty, or damaged insulation shall not be acceptable for installation.
- C. Ensure that pressure testing of piping systems has been completed prior to installing insulation.

3.4. INSTALLATION

A. Piping Systems

1. General:

- a). Install all insulation materials and accessories in accordance with manufacturer's published instructions and recognized industry practices to ensure that it will serve its intended purpose.
- b). Install insulation on piping subsequent to installation of heat tracing, painting, testing, and acceptance tests.
- c). Install insulation materials with smooth and even surfaces. Insulate each continuous run of piping with full-length units of insulation, with single cut piece to complete run. Do not use cut pieces or scraps abutting each other. Butt insulation joints firmly to ensure complete, tight fit over all piping surfaces.
- d). Maintain the integrity of factory-applied vapor barrier jacketing on all pipe insulation, protecting it against puncture, tear or other damage. Seal all

tears, punctures and other penetrations of the pipe insulation vapor barrier coating.

- e). On exposed piping, locate insulation and cover seams in least visible location.
2. Fittings: Cover valves, fittings, unions, flanges, strainers, flexible connections, expansion joints, pump bodies, strainers, blowdowns, backflow preventers, antioflow valves and similar items in each piping system using one of the following:
 - a). Mitered sections of insulation equivalent in thickness and composition to that installed on straight pipe runs.
 - b). Insulation cement equal in thickness to the adjoining insulation.
 - c). PVC fitting covers insulated with material equal in thickness and composition to adjoining insulation.
 3. Penetrations: Extend piping insulation without interruption through walls, floors, and similar piping penetrations, except where otherwise specified.
 4. Joints:
 - a). Butt pipe insulation against hanger inserts. For hot pipes, apply 3-inch (7.5cm) wide vapor barrier tape or bank over butt joints. For cold piping, apply wet coat of vapor barrier lap cement on butt joints, and seal joints with 3-inch (7.5cm) wide vapor barrier tape or band.
 - b). All pipe insulation ends shall be tapered and sealed, regardless of service.
 5. For heat traced piping, insulate fittings, joints, and valves with insulation of like material, thickness and finish as adjoining pipe. Size insulation large enough to enclose pipe and heat tracer. Cover with aluminum jacket with seams located on bottom side of horizontal piping.

B. Equipment insulation:

1. General:

- a). Install insulation in accordance with manufacturer's published instructions and recognized industry practices to ensure that it will serve its intended purpose.
- b). Install insulation on equipment after installation of heat tracing, painting, testing, and acceptance tests.
- c). Install insulation materials with smooth, even surfaces. Rework poorly fitted joints. Do not use joint sealer or mastic as filler for joint gaps and excessive voids resulting from poor workmanship. Apply insulation using

staggered joint method for both single and double layer installation, applying each layer of insulation separately.

- d). Coat insulated surfaces where specified on contract drawings with layer of insulating cement, troweled in a workmanlike manner, leaving a smooth and continuous surface. Fill in seams, broken edges, and depressions. Cover over wire mesh and joints with cement sufficiently thick to remove surface irregularities.
 - e). Maintain the integrity of factory-applied vapor barrier jacketing on all insulation, protecting it against puncture, tears or other damage. Seal all tears, punctures and other penetrations of equipment insulation facing.
 - f). Where specification calls for field-applied at-service vapor barrier jacketing, it shall be neatly fitted and tightly secured. Lap seams 2-inches (5cm) (min.). Seal all joints with adhesive. Tape with 3-inches (7.5cm) matching pressure-sensitive tape or 3-inch (7.5cm) glass fabric and vapor barrier coating.
 - g). On exposed equipment, locate insulation and cover seams in least visible location.
2. Removable Insulation: Provide removable insulation sections to cover parts of equipment which must be opened periodically for maintenance, such as vessel covers, fasteners, flanges, flange accessories, manholes, handholes, cleanouts ASME stamp, and manufacturer nameplates.
 3. Areas Left Uninsulated: Items such as manholes, handholes, clean-outs, ASME stamp, and manufacturers' nameplates should be left uninsulated unless omitting insulation would cause a condensation problem. When such is the case, provide removable insulation and appropriate tagging to identify the presence of these items. Provide neatly beveled edges at interruptions of insulation.
 4. Equipment Exposed to Weather: Protect outdoor insulation from weather by installation of weather barrier mastic protective finish or jacketing as recommended by the jacketing manufacturer.

3.5. FIELD QUALITY ASSURANCE

- A. Upon completion of all insulation work covered by this specification, visually inspect the work and verify that it has been correctly installed. This may be done while work is in progress, to assure compliance with requirements herein to cover and protect insulation materials during installation.

3.6. PROTECTION

- A. Replace damaged insulation which cannot be satisfactorily repaired, including insulation with vapor barrier damage and moisture-saturated insulation.

- B. The insulation contractor shall advise the general and/or the mechanical contractor as to requirements for protection of the insulation work during the remainder of the construction period, to avoid damage and deterioration of the finished insulation work.

3.7. SAFETY PRECAUTIONS

- A. Insulation contractor's employees shall be properly protected during installation of all insulation. Protection shall include proper attire when handling and applying insulation materials, and shall include (but not be limited to) disposable dust respirators, gloves, hard hats, and eye protection.
- B. The insulation contractor shall conduct all job site operations in compliance with applicable provisions of the Occupational Safety and Health Act, as well as with all state and/or local safety and health codes and regulations that may apply to the work.

3.8. INSULATION COVERING

- A. Unless otherwise noted, all exposed equipment insulation shall have a field applied PVC jacket cover neatly cut and pasted over equipment insulation. PVC shall be high gloss white and shall be 20 mils thick. Exposed areas include, but are not limited to, all mechanical equipment rooms/fan rooms, mezzanines, penthouses, boiler rooms, janitor's closets, kitchens, electric rooms, and piping and ductwork exposed in an occupied space.
- B. Unless otherwise noted, all exposed pipe insulation required to be insulated shall be jacketed with a PVC Jacketing with fitting covers. PVC jacket shall be color fade resistant, white high gloss, U.S.D.A. authorized as manufactured by Proto Corporation or approved equal. PVC jacketing shall be high impact, ultraviolet resistant PVC. Minimum thickness shall be 20 mils, roll stock ready for shop or field cutting and forming.
- C. Where PVC jackets are indicated, install with 1 inch overlap at longitudinal seams and end joints, for horizontal applications, install with longitudinal seams along top and bottom of tanks and vessels. Seal with manufacturers recommended adhesive.
 - 1. Apply two continuous beads of adhesive to seams and joints, one bead under lap and the finish bead along seam and joint edge.

END OF SECTION

SECTION 22 40 05

PLUMBING EQUIPMENT

PART 1. GENERAL

1.1. GENERAL

- A. For General Mechanical Requirements, see Division 22 Section, *Common Work Results for Plumbing* & Division 01, *General Requirements*.
- B. Drawings and general provisions of the Contract, including *General and Supplementary Conditions* and Division 01 specifications apply to this Section.
- C. All exposed bolts, screws, etc., shall be vandal proof.
- D. All plumbing materials and equipment shall be new and of best grade, free of defects and complete with all required appurtenances and accessories.
- E. Piping and insulation are specified under other sections.
- F. Provide all materials, equipment and perform all labor required to install plumbing system complete as specified, as drawings indicated and as required by the State of Delaware, National Standard Plumbing Code, International Plumbing Code, City of Dover Code, the local code, and all other authorities have jurisdiction.
- G. Provide stops for all plumbing equipment. Stops are to be accessible.
- H. Provide pumps with manufacturer's name, model number, and rating/capacity identified.
- I. Ensure products and installation of specified products are in conformance with recommendations and requirements of the following organizations:
 - 1. American Gas Association (AGA).
 - 2. National Sanitation Foundation (NSF).
 - 3. American Society of Mechanical Engineers (ASME).
 - 4. National Board of Boiler and Pressure Vessel Inspectors (NBBPVI).
 - 5. National Electrical Manufacturers' Association (NEMA).
 - 6. Underwriters Laboratories (UL).
- J. Ensure pumps operate at specified system fluid temperatures without vapor binding and cavitations, are non-overloading in parallel or individual operation, operate within 25 percent of midpoint of published maximum efficiency curve.

1.2. REFERENCES

- A. ANSI/ASSE 1011 - Hose Connection Vacuum Breakers.
- B. ANSI/ASSE 1012 - Backflow Preventers with Immediate Atmospheric Vent.

- C. ANSI/ASSE 1013 - Backflow Preventers, Reduced Pressure Principle.
 - D. ANSI/ASE 1019 - Wall Hydrants, Frost Proof Automatic Draining Anti-Backflow Types.
 - E. ANSI A112.21.1 - Floor Drains.
 - F. ANSI A112.21.2 - Roof Drains.
 - G. ANSI A112.26.1 - Water Hammer Arrestors.
 - H. AWWA C506 - Backflow Prevention Devices - Reduced Pressure Principle and Double Check Valve Types.
 - I. PDI WH-201 Water Hammer Arrestors.
 - J. ANSI/ASHRAE 90A - Energy Conservation in New Building Design.
 - K. ASME Section VIII - Pressure Vessels; Boiler and Pressure Vessel Codes.
 - L. ANSI/NFPA 54 - National Fuel Gas Code.
 - M. ANSI/NFPA 58 - Storage and Handling of Liquefied Petroleum Gases.
 - N. ANSI/NFPA 70 - National Electrical Code.
 - O. IBC - International Building Code.
- 1.3. DELIVERY, STORAGE, AND HANDLING
- A. Deliver, store, protect and handle products to site under provisions of General Requirements.
 - B. Accept equipment on site in factory packaging. Inspect for damage.
 - C. Protect installed equipment from damage by securing areas and by leaving factory packaging in place to protect equipment and prevent use.
- 1.4. FIELD MEASUREMENTS
- A. Verify that field measurements are as indicated on shop drawings and per the manufacturer.
- 1.5. ALTERNATES
- A. Refer to Division 01 Section, *Alternates* for description of work under this section affected by alternates.

PART 2. PRODUCTS

2.1. FLOOR DRAINS

- A. Provide Nikaloy strainers on all floor drains unless specified otherwise.

- B. Provide flashing clamps on all drains penetrating waterproofing membrane.
- C. Provide suitable flashing material and clamping collar for drains which are not set in place when slab is poured.
- D. Provide backwater valves for all floor drains connecting directly to the storm water system. Depending on conditions of the particular installation backwater valves may be an integral part of the drains or a separate device. Accessibility to valves must be maintained for maintenance. Provide an adequately sized extension sleeve up to floor or grade as required.
- E. Backwater valves are normally closed, flapper type with bronze or brass seat and disc and stainless steel pin.
- F. Provide traps for all floor drains connected to the sanitary system.
- G. Provide E & S primer valve (one valve per trap, per floor drain) on all remote floor drains. When installed on fixture in finished area, primer valve shall be concealed behind a Josam 58650 access door. In Mechanical Rooms, mezzanine, penthouses, and all other locations indicated on the contract drawing, priming lines shall be connected to automatic trap primer.
- H. In lieu of joints specified in piping section, neoprene gaskets may be used if designed for use with the drains and cleanouts employed and if approved by the local plumbing authority.
- I. Where applicable, for floor drains utilized for washing machines, provide a stainless steel lint screen/strainer.
- J. Schedule of Drains and Accessories:
 - 1. FDR.-1: General Service Floor Drain: Zurn ZN-415 floor and shower drain, dura coated cast iron body with bottom outlet, combination invertible membrane clamp and adjustable collar with Type "B" polished nickel bronze strainer. Provide with ½ -inch trap primer connection.
- K. Approved Manufacturers: Josam, J.R. Smith, Zurn, Wade, Ancon, Mifab, Watts.

2.2. CLEANOUTS

- A. Provide cleanouts in sanitary and storm drainage systems at ends of runs, at changes in direction, near the base of stacks, every 50 feet in horizontal runs, of 4-inch diameter or less, every 100 feet in horizontal runs over 4-inches, and where indicated.
- B. Cleanouts shall be full size of pipe up to 4-inches and shall be 4-inches for larger sizes. Where installed in finished floors inserts shall match adjacent floor construction.
- C. Materials and Approved Manufacturers: Josam, J.R. Smith, Zurn, Wade or Ancon, Mifab, Watts, equal to Josam numbers given below:
 - 1. Concealed Piping C.I. Pipe

- 2. Unfinished Areas
- 3. Floors 57000-Z-CI
- 4. Walls 58600-PLG

- 5. Finished Areas - Floors
- 6. Terrazzo 56040-13
- 7. Composition Tile 57000-X-12
- 8. Ceramic Tile 57000-X
- 9. Carpet 56070-14
- 10. Carpet insert to match adjacent carpet in type, color and grade.

- 11. Finished Areas - Walls
- 12. Plaster/Dry Wall 58640-COT
- 13. Tile/CMU 58600-CO

2.3. WALL HYDRANTS


- A. Wall Hydrant (Exterior): Josam 71000 Series Hydraman anti-siphon wall hydrant, 3/4-inch non-freeze, key operated wall hydrant with hinged locking cover, polished bronze box and cover and bronze casing and integral vacuum breaker. Seat and disc shall be removable from front of the hydrant. Wall thickness; see architectural drawings. Wall hydrants shall conform to ANSI/ASSE 1019 with wall plate, lock shield and removable key.
- B. Approved Manufacturers: Josam, Wade, Zurn, J.R. Smith, Mifab, Watts, or approved equal.

2.4. SHOCK ABSORBERS

- A. Provide shock absorbers equal to Josam Shokstops at all fast closing valves, at the top of all cold water risers, at each flush valve or battery of flush valves, and where indicated. Sizes and locations shall be in accordance with PDI Standard WH 201.
- B. Shock absorbers shall conform to ANSI A112.26.1, precharged suitable for operation in temperature range -100 to 300 degrees F and maximum 250 psig working pressure.
- C. Approved Manufacturers: Josam, Wade, Zurn, J.R. Smith, Sioux Chief, Watts, or approved equal.

2.5. VACUUM BREAKERS

- A. Provide vacuum breakers on water connections to fixtures and equipment where minimum air gaps required by Plumbing Code are not possible and on hose bibbs and other outlets to which hoses can be attached.
- B. Vacuum breakers not subject to back pressure, Watts No. 288A; vacuum breakers subject to back pressure, Watts Series 9D or for hose threads, Watts Series 8A.
- C. Hose connection backflow preventers shall be ASSE 1052, suitable for at least 5 gpm flow and applications with up to 10 foot head back pressure. Include two (2) check valves,



intermediate atmospheric vent, and non-removable, ASME B1.20.7 garden-hose thread on outlet.

- D. Hose connection vacuum breakers shall be ASSE 1011, nickel plated, with nonremovable and manual drain features, and ASME B1.20.7 garden-hose threads on outlet. Units attached to rough-bronze finish hose connections may be rough bronze.
- E. Approved manufacturers: Watts, Beeco, B&K Industries, Zurn, Sparco, Conbraco or approved equal.

2.6. VACUUM RELIEF VALVES

- A. Provide vacuum relief valves on cold water supply to water heaters, where indicated on the contract drawings, or where required by the authority having jurisdiction.
- B. Vacuum relief valves shall be Watts Regulator Co. Series 36A or approved equal.

2.7. HOSE BIBBS

- A. Chicago Faucet No. 952 or approved equal hose and faucet. Bronze or brass with integral mounting flange, replaceable hexagonal disc, hose threaded spout, polished chrome plated where exposed in finished areas, with hand wheel and removable key, integral vacuum breaker in conformance with ANSI/ASSE 1011.
- B. Hose bibbs in finished areas shall be polished chrome finish.
- C. Approved Manufacturers: Chicago Faucet, American Standard, Crane, T&S Brass, Watts.

2.8. BACKFLOW PREVENTER (REDUCED PRESSURE PRINCIPAL TYPE)

- A. Furnish and install reduced pressure principal backflow preventers at all cold water make-up connections to HVAC water systems, and where indicated on contract drawings.
- B. Backflow preventers shall be of bronze body construction, inlet and discharge OS&Y gate valves, stainless steel check and relief valve seats, stainless steel relief valve shafts and flange bolts. Ball valve test cocks shall be bronze body.
- C. Pressure ratings shall be up to 175 psi and temperature ratings shall be up to 210 degrees F continuous.
- D. Install unit per local code requirements and authorities having jurisdiction. Unless otherwise noted, install backflow preventers between 12 inches and 60 inches above finished floor.
- E. Units shall be approved by ASSE 1013, UPC, UL, and shall be No. 909 with air gap fitting and inlet/outlet gate valves as manufactured by Watts Regulator, Conbraco, Wilkens, or as approved equal. Pipe discharge to nearest floor drain/floor sink. Provide minimum 18-inch clearance for servicing and testing.
- F. Pipe discharge of backflow preventer full size to closest floor drain utilizing type "L" copper.

- G. Furnish test kit for field testing units. Watts Model TK-9A Analog Differential Gauge or approved equal.

2.9. TRAP PRIMING STATION-AUTOMATIC TRAP PRIMER

- A. Trap priming stations shall be Precision Plumbing Products, Inc., Electronic Trap Priming manifold Model PT. The manifold shall supply a minimum of 2 ounces of potable water per opening at 20 PSIG once in each 24 hour period. The Electronic Trap Priming Manifold must be capable of equally priming from 4 through 30 individual floor drain traps.
- B. The unit shall be factory assembled and prepped, and shall include a bronze body 3/4-inch female NPT WOG rated ball valve 3/4-inch, Water Hammer Arrestor, copper barrel with brass piston and type "L" copper sweat connection, electronic brass body 3/4-inch solenoid valve, and type "L" copper manifold with brass 2-inch compression fitting and orifice opening for precision water distribution to each floor drain trap. Unit shall be pre-piped with atmospheric vacuum breaker.
- C. Electronic components shall include single point power connection at 120 volt 1 phase 60 hertz, manual over-ride switch, minimum 5 amp breaker, 24-hour geared timer with relay and 5 second dwell function.
- D. All components shall be factory assembled, tested and supplied in a 16 gauge steel enclosure suitable for surface or recess mounting, as indicated on contract drawings. In addition, all components must comply with nationally recognized standards. The Precision Plumbing Products Electronic Trap Priming Manifold shall be fully warranted for the life of the plumbing system.
- E. When only a single trap primer is required, as in the case of a restroom with one floor drain in a toilet (or similar) the contractor may submit, in lieu of an electronic multiple station, a single station for review by the Engineer. The fixture serving the trap primer must be within 10' of the trap. Components shall be brass, bronze, and chrome, of the highest quality.
- F. Access door shall be finished with a prime coat and fire rated where installed in a rated wall. Access door latch shall be Allen key type.

2.10. TRAP SEAL PRIMER VALVES

- A. Provide and install one valve per trap, per floor drain on all remote floor drains. When installed on a fixture in a finished area, primer valve shall be concealed behind an access door. In mechanical rooms, mezzanines, penthouses, and all other locations indicated on contract drawings, priming lines shall be connected to automatic trap primer station. Trap seal primer valves shall be as manufactured by E&S, Precision Plumbing Products, Sioux Chief, Mifab, Watts, or approved equal.
- B. Trap seal primer valves shall be ASSE 1018, water supply fed type with the following characteristics:
 - 1. 125 psig minimum working pressure.
 - 2. Bronze body with atmospheric - vented drain chamber.

3. Inlet and outlet connections: ½ inch NPS threaded or solder joint.
4. Gravity drain outlet connection: ½ inch NPS threaded or solder joint.
5. Finish: chrome plated

2.11. INTERIOR RECESSED WALL HYDRANTS

- A. Provide and install recessed wall hydrants where indicated on the contract drawings. Recessed wall hydrants shall be Zurn Model Z 1330, Josam, Ancon, Mifab, Watts or approved equal.
- B. Units shall be encased Ecotrol "anti-siphon" wall hydrant for interior wall installation. Unit shall be suitable for hot or cold water as indicated on Contract Drawings.
- C. Each unit shall be complete with integral backflow preventer, all bronze interior parts, non-turning operating coupling with hemispherical neoprene plunger and 3/4-inch solder inlet.
- D. Furnish each unit mounted in a stainless steel box and hinged cover with operating key lock and "water" stamped on cover.
- E. Furnish each unit with the following accessories:
 1. 3/4 inch – 90 degrees inlet elbow with union nut
 2. cylinder lock
 3. key operator

2.12. GAS SOLENOID SHUT-OFF VALVES

- A. Furnish and install gas solenoid shut-off valves where indicated on the contract drawings. Valve sizes shall be identical to pipe size that solenoid valve is installed within. Gas solenoid valves shall be ASCO 8215G Series or approved equal.
- B. Solenoid enclosures shall have "red-hat" metal solenoid enclosure. Solenoid valves shall be normally closed type, suitable for operation on electrical characteristics as indicated on the contract drawings. Valve body shall be aluminum with Buna "N" seating.
- C. Valves shall be suitable for operating with an operating differential pressure of 50 psig. Valves shall be suitable for operation at maximum fluid temperatures of 125 degrees F.
- D. Gas solenoid valves shall be U.L. listed and F.M. approved.

PART 7. EXECUTION

3.1. GENERAL INSTALLATION REQUIREMENTS

- A. Install all equipment in accordance with manufacturer's instructions.
- B. Install components plumb and level.

- C. Cleanouts in vertical pipes shall be installed in tees near floor. Cleanouts in horizontal pipes shall be installed with wyes on long sweep quarter beds. Cleanouts punching water proofing membranes shall have flashing clamps. Cleanout access covers in dry wall or gypsum board shall be painted to match walls.
- D. Unless otherwise noted, drains are to be installed at the low point of floors. Protect drains during remainder of construction period to avoid clogging with dirt and debris and to prevent damage from traffic and construction work.
- E. Install floor drains in low points so the top of grates are at or below the finished floor level.
- F. Drains not functioning properly shall be removed and re-installed properly at the expense of the contractor.
- G. Coordinate cutting and forming of roof and floor construction to receive drains to required invert elevations.
- H. Extend cleanouts to finish floor or wall surface. Lubricate threaded cleanout plugs with mixture of graphite and linseed oil. Ensure clearance at cleanout for rodding of drainage system.
- I. Encase exterior cleanouts in concrete flush with grade.
- J. All plumbing, vents in exterior walls shall be offset a minimum of 3'-0" in ceiling at roof before penetration.
- K. All plumbing vents within a 10'-0" radius of exhaust vents shall be extended to a height of 3'-0" above exhaust vent crown.
- L. All plumbing vents within a 10'-0" radius of any rooftop unit or intake louver shall be extended to a height of 3'-0" above fresh air intake.
- M. Slopes and invert elevations of all interior piping shall be established before any piping is installed in order that proper slopes will be maintained. All piping shall be located and determined where to be run to avoid conflict with other trades.
- N. Unless otherwise noted, all plumbing piping shall be routed as high as possible between bottom of roof joists and above ceiling to allow proper installation of ductwork, fire protection piping, conduits, etc.
- O. Coordinate with Architectural Drawings before roughing in plumbing.
- P. All openings in ceilings and plenum walls for plumbing shall be sealed air tight and protected with fire stop.
- Q. See site plan for extent of all piping leaving and entering building.
- R. See domestic water riser diagrams for location of valves, shock absorbers, etc.
- S. Make proper HW, CW, re-cir., waste, and vent connections to all equipment even though all

branch main, elbows and connections are not shown.

- T. Cleanouts shall be provided near base of each vertical waste or solid stack. Provide 18" minimum clearance for access.
- U. Unless otherwise noted, sanitary waste piping shown is below floor and all other piping is overhead, above ceiling. Domestic hot, cold and re-circ. water piping shall be installed between ceiling and roof insulation.
- V. Unless otherwise noted, horizontal sanitary piping pitches shall be 1 percent.
- W. Unless otherwise noted, all domestic water piping and limited area fire protection piping shall be installed on heated side of ceiling insulation.
- X. All piping and installation shall comply with all local and national plumbing codes. Test piping as required by plumbing code and authority having jurisdiction.
- Y. For sizes of all domestic water piping see plumbing fixture schedule and domestic water riser diagrams.
- Z. For sizes of all sanitary and vent piping see plumbing fixture schedule and sanitary/vent riser diagrams.

3.2. PLUMBING SPECIALTY INSTALLATION REQUIREMENTS

- A. General: Install plumbing specialty components, connections, and devices according to manufacturer's written instructions.
- B. Install backflow preventers of type, size, and capacity indicated, at each water-supply connection to mechanical equipment and systems, and to other equipment and water systems as indicated. Comply with authorities having jurisdiction. Locate backflow preventers in same room as connected equipment. Install air-gap fitting on units with atmospheric-vent connection and pipe relief outlet drain to nearest floor drain. Do not install bypass around backflow preventer. Label all piping downstream of backflow preventers as "non-potable" water.
- C. Field test all backflow preventers and submit test reports to Engineer. Furnish test kits as required for field testing.
- D. Install pressure regulators with inlet and outlet shutoff valves and balance valve bypass. Install pressure gages on inlet and outlet.
- E. Install strainers on supply side of each control valve, pressure regulator, and solenoid valve, and where indicated.
- F. Install hose bibbs with integral or field-installed vacuum breaker.
- G. Install wall hydrants with integral or field-installed vacuum breaker.
- H. All hose bibbs shall be mounted 18" above finished floor, unless otherwise specified.

- I. All wall hydrants shall be mounted 24" above finished grade unless otherwise specified.
- J. Install trap seal primer valves with valve outlet piping pitched down toward drain trap a minimum of one percent and connect to floor-drain body, trap, or inlet fitting. Adjust valve for proper flow. Install trap priming stations plumb and level with adequate access for servicing and maintenance.
- K. For floor drains located in toilet rooms and similar spaces where flush valves are utilized Contractor may utilize trap primer line from flush valve tail piece.
- M. Install backwater valves in building drain piping as indicated. For interior installation, provide cleanout deck plate flush with floor and centered over backwater valve cover, and of adequate size to remove valve cover for servicing. Fasten wall-hanging plumbing specialties securely to supports attached to building substrate if supports are specified and to building wall construction if no support is indicated. For exterior installation provide handhole with hinged cover and top mounted to be flush with grade.
- O. Fasten recessed, wall-mounting plumbing specialties to reinforcement built into walls.
- P. Secure supplies to supports or substrate.
- Q. Install individual stop valve in each water supply to plumbing specialties. Use ball, gate, or globe valve if specific valve as appropriate is not indicated.
- R. Install water-supply stop valves in accessible locations.
- S. Install escutcheons at wall, floor, and ceiling penetrations in exposed finished locations and within cabinets and millwork. Use deep-pattern escutcheons if required to conceal protruding pipe fittings.
- T. Include wood-breaking reinforcement for recessed and wall-mounting plumbing specialties.
- U. Install ball valves at all shock absorbers to allow removal for service/replacement.

3.3. WATER METER INSTALLATION REQUIREMENTS

- A. Install water meters, piping, and specialties according to Manufacturer's requirements.
 - 1. Install displacement-type water meters with shutoff valve on water meter inlet. Install valve on water meter outlet and valved bypass around meter, unless prohibited by authorities having jurisdiction.
 - 2. Install compound-type water meters with shutoff valves on water meter inlet and outlet and on valved bypass around meter. Support meters, valves, and piping on brick or concrete piers.
 - 3. Install detector-type water meters with shutoff valves on water meter inlet and outlet and on full-size valved bypass around meter. Support meter, valves, and piping on brick or concrete piers. Install roughing-in piping and specialties for water meter

installation according to utility's instructions and requirements.

- C. Install power and control wiring from water meter to ATC system.
- D. Field insulate and jacket water meter to prevent condensation.

3.4. TESTING

- A. After plumbing fixtures are connected, all piping and fixtures shall be tested for operation and a smoke or peppermint test shall be made on all soil, waste and vent piping.
- B. After the building has been occupied and the various equipment is in actual use, the Contractor shall make an operating test of all equipment at a time directed by the Engineer to determine that all contract requirements are met.

3.5. CLEANING AND STERILIZATION

- A. After final testing for leaks, all potable water lines shall be thoroughly flushed, by plumbing contractor, to remove foreign material. Before placing the systems in service, sterilize the new water lines in accordance with local health department codes and at a minimum according to the following procedure:
 1. Through a 3/4-inch hose connection in each branch main and building main, pump in sufficient sodium hypochlorite to produce a free available chlorine residual of not less than 200 ppm. Plumbing Contractor shall provide plumbing connections and power for pumping chlorine into system.
 2. Proceed upstream from the point of chlorine application opening all faucets and taps until chlorine is detected. Close faucets and taps when chlorine is evident.
 3. When chlorinated water has been brought to every faucet and tap with a minimum concentration of 200 ppm chlorine, retain this water in the system for at least three (3) hours.
 4. CAUTION: Over-concentration of chlorine and more than three (3) hours of retention may result in damage to piping system. It is not necessary to retain chlorine in any system for twenty-four hours to achieve sterilization. AWWA states that 200 ppm chlorine for three hours is sufficient.
 5. At the end of the retention period, no less than 100 ppm of chlorine shall be present at the extreme end of the system.
 6. Proceed to open all faucets and taps and thoroughly flush all new lines until the chlorine residual in the water is less than 1.0 ppm.
 7. Obtain representative water sample from the system for analysis by an independent and recognized bacteriological laboratory.
 8. If the sample tested for coliform organisms is negative, a letter and laboratory report shall be submitted by the service organization to the Contractor, certifying

successful completion of the sterilization. Additionally, this report shall be forwarded to the Owner as well as be included in the O&M Manual.

9. If any samples tested indicate the presence of coliform organisms, the entire sterilization procedure shall be repeated.
10. Take precautions to avoid use of plumbing fixtures and domestic water system during sterilization period. Place signs on all plumbing fixtures and outlets during sterilization period.

3.6. EXAMINATION

- A. Verify that walls and floor finishes are prepared and ready for installation of fixtures.
- B. Verify that electric power is available and of the correct characteristics.

3.7. PREPARATION

- A. Review the Kitchen Equipment Consultant's equipment cut sheets. Confirm rough-in location and size of fixtures and openings prior to commencing work.
- B. Rough-in fixture piping connections in accordance with minimum sizes indicated in fixture rough-in schedule for particular fixtures.

3.8. INTERFACE WITH OTHER PRODUCTS

- A. Review millwork shop drawings. Confirm location and size of fixtures and openings before rough-in and installation.

3.9. CLEANING

- A. At completion, clean plumbing equipment.

END OF SECTION

SECTION 23 05 00

COMMON WORK RESULTS FOR HVAC

PART 1. GENERAL

1.1. SUMMARY

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- B. Provide all labor, materials, equipment, and services necessary for and incidental to the complete installation and operation of all mechanical work.
- C. Unless otherwise specified, all submissions shall be made to, and acceptances and approvals made by the Architect and the Engineer.
- D. Contract Drawings are generally diagrammatic and all offsets, fittings, transitions and accessories are not necessarily shown. Furnish and install all such items as may be required to fit the work to the conditions encountered. Arrange piping, ductwork, equipment, and other work generally as shown on the contract drawings, providing proper clearance and access. Where departures are proposed because of field conditions or other causes, prepare and submit detailed shop drawings for approval in accordance with *Submittals* specified below. The right is reserved to make reasonable changes in location of equipment, piping, and ductwork, up to the time of rough-in or fabrication.
- E. Conform to the requirements of all rules, regulations and codes of local, state and federal authorities having jurisdiction.
- F. Coordinate the work under Division 23 with the work of all other construction trades.
- G. Be responsible for all construction means, methods, techniques, procedures, and phasing sequences used in the work. Furnish all tools, equipment and materials necessary to properly perform the work in first class, substantial, and workmanlike manner, in accordance with the full intent and meaning of the contract documents.

1.2. PERMITS AND FEES

- A. Obtain all permits and pay taxes, fees and other costs in connection with the work. File necessary plans, prepare documents, give proper notices and obtain necessary approvals. Deliver inspection and approval certificates to Owner prior to final acceptance of the work.
- B. Permits and fees shall comply with the Division 01, *General Requirements* of the specification.

1.3. EXAMINATION OF SITE

- A. Examine the site, determine all conditions and circumstances under which the work must be done, and make all necessary allowances for same. No additional cost to the Owner will be permitted for contractors' failure to do so.

- B. Examine and verify specific conditions described in individual specifications sections.
- C. Verify that utility services are available, of the correct characteristics, and in the correct locations.

1.4. CONTRACTOR QUALIFICATION

- A. Any Contractor or Subcontractor performing work under Division 23 shall be fully qualified and acceptable to the Architect/Engineer and Owner. Submit the following evidence when requested:
 - 1. A list of not less than five comparable projects which the Contractor completed.
 - 2. Letter of reference from not less than three registered professional engineers, general contractors or building owners.
 - 3. Local and/or State License, where required.
 - 4. Membership in trade or professional organizations where required.
- B. A Contractor is any individual, partnership, or corporation, performing work by contract or subcontract on this project.
- C. Acceptance of a Contractor or Subcontractor will not relieve the Contractor or subcontractor of any contractual requirements or his responsibility to supervise and coordinate the work, of various trades.

1.5. MATERIALS AND EQUIPMENT

- A. Materials and equipment installed as a permanent part of the project shall be new, unless otherwise indicated or specified, and of the specified type and quality.
- B. Where material or equipment is identified by proprietary name, model number and/or manufacturer, furnish named item, or its equal, subject to approval by Engineer. Substituted items shall be equal or better in quality and performance and must be suitable for available space, required arrangement, and application. Submit all data necessary to determine suitability of substituted items, for approval.
- C. The suitability of named item only has been verified. Where more than one item is named, only the first named item has been verified as suitable. Substituted items, including items other than first named shall be equal or better in quality and performance to that of specified items, and must be suitable for available space, required arrangement and application. Contractor, by providing other than the first named manufacturer, assumes responsibility for all necessary adjustments and modifications necessary for a satisfactory installation. Adjustments and modifications shall include but not be limited to electrical, structural, support, and architectural work.
- D. Substitution will not be permitted for specified items of material or equipment where noted.

- E. All items of equipment furnished shall have a service record of at least five (5) years.

1.6. FIRE SAFE MATERIALS

- A. Unless otherwise indicated, materials and equipment shall conform to UL, NFPA and ASTM standards for fire safety with smoke and fire hazard rating not exceeding flame spread of 25 and smoke developed of 50.

1.7. REFERENCED STANDARDS, CODES AND SPECIFICATIONS

- A. Specifications, Codes and Standards listed below are included as part of this specification, latest edition.
- B. AABC - Associated Air Balance Council
 - C. ABMA - American Boiler Manufacturers Association
 - D. ACCA - Air Conditioning Contractors of America
 - E. ADC - Air Diffusion Council
 - F. AGA - American Gas Association
 - G. AMCA - Air Movement and Control Association
 - H. ANSI - American National Standards Institute
 - I. ARI - Air Conditioning and Refrigeration Institute
 - J. ASHRAE - American Society of Heating, Refrigerating and Air Conditioning Engineers
 - K. ASME - American Society of Mechanical Engineers
 - L. ASPE - American Society of Plumbing Engineers
 - M. ASTM - American Society for Testing and Materials
 - N. ASME CSD-1 - American Society of Mechanical Engineers Controls and Safety Devices for Automatically Fired Boilers
 - O. CS - Commercial Standard
 - P. CSD - Control and Safety Devices
 - Q. DNREC - Delaware Department of Natural Resources
 - R. FM - Factory Mutual
 - S. IBC - International Building Code
 - T. IBR - Institute of Boiler and Radiator Manufacturers
 - U. IEEE - Institute of Electrical and Electronics Engineers
 - V. MSSP - Manufacturers Standards Society of the Valve and Fittings Industry
 - W. NEC - National Electrical Code
 - X. NEMA - National Electrical Manufacturers Association
 - Y. NFPA - National Fire Protection Association
 - Z. NSF - National Sanitation Foundation
 - AA. SMACNA - Sheet Metal and Air Conditioning Contractors National Association
 - BB. UL - Underwriters' Laboratories
 - CC. State of Delaware Fire Protection Regulations.
 - DD. All mechanical equipment and materials shall comply with the codes and standards listed in the latest edition of ASHRAE HVAC Applications Handbook, Chapter entitled *Codes and Standards*.

1.8. SUBMITTALS, REVIEW AND ACCEPTANCE

- A. Equipment, materials, installation, workmanship and arrangement of work are subject to

review and acceptance. No substitution will be permitted after acceptance of equipment or materials except where such substitution is considered by the Architect to be in best interest of Owner.

- B. After acceptance of Material and Equipment List, submit six (6) copies or more as required under General Conditions of complete descriptive data for all items. Data shall consist of specifications, data sheets, samples, capacity ratings, performance curves, operating characteristics, catalog cuts, dimensional drawings, wiring diagrams, installation instructions, and any other information necessary to indicate complete compliance with Contract Documents. Edit submittal data specifically for application to this project.
- C. Thoroughly review and stamp all submittals to indicate compliance with contract requirements prior to submission. Coordinate installation requirements and any electrical requirements for equipment submitted. Contractor shall be responsible for correctness of all submittals.
- D. Submittals will be reviewed for general compliance with design concept in accordance with contract documents, but dimensions, quantities, or other details will not be verified.
- E. Identify submittals, indicating intended application, location and service of submitted items. Refer to specification sections or paragraphs and drawings where applicable. Clearly indicate exact type, model number, style, size and special features of proposed item. Submittals of a general nature will not be acceptable. For substituted items, clearly list on the first page of the submittal all differences between the specified item and the proposed item. The contractor shall be responsible for corrective action and maintaining the specification requirements if differences have not been clearly indicated in the submittal.
- F. Submit actual operating conditions or characteristics for all equipment where required capacities are indicated. Factory order forms showing only required capacities will not be acceptable. Call attention, in writing, to deviation from contract requirements.
- G. Acceptance will not constitute waiver of contract requirements unless deviations are specifically indicated and clearly noted. Use only final or corrected submittals and data prior to fabrication and/or installation.
- H. For any submittal requiring more than two (2) reviews by the Engineer (including those caused by a change in subcontractor or supplier) the Owner will withhold contractor's funds by a change order to the contract to cover the cost of additional reviews. One review is counted for each action including rejection or return of any reason.
- I. For resubmissions, the Contractor must address in writing all of the Engineer's comments on the original submission to verify compliance.

1.9. SHOP DRAWINGS

- A. Prepare and submit shop drawings for all mechanical equipment, specially fabricated items, modifications to standard items, specially designed systems where detailed design is not shown on the contract drawings, or where the proposed installation differs from that shown on contract drawings.

- B. Submit data and shop drawings including but not limited to the list below, in addition to provisions of the paragraph above. Identify all shop drawings by the name of the item and system and the applicable specification paragraph number and drawing number.
- C. Every submittal including, but not limited to the list below, shall be forwarded with its own transmittal as a separate, distinct shop drawing. Grouping of items/systems that are not related shall be unacceptable.
- D. Items and Systems

Access Doors/Panels including layouts and locations
Airflow Monitoring Stations
Air Cooled Chillers
Air Handling Units
Air Distribution Systems
Air Separators
Antifreeze Fluids
Antifreeze Tanks
Automatic Temperature Control Systems and Equipment
Automatic Glycol Feed Systems & Pressure Tanks
Branch Selector Boxes/Heat Recovery Boxes
Breaching and Stacks
Carbon Dioxide Sensors
Carbon Monoxide Detectors
Central Control and Monitoring Systems (CCMS) and Equipment
Chemical Feed Systems
Chillers
Condensate Pumps
Condensing Units
Coordinated Drawings
Direct Buried Piping
Direct Fired Make-up Air Units
Drip Pan
Duct Materials
Electric Recessed Cabinet Convectors
Electric Unit Heaters
Electric Radiant Heat Panels
Equipment Rails
Expansion Tanks and Accessories
Exterior Equipment/Duct Piping Supports
Exterior Pipe Roller Supports
Fan Coil Units
Fans
Filters
Filter Housings
Fire Stopping - Methods and Materials
Fire Dampers
Flow Measuring Stations
Flowmeter and Primary Elements (Flow Fittings)
Gas Furnaces

Glycol Feed Systems
 Grilles, Registers, Diffusers
 Horizontal Recessed Cabinet Unit Heaters
 Horizontal Hot Water Unit Heaters
 Identification Systems
 In-Line Circulators
 Intake Hoods
 Kitchen Make-up Air Units
 Kitchen Ventilation System Units
 Louvers
 Material and Equipment Lists
 Operations and Maintenance Manuals
 Pipe Enclosures
 Pipe Guides and Anchors
 Pipe Materials Including Itemized Schedules
 Preliminary Testing and Balancing Reports
 Pressure Relief Valves
 Pressure Regulating Valves
 Pumps
 Radiant Heat Panels
 Refnests
 Refrigerant Monitoring Systems
 Roof Curbs
 Rooftop Units
 Relief Hoods
 Screen shots of ATC System Graphics
 Split System Air Conditioning Units Ductless
 Split System Heat Pumps, Ductless
 Static Pressure Gauges
 Strainers
 Thermal Insulation Materials Include Table Summaries
 Thermometers and Gauges
 Unit Heaters
 Variable Frequency Drive Motor Bearing Protective Rings
 Variable Refrigerant Volume Equipment
 Variable Speed Drives
 Vertical In-Line Pumps
 Vertical Cabinet Unit Heaters
 Vibration Isolation Materials
 Water Heater Flue/Combustion Air Piping
 Water Treatment Services
 Weatherproof Assembly Components
 Wiring Diagrams, Flow Diagrams and Operating Instructions

- E. Contractor, additionally, shall submit for review any other shop drawings as required by the Architect. No item shall be delivered to the site, or installed, until the Contractor has received a submittal from the Engineer marked *Reviewed* or *Comments Noted*. After the proposed materials have been reviewed, no substitution will be permitted except where approved by the Architect.
- F. For any shop drawing requiring more than two (2) reviews by the Engineer (including

those caused by a change in subcontractor or supplier) the Owner will withhold contractor's funds by a change order to the contract to cover the cost of additional reviews. One review is counted for each action including rejection or return of any reason.

1.10. SUPERVISION AND COORDINATION

- A. Provide complete supervision, direction, scheduling, and coordination of all work under the Contract, including that of subcontractors.
- B. Coordinate rough-in of all work and installation of sleeves, anchors, and supports for piping, ductwork, equipment, and other work performed under Division 23.
- C. Arrange for pipe spaces, chases, slots, and openings in building structure during progress of construction to allow for mechanical installations.
- D. Coordinate electrical work required under Division 23 with that under Division 26. Coordinate all work under Division 23 with work under all other Divisions.
- E. Supply services of an experienced (10 year minimum) and competent Project Manager to be in constant charge of work at site.
- F. Where a discrepancy exists within the specifications or drawings or between the specifications and drawings, the more stringent (or costly) requirement shall apply until clarification can be obtained from the Engineer. Failure to clarify such discrepancies with the Engineer will not relieve the Contractor of the responsibility of conforming to the requirements of the Contract.
- G. Failure of contractor to obtain a full and complete set of contract documents (either before or after bidding) will not relieve the contractor of the responsibility of complying with the intent of the contract documents.
- H. Coordinate installation of large equipment requiring positioning before closing in building. Where required arrange for manufacturer to ship equipment in modules.

1.11. CUTTING AND PATCHING

- A. Accomplish all cutting and patching necessary for the installation of work under Division 23. Damage resulting from this work to other work already in place, shall be repaired at Contractor's expense. Where cutting is required, perform work in neat and workmanlike manner. Restore disturbed work to match and blend with existing construction and finish, using materials compatible with the original. Use mechanics skilled in the particular trades required.
- B. Do not cut structural members without approval from the Architect or Engineer.

1.12. PENETRATION OF WATERPROOF CONSTRUCTION

- A. Coordinate the work to minimize penetration of waterproof construction, including roofs, exterior walls, and interior waterproof construction. Where such penetrations are necessary, furnish and install all necessary curbs, sleeves, flashings, fittings and caulking

to make penetrations absolutely watertight.

- B. Where pipes penetrate roofs, flash pipe with Stoneman *Stormtite*, Pate or approved equal, roof flashing assemblies with skirt and caulked counter flashing sleeve.
- C. Furnish and install pitch pockets or weather tight curb assemblies where required.
- D. Furnish and install roof drains, curbs, vent assemblies, and duct sleeves specifically designed for application to the particular roof construction, and install in accordance with the manufacturer's instructions. The Contractor shall be responsible for sleeve sizes and locations. All roof penetrations shall be installed in accordance with manufacturer's instructions, the National Roofing Contractors Association, SMACNA, and as required by other divisions of these specifications.
- E. All work associated with the existing roof shall be performed so as to maintain the roof warranty.

1.13. CONCRETE AND MASONRY WORK

- A. Furnish and install concrete and masonry work for equipment foundations, supports, pads, and other items required under Division 23. Perform work in accordance with requirements of other applicable Divisions of these specifications.
- B. Concrete shall test not less than 3,000 psi compressive strength after 28 days.
- C. Grout shall be non-shrink, high strength mortar, free of iron or chlorides and suitable for use in contact with all metals, without caps or other protective finishes. Apply in accordance with manufacturer's instructions and standard grouting practices.

1.14. CONNECTIONS AND ALTERATIONS TO EXISTING WORK

- A. Unless otherwise noted on the drawings, where existing mechanical work is removed, pipes, valves, ductwork, etc., shall be removed, including hangers, to a point below finished floors or behind finished walls and capped. Such point shall be far enough behind finished surfaces to allow for installation of normal thickness of required finish material.
- B. Where work specified in Division 23 connects to existing equipment, piping, ductwork, etc., Contractor shall perform all necessary alterations, cuttings, fittings, etc., of existing work as may be necessary to make satisfactory connections between new and existing work, and to leave completed work in a finished and workmanlike condition.
- C. Where the work specified under Division 23, or under other Divisions, requires relocation of existing equipment, piping, ductwork, etc., Contractor shall perform all work and make necessary changes to existing work as may be required to leave completed work in a finished and workmanlike condition. Where existing insulation is disturbed, replace insulation where removed or damaged equal to existing, in type, thickness, density, finish and thermal resistance (R-value) value.
- D. Where the relocation of existing equipment is required for access or the installation of new equipment, the contractor shall temporarily remove and/or relocate and re-install as

required to leave the existing and new work in a finished and workman like condition.

1.15. DEMOLITION

- A. Unless otherwise noted all existing equipment, piping, ductwork, etc., shall remain.
- B. Where existing equipment is indicated to be removed, all associated piping, conduit, power, controls, insulation, hangers, ductwork, supports and housekeeping pads, etc., patch, paint and repair walls/roof/floor to match existing and/or new finishes.
- C. Provide necessary piping, valves, traps, temporary feeds, drips, etc., as required. Drain and refill piping systems as often as necessary to accommodate phasing and to minimize time lengths of outages.
- D. The Contractor shall be responsible for visiting the site and determining the existing conditions in which the work is to be performed.
- E. Where any abandoned pipes in existing floors, walls, pipe tunnels, ceilings, etc., conflict with new work, remove abandoned pipes as necessary to accommodate new work.
- F. The location of all existing equipment, piping, ductwork, etc., indicated is approximate only and shall be checked and verified. Install all new mechanical/plumbing/fire protection work to connect to or clear existing work as applicable.
- G. Maintain egress at all times. Coordinate egress requirements with the State Fire Marshal, the Owner and the authorities having jurisdiction.
- H. Make provisions and include in bid all costs associated with confined entry/space requirements in all other applicable OSHA regulations.
- I. Where required to maintain the existing systems in operation, temporarily backfeed existing systems from new equipment. Contractor shall temporarily extend existing piping systems to new piping systems with the appropriate shut-off valves.
- J. At completion of project all temporary piping, valves, controls, etc., shall be removed in their entirety.
- K. Existing piping, equipment, ductwork, materials, etc., not required for re-use or re-installation in this project, shall be removed from the project site.
- L. Deliver to the Owner, on the premises where directed, existing equipment and materials which are removed and which are desired by the Owner or are indicated to remain the property of the Owner.
- M. All other materials and equipment which are removed shall become property of the Contractor and shall be promptly removed, from the premises, and disposed of by the Contractor, in an approved manner. Contractor shall be responsible for proper disposal of all removed equipment containing refrigerants. Contractor shall include in his bid all cost associated with the evacuation, removal and disposal of all existing equipment containing refrigerants in accordance with EPA and Health Department requirements. Where existing split systems or ductless units are indicated to be relocated, extend

refrigeration piping, power, and control wiring to the same.

- N. Where piping and/or ductwork is removed, remove all pipe or ductwork hangers which were supporting the removed piping or ductwork. Patch the remaining penetration voids with like materials and paint to match existing construction.
- O. Where required, provide and coordinate removal and re-installation of existing equipment. Take care to protect materials and equipment indicated for reuse. Contractor shall repair or replace items which are damaged. Contractor shall have Owner's representative present to confirm condition of equipment prior to demolition.
- P. Before demolition begins, and in the presence of the Owners representative, test and note all deficiencies in all existing systems affected by demolition but not completely removed by demolition. Provide a copy of the list of system deficiencies to the Owner and the Engineer. Videotape existing conditions in each space prior to beginning demolition work.
- Q. The Owner shall have the first right of refusal for all fixtures, devices and equipment removed by the Contractor.
- R. All devices and equipment designated by the Owner to remain the property of the Owner shall be moved and stored by the Contractor at a location on site as designated by the Owner. It shall be the Contractor's responsibility to store all devices and equipment in a safe manner to prevent damage while stored.
- S. All existing equipment refused by the Owner shall become the property of the Contractor and shall be removed from the site by the Contractor in a timely manner and disposed of in a legal manner.
- T. Work Abandoned in Place: Cut and remove underground pipe a minimum of 2 inches beyond face of adjacent construction. Cap and patch surface to match existing finish.
- U. Temporary Disconnection: Remove, store, clean, reinstall, reconnect, and make operational equipment indicated for relocation.
- V. Terminate services and utilities in accordance with local laws, ordinances, rules and regulations.
- W. Where hydronic system piping and equipment is removed, Contractor shall be responsible for proper disposal of all contained fluids containing glycol (ethylene or propylene), hazardous waste and water treatment chemicals. Contractor shall include in his bid all associated costs with the removal, testing, and disposal of hydronic system fluid in accordance with EPA, Health Department, and the Local Authority Having Jurisdiction.

1.16. EXCAVATION AND BACKFILLING

A. General

1. Perform all necessary excavation, or installation of work under Division 23, in whatever materials or conditions encountered, using suitable methods and

equipment.

2. Accurately establish required lines and grades and properly locate the work.
3. Determine the locations of all existing utilities before commencing the work.

B. Excavation: (Refer also to other portions of the specifications)

1. Excavate only the required elevations. If excavation is carried below the foundation lines or other required limits, backfill the excess with concrete.
2. Keep banks of trenches as nearly vertical as possible, and provide sheeting and/or shoring as required for protection of work and safety of personnel. Follow local, State, OSHA, and MOSH Guidelines.
3. Keep excavations dry. Protect excavations from freezing.

C. Backfilling: (Refer also to other portions of the specifications)

1. Backfill excavations to the required elevations and restore surfaces to their original or required conditions.
2. Backfill shall be similar material, free from objectionable matter such as rubbish, roots, stumps, brush, rocks and other sharp objects. Unless otherwise indicated, suitable material from the excavation may be used for backfill.
3. Carefully place and mechanically tamp backfill in layers not exceeding 12 inches loose thickness. Compact to 95 percent minimum.
4. Do not backfill against frozen material. Do not use frozen material for backfill.

1.17. DRIVE GUARDS

- A. Provide safety guards on all exposed belt drives, motor couplings, and other rotating machinery. Provide fully enclosed guards where machinery is exposed from more than one direction.
- B. When available, guards shall be factory fabricated and furnished with the equipment. Otherwise fabricate guards of heavy gauge steel, rigidly braced, removable, and finish to match equipment served. Provide openings for tachometers. Guards shall meet local, State and O.S.H.A. requirements.

1.18. VIBRATION ISOLATION

- A. Furnish and install vibration isolators, flexible connections, supports, anchors and/or foundations required to prevent transmission of vibration from equipment, piping or ductwork to building structure. See Division 23 Section, "Vibration Control for HVAC, Plumbing and Fire Protection Equipment".

1.19. ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

1.20. FASTENERS/CAPS

- A. For all exterior grade and roof mounted equipment containing refrigerant install lockable caps on service valves to prevent tampering. Lockable caps shall be Model NPR caps manufactured by Rector Seal or approved equal. Provide Model NPR Movent screwdriver tool with swiveling tip. Caps shall be suitable and specific for the refrigerant type utilized.

1.21. DEFINITIONS

- A. *Approve* - to permit use of material, equipment or methods conditional upon compliance with contract documents requirements.
- B. *Furnish and install* or *provide* means to supply, erect, install, and connect to complete for readiness for regular operation, the particular work referred to.
- C. *Contractor* means the mechanical contractor and any of his subcontractors, vendors, suppliers, or fabricators.
- D. *Piping* includes pipe, all fittings, valves, hangers, insulation, identification, and other accessories relative to such piping.
- E. *Ductwork* includes duct material, fittings, hangers, insulation, sealant, identification and other accessories
- F. *Concealed* means hidden from sight in chases, formed spaces, shafts, hung ceilings, embedded in construction or in crawl space.
- G. *Exposed* means not installed underground or *concealed* as defined above.
- H. *Invert Elevation* means the elevation of the inside bottom of pipe.
- I. *Finished Spaces*: Spaces other than mechanical and electrical equipment rooms, furred spaces, pipe and duct shafts, unheated spaces immediately below roof, spaces above ceiling, unexcavated spaces, crawl spaces, and tunnels.
- J. *Review* - limited observation or checking to ascertain general conformance with design concept of the work and with information given in contract documents. Such action does not constitute a waiver or alteration of the contract requirements.
- K. *SCR*: Silicon Controlled Rectifier: Solid state switching device to provide fast, infinitely variable proportional control.
- L. *ECM*: Electronically Commutating Motor.
- M. *Building Line*: Exterior wall of building.

1.22. MINIMUM EFFICIENCY REQUIREMENTS

- A. All heating, ventilating, and air conditioning equipment shall be manufactured to provide the minimum efficiency requirements as specified in ASHRAE Standard 90.1, latest edition.
- B. All piping, ductwork, and equipment insulation shall comply with ASHRAE Standard 90.1, latest edition.
- C. All mechanical devices, controls, accessories, and components shall be manufactured to provide the minimum efficiency requirements as specified in ASHRAE Standard 90.1, latest edition.

1.23. SYSTEM INTEGRATION

- A. For all HVAC equipment specified to be provided with packaged controls and interfaced with the automatic temperature control system, provide system integration between the equipment manufacturer and the automatic temperature control subcontractor.
- B. HVAC equipment submittals requiring system integration as defined above must identify all required system integration points.
- C. HVAC equipment manufacturers must coordinate with ATC subcontractor regarding system integration prior to submitting on the equipment.
- D. A system integration meeting must be arranged by the Mechanical Contractor and include, but not be limited to, the systems integrator for the HVAC equipment manufacturer and the ATC Subcontractor. This portion of systems integration must occur prior to HVAC equipment being delivered to the project.
- E. Once the HVAC equipment is on site, a second systems integration meeting must be arranged by the Mechanical Contractor to coordinate the packaged controls with the ATC system. The HVAC equipment manufacturer's representative familiar with system integration and the ATC subcontractor familiar with programming must be present.
- F. A final system integrations meeting shall occur once all equipment is in place and ready for operation. The Mechanical Contractor, the HVAC equipment systems' integrator, and the ATC Subcontractor shall meet on site to jointly program, schedule, verify points, interlock devices, and fully set up all systems integration components.
- G. All systems integration coordination, programming, and graphics must be completed prior to requesting commissioning and/or inspections by the Engineer of Record.

1.24. NAMEPLATES

- A. For all fuel conversions of existing equipment provide and affix new nameplates to all equipment that reflects the new fuel source.

PART 2. ELECTRICAL REQUIREMENTS

2.1. GENERAL MOTOR AND ELECTRICAL REQUIREMENTS

- A. Furnish and install control and interlock wiring for the equipment furnished. In general, power wiring and motor starting equipment will be provided under Division 26. Carefully review the contract documents to coordinate the electrical work under Division 23 with the work under Division 26. Where the electrical requirements of the equipment furnished differ from the provisions made under Division 26, make the necessary allowances under Division 23. Where no electrical provisions are made under Division 26, include all necessary electrical work under Division 23.
- B. All electrical work performed under Division 23 shall conform to the applicable requirements of Division 26 and conforming to the National Electrical Code. All wiring, conduit, etc., installed in ceiling plenums must be plenum rated per NFPA and the International Building Code.
- C. Provide wiring diagrams with electrical characteristics and connection requirements.
- D. Test Reports: Indicate test results verifying nominal efficiency and power factor for three phase motors larger than five (5) horsepower.
- E. Protect motors stored on site from weather and moisture by maintaining factory covers and suitable weatherproof covering. For extended outdoor storage, remove motors from equipment and store separately.
- F. All motors shall be furnished with visible nameplate indicating motor horsepower, voltage, phase, cycles, RPM, full load amps, locked rotor amps, frame size, manufacturer's name and model number, service factor, power factor and efficiency.
- G. Motors located in exterior locations, wet air streams, air cooled condensers, and outdoors shall be totally enclosed weatherproof of epoxy-treated type.
- H. Nominal efficiency and power factor shall be as scheduled at full load and rated voltage when tested in accordance with IEEE 112.
- I. Brake horsepower load requirement at specified duty shall not exceed 85 percent of nameplate horsepower times NEMA service factor for motors with 1.0 and 1.15 service factors.
- J. All single phase motors shall be provided with thermal protection: Internal protection shall automatically open power supply circuit to motor when winding temperature exceeds a safe value calibrated to temperature ratings of motor insulation. Thermal protection device shall automatically reset when motor temperature returns to normal range, unless otherwise indicated.

22. MOTORS AND CONTROLS

- A. Motors and controls shall conform to the latest requirements of IEEE, NEMA, NFPA-70 and shall be UL listed. Motor sizes are specified with the driven equipment. Motor starting and control equipment is specified either with the motor which is controlled or in an electrical specification section. The Contractor is advised to consult all specification sections to determine responsibility for motors and controls.
- B. Motors shall be designed, built and tested in accordance with the latest revision of

NEMA Standard MG 1.

- C. Motors used with variable-frequency controllers shall have ratings, characteristics, and features coordinated with and approved by the variable frequency controller (drive) manufacturer. As a minimum the following shall apply to variable frequency controlled motors:
1. Motors shall be manufactured to withstand peak voltages of 1600 volts with .1 microsecond rise time per NEMA MG-1.
 2. Critical vibration frequencies of motor shall not be within operating range of variable frequency controller output.
 3. Temperature rise: Match rating for Class B insulation.
 4. Insulation: Class F.
 5. Thermal Protection: Conform to MG1 requirements for thermally protected motors.
- D. Motors shall be suitable for use under the conditions and with the equipment to which applied, and designed for operation on the electrical systems specified or indicated.
1. Motor capacities shall be such that the horsepower rating and the rated full-load current will not be exceeded while operating under the specified operating conditions. Under no condition shall the motor current exceed that indicated on the nameplates.
 2. Motor sizes noted in the individual equipment specifications are minimum requirements only. It is the responsibility of the equipment manufacturers and of the Contractor to furnish motors, electrical circuits and equipment of ample capacity to operate the equipment without overloading, exceeding the rated full-load current or overheating at full-load capacity under the most severe operating service of this equipment. Motors shall have sufficient torque to accelerate the total WR^2 of the driven equipment to operating speed.
 3. Motors shall be continuous duty type and shall operate quietly at all speeds and loads.
 4. Motors shall be designed for operation on 60 hertz power service. Unless otherwise specified or shown, motors less than ½ horsepower shall be single phase, and motors ½ horsepower and larger shall be 3 phase unless otherwise noted.
 5. Motors shall be mounted so that the motor can be removed without removing the entire driven unit.
- E. Single phase motors, smaller than 1/20 horsepower shall be ball or sleeve bearing; drip-proof, totally enclosed or explosion proof, as specified; 120 volts; permanent-split capacitor or shaded pole type. These motors shall not be used for general power purposes, and shall only be provided as built-in components of such mechanical

equipment as fans, unit heaters, humidifiers and damper controllers. When approved by the Engineer, deviations from the specifications will be permitted as follows:

1. Open motors may be installed as part of an assembly where enclosure within a cabinet provides protection against moisture.
 2. Motors used in conjunction with low voltage control systems may have a voltage rating less than 115 volts.
- F. Single phase motors, greater than 1/20 horsepower and less than 1/2 horsepower shall be ball bearing; drip-proof, totally enclosed or explosion proof, as specified, with Class A or B insulation, as standard with the motor manufacturer; 115 or 120/208/240 volts as required; capacitor start-induction run, permanent split capacitor or repulsion start-induction run type with minimum efficiency of 70 percent and a minimum full load power of 77 percent.
- G. Except as otherwise specified in the various specification sections, 3 phase motors 60 horsepower and smaller shall be NEMA design B squirrel cage induction type meeting the requirements of this paragraph. Motors shall be drip-proof, totally enclosed or explosion proof, as specified or indicated. Insulation shall be Class B or F, at 40 degrees C ambient temperature. Drip-proof motors shall have a 1.15 service factor and totally enclosed and explosion proof motors shall have a service factor of 1.00 or higher. Motors specified for operation at 480, 240, and 208 volts shall be nameplated 460, 230, 200 volts, respectively. Efficiencies and percent power factor at full load for three phase motors shall be not less than the values listed below for premium efficiency motors:

MOTOR NAMEPLATE	MINIMUM PERCENT EFFICIENCY AT NOMINAL SPEED AND RATED LOAD	MINIMUM PERCENT POWER FACTOR
1HP and above to	85.5 percent	84 percent
1-1/2 HP	86.5 percent	85 percent
2HP	86.5 percent	85 percent
3HP	89.5 percent	86 percent
5HP	89.5 percent	87 percent
7 1/2 HP	91 percent	86 percent
10HP	91.7 percent	85 percent
15HP	93.0 percent	85 percent
20HP	93.0 percent	86 percent
25HP	93.6 percent	85 percent
50HP and above	94.5 percent	88 percent

- H. Three phase motors 1/2 HP or greater shall be the Duty Master XE by Reliance Electric

Company, Super-E Premium Efficiency of Baldor Motor and Drives, E-plus Efficient Standard Duty Motor of the Electric Motor Division of Gould, Inc., the MAC II High Efficiency motor of Westinghouse Electric Corp., the equivalent product of General Electric, or approved equal.

- I. For motors serving equipment being controlled by a variable speed drive, motor shall be premium efficiency inverter duty rated.
- J. Motor frames shall be NEMA Standard T-Frames of steel, aluminum, or cast iron with end brackets of cast-iron or aluminum with steel inserts.
- K. Control of each motor shall be manual or automatic as specified for each in the various mechanical sections. In general, and unless otherwise specified for a particular item in the various mechanical sections of the specifications, motor starts and controls shall be specified and provided under the various electrical sections of these specifications.
- L. Provide manufacturer's warranty for all motors for minimum of 5 years including all labor and materials.

2.3. MOTOR INSTALLATION

- A. Install in accordance with manufacturer's instructions.
- B. Install securely on firm foundation. Mount ball bearing motors to support shaft regardless of shaft position.
- C. Check line voltage and phase and ensure agreement with nameplate. Check that proper thermal overloads have been installed prior to operating motors.
- D. Use adjustable motor mounting bases for belt-driven motors.
- E. Align pulleys and install belts.
- F. Tension belts according to manufacturer's written instructions.

2.4. WIRING DIAGRAMS

- A. The Contractor is responsible for obtaining and submitting wiring diagrams for all major items of equipment.
- B. Wiring diagrams shall be provided with shop drawings for all equipment requiring electric power.
- C. Provide wiring diagrams for all major mechanical items of equipment to electrical contractor and ATC subcontractor for coordination.

2.5. VARIABLE FREQUENCY DRIVE MOTOR BEARING PROTECTIVE RINGS:

- A. For all motors driven by a variable frequency PWM drive include a maintenance free, circumferential, conductive micro fiber shaft grounding ring to discharge shaft currents. Grounding rings shall be manufactured by AEGIS SGR or approved equal.

- B. Furnish units with one year warranty.
- C. Size and select Bearing Protective Rings per the manufacturer requirements based on the motor size, shaft diameter, and shaft shoulder length. For motors with slingers furnish and install NEMA /IEC kit as required.
- D. Furnish and apply Colloidal silver shaft coating to all shafts with Bearing Protective Rings to improve shaft voltage discharge capability.

PART 3. EXECUTION

3.1. EQUIPMENT INSTALLATION - COMMON REQUIREMENTS

- A. Install equipment to provide maximum possible headroom, if mounting heights are not indicated.
- B. Install equipment according to approved submittal data. Portions of the work are shown only in diagrammatic form. Refer conflicts to Architect.
- C. Install equipment level and plumb, parallel and perpendicular to other building systems and components in exposed interior spaces unless otherwise indicated.
- D. Install mechanical equipment to facilitate service, maintenance, and repair or replacement of components. Connect equipment for ease of disconnecting, with minimum interference to other installations. Extend grease fittings to accessible locations.
- E. Install equipment giving right of way to piping installed at required slope.
- F. Install flexible connectors on equipment side of shutoff valves, horizontally and parallel to equipment shafts if possible.
- G. Do not install equipment, ductwork, or piping over electrical gear, electrical panels, motor controllers, and similar electrical equipment. Install equipment, ductwork, and piping to maintain clear space above and in front of all electrical components per the National Electric Code.

3.2. SUPPORTS, HANGERS AND FOUNDATIONS

- A. Provide supports, hangers, braces, attachments and foundations required for the work. Support and set the work in a thoroughly substantial and workmanlike manner without placing strains on materials, equipment, or building structure, submit shop drawings for approval. Coordinate all work with the requirements of the structural division.
- B. Supports, hangers, braces, and attachments shall be standard manufactured items or fabricated structural steel shapes. All interior hangers shall be galvanized or steel with rust inhibiting paint. For un-insulated copper piping provide copper hanger to prevent contact of dissimilar metals. All exterior hangers shall be constructed of stainless steel utilizing stainless steel rods, nuts, washers, bolts, etc.
- C. Concrete housekeeping pads and foundations shall be not less than 4 inches high (6

inches for chillers) and shall extend a minimum of 6 inches beyond equipment bases. Provide wire-mesh reinforcement; chamfer exposed edges and corners; and finish exposed surfaces smooth.

- D. Where new concrete housekeeping pads are placed on existing concrete, saw cut the existing concrete to the perimeter dimension of the new pad to a depth of ½ inch. Break out the top ½ inch area of the existing concrete. Add *stubs* of #4 rebar angled into the existing concrete at a depth of approximately 50 percent of the existing slab thickness. The top portion of the rebar *stub* shall extend into the new pad by approximately 50 percent of its thickness. Furnish one rebar stub per every two square feet of new pad. Chemically bond the new concrete to the existing concrete.

3.3. PROVISIONS FOR ACCESS

- A. The contractor shall provide access panels and doors for all concealed equipment, valves, strainers, dampers, filters, controls, control devices, cleanout, fire dampers, damper operators, traps, and other devices requiring maintenance, service, adjustment, balancing or manual operation.
- B. Where access doors are necessary, furnish and install manufactured painted steel door assemblies consisting of hinged door, key locks, and frame designed for the particular wall or ceiling construction. Properly locate each door. Door sizes shall be a 12 inches x 12 inches for hand access, 18 inches x 18 inches for shoulder access and 24 inches x 24 inches for full body access where required. Review locations and sizes with Architect prior to fabrication. Mark each access door within finished spaces with a small color coded and numbered tab. Provide a chart or index for identification. Provide U.L. approved and labeled access doors where installed in fire rated walls or ceilings. Doors shall be Milcor Metal Access Doors as manufactured by Inland-Ryerson, Mifab, or approved equal.
1. Acoustic or Cement Plaster: Style B
 2. Hard Finish Plaster: Style K or L
 3. Masonry or Dry Wall: Style M
- C. Where access is by means of liftout ceiling tiles or panels, mark each ceiling grid using small color coded and numbered tabs. Provide a chart or index for identification. Place markers within ceiling grid not on ceiling tiles.
- D. Access panels, doors, etc. described herein shall be furnished under the section of specifications providing the particular service and to be turned over to the pertinent trade for installation. Coordinate installation with installing contractor. All access doors shall be painted in baked enamel finish to match ceiling or wall finish.
- E. Submit shop drawings indicating the proposed location of all access panels/doors. Access doors in finished spaces shall be coordinated with air devices, lighting and sprinklers to provide a neat and symmetrical appearance.
- F. Where access doors are installed in wet locations (i.e. shower rooms, toilet rooms, natatoriums, kitchens, dishwasher rooms, can wash rooms, and similar spaces, etc...) provide aluminum access doors/frames.

3.4. PAINTING AND FINISHES

- A. Provide protective finishes on all materials and equipment. Use coated or corrosion-resistant materials, hardware and fittings throughout the work. Paint bare, untreated ferrous surfaces with rust-inhibiting paint. All exterior components including supports, hangers, nuts, bolts, washers, vibration isolators, etc. shall be stainless steel.
- B. Clean surfaces prior to application of insulation, adhesives, coatings, paint, or other finishes.
- C. Provide factory-applied finishes where specified. Unless otherwise indicated factory-applied paints shall be baked enamel with proper pretreatment.
- D. Protect all finishes and restore any finishes damaged as a result of work under Division 23 to their original condition.
- E. The preceding requirements apply to all work, whether exposed or concealed.
- F. Remove all construction marking and writing from exposed equipment, ductwork, piping and building surfaces. Do not paint manufacturer's labels or tags.
- G. All exposed ductwork, piping, equipment, etc. shall be painted. Colors shall be as stated in this division or as selected by the Architect and conform to ANSI Standards.
- H. All exterior roof mounted ductwork, equipment, piping, breeching, and vents shall be painted to match roof in color as selected by Architect.
- I. All exposed ductwork, piping, equipment, etc. in finished spaces shall be painted. Colors shall be as selected by the Architect and conform to ANSI Standards.
- J. All exposed ductwork, piping, equipment, etc., in Mechanical Rooms, Boiler Rooms, Penthouses, Fire Pump Rooms, Mezzanines, and Storage where PVC jacketed shall not require painting. Label and identify and color code as specified.

3.5. CLEANING OF SYSTEMS

- A. Thoroughly clean systems after satisfactory completion of pressure tests and before permanently connecting fixtures, equipment, traps, strainers, and other accessory items. Blow out and flush piping until interior surfaces are free of foreign matter.
- B. Flush piping in re-circulating water systems to remove cutting oil, excess pipe joint compound, solder slag and other foreign materials. Do not use system pumps until after cleaning and flushing has been accomplished to the satisfaction of the Engineer. Employ chemical cleaners, including a non-foaming detergent, not harmful to system components. After cleaning operation, final flushing and refilling, the residual alkalinity shall not exceed 300 parts per million. Submit a certificate of completion to Engineer stating name of service company used.
- C. Maintain strainers and dirt pockets in clean condition.
- D. Clean fans, ductwork, enclosures, flues, registers, grilles, and diffusers at completion of

work.

- E. Install filters of equal efficiency to those specified in permanent air systems operated for temporary heating during construction. Replace with clean filters as specified prior to acceptance and after cleaning of system.
- F. Pay for labor and materials required to locate and remove obstructions from systems that are clogged with construction refuse after acceptance. Replace and repair work disturbed during removal of obstructions.
- G. Leave systems clean, and in complete running order.
- H. All HVAC piping/equipment strainers must be pulled and cleaned prior to substantial completion. In addition six (6) months after substantial completion all HVAC piping/equipment strainers must be pulled and cleaned a second time. Document and submit verification of strainer cleaning to Engineer, Owner, and Construction Manager.

3.6. COLOR SELECTION

- A. Color of finishes shall be as selected by the Architect.
- B. Submit color of factory-finished equipment for acceptance prior to ordering.

3.7. PROTECTION OF WORK

- A. Protect work, material and equipment from weather and construction operations before and after installation. Properly store and handle all materials and equipment.
- B. Cover temporary openings in piping, ductwork, and equipment to prevent the entrance of water, dirt, debris, or other foreign matter. Deliver pipes and tubes with factory applied end caps.
- C. Cover or otherwise protect all finishes.
- D. Replace damaged materials, devices, finishes and equipment.
- E. Protect stored pipes and tubes from moisture and dirt. Elevate above grade. Do not exceed structural capacity of floor, where stored inside.

3.8. OPERATION OF EQUIPMENT

- A. Clean all systems and equipment prior to initial operation for testing, balancing, or other purposes. Lubricate, adjust, and test all equipment in accordance with manufacturer's instructions. Do not operate equipment unless all proper safety devices or controls are operational. Provide all maintenance and service for equipment that is authorized for operation during construction.
- B. Where specified, or otherwise required, provide the services of the manufacturer's factory-trained servicemen or technicians to start up the equipment. Where factory start-up of equipment is not specified, provide field start-up by qualified technician.

- C. Submit factory start-up sheets or field start-ups sheets for all equipment prior to the commencement of testing and balancing work. Testing and balancing work shall not commence until start-up reports have been completed, reviewed by Engineer and forwarded to Testing and Balancing Agency.
- D. Do not use mechanical systems for temporary services or temporary conditioning during construction, unless approved by Owner in writing. Refer to Division 01 Section "Temporary Facilities and Controls" for temporary heating/cooling during construction.
- E. Upon completion of work, clean and restore all equipment to new conditions; replace expendable items such as filters.

3.9. DEMONSTRATION AND TRAINING VIDEO RECORDINGS

- A. General: Record demonstration and training video recordings. Record each training module separately.
 - 1. At beginning of each training module, record each chart containing learning objective and lesson outline.
- B. Video Recording Format: Provide high-quality color video recordings with menu navigation in format acceptable to Engineer.
- C. Recording: Mount camera on tripod before starting recording, unless otherwise necessary to show area of demonstration and training. Display continuous running time.
- D. Narration: Describe scenes on video recording by audio narration by microphone while video recording is recorded. Include description of items being viewed.
- E. Transcript: Provide a transcript of the narration. Display images and running time captured from videotape opposite the corresponding narration segment.

3.10. IDENTIFICATIONS, FLOW DIAGRAMS, ELECTRICAL DIAGRAMS AND OPERATING INSTRUCTIONS

- A. Contractor shall submit for approval schematic piping diagrams of each piping system installed in the building. Diagrams shall indicate the location and the identification number of each valve in the particular system. Following approval by all authorities, the diagrams shall be framed, mounted under safety glass and hung in each Mechanical Room where directed. Contractor shall deliver the tracing or sepia from which the diagrams were reproduced to the Owner.
- B. All valves shall be plainly tagged. For any bypass valves, install sign indicating valve position as "Normally Open" or "Normally Closed" as required.
- C. All items of equipment, including motor starters, disconnects and ATC panels shall be furnished with white on black plastic permanent identification cards. Lettering shall be a minimum of ¼ inch high. Identification plates shall be secured, affixed to each piece of equipment, starters, disconnects, panels by screw or adhesive (tuff bond #TB2 or as approved equal).

- D. Provide six (6) copies of operating and maintenance instructions for all principal items of equipment furnished. This material shall be bound as a volume of the *Record and Information Booklet* as hereinafter specified.
- E. All lines piping and ductwork installed under this contract shall be stenciled with *direction of flow* arrows and with stenciled letters naming each pipe and ductwork and service. Refer to Division 23 Section, "HVAC Piping, Fittings, Valves, Etc." and Division 23 Section, "HVAC Air Distribution". Color-code all direction of flow arrows and labels. In finished spaces omit labeling and direction of flow arrows. Paint in color as selected by Architect.
- F. Submit list of wording, symbols, letter size, and color coding for mechanical identification. Submit samples of equipment identification cards, piping label, ductwork labels, and valve tags to Engineer for review prior to installation.
- G. Provide at least 16 hours of straight time instruction to the operating personnel. Time of instruction shall be designated by the Owner. Additional instruction time for the automatic temperature control (ATC) system is specified in Division 23 Section, "Instrumentation & Controls of HVAC & Plumbing Systems".
- H. Contractor shall demonstrate Sequences of Operation of all equipment in presence of Owner's representative, Engineer, and ATC subcontractor.

3.11. WALL AND FLOOR PENETRATION

- A. All penetrations of partitions, ceilings, roofs and floors by ducts, piping or conduit under Division 23 shall be sleeved, sealed, and caulked airtight for sound and air transfer control. Penetrations of mechanical room partitions, ceilings, and floors shall be as specified in Division 23 Section, "Vibration Control for HVAC, Plumbing and Fire Protection Equipment".
- B. All penetration of fire rated assemblies shall be sleeved, sealed, caulked and protected to maintain the rating of the wall, roof, or floor. Fire Marshal approved U.L. assemblies shall be utilized. See Division 07 Section, "Fire Protection, HVAC & Plumbing Penetration Firestopping".
- C. Where piping extends through exterior walls or below grade, provide waterproof pipe penetration seals, as specified in another division of these specifications.
- D. Provide pipe escutcheons and duct flanges for sleeved pipes and ducts in finished areas.
- E. Piping sleeves:
 - 1. Galvanized steel pipe, standard weight where pipes are exposed and roofs and concrete and masonry walls. On exterior walls provide anchor flange welded to perimeter.
 - 2. Twenty-two (22) gauge galvanized steel elsewhere.
- F. Ductwork sleeves: 20 gauge galvanized steel.

- G. Extend all floor sleeves through floor at least 3/4-inches above finished floor, caulk sleeve the entire depth and furnish and install floor plate.
- H. Sleeves for penetrations in kitchen and hood service areas shall finish .375 inches above floor or flush with wall surfaces and be neatly pointed up to fit snugly against floor or wall material.

3.12. RECORD DRAWINGS

- A. Upon completion of the mechanical installations, the Contractor shall deliver to the Architect one complete set of prints of the mechanical contract drawings which shall be legibly marked in red pencil to show all changes and departures of the installation as compared with the original design. They shall be suitable for use in preparation of Record Drawings.
- B. Contractor shall incorporate all sketches, addendums, value engineering, change orders, etc., into record drawings prior to delivering to Architect.

3.13. WARRANTY

- A. Contractor's attention is directed to warranty obligations contained in the GENERAL CONDITIONS.
- B. The above shall not in any way void or abrogate equipment manufacturer's guarantee or warranty. Certificates of equipment manufacturer's warranties shall be included in the operations and maintenance manuals.
- C. The Contractor guarantees for a two year period from the time of final acceptance by the Owner.
 1. That the work contains no faulty or imperfect material or equipment or any imperfect, careless, or unskilled workmanship.
 2. That all work, equipment, machines, devices, etc. shall be adequate for the use to which they are intended, and shall operate with ordinary care and attention in a satisfactory and efficient manner.
 3. That the contractor will re-execute, correct, repair, or remove and replace with proper work, without cost to the Owner, any work found to be deficient. The contractor shall also make good all damages caused to their work or materials in the process of complying with this section.
 4. That the entire work shall be water-tight and leak-proof.

3.14. LUBRICATION

- A. All bearings, motors, and all equipment requiring lubrication shall be provided with accessible fittings for same. Before turning over the equipment to the Owner, the Contractor shall fully lubricate each item of equipment, shall provide one year's supply of lubricant for each, and shall provide Owner with complete written lubricating instructions, together with diagram locating the points requiring lubrication. Include this

information in the Record and Information Booklet.

- B. In general, all motors and equipment shall be provided with grease lubricated roller or ball bearings with Alemite or equal accessible or extended grease fittings and drain plugs.

3.15. OPERATIONS AND MAINTENANCE MANUALS

- A. The Contractor shall have prepared six (6) hardcopies and one (1) electronic copy of the *Operations and Maintenance Manuals* and deliver these copies of the booklet to the Owner. The booklet shall be as specified herein. The booklet must be approved and will not be accepted as final until so stamped.
- B. The booklet shall be bound in a three-ring loose-leaf binder similar to National No. 3881 with the following title lettered on the front: *Operations and Maintenance Manuals – Nellie Stokes Elementary School - HVAC*. No sheets larger than 8-1/2 inches x 11 inches shall be used, except sheets that are neatly folded to 8-1/2 inches x 11 inches and used as a pull-out. Provide divider tabs and table of contents for organizing and separating information.
- C. Provide the following data in the booklet:
 - 1. As first entry, an approved letter indicating the starting/ending time of Contractor's warranty period.
 - 2. Maintenance operation and lubrication instructions on each piece of equipment furnished.
 - 3. Complete catalog data on each piece of heating and air conditioning equipment furnished including approved shop drawing.
 - 4. Manufacturer's extended limited warranties on equipment including but not limited to chiller, variable frequency drives, air conditioning compressors, and VRV Equipment.
 - 5. Chart form indicating frequency and type of routine maintenance for all mechanical equipment. The chart shall also indicate model number of equipment, location and service.
 - 6. Provide sales and authorized service representatives names, address, and phone numbers of all equipment and subcontractors.
 - 7. Provide supplier and subcontractor's names, address, and phone number.
 - 8. Catalog data of all equipment, valves, etc. shall include wiring diagrams, parts list and assembly drawing.
 - 9. Provide and install in locations as directed by the Owner, valve charts including valve tag number, valve type, valve model number, valve manufacturer, style, service and location. Each valve chart shall be enclosed in a durable polymer based frame with a cover safety glass.
 - 10. Copy of the approved balancing report including duct leakage data.
 - 11. ATC systems including as-built ATC drawings of systems including internal of all panels.
 - 12. Access panel charts with index illustrating the location and purpose of access panels.
 - 13. Approved HVAC and Electrical Certificates.
 - 14. Start-up reports for equipment.
 - 15. Water treatment test reports.
 - 16. Provide and install in locations as directed by Owner, filter charts, including filter

type, size, model number, manufacturer, quantity and size for each filter utilized on the project. Filter charts shall be enclosed in a durable polymer based frame with a cover safety glass.

- 17. Insert color graphic with embedded parameters for ATC system into record and information booklet.
- 18. Filter charts indicating equipment served, size, and type of filter required.
- 19. Documentation of strainer pulling and cleaning.

D. Submit Record and Information Booklets prior to anticipated date of substantial completion for Engineer review and approval. Substantial completion requires that Record and Information booklets be reviewed and approved.

3.16. INSTALLATION AND COORDINATION DRAWINGS

A. Prepare, submit, and use composite installation and coordination drawings to assure proper coordination and installation of work. Drawings shall include, but not be limited, to the following:

- 1. Complete Ductwork, Plumbing, Sprinkler and HVAC Piping Drawings showing coordination with lights, electrical equipment, HVAC equipment and structural amenities.

B. Draw plans to a scale not less than 3/8-inch equals one foot. Include plans, sections, and elevations of proposed work, showing all equipment, piping and ductwork in areas involved. Fully dimension all work including lighting fixtures, conduits, pullboxes, panelboards, and other electrical work, walls, doors, ceilings, columns, beams, joists and other architectural and structural work.

C. Identify all equipment and devices on wiring diagrams and schematics. Where field connections are shown to factory-wired terminals, include manufacturer's literature showing internal wiring.


D. Refer to Division 01 Section "Project Management and Coordination" for additional requirements related to coordination drawings.

3.17. PIPING SYSTEMS TESTING

A. The entire new HVAC piping systems shall be tested hydrostatically before insulation covering is applied and proven tight under the following gauge pressures for a duration of four (4) hours. Testing to be witnessed by Owner's representative and documented in writing.

SYSTEM	TEST PRESSURE
Heating, and Chilled Water Supply & Return Piping, Including Chemical Treatment Piping	100 psi
Refrigerant Piping	550 psig with Nitrogen

B. All new piping shall be pressure tested in accordance with NFPA-30. Piping systems shall be proven tight under the following gauge pressures for a duration of four (4) hours:



- C. Ductwork pressure testing shall be as specified in another division of these specifications.
- D. Testing and acceptance thereof shall be in accordance with local requirements and shall meet approval of authority having jurisdiction. Submit certificates and approved permits and insert one (1) copy in the *Operations and Maintenance Manuals*.
- E. Refrigerant piping shall be tested utilizing nitrogen per equipment manufacturer's requirements.

3.18. EQUIPMENT BY OTHERS

- A. This Contractor shall make all system connections required to equipment furnished and installed under other divisions or furnished by the Owner. Connections shall be complete in all respects to render this equipment functional to its fullest intent.
- B. It shall be the responsibility of the supplier of this equipment to furnish complete instructions for connections. Failure to do so will not relieve this contractor of any responsibility for improper equipment operation.

3.19. ADDITIONAL FILTERS AND BELTS

- A. One complete set of additional filters and belts shall be turned over to the owner upon final acceptance of the building by the owner. Provide correspondence to the Engineer (copy) documenting that additional filters and belts have been turned over to Owner.
- B. All filters and belts shall be tagged and identified for equipment served. Furnish filters in protection wrap.

3.20. PHASING

- A. Refer to Architectural Specifications and contract drawings for any required phasing.
- B. Maintain building egress and traffic ways at all times. Coordinate egress requirements with the State Fire Marshal, the Owner and Authorities having jurisdiction.
- C. Provide dust barriers/partitions, penetration closures, etc, to ensure safety of building occupants and protection of existing surroundings.
- D. The Building shall remain watertight at all times.
- E. Refer to phasing plans for additional requirements.
- F. Provide necessary piping, valves, drips, piping, conduit, controllers, ATC wiring, etc. as required. Drain and refill piping systems as often as necessary to accommodate phasing and to minimize time length of outages. Provide steam traps, drips, valves, etc., to maintain existing steam system in operation until all equipment is connected to the hot water system. Temporarily feed new systems with existing system where required or shown on contract drawings.
- G. At completion of the first phase the ATC System shall be sufficiently complete to turn over HVAC equipment. All wiring, testing, balancing, commissioning, programming,

graphics, and ATC computer shall be completed and operational for all equipment in each phase prior to Owner taking ownership of the same.

- H. Within thirty days of Award of Contract, the Contractor shall submit a minimum of six (6) copies of the proposed Phasing Plan (Drawings and detailed written description) to the Architect for review and approval based on the general and specific requirements indicated on the Drawings and Specifications. The phasing plan shall reflect the work of all trades. The phasing plan shall be updated as often as needed (i.e. major deviations and/or modified sequence of events) and reviewed during each progress meeting so the facility and Architect can be aware of the areas of construction and progress as it relates to the approved schedule.
- I. Due to phased construction, some systems must be operated at part load conditions until later phases are completed.
- J. While work is in progress, except for designated short intervals during which connections are made, continuity of service shall be maintained to all existing systems. Interruptions shall be coordinated with the Owner as to time and duration. The contractor shall be responsible for any interruptions to service and shall repair any damages to existing systems caused by his operations.

3.21. STRAINER CLEANING

- A. All equipment strainers must be pulled and cleaned at substantial completion. Document in writing and via digital photographs that all strainers have been pulled and cleaned.
- B. One year after project substantial completion all strainers shall be pulled again and cleaned. Document in writing and via digital photographs that all strainers were pulled and clean at the one year after project substantial completion data.
- C. Insert documentation that the strainers have been pulled and cleaned in the Record and Information Books.
- D. Re-purge hydronic systems of all air after strainers are pulled and cleaned.

3.22. OUTAGES

- A. Provide a minimum of fourteen (14) days notice to schedule outages. The Contractor shall include in their bid outages and/or work in occupied areas to occur on weekends, holidays, or at night. Coordinate and get approval of all outages with the Owner.
- B. Submit *Outage Request form*, attached at end of this Section, to Owner for approval.

END OF SECTION

OUTAGE REQUEST

DATE APPLIED: _____ BY: _____

DATE FOR OUTAGE: _____ FIRM: _____

START OUTAGE-TIME: _____ DATE: _____

END OUTAGE -- TIME: _____ DATE: _____

AREAS AND ROOMS: _____

FLOOR(S): _____

AREA(S): _____

ROOM(S): _____

WORK TO BE PERFORMED: _____

SYSTEM(S): _____

REQUEST APPROVED BY: _____

(FOREMAN OR OTHER PERSON IN CHARGE)

(FOR OWNER'S USE ONLY):

APPROVED: _____

YES ___ NO ___ BY: _____ DATE: _____

DATE/TIME-AS REQUESTED: _____ OTHER : _____

OWNER'S PRESENCE REQUIRED: _____

YES: ___ NO: ___ NAME: _____

POINT OF CONTACT: _____ PHONE: _____

NOT FOR BIDDING PURPOSES

SECTION 23 05 05

HVAC PIPING, FITTINGS AND VALVES

PART 1. GENERAL

1.1. SUMMARY

- A. The conditions of the contract and other general requirements apply to the work specified in this section. All work under this section shall also be subject to the requirements of Division 23 Section, *Common Work Results for HVAC* and Division 01, *General Requirements*.
- B. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2. SYSTEM DESCRIPTION CONDITIONS

- A. Provide all labor and materials necessary to furnish and install all piping systems on this project as herein specified and/or shown on the drawings. Final connections to equipment furnished in other sections of the specifications shall be included under this section.
- B. All piping and insulation installed in ceiling plenums must be plenum rated and comply with NFPA and International Building Code (IBC).
- C. Where more than one piping system material is specified, ensure system components are compatible and joined to ensure the integrity of the system is not jeopardized. Provide necessary joining fittings. Ensure flanges, union, and couplings for servicing are consistently provided.
- D. Use unions, flanges, and couplings downstream of valves and at equipment or apparatus connections. Do not use direct welded or threaded connections to valves, equipment or other apparatus.
- E. Use non-conducting dielectric connections whenever jointing dissimilar metals in open systems.
- F. Provide pipe hangers and supports in accordance with ASTM B31.9 and MSS SP69 unless indicated otherwise.
- G. Use spring loaded "silent" check valves on discharge of all pumps.
- H. Use 3/4 inch (20 mm) ball valves with cap and chain for drains at main shut-off valves, low points of piping, bases of vertical risers, and at equipment. Pipe to nearest floor drain.
- I. At all runout piping serving equipment, use swing joints with elbows to prevent excessive movement of piping due to expansion.

1.3. QUALITY ASSURANCE

- A. Valves: Manufacturer's name and pressure rating marked on valve body.

- B. Welding Materials and Procedures: Conform to ASME Code and applicable state labor regulation. Provide certificate of compliance from authority having jurisdiction indicating approval of welders.
- C. Welders Certification: In accordance with ASME Section 9.
- D. All grooved joint couplings, fittings, valves, and specialties shall be the products of a single manufacturer. Grooving tools shall be of the same manufacturer as the grooved components.
 - 1. All castings used for coupling housings, fittings, and valve bodies shall be date stamped for quality assurance and traceability.
- E. Maintain one copy of each document on site.

1.4. DELIVERY, STORAGE AND HANDLING

- A. Deliver, store, protect and handle products to site under as hereinbefore specified.
- B. Accept valves on site in shipping containers with labeling in place. Inspect for damage.
- C. Provide temporary protective coating on cast iron and steel valves.
- D. Provide temporary end caps and closures on piping and fittings. Maintain in place until installation.
- E. Protect piping systems from entry of foreign materials by temporary covers, completing sections of the work, and isolating parts of completed systems.

1.5. ENVIRONMENTAL REQUIREMENTS

- A. Do not install underground piping when bedding is wet or frozen.

1.6. EXTRA MATERIALS

- A. Provide one (1) repacking kit for each size valve.

1.7. ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

PART 7. PRODUCTS

2.1. PIPE MATERIALS

- A. All materials, unless otherwise specified, shall be new and of the best quality of their respective kinds, and shall conform to the requirements and ordinances of local, state and insurance authorities having jurisdiction.

1. Heating & Chilled Water Supply & Return Piping, Chemical Treatment Piping, Glycol Piping, (Inside of Building):
 - a). Pipe: Schedule 40 Black steel pipe, ASTM A53
1-1/2 inch and smaller - Type F, ASTM A53 steel (CW) with threaded joints

2 inch and larger - Grade B, Type E, ASTM A53 steel (ERW) with welded, flanged or grooved joints.
 - b). Fittings & Joints: 2-1/2 inches & larger, schedule 40 wrought steel ASTM A234 Grade WPB or Std. B16.9 long radius welding; factory-fabricated from ASTM A53 pipe; or ASTM A536 ductile iron; 2 inches & smaller 125 lb. std. cast iron screwed, ASTM Standard B16.4; or Victaulic precision, cold drawn, stainless steel with elastomer O-ring seals. Joints shall be threaded or AWS D1.1 welded. Victaulic or approved equal grooved joints shall be acceptable.
 - c). Flanges: Wrought steel Class 150 welding neck. ASTM Standard B16.5.
 - d). Grooved Joint Couplings: Two ductile iron housings, pressure responsive elastomer gasket, and ASTM A449 zinc electroplated steel bolts and nuts. Couplings shall comply with ASTM F1476 Standard Specification for the Performance of Gasketed Mechanical Couplings for Use in Piping Applications.
 - i. Rigid Type: Coupling housings shall be cast with offsetting, angle-pattern bolt pads to provide joint rigidity and support and hanging in accordance with ASNI B31.1 and B31.9.

Victaulic Style 107H, Installation-Ready or approved equal, for direct stab installation without field disassembly, with grade EHP gasket, suitable for water service to +250 degrees F.
 - ii. Flexible Type: For use in locations where vibration attenuation and stress relief are required, and for the elimination of flexible connectors. Victaulic Installation-Ready Style 177 or Style 77, or approved equal.
 - iii. 14" and Larger: AGS Series, two segment coupling with lead-in chamfer on housing key and wide width FlushSeal gasket. Victaulic Style W07 (rigid) and Style W77 (flexible), or approved equal.
 - iv. Flange adapters shall be suitable for direct connection to ANSI Class 125 or 150 flanged components. Victaulic Style 741/W741, or approved equal.
 - v. Rolled form grooves only. Cut grooves are prohibited.
 - vi. Verify gasket compatibility on Chemical Treatment piping.
 - e). Gate Valves: 2-1/2 inches & larger - IBBM, 150 lb. OS&Y grooved end or flanged; 2 inches & smaller - 150 lb. Bronze body bronze trim. Basis of

Design: Victaulic Series 771V or approved equal.

For valves 4 inch and larger located in mechanical equipment spaces 10 feet-0 inch or greater above finished floor, valve shall have chain wheel operators with chains extending to within 6 feet-0 inch above finished floor. Chain wheels and guides shall be galvanized.

- f). Ball Valves: Shut-off valves 2 inches and smaller shall be ball valves. Ball valves shall be 150 lbs, brass or bronze body, standard port, 2 piece body, TFE seats with bronze trim. Ball valves shall be VicPress end, threaded end or solder end as required to accommodate piping. Ball valves shall be as manufactured by Victaulic, Conbraco, Crane, Apollo, Nibco, Watts or engineer approved equal.
- g). Globe Valves: 2-1/2 inches & larger – IBBM 125 lb std. flanged, with No. 1 disc; 2 inches & smaller - bronze 150 lb. std. screw ends, with #1 disc.
- h). Check Valves: 2-1/2 inches & larger – IBBM or stainless steel trim, 125 lb.std. grooved end or flanged spring-assisted swing check suitable for vertical or horizontal installation, with metal disc; 2 inch & smaller - 125 lb. std. screwed. Provide "silent" spring loaded check valves at all pump discharges. Victaulic Series 715/W715 or approved equal.
- i). Balancing Valves: Victaulic Series 377/365, DeZurik Series 100, Fig. 118 or approved equal, ductile iron or cast iron construction, stainless steel bearings, nickel seats (2 inches and larger) non-lubricated, eccentric plug with EPDM, chlorobutyl rubber or Bunz-N resilient faced plugs suitable for 230 degrees F, steel screwed with fig. 159, removable lever and open nut for valves 3 inches and smaller. For valves 4-inch and larger, provide gear operators and grooved ends or flanged connections. Provide chain operated valves for sizes 4-inches and larger located 10 feet-0 inches or more above finished floor. Chains shall extend to within 6 inch-0 inches above finished floor. All valves shall have adjustable memory stop. Chain wheel and guide shall be galvanized.
- j). Butterfly Valves: Victaulic Vic300 MasterSeal/ AGS-Vic300, DeZurik, high performance or Keystone K-Loc, type with infinite position lever (for 3-inches and smaller) and pressure-responsive seat or double seat type and memory stop. Provide gear operator on valves 4-inches and larger.
- i. Valve stem shall be stainless steel, and shall be offset from the disc centerline to provide complete 360 degree circumferential seating.
 - ii. Valve shall be rated to +250 deg F in sizes through 12-inches.
 - iii. Seat shall be elastomer, of a grade suitable for the intended service. The seat shall be pressure responsive in sizes through 12 inches.
 - iv. For valves 4 inches and larger located 10 feet-0 inches or more

above finished floor shall be provided with chain operators with chains extending to within 6 feet-0 inches above finished floor. Chain wheel and guide shall be galvanized.

k). Combination Shut-off/Balancing Valves:

Victaulic/ TA Hydronics, Taco Circuit Setter, Bell & Gossett Circuit Setter Plus, Flowset Accuset, Gerand, or as approved equal, 2-inch-3-inch 500 lb. rated Ametal (copper-alloy) body globe type or ball valve with bronze body/brass ball construction with glass and carbon filled TFE seats, in-line flow meter and balancing and shut-off valve with built in ball valve for flow adjustment. Valve shall have memory stop, calibrated nameplate, Schrader valve connections and preformed molded insulation. Valves shall be leaktight at full rated working pressure. Balance valve size shall be selected based on manufacturer's acceptable flow range and design flow rate. Pressure drop through combination shut off/balance valves shall not exceed 5 feet of head at design flow rate.

Coil-Hook-up Connections: Victaulic Coil-Kits Series 799 or 79V or approved equal may be used at coil connections. The kit shall include a autoflow balancing valve, Series 781 Strainer-Ball, Series 78U Union-Port fitting, with Series 78T ball valve and required coil hoses. A Style 793 and/or 794 differential pressure controller shall be provided as required.

l). Extended Valve Stems: Provide and install round collar type extended valve stems on all valves installed in insulated piping. Valve stem and collar shall be selected to suit insulation thickness and maintain valve handles outside of insulation.

m). Alternative:

At contractors option all HVAC water supply and return lines may be copper type L (ASTM Std. B88) with wrought copper fittings (ASTM Std. B 16.22) with brazed or 95-5 silver solder joints lead and antimony based solders are prohibited and all bronze valves may be used on piping 2 inches and less in size.

ii. At Contractors option, Viega Pro Press/ Mega Press Pressure Seal mechanical fittings may be utilized. Viega, ProPress Pressure Seal Fittings: Bronze or copper shall conform to ASME B16.51, ICC LC 1002, and IAPMO PS 117. ProPress fittings ½-inch thru 4-inch for use with ASTM B88 copper tube type L and ½-inch up to 1-1/4-inch annealed copper tube. ProPress fittings shall have an EPDM sealing element and Smart Connect (SC) feature. 2-1/2-inch thru 4-inch shall have a 420 stainless steel grip ring, PBT separator ring, EPDM sealing element and Smart Connect (SC) feature.

2. Refrigeration Piping:

a). Concealed: Tube Size ¾ -inch & Smaller:

ASTM B280, copper tube; Type ACR, soft annealed temper fittings; cast copper-alloy fittings for flared copper tubes; flared joints. Fittings shall be ASME B16.22, wrought copper. Joints shall be brazed, AWS A5.8, BCUP silver/phosphorous/copper alloy with melting range 1190 to 1480 degrees F.

- b). Concealed: Tube Size 7/8 inch through 4-1/8inches:

Copper tube, Type ACR, soft annealed temper; wrought-copper, brazed joint fittings; brazed joints.

- c). Exposed: Tube Size 3/4 Inch and Smaller:

Copper pipe, Type ASTM B88, Type K with brazed wrought-copper fittings conforming to ASME B16.22. Filler metal shall be brazing type conform to AWS A5.8.

- d). Exposed: Tube Sizes 7/8 Inch and Larger:

Copper pipe, Type ASTM B88, Type K with brazed wrought-copper fittings conforming to ASME B16.22. Filler metal shall be brazing type conforming to AWS A5.8.

- e). Brazed Joints: Braze joints using American Welding Society (AWS) classification BCuP-1 for brazing filler metal.

- f). Flexible connectors: 500-psig (3450-kPa) minimum operating pressure; stainless-steel core and high-tensile stainless-steel-braid covering; dehydrated, pressure tested, minimum 7 inches (180 mm) long.

- g). Diaphragm Packless Valves:

500-psig (3450-kPa) working pressure and 275 degrees Fahrenheit (135 degrees C) working temperature; globe design with straight-through or angle pattern; forged-brass or bronze body and bonnet, phosphor bronze and stainless-steel diaphragms, rising stem and handwheel, stainless-steel spring, nylon seat disc, and with solder-end connections.

- h). Packed-Angle Valves: 500-psig (3450-kPa) working pressure and 275 degrees Fahrenheit (135 degrees C) working temperature; forged-brass or bronze body, forged-brass seal caps with copper gasket, back seating, rising stem and seat, molded stem packing, and with solder-end connections.

- i). Check Valves: Smaller than NPS 1 (DN 25): 400-psig (2760-kPa) operating pressure and 285 degrees Fahrenheit (141 deg Celsius) operating temperature; cast-brass body, with removable piston, polytetrafluoroethylene seat, and stainless-steel spring; globe design. Valve shall be straight-through pattern, with brazed-end connections.

- j). Check Valves: NPS 1 (DN 25) and Larger: 400-psig (2760-kPa) operating pressure and 285 degrees Fahrenheit (141 deg Celsius) operating

- temperature; cast-bronze body, with cast-bronze or forged-brass bolted bonnet; floating piston with mechanically retained polytetrafluoroethylene seat disc. Valve shall be straight-through or angle pattern, with solder-end connections.
- k). Service Valves: 500-psig (3450-kPa) pressure rating; forged-brass body with copper stubs, brass caps, removable valve core, integral ball check valve, and with brazed-end connections.
 - l). Service valves for VRV branch selector boxes and indoor heat pumps shall be bi-directional Sporlan model EBVT with access fitting. Valves shall be rated for 700psig, shall be U.L. listed, suitable for full refrigeration service temperature range of -40°F to 325°F. Valves shall include the following additional features:
 - i. Welded body joint with forged brass body construction with extended copper fittings.
 - ii. Dual Teflon seals.
 - iii. Full size ports to minimize pressure drop.
 - iv. ¼ turn operation with stainless steel stop plate.
 - v. Internal ball relief port to allow positive shut-off in either direction, even during system evacuation.
 - vi. Suitable for R-410A refrigerant.
 - vii. Date code stamped into valve body.
 - m). Solenoid Valves: Comply with ARI 760; 250 deg Fahrenheit (121 deg Celsius) temperature rating and 400-psig (2760-kPa) working pressure; forged brass, with polytetrafluoroethylene valve seat, 2-way, straight-through pattern, and brazed-end connections; manual operator; fitted with suitable NEMA 250 enclosure of type required by location, with 1/2-inch (12.7mm) conduit adapter and 24-V, normally closed holding coil.
 - n). Pressure-Regulating Valves:

Comply with ARI 770; pilot operated, forged brass or cast bronze, stainless-steel bottom spring, pressure-gage tapings, 24-V dc standard coil, and wrought-copper fittings for brazed-end connections; suitable for refrigerant specified.
 - o). Pressure Relief Valves: Straight-through or angle pattern, brass body and disc, neoprene seat, and factory sealed and ASME labeled for standard pressure setting.
3. Cooling Coil A/C Condensate Drain and Floor Drain Piping that is Collecting A/C Condensate Piping:
- a). Pipe & Fittings: All A/C condensate drain piping, including floor drain piping that is collecting A/C condensate, shall be constructed of Type L copper tubing, with sweat fittings made with 95-5 solder. Washout plugs (cleanouts) shall be strategically located to allow periodic flush out of

system. At a minimum, provide washout plugs at equipment connections and at direction changes of 90 degrees F or greater.

- b). Provide backwater valve (ball float type) at connections of condensate piping to stormwater piping and air gap fitting. Backwater valve shall be Model Z1099 as manufactured by Zurn or approved equal. Backwater valve shall have drain coated cast iron body, plastic ball float, bronze backwater bushing and replaceable neoprene seat.
- B. Steel pipe shall be similar and equal to National Tube Company, Grinnell, Republic, or Bethlehem black or zinc-coated (galvanized) as hereinafter specified. Pipe shall be free from all defects which may affect the durability for the intended use. Each length of pipe shall be stamped with the manufacturer's name.
- C. Copper pipe shall be Revere, Anaconda or Chase with approved solder fittings.
- D. Welding fittings for steel pipe shall meet the requirements of ASTM Standard A-23 and shall be standard catalog products. Fittings fabricated by mitering and notching pipe will not be accepted.

2.2. PIPE HANGERS, ROLLER SUPPORTS, ANCHORS, GUIDES, AND SADDLES

- A. All hangers for metallic piping shall be adjustable, wrought clevis type, or adjustable malleable split ring swivel type, having rods with machine threads. Hangers shall be Grinnell Company's Figure 260 for pipe ¾-inch and larger, and Figure 65 for pipe 2-inches and smaller, or approved equal. Adjustable pipe stanchion with U-bolt shall be Grinnell Company's Figure 191. Pipe roller supports shall be Grinnell's Figure 181 or Figure 271. Exterior pipe hangers shall be galvanized or stainless steel construction. For copper piping in direct contact with the hanger, hanger construction shall be copper coated to prevent contact of dissimilar metals similar to Grinnell's Figure CT-65. Hanger spacing and rod sizes for steel and copper pipe shall not be less than the following:

NOMINAL PIPE SIZE IN	STD. STEEL PIPE	MAXIMUM SPAN FT. COPPER TUBE	MINIMUM ROD DIAMETER INCHES OF ASTM A36 STEEL THREADED RODS
¾ & 1	6	5	3/8
1 - ½	6	8	3/8
2	8	8	3/8
2 - ½	10	9	½
3	12	10	½
4	14	12	5/8
5	14	12	5/8

NOMINAL PIPE SIZE IN	STD. STEEL PIPE	MAXIMUM SPAN FT. COPPER TUBE	MINIMUM ROD DIAMETER INCHES OF ASTM A36 STEEL THREADED RODS
6	16	14	3/4
8	18	16	7/8
10	20	18	7/8
12	20	18	7/8

- B. Anchors, guides, and roller supports shall be installed in accordance with the contract drawings and manufacturer's recommendations to provide pipe support and control pipe movement for all piping systems. Anchors and guides shall be securely attached to the pipe support structure. Submit shop drawing for proposed pipe support structure for guides and anchors for approval of the Structural Engineer. Pipe alignment guides shall be Fig. 255 Grinnell, or as approved equal. Guides shall be sized to accommodate the pipe with insulation. Guides shall be steel factory, fabricated, with bolted two section outer cylinder and base for alignment of piping and two section guiding spider for bolting to pipe.
- C. Hangers for pipe sizes ½ to 1 ½ inch (12 to 38 mm): Carbon steel, adjustable swivel, split ring.
- D. Hangers for cold pipe sizes 2 inches (50 mm) and over: Carbon steel, adjustable, clevis.
- E. Hangers for cold pipe sizes 2 to 4 inches (50 to 100 mm): Carbon steel, adjustable, clevis.
- F. Hangers for cold pipe sizes 6 inches (150 mm) and over: adjustable steel yoke, cast iron roll, double hanger.
- G. Multiple or Trapeze hangers: Steel channels with welded spacers and hanger rods.
- H. Multiple or Trapeze hangers for hot pipe sizes 6 inches (150 mm) and over: Steel channels with welded spacers and hanger rod, cast iron roll.
- I. Wall support for pipe sizes to 3 inches (76 mm): cast iron hook
- J. Wall support for pipe sizes 4 inches (100 mm) and over: Welded steel bracket and wrought steel clamp.
- K. Wall support for hot pipe sizes 6 inches (150 mm) and over: welded steel bracket and wrought steel clamp with adjustable steel yoke and cast iron roll.
- L. Vertical Support: Steel riser clamp.
- M. Floor support for cold pipe: Cast iron adjustable pipe saddle, lock nut, nipple, floor flange, and concrete pier or steel support.

- N. Floor support for hot pipe sizes to 4 inches (100 mm): Cast iron adjustable pipe saddle, lock nut, nipple, floor flange, and concrete pier or steel support.
- O. Floor support for hot pipe sizes 6 inches (150 mm) and over: Adjustable cast iron roll and stand, steel screws, and concrete pier or steel support.
- P. Copper pipe support: Carbon steel ring, adjustable, copper plated.
- Q. Hanger rods: Mild steel threaded both ends, threaded one end, or continuous threaded.
- R. Inserts: Malleable iron case of galvanized steel shell and expander plug for threaded connection with lateral adjustment, top slot for reinforcing rods, lugs for attaching to forms; size inserts to suit threaded hanger rods.
- S. For exterior pipe supports provide stainless steel brackets and anchors.

2.3. HYDRONIC EXPANSION LOOPS

- A. Provide hydronic flexible expansion loops of size and material noted on drawings as manufactured by Metroloop or approved equal. Flexible loops shall be designed to impart no thrust loads on the anchors. The loop shall consist of two flexible sections of hose and braid, two 90 degree elbows, and a 180 degree return. Loops shall be installed in a neutral, precompressed, or pre-extended condition as required for application. Loops are to be installed within four pipe diameters, both upstream and downstream, from a pipe guide.
- B. Where indicated provide nested loops and support the 180 degree return bend. Nested loops shall be sized to absorb the axial compression movement as scheduled on the contract drawings.

2.4. VALVES

- A. Provide parts list and assembly drawings (exploded view) for all valves in shop drawing submittals. Provide valves of the same type by the same manufacturer.
- B. Check valves in base mounted pump discharges shall be of the vertical type and shall be Victaulic Series 716/ W715, Miller "non-slam" check valves or approved equal suitable for service intended. Check valves in circulator discharges shall be horizontal type.
- C. Provide at each base mounted pump a suction diffuser of size and type shown on drawings. Units shall consist of a ductile cast iron angle type body with inlet vanes, magnetic insert, and blowdown connection tapped gauge post, 125 psi ANSI flange and a combination stainless steel diffuser strainer with 5/32 or 3/16-inch diameter opening for pump protection. Unit shall be equipped with a disposable fine 20-mesh stainless steel start up strainer which shall be removable after 30 days. Flow direction shall be from inside the strainer to outside for ease of service and cleaning. The body shall fit the pump and connecting pipe size. The unit shall be provided with a base support boss or an adjustable support foot to relieve piping strains from the pump suction. Suction diffuser shall be Victaulic 731 Series, Taco "SD" Series Catalog 300-4.1, Bell and Gossett Model FLG, Armstrong, Patterson, or engineer approved equal.

- D. Multi-purpose valve (non-slam check valve, throttling valve, shut-off valves and calibrated balancing valve) shall be provided at discharge side of constant speed pumps. The valve shall be of heavy-duty cast iron construction with standard ANSI flanged connections and rated for a maximum working pressure of 175 psig at 240°F. The valve shall be fitted with a stainless steel stem or stem sleeve and brass seat with "O" ring seal. Valve shall be Taco "Plus One" Number 300-4.2, Bell and Gossett 3DS Triple Duty Valve, Armstrong, Patterson, or as approved equal, and shall have check and plug valve features plus a memory stop with pointer and scale. Provide additional shut-off valve to allow servicing of check valve if a multipurpose valve is utilized in lieu of separate check, shut-off, and balance valve. Provide additional shut-off valve downstream of multi-purpose valve to allow servicing of multi-purpose check valve feature. Provide pre-manufactured, removable insulation covers for all multipurpose valves.
- E. Triple Duty Valve Assembly: Assembly shall consist of a Victaulic Master Seal or approved equal butterfly valve with memory stop and a Series 779 Venturi-Check, rated for water service to 230 degrees Fahrenheit (110 degrees Celsius) and pressures to 300 psig (2065-kPa).
- F. Do not install multipurpose valves or balance valves on the discharge of variable speed pumps.

2.5. AUTOMATIC FLOW CONTROL VALVES

- A. Automatic flow control valves shall be provided and installed where indicated. Units shall be factory set to maintain constant flow with plus or minus 5 percent over system pressure fluctuations, and equipped with a readout kit including flow meter, probes, hoses, flow charts, and carrying case. Each valve shall have an identification tag attached by chain and be factory marked with the zone identification, valve number and flow rate. Valves shall be line size and shall be Model AC or WU as manufactured by Flow Design, Inc., Victaulic Series 76, Griswald Controls, Bell & Gossett, or approved equal.
- B. Valves shall be selected for 2 - 32 psig flow range. Furnish valves with extended valve handle, stem extender, ball valve, flow regulator and unions.
- C. Design:
1. The GPM for the automatic flow control valves shall be factory set and shall automatically limit the rate of flow to within 5% of the specified GPM over at least 95 percent of the control range.
 2. For ½ -inch – 2-inches, the flow cartridge shall be removable from the Y-body housing without the use of special tools to provide access for regulator change-out, inspection and cleaning without breaking the main piping. (Access shall be similar to that provided for removal of a Y-strainer screen).
 3. Pump Head Requirements: the permanent pressure loss added to the pump head shall not exceed seven feet.
 4. Each valve shall have two P/T ports.

5. All automatic flow control devices shall be supplied by a single source and certified flow tests, witnessed by a professional engineer, shall be available.
6. Five-year product warranty and free first-year cartridge exchange, up to 10 percent.

D. Construction:

1. The internal wear surfaces of the valve cartridge shall be stainless steel.
2. The internal flow cartridge body shall have machined threads so the spring free height may be compensated for without the use of fixed shims. A crimped sheet metal design is not acceptable.
3. The internal flow cartridge shall be permanently marked with the GPM and spring range.
4. For ½-inch through 2-inch pipe sizes: An assembly shall consist of a brass Y-type body, integral brass-body ball valve and "O" ring type union; Flow Design Model AC or approved equal.
5. For 2 ½-inches and larger flanged connections: Ductile-iron body suitable for mounting wafer style between standard 150# or 300# flanges. The long flange bolts and nuts shall be provided with each control valve. Flow Design Model WS or approved equal.
6. All valves shall be factory leak tested at 100 psig air under water.

E. Minimum ratings:

1. ½-inch through 2-inch pipe size: 400 PSIG at 250 degrees Fahrenheit.
2. 2 ½ -inch through 14-inch pipe size: 600 PSIG at 250 degrees Fahrenheit.
3. 16-inch through 30 -inch pipe size: 250 PSIG at 250 degrees Fahrenheit.

F. Flow Verification

1. The differential pressure across the Automatic Flow Control Valve shall be measured for flow verification and to determine the amount of system over heading or under pumping.

26. STRAINERS

- A. Strainers shall be of the basket or "Y" type and shall be heavy and durable, constructed of ductile iron to ASTM A536 or the best grade gray iron with the bottoms drilled and plugged. Bodies shall have arrows clearly cast on the sides to show flow direction. Strainers shall be equipped with easily removable covers and brass sediment baskets made of stainless steel or brass not less than #22 gauge in thickness. Total area of basket perforations shall be not less than four times the cross section of the entering pipe. Flow shall be into basket, and then out through the perforations. Strainers shall be suitable for water or the intended fluid. Strainers

2 inches and smaller shall have threaded or solder ends, 2 inches and larger shall have flanged ends.

- B. Strainer screens shall be stainless steel with perforations and shall be 1/16-inch for pipe sizes 5 inches and less, 1/8-inch (40 percent open area) perforations for pipe sizes 6-inch and greater.
- C. Provide valved and capped (with chain) blowdowns in each strainer. Blowdown valves shall be Appolo 78-100/200 series or as approved equal.
- D. Strainers shall be manufactured by Victaulic Style 732/W732, Watts, Mueller, Armstrong, Yarway, Spirax/Sarco or as approved equal.

2.7. UNIONS, FLANGES, AND COUPLINGS

- A. Unions in steel pipe 2-inches and smaller shall be malleable iron with brass inserted seats designed for a working pressure of 150 psig.
- B. Unions in copper pipe 2-inches and smaller shall be wrought fittings with bronze seats designed for a working pressure of 125 psig.
- C. Unions in stainless steel pipe 2-inches and smaller shall be hexagonal threaded type stainless steel unions, with VicPress ends. Basis of Design: Victaulic Style P584.
- D. Flanges for steel pipe over 2 inches shall be 150 psig, forged steel, slip on. Gaskets shall be 1/16 inch thick pre-formed neoprene.
- E. Flanges for copper pipe over 2 inches shall be bronze. Gaskets shall be 1/16 inch thick preformed neoprene.

2.8. MANUAL AIR VENTS

- A. Manual air vents shall be similar to the hereinafter specified gauge valves. Provide 1/4-inch size on 1/4-inch pipe and smaller, 1/2 -inch size on 1-inch pipe and larger. Install at all high points of piping. Valves shall be Crane No. 88, or as approved equal, with threaded ends, bronze body, bronze or brass bonnet and bronze stem.

2.9. AUTOMATIC AIR VENTS

- A. Provide at air separators, expansion tanks and where shown on the drawings, float actuated non-modulating high capacity air vent to purge free air from the system and provide a positive shut-off at pressures up to 150 psig at a maximum temperature of 250 degrees Fahrenheit. The high capacity air vent shall prevent air from entering the system if the system pressure drops below atmospheric pressure. The air vent shall be pilot operated for intermittent purging of free air up to pressures of 2 psig during normal system operation and diaphragm operated for full capacity purging of free air at pressures between 2 and 150 psig. The high capacity air vent shall be constructed of cast iron and fitted with components of type 313 stainless steel, brass, EPDM and silicone rubber. Pipe discharge to closest floor drains with Type K copper tubing. The high capacity vent shall be Model 107 by Bell and Gossett, Model 13w by Spirax Sarco, Taco, Spirotherm Spirotop, or as approved equal.

2.10. THERMOMETERS

- A. Unless otherwise indicated, thermometers shall be ASTM E1, in a glass type, organic filled, 9-inch scale size, corrosion-resistant metal case, with "any-angle" mounting with positive locking device. Terice Industrial Thermometers, Weksler Instruments, Ernst Gage Co., Miljoco, or approved equal. Insertion stem length shall suite the pipe size and configuration. Thermometer wells shall be brass with brass union hubs in copper and in ferrous piping. Where piping is insulated or otherwise covered, use wells with lagging extension. Where wells are installed in pipe tees at turns, increase pipe size so that well does not restrict flow. Accuracy shall be 2 percent.
- B. Unless otherwise indicated, thermometer ranges shall be as follows:
1. Chilled water, glycol systems: 0 degrees F to 100 degrees Fahrenheit, 1 degrees Fahrenheit Division
 2. Heating Water: 30 degrees Fahrenheit to 240 degrees Fahrenheit, 2 degrees Fahrenheit Division.
- C. Provide heat conducting compound in wells.
- D. At Contractor's option, light powered thermometers may be utilized in lieu of organic filled thermometers.

2.11. PRESSURE GAUGES

- A. Unless otherwise indicated, pressure gauges shall be the bronze bourdon tube type, 4-1/2-inch dial, stem mounting, cast aluminum adjustable pointer, 1 percent accuracy over middle half of scale range, 1-1/2 percent over balance: Terice Model 600C; Weksler Instruments, Ernst Gage Co., Miljoco, or as approved equal.
- B. Gauges shall have pressure, vacuum, compound, or retard ranges as required, select ranges so that the normal readings are at the approximate midpoint and maximum system pressures do not exceed full scale.
- C. Furnish and install a gauge valve at each pressure gauge. Gauge valves shall be Crane Model No. 88, Needle Valve, Ernst Gage Co. FLG 200, Wexler Instrument Corp. Type BBV4, or approved equal, rated for pressure intended.
- D. Gauge connections for pressure gauges, thermometers, or control instruments shall be made using tee fittings, except that gauge connections up to 1-inch size in steel may be using threaded extra heavy pipe couplings welded directly to the main, provided that the main is at least 2-inch size for 2-inch connections, 3-inch size for 3/4-inch connections, and 4-inch size for 1-inch connections. Minimum gauge connection shall be 2-inch ips.
- E. Provide snubbers on all gauges. Snubbers shall be No. 872 by Terice, RS1/RS6 by Wexler Instruments, Miljoco or as approved equal.

2.12. FLOW METERS

- A. Griswold or Bell & Gossett Venturi disturbed flow measurement quickset flow meters shall be utilized in lieu of sentinel type flow meters. Units shall consist of a spun steel venturi welded into the pipe. Disturbed fluid shall be channeled through the throat of the venturi with a multi-point Piezo Ring. Accuracy shall be $\pm 1\%$ PSID with no straight pipe run required. Furnish differential pressure gauge supplied with carrying case and hoses.

2.13. PIPING SPECIALTIES

- A. Furnish and install flexible pipe connections, as specified and/or shown on the drawings, at suction and discharge connections of all base mounted and vertical in-line pumps, and connections to chillers, all vibrating equipment, and elsewhere as shown. Pump flexible connections shall be utilized at pumps. Refer to Division 23 Section, *Vibration Controls for HVAC, Plumbing and Fire Protection Equipment* for specifications.
- B. Pressure relief valves shall be provided in the number and size required to relieve 110 percent of the full input to the systems. Valves shall be rated and installed in accordance with ASME, and CSD-1 including all amendments. Pipe discharge full size to floor drain, (with union) and support discharge pipe to prevent exerting any strain on relief valve body, piping to be Type-L copper. Water safety relief valves shall be Watts Series 740, Conbraco, Series 154A, Bell and Gossett, or approved equal. Provide pressure gauge adjacent to all safety relief valves.
- C. Gas relief valve piping shall be sized and installed in accordance with the latest edition of ASME Boiler & Pressure Vessel Code, CSD-1 including amendments. Pipe material shall be as specified for gas piping. Gas relief valve piping material shall be the same as hereinbefore specified for gas piping.

2.14. ESCUTCHEONS

- A. Provide chromium plated escutcheons properly fitted and secured with set screws on all exposed piping which passes through walls, floors or ceilings of finished spaces.
- B. All escutcheon plates shall be chrome plated spun brass of plain pattern, and shall be set tight on the pipe and to the building surface. Plastic escutcheon plates will not be accepted.

2.15. DIELECTRIC CONNECTIONS:

- A. Furnish and install electrically insulated dielectric waterway fittings, unions or flanges, as manufactured by Victaulic Company Style 47, EPCO Sales, Inc., or approved equal at the following locations:
 - 1. Where steel piping systems join copper piping.
 - 2. Where copper tube connects to domestic water storage tanks, water heaters, heat exchangers, expansion tanks, and other steel vessels.
 - 3. Avoid the installation of steel nipples, cast iron or steel valves and specialties, or other ferrous components in predominately copper piping systems. Where such installation is necessary, isolate the component with dielectric connections. Do not mix steel pipe and copper tube in the same run of pipe or in the same section of a

pipng system.

4. Dielectric Waterway: Copper silicon casting conforming to UNS C87850 with grooved and/or threaded ends. UL classified in accordance with NSF-61 for potable water service, and shall meet the low-lead requirements of NSF-372. Basis of Design: Victaulic Series 647.

2.16. SLEEVES

- A. Sleeves shall be provided around all pipes through walls, floors, ceilings, partitions, roof structure members or other building parts. Sleeves shall be standard weight galvanized iron pipe two sizes larger than the pipe or insulation so that pipe or insulation shall pass through masonry or concrete walls or floors. Provide 20 gauge galvanized steel sheet or galvanized pipe sleeves for all piping passing through frame walls.
- B. Sleeves through floors shall be flush with the floor except for sleeves passing through Equipment Rooms which shall extend 3/4-inch above the floor. Refer to Division 23 Section, *Vibration Controls for HVAC, Plumbing and Fire Protection Equipment* for mechanical equipment room penetrations additional requirements. Space between the pipe and sleeve shall be caulked. Escutcheon plates shall be constructed to conceal the ends of sleeves. Each trade shall be responsible for drilling existing floors and walls for necessary sleeve holes. Drilling methods and tools shall be as hereinbefore specified.
- C. Sleeves through walls and floors shall be sealed with a waterproof caulking compound.
- D. Firestop at sleeves that penetrate smoke barriers smoke partitions and/or rated walls/floors.

2.17. PRESSURE REDUCING VALVES

- A. Provide pressure reducing valves as indicated, of size and capacity selected by the installer to maintain operating pressure on the system. Body shall be cast-iron or bronze construction, renewable stainless steel seat, non-corrosive disc, water tight cage assembly, adjustable pressure ranges and inlet strainer Watts Regulator Model 223-S, Armstrong, Bell and Gossett or as approved equal.
- B. Provide pressure gauge adjacent to all pressure reducing valves to verify proper set point.

2.18. WATER PROOF PIPE PENETRATION SEALS

- A. Provide and install waterproof pipe penetration seals at all pipes that enter the building below grade or through exterior wall.
- B. Link seals are to be Metraflex Metraseals, Model MS, Linkseal, or approved equal, black EPDM seal material, glass reinforced plastic pressure plates, zinc plated nuts and bolts, seals are to be resistant to sunlight and ozone, pressure rated to make a hydrostatic seal of up to 20 psig and up to 40 feet of head, temperature rated from -40 degrees F to 250 degrees Fahrenheit.

2.19. TEST PLUGS

- A. Where indicated, furnish and install P/T plugs or Pete's Plugs as manufactured by IMAC Systems or approved equal.
- B. Description: Nickel-plated, brass-body test plug in NPS 2 (DN15) fitting. Test plugs shall be as manufactured by Trerice, Watts, Natural Meter or approved equal. Test-station fitting made for insertion in piping tee fitting.
- C. Body: Length as required to extend beyond insulation. Brass or stainless steel with core inserts and gasketed and threaded cap. Include extended stem on units to be installed in insulated piping.
- D. Thread Size: NPS ¼ (DN 8) or NPS ½ (DN15) as required, ASME B1.20.1 pipe thread.
- E. Pressure Rating: 500 psig minimum.
- F. Minimum Pressure and Temperature Rating: 500 psig at 200 degrees F.
- G. Core Inserts: One or two self-sealing valves, suitable for inserting 1/8 inch OD probe from dial-type thermometer or pressure gage. Chlorosulfonated polyethylene synthetic and EPDM self-sealing rubber.
- H. Core Insert: Self-sealing valve, suitable for inserting 1/8 inch OD probe from dial-type thermometer or pressure gage.
- I. Core Material for Air, Water, Oil, and Gas: 20 to 300 degrees F chlorosulfonated polyethylene synthetic rubber.
- J. Test-Plug Cap: Gasketed and threaded cap, with retention chain or strap.
- K. Pressure Gage and Thermometer Ranges: approximately two times the system's operating conditions.
- L. Self-closing valves with caps and retaining straps.

PART 3. EXECUTION

3.1. GENERAL PIPING INSTALLATION REQUIREMENTS

- A. All pipes shall be cut accurately to measurements established at the building, and shall be worked into place without springing or forcing, properly clearing all windows, doors and other openings. Excessive cutting or other weakening of the building structure to facilitate piping installation will not be permitted. All pipes shall be so installed as to permit free expansion and contraction without causing damage. All horizontal mains shall pitch down in the direction of flow with a grade of not less than 1 inch in 40 feet. All open ends of pipe lines, equipment, etc., shall be properly capped or plugged during installation to keep dirt or other foreign material out of the system. All pipes shall be run parallel with the lines of the building and as close to walls, columns and ceilings as may be practical, with proper pitch. All piping shall be arranged so as not to interfere with removal of other equipment on devices not to block access to doors, windows, manholes, or other access openings. Flanges or unions, as applicable for the type of piping specified, shall be provided in the piping at

connections to all items of equipment, coils, etc., and installed so that there will be no interference with the installation of the equipment, ducts, etc. All valves and specialties shall be placed to permit easy operation and access and all valves shall be regulated, packed and glands adjusted at the completion of the work before final acceptance. All piping shall be installed so as to avoid air or liquid pockets throughout the work. Ends of pipe shall be reamed so as to remove all burrs.

- B. All piping shall be graded to convey entrained air to high points where automatic air vents shall be provided. The size of supply and return pipes for each piece of equipment shall in no case be smaller than the outlets in the equipment.
- C. All piping shall be run to provide a minimum clearance of 2-inches between finished covering on such piping and all adjacent work. Group piping wherever practical at common elevations.
- D. All valves, strainers, caps, and other fittings shall be readily accessible.
- E. Drain valves with hose connections shall be provided at low points for drainage of piping systems. Blow down valves shall be provided at the ends of all mains and branches so as to properly clean by blowing down the lines throughout in the direction of normal flow.
- F. Discharge lines from all relief valves shall be piped to within 4-inches of floor and extend to floor drains wherever floors are not pitched to drains. Pitch the relief valve piping away from the relief valve to insure that no fluid can be trapped in valve discharge. Support all relief valve piping to prevent exerting strain on the relief valve body. The end of the relief valve discharge piping shall not be threaded to prevent capping or plugging.
- G. All branches from water mains shall be taken from the top of the supply mains at an angle of forty-five (45) degrees above the horizontal, unless otherwise directed. Branches feeding down shall be taken from the side or bottom of the main on water mains only. All connections shall be carefully made to insure unrestricted circulation, eliminate air pockets or trapped condensate and permit the complete drainage of the system.
- H. Cutoff valves shall be provided on each branch line from the mains on all heating/air conditioning lines.
- I. Shut-off valves shall be installed at the inlet and outlet of each coil and piece of equipment to permit isolation for maintenance and repair. Units having multiple coils shall have separate valves for each coil.
- J. Balancing valves shall be installed in all heating/air conditioning water branches and at all pumps, and where indicated on the drawings.
- K. Unions shall be installed on all bypasses, ahead of all traps, at all connections to equipment, where shown on drawings or where required to facilitate removal of equipment whether shown or not.
- L. Spring clamp plates (escutcheons) shall be provided where pipes are exposed in the building and run through walls, floors, or ceilings. Plates shall be chrome plated spun brass of plain pattern, and shall be set tight on the pipe and to the building surface.

- M. If the size of any piping is not clearly evident in the drawings, the Contractor shall request instructions for the Engineer as to the proper sizing. Any changes resulting from the Contractor's failure to request clarification shall be at his expense. Where pipe size discrepancies or conflicts exist in the drawings, the larger pipe size shall govern.
- N. Approved expansion loops shall be provided to permit free expansion and contraction of all piping systems.
- O. Install all valves with stem upright or horizontal, not inverted.
- P. Where pipe support members are welded to structural building framing, scrape, brush clean, weld and apply one coat of zinc rich primer.
- Q. Provide clearance for installation of insulation and access to valves and fittings.
- R. Protect piping systems from entry of foreign materials by temporary covers, completing sections of the work, and isolating parts of completed systems.
- S. All water containing pipes shall be routed clear of combustion air dampers and louvers to prevent freezing condition when dampers are open.
- T. Provide manual air vents at top of piping system.

3.2. THERMOMETER AND PRESSURE GAGE INSTALLATION REQUIREMENTS.

- A. Install thermometers and adjust vertical and tilted positions.
- B. Install separable sockets in vertical position in piping tees where fixed thermometers are indicated.
 - 1. Install with socket extending to one-third diameter of pipe.
 - 2. Fill sockets with oil or graphite and secure caps.
- C. Install pressure gages in piping tees with pressure-gage valve located on a pipe at most readable location.
- D. Adjust faces of thermometer and gages to proper angle for best visibility.
- E. Clean windows of thermometer and gages and clean factory-finished surfaces. Replace cracked and broken window, and repair scratched and marred surfaces with manufacturer's touch up paint.

3.3. VALVE INSTALLATION REQUIREMENTS

- A. Examine piping system for compliance with requirements for installation tolerances and other conditions affecting performance of valves. Do not proceed with installation until unsatisfactory conditions have been corrected.

- B. Examine valve interior for cleanliness, freedom from foreign matter, and corrosion. Remove special packing materials, such as blocks, used to prevent disc movement during shipping and handling.
- C. Operate valves from fully open to fully closed positions. Examine guides and seats made accessible by such operation.
- D. Examine threads on valve and mating pipe for form and cleanliness.
- E. Examine mating flange faces for conditions that might cause leakage. Check bolting for proper size, length, and material. Check gasket material for proper size, material composition suitable for service, and freedom from defects and damage.
- F. Do not attempt to repair defective valves; replace with new valve.
- G. Install valves as indicated, according to manufacturer's written instructions.
- H. Piping installation requirements are specified in other Division 23 Sections. Drawings indicate the general arrangement of piping, fittings, and specialties.
- I. Install valves with unions or flanges at each piece of equipment arranged to allow servicing, maintenance, and equipment removal without system shutdown.
- J. Locate valves for easy access and provide separate support where necessary.
- K. Install valves in horizontal piping with stem at or above the center of the pipe.
- L. Install valves in a position to allow full stem movement.
- M. For chain-wheel operators, extend chains to 60 inches above finished floor elevation.
- N. Adjust or replace packing after piping systems have been tested and put into service, but before final adjusting and balancing. Replace valves if leak persists.
- O. Install flow control valves with clearances from center line of valve to ceiling to allow servicing as required by manufacturer.

3.4. AUTOFLOW CONTROL VALVE INSTALLATION

- A. Install automatic flow control valves on the return lines of coils as indicated on the contract drawings. A balancing valve on supply side is not acceptable.
- B. The standard ports and handles shall clear 1-inch thick insulation. Provide handle and port extensions for all insulation over 1-inch thick. Do not insulate flow control valves used on heating coils.
- C. Install, on the supply side of coils, a Y-strainer (40 mesh, 2 GPM or less; 20 mesh, above 2 GPM) with brass blow down valve with 3/4-inch hose-end connection with cap. Inline (basket) strainer is not acceptable.

- D. Where installed in piping with a vapor barrier, field insulate valve body to prevent surface condensation.

3.5. REFRIGERANT PIPING AND ACCESSORIES INSTALLATION REQUIREMENTS

- A. Drawing plans, schematics, and diagrams indicate general location and arrangement of piping systems; indicated locations and arrangements were used to size pipe and calculate friction loss, expansion, pump sizing, and other design considerations. Install piping as indicated unless deviations to layout are approved on Shop Drawings.
- B. Install refrigerant piping according to ASHRAE 15.
- C. Install piping in concealed locations unless otherwise indicated and except in equipment rooms and service areas.
- D. Install piping indicated to be exposed and piping in equipment rooms and service areas at right angles or parallel to building walls. Diagonal runs are prohibited unless specifically indicated otherwise. All exposed piping shall be hard copper tubing with brazed joints. Refer to Architectural Contract Documents to determine exposed areas.
- E. Install piping above accessible ceilings to allow sufficient space for ceiling panel removal.
- F. Install piping adjacent to units to allow service and maintenance.
- G. Install piping free of sags and bends. Install VEE clevis hangers and VEE troughs on pipes less than ¾" inch in diameter.
- H. Install fittings for changes in direction and branch connections.
- I. Select system components with pressure rating equal to or greater than system operating pressure.
- J. Install piping as short and direct as possible, with a minimum number of joints, elbows, and fittings.
- K. Arrange piping to allow inspection and service of refrigeration equipment. Install valves and specialties in accessible locations to allow for service and inspection. Install access doors or panels as specified if valves or equipment requiring maintenance is concealed behind finished surfaces.
- L. Install refrigerant piping in protective conduit where installed below ground.
- M. Install refrigerant piping in rigid or flexible conduit in locations where exposed to mechanical injury.
- N. Slope refrigerant piping as follows:
 - 1. Install horizontal hot-gas discharge piping with a uniform slope downward away from compressor.
 - 2. Install horizontal suction lines with a uniform slope downward to compressor.

3. Install traps and double risers to entrain oil in vertical runs.
 4. Liquid lines may be installed level.
- O. When brazing, remove solenoid-valve coils and sight glasses; also remove valve stems, seats and packing, and accessible internal parts of refrigerant specialties. Do not apply heat near expansion-valve bulb.
- P. Install piping with adequate clearance between pipe and adjacent walls and hangers or between pipes for insulation installation.
- Q. Identify refrigerant piping and valves.
- R. Install sleeves for piping penetrations of walls, ceilings, and floors. Comply with requirements for sleeves specified in Division 23 Section, "Common Work Results for HVAC".
- S. Install sleeve seals for piping penetrations of concrete walls and slabs. Comply with requirements for sleeve seals specified in Division 23 Section, "Common Work Results for HVAC".
- T. Install escutcheons for piping penetrations of walls, ceilings, and floors. Comply with requirements for escutcheons specified in Division 23 Section, "Common Work Results for HVAC".
- U. Install the following pipe attachments:
1. Adjustable steel clevis hangers for individual horizontal runs less than 20 feet (6m) long.
 2. Roller hangers and spring hangers for individual horizontal runs 20 feet (6m) or longer.
 3. Pipe Roller, MSS SP-58, Type 44 for multiple horizontal piping 20 feet (6m) or longer, supported on a trapeze.
 4. Spring hangers to support vertical runs.
 5. Copper-clad hangers and supports for hangers and supports in direct contact with copper pipe.
- V. Install hangers for copper tubing with the following maximum spacing and minimum rod sizes:
1. NPS ½ (DN 15): Maximum span, 60 inches (1500mm); minimum rod size, ¼ inch (6.4mm).
 2. NPS 5/8 (DN 18): Maximum span, 60 inches (1500mm); minimum rod size, ¼ inch (6.4mm).
 3. NPS 1 (DN 25): Maximum span, 72 inches (1800mm); minimum rod size, ¼ inch (6.4mm).
 4. NPS 1-1/4 (DN 32): Maximum span, 96 inches (2400mm); minimum rod size, 3/8 inch (9.5mm).
 5. NPS 1-1/2 (DN 40): Maximum span, 96 inches (2400mm); minimum rod size, 3/8 inch (9.5mm).
 6. NPS 2 (DN 50): Maximum span, 96 inches (2400mm); minimum rod size, 3/8 inch

- (9.5mm).
7. NPS 2-½ (DN 65): Maximum span, 108 inches (2700mm); minimum rod size, 3/8 inch (9.5mm).
 8. NPS 3 (DN 80): Maximum span, 10 feet (3m); minimum rod size, 3/8 inch (9.5mm).
 9. NPS 4 (DN 100): Maximum span, 12 feet (3.7m); minimum rod size, 1/2 inch (13mm).
- W. For all interior refrigerant pipe/tubing that is less than 3/4inch in diameter, utilize VEE type clevis hanger Model 200 V and VEE type trough Model 200 VT; as manufactured by Carpenter and Patterson or approved equal. VEE trough materials shall be carbon steel with pre-galvanized finish. Install as required to maintain maximum hanger spacing requirements.
- X. Support multifloor vertical runs at least at each floor.
- Y. Furnish and install complete refrigerant piping systems between the indoor units and outdoor units, branch selector boxes, indoor units, and compressor units. Support piping in accordance with Division 23 Section, *HVAC Piping, Fittings, Valves, Etc.* Piping shall be sized as recommended by unit manufacturer taking into account length of vertical and horizontal runs, and refrigerant type. Provide and install dual sets of refrigerant piping on all units required to have dual independent circuits.
- Z. Furnish and install all required piping accessories including, but not limited to, thermal expansion valves, Sporlan, or approved equal, Packless isolation valves at condenser and evaporator coil, Henry or approved equal, charging valve with chained seal cap, Henry or approved equal, sight glasses, Henry or approved equal; filter dryer with replaceable cartridge, sporland, or approved equal, liquid line solenoid valve l20V/1/60 Hz., Sporlan, or approved equal. Contractor shall provide traps and double suction risers if required by equipment manufacturer. Pitch piping for proper oil return. Submit shop drawings on all components, and piping arrangements.
- AA. All accessories shall be ARI rated. Furnish required nitrogen and refrigerant to fully test and charge system. Flood piping system with nitrogen when brazing.
- BB. Refrigerant piping shall be Type 1 hard temper (ACR) copper tubing with wrought copper brazed fittings. Make joints with brazed wrought copper fittings.
- CC. Refrigerant piping shall be cleaned, dehydrated and evacuated. Piping shall be evacuated and held to less than 2.5 mm Hg vacuum for a period of not less than 12 hours without appreciable pressure rise. Vacuum shall then be broken with refrigerant or dry nitrogen and re-evacuated to 2.5 mm Hg vacuum for an additional 12 hours. Piping test to be witnessed by Owner's representative and documented in writing. Submit results of tests to Architect/Engineer.
- DD. All refrigerant/suction lines sets shall be fully insulated. Exterior pipe insulation shall be fully jacketed as specified in Division 23 Section, "HVAC Insulation". Exposed interior pipe insulation shall be fully jacketed as specified in Division 23 Section, "HVAC Insulation".
- EE. Follow ASHRAE 15, latest edition procedures for charging and purging of systems and for

disposal of refrigerant.

- FF. Provide replaceable cartridge filter-driers, with isolation valves and valved bypass.
- GG. Locate expansion valve sensing bulb immediately downstream of evaporator on suction line.
- HH. Provide external equalizer piping on expansion valves with refrigerant distributor connected to evaporator.
- II. Install flexible connectors at right angles to axial movement of compressor, parallel to crankshaft.
- JJ. Fully charge completed system with refrigerant after tested.
- KK. Provide electrical connection to solenoid valves.
- LL. Install liquid indicators in liquid line leaving condenser, in liquid line leaving, and on leaving side of liquid solenoid valves.
- MM. Install strainers immediately upstream from each automatic valve, including expansion valves, solenoid valves, hot-gas bypass valves, and compressor suction valves.
- NN. Install strainers in main liquid line where multiple expansion valves with integral strainers are used.
- OO. Install strainers in suction line of steel pipe.
- PP. Install moisture-liquid indicators in liquid lines between filter-driers and thermostatic expansion valves and in liquid line to receiver.
- QQ. Install flexible connectors at or near compressors where piping configuration does not absorb vibration.
- RR. Test and inspect refrigerant piping according to ASME B31.5, Chapter VI.
 1. Test refrigerant piping, specialties. Isolate compressor, condenser, evaporator, and safety devices from test pressure.
 2. Test high- and low-pressure side piping of each system at not less than the lower of the design pressure or the setting of pressure relief device protecting high and low side of system.
 - a). System shall maintain test pressure at the manifold gage throughout duration of test.
 - b). Test joints and fittings by brushing a small amount of soap and glycerin solution over joint.
 - c). Fill system with nitrogen to raise a test pressure of 150 psig (1035 kPa) or higher as required by authorities having jurisdiction.
 - d). Remake leaking joints using new materials, and retest until satisfactory results are achieved.
- SS. Adjust thermostatic expansion valve to obtain proper evaporator superheat requirements.

- TT. Adjust high- and low-pressure switch settings to avoid short cycling in response to fluctuating suction pressure.
- UU. Adjust set-point temperature of the conditioned air or chilled-water controllers to the system design temperature.
- VV. Perform the following adjustments before operating the refrigeration system, according to manufacturer's written instructions:
1. Open shutoff valves in condenser water circuit.
 2. Check compressor oil level above center of sight glass.
 3. Open compressor suction and discharge valves.
 4. Open refrigerant valves, except bypass valves that are used for other purposes.
 5. Check compressor-motor alignment, and lubricate motors and bearings.
- WW. Before installing copper tubing other than Type ACR, clean tubing and fittings with trichloroethylene.
- XX. Replace core of filter-dryer after system has been adjusted and design flow rates and pressures are established.
- YY. Charge system using the following procedures:
1. Install core in filter-dryer after leak test but before evacuation.
 2. Evacuate entire refrigerant system with a vacuum pump to a vacuum of 500 micrometers (67 Pa). If vacuum holds for 12 hours, system is ready for charging.
 3. Break vacuum with refrigerant gas, allowing pressure to build up to 2 psig (14 kPa).
 4. Charge system with a new filter-dryer core in charging line. Provide full-operating charge.

3.7. PIPE JOINTS INSTALLATION REQUIREMENTS

- A. **Welded Joints:** Joints in piping 2-1/2-inches and larger shall be fusion welded. Welding shall be in accordance with recommendations of the American Welding Society. Welding fittings shall conform in physical and chemical properties to the latest revisions of the American Society for Testing Materials.
- B. Qualify welding procedures, welders and operators in accordance with ASME B31.1, or ASME B31.9 as applicable, for shop and project site welding of piping work. Certify welding of piping work using Standard Procedure Specifications by, and welders tested under supervision of, National Certified Pipe Welding Bureau (NCPWB). Submit welders qualifications for approval.
- C. **Grooved Joints:** Grooved joint shall be installed in accordance with the manufacturer's

written recommendations. Grooved ends shall be clean and free from indentations, projections, or roll marks. The gasket shall be molded and produced by the coupling manufacturer of an elastomer suitable for the intended service. The coupling manufacturer's factory trained representative shall provide on-site training for the contractor's field personnel in the use of grooving tools and installation of product. The representative shall periodically visit the job site to ensure best practices in grooved product installation are being followed. (A distributor's representative is not considered qualified to conduct training.)

- D. Screwed Joints: All screwed joints shall be made with tapered threads properly cut. Screwed joints shall be made perfectly tight with a stiff mixture of graphite and oil, applied with a brush to the male threads on the fittings.
- E. Soldered Joints and Copper Piping: Joints in copper piping shall conform to the following minimum standards.
1. The pipes shall be cut to a length making certain that the ends are square, using a fine hacksaw blade or tube cutter. The ends of all pipes shall be reamed and all burrs removed.
 2. The outside end of the pipe and the cut end of the fitting shall be cleaned with steel wool, sand cloth, or steel wire brush. All dark spots shall be removed.
 3. The flux shall be applied evenly and sparingly to the outside end of the pipe and the inside of the outer end of the fitting until all surfaces to be jointed are completely covered. The piping and fitting shall be slipped together and reworked several times to insure an even distribution of the flux.
 4. The correct amount of solder per joint for each size pipe shall be used in accordance with the manufacturer's recommendations.
 5. Solder joints shall be made by using a direct flame from a torch.
 6. On pipe sizes larger than 1/4-inch, the fittings and valves in the pipe shall be moved or tapped with a hammer when the solder starts to melt to insure an even distribution of the solder.
 7. The excess solder shall be removed while it is still in the plastic state leaving a fillet around the cup of the fitting.
 8. Solder joints shall be suitable for working pressure of 100 psig and for working temperature of not less than 250 degrees F. The type of solder and flux used will be submitted for approval. Type 95-5 shall be the minimum standard.
 9. Lead and antimony-based solders shall not be used for potable water systems. Brazing and silver solders are acceptable.
- F. Where copper piping joins steel piping, approved bronze adapters shall be used.
- G. Prohibited Connections: No direct weld, soldered, or brazed connections, without unions or

flanges, shall be made to valves, strainers, apparatus, or related equipment. Right and left couplings, long threads, or caulking of pipe threads or gasket joints will not be permitted.

3.8. HANGERS, SUPPORTS, ANCHORS, GUIDES INSTALLATION REQUIREMENTS

- A. General: All hangers shall be of an approved type arranged to maintain the required grading and pitching of lines to prevent vibration and to provide for expansion and contraction. Provide protection saddles between hangers and insulation on heating water insulated pipe. Saddles shall be Grinnells Figure 173/273 or approved equal. Provide approved spacers between saddles and pipe where flexible insulation is specified. Provide insulation protection shields for insulated piping without saddles. Shield shall be Grinnell Figure 167 or as approved equal.
- B. Spacing: Regardless of spacing, hangers shall be provided at or near all changes in direction, both vertical and horizontal, for all piping. For cast iron soil pipe, one hanger shall be placed at each hub or bell.
- C. Vertical Lines: Shall be supported at their bases, using either a suitable hanger placed in a horizontal line near the riser, or a base type fitting set on a pedestal, foundation or support. All vertical lines extending through more than one floor level shall be supported at each floor with a riser clamp. Riser clamp shall be Grinnell Co. Figure 261, or approved equal. All vertical drops to pump suction elbows shall be supported by floor posts.
- D. Racks and Brackets: All horizontal piping on vertical walls shall be properly supported by suitable racks securely anchored into the wall construction. Where not practical to obtain ceiling anchorage, all piping near walls shall be supported by approved brackets securely anchored into the wall construction. Washer plates (Fib. 60, 60L) and other miscellaneous attachments, fasteners, etc. shall be Grinnell or as approved equal. All exterior hanger and bracket systems in their entirety shall be galvanized.
- E. Pipe Hangers and supports shall be attached to the panel point at the top chord of bar joist or at a location approved by the structural engineer.
- F. Select hangers and components for loads imposed. Secure rods with double nuts.
- G. Support of horizontal piping shall allow for vertical adjustment after installation of piping.
- H. Support overhead piping with clevis hangers.
- I. Do not support all parallel piping from the same joist. Stagger all supports in accordance with the structural engineer's recommendations.
- J. Install guides on piping adjoining expansion fittings and loops.
- K. Attach guides to pipe and secure to building structure.
- L. Install anchors at locations to prevent stresses from exceeding those permitted by ASME B31.9 and to prevent transfer of loading and stresses to connected equipment.
- M. Fabricate and install steel anchors by welding steel shapes, plates, and bars to piping and to

structure. Comply with ASME B31.9 and AWS D1.1.

- N. Construct concrete anchors of poured-in-place concrete of dimensions indicated and include embedded fasteners.
- O. Install pipe anchors according to expansion fitting manufacturer's written instructions if expansion fittings are indicated.
- P. Use grout to form flat bearing surfaces for expansion fittings, guides, and anchors installed on or in concrete.
- Q. Refer to structural documents for appropriate connection/attachment materials to building.

3.9. AIR VENTING INSTALLATION REQUIREMENTS

- A. The top of each hydronic water supply and return piping and other points as indicated or where necessary for the removal of air from the system or equipment, shall be vented using an approved type of manual air vent.
- B. In addition to manual air vents at high points of system, each item of water heat transfer equipment shall be manually vented using an approved type manual air vent. All air vents shall be accessible.

3.10. EXPANSION LOOPS AND SWING CONNECTION INSTALLATION REQUIREMENTS

- A. Install expansion fittings according to manufacturer's written instructions.
- B. Install expansion fittings in sizes matching pipe size in which they are installed.
- C. Align expansion fittings to avoid end-loading and torsional stress.
- D. Install pipe bends and loops cold-sprung in tension or compression as required to partly absorb tension or compression produced during anticipated change in temperature.
- E. Attach pipe bends and loops to anchors.
 - 1. Steel Anchors: Attach by welding. Comply with ASME B31.9 and ASME Boiler and Pressure Vessel Code: Section IX, "Welding and Brazing Qualifications."
 - 2. Concrete Anchors: Attach by fasteners. Follow fastener manufacturer's written instructions.
- F. Connect risers and branch connections to mains with at least five pipe fittings, including tee in main.
- G. Connect risers and branch connections to terminal units with at least four pipe fittings, including tee in riser.
- H. Connect mains and branch connections to terminal units with at least four pipe fittings, including tee in main.

3.11. PIPING IDENTIFICATION INSTALLATION REQUIREMENTS

- A. All piping shall be identified with painted background marked with the name of the service with arrows to indicate flow direction. Color code and system identification shall comply with ANSI Standards and piping identification system shall comply with ASME A13.1-81, scheme for the identification of piping systems and ASHRAE Fundamentals Handbook, latest edition.
- B. Markings shall be plain block letters, stenciled on pipes, and shall be located near each branch connection, near each valve, and at least every 10 feet on straight runs of pipe. Where pipes are adjacent to each other, markings shall be neatly lined up. All markings shall be located in such manner as to be easily legible from the floor. Pipe identification schedule shall be as follows:

OUTSIDE DIAMETER OF PIPE OR COVERING (INCHES)	LENGTH OF COLOR FIELD (INCHES)	SIZE OF LETTERS (INCHES)
½ to 1 ¼	8	½
1-½ to 2	8	¾
2 ½ to 6	12	1 ¼
8 to 10	24	2 ½
Over 10	32	3 ½

3.12. VALVE IDENTIFICATION REQUIREMENTS

- A. All valves shall be tagged with a numbered tag.
- B. The tags shall be made of 1-inch diameter brass tags fastened to the valve by means of brass chains. Numbers shall agree with valve numbers on diagrammatic herein before specified.
- C. Provide a minimum of six (6) valve charts with valve numbers indicating valve type, size, manufacturer and service.
- D. Additional valve charts shall be mounted behind glazed wooden frames and be hung in each mechanical equipment room including each air handling unit mechanical equipment room. Additional copies shall be provided in each copy of the O&M manuals.

3.13. CLEANING PIPING AND EQUIPMENT

- A. All glycol, chilled water, condensate, heating water, and HVAC systems shall be cleaned by filling with a solution of one (1) pound of trisodium phosphate to each 50 gallons of water and circulating this solution for a period of six (6) hours during which time the system shall reach operating temperature. The systems shall then be flushed with fresh water and refilled with fresh water and/or where indicated antifreeze solution and purged of all air.
- B. All glycol, condensate, chilled water, heating water, HVAC, piping system shall be flushed

clean with fresh water. See Division 22 Sections, *Plumbing Fixtures* and *Plumbing Equipment* for domestic potable water cleaning and sterilization. Where indicated, hydronic systems shall be filled with 30 percent by volume antifreeze.

- C. Any equipment, such as coils that have small tubing, shall be bypassed to prevent deposition of debris from the piping. Water balancing shall not be scheduled until the completion of the cleaning and treatment process.
- D. All strainers shall be inspected and cleaned prior to testing and balancing. In addition, prior to substantial completion, contractor must inspect and clean all strainers.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 23 05 48

VIBRATION CONTROLS FOR HVAC, PLUMBING AND FIRE PROTECTION EQUIPMENT

PART 1 RELATED DOCUMENTS

1.1 GENERAL

- A. Drawings and General Provisions of Contract, including General and Supplementary Conditions and Division 01 Specification Sections apply to work of this section.
- B. All work under this section shall also be subject to the requirements of Division 23 Section, *Common Work Results for HVAC*.

1.2 SUMMARY

- A. Provide all labor and materials necessary to furnish and install vibration control systems on this project as herein specified and/or shown on the drawings.
- B. Mount all mechanical equipment on suitable vibration isolators so as to prevent transmission of vibration into or through the building structure. Isolators shall be as manufactured by Mason Industries, Inc., Korfund, Inc., Amber Booth, Vibration Mounting and Controls, or approved equal, and shall be selected by the isolator manufacturer for each item of equipment in accordance with requirements hereinafter specified.
- C. The equipment manufacturer shall supply all pump and motor bases, fan and motor bases, cradles, isolation pipe/duct hangers, spring and/or neoprene isolators, neoprene pads, flexible connectors, etc. as a coordinated package by a single manufacturer.
- D. Select isolators for uniform static deflections according to distribution of weight; and for not less than the indicated isolation efficiency with the lowest rotational speed of equipment as the disturbing frequency.
- E. Isolators and bases shall be stable during stopping and starting of equipment without transverse or eccentric movement of equipment, and shall be designed to resist horizontal forces of equipment which may operate unbalanced.
- F. In general, select isolators on the basis of criteria as specified in the ASHRAE Applications Handbook, Latest Edition.

1.3 SUBMITTALS

- A. Shop Drawings: Indicate inertia bases and locate vibration isolators, with static and dynamic load on each.
- B. Product Data: Provide schedule of vibration isolator type with location and load on each.
- C. Manufacturer's Installation Instructions: Indicate special procedures and setting dimensions.
- D. Manufacturer's Certificate: Certify that isolators are properly installed and adjusted to meet or

exceed specified requirements.

1.4 PROJECT RECORD DOCUMENTS

- A. Record actual locations of hangers including attachment points.

1.5 COLOR CODING

- A. All springs shall be color coded for load carrying capacity.

1.6 ALTERNATES

- A. Refer to Division 01 Section, *Alternates* - Alternates for description of work under this section affected by alternates.

PART 2 PRODUCTS

2.1 MANUFACTURER

- A. Isolators shall be the equivalent of the following types by Mason Industries, Inc., Korfund, Inc. or approved equal.

2.2 CORROSION PROTECTION FOR STEEL PARTS

- A. Where steel parts are exposed to weather or humid environments provide hot-dipped galvanized coating of at least 2 ounces of zinc per square foot of surface. Coat springs with neoprene.

2.3 SPRING MOUNTS AND SOUND PADS

- A. Provide all spring mounts with leveling devices, minimum .25 inch thick neoprene sound pads, and zinc chromate plated hardware.
- B. All sound pads shall be size for minimum deflection of .05 inch; meet requirements for neoprene pad isolators.

2.4 SPRINGS

- A. All springs shall have minimum horizontal stiffness equal to 75 percent vertical stiffness, with working deflection between .3 and .6 of maximum deflection.

2.5 NEOPRENE

- A. Grade durometer 40, 50 OR 60 AND OIL RESISTANT.

2.6 FLOOR MOUNTED ISOLATORS:

- A. Neoprene Isolation Pads: Provide pads at least ¼" thick with cross-ribbed or waffle design. For concentrated loads provide steel bearing plates bonded or cold cemented to the pads. Neoprene isolation pads shall be Type Super W.

- B. Neoprene Isolators: Rubber (neoprene)-in-shear mounting: Provide molded neoprene isolators having steel base plates with mounting holes and, at the top, steel mounting plates with mounting holes or threaded inserts. Provide elements of type and size coded with molded letters or color-coded for capacity identification. Embed metal parts completely in neoprene. Double deflection neoprene mountings shall have a minimum static deflection of 0.35". Bolt holes shall be provided for these areas where bolting is required. On equipment such as small vent sets and close coupled pumps, steel rails shall be used above the mounting to compensate for the overhang. Mountings shall be type ND or rails type DNR.

2.7 SPRING ISOLATORS

- A. General: Provide spring isolators or protected spring isolators that are adjustable and laterally stable with free-standing springs of horizontal stiffness at minimum 80 percent of the vertical (axial) stiffness. For machine-attached and floor-attached restraining elements, separate from metal-to-metal contact by neoprene cushions 1/8 inch thick minimum. Provide neoprene acoustic friction pads at least 1/4 inch thick.
- B. Spring Isolator: Spring type isolators shall be free standing and laterally stable without any housing and complete with 1/4" neoprene acoustical friction pads between the baseplate and the support. All mountings shall have leveling bolts that must be rigidly bolted to the equipment. Spring diameters shall be no less than 0.8 of the compressed height of the spring at rated load. Springs shall have a minimum additional travel to solid equal to 50% of the rated deflections, compressed spring height and solid spring height. Mountings shall be type SLF as manufactured by Mason Industries, Inc. or as approved equal.
- C. Restrained Spring Isolator: Equipment with operating weight different from the installed weight such as chillers, boilers, etc. and equipment exposed to the wind such as air cooled chillers, and fans, shall be mounted on spring mountings as described above, but a housing shall be used that includes vertical limit stops to prevent spring extension when weight is removed. The housing shall serve as blocking during erection and mounts shall be located between the supporting steel and roof or the grillage and dunnage as shown on the drawings. The installed and operating heights shall be the same. A minimum clearance of 1/2" shall be maintained around restraining bolts and between the housing and the spring so as not to interfere with the spring action. Limit stops shall be out of contact during normal operations. Mounting shall be type SLR.

2.8 SUSPENSION ISOLATORS

- A. General: Provide hangers with suspension isolators encased in open steel brackets. Isolate hanger rods from isolator steel brackets with neoprene-lined opening.
- B. Suspension Neoprene Isolators: Provide double-deflection elements with minimum 3/8 inch deflection.
- C. Suspension Spring Isolators: Vibration hangers shall contain a steel spring and 0.3" deflection neoprene element in series. The neoprene element shall be molded with a rod isolation bushing that passes through the hanger box. Spring diameters and hanger box lower hole sizes shall be large enough to permit the hanger rod to swing thru a 30° arc before contacting the hole and short circuiting the spring. Springs shall have a minimum additional travel to solid equal to 50% of the rated deflection. Submittals shall include a scale drawing of the hanger showing the 30° capability. Hangers shall be type 30N.

- D. Precompressed Suspension Spring Isolators: Vibration hangers shall be as described in "C" above, but they shall be precompressed to the rated deflection so as to keep the piping or equipment at a fixed elevation during installation. The hangers shall be designed with a release mechanism to free the spring after the installation is complete and the hanger is subjected to its full load. Deflection shall be clearly indicated by means of a scale. Submittals shall include a scale drawing of the hanger showing the 30° capability. Hangers shall be type PC30N.
- E. Ductwork Suspension Spring Isolators: Vibration hangers shall contain a steel spring located in a neoprene cup manufactured with a grommet to prevent short circuiting of the hanger rod. The cup shall contain a steel washer designed to properly distribute the load on the neoprene and prevent its extrusion. Spring diameters and hanger box lower hole sizes shall be large enough to permit the hanger rod to swing thru a 30° arc before contacting the hole and short circuiting the spring. Spring shall have a minimum additional travel to solid equal to 50% of the rated deflection. Hangers shall be provided with an eye bolt on the spring and a provision to attach the housing to the flat iron duct straps. Submittals shall include a scale drawing of the hanger showing the 30° capability. Hangers shall be type W30.

2.9 INERTIA BASES

- A. Structural Bases: Vibration isolator manufacturer shall furnish integral structural steel bases. Bases shall be rectangular in shape for all equipment other than centrifugal refrigeration machines and pump bases which may be "T" or "L" shaped. Pump bases for split case pumps shall include supports for suction and discharge base ells. All perimeter members shall be beams with a minimum depth equal to 1/10th of the longest dimension of the base. Beam depth need not exceed 14" provided that the deflection and misalignment is kept within acceptable limits as determined by the manufacturer. Height saving brackets shall be employed in all mounting locations to provide a base clearance of one inch- bases shall be type WF.
- B. Structural Rails: Vibration isolator manufacturer shall provide steel members welded to height saving brackets to cradle machines having legs or bases that do not require a complete supplementary base. Members shall be sufficiently rigid to prevent strains in the equipment. Inverted saddles shall be type ICS.
- C. Concrete Bases: Vibration isolator manufacturer shall furnish rectangular structural beam or channel concrete forms for floating foundations. Bases for split case pumps shall be large enough to provide support for suction and discharge base ells. The base depth need not exceed 12" unless specifically recommended by the base manufacturer for mass or rigidity. In general, bases shall be a minimum of 1/12th of the longest dimension of the base, but not less than 6". Forms shall include minimum concrete reinforcement consisting of half inch bars or angles welded in place on 6" centers running both ways in a layer 1-1/2" above the bottom, or additional steel as is required by the structural conditions. Forms shall be furnished with steel members to hold anchor-bolt sleeves when the anchor bolts fall in concrete locations. Height saving brackets shall be employed in all mounting locations to maintain a 1" clearance below the base. Concrete shall be 3,000 psi concrete. Mass of concrete inertia bases shall be minimum of 2 times weight of isolated equipment. Bases shall be type K.

2.10 FLEXIBLE CONNECTORS FOR PIPING

- A. General: Straight or elbow flexible connectors rated for temperatures, pressures, and fluids to be

conveyed. Provide flexible connectors with the strength 4 times operating pressure at highest system operating temperature. Provide elbow flexible connectors with a permanently set angle.

- B. **Elastomeric Flexible Connectors:** Flexible neoprene connectors shall be manufactured of multiple plies of nylon tire cord fabric and neoprene both molded and cured in hydraulic rubber presses. No steel wire or rings shall be used as pressure reinforcement. Straight connectors shall have two spheres. Connectors up to and including 1 1/2" diameter may have threaded ends. Connectors 2" and larger shall be manufactured with floating galvanized flanges recessed to lock the connector's raised face neoprene flanges. Hoses shall be installed on the equipment side of the shut-off valves. Connectors shall be rated a minimum of 150 psi at 220 F. Flanged equipment shall be directly connected to neoprene elbows in the size range 2 1/2" through 12" if the piping makes a 90° turn at the equipment. All straight through connections shall be made with twin-spheres properly pre-extended as recommended by the manufacturer to prevent additional elongation under pressure. 12" and larger sizes operating above 100 psi shall employ control cables with end fittings isolated by means of 1/2" thick bridge bearing neoprene washer bushings designed for a maximum of 1000 psi.

Submittals shall include two test reports by independent consultants showing minimum reductions of 20 DB in vibration accelerations and 10 DB in sound pressure levels at typical blade passage frequencies.

Elbows shall be Mason-Flex type MFNEC, straight connectors Mason-Flex type MFTFU or MFTNC, and control cable assemblies type A/C.

- C. **Metal Flexible Connectors:** Fabricated of Grade E phosphor bronze, monel or corrugated stainless steel tube covered with comparable bronze or stainless steel braid restraining and pressure cover. Sizes 3" and larger shall be flanged. Sizes 2 1/2" and smaller shall have male nipples. Lengths shall be as indicated:

Nominal Diameter (Inches)	Diameter	Length (Inches)
1/2"		12"
3/4"		12"
1 1/2"		12"
1 1/2"		12"
2"		12"
2 1/2"		12"
3"		18"
4"		18"
5"		24"
6"		24"

8"	24"
10"	24"
12"	36"
14"	36"
16"	36"

Hoses shall be installed on the equipment side of the shut-off valves horizontally and parallel to the equipment shafts wherever possible. Hoses shall be type BSS.

2.11 NEOPRENE PAD ISOLATORS

- A. Rubber or neoprene waffle pads.
 - 1. 30 durometer
 - 2. Minimum 2 inch (13mm) thick
 - 3. Maximum loading 40 psi (275 kPa)
 - 4. Height of ribs shall not exceed 0.7 times width.
- B. Configuration: ½ inch (13mm) thick waffle pads bonded each side of ¼ inch (6 mm) thick steel plate.

2.12 RUBBER MOUNTS

- A. Molded rubber designed for 0.6 inches (13 mm) deflection with threaded insert.

PART 3 EXECUTION

3.1 GENERAL PROVISIONS

- A. Install vibration and noise isolation materials and equipment as indicated and in accordance with machinery manufacturer's instructions.
- B. Where neoprene elements of vibration isolator may be subjected to high pipe temperatures above 150°F, provide metal heat shields or thermal isolators.
- C. A minimum of 4" thick reinforced concrete housekeeping pads shall be provided under all floor mounted equipment. A minimum of 6" thick reinforced concrete housekeeping pads shall be provided under all chillers. Rest subbases on structural floor and reinforce with steel rods interconnected with floor reinforcing bars by tie bars hooked at both ends. Provide at least one (1) inch clearance between subbases and inertia bases, steel bases, and steel saddles with machinery in operation.
- D. All vibration isolators exposed to weather or humid environment shall be hot dipped galvanized with springs coated with neoprene in accordance with paragraph hereinbefore described.
- E. Concrete inertia bases shall be a minimum of two (2) times the weight supported. Clearance

- between the underside of the inertia base and the housekeeping pad below shall not be less than 1 inch. Concrete shall be 3000 psi. Install inertia bases in accordance with the recommendations of the machinery manufacturer and the inertia base manufacturer.
- F. Anchor Bolts and Grout: Secure machinery to foundations and inertia bases with anchor bolts. Grout equipment with baseplates, the full area under baseplates with premixed non-shrinking grout. After grout has set, remove wedges, shims, and jack bolts and fill spaces with grout.
- G. Common Machinery Foundations: Mount electrical motors on the same foundations as other machinery. Support piping connections, strainers, valves, and risers on the same foundation as the pumps.
- H. Vertical Stops: For machinery affected by wind pressure or having an operational weight different from installed weight, provide resilient vertical limit stops which prevent spring extension when weight is removed. Provide vertical stops for machinery containing liquid, such as water chillers. Spring isolated or protected spring isolated machinery must rock and move freely within limits of stops or seismic restraint devices.
- I. Machinery: Provide vibration isolators, flexible connections, and seismic snubbers in accordance with manufacturer's recommendations. Machinery with spring isolators or protected spring isolators shall rock or move freely within limits of stops or seismic snubber restraints.
- J. Stability: Isolators shall be stable during starting and stopping of machinery without traverse and eccentric movement of machinery that would damage or adversely affect the machinery or attachments.
- K. Lateral Motion: The installed vibration isolation systems for each piece of floor or ceiling mounted machinery shall have a maximum lateral motion under machinery start up and shut down conditions of not more than 1/4 -inch. Restrain motions in excess by approved spring mountings.
- L. Unbalanced Machinery: Provide foundation suspension systems specifically designed to resist horizontal forces for machinery with large unbalanced horizontal forces. Vibration isolator systems shall conform to the machinery manufacturer's recommendations.
- M. Nonrotating Machinery: Mount nonrotating machinery in systems which includes rotating or vibrating machinery on isolators having the same deflection as the hangers and supports for the pipe connected to.
- N. Unitized Machinery Assemblies: Unitized assemblies such as chillers with evaporator and condenser designed with end supports, may be mounted on steel rails and springs in lieu of steel bases and springs. Where the slab or deck is less than 4 inches thick, provide spring isolation units with the deflection double that of the vibration isolation schedule, up to a maximum static deflection of 5 inches.
- O. Roof and Upper Floor Mounted Machinery: On the roof or upper floors, mount machinery on isolators with vertical stops. Rest isolators on beams or structures designed and installed in accordance with the SMACNA ASMM Plate 61.
- P. Vibration isolation ceiling hangers shall be installed so that the hanger rods do not touch the

sides of the isolator housing, thereby seriously degrading the vibration isolation performance. Vibration isolation ceiling hangers shall be located so that the hanger housing may rotate 360° without touching any object.

- Q. Electrical Connections: Provide flexible conduit or multiple conductor cable connections for machinery with sufficient extra length to permit 2 inch minimum displacement in any direction without damage.
- R. Systems Not To Be Vibration Isolated: Do not provide vibration isolation for electrical raceways and conduits or for fire protection, storm, sanitary, and domestic water piping systems which do not include pumps or other vibrating, rotating, or pulsating equipment including control and pressure reducing valves.
- S. Install in accordance with manufacturer's instructions.
- T. Install isolation for motor driven equipment.
- U. Bases:
 1. Set steel bases for one inch (25mm) clearance between housekeeping pad and base.
 2. Set concrete inertia bases for 2 inch (50mm) clearance between housekeeping pad and base.
 3. Adjust equipment level.
- V. Install spring hangers without binding.
- W. On closed spring isolators, adjust so side stabilizers are clear under normal operating conditions.
- X. Prior to making piping connections to equipment with operating weights substantially different from installed weights, block up equipment with temporary shims to final height. When full load is applied, adjust isolators to load to allow shim removal.
- Y. Connect wiring to isolated equipment with flexible hanging loop.

3.2 PIPE ISOLATION

A. Horizontal Pipe Isolation:

1. Precompressed Suspension Spring Isolators:
 - a. For the first three pipe hangers in the main lines near the mechanical equipment provide precompressed suspension spring isolators. Floor supported piping shall rest on trained spring isolators. All precompressed suspension spring isolators hangers or the first three trained spring isolators mounts as noted above, will have the same static deflection as specified for the mountings under the connected equipment. If piping is connected to equipment located in basements and hangs from ceiling under occupied spaces, the first three hangers shall have 0.75" deflection for pipe sizes up to and including 3", 1.5" deflection for pipe sizes up to and including 6" and 2.5" deflection thereafter. All other hangers and mounts will have a minimum steel spring deflection of 0.75". Hangers shall be located as close

to the overhead supports as practical.

2. Combination Spring and Neoprene Suspension Hanger:
 - a. For horizontal runs in other than those hereinbefore specified provide suspension spring hangers (combination spring and neoprene) with .75" minimum steel spring deflection.
 - b. Chilled and Hot Water Piping:
 - 1). For the first 20 feet of the branch connection of the main supply and return piping at each floor.
 - 2). For all piping over 2" diameter.
- B. Floor-Supported Piping:
 1. Floor supports for piping in equipment rooms and adjacent to isolated equipment shall use vibration isolators as described hereinbefore and selected to the guidelines of hangers.
 2. The first three adjacent floor supports shall be the restrained spring type with a blocking feature that prevents load transfer to equipment flanges as the piping is filled and drained.
 3. Where piping is subject to larger thermal movement a slide plate shall be installed on the top of the isolator. Slide plate shall be teflon, graphite or steel.
 4. Provide a thermal barrier where neoprene products are installed directly beneath steam or hot water lines.
- C. Pipe Risers: Provide pipe riser supports with bearing plates and two layers of ¼ " thick ribbed or waffled neoprene pad loaded to not more than 50 psi. Separate isolation pads with ¼ " steel plate. Weld pipe riser clamps at anchor points to the pipe and to pairs of vertical acoustical pipe anchor mountings which shall be rigidly fastened to the steel framing.
- D. Supports at Base of Pipe Risers: Piping isolation supports at the base of risers shall be two layers of ½" thick heavy-duty neoprene pad separated by ¼ " thick steel plate. Use bearing plates sized to provide a pad loading of not more than 500 psi. Weld the stanchion between the pipe and isolation support to the pipe and weld or bolt to the isolation support. Bolt isolation support to the floor slab with resilient sleeves and washers. Where supplementary steel is required to support piping, provide a maximum deflection of 0.08 inches at the mid-span of this steel under the load. Rigidly support piping from the supplementary steel with the supplementary steel isolated from the building structure with isolators.
- E. Pipe Anchors: Attach each end of the pipe anchor to an omni-directional pipe isolator which in turn shall be rigidly fastened to the steel framing or structural concrete. Provide a telescoping pipe isolator of two sizes of steel tubing separated by a minimum ½ " thick pad of heavy-duty neoprene or heavy-duty neoprene and canvas. Provide vertical restraints by similar material to prevent vertical travel in either direction. The load on the isolation material shall not exceed 500 psi.

3.3 BOILER, MECHANICAL, FAN AND EQUIPMENT ROOM SOUND ISOLATION

- A. Do not allow direct contact between pipes or ducts and walls, floor slabs, roofs, ceilings or partitions of equipment rooms.
- B. Pipe Penetrations: All piping passing through mechanical equipment room and fan room walls, floors and ceilings shall be protected against sound leakage by means of an acoustical wall seal as described hereinbefore and fire stopping.
- C. Duct Penetrations: Provide with sound insulation equal to the sound attenuation value of the wall, floor, or ceiling penetrated.

3.4 FLEXIBLE PIPE CONNECTORS

- A. Provide flexible connectors in accordance with manufacturers instructions where piping systems serving vibration isolated equipment and as shown on the drawings. Flexible connectors shall be installed near the connection to the equipment. Where liquid pulsation dampening is required, flexible connectors with spherical configuration may be used. Provide restraints for pipe connectors at pumps to prevent connector failure upon pump start-up.
- B. Provide flexible connectors at connections of air compressors to piping systems.

3.5 ISOLATION FOR SPECIFIC EQUIPMENT

- A. The vibration isolator manufacturer shall provide isolators for all pieces of equipment provided for the job. Isolator shall be selected by the isolator manufacturer on the basis of criteria as specified in the ASHRAE Applications Handbook, latest edition, unless a more stringent requirement is indicated on the drawings.
- B. Pumps:
 - 1. All base mounted pumps shall be mounted on concrete inertia blocks supported on stable steel springs in series with ribbed neoprene pads selected for not less than 1.5 inch static deflection under full operating load. Mason Industries type SLF or as approved equal.
 - 2. Floor support of the initial pipe elbows at the pump discharge and suction diffuser at the pump intake shall be made from the isolated inertia base, not from the equipment room floor. Mason Industries Type K or as approved equal.
 - 3. Provide flexible pipe connections at pump suction and discharge. Mason Industries Type BSS or MFTNC/MFTFU with control rods type ACC or as approved equal.
 - 4. Provide discharge and suction vibration isolators at all vertical in-line pumps.
- C. Air Handling Units and Kitchen Make-up Air Units:
 - 1. All air handling units, make-up air units, kitchen make-up air units, units shall be supported on stable steel springs in series with ribbed neoprene pads selected for not less than 2.5" deflection under full operating load. Mason Industries type SLF springs or as approved equal. Following the manufacturer's specific installation instructions for

specific equipment is acceptable.

D. Fans:

1. Fans up to 22" wheel diameter shall be mounted stable steel springs in series with ribbed neoprene pads selected for not less than 1.5" static deflection (Mason Industries Type SLF or equivalent).
2. Fans with wheel diameters 24" and greater shall be mounted on unhoused stable steel springs in series with ribbed neoprene pads and structural rails selected for not less than 2.5" static deflection (Mason Industries Type SLF or equivalent and structural rail Type ICS with thrust restraint provisions) and rails shall be Type ICS.
3. All fans suspended from the ceiling, joists or roof structure, including outside air fans, return fans, relief air, ventilation fans, and exhaust fans, shall be suspended using hangers incorporating steel springs in series with neoprene, selected for not less than 3.5" static deflection under full load (Mason Industries Type 30N or equivalent).

E. Chillers: Chillers shall be mounted on restrained spring isolators with vertical limit stops for not less than 1 inch static deflection under full operating load. Isolators shall be Mason Industries Type SLR or as approved equal. All exterior isolators for chillers shall be hot dipped galvanized including all hardware. Provide neoprene coated springs.

F. Condensing Units: All condensing units shall be supported on stable steel springs in series with ribbed neoprene pads and structural rails selected for not less than 2.5" deflection under full operating load. All exterior isolators for condensing units shall be hot dipped galvanized including all hardware. Mason Industries Type SLF springs or as approved equal. Provide neoprene coated springs.

G. All horizontal, vertical, and recessed unit heaters shall be suspended using hangers incorporating steel springs in series with neoprene selected for not less than 1" static deflection under full load (Mason Industries Type 30N or equivalent).

H. Ductless Units: Indoor ductless units shall be supported with rubber grommet type suspension isolators. Outdoor ductless units shall be supported on ribbed neoprene pads resting on roof curbs (roof application) or concrete pad.

3.6 MANUFACTURER'S FIELD SERVICES

- A. Inspect isolated equipment after installation and submit report. Include static deflections.

END OF SECTION

SECTION 23 05 93

TESTING, ADJUSTING, AND BALANCING FOR HVAC AND PLUMBING

PART 1. GENERAL

1.1. GENERAL

- A. This section covers performance testing, adjusting and balancing of heating, ventilating, air conditioning and domestic re-circulating systems as specified in Division 23 Section, *Heating, Ventilating, and Air Conditioning Equipment* and in Division 22 Section, *Plumbing Fixtures and Plumbing Equipment*.
- B. For *Common Work Results of HVAC*, See Division 23. See Division 01 for *General Requirements*.
- C. The mechanical contractor shall select and employ an impartial, independent balancing agency to provide testing and balancing services for the heating, ventilating and air conditioning (HVAC) systems and other specified systems of this project.
- D. The work included in this section consists of furnishing labor, instruments, and tools required in testing, adjusting and balancing the HVAC and plumbing systems, as described in these specifications or shown on accompanying drawings. Services shall include checking equipment performance, taking the specified measurements, and recording and reporting the results.
- E. The items requiring testing, adjusting, and balancing include, but are not limited to, the following:

Air Systems:

Air Flow Monitoring Stations
Ceiling Paddle Fans
Coils (Air Temperatures & Static Pressure Drops)
Chimney Vent Fans
Diffusers, Registers and Grilles
Ductless Split System Units (Indoors, Outdoor, & water-cooled units)
Electric Unit Heaters
Exhaust Fans
Fan Coil Units
Heat Recovery Systems
Intake Hoods
Kitchen Hoods – Supply Plenums
Kitchen Make-up Air Units
Make-up Air Units
Power Relief Fans
Radiant Heat Panels
Relief Fans
Relief Hoods
Return Fans
Supply Fan AHU
Unit Heaters

Variable Refrigerant Volume Systems
Ventilation Fans
Zone Branch and Main Ducts

Hydronic Systems:

Autoflow valves
Boilers
Chillers
Coils
Condensate Pumps
Condensate overflow safety switches
Differential Pressure Bypass Valves
Fan Coil Units
Flow Measuring Stations
Flow Meter Fittings
Glycol Feed Pumps
In-line Pumps
Kitchen Ventilation Systems
Make-up Air Units/Outside Air Units
Pumps
System Mains and Branches
Unit Heaters

In addition, any existing fans, equipment, or devices specified to be re-used under this project shall be tested and balanced, similar to new fans.

1.2. EXAMINATION

- A. Verify that systems are complete and operable before commencing work. Ensure the following conditions:
1. Systems are started and operating in a safe and normal condition.
 2. Temperature control systems are installed complete and operable.
 3. Proper thermal overload protection is in place for electrical equipment.
 4. Final filters are clean and in place. If required, install temporary media in addition to final filters.
 5. Duct systems are clean of debris.
 6. Fans are rotating correctly.
 7. Fire dampers, smoke dampers, and volume dampers are in place and open.
 8. Air coil fins are cleaned and combed.
 9. Access doors are closed and duct end caps are in place.
 10. Air outlets are installed and connected.

11. Duct system leakage is minimized.
 12. Hydronic systems are flushed, filled, and vented.
 13. Pumps are rotating correctly.
 14. Proper strainer baskets are clean and in place.
 15. Service and balance valves are open.
- B. Submit field reports. Report defects and deficiencies noted during performance of services which prevent system balance.
- C. Beginning of work means acceptance of existing conditions.
- 1.3. QUALIFICATIONS OF THE BALANCE AGENCY
- A. The balancing agency shall be a member of the Associated Air Balance Council (AABC).
 - B. The certified test and balance engineer shall be responsible for supervision and certification for the total work herein specified.
 - C. All final reports shall be signed by the certified test and balance engineer.
- 1.4. PRE-BALANCING CONFERENCE
- A. Convene a conference one week prior to commencing work of this Section with all appropriate individuals.
- 1.5. STANDARDS
- A. The balancing agency shall perform the services specified herein in accordance with the Associated Air Balance Council's National Standards, including revisions, to the date of the contract.
 - B. All terms in this specification shall have their meaning defined as stated in the National Standards.
 - C. ADC: Test Code for grilles, registers, and diffusers.
 - D. ASHRAE III: Practice for measurement, testing, adjusting and balancing of building heating, ventilation, air conditioning, and refrigeration systems.
 - E. NEBB: Procedure standards for testing, adjusting, and balancing of environmental systems.
 - F. SMACNA: HVAC systems testing, adjusting, and balancing.
 - G. AABC: Associated Air Balance Council

1.6. COORDINATION

- A. It will be necessary for the balancing agency to perform its services in close coordination with the mechanical contractor.
- B. The plans and specifications have indicated meters, valves, dampers, and other devices for the purpose of adjusting the system to obtain optimum operating conditions. It will be the responsibility of the mechanical contractor to install these devices in a manner that will leave them accessible and readily adjustable. The balancing agency shall provide guidance if there is a questionable arrangement of a control or balancing device.
- C. The general contractor, mechanical contractor, temperature control contractor and suppliers of the HVAC equipment shall all cooperate with the balancing agency to provide all necessary data on the design and proper application of the system components.

1.7. INSTALLATION TOLERANCE

- A. Unless otherwise indicated, all air devices shall be adjusted to within plus or minus 10 percent of design. All fans shall be adjusted to within plus or minus 5 percent of design. All pumps and Hydronic equipment shall be adjusted to within plus or minus 5 percent of design.

1.8. RESPONSIBILITIES OF THE MECHANICAL CONTRACTOR

- A. The mechanical contractor shall sufficiently complete the installation and start all HVAC systems to insure they are working properly and shall perform all other items as described hereinafter to assist the balancing agency in performing the testing and balancing of the HVAC system.
- B. Record equipment manufacturer's standard start-up information and submit to Engineer for review. Testing and balancing work shall not commence on any equipment until start-up reports have been completed, reviewed by Engineer, and forwarded to Testing and Balancing Agency.
- C. Air Distribution Systems
 1. Verify installation for conformity to design.
 2. Terminate all supply, return, outside air, exhaust air, relief air, ventilation air ducts, and pressure test them for leakage. Test pressure and leakage rate shall be as specified in Division 23 Section, *HVAC Air Distribution System* under Leakage Tests. Pressure testing shall be performed by mechanical contractor and witnessed by Test and Balance Engineer.
 3. Ensure that all splitters, extractors, volume dampers, fire dampers, and smoke damper are properly located and functional. Dampers serving requirements of minimum and maximum outside - return - relief, and exhaust air shall provide tight closure and full opening, with a smooth and free operation.
 4. Verify that all supply - return - exhaust and transfer grilles; registers, and

diffusers are installed and operational.

5. Ensure that air-handling systems, units, and associated apparatus, such as heating and cooling coils, filter sections, access doors, etc., are blanked and/or sealed to eliminate excessive bypass or leakage of air.
6. Ensure that all fans are operating and free of vibration. All fans and drives shall be checked for proper fan rotation and belt tension. Overload protection shall be of proper size and rating. A record of motor current and voltage shall be made to verify that the motors do not exceed nameplate rating. Record thermal overload ratings for all motors in the Test and Balance Report.
7. Make any necessary changes to the sheaves, belts, and dampers, as required by the balancing agency, at no additional cost to the owner.
8. Install clean filters.
9. For heat pumps, provide refrigerant suction and discharge pressure to Test and Balance Engineer for inclusion in the final TAB Report.

D. Water Circulating Systems

1. Verify installation for conformity to design.
2. Check all pumps to verify pump alignment and rotation.
3. Ensure that systems are clean, with the proper strainer screens installed for normal operation.
4. Check all pump motors for current and voltage, to ensure that motors do not exceed nameplate rating.
5. Provide thermal overload protection of proper size and rating. Record thermal overload ratings for all motors. Insert data in Test and Balance Report.
6. Ensure that all water circulating systems shall be full and free of air; that expansion tanks are set for proper water level; and that all air vents were installed at high points of systems and are operating.

1.9. RESPONSIBILITIES OF THE TEMPERATURE CONTROL CONTRACTOR

A. The temperature control contractor shall complete the installation of the temperature control system, and operate and test all control systems to ensure they are functioning properly as designed. The temperature control contractor shall assist the balancing agency in testing and balancing the HVAC systems, as described hereinafter.

1. Verify that all control components are installed in accordance with project requirements and are functional, including all electrical interlocks, damper sequences, air and water reset, freeze stats and duct smoke detectors.
2. Verify that all controlling instruments are calibrated and set for design operating

conditions.

3. Calibrate temperature sensors after installation, and before the temperature sensors control verification tests are performed. The balancing agency shall prove the accuracy of final settings by taking temperature readings. The readings shall be in a typical conditional space for each separately controlled zone.
 4. The temperature control contractor shall allow sufficient time in the project to provide assistance and instruction to the balancing agency in the proper use and setting of control components such as, but not limited to, computers, static pressure controllers, or any other device that may need set points changed so that the testing and balancing work can be performed.
- B. All control sequences, software, equipment, and components shall be started-up by a qualified technician. Start-up report shall be submitted to Engineer prior to the commencement of testing and balancing work. Testing and balancing shall not commence until start-up reports are completed, reviewed by engineer and forwarded to Testing and Balancing Agency.

1.10. NOTIFICATION FOR TESTING AND BALANCING WORK TO BEGIN

- A. The mechanical contractor shall notify the balancing agency in writing when all heating, ventilating, and air conditioning systems are complete and ready for testing and balancing. The mechanical contractor shall attest that he has completed all items as herein described.
- B. The following must be completed prior to start of system balancing:
1. All duct work and associated grilles/registers/diffusers installed and completed.
 2. Piping systems completed, flushed and filled.
 3. Equipment properly started by qualified personnel or start-up technicians.
 4. Ceiling tiles installed.
 5. Automation system (temperature controls) installed and completed for both air and water systems.
 6. All equipment controlled in automatic ("Auto") mode.
 7. Access granted to the balancing contractor to the automation/controls system provided.

1.11. DEFICIENCIES

- A. Any deficiencies in the installation or performance of a system or component observed by the TAB agency shall be brought to the attention of the appropriate responsible person.
- B. The work necessary to correct items on the deficiency listing shall be performed and

verified by the affected Contractor before the TAB Agency returns to retest. Unresolved deficiencies shall be noted in the final report.

1.12. ADJUSTING

- A. Ensure recorded data represents actual measured observed conditions.
- B. Permanently mark settings of valves, dampers, and other adjustment devices allowing settings to be restored. Set and lock memory stops.
- C. After adjustment, take measurements to verify balance has not been disrupted or that such disruption has been rectified.
- D. Leave systems in proper working order, replacing belt guards, closing access doors, closing doors to electrical switch boxes, and restoring all sensors to specified settings.
- E. At final inspection, recheck random selections of data recorded in report. Recheck points or areas as selected and witnessed by the Owner.
- F. Check and adjust systems approximately six months after final acceptance and submit report.
- G. Permanently mark the locations of all duct traverses on the exterior surface of the duct insulation.

1.13. ALTERNATES

- A. Refer to Division 01 Section, *Alternates* for description of work under this section affected by alternates.

1.14. GENERAL COMMISSIONING REQUIREMENTS

- A. Refer to Division 01 Section, "General Commissioning" for description of work under this Division affected by General Commissioning.

PART 2. PRODUCTS (NOT APPLICABLE)

PART 3. EXECUTION

3.1. GENERAL

- A. Perform all testing and balancing in complete accordance with AABC National Standards for Field Measurements and Instrumentation.
- B. Furnish all test instruments and equipment. All instruments must have been calibrated within twelve (12) months prior to use and shall be checked for accuracy prior to and during the work. Submit certificate for calibration of all equipment utilized on project with date of calibration clearly identified.
- C. Review all systems designs and equipment, manufacturers' data, and be completely familiar with the work before proceeding.

- D. Report all malfunctions or deficiencies to the contractor so that corrective action can be taken. Test and Balance Report shall not be submitted for review until all malfunctions or deficiencies are corrected. Repeat tests where required until design conditions are achieved.
- E. Where systems or equipment cannot be balanced or adjusted to design conditions, determine the cause and submit a complete report to the Engineer.
- F. Retest or rebalance the system as required during the warranty period.
- G. Test and balance all systems under adequate load condition. If, in the opinion of the Engineer, there is insufficient load to properly test and balance the systems, perform sufficient preliminary balancing and adjustment to permit operation of the systems until such time as final testing and balancing can be done. Provide in writing the future date when systems shall be tested under sufficient load.
- H. At project completion provide a complete set of ½ scale drawings indicating the locations of all duct traverses.

3.2. EXAMINATION

- A. Examine the Contract Documents to become familiar with Project requirements and to discover conditions in systems' designs that may preclude proper TAB of systems and equipment.
- B. Examine systems for installed balancing devices, such as test ports, gage cocks, thermometer wells, flow-control devices, balancing valves and fittings, and manual volume dampers. Verify the locations of these balancing devices are accessible.
- C. Examine the approved submittals for HVAC systems and equipment.
- D. Examine design data including HVAC system descriptions, statements of design assumptions for environmental conditions and systems' output, and statements of philosophies and assumptions about HVAC system and equipment controls.
- E. Examine ceiling plenums used for supply, return, or relief air to verify that they meet the leakage class of connected ducts and are properly separated from adjacent areas. Verify that penetrations in plenum walls are sealed and fire-stopped if required.
- F. Examine equipment performance data including fan and pump curves.
 - 1. Relate performance data to Project conditions and requirements, including system effects that can create undesired or unpredicted conditions that cause reduced capacities in all or part of a system.
 - 2. Calculate system-effect factors to reduce performance ratings of HVAC equipment when installed under conditions different from the conditions used to rate equipment performance. To calculate system effects for air systems, use tables and charts found in AMCA 201, "Fans and Systems," or in SMACNA's "HVAC Systems – Duct Design". Compare results with the design data and installed conditions.

- G. Examine system and equipment installations and verify that field quality-control testing, cleaning and adjusting specified in individual Sections have been performed.
- H. Examine test reports specified in individual system and equipment Sections.
- I. Examine HVAC equipment and filters and verify that bearings are greased, belts are aligned and tight, and equipment with functioning controls is ready for operation.
- J. Examine terminal units, and verify that they are accessible and their controls are connected and functioning.
- K. Examine strainers. Verify that startup screens are replaced by permanent screens and indicated perforations.
- L. Examine heat-transfer coils for correct piping connections and for clean and straight fins.
- M. Examine system pumps to ensure absence of entrained air in the suction piping.
- N. Examine operating safety interlocks and controls on HVAC equipment.
- O. Report deficiencies discovered before and during performance of TAB procedures. Observe and record system reactions to changes in conditions. Record default set points if different from indicated values.

3.3. AIR SYSTEM PROCEDURES

- A. The balancing agency shall perform the following testing and balancing functions in accordance with the Associated Air Balance Council's National Standards:
 - 1. Fan Speed - Test and adjust fan RPM to achieve design CFM requirements.
 - 2. Current and Voltage - Measure and record motor current and voltage. Check and record thermal overload ratings for all motors.
 - 3. Pitot-Tube Traverse - Perform a Pitot-tube traverse of main supply, return and exhaust ducts to obtain total CFM. If a Pitot-tube traverse is not practical, the summation of the outlets or inlets may be used. An explanation why a traverse was not made must appear on the appropriate data sheet.
 - 4. Outside Air - Test and adjust system minimum outside air by Pitot-tube traverse. If a Pitot-tube traverse is not practical, the percentage of outside air may be determined by calculations from the return air, outside air, and mixed air temperatures. Make allowances for heat of compression and motor heat where applicable.
 - 5. Static Pressure - Test and record system static pressures, including suction and discharge static pressure of each fan. Record hood static pressure at kitchen hood exhaust taps, and similar equipment. Measure static air pressure conditions on air supply units, including filter and coil pressure drops, and total pressure across the fan. Make fan RPM allowances for 50 percent loading of filters.

6. Air Temperature - Take wet-bulb and dry-bulb air temperatures on the entering and leaving side of each cooling coil and/or heat recovery coil. Dry-bulb temperature shall be taken on the entering and leaving side of each heating coil.
7. Zone Ducts - Adjust zone ducts to within design CFM requirements. At least one zone balancing damper shall be completely open.
8. Main Ducts - Adjust main ducts to within design CFM requirements and balance for total CFM quantities.
9. Branch Ducts - Adjust branch ducts to within design CFM requirements. Multi-diffuser branch ducts shall have at least one outlet or inlet volume damper completely open.
10. Magnahelic Gauges - Static pressure at static pressure taps for Magnahelic gauges shall be recorded in Test and Balance Reports.
11. Tolerances - Test and balance each diffuser, grille, and register to within 10 percent of design requirements. Test and balance all fans to within 5 percent of design requirements.
12. Identification - Identify the location and area of each grille, diffuser, register, and terminal box. This information shall be recorded on air outlet data sheets.
13. Description - Record the size, type, and manufacturer of each diffuser, grille, and register on air outlet data sheets.
14. Minimizing Drafts - Adjust all diffusers, grilles, and registers to minimize drafts in all areas.
15. Test and Balance Engineer shall witness and record all leakage testing of ductwork. Leakage test data shall be included in final Test and Balance Reports.
16. Where modulating dampers are provided, take measurements and balance at extreme conditions.
17. Measure temperature conditions across outside air, return air, and exhaust dampers to check leakage.
18. For all equipment specified with condensate overflow safety switches/floats test operation of such device and record results. Verify interlock with ATC system.
19. Outside air and exhaust/relief air measurements must be measured and submitted in all modes of operation including the following:
 - a). Min Min Outside Air/Exhaust/Relief air mode (square footage outside air).
 - b). Min Max Outside Air/Exhaust/Relief air mode (square footage and people outside air).
 - c). Maximum outside air/exhaust/relief mode (full 100% economizer mode).

20. For all outside air modes of operation record and submit full static pressure profiles, amperage, BHP, air flow rates, external static pressure, and internal static pressure. Verify airflow rates with air flow monitoring stations and record results.

3.4. WATER SYSTEM PROCEDURES

- A. The various water circulating systems shall be filled, purged of air, and put into operation before hydronic balancing by the mechanical contractor.
- B. The flow of water through all coils shall be adjusted by manipulating balancing valves until the rated pressure drop through the coil or metering device is obtained. Perform balancing by measurement of temperature differential in conjunction with air balancing.
- C. The balancing agency shall perform the following testing and balancing functions in accordance with the AABC National Standards.
- D. All Hydronic equipment, domestic re-circulating pumps, and HVAC pumps shall be Tested and Balanced as described below:
 1. Water Treatment - Examine the water in the system and determine if the water has been treated and cleaned. If not, request the mechanical contractor to clean and treat the water prior to TAB work
 2. Strainers - Request that the mechanical contractor clean all strainers.
 3. Air Vents - Check all air vents at the high points of the water system and determine if they are installed and operating.
 4. Valves - Set all balancing valves to the full-open position for balancing.
 5. Pumps - Adjust all pumps and domestic hot water re-circulating water pumps to meet design GPM requirements. Check pumps for proper operation. Pumps shall be free of vibration and cavitation. Measure and record operating current and voltage. Check and record thermal overloads installed on all pumps. Record in Test and Balance Report.
 6. Tolerances - Proceed to balance all coils, pumps, balance valves chillers, boilers to within 5 percent of design requirements.
 7. Marking - Mark all settings and record all data after completing the flow readings and coil adjustments.
 8. Where available pump capacity (due to diversity) is less than total flow requirements or individual system parts, full flow in one part may be simulated by temporary restriction of flow to other parts.
 9. Test all A/C condensate pumps for proper operation.
 10. Test condensate overflow safety switches.

E. Chillers:

1. Verify that chillers have been started by others and are in operation. Test and adjust chiller water flows to achieve maximum or design GPM.
2. Current and Voltage - Test and record motor voltage and amperage, and compare data with the nameplate limits to ensure compressor motor is not in or above the service factor.
3. Test and record temperature profiles of chillers.
4. Description of liquid sufficient to obtain physical properties.
5. Power input to controls and auxiliary components in KW.
6. Dry bulb temperature of air entering condenser (degrees F).
7. Condenser fans motor power consumption in KW.
8. Condenser fans rotating speed in rpm.
9. Test operation of flow switches.

F. Boilers:

1. Verify that boilers have been filled and started by others, and are in operation.
2. Current and Voltage - As applicable, test and record motor voltage and amperage, and compare data with the nameplate limits to ensure motor is not in or above the service factor.
3. Test and adjust water flow through water boilers.
4. Test and record temperature and pressure profiles of water or steam boilers.

G. Coils:

1. Tolerances - Test, adjust, and balance all hydronic coils within 5 percent of design requirements.
2. Verification - Verify the type, location, final pressure drop and GPM of each coil. This information shall be recorded on coil data sheets.

H. TESTING AND BALANCING OF EXISTING SYSTEMS

- A. The balancing agency shall perform testing and balancing of existing air handling, fan and pump systems to the extent indicated. Existing air devices and terminals shall be re-tested and balanced where effected by new ductwork modifications.
- B. Test and Balance Agency shall assist the mechanical contractor in selection of new

sheaves and belts, if required. Re-sheaving of existing air handling units or fans shall be done at no additional cost to owner. Where required, new sheave and belt size calculations shall be forwarded to the Engineer for review and approval.

- C. The Test and Balance Agency shall perform water system procedures (here-in before specified) on the following hydronic systems.

1. Boiler #1
2. Boiler #2
3. HWP-1
4. HWP-2
5. Provide temperature measurements across all existing coils and heat exchangers.

3.6. KITCHEN HOOD TESTING AND BALANCING PROCEDURES

- A. The kitchen hood exhaust and make-up air quantities shall be tested and balanced to the indicated design quantities (CFM). The air flow of each shall be determined by the use of pitot tube traverse and/or a short ridge velgrid.
- B. The kitchen hood should then be tested for adequate capture using a 30 second smoke bomb. The cooking equipment below the hood should be turned on and brought up to normal operating temperature. All grease filters should be in place. The kitchen make-up air unit and exhaust fans shall be on. The hood static pressure should be recorded and documented in the Test and Balance Report and the hood shall be tested and must provide 100 percent capture. If the hood does not prove 100 percent capture, the source of the problem shall be determined and the test repeated. Record results of tests within TAB report.

3.7. FIRE AND SMOKE TESTING PROCEDURES

- A. The TAB agency shall test fire/smoke damper to assure operation. It shall verify that an access door has been installed for each fire and smoke damper. For fire dampers, the TAB agency shall open the access door, disconnect the fusible link, and allow the damper to close. Operation should be smooth and the damper must close completely. The TAB agency shall then reset the damper. For the smoke damper, the TAB agency shall open the access door, activate the damper, and observe operation. The damper must close quickly and completely. The TAB agency shall then reset the damper and observe its complete opening. Record results of tests within TAB report.

3.8. LIFE SAFETY CONTROLS TESTING PROCEDURES

- A. The TAB agency shall test and record life safety control operation on the HVAC equipment. It shall verify the installation of required smoke detectors in air handling equipment (AHE), and shall verify operation of the smoke detector by activating the smoke detector and observing air handler shutdown. With the controls and alarm contractors, the TAB agency shall verify the operation of interconnected systems such as the AHU smoke detector's activation of the fire alarm system and the alarm system's activation of the life safety control sequences. Record results of tests within TAB report.

3.9. VERIFICATION OF TEMPERATURE CONTROL

- A. The balancing agency shall be assisted by the temperature control contractor in verifying the operation and calibration of all temperature control systems. The following tests shall be conducted:
1. Verify that all control components are installed in accordance with project requirements and are functional, including all electrical interlocks, damper sequences, air and water reset.
 2. Verify that all controlling instruments are calibrated and set for design operating conditions.
 3. Verify the accuracy of the final settings by taking temperature readings. The readings shall be in a typical conditioned space for each separately controlled zone.
 4. Test and calibrate all air flow monitoring stations for proper air flow.
 5. Test and calibrate all static pressure sensors for proper set point and control.
 6. Test and calibrate all differential pressure sensors. Record set point in Record and Information Books.

3.10. TEST AND BALANCE REPORTS

- A. The test and balance report shall be complete with logs, data, and records as required herein. All logs, data, and records shall be typed on white bond paper and bound. The report shall be certified accurate and complete by the balancing agency's certified test and balance engineer.
- B. Six (6) copies of the test and balance report are required and shall be submitted to the Engineer. If, in the opinion of the Engineer, test results or portions thereof are incomplete or inconclusive, repeat necessary portions of the work to the satisfaction of the Engineer.
- C. The report shall contain the following general data in a format selected by the balancing agency:
1. Project Number
 2. Contract Number
 3. Project Title
 4. Project Location
 5. Project Architect
 6. Project Mechanical Engineer
 7. Test & Balance Agency

8. Test & Balance Engineer
 9. General Contractor/Construction Manager
 10. Mechanical Subcontractor
 11. Dates tests were performed
 12. Certification
 13. Duct Leakage Tests
 14. Phone Numbers of all Individuals Listed Above
- D. The test and balance report shall be recorded on report forms conforming to the recommended forms in the AABC National Standards.

3.11. TEST REPORT FORMS

- A. Air Moving Equipment and Fan Test Forms - Submit fan curve showing design and operating points of operation. Also, record the following on each air-handling equipment test form:
1. Manufacturer, model number, serial number, arrangement.
 2. All design and manufacturer-rated data.
 3. Total actual CFM by traverse if practical. If not practical, the sum of the outlets may be used, or a combination of each of these procedures. For specific systems, such as ones with diversity, see the AABC National Standards.
 4. Suction and discharge static pressure of each fan, as applicable. Include pressure drops across coils, filters, mixing boxes, and similar devices.
 5. Outside-air, return-air, and exhaust air total CFM.
 6. Actual operating current, voltage and brake horsepower of each fan motor. For packaged equipment, this includes supply fans, relief air fans, and condenser fans.
 7. Final RPM of each fan.
 8. Fan and motor sheave manufacturer, model, size, number of grooves, bore, and center distance.
 9. Belt size, quantity and make.
 10. Static-pressure controls final operating set points (if applicable).
 11. Total and external static pressure.

- B. Pump Test Forms - Submit pump curve showing design, operating, and no-flow points of operation. Also, record the following items on each pump test form:
1. Manufacturer, size, model, service and serial number.
 2. All design and manufacturer's rated data.
 3. Pump operating suction and discharge pressure and final total dynamic head.
 4. No flow (pump discharge valve closed) suction and discharge pressure and corresponding total dynamic head. This procedure is to determine actual impeller size. Record impeller size.
 5. Rated and actual operating current, voltage, and brake horsepower of each pump motor.
 6. Total operating head pressure.
 7. Shutoff, discharge and suction pressures.
 8. Shutoff, total head pressure.
- C. Chiller and Boiler Test Forms - Record the following items on each chiller and boiler test form:
1. Manufacturer model number, serial numbers.
 2. All design and manufacturer's rated data.
 3. Service and location.
 4. Actual pressure drop and related GPM primary side.
 5. Actual pressure drop and related GPM, secondary side.
 6. Primary side entering and leaving temperatures.
 7. Secondary side entering and leaving temperatures.
 8. Temperature control settings.
 9. Electrical characteristics.
 10. For air cooled chillers condenser fan speed and kw.
- D. Heating and Cooling-Coil Test Forms - Record the following items on each test form:
1. Manufacturer, location, service.
 2. All design and manufacturer's rated data.

3. Rated and actual water pressure drop through each coil and related GPM.
4. Rated and actual static pressure drop across each coil.
5. Rated and actual entering and leaving water temperatures across each coil.
6. Wet-bulb and dry-bulb temperatures entering and leaving each cooling coil; dry-bulb temperatures entering and leaving each heating coil.
7. Air flow (Design and Actual).
8. For DX-coil, provide design and actual saturated suction temperature.
9. For DX-Coil, provide design and actual discharge pressures.

E. Air Monitoring Station Test Forms:

1. Identification /location.
2. Manufacturer.
3. Systems.
4. Size and Model Number.
5. Area.
6. Design Velocity.
7. Design Airflow.
8. Test Velocity.
9. Test Airflow.
10. Static Pressure Drop and Velocity Pressure.
11. Station Calibrated Setting.

F. Flow Measuring Station Test Forms:

1. Identification/location.
2. Manufacturer.
3. Size and Model Number.
4. Design and Actual Flow Rate.
5. Design and Actual Pressure Drop.

6. ATC flow rate versus field measured flow rate.
- G. Electric Motors Test Forms: (Applies to all motors, including pumps, fans and HVAC equipment)
1. Manufacturer.
 2. Model/Frame.
 3. HP/BHP.
 4. Phase, voltage, amperage; nameplate, actual, no load.
 5. RPM.
 6. Service factor.
 7. Starter size, rating, heater elements.
 8. Sheave Make/Size/Bore.
 9. Thermal overload settings
- H. V-Belt Drive Test Forms:
1. Identification/location.
 2. Required driven RPM.
 3. Driven sheave, diameter and RPM.
 4. Belt, size and quantity.
 5. Motor sheave diameter and RPM.
 6. Center to center distance, maximum, minimum, and actual.
- I. Duct Traverse Test Forms:
1. System zone/branch.
 2. Duct size.
 3. Area.
 4. Design velocity.
 5. Design air flow.
 6. Test velocity.

7. Test airflow.
8. Duct static pressure.
9. Air temperature.
10. Air correction factor.

J. Duct Leakage Test Forms:

1. Description of ductwork under test.
2. Duct design operating pressure.
3. Duct design test static pressure.
4. Duct capacity, air flow.
5. Maximum allowable leakage duct capacity times leak factor.
6. Test apparatus.
 - a). Blower.
 - b). Orifice, tube size
 - c). Orifice size
 - d). Calibrated.
7. Test static pressure.
8. Test orifice differential pressure.
9. Leakage.

K. Air Distribution Test Sheet:

1. Air terminal number.
2. Room number/location.
3. Terminal type.
4. Terminal size.
5. Area factor.
6. Design velocity.
7. Design air flow.

NOT FOR BIDDING PURPOSES

8. Test (final) velocity.
9. Test (final) air flow.
10. Percent of design air flow.

L. Ductless Unit Test Forms:

1. Manufacturer
2. Type, air conditioning, heat pump
3. Identification number
4. Location
5. All design and manufacturer's rated data.
6. Rated and actual entering and leaving dry bulb temperatures.
7. Rated and actual entering and leaving wet bulb temperatures.
8. Air flow (design and actual)
9. Provide actual saturated suction temperature.
10. Actual operating current, voltage and brake horsepower of each fan motor.
11. Final fan RPM.
12. For Air Cooled Variable Refrigerant Volume System test current, voltage, RPM, and breaker horsepower for outdoor unit.

M. Fan Coil Unit Data Test Forms:

1. Manufacturer.
2. Type.
3. Identification/number.
4. Location.
5. Model number.
6. Size.
7. Water Pressure drops (all coils).
8. Static pressure

NOT FOR BIDDING PURPOSES

9. Test amperage
10. Entering coil conditions (wet bulb and dry bulb).
11. Leaving coil conditions (wet bulb and dry bulb).
12. Water flow rates (all coils)
13. Test voltage.
14. Supply return and outside air flow rates.

N. Kitchen Make-up Air Unit

1. Manufacturer model number, serial numbers.
2. All design and manufacturer's rated data.
3. Electrical characteristics, design, and actual.
4. Fan speed, static pressure voltage, amp draw.
5. Wet Bulb and dry Bulb temperatures entering, leaving coil design, actual.
6. Air flow rate/RPM at maximum flow and minimum flow.
7. Interlocked exhaust fan air flow rate/RPM at maximum flow and minimum flow.
8. Temperatures entering and leaving the heat pipe, design, and actual.
9. Where applicable entering/leaving temperatures at hot gas re-heat coils, design, and actual.
10. For gas fired units, entering and leaving air temperatures.
11. Record the supply fan and exhaust fan maximum hertz/speed and minimum hertz/speed. Provide measurements to ATC subcontractor for fan tracking control.

C. Condensate Over Flow Switches/Floats

1. Manufacturer
2. Type
3. Location
4. Equipment shut down verification
5. ATC interlock verification

P. Gas Make-up Air Units Test Forms:

1. Manufacturer.
2. Identification number.
3. Location.
4. Model number.
5. Phase, voltage, amperage.
6. Test voltage.
7. Test amperage.
8. Air flow, specified and actual.
9. Temperature rise, specified and actual.
10. Entering and leaving temperature (dry bulb and wet bulb) of enthalpy wheel.
11. Pressure drop, specified and actual.
12. Delivered Gas Pressure, specified and actual.

Q. Electric Radiant Heat Panels Test Forms:

1. Manufacturer.
2. Identification number.
3. Location.
4. Model number.
5. Design kW and actual kW.
6. Phase, voltage, amperage.
7. Test voltage (each phase).
8. Test amperage (each phase).
9. Air flow, specified and actual.
10. Temperature rise, specified and actual.

END OF SECTION

SECTION 23 06 00

HEATING, VENTILATING, AND AIR CONDITIONING EQUIPMENT

PART 1 GENERAL

1.1 GENERAL

- A. The Conditions of the Contract and other General Requirements apply to the work specified in this section. All work under this section shall also be subject to the requirements of Division 23 Section, *Common Work Results for HVAC* and Division 01 Section *General Requirements*.

1.2 DESCRIPTION

- A. The work to be performed shall include all labor, materials and equipment necessary to furnish and install complete, all mechanical equipment as shown on drawings, hereinafter specified or reasonably implied, and leaving the same in satisfactory operation condition. It is the intent that systems be installed complete with all items necessary to accomplish this purpose.

1.3 SUBMITTALS

- A. Shop Drawings: Indicate assembly, equipment dimensions, weight loading, required clearances, construction details, field connection details, and electrical characteristics and connection requirements.
- B. Product Data:
1. Provide literature which indicates dimensions, weights, capacities, ratings, performance, gages and finishes of materials, and electrical characteristics and connection requirements.
 2. Provide data of filter media, filter performance data, filter assembly, and filter frames.
 3. Provide fan and pump curves with specified operating point clearly plotted.
 4. Submit sound power level data for both fan outlet and casing radiation at rated capacity. Submit sound power levels by octave band or sound pressure levels by octave band for all equipment.
 5. Submit electrical requirements for power supply wiring including wiring diagrams for interlock and control wiring, clearly indicating factory-installed and field-installed wiring.

1.4 OPERATION AND MAINTENANCE DATA

- A. Maintenance Data: Include instructions for lubrication, filter replacement, motor and drive replacement, spare parts lists, and wiring diagrams.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Deliver, store, protect and handle products to site under provisions of General Requirements.
- B. Accept products on site in factory-fabricated protective containers, with factory-installed shipping skids and lifting lugs. Inspect for damage.
- C. Store all equipment in clean dry place and protect from weather and construction traffic. Handle carefully to avoid damage to components, enclosures, and finish.
- D. Comply with manufacturer's installation instructions for rigging, unloading and transporting equipment.
- E. Protect all motors, shafts, and bearings from weather and construction dust.

1.6 ENVIRONMENTAL REQUIREMENTS

- A. Do not operate any equipment for any purpose, temporary or permanent, until ductwork/piping is clean, filters/strainers are in place, bearings lubricated, and equipment has been test run under observation.

1.7 ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

1.8 EXTRA MATERIALS

- A. Provide one set of seals for each type and model of pump provided on the project.

PART 2 PRODUCTS

2.1 100% OUTSIDE AIR DOUBLE WALL INDOOR CENTRAL STATION AIR HANDLING UNITS

- A. Provide and install central station air handling units as shown and scheduled on the plans. The units shall be installed in a neat and workmanship like manner in strict accordance with specifications. Air handling units shall be York AirPack, Trane IAQ Modular Climate Changers, McQuay Vision, Carrier, Daikin, or approved equal. Provide components as detailed on the contract drawings.

B. General

1. Central station air handling units shall be certified in accordance with the Air Conditioning and Refrigeration Institute (ARI) Standards 430 for Central Station Air Handling units and 410 for coils.
2. Units shall be provided with nominal 1-inch deflection spring isolators, as required, or as recommended by the unit manufacturer.
3. The units shall be furnished complete with double wall insulated casings, centrifugal fans, coils as scheduled, insulated drain pan, motor, drive, belt guard,

and accessories as required. Coils shall not exceed specified face velocities.

4. Adequate space around all sides of the air handling unit shall be provided for proper service and maintenance.
5. All units shall be horizontal draw through medium pressure units. Construct casing section located upstream of supply fan for operation at a minimum of 4 inches w.g. negative static pressure and downstream sections for operation at a minimum of 6 inches water gauge positive static pressure.
6. All units shall be factory primed and finished in colors as selected by Engineer.
7. Provide unit mounting legs to support all sections of unit and raise unit for proper trapping. Unit mounting devices not constructed of galvanized steel shall be chemically cleaned, coated with rust inhibiting primer, and finished with rust inhibiting enamel. Contractor shall be responsible for all steel supports and hangers for hung units.
8. Fan discharge arrangements shall be coordinated with ductwork layout to minimize "system effect" per AMCA-Publication 201-90.
9. Provide 6-inch high unit mounting legs or base rail to support all sections of unit and raise unit for proper trapping. Unit mounting devices shall be galvanized steel and a minimum of 10 gauge. Unit mounting devices not constructed of galvanized steel shall be chemically cleaned, coated with rust inhibiting primer, and finished with rust inhibiting enamel. Contractor shall be responsible for all steel supports and hangers for hung units.
10. All glycol cooling coil capacities shall be based on 30 percent propylene glycol.

C. Construction

1. Unit casing shall be constructed of minimum 18 gauge galvanized metal, formed and reinforced to provide a rigid assembly. Formed panels shall be removable to provide easy access to internal components. Each of the sectionalized modules and accessories shall be factory assembled. Removal of side panels shall not affect the structural integrity of the unit.
2. All exterior panels and structural frames shall be constructed of G90-U galvanized steel. Casings not constructed of G90-U galvanized steel, casings with welds on exterior surfaces, or casings with welds on interior surfaces that have burned through to exterior surfaces shall be chemically cleaned, coated with rust inhibiting primer, and finished with rust inhibiting enamel in order to prevent premature corrosion and microbial growth.
3. Seal and gasket all joints between exterior panels and structural frames with closed-cell foam gasketing for air seal and acoustical break.
4. Casing shall have full size removal access doors as shown on drawings. Access doors shall have 2-inch double wall construction. Provide automotive style

neoprene gasketing around full perimeter of access doors to prevent air leakage. Provide "ventlock" style non-corrosive alloy latches operable from the inside or outside of unit. If access doors open against unit operating pressure, provide safety latches that allow access doors to partially open after first handle movement and fully open after second handle movement.

5. Insulate casing sections with 2-inch thick 1 ½ pound per cubic foot density fibreglass insulation or equivalent. Provide double wall casing construction and encase insulation between solid exterior and double wall interior casing panels such that no insulation is exposed to airstream. Foil facing on insulation is not acceptable as alternate to double wall construction. Insulation shall comply with NFPA 90A.
6. Cooling coil sections shall have positive draining, double sloped drain pans. Each pan shall be of heavy gauge galvanized steel. Drain connections shall be provided on both sides of the pan. The drain pan shall be of double wall construction with closed-cell insulation provided between the interior and exterior pans. Insulation shall be 1-inch - 3# insulation sandwiched between the pans.
7. Cooling coil sections having stacked coils or finned heights greater than 46-inches shall have an additional intermediate drain pan(s), each with drop tubes to guide condensate to the main drain pan without flooding of the lower coil(s). Coil sections shall provide easy removal of coils from either the top or side for service and maintenance.
8. Coils sections with two or more coils shall have a 4-inch spacer between each adjacent coil.
9. Fan sections with internally mounted motors shall be provided with a standard full size access door allowing easy access to the fan/motor assembly. Units with externally mounted motors shall be provided with an expanded metal belt guard with hole for tachometer.

D. Fans

1. Units shall be provided with double width double inlet, centrifugal-type wheels. Fans shall be Standard or Class II (as required by total static pressure) forward curved wheels or air foil type as scheduled. Every fan shall be rated in accordance with AMCA Standards and the fan section shall be certified in accordance with ARI Standard 430. Fan shafts shall be selected to operate well below the first critical speed and each shaft shall be factory coated after assembly with an anti-corrosion coating. After the pre-balanced fan is installed in the air handler the entire fan section shall be run to assure smooth and trouble-free operation.
2. Fan bearings shall be self-aligning, pillow block or flanged-type re-greasable ball bearings and shall be supplied for an average life (L50) or 200,000 hours. All bearings shall be factory-lubricated and equipped with standard hydraulic grease fittings and extended lube lines. Provide dust caps on all hydraulic grease fittings.

3. Mount fans on isolation bases. Internally mount motors on same isolation bases and internally isolate fans and motors with spring isolators. Install flexible canvas ducts between fan and casings to ensure complete isolation. Flexible canvas ducts shall comply with NFPA 90A.
4. Fan section shall have full height, double wall, hinged, removable access door for inspection and maintenance of internal components.
5. Weigh fan and motor assembly at AHU manufacturer's factory for isolator selection. Statically and dynamically balance fan section assemblies. Fan section assemblies include fan wheels, shafts, bearings, drives, belts, isolation bases and isolators. Allow isolators to free float when performing fan balance. Measure vibration at each fan shaft bearing in horizontal, vertical and axial directions. Balance at design RPM's as scheduled on drawings.
6. Fans with variable frequency drives shall be balanced for inverter duty operation.

E. Motors and Drives

1. Fan motors shall be externally mounted or as indicated on contract drawings. Air handling units with internal motors shall be provided with additional cooling capacity to compensate for motor heat added to airstream. Total cooling capacity, as schedule, shall be increased by 2500 BTUH per motor horsepower for units with internally mounted motors.
2. Units shall be provided with the motor efficiencies as specified in Division 23 Section, *Common Work Results for HVAC*.
3. Motors shall be per NEMA Design B, rigid base, open drip proof, with Class B insulation.
4. Fan drives shall be selected for a 1.5 service factor and anti-static belts shall be furnished. One additional set of belts shall be provided for each air handling unit and delivered to the Owner's representative at the completion of the project.
5. Fan sections shall be equipped with double width double inlet, centrifugal type wheels.
6. Drives shall be variable pitch and suitable for adjustment within plus or minus 15 percent of specified RPM but not to exceed the maximum RPM of the unit.

F. Coils

1. Cooling, and heating coils shall be furnished to meet the performance requirements set forth in the schedule. All coils shall have performance certified in accordance with ARI Standard 410. Coils shall be arranged in the unit for horizontal air flow and selected for a maximum face velocity as scheduled. Install coils such that headers and return bends are enclosed by unit casings. Low temperature coils (40 degrees F EPT) shall be properly circulated to prevent

laminar flow at part load conditions.

2. Coil casing shall be constructed of heavy gauge galvanized metal with aluminum die-formed corrugated fins and guide channels to create turbulent wiping behind the tubes. The fins shall have drawn collars, be belled and mechanically expanded to firmly bind the copper tubes to the fins. All coils shall be installed on tracks for easy removal from the air handling unit.
3. Drainable water coils shall be designed to operate at 250 psig design working pressure and up to 300 degrees F and shall be tested with 325 psig compressed air under water. Circuiting shall provide free draining and venting when installed, counter flow of air and water with water velocities not to exceed seven feet per second and without exceeding the water pressure drops scheduled. All coils must have same end connections regardless of the number of rows deep. Clearly label supply and return headers on outside of units such that direction of coil water flow is counter to direction of unit airflow.
4. Construct coils of configuration plate fins and seamless tubes. Fins shall have collars drawn, belled and firmly bonded to tubes by means of mechanical expansion of tubes. Do not use soldering or tinning in bonding process.
5. Construction coil casings of Galvanized G90-U Steel with formed end supports and top and bottom channels. If two or more coils are stacked in unit, install intermediate drain channels between coils to drain condensate to main drain pans without flooding lower coils or passing condensate through airstream.
6. Coil grommets shall be provided on all coils to completely seal the area between the coil connection and the unit casing.
7. Wrap-Around Heat Pipe: De-humidifier heat pipe shall pre-cool the outdoor air and reheat the air leaving the cooling coil in a wrap around configuration. Both heat exchangers shall be inside and integral to the equipment cabinet. Tubes shall be 1/2-inch OD seamless copper tube, 12 fins per inch and 0.006-inch thick fins. Fins shall be permanently expanded aluminum. Wrap around heat pipe shall be UL listed. Heat transfer fluid shall be classified as Safety Group A1 in ASHRAE Std. 15-1989R.

G. Filters

1. Filters shall be nominal 2-inch standard size filters; pleated media type. Filters shall be Farr, medium efficiency pleated type 30/30 with welded wire media support grid.
2. Provide one additional set of filter media for each air handling unit to be delivered to the Owner's representative upon completion of the project.

H. Access Sections and Access Doors

1. Fully insulated, access sections shall be provided as indicated on the drawings. Sections provide a minimum of 18-inch accessible space with full-size access doors. Access for inspection and cleaning of the unit drain pan, coils, and fans

sections shall be provided.

2. Access doors shall be provided in all sections. Access doors shall be of double wall construction.
3. Panels shall be fully removable to allow for a proper way to thoroughly clean panels of microbial growth and to access internal parts.

I. Filter Box Section

1. Provide factory fabricated filter box section of the same construction and finish as unit casing. Filter sections shall have filter guides, and full height double wall, hinged, removable access door for filter removal. Provide filter block-offs as required to prevent air bypass around filters. Angle filters shall be accessible from either side with hinged access doors.
2. Motor operated outside air dampers shall be supplied by ATC contractor and installed by mechanical contractor in adjacent ductwork. Damper blades shall be parallel acting and shall rotate in nylon bearings providing smooth action and requiring no lubrication. Dampers shall be sectionalized to limit blade length, prevent warping and assure a tight closure. Actuators shall be provided and installed by the ATC contractor.
3. Provide field installed differential pressure gauge, two static pressure tips, vent valves, and red pointer flag, and air filter gauge accessory package to measure filter resistance. Accuracy shall be ± 2 percent of full scale 0 to 1.0 inch w.g. range. Gauges shall be 3005 magnahelic by Dwyer Instruments or approved equal.

J. Installation

1. Install air handling units and make-up air units where shown, in accordance with equipment manufacturer's written instructions, and with recognized industry practices, to ensure that units comply with requirements and serve intended purposes.

K. The manufacturer shall in his selection, calculate and account for all heat produced within the air handling system casing. Heat sources which shall be accounted for are:

1. Heat produced by the inefficiency of the fan in converting energy input to static and velocity pressure.
2. Heat produced by the fan motor if located in the airstream.
3. Heat produced by the belts and sheaves, if located in the airstream.
4. Any other gains.
5. The manufacturer shall then modify the coil entering or leaving air temperatures such that when the heat gains act on the system, the specified performance is

achieved.

L. Air Handling System Efficiency

1. Because it is important to the Owner to minimize the operating cost of equipment where applicable, the unit manufacturer's selected air handling unit shall not exceed the maximum cumulative break horsepower indicated on the plans.

M. Fan-Section Source Quality Control: the following factory tests are required.

1. Sound Power Level Ratings: Comply with AMCA 301, *Methods for Calculating Fan Sound Ratings from Laboratory Test Data*. Test fans according to AMCA 300, *Reverberant Room Method for Sound Testing of Fans*. Fans shall bear AMCA-certified sound ratings seal.
2. Factory test fan performance for flow rate, pressure, power, air density, rotation speed, and efficiency. Establish ratings according to AMCA 210, *Laboratory methods of Testing Fans for Rating*.

2.2 AIR COOLED SCREW CHILLER

- A. Provide packaged air cooled "screw" chillers of the size, capacity, and electrical characteristics as shown on the contract drawings. Provide demand limiting feature and interlock with automatic temperature control system.

Chiller shall be Trane Model RTAC Model YCAV as manufactured by York, Daikin, or approved equal.

B. General

1. Operating test shall include operation with water flowing through the cooler. The unit structure shall be heavy-gauge, galvanized steel. All external parts shall be covered with a baked-on powdered paint to withstand 500 hours of salt-spray testing using 5 percent salt-spray solution per ASTM B117 without exhibiting any film breakdown beyond 1/8-inch on each side of a scribed line. (This shall be equivalent to an ASTM D 1654 rating of "6".) The unit shall be shipped with full operating charge of R-134A and reorded refrigerant oil. All units shall contain multiple refrigerant circuits, each with two (2) compressors, for standby operation. All units shall be designed and constructed in accordance with the applicable sections of the following: *ANSI/ASHRAE 15 Safety Code for Mechanical Refrigeration*; *American Society of Mechanical Engineers (ASME) Pressure Vessel Code*; *National Electrical Code/National Fire Protection Association NFPA 70*; U.L. and C.U.L. listed. All units shall be produced at an ISO 9000 registered facility. All units shall be rated in accordance with ARI Standard 550 and shall be certified up to 300 tons in accordance with ARI Standard 590.
2. All schedule capacities are based on water.
3. Provide bird screen around compressors, tubes, etc, to prevent bird nesting and vandalism.

4. Provide bird screen around compressors, tubes, etc, to prevent bird nesting and vandalism. Bird screen shall be heavy gauge, welded wire mesh, coated to resist corrosion and factory installed.
5. Furnish chiller with low sound fans, discharge mufflers, and complete compressor enclosure attenuator housings.
6. Install and commission, as shown on the schedules and plans, one factory assembled, charged, and tested air-cooled screw compressor chiller as specified herein. Chiller shall be designed, selected, and constructed using a refrigerant with Flammability rating of "1", as defined by ANSI/ASHRAE STANDARD-34 Number Designation and Safety Classification of Refrigerants. Chiller shall include, but is not limited to: a complete system with screw compressors, direct expansion type evaporator, air-cooled condenser, refrigerant lubrication system, interconnecting wiring, safety and operating controls including capacity controller, control center, motor starting components, and special features as specified herein or required for safe, automatic operation.
7. Cabinet: External structural members shall be constructed of heavy gauge, galvanized steel coated with baked on powder paint which, when subject to ASTM B117, 1000 hour, 5 percent salt spray test, yields, minimum ASTM 1654 rating of "6".
8. Chiller shall be delivered to the job site completely assembled and charged with refrigerant and oil by the manufacturer.

C. Compressor and Refrigerant Circuits

1. There shall be a maximum of two compressors per refrigerant circuit. The compressor shall be of the accessible-hermetic rotary twin-screw type. The compressor shall be driven by electrical motor via a gear speed-increaser. The compressor housing shall be made of cast iron, precisely machined to provide minimal clearance of the rotors. The design working pressure shall be 250 PSIG (17.2 kPa) on the suction side and 450 PSIG (3.1mPa) on the discharge side (hydrostatic tests shall be done at 5 times design working pressure, i.e. 1250 PSIG (5.0 mPa) and 2250 PSIG (15.5 mPa) respectively). The compressor shall be mounted on isolators. The rotors shall be manufactured from hot-rolled steel and use asymmetric profiles. Accurate rotor positioning shall be maintained at all pressure ratios by four separate, cylindrical, roller bearings for radial loads and angular-contact ball bearings for axial loads. The compressor shall contain an internal discharge check-valve to prevent reverse-rotation at shut-down. The compressor shall also contain a 500 watt 115 volt/1 phase/60 Hz) temperature-actuated, immersion heater to prevent refrigerant condensation during shutdown.
2. Capacity Control

Compressor slide valves shall provide fully modulating capacity control from 100 percent of full load down to 15 percent of chiller full load. The slide valve shall be actuated by oil pressure, controlled by external solenoid valves via the

Control Center or approved equal. Additional capacity controls shall be provided as necessary to accomplish sequence of operation.

3. The unit shall contain two (2) separate refrigerant circuits. Each shall be constructed of ACR copper tubing with brazed joints and shall include shut-off valve with charging connection, liquid sight glass with moisture indicator, direct acting maximum operating pressure thermal expansion valve, solenoid valve, and filter drier. The entire suction line and liquid line between the expansion valve and the cooler shall be insulated with 1-inch flexible closed cell insulation.

4. Accessible Hermetic Motor

The compressor motor shall be refrigerant-gas-cooled, 60 Hz motors shall operate at 3,600 RPM. The motor starter shall have UL Class "H" insulation. The terminal boxes shall be rain-tight. The hermetic motor shall be high torque, (Wye-Delta) start. The motor shall be equipped with a minimum of three, internal, heat-sensing thermistors.

5. Oil Separation, Lubrication, and Cooling

An external oil separator with no moving parts shall be provided to minimize oil carry-over for each circuit. Oil separation shall be achieved by the impingement and direction change of the refrigerant gas as its velocity decreases. The oil separators shall be utilized to provide gas/oil separation before the gas enters the air-cooled condenser. The oil separators shall be designed for a maximum working pressure of 450 PSIG (3.1mPa) and are UL/CSA-listed. The oil separator shall include a sight glass. The compressor shall also have integral oil reservoirs located at the motor bearings to provide lubrication during start-up, coast-down and in the event of power failure. During operation, system-pressure differential shall provide proper oil flow without the need of an oil pump.

6. An external, replaceable-cartridge, 3-micron oil filter shall be provided, with manual isolation stop-valves for ease of servicing.

7. Oil cooling shall be provided by liquid injection to maintain proper oil temperatures for all conditions. A temperature-blending solenoid, controlled via the Millennium Control Center, or equal shall provide consistent oil temperature at all times to assure proper oil viscosity, independent of system conditions.

D. Economizer

1. An economizer shall be included in each circuit to enhance the overall system performance. The refrigerant-to-refrigerant, plate-type economizer shall be constructed of acid-resistant stainless steel. The heat exchanger shall be UL/CSA-listed and designed for 450 PSIG (3.1 mPa). The temperature limits shall be -320 degrees F (-195.6 degrees C) minimum to 365 degrees F (185 degrees C) maximum.

E. Cooler

1. The dual-circuit cooler shall be a direct-expansion type, with refrigerant in the

tubes and chilled liquid in the baffled shell. The design working pressure of the cooler shell (liquid side) shall be 150 PSIG (1.0 mPa), and 200 PSIG (1.6 mPa) for the tube (refrigerant side). Refrigerant shall be removable. The cooler shall be equipped with a heater cable covered with 1-½-inch, flexible, closed-cell-foam insulation (K'0.25 maximum) and thermostatically controlled immersion heaters and strip heaters for freeze-up protection to -20 degrees F (-28.9 degrees C) ambient. The cooler shall be constructed and tested in accordance with the applicable sections for the ASME Pressure Vessel Code requirements Section VIII, Division (1). The water connections shall be fully accessible and grooved to accept victaulic couplings, welded, or flanged.

2. Brazed plate stainless steel heat exchangers shall be UL Listed. Unit shall have a water strainer that is factory furnished and installed with blow down valve.

F. Condenser

1. Coils: The condenser coils shall be constructed of seamless copper tubes, arranged in staggered rows, mechanically expanded into aluminum fins and include an integral subcooling section. The design working pressure of the condenser coil shall be 450 PSIG (3.1 mPa). Provide louvered panels to protect condensers. Provide condenser corrosion protection including flexible dip and baked epoxy coating.
2. Fans: The condenser fans shall be glass-reinforced polypropylene, high-efficiency, airfoil-type, providing vertical air discharge. The fans shall be directly driven by independent motors and positioned in extended orifices for low sound. The fan guards shall be constructed of heavy-gauge, rust-resistant, PVC-coated steel. Fan blades shall be dynamically and statically balanced for vibration-free operation.
3. Motors: The fan motors shall be Totally Enclosed Air-Over (TEAO), squirrel-cage type, and current-protected. They shall feature ball bearings that are double-sealed and permanently lubricated. Each motor shall have U. L. Class F" insulation.
4. Fans shall be partitioned to avoid cross circulation.

G. Refrigerant Circuit

1. The unit shall contain two independent refrigerant circuits and shall be constructed of copper tubing with brazed joints. The liquid line shall include a shutoff valve with a charging port; sight glass with moisture-indicator; direct-acting maximum-operating-pressure thermal expansion valve; solenoid valve with internal relief; and filter-drier. The entire suction line, and the liquid line between the expansion valve and the cooler, shall be insulated with flexible, closed cell-insulations.

H. Control Center

1. Each unit shall contain a Control Center or approved equal. Control center shall

include BACnet protocol. All controls shall be contained within a rain tight/dust tight NEMA 3R (and equivalent to IP55 European standard) cabinet with hinged outer door having positive-acting latches. The center shall contain the "user friendly" and interactive inputs and outputs as follows: LCD display with light-emitting-diode back-lighting for outdoor viewing of data, and input buttons for DISPLAY (temperatures, pressures, etc.). ENTRY (enter/cancel inputs, advance day, change AM/PM), SET POINTS (change), CLOCK (set time and schedule), PRINT (calling up operating and shutdown data), PROGRAM (change inputs for special conditions such as brine chilling, and UNIT ON/OFF.

2. The Control Center or approved equal shall be capable of displaying the following in English or Metric: return and leaving liquid temperature; low leaving-liquid-temperature cutout setting; ambient temperature (actual outdoor temperature, low and high ambient cutout); suction pressure cutout setting; percent full-load motor current for each phase and the average of all three phases, suction, discharge and oil differential pressures; liquid flooddown rate-sensitivity adjustment (0.5 degrees F to 5 degrees F (6.3 to 2.8 degrees C) per minute in one-tenth increment); anti-recycle-timer status; slide-valve position (each compressor); superheat status; discharge pressure and current limiting; phase-rotation safety; compressor-run status; no cooling-load condition; day; date; time: out-of-range message; daily and holiday scheduling of start/stop times; automatic or manual lead/lag status; lead-compressor definition; number of compressor starts and running hours; evaporator heater, fan operation; liquid line solenoid valves; water pump; last fault-shutdown data; number of unloading steps; chiller pump control for freeze protection, compressor load-and-unload timer status.
3. The standard unit shall include run-signal contacts; automatic pumpdown on start-up and shutdown; alarm contacts; evaporator-pump control; automatic restart after power failure, remote start-stop, high suction and discharge pressure unloading, Three steps of demand load limiting, and remote chilled liquid re-set from an external building automatic system via 4 to 20 Ma or 0 to 10VDC with an interface board.
4. The operating program is stored in a non-volatile memory (EPROM) to eliminate chiller failure due to AC-power failure/battery discharge. Programmed setpoints are retained in lithium-battery-backed RTC memory for 5 years minimum.
5. Provisions shall be included for: a hard copy print-out from a printer (by others) via an RS-232 electrical output; remote water-temperature and current reset.
6. Pressure transducers shall be factory mounted to allow control to sense and display discharge pressure.
7. All controls, setpoints and BACNET attributes shall be fully integrated with ATC system.
8. The unit shall be protected in two ways: (1) by alarms that shut the unit down and require manual reset to restore unit operation and (2) by limit alarms that reduce unit operation in response to some out-of-limit condition. Shut down alarms shall activate an alarm signal.

9. Shutdown Alarms
 - a. No evaporator water flow (auto restart)
 - b. Sensor failures
 - c. Low evaporator pressure
 - d. Evaporator freeze protection
 - e. High condenser pressure
 - f. Outside ambient temperature (auto-restart)
 - g. Motor protection system
 - h. Phase voltage protection (Optional)
10. Limit Alarms
 - a. Condenser pressure stage down, unloads unit at high discharge pressures.
 - b. Low ambient lockout, shuts off unit at low ambient temperatures.
 - c. Low evaporator pressure hold, holds stage #1 until pressure rises.
 - d. Low evaporator pressure unload, shuts off one compressor.
11. Unit Enable Section
 - a. Enables unit operation from either local keypad, digital input, or BAS.
12. Unit Mode Selection
 - a. Selects standard cooling, or test operation mode.
13. Analog Inputs:
 - a. Reset or leaving water temperature, 4-20mA.
 - b. Current Limit.
14. Digital Inputs
 - a. Unit off switch
 - b. Remote start/stop
 - c. Flow switch
 - d. Motor protection
15. Digital Outputs
 - a. Shutdown alarm; field wired, activates on an alarm condition, off when alarm is cleared.
 - b. Evaporator pump; field wired, starts pump when unit is set to start.
 - c. Chiller pump control for freeze protection. (Sends a signal to ATC system to energize pump flow for freeze protection.)

I. Building Automation System (BAS) Interface

- a. Factory mounted DDC controller(s) shall support operation on a BACnet® network via one of the data link/physical layers listed below as

specified by the successful Building Automation System (BAS) supplier.

- b. BACnet MS/TP master (Clause 9)
- c. BACnet IP, (Annex J)
- d. BACnet ISO 8802-3, (Ethernet)
- e. The information communicated between the BAS and the factory mounted unit controllers shall include the reading and writing of data to allow unit monitoring, control and alarm notifications as specified in the unit sequence of operation and the unit points list.
- f. All communication from the chiller unit controllers specified in the points list shall be via standard BACnet objects. Proprietary BACnet objects shall not be allowed. BACnet communications shall conform to the BACnet protocol (ANSI/ASHRAE135-2004). A BACnet Protocol Implementation Conformance Statement (PICS) shall be provided along with the unit submittal.

J. Power Panel

1. The power panels shall contain the compressor power terminals, compressor motor-starting contactors with three external over-load protection, three additional current transformer sensing on each compressor phase for current monitoring, for protection against under-voltage, over voltage, imbalanced voltage, single phasing, compressor stall and voltage spikes, and control power supply terminal strip for 115-1-60. The power panel shall contain a 15-amp, 115 volt convenience outlet with Ground Fault Protection.
2. The compressor and fan power wiring shall be routed through U.L. listed, liquid-tight, non-metallic conduit suitable for outdoor use.
3. Single Point Connection Circuit Breaker: Provide a HACR rated molded case capacity circuit breaker (U.L. Approved). The circuit breaker shall be able to be used as disconnect through the door handle and shall be pre-wired from factory with terminal block connections. The external operator handle shall be lockable.

K. Control Transformer

1. A control transformer shall be factory installed to convert unit power voltage to 115-1-60. Factory mounting shall include primary and secondary wiring between the transformer and the control panel.

L. Tuned Discharge Mufflers

1. Muffler shall be included in each discharge line. It is acoustically tuned to attenuate the predominant frequencies of the gas pulsations for the particular compressor.

M. Sound Attenuation

1. Provide comprehensive sound enhancement package, including, low sound fans and an acoustical blanket shall be furnished on each unit. Fans shall be reduced RPM, 8 pole fan motors with steeper pitch fans.

N. Start-up and Warranty:

1. Provide the services of the chiller manufacturer's factory trained service technician to start the chiller(s). Service shall also provide concurrent training to the Owner's personnel.
2. Provide two (2) year parts and labor warranty with each unit. Provide extended compressor warranty for three (3) additional years.

O. Comprehensive Sound Enhancement Packages:

1. Low sound fans and an acoustical blanket shall be furnished on each unit. Fans shall be reduced RPM, 8 pole fan motors with steeper pitch fans.
2. Sound power levels so as not to exceed the following:

Sound Power Level db re 1 picowatt								
dBa	63Hz	125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	8000Hz
99	90	98	99	97	94	92	85	80

3. Compressor sound attenuation shall be of the perimeter design to allow ease of removal and access to compressor components.
4. Net chiller capacity shall be maintained as scheduled with the addition of the chiller sound enclosures.

P. Vibration Isolators

1. Provide level adjusting spring type, 1-inch deflection isolator with mounting brackets for mounting under the unit base. All exterior vibration isolators shall be stainless steel including hardware. As an alternate, vibration isolators may be provided as specified under Section 230548 at contractor's option.

Q. Training:

1. Chiller manufacturer shall include with his bid all cost associated with sending one (1) individual to chiller manufacturer's training center for one (1) week of training on the operation, troubleshooting and maintenance of the chiller. Training shall include all instruction and work materials.

R. Accessories and Options

1. Microprocessor controlled, Factory installed Across-the-Line type compressor

motor starters as standard.

2. Power Supply Connection:

- a. Single Point Connection Circuit Breaker: Provide a HACR rated molded case capacity circuit breaker (U.L. Approved). The circuit breaker shall be able to be used as disconnect through the door handle and shall be pre-wired from factory with terminal block connections. The external operator handle shall be lockable.
- b. Ground Fault Protection: Factory installed circuit breakers.
- c. Phase loss protection with under/over voltage protection and with LED indication of the type of fault.

3. Pressure Transducers and Readout Capability

- a. Discharge Pressure Transducers: Permit unit to sense and display discharge pressure.
- b. Suction Pressure Transducers: Permit unit to sense and display suction pressure.

4. Control Power Transformer: Converts unit power voltage to 120-1-60 (500 VA capacity). Factory mounting includes primary- and secondary-wiring between the transformer and the control panel.

5. Flow Switch (Factory Mounted): Vapor proof NEMA 4X switch (150 psig), -20 degrees F to 250 degrees F. Thermal dispersion type. Provide additional contacts to allow monitoring on the ATC system. An additional mechanical flow switch shall also be installed in evaporator piping.

6. Building Automation System (EMS) Reset Interface: Chiller to accept 4 to 20mA, 0 to 10 VDC, or discrete contact closure input to reset the leaving chilled liquid temperature.

7. Sound Reduction (Factory Mounted): Acoustic Compressor Blankets. Low speed condenser fans.

8. Vibration Isolation (Field Mounted):

- a. 1 inch deflection spring isolators: level adjusting, spring and cage type isolators for mounting under the unit base rails.

9. Wye strainers with stainless steel mesh size as required by chiller manufacturer. Furnish with blowdown valve, pipe extension, two Schraeder valves, fittings, and grooved couplings.

S. Source Quality Control

1. Verification of Performance: Rate chillers according to ARI 550 and up to 200 tons in accordance with ARI Standard 590.
2. Testing Requirements: Factory test for the following:

- a. Sound-Power-Level Ratings: According to ARI 370

NOT FOR BIDDING PURPOSES

2.3 AUTOMATIC GLYCOL MAKEUP SYSTEM

- A. Furnish an automatic glycol feeder to provide consistent operating pressure in the closed loop system by feeding a controlled percentage of glycol solution. Glycol shall be made-up automatically from a pre-mixed solution tank. A low level switch shall prevent pump operation when solution level is too low.
- B. The glycol feeder package to consist of a prewired control unit in a NEMA 1 steel enclosure and a pre-piped flow assembly including a pressure switch, pressure relief valve, 50 gallon polyethylene tank, low level switch, positive displacement pump, and pressure gauges. Automatic glycol feed system shall be Pulsafeeder Model GF-1, or approved equal.
- C. Glycol solution tank shall be 50 gallons polyethylene tank with steel supports for mounting the transfer pump below the tank. Provide hinged polyethylene cover, pump suction connection, and drain valve.
- D. Positive displacement flooded suction pump rated at capacity as scheduled on the contract drawings.
- E. Provide PVC piping from the tank to the pump with PVC ball valve and steel strainer. Include at discharge a check valve, ball type shutoff valve and pressure relief valve piped back to the solution tank.
- F. Provide a dolly suitable for transporting 55 gallon drums to the charging station. Dollies shall be suitable for storing a drum in the horizontal position so that the solution may be drained into a transfer pail. Include spring loaded draw valve.
- G. Provide 5 gallon plastic pail.

2.4 INDUSTRIAL INHIBITED PROPYLENE GLYCOL

- A. Provide a 30 percent by volume (as installed) industrial grade inhibited propylene glycol heat transfer fluid as manufactured by the Dow Chemical Company (Dowfrost HD), Houghton Interstate Chemical (Intercool P-300) Glycochill Plus or approved equal. The 30 percent solution shall provide freeze protection to 12 degrees F and burst protection to -20 degrees F. The propylene glycol solution as supplied by the manufacturer shall contain corrosion inhibitors specially formulated for cool storage services to keep internal surfaces free from corrosion and fouling and shall include buffers, reserve alkalinity agents, antifoaming additives, and a fluorescent dye to aid in leak detection. The solution shall be easily re-inhibited using specially formulated inhibitor readily available from the field manufacturer. The manufacturer shall provide free propylene glycol yearly solution laboratory analysis. The analysis shall accurately report propylene glycol concentration, freeze point temperature, inhibitor level, alkalinity, particulate and recommended additions of glycol, inhibitor and buffers to ensure twenty-year minimum life. The fluid shall pass the ASTM D-1384 test with less than 0.5 mils penetration per year.
- B. Automotive antifreeze or any solutions containing silicates shall not be acceptable.
- C. Propylene glycol shall be supplied preduilted with deionized water and installed in the

specified piping systems.

- D. Provide a Misco Products calibrated hand held refractor meter.
- E. Provide one spare 55 gallon drum of glycol.
- F. Contractor shall chemically clean and flush the completed propylene glycol system. As a minimum, system shall be cleaned with a 1 percent to 2 percent solution of trisodium phosphate in water. Provide temporary bypasses at the ice storage modules for the initial pressure testing, cleaning and flushing operations. This prevents the transfer of contaminants to the clean tubing in the modules. The system shall be thoroughly flushed using clean water and circulated for a minimum of 72 hours at which time water samples shall be taken by the contractor who shall certify that the system is free of particulate, mil scale, weld scale, solder flux, rust, metal filings, oil, grease, chlorides, sulphates, silicates and other foreign matter that could degrade the propylene glycol. After the system is charged with the approved heat transfer fluid, air shall be eliminated from the system, and the heat transfer fluid shall be circulated for 72 hours through all components. The contractor shall test and adjust the concentration to achieve 30 percent by volume propylene glycol.
- G. Entire system shall conform to EPRI Standard propylene glycol systems 15751.
- H. Flushing period (72 hours) shall be closely monitored to prevent excess heat build-up due to pump heat.

2.5 GLYCOL FEEDER PRESSURE TANK

- A. Provide and install glycol feeder pressure tanks of size, capacity and as indicated on contract drawings. Glycol feeder pressure tanks shall be Therm-X-TROL as manufactured by AMTROL Inc., Flexcon, Wessels, Taco or approved equal. Mount tank as detailed on the drawings.
- B. Glycol feeder pressure tanks shall be specifically designed for use in glycol systems. Tanks shall be pre-charged to require pressure at the factory. The maximum working pressure shall be 150 psig. The maximum operating temperature shall be 200 degrees F. Expansion tanks shall contain removable FDA approved butyl bladder.
- C. Before installation, Contractor shall adjust the tank air pre-charge pressures to equal glycol feed pump pressure.
- D. The tank must be constructed in accordance with Section VIII of the A.S.M.E. boiler and pressure vessel code and stamped 150 psig working pressure.
- E. Accessories: Pressure gauge and air charging fitting, tank drain, pre-charge as indicated on contract drawings and factory installed clip angles.

2.6 DUCTLESS SPLIT SYSTEM AIR CONDITIONER (INVERTER TYPE) (CEILING CASSETTE TYPE)

- A. The air conditioning systems shall be a Mitsubishi split type system, Sanyo, LG, Daikin,

Samsung, or approved equal. The system shall consist of a compact ceiling mounted packaged evaporator section and matching Slim Line air cooled outdoor unit. The units shall be listed by Electrical Testing Laboratories (ETL) and bear the ETL label. All wiring to be in accordance with the National Electrical Code (NEC). The units shall be rated in accordance with ARI Standard 210 and bear the ARI label. A full charge of R-410A for 100 feet of refrigerant tubing shall be provided in the condensing unit. A dry nitrogen holding charge shall be provided in the evaporator. System SEER shall meet or exceed 1992 Federal Standards.

- B. The units shall have a manufacturer's warranty for a period of one (1) year from date of installation. The compressor shall have a warranty of six (6) years from date of installation. If, during this period, any part should fail to function properly due to defects in workmanship or material, it shall be replaced or repaired at the discretion of Mitsubishi Electronics America, Inc. This warranty does not include labor. Manufacturer shall have ten years experience in the U.S. market.
- C. Capacity shall be as scheduled on the contract drawings.
- D. The indoor unit shall be completely factory assembled and wired. The casing shall be galvanized sheet with grey heat insulation. This unit shall fit in the ceiling and have the capability of attaching a branch supply duct as well as a fresh air duct. The evaporator fan shall be an assembly with a high performance fan direct driven by a single motor. The fan shall be statically and dynamically balanced and run on permanently lubricated bearings. The indoor unit shall have an adjustable air outlet system offering 4-way air flow, 3-way air flow, or 2-way air flow. The auto air swing vanes shall automatically swing up and down for uniform air distribution. Return air shall be filtered by a long-life filter to provide approximately 2,500 hours of use in a normal office environment before cleaning. The indoor unit shall be covered with a flat panel which protrudes only 1 inch below the ceiling to provide a neat and clean installation. The coils shall be of nonferrous construction with smooth plate fins bonded to copper tubing. The tubing shall have inner grooves for high efficiency heat exchange. All tube joints shall be brazed with phosphor copper or silver alloy. The coils shall be pressure tested at the factory. A condensate pan shall extend under the coil and piping. An integral drain pan pump capable of lifting condensate 12 inches shall be provided. The unit electrical power requirements shall be as indicated on the contract drawings.
- E. The control system shall consist of two (2) microprocessors interconnected by a single non polar two wire cable as supplied. Wiring shall run from indoor unit to controller direct. NO SPLICES. When running longer lengths or more than one set of hardwired remote controller wires together, a double insulated, two wire cable equivalent to that provided e.g. Belden 9407 cable, is mandatory or used shielded two wire cable. One microprocessor shall be factory wired and located within the indoor unit. It shall have the capability of sensing return air temperature and indoor coil temperature; receive and process commands from the hardwired remote controller; provide emergency operations, and control the outdoor unit. The microprocessor within the wall mounted hardwired remote controller shall provide automatic cooling, display set point and room temperature; a 24-hour on/off timer so that automatic operation can be set on the timer at one-hour intervals from one to twenty-four hours; have self-diagnostic function display; check mode for memory of most recent problem; control operation of the air sweep louvers; and provide on-off and system/mode function switching. Normal operation of the hardwired remote controller provides individual system control in which one

hardwired remote controller and one indoor unit are installed in the same room. The hardwired remote controller shall have the capability of controlling up to a maximum of 50 systems at a maximum developed control cable distance of 1650 feet. The control voltage between the hardwired remote controller and the indoor unit shall be 12 volts, D.C. The control voltage between the indoor unit and the outdoor unit shall be 12 volts, D.C. Both 12VDC shall be generated from the indoor unit microprocessor board. The system shall be capable of automatic restart when power is restored after power interruption. System shall include twenty function self diagnostics including total hours of compressor run time.

- F. The outdoor unit shall be completely factory assembled, piped, and wired. The casing shall be fabricated of galvanized steel, bonderized and finished with baked enamel. The unit shall be furnished with one (1) direct drive, propeller type fan arranged for horizontal discharge. The motor shall have inherent protection, be of the permanently lubricated type and resiliently mounted for quiet operation. Each fan shall be provided with a raised guard to prevent contact with moving parts. The variable speed compressor shall be of the high performance, rotary type with crankcase heater, accumulator and internal thermal overloads. The variable speed compressor shall be mounted so as to avoid the transmission of vibration. The refrigeration system shall be equipped with high pressure switch and have the capability to operate with a maximum height difference of 130 feet and overall refrigerant tubing length of 130 feet between indoor and outdoor sections without the need for line size changes, traps or additional oil. Refrigerant flow from the condenser to be controlled by means of a capillary tube. The condenser coil shall be nonferrous construction with smooth plate fins bonded to copper tubing. The tubing shall be inner grooves for high efficiency heat exchange. The coil shall be protected with an integral metal guard. The units shall be controlled by the microprocessor located in the matching indoor unit. A built-in, low-ambient controller shall allow cooling to 0 degrees F outdoor temperature. The unit electrical power requirements shall be as scheduled on the contract drawings. The outdoor condensing unit shall be placed on vibration isolators and mounted on rooftop equipment rail or concrete pad as indicated.
- G. High condensate water safety shutdown: Each indoor unit's detection unit shall be interlocked to alarm and stop the outdoor unit if a high condensate water level is sensed.

2.7 ELECTRIC RADIANT HEATERS

A. Electric Radiant Ceiling Panel

1. General: Provide electric radiant ceiling panels as indicated on the drawings. The electric ceiling heating panel shall be AZTEC, as manufactured by Berko, a Division of Marley Electric Heating, or as approved equal. The construction and design shall permit it to be: recessed ceiling-mounted with the use of Recessed Mounting Kit, fit into standard or custom designed modules of a T-bar suspended ceiling, surface-mounted with the use of a Surface Mounting Kit, or exposed with the use of a surface mounting kit and duct strap attached to roof structure. In finished spaces with hard ceilings, install units recessed. Panels shall be UL listed. Panels shall include the custom features listed below.
2. Heating Assembly: The heating assembly shall be UL and CSA approved and shall consist of powdered graphite encapsulated in a plastic laminate with heavy

duty copper buss bars running the entire length, backed by 1-inch, 1-pound density high temperature fiberglass insulation to insulate against heat loss to the ceiling and separated from the inside of the panel by a dielectric insulation to assure uniform heat transfer throughout the entire radiating surface of the heater.

3. Thermal Cutout: A thermal cutout shall be built into all high density panels to automatically shut off the heater in the event of overheating and reactivate the heater when temperatures return to normal.
4. Wiring: For connection to the main power supply, the heater shall be completely prewired, with the lead wires housed in a 40-inch length of flexible metal conduit and connector for J-Box mounting. Appropriate diagrams shall appear on the back of the panel. Provide modular connectors, pre-wired system for unit mounted end to end. Coordinate with Division 26.
5. Panel Assembly: The metal heating panel, containing the completely prewired heating assembly, shall be of 22 gauge formed galvanized steel front and 24 gauge formed galvanized steel back. Sides are overlapping front and back panels riveted together.
6. Finish: The front of the heating panel shall be multi-faceted crystalline type surface finished with high temperature silicone paint.
7. Controls: All radiant heaters shall be thermostatically controlled. When more than one radiant heater is shown in a space, provide the minimum number of thermostats required to control the total quantity of heating panels in the space. Thermostats, control transformers and associated controls shall be provided by the Manufacturer. Coordinate requirements with Division 26 and ATC Subcontractor.
8. Features: Radiant heating panels shall be provided with the following features:
 - a. Painted frame to match heater.
 - b. Factory silicone sealed for shower rooms.
 - c. Seal tight flexible conduit and connectors for shower rooms.
9. Thermostats shall be Q-Mark Model WRIE 30S Mercury Bulb, single pole single throw, 24 volt with 40 degrees F and 80 degrees F range. Provide and install stainless steel thermostat guards over all thermostats. Provide and install Q-Mark Model LTR2-277 dual level temp relays. Relays shall be enclosure mounted. Provide and install low voltage transformers as required.

28 BASE MOUNTED PUMPS - END SUCTION

- A. Furnish and install base mounted centrifugal end suction pumps to circulate hydronic water to the various items of equipment throughout the building, associated with the HVAC system. Pumps shall have sizes and capacities as indicated on the drawings.
- B. All pumps shall be suitable for the service and temperatures designated and shall conform to the following requirements. Each pump shall have a factory installed seal flushing line running from the seal area to the pump suction to insure removal of trapped air from the

seal area, removal of sediment, and cooling of the seal to extend seal life. Provide and install Cuno five (5) micron filters in seal flushing lines. Provide two (2) sets of cartridges for each side - stream filter.

- C. Pumps shall be cast iron bronze fitted and shall be suitable for up to 175 psi working pressure and up to 250 degrees F water temperature. Pumps shall have center-line discharge for positive venting and flanged bodies. Pumps shall incorporate a grease lubrication system and be so designed that the bearing assembly can be removed in one piece. A water slinger shall be provided between the mechanical seal and bearing areas. Pump shafts shall be stainless steel with a cupro-nickel sleeve, and be coupled to the motor shaft by a noiseless, non-metallic coupler with guard. Impellers shall be one piece cast bronze, dynamically balanced. Motors shall be 1750 rpm. For variable speed pumps, motors shall be inverter duty rated.
- D. Pumps shall be designed so that they shall not overload at low heads and shall not develop excessive pressure under throttled flow conditions or overload motor anywhere on the operating curve. Operating performance curves shall be submitted for approval. Provide gauge tappings on each pump flange. Furnish dust caps at all oil fill tubes. Pump motors shall be non-overloading throughout the range of the curves.
- E. Units shall be provided with motors of not less than the horsepower indicated, suitable for the service and available electrical characteristics. Units shall be controlled as hereinafter specified. After installation and prior to operation, each pump shall be aligned. Motors shall be as specified hereinbefore.
- F. Casing: Cast iron, with suction and discharge gage ports, renewable bronze casing wearing rings, seal flush connection, drain plug, flanged suction and discharge.
- G. Impeller: Bronze, fully enclosed, keyed to shaft.
- H. Baseplate: Cast iron or fabricated steel with integral drain rim.
- I. Pumps shall be primed and painted in baked enamel, rust resistant paint.
- J. Electrical characteristics shall be as scheduled on the contract drawings. Provide terminal lugs to match branch circuit conductor quantities, sizes, and materials indicated. Enclose terminal lugs in terminal box sized to NFPA-70.
- K. Pumps shall be FE series as manufactured by Taco, 2000 Series by Allis Chalmers, Aurora, Bell & Gossett, PACO, Armstrong, Patterson, or as approved equal.

29 IN-LINE CIRCULATING PUMPS

- A. Furnish and install in-line circulating pumps as shown on the contract drawings. Pump and motor shall be equipped with sleeve bearings for quiet operation. Pumps shall be suitable for up to 175 psi working pressure and up to 300 degrees F water temperature as per ASA B16.1. Pump rating curves shall be the result of testing and rating in accordance with the procedures of the Hydraulic Institute.
- B. Pump motors shall be non-overloading throughout the range of the curves. Pumps shall

have center-line discharge for positive venting, flanged bodies, and same size suction and discharge. Pumps shall incorporate a disc type lubrication system and be so designed that the bearing assembly can be removed in one piece. One bearing assembly shall be suitable for all sizes of the inline pumps furnished. Sump oil temperature may not exceed 180 degrees F when circulating 250 degrees F water with a 90 degree F ambient. Vent and drain openings at least 3 square inches in area and a water slinger shall be provided between the mechanical seal and bearing area. This water slinger shall be integral with shaft sleeve. All in-line circulating pumps shall be provided with all bronze construction when used in open system and shall be bronze fitted for closed system.

- C. Provide gauge tappings on each pump flange.
- D. Pump body shall be cast iron and pump shafts shall be alloy steel with cupro-nickel sleeve covering all wetted parts, and be coupled to the motor shaft by a noiseless non-metallic coupler. Impellers shall be one piece cast bronze, dynamically balanced. Pumps shall have a two piece mechanical seal assembly easily replaceable without the use of special tools. Motors shall be resilient mounted, 1750 RPM and require no external overload protection when used with single phase current.
- E. Electrical characteristics shall be as scheduled on the contract drawings. Provide terminal lugs to match branch circuit conductor quantities, sizes, and materials indicated. Enclose terminal lugs in terminal box sized to NFPA-70.
- F. In line pumps shall be Red Baron Series 110 in-line circulators or 1600 Series, as manufactured by Taco, Bell & Gossett, Thrush, Armstrong, Patterson, or as approved equal.

2.10 VARIABLE SPEED DRIVES

- A. Provide variable speed drive controllers for 100% Air Handling Units and associated Exhaust Air Fans, Pumps, as indicated on contract drawings. Drive shall be subject to the requirements of this section.
- B. Kitchen make-up air unit and kitchen exhaust fan variable speed drives shall be factory furnished with the packaged kitchen hood ventilation control system. Under this Division install VFDs where indicated on the Contract Drawings.
- C. The adjustable frequency controller (AFC) shall convert three phase 60 Hertz utility power to adjustable voltage and frequency, three phase, AC power for stepless motor control from 5 percent to 110 percent of base speed.
- D. The AFC shall be a voltage source type with a PWM output utilizing power transistor semi-conductors.
- E. The AFC together with all options and modifications shall mount within a standard NEMA 1 enclosure suitable for continuous operation at ambient temperature of 0 to 40 degrees C. with relative humidity to 95 percent non-condensing. All high voltage components within enclosure shall be isolated with steel covers. The complete unit shall be UL approved and UL labeled.
- F. Circuits shall provide DV/DT and DI/DT protection for semi-conductors. AFC shall be

capable of starting into a rotating load without delay. Protective circuits shall cause instantaneous trip (IET) should any of the following faults occur:

1. Motor overload.
 2. Shortcircuit.
 3. Motor overtemperature fault.
 4. Reverse phase.
 5. 110 percent of controller maximum sine wave current rating is exceeded.
 6. Output phase to phase and phase to ground short circuit condition.
 7. High input line voltage.
 8. Low input line voltage.
 9. Loss of input phase.
 10. External fault. This protective circuit shall permit, by means of the terminal strip, wiring of remote NC safety contacts such as high static, firestat, etc., to shut down the drive.
- G. The following adjustments shall be available in the controller and retained in non-volatile memory:
1. Maximum frequency (15 to 400 Hz) factory set at 60 Hz.
 2. Minimum frequency (3 to 60 Hz) factory set at 6 Hz.
 3. Acceleration (.1 to 360 seconds) factory set at 20 seconds.
 4. Deceleration (.1 to 360 seconds) factory set at 20 seconds.
 5. Volts/Hertz ratio factory set for 460 v at 60 Hz.
 6. Voltage offset or boost factory set at 100 percent torque.
 7. Current limit (50 percent to 110 percent sine wave current rating) factory set at 100 percent current.
- H. The AFC shall have the following basic features:
1. Door-mounted operators controls consisting of a membrane command center which allows manual stop/start and speed control, local/remote indication and manual/automatic speed control selection. In addition, the command center shall serve as a means to configure controller parameters such as min speed, max speed, acceleration and deceleration times, Volts/Hz ratio, torque boost etc. Potentiometers shall not be allowed for these settings.
 2. Main input disconnect to provide a positive disconnect between the controller and all phases of the incoming A-C line. This disconnect shall be mounted inside the controller enclosure and have through-the-door interlocking toggle with provisions for padlocking.
 3. Electronic motor overload relay.
 4. Automatic restart after power outage, drive fault or external fault, with drive in automatic mode. The circuit shall allow the user to select up to (10) restart attempts as well as the dwell time between attempts. The reset time between fault occurrences shall also be selectable. All settings shall be via the membrane command center.

5. Door-mounted LED display for digital indication of:
 - a. Frequency output
 - b. Voltage output
 - c. Current output
 - d. First fault indication
 - e. Fan or Pump Speed (RPM)
 6. Relay contacts for remote indication of drive fault and motor finning.
 7. Three critical frequency avoidance bands, field programmable via the membrane command center. Each critical frequency avoidance band shall have a bandwidth adjustable via keypad entry of up to 10 Hz.
 8. Three programmable preset speeds which shall force the AFC to a preset speed upon a user contract closure.
 9. Isolated process follower to enable VFC to follow a 4-20 mA signal.
 10. The AFC shall have the capability to ride through power dips up to 500 msec without a controller trip depending on load and operating condition.
 11. Line reactor to minimize line surges, line notching, and voltage distortions. Line reactor shall be installed upstream of the drive.
- I. Manual bypass-to-line with magnetic contactors to transfer motor from the variable frequency controller to full speed operation on utility supplied input power while the motor is at any speed. Two motor contactors, electrically interlocked shall be utilized, one contactor between the controller output and the motor and the other between the bypass power line and the motor, providing across-the-line starting.
 - J. Motor protection per National Electrical Code shall be provided in both the "controller" mode and the "bypass" mode by a motor overload relay. The 115 volt A-C relay control logic, allowing common start/stop commands in the "controller" mode and the "bypass" mode shall also be included within the enclosure.
 - K. The bypass shall include a door interlocked, main power input circuit breaker providing positive shutdown of all power to both the bypass circuitry and the VFC. The bypass circuit shall also include a second input disconnect to the VFC. This disconnect shall provide the ability to safely trouble shoot and test the controller, both energized and de-energized, while operating the bypass mode. Terminal connectors for over pressurization switches shall be provided, to protect the duct work in the bypass mode.
 - L. The VFC and all components shall be supplied within a single NEMA 1 enclosure, and shall be U.L. Listed as a single unit. Furnish all components necessary to provide a minimum lead length between motor and drive of 400 ft. The VFC shall not generate damaging transistor pulses greater than the limits set by NEMA MG-1 at 400 Ft lead length.
 - M. The VFC manufacturer shall maintain and staff nationwide service centers. These service engineers shall be employed by the manufacturer and provide start-up service

including physical inspection of drive and connecting wiring and final adjustments to meet specified performance requirements.

- N. The VFC shall carry a full parts and labor warranty for two years from date of Owner acceptance of the building.
- O. The variable speed drive shall be ABB, or approved equal of Accutrol, Cutler Hammer, Graham, York, Baldor, AC Tech, Trane, Emerson, Danfos, Yaskawa, Toshiba, or as approved equal.
- P. The variable speed drive manufacturer shall coordinate with the ATC contractor and provide all necessary devices whether optional or not to perform complete and automatic operation as described in the sequence of operation. All safeties, including freestats, duct smoke detectors, and high static pressure sensors shall be enabled when variable speed drives are in manual or bypass.
- Q. BAS Interface: Factory-installed hardware and software to enable the BAS to monitor, control, and display VFC status and alarms. Allows VFC to be used with an external system within a multidrop LAN configuration; settings retained within VFC's nonvolatile memory.
 - 1. Network Communications Ports: Ethernet and RS-422/485.
 - 2. Embedded BAS Protocols for Network Communications: ASHRAE 135 BACnet; protocols accessible via the communications ports.
- R. Variable speed drives shall be carefully selected for the duty required. Variable speed drives shall be specifically designed for the specified equipment to be controlled. Pump drives shall be selected for pumps and fan drives shall be selected for fans.

2.11 COALESCING AIR SEPARATOR

- A. Furnish and install as shown on the drawings a Spirotherm, Bell and Gossett, Taco 4900 Series, Caleffi, Armstrong, Wessels, or approved equal air elimination separator. All fittings shall be fabricated steel, rated for 150 psig design pressure and selected for less than 1 foot of water pressure drop and velocity not to exceed 4 feet per second through the unit at specified GPM. All units shall include an integral copper bundle of Spirotubes or approved equal, to act as the turbulence suppressive coalescing medium which must completely fill the fitting's internal area. Units are to remove free and entrained air during system start up and continue to eliminate dissolved air through continual circulation and the coalescing action of the Spirotubes. Each fitting is to have a separate air and venting chamber to prevent system contaminants from harming the float and venting valve operation. At the top of the venting chamber shall be an integral float actuated brass air vent. There shall be no restriction in the connection from the venting chamber to the vent. The fittings are to include a valve side tap to flush floating dirt or liquids and for quick bleeding of large amounts of air during system fill or refill. Units shall include a bottom connection for use as a blow down connection for periodic cleaning. Air separator shall be primed and finished in rust resistant paint. Units shall be Spirovent Senior models of the size required to meet pressure drop and velocity criteria.
- B. A blowdown connection shall be provided to facilitate routine cleaning of the strainer and

the separator.

- C. A manufacturer's data report for pressure vessels, for U-1 as required by the provisions of ASME Boiler and Pressure Vessel code, shall be furnished for each air separator upon request. Manufacturer to furnish data sheet specifying air collection efficiency and pressure drop at rated flow.
- D. Conventional tangential or centrifugal non-coalescing air separators shall ~~not~~ be acceptable.

2.12 EXPANSION TANKS

- A. Furnish and install as shown on the drawings, pre-pressurized captive air bladder type expansion tank pre-charged with air. Tank shall be suitable for a maximum working pressure of 125 psi and constructed and certified to ASME Section VII. It shall have a replaceable elastomeric bladder suitable for a maximum operating temperature of 240 degrees F (115 degrees C). Expansion tanks shall be primed and finished in rust resistant paint. It shall have an integral steel base ring for vertical mounting and saddle for horizontal mounting. Expansion tank shall be as manufactured by Taco, Bell & Gossett, Wessels, Amtrol, Armstrong or as approved equal.

2.13 HORIZONTAL RECESSED CABINET UNIT HEATERS(WITH INTEGRAL SUPPLY/RETURN GRILLES)

- A. Furnish and install horizontal recessed cabinet unit heaters of the size, capacity, and electrical characteristics shown on the contract drawings. Units shall be Trane, Model E, Dunham Bush, Modine Corp or approved equal.
- B. Cabinet is galvanized steel wrap-around structural frame with all edges flanged. Insulation is faced, heavy density glass fiber. Unit to have 18 gauge steel, removable, four-side overlap bottom panel adjustable 3/8 inch with full length, piano type hinge at back and camlocks a front. All cabinet parts shall be finished in a baked on enamel finish in color as selected by Architect. Bottom panels on horizontal recessed units shall be provided with tamper-proof screw fasteners and safety chain.
- C. Water coils to be 5/8 inch OD seamless copper tubes mechanically bonded to configured aluminum fins with continuous fin collars and sleeved coil end supports. Maximum working pressure 300 psig, factory test pressure 450 psig (air). Supply and return connections on same side of units.
- D. Fans shall be centrifugal, forward curved, double width of non-corrosive, molded, fiberglass-reinforced thermo-plastic materials. Fan wheels and housings shall be corrosion resistant.
- E. Motor shall have integral thermal overload protection and start at 78 percent of rated voltage. Motor to be factory installed and tested prior to shipping.
- F. Filters to be accessed by pivoting hinged bottom panel. Filters shall be 1 inch woven glass filters.
- G. Provide each unit with factory furnished bottom integral grilles for supply and return.

Unit shall be provided with factory furnished vibration isolators and mounted in an approved manner with all threaded steel rod.

- H. Provide 18 gauge steel flanges (factory furnished) for recessing unit heater into ceiling.
- I. Unit shall be U.L. listed.

2.14 HORIZONTAL HOT WATER UNIT HEATERS

- A. Provide and install horizontal hot water unit heaters of the size, capacity and electrical characteristics as indicated on the contract drawings. Horizontal unit heaters shall be Trane Model S, Dunham Bush, Modine Corp. or approved equal.
- B. Casing shall be two-piece with "picture frame" front formed into wrap around sides, top and bottom. Furnish each unit with louvered fin diffuser for versatility in lateral diffusion. Casing shall be 18 gauge back panel with deep draft fan orifice for extreme rigidity. Steel supply and return pipe top connectors bolted to back. Casings phosphatized to prevent corrosion and finished with a green baked enamel finish.
- C. Fan shall be high efficiency Model A with aluminum blades, factory balanced and sturdy for standard applications.
- D. Coils shall be hot water, single tube single serpentine design. Fins shall be aluminum sigma-flow, mechanically bonded to seamless copper tubing. All coils one-row deep in air flow direction. Coils shall be tested at 500 psig air under water. Coils shall be suitable for operation at 200 psig or 325 degrees F.
- E. Motors shall be totally enclosed, class "B" insulated shaded pole and permanent split capacitor. All motors shall have built-in overload protection. Sleeve bearing motors can be oiled. Ball bearing motors are permanently lubricated. Units shall be U.L. listed.

2.15 FAN COIL UNITS

- A. Provide and install fan coil units of the type, capacity, and electrical characteristics as shown and scheduled on the plans. The units shall be installed in a neat and workmanship like manner in strict accordance with specifications. Floor mounted fan coil units shall be fully recessed units as manufactured by York, Carrier, McQuay, Pittling, Johnson Controls, or Trane. All fan coil units shall be U.L. and CSA approved. All floor mounted units shall be rated in accordance with ARI Industry Standard 440.
- B. Basic Unit: The basic unit shall be fabricated of 18 gauge galvanized steel. Interior surfaces of coil section of Floor mounted models shall be lined with 2 inch coated glass fiber insulation meeting NFPA-90A requirements. The fan and motor assembly shall be easily removable for serviceability.
- C. Cabinet: Units shall have 18 gauge steel panels acoustically and thermally insulated with ½ inch coated glass fiber insulation meeting NFPA-90A requirements. Exposed panels shall be bonderized and finished with a baked primer. Baked enamel finish, of color selected by Engineer shall be provided. Floor mounted models shall have an easily removable front panel for complete serviceability. Stamped aluminum supply grilles and

die formed recessed access doors for control and piping compartments shall be provided in the front panel. Each unit shall have a supply and return air grille stamped into the front panel.

- D. Coils: All cooling coils shall be ARI rated. Coils shall have 2 inch OD copper tubes with aluminum fins, mechanically bonded to the tubes. All coils shall be fitted with manual air vents. Coils shall be factory leak tested at 300 psig and suitable for working pressures to 250 psig at 200 degrees F. Coil connections shall be 5/8 inch OD male sweat fittings.
- E. Motors: Motors shall be 3-speed, resilient mounted with UL listed thermal overload protection. Motor bearings shall be of the sleeve type or ball bearing type. Standard motors are permanent split capacitor (PSC). Motors shall be premium efficiency type.
- F. Fan Switch: All units shall be provided with a OFF-HI-MED-LO fan speed switch unit mounted on Floor models. Fan switches shall be utilized for balancing to design CFM.
- G. Junction Box: Exposed floor shall have the fan speed switch and optional controls wired to the control box.
- H. Fans: Fans shall be of the centrifugal, forward-curved type. Fan wheels shall be statically and dynamically balanced. Fan wheels shall be painted or galvanized, and housings shall be galvanized steel.
- I. Drain Pan: Floor models shall have a combination drain pan and fan deck assembly, fabricated of 18 gauge galvanized steel. Pans shall be insulated with closed cell, polyurethane, sprayed-on foam. Floor models shall be provided with an auxiliary drain pan of molded plastic with a 3/4 inch MPT drain connection. Steel sleeved auxiliary drain pans shall be provided to permit piping through the auxiliary drain pan.
- J. Filters: Floor models shall have 1 inch throwaway filters of woven glass fiber furnished as standard equipment.
- K. The ATC controls contractor shall furnish the terminal control unit controller for installation on each fan coil unit by the unit manufacturer. These devices shall be delivered to the unit manufacturer's factory in sufficient time for the manufacturer to meet their schedule obligations. The relay for fan shall be provided by the unit manufacturer who shall also provide the interconnect wiring between the relays and the DDC control unit. The unit manufacturer shall also provide a 24 VAC power source at each terminal unit. The cost of factory mounting, wiring, enclosure to meet local code and any factory testing and programming of the terminal control unit shall be included by the terminal box manufacturer.
- L. All units shall be sound tested using a qualified reverberant room per ARI Standard 350-82.

2.16 KITCHEN VENTILATION UNIT

- A. Provide and install supply kitchen ventilation system of the size, arrangement, performance, and electrical characteristics as indicated on contract drawings. Kitchen ventilation system shall be Model I6X as manufactured by Greenheck. The supply unit

shall include a Model I6X make-up air unit, Model ES-4 equipment support and Model GPNS roofcurb.

- B. Filtered makeup air units shall have belt driven double width/double inlet, forward curved centrifugal type supply fans.
- C. The entire fan and motor assembly shall be mounted on vibration isolators to prevent noise transmission. Motors shall be permanently lubricated, heavy duty, ball bearing type, carefully matched to the fan load and furnished at the specified voltage, phase and enclosure. The fan shaft shall be ground and polished steel mounted in heavy duty sealed ball bearings. Bearings shall be selected for a minimum average (L50) life in excess of 200,000 hours at maximum cataloged operating speeds. Pulleys shall be of the fully machined, cast iron type, keyed and securely attached to the wheel and motor shafts.
- D. Motor sheaves shall be adjustable for final system balancing. Drives shall be sized for a minimum of 150 percent of driven horsepower. Fan wheels shall be of the forward curved type, constructed of heavy gauge steel and statically and dynamically balanced to ensure smooth vibration free operation.
- E. Housing construction shall be heavy gauge galvanized steel with removable panels for access to fan and tempering unit components, filters and controls. Filters shall be one inch aluminum mesh and shall be U. L. Classified. Housing shall be externally painted for rooftop installation.
- F. The tempering units shall be direct fired natural gas heaters with Maxitrol 44 gas controls with ETL label. The pre-wired control center shall include, but not be limited to, an integral master disconnect switch with fuse blocks for main power connection, magnetic motor starters with thermal overloads and manual reset, fused 115 volt control transformer, auxiliary relay(s) as required for interlocking of remote exhaust fans, and distribution terminal control strip for control wiring connection. All electrical components shall be U. L. Listed, Approved or Classified where applicable and wired in compliance with the National Electrical Code. Wiring shall be complete, requiring two point field connection (one for power service and one for point field connection for low voltage).
- G. Indirect Gas Fired Furnace
1. Shall be ETL Certified as a component of the unit.
 2. Shall have an integral combustion gas blower.
 3. Shall be ETL Certified for installation downstream of a cooling coil.
 4. Shall have fault sensors to provide fault conditions to optional digital controller or building controls.
 5. Shall have 4-pass tubular heat exchangers, constructed of type 409 stainless steel. Heat exchanger tubes shall be installed on the vest plate by means of swaged assembly, welded connections are not acceptable. Heat exchanger tubes shall be supported by a minimum of two fabricated assemblies that support the tubes and also permit expansion and contraction of the tubes.
 6. Heat exchanger shall have a five year extended warranty.
 7. Shall be encased in a weather-tight metal housing with intake air vents. Large, metal lift-off or hinged door shall provide easy access to the enclosed vest plate,

- control circuitry, gas train, burner assembly and exhaust blower.
8. Shall include a kit for outdoor mounting the vertical stack venting.

H. The make-up air unit shall be factory furnished with weatherhood, with birdscreen, 1 inch aluminum mesh filter, control center with combined switching, NEMA 1 toggle disconnect switch and motor operated damper. Motor operated damper actuator and end switch shall be furnished by ATC subcontractor and installed by mechanical contractor.

2.17 AIR CONDITIONING CONDENSATE PUMPS

- A. Provide and install air conditioning, condensate pumps of the size, capacity, and electrical characteristics as shown on the contract drawings. Units shall be Little Giant, Beckton, Diversitech, or approved equal.
- B. Units shall be U.L. listed and CSA certified. Each pump shall include 6 ft power cord with 3 prong molded 115 volt plug and thermal overload protection or with pigtail lead in lieu of plug and cord, removing the plug shall not violate the pump manufacturer's warranty, nor shall it void the pump's U.L. listing. Include low voltage safety switch with polypropylene float that shall be wired to cut off the indoor unit in the case of malfunction. Safety switch should be connected to a Class II low voltage safety device.
- C. Housing shall be constructed of high impact resistant polystyrene, ABS impeller and volute, and stainless steel shaft. Mount units directly below adjacent indoor units as detailed and pipe discharge with check-valve as shown on the drawings.
- D. Water heater condensate pump shall be specifically engineered and listed for use with high temperature boiler and water heater acidic condensate.
- E. Refer to Division 23 Section, "Instrumentation and Controls of HVAC and Plumbing Systems".

2.18 EXTERIOR EQUIPMENT/DUCT SUPPORT

- A. Exterior Equipment Supports shall be Pate Model ES suitable for roof construction. Equipment supports shall be constructed of 18 gauge galvanized steel, unitized construction with integral base plate, continuous welded corner seams, pressure treated wood nailer counterflashing and lag screws. Units shall be internally reinforced. Minimum height shall be 12-inches above the finished roof or as shown on the detail(s) on the drawing(s).

2.19 EXTERIOR PIPE ROLLER SUPPORTS

- A. Furnish and install pipe roller supports for all exterior piping as indicated on contract drawings. Pipe roller supports shall be constructed of heavy gauge galvanized steel, continuous welded corner seams, 2 x 4 treated wood nailer, heavy gauge galvanized steel counterflashing with galvanized steel channel track attached.
- B. Roller assembly shall consist of galvanized steel channel track, galvanized steel fittings, washers, nuts, and painted cast iron roller. Installation shall permit both vertical and horizontal adjustment. Units shall be Pate Model RAC or approved equal.

2.20 ROOF CURBS (DUCT PENETRATIONS)

- A. Furnish and install roof curbs at all penetrations of roof by ductwork and where indicated on contract drawings. Roof curbs shall be Model PC as manufactured by Pate, Greenheck, or approved equal.
- B. Roof curbs shall be constructed of heavy gauge galvanized steel, unitized, full material corners, all seams welded, 1 ½ -inch thick rigid fiberglass insulation, pressure treated wood nailer strip. Curbs shall be minimum 12-inch height unless otherwise noted, and have inner diameter equal to indicated duct diameter.

2.21 AIR MONITORING STATIONS (ERV & KITCHEN MAKE-UP AIR UNITS)

- A. General: Provide complete air monitoring station for air handling units, as indicated on drawings. The air monitoring station shall include airflow measuring stations, static pressure probes and electronic velocity pressure transmitter. All components shall be of the same manufacturer. The manufacturer shall be Air Monitor, Gold Series Ebtron Thermistar, or as approved equal. An air monitor station shall be provided for each supply duct main, exhaust duct main, and return duct main as indicated on contract drawings. All air flow monitoring stations shall be fully externally insulated to prevent condensation.
- B. Air Monitor Airflow Measuring Stations
 1. Provide where indicated airflow measuring stations capable of continuously monitoring the fan or duct capacities (air volumes) they serve.
 2. Each airflow measuring station shall contain multiple total and static pressure sensors positioned at the center of equal area of the station cross-section and interconnected by their respective averaging manifolds. For stations of 4 square feet or less, one total and one static pressure sensor shall be present for every 16 square inches of station area respectively. For stations of larger area, one total and one static pressure sensor shall be present for every 36 square inches of station area respectively.
 3. The airflow measuring station shall be fabricated of a minimum of 14 ga. galvanized steel, welded casing in 8-inch depth with 90 degree connecting flanges in a configuration and size equal to that of the duct it is to be mounted into. Each station shall be complete with an open parallel cell air straightener or air equalizer honeycomb mechanically fastened to the casing, total and static pressure sensors located on an equal area basis and connected to symmetrical averaging manifolds, internal piping, and external pressure transmitter ports. An identification label shall be placed on each station casing listing model number, size, area, and specified airflow capacity.
 4. Cell construction shall be 3/8-inch .003-inch, type 3003 aluminum, expanded.
 5. The maximum allowable pressure loss through the station shall not exceed .015-inch wc at 1000 fpm, or .085-inch wc at 2000 fpm. Each station shall be capable of measuring the airflow rate within an accuracy of 2 percent as determined by

U.S.G.S.A. certification tests. The stations shall have a self-generated sound rating of less than NC 40, and the sound level within the duct shall not be amplified, nor shall additional sound be generated.

- 6. Stations shall be Fan-E type as manufactured by Air Monitor Corporation, Paragon or as approved equal.

C. Air Monitor Duct Static Pressure Traverse Probes

- 1. Provide where indicated duct static traverse probe capable of continuously monitoring the duct or system static pressure it serves.
- 2. Each duct static traverse probe shall contain multiple static pressure sensors located along the exterior surface of the cylindrical probe. Said sensors shall not protrude beyond the surface of the probe.
- 3. The duct static traverse probe shall be of extruded aluminum construction and (except for 3/4-inch diameter probes with lengths of 24-inches or less) be complete with threaded end support rod, sealing washer and nut and mounting plate with gasket and static pressure signal fitting.
- 4. The static traverse probe shall be capable of producing a steady, non-pulsating signal of standard static pressure without need for correction factors, with an instrument accuracy of 0.5 percent.
- 5. The duct static pressure traverse probe shall be the STAT-probe/1 as manufactured by the Air Monitor Corporation, Paragon or as approved equal.

D. Air Monitor Electronic Velocity Pressure Transmitters

- 1. The electronic control-instrument components shall be of industrial process control quality with operating features described herein and capable of producing the outlined performances. Commercial grade control-instruments, devices, are not acceptable.
- 2. The electronic differential pressure transmitter shall include an automatic zeroing circuit capable of automatically readjusting the transmitter zero at predetermined (adjustable) time intervals while retaining (locking in) the output signal. The electronic differential pressure transmitter shall be capable of receiving signals of duct total and static pressures, and of amplifying and scaling the sensed differential pressure into a 4-20 mADC or 0-5 (0-10) VDC output signal linear to differential pressure, within the following minimum performance criteria:

Zeroing	Automatic, within 0.1 percent of operating span, on 4 to 256 minute intervals (selectable)
Spans	Factory custom spanned, coordinated with system, ranges from 0 to .01-inch to 0 to 10.0-inches. Field adjustment ± 20 percent of span.

Zeroing	Automatic, within 0.1 percent of operating span, on 4 to 256 minute intervals (selectable)
Accuracy	± 0.25 percent of span
DeadBand and Hysteresis (Combined):	Less than 0.2 percent of span
Linearity:	± 0.2 percent of span
Repeatability:	0.15 percent of span
Response:	0.5 second for 98 percent full span input
Power Supply:	24 VAC, 20 to 40 VDC, selectable; 4 wire

3. Coordinate requirements with the buildings direct digital control system to perform the required sequence of operation.
4. The pressure transmitter shall be the VELTRON series 5000AZ as manufactured by the Air Monitor Corporation, Paragon, Greenheck, Johnson Controls, or as approved equal.

2.22 AIR MONITORING STATIONS (FIELD INSTALLED AT INLET)

- A. Furnish outside air flow measuring station for field installation on outside air inlet. Outside air flow measuring station shall be as manufactured by Paragon or approved equal. The Model OAFE-1500 shall be an AMCA certified outdoor airflow measurement system with integral signal processor that is capable of producing an overall ±0.5% accuracy through the velocity range of 200 to 1,200 fpm and ±5% accuracy at 100 fpm. The air flow measurement station shall consist of multiple airflow elements, factory mounted and pre-piped in a casing designed for flanged connection to control dampers, louvers, etc... An optional inlet bell shall be available for plenum applications. Standard materials consist of a G90 galvanized casing and 6063-T5 anodized aluminum flow sensors. The airflow averaging elements shall be head type devices, which generate a differential (velocity) pressure signal similar to the orifice, venturi, and other head producing primary elements. The air flow measurement station shall be constructed so as to comply with ASHRAE Standard 111 for equal area traversing of an airflow measurement plane. Multiple elements shall be manifolded together for connection to the integral airflow signal processor. The signal processor shall utilize current state-of-the-art digital microprocessor technology capable of producing unequaled 20-bit (1,048,576 steps) A/D and 12 bit (4,096 steps) D/A signal conversion resolution. Having a twelve-point linearization capability, the signal processor shall be field calibrated to accurately determine true airflow rates even when the primary airflow measurement stations do not meet their minimum installation requirements. The ultra low operating ranges and the auto zeroing function of the signal processor shall provide accurate airflow measurement down to 100 fpm. The signal processor shall accept a temperature input signal for air temperature indication, temperature signal transmission for remote readout, and air density compensation for standard or actual airflow calculations. A password protected configuration menu shall provide quick and simple field configuration by authorized personnel. Field configuration of engineering units, process noise filtering, operating

range, alarm set points, etc... shall be performed via user friendly menus and a six button touch pad. An optional temperature transmitter with 4 to 20 mA output and temperature range of -30 to 130°F shall be provide a temperature input signal to the signal processor for air density compensation.

2.23 AIR MONITORING STATIONS

- A. General: Provide complete air monitoring station for air handling units and return air systems as indicated on drawings.. The air monitoring station shall include airflow measuring stations, static pressure probes and electronic velocity pressure transmitter. All components shall be of the same manufacturer. The manufacturer shall be Air Monitor, Gold Series Ebtron Thermistar, or as approved equal. An air monitor station shall be provided for each supply duct main and return duct main as indicated on contract drawings. All air flow monitoring stations shall be fully externally insulated to prevent condensation.
- B. Air Monitor Airflow Measuring Stations
1. Provide where indicated, airflow measuring stations capable of continuously monitoring the fan or duct capacities (air volumes) they serve.
 2. Each airflow measuring station shall contain multiple total and static pressure sensors positioned at the center of equal area of the station cross-section and interconnected by their respective averaging manifolds. For stations of 4 square feet or less, one total and one static pressure sensor shall be present for every 16 square inches of station area respectively. For stations of larger area, one total and one static pressure sensor shall be present for every 36 square inches of station area respectively.
 3. The airflow measuring station shall be fabricated of a minimum of 14 ga. galvanized steel welded casing in 8-inch depth with 90 degree connecting flanges in a configuration and size equal to that of the duct it is to be mounted into. Each station shall be complete with an open parallel cell air straightener or air equalizer honeycomb mechanically fastened to the casing, total and static pressure sensors located on an equal area basis and connected to symmetrical averaging manifolds, internal piping, and external pressure transmitter ports. An identification label shall be placed on each station casing listing model number, size, area, and specified airflow capacity.
 4. Cell construction shall be 3/8-inch .003-inch, type 3003 aluminum, expanded.
 5. The maximum allowable pressure loss through the station shall not exceed .015-inch wc at 1000 fpm, or .085-inch wc at 2000 fpm. Each station shall be capable of measuring the airflow rate within an accuracy of 2 percent as determined by U.S.G.S.A. certification tests. The stations shall have a self-generated sound rating of less than NC 40, and the sound level within the duct shall not be amplified, nor shall additional sound be generated.
 6. Stations shall be Fan-E type as manufactured by Air Monitor Corporation, Paragon or as approved equal.

C. Air Monitor Duct Static Pressure Traverse Probes

1. Provide where indicated duct static traverse probe capable of continuously monitoring the duct or system static pressure it serves.
2. Each duct static traverse probe shall contain multiple static pressure sensors located along the exterior surface of the cylindrical probe. Said sensors shall not protrude beyond the surface of the probe.
3. The duct static traverse probe shall be of extruded aluminum construction and (except for 3/4-inch diameter probes with lengths of 24-inches or less) be complete with threaded end support rod, sealing washer and nut and mounting plate with gasket and static pressure signal fitting.
4. The static traverse probe shall be capable of producing a steady, non-pulsating signal of standard static pressure, without need for correction factors, with an instrument accuracy of 0.5 percent.
5. The duct static pressure traverse probe shall be the STAT-probe/1 as manufactured by the Air Monitor Corporation, Paragon or as approved equal.

D. Air Monitor Electronic Velocity Pressure Transmitters

1. The electronic control-instrument components shall be of industrial process control quality with operating features described herein and capable of producing the outlined performances. Commercial grade control-instruments, devices, are not acceptable.
2. The electronic differential pressure transmitter shall include an automatic zeroing circuit capable of automatically readjusting the transmitter zero at predetermined (adjustable) time intervals while retaining (locking in) the output signal. The electronic differential pressure transmitter shall be capable of receiving signals of duct total and static pressures, and of amplifying and scaling the sensed differential pressure into a 4-20 mA DC or 0-5 (0-10) VDC output signal linear to differential pressure, within the following minimum performance criteria:

Zeroing	Automatic, within 0.1 percent of operating span, on 4 to 256 minute intervals (selectable)
Spans	Factory custom spanned, coordinated with system, ranges from 0 to .01-inch to 0 to 10.0-inches. Field adjustment ± 20 percent of span.
Accuracy	± 0.25 percent of span
DeadBand and Hysteresis (Combined):	Less than 0.2 percent of span
Linearity:	± 0.2 percent of span
Repeatability:	0.15 percent of span

Zeroing	Automatic, within 0.1 percent of operating span, on 4 to 256 minute intervals (selectable)
Response:	0.5 second for 98 percent full span input
Power Supply:	24 VAC, 20 to 40 VDC, selectable; 4 wire

3. Coordinate requirements with the buildings direct digital control system to perform the required sequence of operation.
4. The pressure transmitter shall be the VELTRON series 5000A, as manufactured by the Air Monitor Corporation, Paragon, Greenheck, or as approved equal.

2.24 WATER TREATMENT SERVICES

- A. Complete chemical water treatment service shall be provided by an organization regularly engaged in water treatment, ARC, Inc., RCCO Corp., Aquatel Ind., Inc., Mogul Corp., Oilin, Inc., HVAC Services, Inc., Feedwater Treatment Systems, Inc., Eco-Lab, or approved equal. The service shall provide all equipment, chemicals and labor necessary to prevent corrosion, inhibit scale build-up and minimize organic growth for a period of 2 years starting from building acceptance. Water Treatment shall be conducted for each phase prior to substantial completion of each phase. Service visits for the purpose of adding chemicals to feeding equipment, regulating bleed-off, inspecting and adjusting water treatment equipment, and obtaining samples for laboratory analysis shall be performed at monthly intervals for closed systems and every two weeks for open systems during the entire guarantee period. Chemicals shall not be injurious to water side equipment and construction materials. Records of all injurious to water side equipment and construction materials. Records of all service visits, chemical additions, laboratory tests, etc., shall be maintained and shall be provided to owner after each visit during guarantee period. Instruct mechanical contractor in field on piping and wiring of chemical feeding equipment.
- B. Systems to be protected shall include glycol systems, chilled water system, and hot water heating system. Services shall include flushing and cleaning of piping systems specified under Division 23 Section, "HVAC Piping, Fittings, and Valves" section, furnishing and installing all chemical treatment equipment and accessories to perform the water treatment specified below. Maintain complete records of the treatment program for each system.
- C. Contractor shall perform an analysis of the building water supply as a basis of the chemical treatment. Contractor shall provide the Owner with written instructions for chemical feeding bleed-off, blowdown control and testing procedures, provide all required chemicals during the guarantee period, and provide all required test kits.
- D. Contractor shall maintain the following conditions in each system:

SYSTEMS	Chiller Water System	Hot Water System
ph	8.0 to 10.5	7.0 to 10.0
Inhibitor for Scale & Corrosion Cycles	---	---
Cycles*	---	---
Organic	---	---
Buffered Nitrate	550 ppm	1000 ppm to 180 degrees F 2000 ppm to 180 degrees F
Chromate (Low)		
Molybdate	30 to 50 ppm	50 to 100 ppm
Sulfite	---	---
Sodium Nitrite	500 to 1000 PPM	1000 to 1500 PPM
Corrosion Inhibitor	100 to 150 PPM (as Molybdate) or 1000 to 1500 PPM sodium Nitrite	
*Actual cycles of concentration to be determined from analysis of make-up water.		
* Use Inhibited Glycol supplied by Manufacturer		

E. Chemical Feeding Equipment: Provide chemical feeding equipment, as specified below, to introduce chemicals into each system only when the system is operating.

1. Closed Recirculating Systems

Provide (5) gallon steel by-pass feeder installed across circulating pump suction and discharge lines, with tank and piping insulated using the same thickness and type of insulation as provided for the piping system. Provide filter. Unit shall contain quick opening cap and shall be suitable for working pressure of 175 psig. Tank shall be primed and finished in baked enamel paint.

2. Replace bypass feeder filter monthly during the entire 2-year warranty period.

F. Closed Recirculating Systems shall be filled and sufficient detergent and dispersant added to remove all dirt, oil, and grease. System shall be circulated for at least 48 hours after which a drain valve at the lowest point shall be opened and allowed to bleed while the system continues to circulate. The automatic make-up valve shall be checked to be sure it is operating. Bleeding shall continue until water runs clear and all detergent is removed. A sample of water shall be tested and if PH exceeds the PH of the make-up water, flushing shall be resumed.

2.25 DUCTLESS FAN COIL UNITS

A. General:

1. The supplied product shall be an Airedale, Aeremec, Carrier Airstream, Multiaqua, or approved equal, four (4) pipe chilled/hot water ceiling cassette unit.

B. Cases:

1. The unit casing shall be manufactured from lightweight galvanized sheet steel with integral fan mounting rails for added strength. Fire resistant foam insulation (to UL94 VO) shall be fitted internally to provide both thermal and acoustic insulation.

C. Coils:

1. Chilled water units utilize large surface area coils positioned to optimize heat transfer and airflow. Each coil shall be manufactured from refrigeration quality copper tubes with mechanically bonded aluminum fins and shall be circuited from headers to ensure low water pressure drops.

D. Condensate Pump:

1. A condensate pump and check valve shall be fitted to carry water out of the unit and stop water from flowing back into the condensate tray. The pump shall be fixed to a mounting bracket which can be withdrawn from the side of the chassis and shall incorporate an inspection hole to allow a visual check of the pump during operation. A float switch shall be fitted to stop the cooling action should the pump become blocked or fail.

E. Air Vanes:

1. Air outlet vanes shall be designed to prevent condensation from forming. Vanes shall be manually adjustable on the 2 x 2 model units but driven by an electric motor on all other model units. Where fitted, the motorized air vanes can be set to auto sweep or can be stopped in a fixed position. Polystyrene blanking pieces are supplied with Cassette packing so that up to two fascia discharge slots can be blanked off.

F. Fans & Fan Motor:

1. All units, utilizing backward curved centrifugal fans, are statically and dynamically balanced for quiet operation. Fan impellers are made from either aluminum or fire-retardant plastic (UL94 VO) for light weight and corrosion resist shall be operation. Fans are driven by an enclosed multi-speed external rotor motor allowing good heat dissipation and an increased motor efficiency. Fans shall come complete with thermal overload protection and sealed-for-life lubricated bearings.

G. Step Up Transformer:

1. The unit shall be fitted with an appropriate 115 volt to 230 volt step up

transformer.

H. Filter:

1. MERV 10, 2" thick radial pleated disposable cotton and synthetic blend filters. Minimum Efficiency Reporting Value of MERV 10 per ASHRAE standard 52.2.

I. Electro-Mechanical Controls:

1. The unit shall include an electro-mechanical controller that includes the resetting relays and safety switch for proper operation. The ATC contractor shall field install unit controls and control valves to fully control and monitor the units operation per the sequence of operations.

J. Options - Factory Installed:

1. Alarm Interlock Relay: The unit shall include a relay for unit failure notification. Normally open contact available for field connection.
2. Start / Stop Terminals: The unit shall include terminals for remote start/stop of the unit. The unit is enabled when contact between the terminals is closed.
3. Hot Water Coil: A hot water heating coil will be factory fitted in addition to the chilled water coil to provide heating. The coil shall be manufactured from refrigeration quality copper tubes with mechanically bonded aluminum fins.
4. Hot Water Coil Freeze Protection: The unit shall be fitted with a freeze protection sensor to prevent freezing of the hot water coil assembly. When the sensor detects a freeze up condition it will force the flow control valve open and prevent the unit fan(s) from running.
5. Disconnect Switch: The unit shall be fitted with a power disconnect switch located on the control panel, sized for the full load amperage of the unit to enable the unit to be disconnected from the power supply prior to any maintenance.

K. Accessories - Field Installed:

1. Fresh Air Kit: Duct collars for fastening to the unit to allow connection of 3" flexible duct to the Cassette. Includes Merv 8 filter set for replacing standard filter shipped with the Cassette unit.
2. Supply Air Duct Collars: Duct collars for fastening to the unit to allow connection of a 5" or 6" (depending on units size) flexible duct to the Cassette.
3. Shroud: A sheet metal shroud to cover the unit housing when the unit is not mounted in a drop ceiling. Painted Sky White with hammertone finish.

PART 3 EXECUTION

3.1 EXAMINATION

- A. Verify all dimensions by field measurements. Verify that all equipment may be installed in accordance with pertinent codes and regulations, the original design, and the referenced standards.
- B. Verify structure, mounting supports and membrane installations are completed to the proper point to allow installation of roof mounted equipment, where applicable.
- C. Examine rough-in requirements for all piping systems to verify actual locations of piping connections prior to installation.
- D. Verify that electrical work installation is in accordance with manufacturer's submittal and installation requirements of Division 26 sections. Do not proceed with equipment start-up until electrical work is acceptable to equipment installer. Coordinate sizes of all thermal overloads with Division 26.
- E. Do not proceed until unsatisfactory conditions have been corrected.
- F. Provide wiring diagrams of all equipment as specified in Division 23 Section, *Common Work Results for HVAC*.

3.2 GENERAL INSTALLATION REQUIREMENTS

- A. Install all equipment in accordance with manufacturer's installation instructions, in accordance with state and local code requirements, and in accordance with the contract drawings. Install all equipment plumb and level, to tolerances as required by the manufacturer of each item of equipment. Maintain manufacturer recommended clearances around and over all equipment. Water heater minimum clearances shall be provided per the State Requirements.
- B. Coordinate vibration isolation requirements with all equipment in accordance with Division 23 Section, *Vibration Controls for HVAC, Plumbing and Fire Protection Equipment*.
- C. Coordinate all electrical requirements with Division 26.
- D. Coordinate all indoor and outdoor equipment pad locations and sizes with approved shop drawing submittals. Provide operating weights of equipment to Structural Engineer for review. Coordinate equipment pad locations and sizes with the Concrete Contractor or General Contractor. Furnish anchor bolts which are to be inserted in concrete pads to concrete installer.
- E. Verify piping arrangements of all equipment with the contract drawings. Piping details shall be strictly adhered to concerning valves, fittings, components, etc. At coils, where a rebuildable and repairable autoflow valve is installed in the line without the need for draining or shutting of the water, the same may be utilized as the isolation valve and additional shut-off valve is not required.
- F. Connect all equipment, devices and components to wiring systems and to ground as indicated and instructed by manufacturer. Tighten connectors and terminals, including screws and bolts, according to equipment manufacturer's published torque-tightening

values for equipment connectors. Where manufacturer's torquing requirements are not indicated, tighten connectors and terminals according to tightening requirements specified in UL 486A.

- G. Testing: After installing HVAC equipment, devices and components and after electrical circuitry has been energized, demonstrate product capability and compliance with requirements.
- H. Remove and replace malfunctioning units with new units and retest.
- I. All mechanical penetrations or terminations in exterior walls shall be flashed and caulked watertight.
- J. Arrange for equipment such as air handling units, 100% outside air units, to be shipped to project in modules where space constraints require the same. Field erect components as required.

3.3 FIELD QUALITY CONTROL

- A. Where indicated provide the services of a factory authorized service representative to examine the field assembly of components, installation, piping, electrical connections, controls, and clearances. Submit factory start-up check list to Engineer for information purposes. Testing and balancing work shall not commence until start-up reports have been completed, reviewed by Engineer, and forwarded to Testing and Balancing Agency.
- B. Where factory start-up of equipment is not specified, provide field start-up by qualified technician to examine the field assembly of components, installation, piping, electrical connections, controls and clearances. Record equipment manufacturers standard start-up information and submit to Engineer for review. Testing and balancing work shall not commence until start-up reports have been completed, reviewed by Engineer, and forwarded to Testing and Balancing Agency.
- C. Charge all refrigerant systems with refrigerant and oil and test for leaks. Repair leaks and replace lost refrigerant and oil.
- D. Fill all hydronic systems with water and/or antifreeze (when required) after flushing and test for leaks. Repair leaks and replace lost water and/or antifreeze. Coordinate with water treatment contractor.
- E. Submit to Engineer a written table of all relief valve and make-up water valve settings for each system. Provide an additional copy in the Operations and Maintenance Manuals.
- F. Verify proper motor sizes, voltages, thermal overloads, nameplate data, etc. All equipment voltages and current shall be recorded to insure that motors are operating below their service factors. Test and Balance Engineer shall record electrical data before continuous or permanent operation.

3.4 DEMONSTRATION

- A. Provide the services of a factory authorized service representative to provide start-up and

to demonstrate and train the Owner's maintenance personnel.

- B. Place equipment into operation and adjust controls and safeties. Replace damaged or malfunctioning components and controls.
- C. Training:
 - 1. Train the Owner's maintenance personnel on start-up and shut-down procedures, trouble shooting procedures, lubrication, servicing procedures and preventative maintenance schedules/procedures. Review with the Owner's personnel, the contents of the operation and maintenance data specified in Division 23 Section, *Common Work Results for HVAC*.
 - 2. Submit operation and maintenance data as soon as possible prior to project close-out. Operations and maintenance data shall be submitted to the Owner for review and comment prior to submission to the Engineer.
 - 3. Schedule training with the Owner through the Architect and/or Engineer with at least seven (7) days prior notice.
- D. Contractor shall demonstrate removal and replacement of filters at all pieces of equipment with filters in the presence of the Owners representative.

3.5 CLEANING

- A. After completing installation inspect exposed finish. Remove burrs, dirt, and construction debris, and repair damaged finishes including chips, scratches, and abrasions.
- B. Clean fan and equipment interiors to remove foreign material and construction dirt and dust. Vacuum clean fan wheels, cabinets, and coils' entering air face.

3.6 AIR HANDLING UNIT INSTALLATION REQUIREMENTS

- A. Install in conformance with ARI 435. Install air handling units level and plumb, according to manufacturer's written instructions.
- B. Install AHU's with resilient mounting and flexible electrical leads.
- C. Install flexible connections as hereinafter specified at all duct connections.
- D. Comb out fins on AHU coils where deformed or bent. Replace or repair broken fins.
- E. Install coils level. Install cleanable tube coils with 1:50 pitch.
- F. Make connections to coils with unions and flanges.
- G. Provide air tight seals between coils and duct or casings. Gasket all access panels, door openings and inspection windows. Seal all joints between sections.
- H. Insulate all headers outside air flow as specified for piping.

- I. Arrange installation of units to provide access space around air handling units for service and maintenance.
- J. Adjust damper linkages for proper damper operation.
- K. Install air tight seals at all air handling penetration points, including pipe penetrations at the coils, unused maintenance - only drain openings, and any penetrations for electrical wiring.

3.7 CHILLER INSTALLATION REQUIREMENTS

- A. Align chiller package on steel or concrete foundations as indicated.
- B. Arrange chiller piping for easy dismantling to permit tube cleaning.
- C. Supply initial charge of refrigerant and oil as required.
- D. Comb out fins on air cooled chillers where deformed or bent. Replace or repair broken fins.
- E. Install chillers according to manufacturer's written instructions.
- F. Install chillers plumb and level, and anchor. Anchor housekeeping pads to building floor. Anchor chiller and vibration isolators to housekeeping pad.
- G. Install vibration isolators according to isolator manufacturer's written instructions.
- H. Maintain manufacturer's recommended clearances for service and maintenance.
- I. Install piping connections maintaining clearances for service and maintenance of chillers.
- J. Manufacturer's Field Service: Provide services of a factory-authorized service representative to supervise field assembly of components and installation of chillers, including piping and electrical connections, and to report results in writing.
 - 1. Test and adjust controls and safeties. Replace damaged and malfunctioning controls and equipment.
- K. Touch up scratches in unfinished surfaces to restore corrosion resistance.
- L. Touch up scratches in finished surfaces to restore finish.
- M. Provide services of a factory trained service technician to start chiller and train Owner on the chiller operation.
- N. Interlock chiller with automatic temperature control system. Coordinate requirements with automatic temperature control contactor.
- O. Install, wire, and interlock fluid flow switch. Interface with automatic temperature

control system.

- P. Install flexible connectors, valves, fittings, thermostats, gauges, balance valves, etc... as indicated on flow diagram.
- Q. Test flow switch.
- R. Install manufactured supplied strainer in the chilled water return line.
- S. Install vent and drain piping adjacent to evaporator per manufacturer's requirements.

3.8 DUCTLESS UNITS EQUIPMENT INSTALLATION REQUIREMENTS

- A. Mount indoor and outdoor units as detailed on contract drawings.
- B. Supply initial charge of refrigerant and oil as required.
- C. Install all interlock and control wiring between indoor units, outdoor units, thermostats, and condensate pumps.
- D. Install indoor ceiling cassette on vibration isolators.
- E. Install outdoor units on concrete pads or on roof curbs as indicated on drawings.
- F. Comb out fins on condensing unit where deformed or bent. Replace or repair broken fins.
- G. Install condensate lift pumps, float switches, alarm, unit shut down wiring and detection block units per manufacturer's recommendations.
- H. For wall mounted units, locate condensate pumps above ceiling. Install all piping, tubing between indoor unit, adapter, detection block, and condensate pump.
- I. For wall mounted units field wire power wiring, alarm circuits, control cable, safety circuit connection, alarm, and condensate pump. Condensate pump shall be powered from indoor unit power wiring. Coordinate condensate pump electrical characteristics with indoor unit electrical characteristics.
- J. Install wind baffles when required for low ambient operation. Locate wind baffles facing the predominant wind direction in winter.

3.9 ELECTRIC HEATING EQUIPMENT INSTALLATION REQUIREMENTS

- A. Examine heating units for compliance with requirements for installation tolerances and other conditions affecting performance of units. Do not proceed with installation until unsatisfactory conditions have been corrected.
- B. Install electric finned-tube radiation units level and plumb, according to manufacturer's written instructions, rough-in drawings, the original design, and referenced standards.
 - 1. Use methods and accessories to accommodate thermal expansion.
 - 2. Install cabinet continuously around corners, using manufacturer's outside and

- inside corner fittings.
 3. Use manufacturer's standard wall trim.
 4. Install manufacturer's access fitting for access to valves and other fittings.
 5. Install air-seal gasketing between wall and enclosure mounting channel.
 6. Terminate unit enclosures with manufacturer's end caps.
 7. Install pedestals and securely attach to floor.
- C. Connect heating units and components to wiring systems and to ground as indicated and instructed by manufacturer. Tighten connectors and terminals, including screws and bolts, according to equipment manufacturer's published torque-tightening values for equipment connectors. Where manufacturer's torquing requirements are not indicated, tighten connectors and terminals according to tightening requirements specified in UL 486A.
- D. After completing system installation, including outlet fittings and devices, inspect exposed finish. Remove burrs, dirt, and construction debris; repair damaged finishes, including chips, scratches, and abrasions.
- E. Install and mount electric radiant heat panels from building structure as required to accommodate ceiling type. Field furnish all accessories necessary to mount radiant heat panels.
- 3.10 FAN INSTALLATION REQUIREMENTS.
- A. Install fans with resilient mounting and flexible electrical leads.
 - B. Install flexible connections and vibration isolators as specified in Division 23 Section, *Common Work Results for HVAC* and Division 23 Section *Vibration Controls for HVAC, Plumbing and Fire Protection Equipment*. Ensure metal band of connectors are parallel with minimum one inch flex between ductwork and fan while running.
 - C. Provide safety screen/guards on all fans and permanently mount after final testing and balancing.
 - D. Where indicated install and pipe grease collectors with valve, union, and discharge to closest floor drain.
 - E. Do not operate fans for any purpose until ductwork is clean, filters in place, bearings lubricated, and fans have been test run under operation.
 - F. Provide sheave required for final air balance.
 - G. Install fans according to manufacturer's written instructions.
 - H. Adjust damper linkages for proper damper operation.
 - I. Adjust belt tension.
 - J. Lubricate bearings.

- K. Replace fan and motor pulleys and belts as required to achieve design conditions.
- L. Where specified, mount, install, and wire speed controllers for direct drive fans. Speed controllers for direct drive fans shall be mounted adjacent to fan and wired in accordance with the NEC.

3.11 HVAC PUMP INSTALLATION REQUIREMENTS

- A. Provide access space around pumps for service. Provide no less than minimum as recommended by manufacturer.
- B. Decrease from line size with long radius reducing elbows or reducer. Support piping adjacent to pump such that no weight is carried on pump casings. For close coupled or base mounted pumps, provide supports under elbows on pump suction and discharge line sizes 4 inches (102 mm) and over.
- C. Provide air cock and drain connection on horizontal pump casings.
- D. Provide drains for bases and seals, piped to and discharging into floor drains.
- E. Check, align, and certify alignment of base mounted pumps prior to start-up. Prior to starting pumps, the alignment of the pumps and their motors or other drivers shall be carefully checked. Alignment should be checked for both offset and angularity. Alignment by means of an Ames dial, Laser or equivalent shall be accomplished for all pumps. Alignment by straight edge across the pump couplings shall not be acceptable.
- F. Install close coupled and base mounted pumps on concrete housekeeping pads, with anchor bolts, set and level, and grout in place. See Division 23 Section, *Vibration Controls for HVAC, Plumbing and Fire Protection Equipment* for inertia pad requirements. After alignment is correct, tighten foundation bolts evenly but not too firmly, completely fill baseplate with non shrink, non metallic grout while metal blocks and shims or wedges are in place. After grout has cured, fully tighten foundation bolts.
- G. Lubricate pumps before start-up.
- H. Provide side-stream filtration system for base mounted pumps. Install across pump with flow from pump discharge to pump suction from pump tapings. Install flow indicator, filter housing with cartridge filter, shut-off valves, and flow control valves. Install 30 micron filter for start-up and 5 micron filter for system operation.
- I. Install pumps according to manufacturer's written instructions.
 - 1. Install pumps according to HI 1.1-1.5, *Centrifugal Pumps for Nomenclature, Definitions, Application and Operation*.
- J. Install pumps to provide access for periodic maintenance, including removing motors, impellers, couplings, and accessories.
- K. Suspend in-line pumps using continuous-thread hanger rod and vibration-isolation hangers.

- L. Set base-mounted pumps on concrete foundation. Disconnect coupling halves before setting. Do not reconnect couplings until alignment operations have been completed.
 - 1. Support pump baseplate on rectangular metal blocks and shims, or on metal wedges with small taper, at points near foundation bolts to provide a gap of 3/4 to 1-1/2 inches between pump base and foundation for grouting.
 - 2. Adjust metal supports or wedges until pump and driver shafts are level. Check coupling faces and suction and discharge flanges of pump to verify that they are level and plumb.

3.12 HYDRONIC EQUIPMENT AND SPECIALITIES INSTALLATION REQUIREMENTS

- A. Where large air quantities can accumulate, provide enlarged air collection standpipes.
- B. Provide manual air vents at system high points and as indicated.
- C. For automatic air vents provide vent tubing to nearest drain.
- D. Provide air separator on suction side of system circulation pump and connect to expansion tank.
- E. Provide valved drain and hose connection on strainer blow down connection.
- F. Provide pump suction fitting on suction side of base mounted centrifugal pumps. Remove temporary strainers after cleaning systems.
- G. Support pump fittings with floor mounted pipe and flange supports.
- H. Select system relief valve capacity so that it is greater than make-up pressure reducing valve capacity. Select equipment relief valve capacity to exceed rating of connected equipment and in accordance with ASME requirements.
- I. Pipe all relief valve outlets to nearest floor drain.
- J. Where one line vents several relief valves, make cross sectional area equal to sum of individual vent areas.
- K. Perform test determining strength of antifreeze and water solution and submit written test results.
- L. Install equipment exposed to finished area after walls and ceiling are finished and painted. Avoid damage.
- M. Protection: Provide finished cabinet units with protective covers during balance of construction.
- N. Unit heaters: hang from building structure, with pipe hangers anchored to building, not from piping. Mount as high as possible to maintain greatest headroom unless otherwise indicated.

- O. Cabinet Unit Heaters: Install as indicated. Coordinate to assure correct recess size for recessed units.
- P. Install finned-tube radiation units level and plumb, according to manufacturer's written instructions, rough-in drawings, the original design, and referenced standards.
 - 1. Use methods and accessories to accommodate thermal expansion.
 - 2. Install cabinet continuously around corners, using manufacturer's outside and inside corner fittings.
 - 3. Use manufacturer's standard wall trim.
 - 4. Install manufacturer's access fitting for access to valves and other fittings.
 - 5. Install air-seal gasketing between wall and enclosure mounting channel.
 - 6. Terminate unit enclosures with manufacturer's end caps.
- Q. Testing: After installing and connecting units, demonstrate product capability and compliance with requirements.
- R. Remove and replace malfunctioning units with new units and retest.

3.13 INCREMENTAL EQUIPMENT INSTALLATION REQUIREMENTS

- A. Coordinate installation of all incremental units (unit ventilators, fan coil units, PTACs., etc.) with architectural and electrical work.
- B. Fan-coil Units: Install as indicated. Coordinate to assure correct recess size for recessed units.
- C. Units with Cooling Coils: connect drain pan to condensate drain
- D. Coordinate cover openings for all thru-the-wall units with architectural work. Coordinate installation of wall sleeves in finished wall assembly; seal and weather proof.
- F. Vacuum out all units and replace filters prior to turning over the same to the owner.
- F. Electrical: Connect units to wiring systems and to ground as indicated and instructed by manufacturer.
- G. Ground equipment
 - 1. Tighten electrical connectors and terminals according to manufacturer's published torque-tightening values. Where manufacturer's torque values are not indicated, use those specified in UL 486A and UL 486B.
- H. After completing system installation, including outlet fittings and devices, inspect exposed finish. Remove burrs, dirt, and construction debris, and repair damaged finishes including chips, scratches, and abrasions.

- I. Lubricate bearings on fan.
- J. Check fan-wheel rotation for correct direction without vibration and binding.
- K. Start unit according to manufacturer's written instructions.
 - 1. Complete manufacturer's startup checks.
- L. After starting and performance test, change filters.
- M. Prior to installing all fan coil units provide mock-up for 1 unit. Installation shall be reviewed by Owner's Mechanical Inspector and Engineer of Record. Provide three (3) days notice.

3.14 KITCHEN VENTILATION EQUIPMENT INSTALLATION REQUIREMENTS

- A. Install all kitchen ventilation equipment in accordance with NFPA-96, NFPA-90A, NFPA-90B, and the requirements of the local Health Department.
- B. Install gas fired units in accordance with NFPA-54/NFPA-58 where applicable .
- C. Provide flexible duct connectors on outlet from makeup air unit.
- D. Rooftop units shall be installed on curbs and shall be leveled.
- E. Indoor units shall be installed on housekeeping pads and shall be leveled.
- F. The installer of the kitchen hood equipment shall submit a certification of installation to the Delaware Office of State Fire Marshal.
- G. Provide factory start-up and training. Submit start-up reports to Engineer.
- H. Interlock air flow monitoring station with ATC system.
- I. Interlock make-up air unit with kitchen hood exhaust fan hood suppression system and gas solenoid valve.
- J. Verify and record minimum and maximum air flow rates for the supply and exhaust air fan.
- K. Verify and record the minimum and maximum supply/exhaust fan speeds/ hertz and incorporate into the fan tracking sequence of operation.
- L. Verify and record temperature rise across all coils.
- M. For gas fired equipment verify and record gas pressure at burner manifold.

3.15 WATER TREATMENT INSTALLATION REQUIREMENTS

- A. Systems shall be operational, filled, started, and vented prior to cleaning. Use water meter to record capacity in each system.
- B. Place terminal control valves in open position during cleaning. Open bypass valves on coils and close isolation valves on coils during initial flushing.
- C. Verify that electric power is available and of the correct characteristics.
- D. Use neutralizer agents on recommendation of system cleaner supplier and approval of Architect.
- E. Flush open systems and closed systems with clean water for one hour minimum. Drain completely and refill.
- F. Remove, clean, and replace strainer screens.
- G. Inspect, remove sludge, and flush low points with clean water after cleaning process is completed. Include disassembly of components as required.
- H. Test and submit antifreeze concentration where the same is utilized.

3.16 SPLIT SYSTEM EQUIPMENT INSTALLATION REQUIREMENTS

- A. Mount indoor and outdoor units as detailed on contract drawings. Install units level and plumb.
- B. Supply initial charge of refrigerant and oil as required.
- C. Install all interlock and control wiring between indoor units, outdoor units and thermostats.
- D. Install all indoor and outdoor units on vibration isolators.
- E. Install outdoor units on concrete pads as hereinbefore specified or on roof curb as indicated on drawings.
- F. Install refrigerant suction, liquid, and hot gas bypass lines between indoor and outdoor units per manufacturers instructions. Connect precharged refrigerant tubing to components quick connect fittings. Install tubing to allow access to unit.
- G. Size all refrigerant piping per manufacturers instructions.
- H. Connect drain lines to condensate pans.
- I. Provide auxiliary drain pans on all horizontal units. Pipe drain to closest floor drain or as indicated on drawings.
- J. Comb out evaporator coil and condensing unit fins.

3.17 FILTRATION EQUIPMENT INSTALLATION REQUIREMENTS

- A. Duct mounted filter housings shall be supported independent of adjacent ductwork. Hang filter housings using galvanized steel rods.
- B. Where filter housing are not factory insulated, externally insulate to prevent surface condensation.
- C. Install static pressure gauges, tubing, vents, etc., across all filter banks.
- D. Transition ductwork to filter housings as indicated on drawings.
- E. Where indicated, field test all filters in an installed condition.
- F. Install air cleaning devices in accordance with manufacturers instructions.
- G. Prevent passage of unfiltered air around filters with felt, rubber, or neoprene gaskets.
- H. Do not operate fan system until filters are in place. Replace temporary filters used during construction and testing, with clean set.
- I. Position each filter unit with clearance for normal service and maintenance. Anchor filter holding frames to substrate.
- J. Coordinate filter installations with duct and air handling unit installations.
- K. After completing system installation and testing, adjusting, and balancing air handling and air distribution systems, clean filter housings and install new filter media.

3.18 GAS FIRED MAKE-UP AIR UNIT INSTALLATION REQUIREMENTS

- A. Examine areas to receive energy recovery units, make-up air unit, and H & V unit for compliance with requirements for installation tolerances and other conditions affecting performance of energy recovery units. Do not proceed with installation until unsatisfactory conditions have been corrected.
- B. Install units as indicated, according to manufacturer's written instructions.
- C. Install heat wheels so supply and exhaust flow in opposite directions and rotation is from exhaust side to purge section to supply side.
 - 1. Provide access doors in both supply and exhaust ducts, both upstream and downstream, for access to wheel surfaces, drive motor, and seals.
 - 2. Provide removable panels or access doors between supply and exhaust ducts on building side for bypass during startup.
- D. Install and interlock outside air flow monitoring station.
- E. Install new filters at completion of equipment installation and before testing, adjusting, and balancing.

- F. Ducts and fan installation requirements are specified in other Division 23 Sections. Drawings indicate the general arrangement of piping, fittings, and specialties.
- G. Ground Equipment
1. Tighten electrical connectors and terminals according to manufacturer's published torque-tightening values. Where manufacturer's torque values are not indicated, use those specified in UL 486A and UL 486B.
- H. After completing system installation, including outlet fittings and devices, inspect and clean exposed finishes. Remove dirt and construction debris and repair damaged finishes.
- I. Test all gas fired equipment.
- J. Startup Services: Engage a factory-authorized service representative to commission units as specified below.
1. Energize and verify correct rotation of heat wheels and fans.
 2. Adjust seals and purge.
 3. Test and adjust controls and safeties. Replace damaged or malfunctioning controls and equipment.
 4. Test refrigerant circuit and controls.
 5. Record refrigerant pressures.
 6. Verify sequence of operation.
- K. Training
1. Train Owner's maintenance personnel on procedures and schedules related to startup and shutdown, troubleshooting, servicing, and preventative maintenance.
 2. Review data in the operation and maintenance manuals. Refer to Division 01 Section, *Demonstration and Training*.
 3. Schedule training with Owner, through Architect, with at least 7 days advance notice.
- L. Where specified field install and interlock air flow monitoring stations

END OF SECTION

SECTION 23 07 01

HVAC INSULATION

PART 1. GENERAL

1.1. REFERENCE

- A. The Conditions of the Contract and other General Requirements apply to the work specified in this Section. All work under this Section shall be subject to the requirements of Division 23 Section, *Common Work Results for HVAC*.
- B. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2. DESCRIPTION

- A. All piping, ductwork, and equipment installed under this Contract shall be covered as specified.

1.3. SCOPE

- A. The work covered by this specification consists of furnishing all labor, equipment, materials and accessories, and performing all operations required, for the correct fabrication and installation of thermal insulation applied to all piping, equipment, and duct systems, in accordance with applicable project specifications and drawings, subject to the terms and conditions of the contract.

1.4. STANDARDS

- A. Thermal insulation materials shall meet the property requirements of one or more of the following specifications as applicable to the specific product or use:
 - 1. American Society for Testing of Materials Specifications:
 - a). ASTM C 547, "Standard Specification for Mineral Fiber Preformed Pipe Insulation".
 - b). ASTM C 533, "Standard Specification for Calcium Silicate Pipe & Block Insulation".
 - c). ASTM C 55, "Standard Specification for Mineral Fiber Blanket and Felt Insulation".
 - d). ASTM E 96, "Standard Test Methods for Water Vapor Transmission of Material".
 - e). ASTM C 585, "Recommended Practice for Inner and Outer Diameters of Rigid Pipe Insulation for Nominal Sizes of Pipe and Tubing (NPS System)".

- f). ASTM C 612, "Standard Specification for Mineral Fiber Block and Board Thermal Insulation".
 - g). ASTM C 1136, "Standard Specification for Barrier Material, Vapor, "Type 1 or 2 (Jacket only).
2. ASHRAE 90.1 "Energy efficient design of new buildings except low-rise residential buildings", latest edition.
 3. International Energy Conservation Code, latest edition.
- B. Insulation materials, including all weather and vapor barrier materials, closures, hangers, supports, fitting covers, and other accessories, shall be furnished and installed in strict accordance with project drawings, plans, and specifications.

1.5. SYSTEM PERFORMANCE

- A. Insulation materials furnished and installed hereunder should meet the minimum economic insulation thickness requirements of the North American Insulation Manufacturers' Association (NAIMA) (formerly known as TMAA), to ensure cost-effective energy conservation performance. Alternatively, materials should meet the minimum thickness requirements of National Voluntary Consensus Standard 90.1, (latest edition) and "Energy Efficient Design of New Buildings," of the American Society of Heating, Refrigeration, and Air-Conditioning Engineers (ASHRAE), latest edition. However, if other factors such as condensation control or personnel protection are to be considered, the selection of the thickness of insulation should satisfy the controlling factor. As minimum, all insulation thicknesses shall be as hereinafter specified.
- B. Insulation materials furnished and installed hereunder shall meet the fire hazard requirements of any one of the following specifications:
1. American Society for Testing of Materials ASTM E 84
 2. Underwriters' Laboratories, Inc. UL 723
 3. National Fire Protection Association NFPA 255
 4. ASTM E 96, "Standard Test Methods for Water Vapor Transmission of Materials".
- C. Calcium silicate products shall include a visual identification system to permit positive field determination of their asbestos-free characteristics.

1.6. QUALITY ASSURANCE

- A. Insulation materials and accessories furnished and installed hereunder shall, where required, be accompanied by manufacturers' current submittal or data sheets showing compliance with applicable specifications listed in Section 1.4 above.

- B. Insulation materials and accessories shall be installed in a workmanlike manner by skilled and experienced workers who are regularly engaged in commercial insulation work.

1.7. DELIVERY AND STORAGE OF MATERIALS

- A. All of the insulation materials and accessories covered by this specification shall be delivered to the job site and stored in a safe, dry place with appropriate labels and/or other product identification.
- B. The Contractor shall use whatever means are necessary to protect the insulation materials and accessories before, during, and after installation. No insulation material shall be installed that has become damaged in any way. The Contractor shall also use all means necessary to protect work and materials installed by other trades.
- C. If any insulation material has become wet because of transit or job site exposure to moisture or water, the Contractor shall not install such material, and shall remove it from the job site. An exception may be allowed in cases where the Contractor is able to demonstrate that wet insulation when fully dried out (either before installation or afterward following exposure to system operating temperatures) will provide installed performance that is equivalent in all respects to new, completely dry insulation. In such cases, consult the insulation manufacturer in writing for technical assistance.
- D. Maintain ambient temperatures and conditions required by manufacturers of adhesives, mastics, and insulation cements. Protect all insulation from water, construction traffic, dirt, chemical and mechanical damage.

1.8. ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

PART 2. PRODUCTS

2.1. GENERAL

- A. All materials to be insulated shall be thoroughly cleaned, after completion of successful tests, and shall be covered as specified below. Fiberglass insulation shall be Owens-Corning, Manville, Armstrong, or P.P.G, or as approved equal.

2.2. PIPE INSULATION MATERIALS

- A. Unless otherwise noted, insulation shall be one piece or half sectional molded fibrous glass with "K" rating of .23 at 75 degrees Fahrenheit mean temperature, for service temperatures between -60 degrees Fahrenheit and +450 degrees Fahrenheit with all service poly-encapsulated jacket. Pipe insulation shall be fiberglass ASJMax SSL II with double closure system as manufactured by Owens Corning, Johns Manville, Knauf or approved equal.
- B. Exterior refrigerant pipe insulation shall be Armacell, or approved equal, foam insulation with exterior field applied aluminum jacketing. Interior refrigerant piping shall be Armacell

or approved equal foam insulation. Where interior refrigerant piping is exposed also install field applied PVC jacketing.

- C. Unless otherwise noted, pipe insulation jacket shall be factory-applied vinyl coated, embossed and reinforced vapor barrier laminate, with a perm rating of not more than 0.02 perms. All hot and cold, concealed and exposed butt strips shall be of the same material as the jacket. Jacket and butt strips shall be sealed with field-applied Foster 85-20/85-60 Childers CP-82 (5 gal cans only) adhesive. Jacket and butt strips shall be off-white color and shall be equivalent to Owens-Corning Fiberglass 25-ASJ.
- D. Indoor chilled water pipe insulation shall be ASJ Max with SSL-II closure system pipe insulation as manufactured by Owens Corning or approved equal. Pipe insulation shall be composed of heavy density fiberglass insulation with an organic binder. The insulation shall include a white, factory jacketed, resilient, tough, soil resistant polymer facing that matches standard PVC fitting covers. Furnish all accessories and matching butt joints sealing tape for system closure. Insulation shall be suitable for operating temperatures between 32 degrees Fahrenheit and 220 degrees Fahrenheit. Flame spread rating of 25 or less, and smoke development rating of 50 or less to comply with building code for installation in return air plenums. The maximum thermal conductivity (K-value) at a mean temperature of 50 shall be .22 BTU-in/hr-Ft²-degrees Fahrenheit.
- E. Exterior and exposed interior chilled water located in a finished space requiring jacketing and/or painting shall be standard non-wicking pipe insulation as here-in-before specified with specified covering. Indoor exposed interior chilled water piping located in non-finished spaces such as mechanical room, boilers, air handling rooms, attic, penthouses, etc., shall be ASJ Max with SSL-II closure system pipe insulation as manufactured by Owens Corning or approved equal.
- F. For fittings on all piping, valves and flanges, apply fiberglass molded or segmented insulation equal in thickness to the adjoining insulation and securely fasten in place using wire. Cold piping: Apply a tack coat of vapor barrier coating and reinforcing mesh. After ½ hour, apply second coat of same vapor barrier coating, UL labeled, Type C, for cold water piping, Hot piping Type H for hot water piping: Apply tack of breather mastic. Wrap fitting with fiberglass reinforcing cloth overlapping adjoining sections of pipe insulation by 2-inches. Apply a second coat of breather mastic over the reinforcing cloth, working it to a smooth finish.
1. Vapor Barrier Coating: Foster 30-65; Childers CP-34 or Vimasco 749. Permeance shall be 0.03 perms or less at 45 mils dry as test by ASTM E96.
 2. Breather mastic: Foster 46-50; Childers CP-10/11 or Vimasco WC-5
 3. Reinforcing Mesh: Foster Mast a Fab; Childers Chil Glas #10 or Vimasco Elastafab
- G. All pipe insulation, jackets, or facings, and adhesives used to adhere jacket or facing to the insulation, including fittings and butt strips, shall have non-combustible fire and smoke hazard system rating and label as tested by ASTM E-84, NFPA 225, and UL 73, not exceeding Flame Spread 25, Fuel Contributed 50, Smoke Developed 50. Accessories such as adhesives, mastic cements, tapes and cloth for fittings shall have the same ratings as listed above. All products or their shipping cartons shall bear the Underwriter's label indicating that flame and smoke ratings do not exceed the above criteria.

- H. For piping having a vapor barrier insulation and for all insulated piping requiring supports, hangers and supports shall be installed outside the insulation. Wherever hangers and supports are installed outside the insulation, pipe insulation protecting shields shall be provided. Where insulation is a load bearing material, of sufficient strength to support the weight of the piping, pipe shields one-third the circumference of the insulation and of a length not less than three times the diameter of the insulation (maximum length 24-inches) shall be provided. Insulation of 7-1/4 pound or greater density will be considered as load bearing for pipe sizes up to and including 2-inches. Where insulation is not of sufficient strength to support the weight of the piping, a half section of high density fiberglass or foam inserts, shall be provided. Vapor barrier and finish shall be applied as required to match adjoining insulation. In addition, shields shall be furnished as specified above.
- I. For piping located outside of the building, a corrugated aluminum weatherproof jacketing system shall be provided. This system shall be Micro-Lot ML as manufactured by Manville, Polyweld by Pabco Metals Corp., Childers, or as approved equal, and installed per the manufacturer's recommendations. Where outdoor piping is receiving electric heat tape, the insulation shall be oversized so that the heat tape is not compressed tightly to the pipe. Pipe jacketing shall be corrugated (3/16-inch) deep aluminum, .016-inch thickness of H-14 temper with aluminum strapping of .75-inch width and .020-inch thickness with moisture barrier. Aluminum jacketing elbows shall be smooth, .036-inch thickness and 1100 alloy. All jacketing shall have an integrally bonded moisture barrier over the entire surface in contact with the insulation. Longitudinal joints shall be applied so they will shed water and shall be sealed completely with metal jacketing sealant. Sealant shall be Foster 95-44 or Childers CP-76. Circumferential joints shall be closed using preformed butt strips following manufacturer's recommendations for securement. Jacket seams shall be located on the bottom side of the horizontal piping.
- J. All disturbed piping insulation in existing areas shall be re-insulated with insulation type, density, and thickness as specified for new piping. Insulation damaged due to new work and demolition only shall be replaced unless otherwise noted.
- K. On cold systems such as refrigerant piping chilled water piping, cooling coil drain piping, and glycol piping, vapor barrier performance is extremely important. All penetrations and seams of the ASJ and exposed ends of insulation must be sealed with vapor barrier coating. The ASJ must be protected with either a coating or a suitable vapor retarding outer jacket. Vapor seals at butt joints shall be applied at every fourth pipe section joint and at each fitting to provide isolation of water incursion. Vapor Barrier Coating: Foster 30-65; Childers CP-74 or Vimasco 749. Permeance shall be 0.03 perms or less at 45 mils dry as test by ASTM E96.
- L. Fittings and valves shall be insulated with pre-formed fiberglass fittings, fabricated sections of fiberglass pipe insulation, Fiberglass pipe and tank insulation, Fiberglass blanket insulation, or insulating cement. Thickness shall be equal to adjacent pipe insulation. Finish shall be with pre-formed PVC fitting covers or as otherwise specified on contract drawings. Where applicable, Victaulic PVC fitting valve and coupling covers shall be utilized. Victaulic PVC covers shall be installed with matching pipe insulation jacketing material, vinyl tape solvent weld adhesive and appropriate fasteners.
1. Flanges, couplings and valve bonnets shall be covered with an oversized pipe insulation section sized to provide the same insulation thickness as on the main pipe

section. An oversized insulation section shall be used to form a collar between the two insulation sections with low density blanket insulation being used to fill gaps. Jacketing shall match that used on straight pipe sections. Rough cut ends shall be coated with a suitable weather or vapor-resistant mastic as dictated by the system location and service. Finish valve installation with a Tyvac jacket with ends that secure to adjacent piping.

2. On hot systems where fittings are to be left exposed, insulation ends should be beveled away from bolts for easy access.
 3. On cold systems, particular care must be given to vapor sealing the fitting cover or finish to the pipe insulation vapor barrier. All valve stems must be sealed with caulking which allows free movement of the stem but provides a seal against moisture incursion. All gauge and thermometer penetrations and extensions shall be correctly sealed and insulated to prevent surface condensation. Install oversized hangers to prevent penetrations of pipe insulation vapor barrier.
- M. All piping shall be supported in such a manner that neither the insulation or the vapor/weather barrier is compromised by the hanger or the effects of the hanger. In all cases, hanger spacing must be such that the circumferential joint may be made outside the hanger. On cold systems, vapor barrier must be continuous, including material covered by the hanger saddle.
1. Piping systems 3-inches (7.5cm) in diameter or less, insulated with Fiberglass insulation, may be supported by placing saddles of the proper length and spacing, as designated in Owens-Corning Pub. 1-IN-12534, under the insulation. Hangers saddles shall be minimum #6 gauge with a saddle arc of 120 degrees minimum.
 2. For hot or cold piping systems larger than 3-inches (7.5 cm) in diameter, operating at temperatures less than +200 degrees F (93 degrees C) and insulated with fiber glass, high density inserts such as foam or wood blocks with sufficient compressive strength shall be used to support the weight of the piping system. At temperatures exceeding +200 degrees F (93 degrees C), Owens-Corning Pink Calcium Silicate, IIG or approved equal pipe insulation shall be used for high density inserts.
 3. Owens-Corning Pink Calcium Silicate pipe insulation may be used to support the entire weight of the piping system provided the hanger saddle is designed so the maximum compressive load does not exceed 100 psi (7kg/cm).
 4. Where pipe shoes and roller supports are required, insulation shall be inserted in the pipe shoe to minimize pipe heat loss. Where possible, the pipe shoe shall be sized to be flush with the outer pipe insulation diameter.
 5. Thermal expansion and contraction of the piping and insulation system shall generally be taken care of by utilizing double layers of insulation and staggering both longitudinal and circumferential joints. Where long runs are encountered, expansion joints may be required where single layers of insulation are being used and should be so noted on the contract drawings.
 6. On vertical runs, insulation support rings shall be used.

2.3. PIPING INSULATION THICKNESSES SCHEDULE

A. All piping shall be insulated with pipe insulation of the thicknesses indicated below:

PIPING INSULATION THICKNESS SCHEDULE SERVICES	THICKNESS
Chilled Water Piping 2 ½-inches & Larger	2-inch thickness
Chilled Water Piping 2-inches & Smaller	2-inch thickness
All Branch Runouts to Unit Heaters/Fin Tube/Convectors	½-inch thickness
Heating Hot Water Piping 2-inches & Larger	2-inch thickness
Heating Hot Water Piping 1-½ -inches & Smaller	1 ½ -inch thickness
All Drain Piping from Cooling Coils/Evaporators	1-inch thickness
Chemical Feed System	1-inch thickness
All Refrigerant Piping	1-inch thickness
Piping within Fan Coil Unit Enclosures	½-inch thickness

2.4. EQUIPMENT INSULATION MATERIALS AND THICKNESSES

A. The following equipment shall be insulated with Fiberglass Rigid Board Insulation or Foam Plastic Insulation:

1. Chilled Water Pump and Hot Water Pump Bodies.
2. Air Separators.
3. Expansion Tanks.
4. Chiller Heads.
5. Chemical Feed Tanks.
6. Freeze Protection Pump Bodies.
7. All Pump Volutes and Strainers.

B. Insulation for cold surfaces shall be 1-1/2-inch thickness, 6 lb. density, 705 FRK with a "K" rating of .23 at 75 degrees F mean temperature. Insulation for hot surfaces except as otherwise noted shall be 1-1/2-inch thickness, 6 lb. density, 705 with a "K" rating of .23 at 75 degrees F mean temperature. Insulation shall be applied with staggered joints firmly butted and joined. The insulation shall be held in place by steel bands. Bands shall be 1-

inch by 25 gauge galvanized steel spaced on not over 12-inch centers. All joints and voids shall be filled with Owens-Corning #110 cement, well troweled into openings. For 705 FRK insulation, all joints and voids shall be FRK taped and vapor sealed. There shall be applied over the insulation surface 1-inch galvanized wire netting laced together at all edges and wired to the steel bands with 16 gauge soft annealed wire. Over this shall be applied 2-inch thick layer of Owens-Corning #110 cement applied in two layers. Install metal corner beads at all corners and edges in order to provide a permanent installation. Onto the dry cement surface apply a brush coat of Foster Sealfas 30-36 or Childers CP-50AMV1 lagging adhesive at the rate of 60-70 square feet per gallon. Embed into wet coating a layer of 8 ounce canvas or fiberglass lattice mesh smoothed out to avoid wrinkles and lap all seams a minimum of 2-inches. Apply a second brush coat of Sealfas 30-36 or Childers CP-50AMV1 lagging adhesive to the entire surface at the rate of 60-70 square feet per gallon. Cleanouts, nameplates, and manholes shall not be insulated, and the insulation on surrounding surfaces shall be neatly beveled off at such openings.

C. Insulation Installation on Pumps:

1. Fabricate metal boxes lined with insulation. Fit boxes around pumps and coincide box joints with splits in pump casings. Fabricate joints with outward bolted flanges. Bolt flanges on 6-inch (150-mm) centers, starting at corners. Install 3/8-inch- (10-mm-) diameter fasteners with wing nuts. Alternatively, secure the box sections together using a latching mechanism.
2. Fabricate boxes from aluminum at least 0.040 inch (1.0 mm) thick.
3. For below ambient services, install a vapor barrier at seams, joints, and penetrations. Seal between flanges with replaceable gasket material to form a vapor barrier.

D. Boards shall be scored to allow them to conform to curved or irregular surfaces.

E. Mechanical fasteners shall be utilized to hold insulation to surface with bands as required to hold the curvature of the material.

F. Support rings shall be provided to support the top head insulation where required.

G. Outdoor installations require a weather barrier for protection of the insulation jacketing.

H. Insulation types materials shall be suitable for temperatures encountered by each item of equipment.

2.5. DUCTWORK INSULATION MATERIALS AND THICKNESSES

- A. Insulate all supply, return, relief, combustion air, discharge, and outside air intake ductwork with fiberglass exterior duct insulation with factory-applied foil facing. All exposed fiberglass duct insulation shall be 2-inch rigid or non-flexible board type 3.0 pcf minimum density, 0.23 max. "K" factor at 75 degrees F mean temperature, with white vinyl A.S.J. max, polymer coating vapor barrier facing. All concealed fiberglass duct insulation shall be 2-inch flexible blanket type, 1.0 pcf minimum density. All concealed insulation shall be 0.27 max. "K" factor at 75 degrees F mean temperature with reinforced foil-scrim Kraft vapor barrier facing. Unless otherwise noted, the minimum installed R-value shall be 6.0 HR x ft² x °F/btu.

- B. Refer to Division 23 Section, *HVAC Air Distribution System* and contract drawings for location of all sound-lined ductwork. Sound-lined ductwork from the discharge or supply side of all air handling units, make-up air units, and rooftop units, shall require external insulation in addition to internal lining specified hereinafter. All other ducts indicated to be provided with interior lining shall not require additional exterior insulation.
- C. Where a vapor barrier is required, all joints, seams, tears, punctures, and other penetrations shall be closed with 3-inch (7.5cm) pressure-sensitive tape matching the facing or with vapor barrier coating reinforced with 3-inch (7.5cm) glass scrim tape.
- D. Contractor-applied internal linings shall be as specified and installed as hereinafter specified.
- E. For exposed Fiberglass duct insulation, tightly butt all edges and seams. Secure insulation with flush mechanical fasteners spaced not less than one per square foot. Insulation may be secured with 100 percent coverage of adhesive with mechanical fasteners on the underside of the duct only, in addition to adhesive. Adhesive shall be water-based Foster 85-60 or Childers CP-127. Cover all seams, joints and fasteners with not less than 3-inch wide tape matching the insulation facing. Pre-finished white fastener caps may be left exposed if the spacing and pattern is uniform in appearance. Staples will not be permitted.
- F. All disturbed ductwork insulation in existing areas shall be re-insulated with insulation type and thickness as specified for new ductwork. Duct insulation damaged due to installation of new work and demolition only shall be replaced.
- G. All supply air diffusers and supply air registers shall be fully insulated on the rear exposed surface to prevent condensation. Insulation shall be 1 1/2" inch flexible blanket type 1 1/2 pcf minimum density with reinforced foil-scrim-Kraft vapor barrier facing, .25 max "k" factor.
- H. All airflow monitoring stations shall be externally insulated similar to adjacent ductwork as hereinbefore specified.
- I. Existing ductwork that is indicated to be re-used shall be cleared, degreased, sealed, and insulated as specified for new ductwork.

2.6. ACCESSORY MATERIALS

- A. Accessory materials installed as part of insulation work under this section shall include, but not be limited to:
 - 1. Closure Materials - Butt strips, bands, wires, staples, mastics, adhesives; pressure-sensitive tapes.
 - 2. Field-applied jacketing materials - sheet metal, plastic, canvas, fiber glass cloth, insulating cement; PVC fitting covers, PVC jacketing.
 - 3. Support Materials - Hanger straps, hanger rods, saddles.
 - 4. Fasteners, weld pins/studs, speed clips, insulation washers.
 - 5. Metal mesh or expanded metal lagging.

- B. All accessory materials shall be installed in accordance with project drawings and specifications, manufacturer's instructions, and/or in conformance with the current edition of the Midwest Insulation Contractors Association (MICA) "Commercial & Industrial Insulation Standards."

2.7. GREASE DUCT ENCLOSURE WRAP

- A. Provide listed grease duct enclosure wrap on all kitchen hood exhaust ducts. Duct wrap shall comply with ASTM E 2336-01 "Standard Test Method" for Fire Resistant Grease Duct Enclosure System. Duct wrap shall be Fire Master as manufactured by Thermal Ceramics, Fyrewrap as manufactured by Unifrax, and Fire Barrier as manufactured by 3M, Schebbler, or approved equal.
- B. Duct wrap shall be foil-encapsulated, non-combustible, inorganic, flexible fire proofing wrap. Duct wrap shall be utilized in combination with Fire Master or approved equal, Putty and Fire Master or approved equal, bulk fiber to fire rate kitchen hood exhaust ducts. Duct wrap shall be capable of withstanding 2300 degrees F temperatures and protect combustible construction at zero clearance.
- C. Two (2) layers of duct wrap shall be applied directly to the duct to provide a two (2) hour fire resistance enclosure for both vertical and horizontal duct runs. Apply putty and bulk fiber in conjunction with duct wrap at all duct penetrations of fire rated walls and ceilings. Insulate all duct access doors per U.L. listing and label per N.F.P.A.-96.
- D. Furnish and install all material per manufacturer's installation requirements and per U.L. listing. Install support hangers, duct access door enclosures, and through penetration systems in accordance with N.F.P.A.-96, A.S.T.M. listing, and manufacturer's installation requirements.
- E. Insulate all access doors and pitot tube openings. Install signs indicating either "access door" or "pitot tube".

2.8. FIELD-APPLIED JACKET

- A. Field-applied jackets shall comply with ASTM C 921, Type I, unless otherwise indicated.
- B. PVC Jacket: High-impact-resistant, UV-resistant PVC complying with ASTM D 1784, Class 16354-C; thickness as scheduled; roll stock ready for shop or field cutting and forming. Thickness is indicated in field-applied jacket schedules.
 - 1. Products: Subject to compliance with requirements, available products that may be incorporated into the Work include, but are not limited to, the following:
 - a). Johns Manville; Zeston.
 - b). P.I.C. Plastics, Inc.; FG Series.
 - c). Proto PVC Corporation; LoSmoke.
 - d). Speedline Corporation; SmokeSafe.
 - 2. Adhesive: As recommended by jacket material manufacturer.

3. Color: High gloss white.
4. Factory-fabricated fitting covers to match jacket if available; otherwise, field fabricate.
 - a). Shapes: 45- and 90-degree, short- and long-radius elbows, tees, valves, flanges, unions, reducers, end caps, soil-pipe hubs, traps, mechanical joints, and P-trap and supply covers for lavatories.
5. Factory-fabricated tank heads and tank side panels.

2.9. HANGER BLOCKS

- A. For all pipes larger than 3 inches in diameter the hanger blocks shall be high compressive strength foam or wood blocks. Wood blocks shall be precision cut thickness to match specified insulation and shall include flared edge hanger saddle as manufactured by Buckaroo.
- B. The wood blocks shall be suitable for temperatures from -120 degrees Fahrenheit to 200 degrees Fahrenheit. Do not utilize the wood blocks for piping systems operating outside of the indicated temperature range.
- C. Wood blocks are not acceptable for use at refrigerant pipe hangers.

PART 3. EXECUTION

3.1. WORKMANSHIP

- A. The Contractor shall take special care to prevent soiling equipment below or adjacent to areas being insulated. He shall be completely responsible for removing insulation cement splashes and smears and all surfaces that he mars or otherwise soils or defaces, and he will be totally responsible for restoring these damaged surfaces to their like-new condition when delivered to the site.

3.2. SITE INSPECTION

- A. Before starting work under this section, carefully inspect the site and installed work of other trades and verify that such work is complete to the point where installation of materials and accessories under this section can begin.
- B. Verify that all materials and accessories can be installed in accordance with project drawings and specifications and material manufacturers' recommendations.
- C. Verify, by inspecting product labeling, submittal data, and/or certifications which may accompany the shipments, that all materials and accessories to be installed on the project comply with applicable specifications and standards and meet specified thermal and physical properties.

3.3. PREPARATION

- A. Ensure that all pipe and equipment surfaces over which insulation is to be installed are clean and dry.
- B. Ensure that insulation is clean, dry, and in good mechanical condition with all factory-applied vapor or weather barriers intact and undamaged. Wet, dirty, or damaged insulation shall not be acceptable for installation.
- C. Ensure that pressure testing of piping or duct systems has been completed prior to installing insulation.

3.4. INSTALLATION

A. Piping Systems

1. General:

- a). Install all insulation materials and accessories in accordance with manufacturer's published instructions and recognized industry practices to ensure that it will serve its intended purpose.
- b). Install insulation on piping subsequent to installation of heat tracing, painting, testing, and acceptance tests.
- c). Install insulation materials with smooth and even surfaces. Insulate each continuous run of piping with full-length units of insulation, with single cut piece to complete run. Do not use cut pieces or scraps abutting each other. Butt insulation joints firmly to ensure complete, tight fit over all piping surfaces.
- d). Maintain the integrity of factory-applied vapor barrier jacketing on all pipe insulation, protecting it against puncture, tear or other damage. Seal all tears, punctures and other penetrations of the pipe insulation vapor barrier coating.
- e). On exposed piping, locate insulation and cover seams in least visible location.

2. Fittings: Cover valves, fittings, unions, flanges, strainers, flexible connections, expansion joints, pump bodies, strainers, blowdowns, backflow preventers, autoflow valves and similar items in each piping system using one of the following:

- a). Mitered sections of insulation equivalent in thickness and composition to that installed on straight pipe runs.
- b). Cold pipe fittings: Apply a tack coat of vapor barrier coating and reinforcing mesh to produce a smooth surface. After ½ hour, apply a second coat of same vapor barrier coating, UL labeled, Type C, for cold water piping.

- c). Hot pipe fittings and Type H for hot water piping: Apply tack of breather mastic. Wrap fitting with fiberglass reinforcing cloth overlapping adjoining sections of pipe insulation by 2-inches. Apply a second coat of Type C or Type H breather mastic over the reinforcing cloth, working it to a smooth finish.
 - d). Insulation cement equal in thickness to the adjoining insulation.
 - e). PVC fitting covers insulated with material equal in thickness and composition to adjoining insulation.
3. Penetrations: Extend piping insulation without interruption through walls, floors, and similar piping penetrations, except where otherwise specified.
 4. Joints:
 - a). Butt pipe insulation against hanger inserts. For hot pipes, apply 3-inch (7.5cm) wide vapor barrier tape or band over butt joints. For cold piping, apply wet coat of vapor barrier lap cement on butt joints, and seal joints with 3-inch (7.5cm) wide vapor barrier tape or band.
 - b). All pipe insulation ends shall be tapered and sealed, regardless of service.
 5. For heat traced piping, insulate fittings, joints, and valves with insulation of like material, thickness and finish as adjoining pipe. Size insulation large enough to enclose pipe and heat trace. Cover with aluminum jacket with seams located on bottom side of horizontal piping.
 6. Exterior above ground chilled water piping shall not be insulated with vapor wick insulation. Fiberglass insulation with aluminum jacketing shall be utilized for exterior above ground applications. Seal all aluminum jacketing laps with 1/8" bead of metal jacketing sealant to prevent water entry.
 7. All existing floor drain piping that is indicated to receive A/C condensate shall be fully insulated to prevent condensation.

B. Equipment Insulation:

1. General:

- a). Install insulation in accordance with manufacturer's published instructions and recognized industry practices to ensure that it will serve its intended purpose.
- b). Install insulation on equipment after installation of heat tracing, painting, testing, and acceptance tests.
- c). Install insulation materials with smooth, even surfaces. Rework poorly fitted joints. Do not use joint sealer or mastic as filler for joint gaps and excessive voids resulting from poor workmanship. Apply insulation using

staggered joint method for both single and double layer installation, applying each layer of insulation separately.

- d). Coat insulated surfaces where specified on contract drawings with layer of insulating cement, troweled in a workmanlike manner, leaving a smooth and continuous surface. Fill in seams, broken edges, and depressions. Cover over wire mesh and joints with cement sufficiently thick to remove surface irregularities.
 - e). Maintain the integrity of factory-applied vapor barrier jacketing on all insulation, protecting it against puncture, tears or other damage. Seal all tears, punctures and other penetrations of equipment insulation facing.
 - f). Where specification calls for field-applied at-service vapor barrier jacketing, it shall be neatly fitted and tightly secured. Lap seams 2-inches (5cm) (min.). Seal all joints with adhesive. Tape with 3-inches (7.5cm) matching pressure-sensitive tape or 3-inch (7.5cm) glass fabric and vapor barrier coating.
 - g). On exposed equipment, locate insulation and cover seams in least visible location.
2. Removable Insulation: Provide removable insulation sections to cover parts of equipment which must be opened periodically for maintenance, such as vessel covers, fasteners, flanges, flange accessories, manholes, handholes, cleanouts ASME stamp, and manufacturer nameplates.
 3. Areas Left Uninsulated: Items such as boiler manholes, handholes, clean-outs, ASME stamp, and manufacturers' nameplates should be left uninsulated unless omitting insulation would cause a condensation problem. When such is the case, provide removable insulation and appropriate tagging to identify the presence of these items. Provide neatly beveled edges at interruptions of insulation.
 4. Equipment Exposed to Weather: Protect outdoor insulation from weather by installation of weather barrier mastic protective finish or jacketing as recommended by the jacketing manufacturer.

C. Ductwork Insulation:

1. General:
 - a). Before installing insulation, ensure that all seams and joints in ductwork have been sealed and leak tested by the contractor responsible for the duct system. Before applying duct insulation, air ducts shall be clean and dry.
 - b). Install insulation in accordance with manufacturer's published instructions and recognized industry practice to ensure that it will serve its intended purpose.

- c). Install insulation materials with smooth and even surfaces. Butt joints firmly together to ensure complete and tight fit over surfaces to be covered.
- d). Maintain the integrity of factory-applied vapor barrier jacketing on all insulation, protecting it against puncture, tears or other damage. All staples used on ductwork insulation shall be coated with suitable sealant to maintain vapor barrier integrity and covered with pressure sensitive vapor barrier tape and vapor barrier coating as specified.
- e). Insulate entire system including fittings, joints, flanges, fire dampers, flexible connections, and exposed joints. All portions of duct designated to receive duct wrap shall be completely covered with duct wrap.
- f). To ensure installed thermal performance, duct wrap insulation shall be cut to "stretch-out" dimensions. Maintain specified duct insulation thickness and vapor barrier at all fittings, obstructions, and duct flanges.
- g). A 2-inch (50mm) piece of insulation shall be removed from the facing at the end of the piece of duct wrap to form an overlapping stapling and taping flap.
- h). Install duct wrap insulation with facing outside so that the tape flap overlaps the insulation and facing at the other end of the piece of duct wrap. Adjacent sections of duct wrap insulation shall be tightly butted with the 2-inch (50mm) stapling and taping flap overlapping. If ducts are rectangular or square, install so insulation is not excessively compressed at corners. Seams shall be stapled approximately 6-inches (150mm) on center with 2-inch (50mm) (min) steel outward clinching staples.
- i). Seams, joints and staples shall be sealed with pressure-sensitive tape matching the insulation facing (either plain foil or FRK backing stock) and glass fabric and vapor barrier coating. Cloth duct tape of any color or finish using reclaimed rubber adhesives shall not be utilized on duct wrap insulation. Adjacent sections of duct wrap shall be tightly butted with the 2-inch (50mm) tape flap overlapping.
- j). Where rectangular ducts are 24-inch (600mm) in width or greater, duct wrap insulation shall be additionally secured to the bottom of the duct with mechanical fasteners such as pins and speed clip washers, spaced on 18-inch (425mm) centers (maximum) to prevent sagging of insulation.
- k). Seal all tears, punctures and other penetrations of the duct wrap facing using one of the above methods to provide a vapor tight system.
- l). Upon completion of installation of duct wrap and before operation is to commence, visually inspect the system and verify that it has been correctly installed.

- m). Open all system dampers and turn on fans to blow all scraps and other loose pieces of material out of the duct system. Allow for a means for removal of such material.
- n). Check the duct system to ensure that there are no air leaks through joints.
- o). No ductwork insulation shall be supported utilizing tie wire or bailing wire. Penetrations of ductwork insulation vapor barrier are prohibited.
- p). Bevel and terminate insulation at access doors. Paint edge with vapor barrier mastic.
- q). Install insulation board between volume dampers and sheet metal standoffs.
- r). Provide removable insulation section at all pitot tube traverse points. Insulation section shall contain tether that attaches to adjacent ductwork.
2. Penetrations: Extend ductwork insulation without interruption through walls, floors and similar ductwork penetrations, except where otherwise specified.
3. Ductwork Exposed to Weather: Protect outdoor insulation from weather by installing outdoor weather barrier mastic or jacketing as recommended by the insulation manufacturer.
4. Rigid Insulation:
- a). Rigid duct insulation may be impaled over welded pins and secured with insulation caps and washers matching the color of the vapor barrier facing. All seams shall be firmly butted and sealed with pressure-sensitive vapor barrier tape matching the facing and vapor barrier coating.
- b). Corner angles shall be installed on all external corners of rigid duct insulation in exposed finished areas before jacketing, except oven and hood exhaust duct insulation, which shall have no corner angles.
5. Duct Wrap Insulation: Duct wrap insulation shall be applied with all joints butted firmly together. All joints in the insulation covering shall be sealed with adhesive. Duct wrap insulation shall be secured to bottom of rectangular or oval ducts over 24 inches (60cm) wide with mechanical fasteners on 16-inch (40 cm) (approx.) centers to prevent sagging.
6. Duct Lining Insulation: Duct liner insulation shall be applied with all joints tightly butted using 90 percent coverage of adhesive meeting the requirements of ASTM C 916 plus mechanical fasteners spaced according to the liner manufacturer's schedule for the interior width of the plenum, housing, or air shaft. (Also refer to Division 23 Section, *HVAC Air Distribution System*.)

3.5. FIELD QUALITY ASSURANCE

- A. Upon completion of all insulation work covered by this specification, visually inspect the work and verify that it has been correctly installed. This may be done while work is in progress, to assure compliance with requirements herein to cover and protect insulation materials during installation.

3.6. PROTECTION

- A. Replace damaged insulation which cannot be satisfactorily repaired, including insulation with vapor barrier damage and moisture-saturated insulation.
- B. The insulation contractor shall advise the general and/or the mechanical contractor as to requirements for protection of the insulation work during the remainder of the construction period, to avoid damage and deterioration of the finished insulation.

3.7. SAFETY PRECAUTIONS

- A. Insulation contractor's employees shall be properly protected during installation of all insulation. Protection shall include proper attire when handling and applying insulation materials, and shall include (but not be limited to) disposable dust respirators, gloves, hard hats, and eye protection.
- B. The insulation contractor shall conduct all job site operations in compliance with applicable provisions of the Occupational Safety and Health Act, as well as with all state and/or local safety and health codes and regulations that may apply to the work.

3.8. INSULATION COVERING

- A. Unless otherwise noted, all exposed duct and equipment insulation shall have a field applied PVC jacket cover neatly cut and pasted over ductwork and equipment insulation. PVC shall be high gloss white and shall be 20 mils thick.
- B. Unless otherwise noted, all exposed pipe insulation required to be insulated shall be jacketed with a PVC Jacketing with fitting covers. PVC jacket shall be color fade resistant, white high gloss, U.S.D.A. authorized as manufactured by Proto Corporation or approved equal. PVC jacketing shall be high impact, ultraviolet resistant PVC. Minimum thickness shall be 20 mils, roll stock ready for shop or field cutting and forming.
- C. Exposed areas include, but are not limited to, all mechanical equipment rooms/fan rooms, mezzanines, penthouses, boiler rooms, kitchens, electric rooms, piping and ductwork exposed in an occupied space.
- D. Where PVC jackets are indicated, install with 1 inch overlap at longitudinal seams and end joints, for horizontal applications, install with longitudinal seams along top and bottom of tanks and vessels. Seal with manufacturers recommended adhesive.
 - 1. Apply two continuous beads of adhesive to seams and joints, one bead under lap and the finish bead along seam and joint edge.

- E. Exterior exposed pipe insulation required to be insulated shall be jacketed with a corrugated aluminum jacketing system as previously described. Seal all laps with 1/8" bead metal jacketing sealant.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 23 09 00

INSTRUMENTATION AND CONTROLS OF HVAC AND PLUMBING SYSTEMS

PART 1. GENERAL

1.1. SUMMARY

- A. For General Mechanical Requirements, see Division 23 Section, *Common Work Results for HVAC*, and Division 01 Sections.
- B. Comply with all code requirements and fire safety requirements as specified in Division 23 Section, *Common Work Results for HVAC*.
- C. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.
- D. This Section includes control equipment for HVAC systems and components, including control components for terminal heating and cooling units not supplied with factory wired controls.
- E. The automatic temperature control system ATC and central control and monitoring system (CCMS) shall be electric/electronic direct digital control (DDC), Alerton, Johnson Controls (Metasys), Johnson Controls FV as installed by Modern Controls, Honeywell, Siemens, Automated Logic Corporation, Reliable Controls, Schneider Electric, Advanced Power, Trane, and TAC Controls by Schneider Electric installed by Automation and Control Concepts or Niagara Control Technologies shall be an acceptable installer of the ATC system. All work associated with the automatic temperature control system shall be performed by personnel regularly and directly employed by the Automatic Temperature Controls Contractor. Control System shall be web based, allowing the client access via a standard web browser.
- F. Coordinate controls with controlled equipment. Upon completion of the work, calibrate and adjust all controls for proper function. Electric wiring, including interlock wiring for equipment such as air handlers, fans, switches, pumps, variable refrigerant volume systems, gas fired equipment, make-up air units, 100% outside air units, unit heaters, condensing units, etc., shall be furnished and installed under this section. All electrical work shall conform to the applicable requirements of Division 26.
- G. All automatic temperature control dampers, valves and separable wells for immersion elements furnished by the Control Manufacturer shall be installed by the Mechanical Contractor or his sheet metal subcontractor under the Control Manufacturer's supervision.
- H. Reference is hereby made for this contractor to become familiar with Division 26 of these specifications. Familiarization is for coordination purposes only. The control contractor shall provide all necessary relays, contacts, interlock wiring etc. not provided under Division 26 for the automation of the ATC and CCMS systems as required by the sequence of operation and input/output schedule. The control contractor shall coordinate all requirements with the building Fire Alarm System. The control contractor shall provide all additional devices and interlock wiring required for the automation of the ATC system and monitoring of the CCMS system.

- I. Furnish all labor, materials, software, equipment and services necessary for and incidental to furnishing and installing a complete direct digital control, automatic temperature control system to meet the requirements of the sequence of operation described on the Drawings.
- J. Unless the necessary items are specified to be provided with mechanical equipment by Division 23, the ATC contractor shall coordinate with Division 23, Mechanical, and shall furnish and install all items necessary to meet the requirements of the Sequence of Operation and the Central Control and Monitoring System (CCMS) indicated on the drawings and as required in this specification.
- K. The control system shall include all necessary and specified control equipment properly installed in accordance with the specifications and drawings and shall include, but not be limited to the automatic temperature control and energy management system of the following:
1. Air Handling Units
 2. Airflow Monitoring Stations
 3. Building Facilities
 4. Building Demand and Energy Consumption
 5. Carbon Dioxide Sensors
 6. Chilled Water Systems
 7. Condensing Units
 8. Dish Machine Exhaust Fan
 9. Domestic Hot Water Systems
 10. Domestic Water Consumption
 11. Duct Heating Coils
 12. Ductless Units
 13. Duct Detector Fan Interlocks
 14. Electric Radiant Heat Panels
 15. Fan Coil Units
 16. Flow Measuring Stations
 17. Flow Switches
 18. General Exhaust Systems
 19. Glycol Feed Systems
 20. Heating System
 21. High Temperature Alarms
 22. Hot Gas Re-heat Coils
 23. Kitchen Ventilation System
 24. Make-up Water Systems Interlocks and Alarms
 25. Make-up Air Units
 26. Mechanical Room Heat and Ventilation Control
 27. Miscellaneous interlocks required for gas systems, ventilation systems, etc.
 28. Plumbing Systems
 29. Pumps
 30. Radiant Heat Panels
 31. Static Pressure Controllers
 32. Unit Heater Control
 33. Variable Speed Drives

34. Ventilation Systems
35. 100% Outside Air Units
36. Variable Refrigerant Volume Systems

- L. All labor, material, equipment and software to meet the functional intent of the system, as specified herein and as shown on the drawings, shall be included. Drawings are diagrammatic only. Equipment and labor not specifically referred to herein or on the plans, that are required to meet the functional intent, shall be provided without additional cost to the owner.
- M. Where equipment is specified to be provided by equipment manufacturer or where packaged controls are specified map out all points provided by the manufacturer so the same can be viewed by ATC system. As a minimum all points indicated in the point list and control diagram must be viewable and adjustable from the ATC system. Coordinate with equipment manufacturer.

1.2. DEFINITIONS

- A. DDC: Direct digital control.
- B. I/O: Input/output.
- C. LonWorks: A control network technology platform for designing and implementing interoperable control devices and networks.
- D. MS/TP: Master slave/token passing.
- E. PC: Personal computer.
- F. PID: Proportional plus integral plus derivative.
- G. RTD: Resistance temperature detector.
- H. UPS: Uninterruptible Power Supply.
- I. NAE: Network Automated Engine.

1.3. SYSTEM PERFORMANCE

- A. Comply with the following performance requirements:
1. Graphic Refresh: Update graphic with minimum 20 dynamic points with current data within 8 seconds.
 2. Object Command: Reaction time of less than two seconds between operator command of a binary object and device reaction.
 3. Object Scan: Transmit change of state and change of analog values to control units or workstation within six seconds.
 4. Alarm Response Time: Annunciate alarm at workstation within 45 seconds. Multiple workstations must receive alarms within five seconds of each other.
 5. Program Execution Frequency: Run capability of applications as often as five seconds, but selected consistent with mechanical process under control.

6. Performance: Programmable controllers shall execute DDC PID control loops, and scan and update process values and outputs at least once per second.
7. Reporting Accuracy and Stability of Control: Report values and maintain measured variables within tolerances as follows:
 - a). Water Temperature: Plus or minus 1 deg F (0.5 deg C).
 - b). Water Flow: Plus or minus 5 percent of full scale.
 - c). Water Pressure: Plus or minus 2 percent of full scale.
 - d). Space Temperature: Plus or minus 1 deg F (0.5 deg C).
 - e). Ducted Air Temperature: Plus or minus 1 deg F (0.5 deg C).
 - f). Outside Air Temperature: Plus or minus 2 deg F (1.0 deg C).
 - g). Dew Point Temperature: Plus or minus 3 deg F (1.5 deg C).
 - h). Temperature Differential: Plus or minus 0.25 deg F (0.15 deg C).
 - i). Relative Humidity: Plus or minus 5 percent.
 - j). Airflow (Pressurized Spaces): Plus or minus 3 percent of full scale.
 - k). Airflow (Measuring Stations): Plus or minus 5 percent of full scale.
 - l). Airflow (Terminal): Plus or minus 10 percent of full scale.
 - m). Air Pressure (Space): Plus or minus 0.01-inch w.g. (2.5 Pa).
 - n). Air Pressure (Ducts): Plus or minus 0.1-inch w.g. (25 Pa).
 - o). Carbon Dioxide: Plus or minus 50 ppm.
 - p). Electrical: Plus or minus 5 percent of reading.

1.4. DELIVERY, STORAGE, AND HANDLING

- A. Factory-Mounted Components: Where control devices specified in this Section are indicated to be factory mounted on equipment, arrange for shipping of control devices to equipment manufacturer.
- B. System Software: Update to latest version of software at Project completion.

1.5. COORDINATION

- A. Coordinate location of thermostats, humidistats, and other exposed control sensors with plans and room details before installation.
- B. Coordinate equipment with Division 28 Section, "*Fire Alarm System*" to achieve compatibility with equipment that interfaces with that system.
- C. Coordinate supply of conditioned electrical branch circuits for control units and operator workstation.
- D. Coordinate equipment with Division 26 Section, *Panelboards* to achieve compatibility with starter coils and annunciation devices.
- E. Coordinate equipment with Division 26 Section, *Motor-Controllers* to achieve compatibility with motor starters and annunciation devices.

1.6. WORK BY OTHERS

- A. Automatic temperature control valves, air flow stations, pipe taps, flow meters, and separable wells for immersion elements furnished by the control manufacturer shall be

installed by the mechanical contractor under the control manufacturer's supervision. The control contractor shall deliver to the mechanical contractor valves and wells for installation within the various systems.

- B. All automatic dampers furnished by the control manufacturer shall be installed by the mechanical contractor under the control manufacturer's supervision.

1.7. QUALITY ASSURANCE

- A. The automatic temperature control (ATC) system and the central control and monitoring system (CCMS) shall be as manufactured by Johnson Controls, Honeywell, Siebe, Siemens, Alerton, Automated Logic Corporation, Reliable Controls, Schneider Electric, Advanced Power, Trane, shall be an acceptable installer of the ATC system.
- B. Supplier shall have an in-place support facility with technical staff, spare parts inventory and all necessary test and diagnostic equipment. The fully staffed and equipped office shall be within a 60 mile radius of the job site.
- C. The systems shall be complete in all respects, and shall be installed by skilled personnel. The Control Contractor shall have a successful history in the installation and maintenance of automatic temperature control systems similar in size and performance to that specified herein.
- D. All electrical wiring in connection with the Automatic Temperature Control System shall be furnished and installed by the ATC Contractor. This shall include all interlock wiring between the air handling units, fan pumps, heating systems, boilers, chillers, dampers, ductless units, condensing units, static pressure controllers, and variable refrigerant volume systems, gas fired units, etc.
- E. Bids by wholesalers, contractors or franchised dealers or any other firm whose principal business is not that of manufacturing or installing automatic temperature control systems, shall not be acceptable. Bid documents that are not complete in their response to these documents or take exception to any of the capabilities defined within these documents shall not be acceptable.
- F. Installer Qualifications: Automatic control system manufacturer's authorized representative who is trained and approved for installation of system components required for this Project.
- G. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.
- H. Comply with ASHRAE 135 for DDC system components.

1.8. GUARANTEE AND INSTRUCTION

- A. The control system including all components, system software, parts and assemblies herein specified shall be free from defects in workmanship and materials under normal use and service. After completion of the installation, the Control Manufacturer shall regulate and adjust all thermostats, control valves, control motors, and other equipment

provided under this contract. If within two (2) years from the date of acceptance by Owner any of the equipment herein described is proved to be defective in workmanship or materials, it will be replaced or repaired at no additional cost to the Owner. The Control Manufacturer shall, after completion, provide any service incidental to the proper performance of the Control System under guarantees outlined above for a period of two (2) years. Normal maintenance of the system is not to be considered part of the guarantee. All corrective modifications made during warranty service periods shall be updated on all user documentation including "as-built" shop drawings and on user and manufacturer archived software disks.

- B. The control contractor shall completely check out, calibrate and test all connected hardware to insure that the system performs in accordance with the approved specifications and sequences of operation submitted.
- C. Upon completion of the work, the control drawings encased in heavy plastic shall be provided where directed. Layout shall show all control equipment and the function of each item indicated.
- D. The temperature control contractor's office shall be within a 100 mile radius of the job site.
- E. The contractor shall respond to the job site with qualified technicians within a 4 hour period for any emergency relating to the control system or energy management systems.
- F. This agreement shall include emergency service during normal working hours.

1.9. SUBMITTALS

- A. Product Data: Include manufacturer's technical literature for each control device. Indicate dimensions, capacities, performance characteristics, electrical characteristics, finishes for materials, and installation and startup instructions for each type of product indicated.
 1. DDC System Hardware: Bill of materials of equipment indicating quantity, manufacturer, and model number. Include technical data for operator workstation equipment, interface equipment, control units, transducers/transmitters, sensors, actuators, valves, relays/switches, control panels, and operator interface equipment.
 2. Control System Software: Include technical data for operating system software, operator interface, color graphics, and other third-party applications.
 3. Controlled Systems: Instrumentation list with element name, type of device, manufacturer, model number, and product data. Include written description of sequence of operation including schematic diagram.
- B. Shop Drawings: Detail equipment assemblies and indicate dimensions, weights, loads, required clearances, method of field assembly, components, and location and size of each field connection.

1. Bill of materials of equipment indicating quantity, manufacturer, and model number.
 2. Schematic flow diagrams showing equipment, fans, pumps, coils, dampers, valves, and control devices.
 3. Wiring Diagrams: Power, signal, and control wiring.
 4. Details of control panel faces, including controls, instruments, and labeling.
 5. Written description of sequence of operation.
 6. Schedule of dampers including size, leakage, and flow characteristic.
 7. Schedule of valves including flow characteristics.
 8. DDC System Hardware:
 - a). Wiring diagrams for control units with termination numbers.
 - b). Schematic diagrams and floor plans for field sensors and control hardware.
 - c). Schematic diagrams for control, communication, and power wiring, showing trunk data conductors and wiring between operator workstation and control unit locations.
 9. Control System Software: List of color graphics indicating monitored systems, data (connected and calculated) point addresses, output schedule, and operator notations.
 10. Controlled Systems:
 - a). Schematic diagrams of each controlled system with control points labeled and control elements graphically shown, with wiring.
 - b). Scale drawings showing mounting, routing, and wiring of elements including bases and special construction.
 - c). Written description of sequence of operation including schematic diagram.
 - d). Points list.
- C. Data Communications Protocol Certificates: Certify that each proposed DDC system component complies with LonWorks or Bacnet.
- D. Software and Firmware Operational Documentation: Include the following:
1. Software operating and upgrade manuals.
 2. Program Software Backup: On a magnetic media or compact disc, complete with data files.
 3. Device address list.
 4. Printout of software application and graphic screens.

5. Software license required by and installed for DDC workstations and control systems.
- E. Software Upgrade Kit: For Owner to use in modifying software to suit future systems revisions or monitoring and control revisions.
- F. Qualification Data: For Installer and manufacturer.
- G. Field quality-control test reports.
- H. Submit screen shots of ATC system graphics at substantial completion.
- I. Operation and Maintenance Data: For HVAC instrumentation and control system to include in emergency, operation, and maintenance manuals. In addition to items specified in Division 01 Section, *Operation and Maintenance Data*, and Division 23 Section, *Common Work Results for HVAC* include the following:
 1. Maintenance instructions and lists of spare parts for each type of control device.
 2. Interconnection wiring diagrams with identified and numbered system components and devices.
 3. Keyboard illustrations and step-by-step procedures indexed for each operator function.
 4. Inspection period, cleaning methods, cleaning materials recommended, and calibration tolerances.
 5. Calibration records and list of set points.
- J. Upon completion of the work, provide a complete set of "as-built" drawings and application software on CD, USB, or other type of electronic storage device. Drawings shall be provided in format as acceptable to the Owner's files. Submit as-built drawings and specification to Owner's representative for review and approval prior to final project closeout.

1.10. SOFTWARE LICENSE AGREEMENT

- A. The owner shall sign a copy of the manufacturer's standard software and firmware licensing agreement as a condition of this contract. Such license shall grant use of all programs and application software to owner as defined by the manufacturer's license agreement, but shall protect manufacturer's rights to disclosure of trade secrets contained within such software.
- B. Software license agreement shall not apply on projects where existing ATC system is being extended.

1.11. ELECTRICAL SURGE PROTECTION

- A. It is the responsibility of the ATC/FMS contractor to provide adequate surge protection for all wall mounted control panels required for this project.

1. Devices under surge protection shall be of design that loss of memory will not occur in the event of the surge protection device being activated due to surge/spike conditions.
2. Surge protection devices will be required to be hard wired, with the exception of peripheral devices that use standard 110VAC plugs for connections (i.e. Modems).
3. Surge protection devices are to be rated for 120 VAC single phase 20 (or greater) amps capacity.
4. Surge Protection devices to include internal fuse protection, audible surge alarm & LED indicators.
5. Surge protectors to have clamping voltage of 80V peak, maximum surge current rating of 50,000 amps. Unit to have NEMA 12 enclosure with wall mounting bracket and conduit connection.

1.12. TRAINING

- A. The Automatic Temperature Controls (ATC) Contractor shall include in his bid, provisions for additional computer training at the company's regular school or training center. The ATC contractor shall include in his bid all costs associated with sending one (1) individual to the ATC contractor's school for a period of not less than one (1) week. This training is in addition to the aforementioned training required under the General Provisions.
- B. The training time period shall be coordinated with the school system's facility Engineer. The schedule training period shall be arranged at the owner's convenience.
- C. Cost shall include all training material, instruction books, and two copies of video tape with sound DVD of training session.
- D. Upon completion of the work, the Control Contractor shall have completely adjusted the entire control system. He shall arrange to instruct the Owner's representative on the operation of the control system for a period of not less than two (2) eight (8) hour days. All training shall be by the control contractor and shall utilize specified manuals and as-built documentation.
- E. Engage a factory-authorized service representative to train Owner's maintenance personnel to adjust, operate, and maintain control systems and components.
 1. Train Owner's maintenance personnel on procedures and schedules for starting and stopping, troubleshooting, servicing, and maintaining equipment and schedules.
 2. Provide operator training on data display, alarm and status descriptors, requesting data, executing commands, calibrating and adjusting devices, resetting default values, and requesting logs. Include a minimum of 40 hours' dedicated instructor time on-site.
 3. Review data in maintenance manuals. Refer to Division 01 Section, *Contract*

Closeout.

4. Review data in maintenance manuals. Refer to Division 01 Section, *Operation and Maintenance Data*.
5. Schedule training with Owner, through Architect, with at least seven days' advance notice.

1.13. ALTERNATES

- A. Refer to Division 01 Section, *Alternates* for description of work under this section affected by alternates.

1.14. CAESAR RODNEY SCHOOL DISTRICT SPECIFIC REQUIREMENTS

- A. The ATC Subcontractor shall include in his bid all costs associated with incorporating the following specific requirements:
 1. All holiday schedules shall incorporate a 12 month block. Coordinate exact holidays, schedules, calendars, occupied, unoccupied periods with Owner prior to writing software. All schedules shall be reviewed and approved by the Owner.
 2. Relays for ATC equipments shall not be located in ceilings. All relays shall be located in equipment control panels and/or mechanical rooms.
 3. All exhaust fans shall be assigned a designated point. Utilizing relays to provide digital point for exhaust fans shall not be acceptable.
 4. Graphics on ATC computer shall in addition to basic requirements indicate the percentage open or closed on all valves and dampers.
 5. The ATC Computer Graphics shall incorporate the final room numbers actually utilized in the school. All room names utilized in the graphic display shall be reviewed and approved by the Owner.
 6. The ATC Computer Graphics shall indicate for each item of equipment the "on" or "off" status and command shall be "run" or "stop".
 7. The ATC Computer Graphic shall indicate for each duct smoke detector the "on" or "off" status and command.
 8. All Temperature Sensors, equipment, humidity sensors, current sensors, CO₂ sensors, differential pressure sensors, etc. indicated on ATC Control Diagrams and point list shall be displayed on the ATC Computer Graphic. Measured value or status shall be displayed.
 9. For any multi-stage HVAC units, the quantity of compressor stages and the quantity of electric heat stages shall be displayed on the Computer Graphics.
 10. The exact space temperature set points, humidity set points, changeover set points. etc., shall be coordinated with Owner prior to final data entry. All items

indicated in sequences of Operation as “adjustable” shall be reviewed and approved by Owner prior to implementation of the same.

11. The outside air humidity and outside air temperature shall be monitored on ATC system and reported on ATC Computer Graphics. See Floor plans for exact locations.
12. Provide a graphic of all floor plans indicating location of all equipment interlocked with ATC System including all control panels.
13. Graphic shall also indicate area of building served by each item of equipment. Graphics shall indicate all global sensor readings.
14. For the chilled water loop provide a single command on the control system to allow all control valves to be manually opened for balancing by activating a single command.
15. All equipment shall be labeled with name of equipment, area served, and area location (room name/number).

1.15. GLOBAL SENSORS

A. General

1. Furnish and install global sensors and report the same on the automatic temperature control system.
2. Global sensors shall monitor and trend the following conditions:
 - a). Outside air temperature.
 - b). Outside air humidity.
 - c). Chilled water supply water temperature.
 - d). Chilled water return water temperature.
 - e). All ventilation fan speeds where variable frequency drives are specified.
 - f). Outside air carbon dioxide level.
 - g). All ventilation fan amperage where variable frequency drives are specified.
 - h). All pump or fan speeds where variable frequency drives are specified.
 - i). All pump amperage's where variable frequency drives are specified.
 - j). All fan amperages where variable speed fans are indicated. Graphic shall also indicate area of building served by each item of equipment.

- k). Main Distribution Frame (MDF), and I.T. server room space temperature sensor.
- l). Global holiday schedules:
 - i. Provide all interlock wiring and programming to allow a global holiday schedule for all equipment except the administration equipment. Global holiday schedule shall allow the Owner to shut down the entire school's HVAC systems if an unscheduled event occurs when school is cancelled.
 - ii. System shall also be capable of individual scheduling of equipment as specified or all can be globally modified at once.
- m). All equipment interlocked with ATC system shall be able to be turned on/off via ATC system as specified. Changing temperature set point alone is not acceptable method for turning equipment on/off.
- n). Where valve or damper position is indicated ATC graphic shall indicate percentage open or percentage closed.

PART 2. PRODUCTS

2.1. BUILDING MANAGEMENT SYSTEM

- A. The Building Management System (BMS) shall use an open architecture and fully support a multi-vendor environment. To accomplish this effectively, the BMS shall support open communication protocol standards and integrate a wide variety of third-party devices and applications. The system shall be designed for use on the Internet, or intranets using on the shelf, industry standard technology compatible with other owner provided networks.
- B. The Building Management System shall consist of the following:
 1. Standalone Network Automation Engine(s)
 2. Field Equipment Controller(s)
 3. Input/Output Module(s)
 4. Local Display Device(s)
 5. Portable Operator's Terminal(s)
 6. Distributed User Interface(s)
 7. Network processing, data storage and communications equipment
 8. Other components required for a complete and working BMS

- C. The system shall be modular in nature, and shall permit expansion of both capacity and functionality through the addition of sensors, actuators, controllers and operator devices, while re-using existing controls equipment.
- D. System architectural design shall eliminate dependence upon any single device for alarm reporting and control execution. The failure of any single component or network connection shall not interrupt the execution of control strategies at other operational devices.
- E. Acceptable Manufacturers
1. Johnson Controls, Reliable, Siemens, Honeywell, Automated Logic Cooperation, Schneider Electric, Advanced Power, Trane, Merton, Niagara, or TAC Controls by Schneider Electric.
- F. Automation Network
1. The automation network shall be based on the industry standard of Ethernet TCP/IP. Where used, LAN controller cards shall be standard “off the shelf” products available through normal PC vendor channels.
 2. The automation network shall be capable of operating at a communication speed of 100 Mbps, with full peer-to-peer network communication.
 3. Network Automation Engines (NAE) and/or system controllers shall reside on the automation network.
 4. The automation network will be compatible with other enterprise-wide networks. Where indicated, the automation network shall be connected to the enterprise network and share resources with it by way of standard networking devices and practices.
- G. Control Network
1. Network Automation Engines and/or system controllers shall provide supervisory control over the control network and shall support all three (3) of the following communication protocols:
 - a). BACnet Standard MS/TP Bus Protocol ASHRAE SSPC-135, Clause 9.
 - b). LonWorks enabled devices using the Free Topology Transceiver (FTT-10a).
 - c). The Johnson Controls N2 Field Bus or equivalent.
 - d). Tridium FX-40
 - e). Honeywell Webs
 - f). Trend Controls: A division of Honeywell by HavTech Solutions – IQ3
 - g). TAC Controls by Schneider Electric
 - h). Siemens P1/P2 Serial
 2. Control networks shall provide either “Peer-to-Peer,” Master-Slave, or Supervised Token Passing communications, and shall operate at a minimum

communication speed of 9600 baud.

3. DDC Controllers shall reside on the control network.
4. Control network communication protocol shall be BACnet Standard MS/TP Bus Protocol ASHRAE SSPC-135.
5. A BACnet Protocol Implementation Conformance Statement shall be provided for each controller device (master or slave) that will communicate on the BACnet MS/TP Bus.
6. The Conformance Statements shall be submitted 10 day prior to bidding.

H. Integration

1. Hardwired

- a). Analog and digital signal values shall be passed from one system to another via hardwired connections.
- b). There will be one separate physical point on each system for each point to be integrated between the systems.

2. BACnet Protocol Integration – BACnet

- a). The neutral protocol used between systems will be BACnet over Ethernet and comply with the ASHRAE BACnet standard 135-2003.
- b). A complete Protocol Implementation Conformance Statement (PICS) shall be provided for all BACnet system devices.
- c). The ability to command, share point object data, change of state (COS) data and schedules between the host and BACnet systems shall be provided.

I. Dedicated Web Based User Interface

1. Where required by the Owner, the BMS Contractor shall provide and install a personal computer for command entry, information management, network alarm management, and database management functions. All real-time control functions, including scheduling, history collection and alarming, shall be resident in the BMS Network Automation Engines to facilitate greater fault tolerance and reliability. Coordinate with Owner to determine computer type (i.e. PC (Windows based) or Macintosh (Apple)).
2. Dedicated User Interface Architecture – The architecture of the computer shall be implemented to conform to industry standards, so that it can accommodate applications provided by the BMS Contractor and by other third party applications suppliers, including but not limited to Microsoft Office Applications. Specifically it must be implemented to conform to the following interface standards.
 - a). Microsoft Internet Explorer for user interface functions

- b). Microsoft Office Professional for creation, modification and maintenance of reports, sequences other necessary building management functions
 - c). Microsoft Outlook or other e-mail program for supplemental alarm functionality and communication of system events, and reports
 - d). Required network operating system for exchange of data and network functions such as printing of reports, trends and specific system summaries.
3. Computer Hardware – The personal computer(s) shall be configured as follows:
- a). Description: A tower or all-in-one computer designed for normal use at a single, semipermanent location.
 - b). Performance Requirements:
 - 1). Performance requirements may include equipment exceeding minimum requirements indicated.
 - 2). Energy Star compliant.
 - c). Personal Computer:
 - 1). Minimum Processor Speed: 3 gigahertz (GHz).
 - d). RAM:
 - 1). Capacity: 8GB.
 - 2). Speed and Type: 1333 MHz, SDRAM.
 - e). Hard Drive:
 - 1). Media: Solid state.
 - 2). Number of Hard Drives: One.
 - 3). Capacity: 250GB.
 - f). Optical Read and Write Drive:
 - 1). Include with at least 2 MB of data buffer.
 - 2). Type: SCSI CD-ROM Drive with Read/Write Capability.
 - 3). Average access time of 150 ms or less.
 - g). At least four expansion slots.
 - h). Video Card:
 - 1). Resolution: 1920 by 1200 pixels.
 - 2). RAM: 4 GB.
 - 3). Controller Speed: 4GHz.
 - i). Sound Card:
 - 1). At least 128 voice wavetable synthesis.
 - 2). Capable of delivering three-dimensional sound effects.
 - 3). High-resolution 16-bit stereo digital audio recording and playback with user-selectable sample rates up to 48,000 Hz.
 - j). Network Interface Card: Include card with connection, as applicable.

- 1). 10-100-1000 base TX Ethernet with RJ45 connector port.
 - 2). 100 base FX Ethernet with SC or ST port.
- k). Wireless Ethernet, 802.11 a/b/g/n.
- l). Optical Modem: Full duplex link for connection to optical fiber cable provided.
- m). I/O Ports:
- 1). Two USB 3.0 ports on front panel, six on back panel, and three internal on motherboard.
 - 2). One serial port.
 - 3). One parallel port.
 - 4). Two PS/2 ports.
 - 5). One RJ-45.
 - 6). One stereo line-in and headphone/line-out on back panel.
 - 7). One microphone and headphone connector on front panel.
 - 8). One IEEE 1394 on front and back panel with PCI-e card.
 - 9). One ESATA port on back panel.
- n). Battery: Life of at least three years to maintain system clock/calendar and ROM, as a minimum.
- o). Keyboard:
- 1). 101 enhanced keyboard.
 - 2). Full upper- and lowercase ASCII keyset, numeric keypad, dedicated cursor control keypad, and 12 programmable function keys.
 - 3). Wireless operation within up to 72 inches (1800 mm) in front of workstation.
- p). Pointing Device:
- 1). Either a two- or three-button mouse.
 - 2). Wireless operation within up to 72 inches (1800 mm) in front of workstation.
- q). Flat Panel Display Monitor:
- 1). Display:
 - i. Color display with 21 inches diagonal viewable area.
 - ii. Digital input signal.
 - iii. Aspect Ratio: 16 to 9.
 - iv. Antiglare display.
 - v. Tilt adjustable base.
 - vi. Energy Star compliant.
 - vii. Resolution: 1920 by 1200 pixels at 60 Hz.
 - viii. Number of Displays: One.
- r). Speakers:

- 1). Two, with individual controls for volume, bass and treble.
 - 2). Signal to Noise Ratio: At least 65 dB.
 - 3). Power: At least 4 W per speaker/channel.
 - 4). Magnetic shielding to prevent distortion on the video monitor.
- s). I/O Cabling: Include applicable cabling to connect I/O devices.

J. User Interface Application Components

1. Operator Interface

- a). An integrated browser based client application shall be used as the user operator interface program.
- b). All Inputs, Outputs, Setpoints, and all other parameters as defined within Part 3 or on the drawings, shown on the design drawings, or required as part of the system software, shall be displayed for operator viewing and modification from the operator interface software.
- c). The user interface software shall provide help menus and instructions for each operation and/or application.
- d). All controller software operating parameters shall be displayed for the operator to view/modify from the user interface. These include: setpoints, alarm limits, time delays, PID tuning constants, run-times, point statistics, schedules, and so forth.
- e). The Operator Interface shall incorporate comprehensive support for functions including, but not necessarily limited to, the following:
 - i. User access for selective information retrieval and control command execution
 - ii. Monitoring and reporting
 - iii. Alarm, non-normal, and return to normal condition annunciation
 - iv. Selective operator override and other control actions
 - v. Information archiving, manipulation, formatting, display and reporting
 - vi. FMS internal performance supervision and diagnostics
 - vii. On-line access to user HELP menus
 - viii. On-line access to current FMS as-built records and documentation
 - ix. Means for the controlled re-programming, re-configuration of FMS operation and for the manipulation of FMS database information in compliance with the prevailing codes, approvals and regulations for individual FMS applications.
 - x. The operation of the control system shall be independent of the user interface, which shall be used for operator communications only. Systems that rely on an operator workstation to provide supervisory control over controller execution of the sequences of operations or system communications shall not be acceptable.

2. Navigation Trees

- a). The system will have the capability to display multiple navigation trees that will aid the operator in navigating throughout all systems and points

- connected. At minimum provide a tree that identifies all systems on the networks.
- b). Provide the ability for the operator to add custom trees. The operator will be able to define any logical grouping of systems or points and arrange them on the tree in any order. It shall be possible to nest groups within other groups. Provide at minimum 5 levels of nesting.
 - c). The navigation trees shall be “dockable” to other displays in the user interface such as graphics. This means that the trees will appear as part of the display, but can be detached and then minimized to the Windows task bar or closed altogether. A simple keystroke will reattach the navigation to the primary display of the user interface.

3. Alarms

- a). Alarms shall be routed directly from Network Automation Engines to PCs and servers. It shall be possible for specific alarms from specific points to be routed to specific PCs and servers. The alarm management portion of the user interface shall, at the minimum, provide the following functions:
 - i. Log date and time of alarm occurrence.
 - ii. Generate a “Pop-Up” window, with audible alarm, informing a user that an alarm has been received.
 - iii. Allow a user, with the appropriate security level, to acknowledge, temporarily silence, or discard an alarm.
 - iv. Provide an audit trail on hard drive for alarms by recording user acknowledgment, deletion, or disabling of an alarm. The audit trail shall include the name of the user, the alarm, the action taken on the alarm, and a time/date stamp.
 - v. Provide the ability to direct alarms to an e-mail address or alphanumeric pager. This must be provided in addition to the pop up window described above. Systems that use e-mail and pagers as the exclusive means of annunciating alarms are not acceptable.
 - vi. Any attribute of any object in the system may be designated to report an alarm.
- b). The FMS shall annunciate diagnostic alarms indicating system failures and non-normal operating conditions
- c). The FMS shall annunciate application alarms as required.

4. Reports and Summaries

- a). Reports and Summaries shall be generated and directed to the user interface displays, with subsequent assignment to printers, or disk. As a minimum, the system shall provide the following reports:
 - i. All points in the BMS
 - ii. All points in each BMS application
 - iii. All points in a specific controller

- iv. All points in a user-defined group of points
 - v. All points currently in alarm
 - vi. All points locked out
 - vii. All BMS schedules
 - viii. All user defined and adjustable variables, schedules, interlocks and the like.
- b). Summaries and Reports shall be accessible via standard UI functions and not dependent upon custom programming or user defined HTML pages.
 - c). Selection of a single menu item, tool bar item, or tool bar button shall print any displayed report or summary on the system printer for use as a building management and diagnostics tool.
 - d). The system shall allow for the creation of custom reports and queries via a standard web services XML interface and commercial off-the-shelf software such as Microsoft Access, Microsoft Excel, or Crystal Reports.
5. Schedules
- a). A graphical display for time-of-day scheduling and override scheduling of building operations shall be provided. At a minimum, the following functions shall be provided:
 - i. Weekly schedules
 - ii. Exception Schedules
 - iii. Monthly calendars
 - b). Weekly schedules shall be provided for each group of equipment with a specific time use schedule.
 - c). It shall be possible to define one or more exception schedules for each schedule including references to calendars
 - d). Monthly calendars shall be provided that allow for simplified scheduling of no days and special days for a minimum of five years in advance. Holidays and special days shall be user-selected with the pointing device or keyboard, and shall automatically reschedule equipment operation as previously defined on the exception schedules.
 - e). Changes to schedules made from the User Interface shall directly modify the Network Automation Engine schedule database.
 - f). Schedules and Calendars shall comply with ASHRAE SP135/2003 BACnet Standard.
 - g). Selection of a single menu item or tool bar button shall print any displayed schedule on the system printer for use as a building management and diagnostics tool.
6. Password
- a). Multiple-level password access protection shall be provided to allow the user/manager to user interface control, display, and database manipulation capabilities deemed appropriate for each user, based on an assigned password.
 - b). Each user shall have the following: a user name (24 characters minimum), a password (12 characters minimum), and access levels.

- c). The system shall allow each user to change his or her password at will.
- d). When entering or editing passwords, the system shall not echo the actual characters for display on the monitor.
- e). A minimum of five levels of access shall be supported individually or in any combination as follows:
- i. Level 1 = View Data
 - ii. Level 2 = Command
 - iii. Level 3 = Operator Overrides
 - iv. Level 4 = Database Modification
 - v. Level 5 = Database Configuration
 - vi. Level 6 = All privileges, including Password Add/Modify
- f). A minimum of 100 unique passwords shall be supported.
- g). Operators shall be able to perform only those commands available for their respective passwords. Display of menu selections shall be limited to only those items defined for the access level of the password used to log-on.
- h). The system shall automatically generate a report of log-on/log-off and system activity for each user. Any action that results in a change in the operation or configuration of the control system shall be recorded, including: modification of point values, schedules or history collection parameters, and all changes to the alarm management system, including the acknowledgment and deletion of alarms.
7. Screen Manager - The User Interface shall be provided with screen management capabilities that allow the user to activate, close, and simultaneously manipulate a minimum of 4 active display windows plus a network or user defined navigation tree.
8. Dynamic Color Graphics
- a). The graphics application program shall be supplied as an integral part of the User Interface. Browser or Workstation applications that rely only upon HTML pages shall not be acceptable.
 - b). The graphics applications shall include a create/edit function and a runtime function. The system architecture shall support an unlimited number of graphics documents (graphic definition files) to be generated and executed.
 - c). The graphics shall be able to display and provide animation based on real-time data that is acquired, derived, or entered.
 - d). Graphics runtime functions – A maximum of 16 graphic applications shall be able to execute at any one time on a user interface or workstation with 4 visible to the user. Each graphic application shall be capable of the following functions:
 - i. All graphics shall be fully scalable
 - ii. The graphics shall support a maintained aspect ratio.
 - iii. Multiple fonts shall be supported.
 - iv. Unique background shall be assignable on a per graphic basis.
 - v. The color of all animations and values on displays shall indicate the status of the object attribute.

- e). Operation from graphics – It shall be possible to change values (setpoints) and states in system controlled equipment by using drop-down windows accessible via the pointing device
- f). Graphic editing tool – A graphic editing tool shall be provided that allows for the creation and editing of graphic files. The graphic editor shall be capable of performing/defining all animations, and defining all runtime binding.
- i. The graphic editing tool shall in general provide for the creation and positioning of point objects by dragging from tool bars or drop-downs and positioning where required.
- ii. In addition, the graphic editing tool shall be able to add additional content to any graphic by importing backgrounds in the SVG, BMP or JPG file formats.
- g). Aliasing – Many graphic displays representing part of a building and various building components are exact duplicates, with the exception that the various variables are bound to different field values. Consequently, it shall be possible to bind the value of a graphic display to aliases, as opposed to the physical field tags.
9. Historical trending and data collection
- a). Each Automation Engine shall store trend and point history data for all analog and digital inputs and outputs, as follows:
- i. Any point, physical or calculated, may be designated for trending. Two (2) methods of collection shall be allowed:
- Defined time interval
 - Upon a change of value.
- ii. Each Automation Engine shall have the capability to store multiple samples for each physical point and software variable based upon available memory, including an individual sample time/date stamp. Points may be assigned to multiple history trends with different collection parameters.
- b). Trend and change of value data shall be stored within the engine and uploaded to a dedicated trend database or exported in a selectable data format via a provided data export utility. Uploads to a dedicated database shall occur based upon one of the following: user-defined interval, manual command, or when the trend buffers are full. Exports shall be as requested by the user or on a time scheduled basis.
10. Trend data viewing and analysis
- a). Provide a trend viewing utility that shall have access to all database points.
- b). It shall be possible to retrieve any historical database point for use in

displays and reports by specifying the point name and associated trend name.

- c). The trend viewing utility shall have the capability to define trend study displays to include multiple trends
- d). Displays shall be able to be single or stacked graphs with on-line selectable display characteristics, such as ranging, color, and plot style.
- e). Display magnitude and units shall both be selectable by the operator at any time without reconfiguring the processing or collection of data. This is a zoom capability.
- f). Display magnitude shall automatically be scaled to show full graphic resolution of the data being displayed.
- g). Trend studies shall be capable of calculating and displaying calculated variables including highest value, lowest value and time based accumulation.

K. Portable Operator Terminal

1. For systems that do not provide full access to systems configuration and definition via the Browser Based user interface the BMS Contractor shall provide a portable operator terminal for programming purposes. The terminal shall be configured as follows:

- a). Personal Laptop Computer Manufacturer – Dell, Compaq or HP
- b). 1 GB RAM (256 MB minimum) – Windows 2000 or XP Professional.
- c). 1.8 GHz Clock Speed Pentium 4 Microprocessor (800 MHz minimum).
- d). 40 GB Hard Drive (40 GB minimum)
- e). (1) CD-ROM Drive, 32x speed.
- f). (1) Serial (1) Parallel (2) USB ports
- g). 1 Keyboard with 83 keys (minimum).
- h). Integral 2 button Track Point or Track Ball.
- i). 17" SVGA 1024x768 resolution color display
- j). Two PCMCIA Type II or one Type III card slot.
- k). Complete operator workstation software package, including any hardware or software.
- l). Original printed manuals for all software and peripherals.
- m). Original installation disks or CD for all software, device drivers, and peripherals.
- n). Software registration cards for all included software shall be provided to the Owner.
- o). Carrying case.
- p). Spare battery.
- q). External power supply/battery charger.

2. Proprietary Portable Terminal

- a). Manufacturers providing proprietary portable terminals shall submit technical data sheets for the terminal and all associated software and hardware.
- b). The proprietary terminal shall meet the same operator interface software requirements as specified above.

3. Software

- a). Portable operator terminals shall support all controllers within the system on a direct-connect communications basis.
- b). When used to access First or Second Tier controllers, the portable operator terminal shall utilize the standard operator workstation software, as previously defined.
- c). When used to access Application Specific Controllers, the portable operator terminal shall utilize either the standard operator workstation software, as previously defined, or controller-specific utility software.

2.2. WIRING

- A. The multi-conductor cable for field wiring of electronic analog sensors shall be minimum No. 22 AWG, 300 volt, thermoplastic with stranded copper wire and 100 percent shield coverage. The number of conductors in each sensor cable shall be as determined by the Contractor. 2/c #22 shielded cables shall be Belden Cat. #8451 3/c #20 shielded cables shall be Belden Cat. #9770 or approved equal.
- B. Conductors for digital sensors or contact control shall be the same as for the analog sensors, except the grounded shield is not required.
- C. Individual conductors shall be color coded and in addition shall be numbered in the field to identify the particular terminal to which attached. Field numbering shall be performed with Brady or approved equal markers wrapped around the wire near the terminal connection. All wires shall be terminated with pressure type connectors suitable for wire size, material and terminal connection.
- D. All exposed wiring or wiring concealed in partitions shall be installed in a designated conduit raceway. The conduit shall conform to Division 26 of the specification. Where wiring is installed in an air plenum the same shall be plenum rated cable.
- E. All junction boxes shall have covers painted *safety green*, and be rigid steel.
- F. All wiring between differential pressure transmitters and variable frequency drive pump controllers shall be shielded and grounded at the pump controller end. Directly route the variable frequency drive pump controller to the differential pressure transmitter(s).
- G. All wiring between static pressure controllers and/or air flow monitoring stations and variable frequency drive fan controllers shall be shielded and grounded at the fan controller end. Directly route the variable frequency drive fan controller to the static pressure controller(s) and/or air flow monitoring stations.
- H. All control wiring between VRV compressor units, branch selector boxes, and indoor VRV units shall be shielded and grounded per VRV manufacturer requirements.

2.3. CONTROLLERS

- A. Temperature, humidity, and CO2 sensor covers shall be stainless steel wire guard type with vandal proof screws. All room humidity, CO2, and temperature sensors shall be

mounted 4'-0 inches above the finished floor, except in stairways, corridors and toilets, which shall be 7'-0 inches. Provide insulating bases where temperature sensors are located on exterior or unconditioned walls. Each temperature sensor shall have adjustable limit stops and adjustable sensitivity. User adjustment shall be 2 degrees F above and below set points or as determined by the Owner. Room temperature sensors shall include range of 55 degrees F to 85 degrees F set point adjustment. Temperature sensors shall include set-point adjusters, U.L. approved for mounting base in air plenums and RJ-11 jack for communications. Room temperature sensors shall be fully adjustable and shall display set point and actual temperature.

- B. Space sensor wiring shall be installed concealed where possible. Should the Division 23 Contractor be unable to do so then surface metal raceway shall be utilized as specified in Division 26.
- C. Low Limit Thermostats: Freezestats shall have a minimum 20 foot (averaging sensing element) capillary tube sized to the basis of one linear foot of capillary tube for each square foot of coil surface. Thermostat sensitivity shall be adjustable. Freezestats shall stop supply and return fans and close the outside air damper if mixed air temperature drops below 35 degrees F and open hot water heating valves. Additional requirements are indicated in Sequence of Operation.
- D. Room temperature sensors shall be accessible to ADA occupants.

2.4. DAMPERS

A. Control Dampers

1. The temperature control contractor shall provide all automatic control dampers of the types indicated on the plans and not specified to be integral with other equipment. Frames shall be not less than 16 gauge galvanized steel. Blades shall not be over 6 inches wide airfoil shaped double skin construction of 14 gauge equivalent thickness. Bearings shall be stainless steel sleeves with 2 inch shafts. Blade edge seals shall be vinyl blade with flexible metal compressible gaskets and seals of the tight-seal spring type. Dampers and seals shall be suitable for temperature ranges of -40 to 250 degrees F.
2. All proportional control dampers shall be opposed blade type and all two-position dampers shall be parallel blade type.
3. Dampers shall be sized to meet flow requirements of the application. The sheet metal contractor shall furnish and install baffles to fit the damper to duct size. Baffles shall not exceed 6 inches.
4. Dampers shall be minimum leakage type to conserve energy and the temperature control manufacturer shall submit leakage and flow characteristic data for all control dampers with the temperature control submittal. Maximum leakage shall be 3 CFM/Sq. Ft. at static pressure of 1 inch W.C. for a damper width of 48 inches.
5. Ultra-low leakage dampers shall have blade edges shall to be fitted with

replaceable, snap-on, inflatable seals to limit damper leakage to 2 percent at applied static pressure.

6. Low pressure rectangular control dampers shall be Type CD60 airfoil low leakage damper as manufactured by Ruskin or as approved equal of American Warming and Ventilating, Air Balance and Arrow.
7. Round control dampers shall be Type CERS25 with blade edge seals as manufactured by Ruskin or as approved equal.
8. Provide damper end switch for all control dampers where indicated. Damper end switch shall be independent of the damper actuator and shall provide "proof of open" prior to allowing fan to energize. Damper end switch shall be Model TS-475 Mechanical Damper Arm Switch (no-mercury) as manufactured by MDI, Inc. or approved equal. Install per manufacturer's recommendations on control damper. End switch shall have the following features:
 - a). Housing Material: Glass filled PBT (polybutylene terephthalate).
 - b). Bracket Material: Plated steel.
 - c). Operation: Steel ball actuated sub-miniature snap action switch.
 - d). Operating angle: 15 degrees. (Contact closes at 10 degrees above horizontal and contact opens at 5 degrees below horizontal).

B. Smoke Detectors

1. Smoke detectors shall be provided by the Electrical Contractor and installed by the Mechanical Contractor. All wiring, interlocks, etc., to be provided by Electrical Contractor. Wiring from duct smoke detectors to fans shall be by ATC Contractor. Duct smoke detectors shall be tested by the Test and Balance Engineer as specified in Division 23 Section, *Testing, Adjusting & Balancing for HVAC and Plumbing*.

C. Damper Operators

1. Electric damper actuators shall be properly sized to provide sufficient torque to position the damper throughout its operating range.
2. Use devices which are quiet in operation and which in the event of power failure, will "fail safe" by spring action in either the normally open or normally closed position as required for freeze, moisture, smoke, or fire protection.
3. Electric actuators requiring a 24 VAC power supply will be utilized. Motors shall be specifically designed and sized with proper torque according to requirements of the device it is to be used on (i.e.: valve, damper). Each actuator will accept the proper control input as the system is designed, (i.e.: floating, 0-10VDC, 4-20Ma etc.) without the need for any additional interface devices.
4. For all exterior damper operators provide NEMA 4X stainless steel corrosion resistant enclosure. Damper operator enclosure shall be model ZS-300 as manufactured by Belimo or approved equal.

2.5. PRESSURE INDEPENDENT HYDRONIC CONTROL VALVES

- A. All automatic control valves 2 inches and smaller shall be screwed type, and valves 2 ½ inches and larger shall be flanged. Valves shall be factory-rated to withstand the pressures encountered. Valves shall have stainless-steel stems and spring loaded Teflon packing with replaceable seats and discs. All control valves must be capable of withstanding the shut-off head of the pumps, they are connected to without the valve seat lifting. Valves shall have stainless steel stems and spring loaded Teflon packing with replaceable seats and discs.
1. All modulating straight-through water valves shall be provided with equal-percentage contoured throttling plugs and shall be pressure independent type. All three-way valves shall be provided with linear throttling plugs such that the total flow through the valve shall remain constant regardless of the valve's position modulating. Valves shall be sized for a pressure drop equal to the coil they serve but not to exceed 5 psi. Valves shall have replaceable seats and discs. Pressure independent control valves shall be as manufactured by Griswold, Delta P, Warren Controls, Danfos, Bray, or approved equal.
 2. Pressure Independent Actuated Ball Valves (PIC-V) for Flows up to 85 GPM
 - a. The modulating control valves shall be pressure independent.
 - b. Valves shall accurately control flow within +/-5% (including manufacturing tolerance) independent of system pressure fluctuation by maintaining a constant pressure differential across the control valve so that the valve only repositions on a change in load demand.
 - c. The pressure independent modulating control valve shall include a Pressure Compensating Cartridge, Actuated Ball Valve, 2 PT's, Manual Adjustment, Union, and Manual Isolation Ball in a single valve housing.
 - d. The valve shall have an accuracy of +/- 5% including manufacturing tolerances and pressure variations.
 - e. Valve housing shall consist of forged brass, rated at no less than 360 psi at 250°F.
 - f. Valve shall include a venturi metering station so that the flow rate can be read by means of differential pressure. Venturi metering station shall not require any straight runs of piping before or after meter.
 - g. Both the ATC and shutoff valve shall have stems that are field repairable with the valve in the line. The body design shall allow inspection or repair of the stem without disturbing piping connections or draining water. The repairable stem shall include two Teflon seals and one EPDM O-ring for protection against chemicals and modulating temperature.

- h. Valve shall have a union end connection with factory installed air vent to allow for venting of the coil or heat pump.
- i. The control valve shall accurately control the flow from 0 to 100% full rated flow.
- j. The ATC portion of the valve shall use the full 90 degrees of the stroke for control. Stroke limiting of the valve shall not be acceptable.
- k. A flow tag shall be furnished with each valve.
- l. A universal mounting plate shall allow installation of actuators meeting the system electrical requirements and valve torque requirements as provided by Honeywell, Invensys, Johnson Controls, KMC, Schneider, Neptronic, or Siemens.
- m. The actuator and plate can be rotated after mounting.
- n. The actuator mounting assembly shall accommodate no less than 1 ½" of insulation.
- o. Pressure Compensating Cartridge (PCC)
 - 1). PCC shall automatically compensate for pressure changes in valve and shall maintain a constant pressure drop across the flow limiting actuated ball.
 - 2). The operating pressure range shall be available with the minimum range requiring 3 PSID to actuate the cartridge and the maximum 8 psid to actuate the cartridge
 - 3). Valve internal control mechanism includes a diaphragm and full travel linear coil spring.
 - 4). Valves shall include an accessible/ replaceable cartridge.
 - 5). Dual pressure/temperature test valves for verifying the pressure differential across the cartridge and flow limiting ball shall be standard.
- p. Actuated Ball Valve
 - 1). Valve ball shall consist of chemically plated nickel brass or stainless steel.
 - 2). Actuator stem shall be removable/ replaceable without removing valve from line.
 - 3). Manufacturer shall be able to provide ball insert to limit flow to maximum flow rate with $\pm 5\%$ accuracy. Insert shall be

constructed of a Glass-Filled Polymer. The insert shall be press fit to the inside of the ball. Clipping the insert onto the exiting side of the ball shall not be acceptable.

- 4). Each maximum flow rate selected shall use a different characterizing disc so that stroke limiting is not required.
 - 5). Valve shall have a minimum rangeability as follows: 1/2"-40:1, 3/4"-160:1, 1" to 3"-400:1
 - 6). Valve shall have EPDM O-rings behind Reinforced PTFE (PTFE) ball seals.
 - 7). The valve shall have a minimum close off pressure differential rating of 100 psi with 35 in-lbs of torque for 1/2" to 2" sizes.
 - 8). Actuator shall provide minimum torque required for full valve shutoff position.
- q. Isolation Ball Valve
- 1). Valve shall include a 600 WOG manual isolation ball valve.
 - 2). Stem shall be removable/replaceable with the valve in the line.
- r. The control valve actuator will be furnished by the controls contractor under Section 230000.
- s. Pressure independent valves shall come as one complete assembly from Griswold Controls or approved equal and shall include a supply side combination shutoff/ strainer valve.
3. MVP Pressure Independent Control Valves for Flows above 85 GPM.
- a. Pressure Independent Flow Control Valve 2.5" and Larger
- 1). The modulating control valves shall be pressure independent.
 - 2). Valve shall accurately control flow within +/-5% (including manufacturing tolerance) independent of system pressure fluctuation by maintaining a constant pressure differential across the control valve so that the valve only repositions on a change in load demand.
 - 3). Contactor shall install pressure independent flow control valves where indicated in drawings.
 - 4). Valve shall be electronic, pressure independent, modulating 2-way control device.

- 5). Balancing valves shall not be required where pressure-independent valves are installed.
- 6). Install flow measuring station and shut-off valve on return pipe to measure flow rate in gallons per minute.

b. Valve Actuator

- 1). Valve actuator housing shall be rated to IP44 insulation.
- 2). Actuator shall be driven by a 24Vdc motor, and shall accept 2-10 Vdc, 4-20mA, 3-point floating or pulse width modulation electric signal and shall include resistor to facilitate any of these signals.
- 3). Actuator shall be capable of providing 4-20mA or 2-10 Vdc feedback signal to the control system so that the gpm can be determined.
- 4). External LED readout of current valve position and maximum valve position setting shall be standard.
- 5). Maximum flow setting shall be adjustable to 51 different settings within the range of the valve size by changing the settings electronically on the actuator.
- 6). Optional fail safe system to power valve to either open or closed position from any position in case of power failure shall be provided per the sequence of operations and the automatic temperature control diagrams.

c. Valve Housing

- 1). 2.5"-6": Housing shall be constructed of Ductile Iron ASTM A536-65T, Class 60-45-18 rated at no less than 580 psi static pressure and 248°C.

d. Pressure Regulation Unit

- 1). Pressure regulation unit shall consist of 304 Stainless Steel and hydrogenated acrylonitrile butadiene rubber (1/2"-1-1/2") or 316 Stainless Steel and EPDM (2"-6").
- 2). Flow regulation unit shall be accessible for maintenance without disturbing the piping.
- 3). Valve shall have a maximum of 8.6 psid to actuate the pressure regulating cartridge.
- 4). Dual pressure/temperature test valves for verifying accuracy of flow performance shall be available for all valve sizes.

4. Where applicable, all two (2) position control valves may be furnished with hose kits at Contractor's option. Coordinate actuator and pressure drop requirements with hose kit supplier. Maximum allowable pressure drop for two (2) position modulating control valves shall be 12 feet at scheduled flow rate.
5. Optional accessories shall include a stem packing lubricator for factory or field assembly. Valve stem packing shall be low friction, tight sealing Teflon.
6. Unitary valves shall be straight-through or three way type as specified in the sequence of operation with high-pressure connections suitable for copper pipe and rated for 250 psig. Stems shall be polished stainless-steel and packing shall be ethylene-propylene suitable for both chilled water and 250 degree hot water service. Straight-through valves shall have back-seating feature, to allow packing to be replaced without draining system.
7. All valves shall use guided valve plugs for good seating and reliable operation. Valves ½ inch to 1 inch shall be ANSI Class 125 brass body with screwed ends. Valves 1-1/4 inches to 2 inches shall be ANSI Class 150 brass body with screwed ends. Valves 2-1/2 inches to 4 inches shall be Class 125 cast iron body with bronze trim and flanged ends. Valves 6 inches and larger shall be Class 125 steel body with bronze trim and flanged ends. Butterfly valves shall be DeZurick HIGH performance or Keystone Keylock, Lug style as specified in Division 23 Section, *HVAC Piping, Fittings, and Valves*.
8. All heating coil valves shall be normally open to the coil.

B. Control Valve Operators

1. Electric valve actuators shall be properly sized to provide sufficient torque to position valve throughout its operating range.
2. Use devices which are quiet in operation and which in the event of power failure, will "fail safe" by spring action in either the normally open or normally closed position as required for freeze, moisture, smoke, or fire protection. Spring return valves are required for all control valves where coils are exposed to outside air conditions.
3. Electric actuators requiring a 24VAC power supply will be utilized. Motors shall be specifically designed and sized with proper torque according to requirements of the device it is to be used on (i.e: valve, damper). Each actuator will accept the proper control input as the system is designed, (i.e.: floating, 0-10VDC, 4-10Ma etc.) without the need for any additional interface devices.

2.6. CONTROL PANELS

- A. Furnish and install local panels for ATC devices. Control panels shall be fully enclosed cabinets, all steel construction and shall meet the requirements of NEMA 1 enclosures. Cabinet shall have piano hinged door with a locking latch. All cabinet locks shall use common key. Provide means of storing control system instructions and drawings inside

cabinet for future reference. Panel shall be wall mounted or free standing and located where directed by the Contract Drawings or Engineer.

1. Each panel shall have all internal devices factory wired to a numbered terminal strip. Controllers and associated devices shall be mounted within the panel, accessible through a hinged door.
2. All ATC panels shall be provided with integral disconnect, wiring, and control transformers.
3. Any ATC control panel that is serving equipment on the emergency generator must be powered by an emergency generator fed circuit/electrical panel. Refer to electrical contract documents for all emergency powered equipment.

2.7. MISCELLANEOUS ELECTRICAL DEVICES

- A. Electric Actuators. All automatically controlled devices, unless specified otherwise elsewhere, shall be provided with electric actuators which shall be sized to operate their appropriate loads with sufficient reserve power to provide smooth modulating action or two-position action and tight close off as specified.
- B. Aquastats shall be line voltage strap on type with single pole, single throw switching. Switches shall have an adequate rating for the applied load. All wiring from aquastats to domestic recirculating pumps shall be by ATC contractor.

2.8. UNINTERRUPTIBLE POWER SUPPLY

- A. Furnish, size and install uninterruptible power supplies (UPS's) at all ATC panels.
- B. Provide all interlock and power wiring from U.P.S. to control panels as required such that all components are powered via the UPS. For hard-wired equipment furnished with pigtails/wire leads, e.g. control power transformers, splice pigtails/wire leads in junction box to a flexible cord with NEMA 5-15P Plug, which shall be plugged into the UPS.
- C. UPS's shall be sized for the ATC panel load and shall provide at least 10 minutes of full load power in the event of a power outage.
- D. UPS shall be furnished with plug and cord and shall be powered from power receptacle(s) in ATC panels.

2.9. DESKTOP WORKSTATIONS

- A. Description: A tower or all-in-one computer designed for normal use at a single, semipermanent location.
- B. Performance Requirements:
 1. Performance requirements may dictate equipment exceeding minimum requirements indicated.
 2. Energy Star compliant.

C. Personal Computer:

1. Minimum Processor Speed: 3 gigahertz (GHz).
2. RAM:
 - a). Capacity: 8GB.
 - b). Speed and Type: 1333 MHz, SDRAM.
3. Hard Drive:
 - a). Media: Solid state.
 - b). Number of Hard Drives: One.
 - c). Capacity: 250GB.
4. Optical Read and Write Drive:
 - a). Include with at least 2 MB of data buffer.
 - b). Type: SCSI CD-ROM Drive with Read/Write Capability.
 - c). Average access time of 150 ms or less.
5. At least four expansion slots.
6. Video Card:
 - a). Resolution: 1920 by 1200 pixels.
 - b). RAM: 4 GB.
 - c). Controller Speed: 4GHz.
7. Sound Card:
 - a). At least 128 voice wavetable synthesis.
 - b). Capable of delivering three-dimensional sound effects.
 - c). High-resolution 16-bit stereo digital audio recording and playback with user-selectable sample rates up to 48,000 Hz.
8. Network Interface Card: Include card with connection, as applicable.
 - a). 10-100-1000 base TX Ethernet with RJ45 connector port.
 - b). 100 base FX Ethernet with SC or ST port.

D. Wireless Ethernet, 802.11 a/b/g/n.

1. Optical Modem: Full duplex link for connection to optical fiber cable provided.
2. I/O Ports:
 - a). Two USB 3.0 ports on front panel, six on back panel, and three internal on motherboard.
 - b). One serial port.
 - c). One parallel port.
 - d). Two PS/2 ports.
 - e). One RJ-45.
 - f). One stereo line-in and headphone/line-out on back panel.
 - g). One microphone and headphone connector on front panel.
 - h). One IEEE 1394 on front and back panel with PCI-e card.

- i). One ESATA port on back panel.
- 3. Battery: Life of at least three years to maintain system clock/calendar and ROM, as a minimum.
- E. Keyboard:
 - 1. 101 enhanced keyboard.
 - 2. Full upper- and lowercase ASCII keyset, numeric keypad, dedicated cursor control keypad, and 12 programmable function keys.
 - 3. Wireless operation within up to 72 inches (1800 mm) in front of workstation.
- F. Pointing Device:
 - 1. Either a two- or three-button mouse.
 - 2. Wireless operation within up to 72 inches (1800 mm) in front of workstation.
- G. Flat Panel Display Monitor:
 - 1. Display:
 - a). Color display with 21 inches diagonal viewable area.
 - b). Digital input signal.
 - c). Aspect Ratio: 16 to 9.
 - d). Antiglare display.
 - e). Tilt adjustable base.
 - f). Energy Star compliant.
 - g). Resolution: 920 by 1200 pixels at 60 Hz.
 - h). Number of Displays: One.
- H. Speakers:
 - 1. Two, with individual controls for volume, bass and treble.
 - 2. Signal to Noise Ratio: At least 65 dB.
 - 3. Power: At least 4 W per speaker/channel.
 - 4. Magnetic shielding to prevent distortion on the video monitor.
- I. I/O Cabling: Include applicable cabling to connect I/O devices.

2.10. CENTRAL CONTROL AND MONITORING SYSTEM (CCMS) (HARDWARE DESCRIPTION)

A. General

- 1. The Facilities Management Control System (FMCS) shall be comprised of a network of various independent, Stand-alone Digital Controllers (SDC'S), Mechanical System Digital Controllers (MSDC's), Air Handler Digital Controllers (AHDC's), Unitary Digital Controllers (UDC's); together with Centralized Control Stations (CCS), and Centralized Host Stations (CHS) as specified, to provide centralized access and facility wide control functions. The SDC's, MSDC's, AHDC's, UDC's shall be interconnected in a communicating

network to provide facility wide access and sharing of information. A Gateway Digital Controller (GDC's) shall be provided to allow interface with third party microprocessor based control systems that are specified for integration within specification. A Local Area Network (LAN) shall be provided to interconnect SDC's for high-speed data transmission.

2. Specification Nomenclature

FMCS	Facility Management Control System
SDC	Stand-alone Digital Controller
MSDC	Mechanical System Digital Controller
AHDC	Air Handler Digital Controller
UDC	Unitary Digital Controller
HHOT	Hand Held Operator Terminal
GDC	Gateway Digital Controller
GP	Graphical Programmer
CHS	Central Host Station
CCS	Central Control Station
RPTR	Communications Repeater

B. Centralized Host Stations (CHS)

1. The FMCS shall include Centralized Host Stations. CHS's shall, in conjunction with the full compliment of Digital Controllers, provide the performance requirements within this specification. Each CHS shall include all hardware and software components to serve as a centralized facility operator station, providing color graphics, facility wide access, operator initiation of global control strategies, and centralized documentation.

The CHS shall be capable of simultaneously interfacing with the following:

- mouse pointing device
- two parallel printers
- high resolution VGA color graphics monitor
- seven auto answer/auto dial modems
- color inkjet printer
- two serial printers
- three FMCS LAN interface
- Alarm Graphic and Report FAX dial out service interface
- Mass storage tape system

As a minimum, the temperature control contractor shall provide the types and quantities of CHS, CCS, SDC, MSDC, AHDC, GDC, UDC, as required.

2. Computer

- a). The existing FMS computer located in the Maintenance Office shall be utilized with the new CCMS System if compatible with the same. If the selected ATC contractor cannot tie into the existing computer, then a new stand-alone computer shall be furnished.

- b). Coordinate IP address with Owners' I.T. Department for network connection. The CCMS must be fully networkable.
 - c). Provide fiber optic cable as required.
3. Operator Workstation: One PC-based microcomputer with minimum configuration as follows:
- a). Uninterruptible Power Supply: 2 kVa.
 - b). Operating System: Microsoft Windows – Latest Version
 - i. ASHRAE 135 Compliance: Workstation shall use ASHRAE 135 protocol and communicate using ISO 8802-3 (Ethernet) datalink/physical layer protocol.
 - ii. LonWorks Compliance: Control units shall use LonTalk protocol and communicate using EIA/CEA 709.1 datalink/physical layer protocol.
 - c). Printer: Color, ink-jet type as follows
 - i. Print Head: 4800 x 1200 dpi optimized color resolution.
 - ii. Paper Handling: Minimum of 100 sheets.
 - iii. Print Speed: Minimum of 17 ppm in black and 12 ppm in color.

C. Centralized Control Stations (CCS)

The FMCS shall include Centralized Control Stations, as required. CCS's shall, in conjunction with the network of SDC's and additional CCS components as required, provide the performance requirements within this section of the specification. Each CCS shall include all hardware and software components to serve as a centralized facility operator station, providing facility wide access, for review and modification of global control strategies, real time system monitoring, controller database editing or creation, and centralized documentation.

D. Local Area Networks

1. The LAN shall utilize packetized transmissions, CRC 16 error checking, and distributed error recovery. Single or multiple SDC failures shall not cause loss of communication between other LAN-connected SDC's.
2. LAN connected SDC's shall be provided with a communications watchdog to assure that an individual SDC cannot permanently occupy the LAN. If an SDC is determined to be monopolizing communications, it shall be automatically shut down and an exception reported to annunciate this fact.
3. The LAN shall employ a token passing, peer-to-peer convention, same as or similar to the industry standard format IEEE 802.4. The content of messages shall be the manufacturer's standard. The Local Area Network components shall be manufacturer's standard or available from third party vendors which utilize the same chip implementation as used by the manufacturer.
4. Industry standard ANSI, RS-485 Network Communication System, Lon, or Bacnet, or Equivalent shall be utilized.

a). Trunk Wiring Practices - General

The distributed communication network system shall consist of a multi-drop RS-485 bus architecture connecting SDC's, MSDC's, AHDC's, GDC's, and UDC's. The trunk shall consist of:

- i. A twisted pair of wires (24 awg) completely encased in continuous metallic conduit.
- ii. A twisted shielded pair of wires (24awg) with the shield grounded in accordance with the manufacturer's wiring practices.
- iii. Or a dual channel, 62.5 micron fiber cabling system with ST type connectors.

There shall be no power wiring, in excess of 30 VAC rms voltage, run in conduit with communications trunk wiring. In cases where power or signal wiring is run in conduit with trunk wiring, all communications trunk wiring and power wiring shall be run using separate twisted shielded pairs (24awg) with the shields grounded in accordance with the manufacturer's wiring practices.

b). Communication Transient Protection

- i. The manufacturer's catalog data sheet shall provide evidence that all FMCS products offered by the manufacturer are tested and comply with the standard for Transient Surge withstand capabilities for electrical devices ANSI C62.41, IEEE-587-1980, Categories A and B. Such testing shall have included power and communication trunk wiring. Compliance with IEEE-587 shall imply conformance with IEEE-472 transient standards based on the stated position of ANSI and IEEE regarding applicability of the rated standards.
- ii. In addition, at each building entry and exit point, the wire communications trunk wiring shall be protected with a transient surge protection device providing the minimal protection specifications of the General semiconductor, Model #422E device. Transient surge protection is not necessary if the communication trunk, external to the building, is fiber optic in nature.
- iii. The communications circuitry and input/output circuitry, of the SDC's, MSDC's, and AHDC's shall provide protection against a 1000 volt, 3 amp transient signal, directly applied to the communication or input/output terminations. The manufacturer's catalog data sheet shall provide evidence of conformance with this requirement. Systems not complying with this requirement shall provide equivalent protection external to the FMCS controller. Protection shall be provided for the individual

communications and input/output terminations for each FMCS controller. Submittal documentation shall clearly define how this requirement will be met and how the external protection will not affect the performance of the controllers.

c). RS-485 Trunk Distance and Topology

The manufacturer's RS-485 trunk shall provide operation over end to end linear distances of 4000 feet for wire connections and 6,500 feet for fiber optic connections, without repeaters, at communication data rates of up to 64 kbps. The trunk may be extended up to 20,000 feet through the use of wire repeaters or 80,000 feet through the use of fiber optic repeaters.

At data rates of up to 19.2 kbps, the trunk distance shall be extendible to distances of up to 20,000 feet using RS-485 communication wire or fiber optic repeaters. A repeater shall be used every 4,000 feet of linear distance for wire or every 6,500 feet for fiber optics. Repeating devices shall contain separate LED indication for each communication interface trunk to indicate proper operation of the repeater as well as the communications trunks.

Contractors shall provide devices which are of FMCS control system manufacturer's design.

It shall be possible for the trunk to be "T" feed or "starred", at any location using a repeater, to facilitate the installation. Systems which do not provide this capability shall provide a trunk riser diagram showing end to end distances and locations of system topology necessary to meet the trunk diagram shown on the plans.

d). Fiber Optic Communication Trunk

The temperature control contractor shall provide a dual channel fiber optic data link, as required, to minimize the effects of transient surges caused by lightning or external EMI generating equipment. The data link shall be comprised of a single duplex cable containing two fibers (transmit and receive), of 62.5 micron construction, to accommodate data rates of up to 64 kbps.

The fiber optic trunk shall be connected to SDC devices using manufacturer's standard RS-485 to fiber optic data link modem. Repeating devices shall contain separate LED indication for each communication interface and the fiber modem, to indicate proper operation of all aspects of the device. Fiber modem devices shall be tested and conform with transient surge withstand tests for electrical devices, ANSI C62.41 IEEE-587 Categories A and B. Manufacturer's data sheet shall provide evidence of compliance with this requirement. Manufacturer's products which do not meet this minimum performance requirement shall not be acceptable.

Systems which require a special gateway controller to accommodate the fiber optic trunks, shall provide such a controller per point where the

fiber optic cable enters and leaves the building. Gateway controllers shall not inhibit transfer of point data values between SDC controllers throughout the LAN. Such inhibitive systems shall not be acceptable.

In lieu of the above two options, the contractor may provide a fiber optic link to each SDC controller within the LAN. All controllers shall have access to the fiber optic link for LAN.

Fiber optic cable shall be fully tested and terminated by the temperature control contractor.

E. Standalone Digital Controllers (SDC)

1. General

Standalone Digital Controllers (SDC) shall be 16 bit microcomputer based, utilizing a multi-tasking, multi-user operating system.

The SDC controllers shall permit the simultaneous operation of all control, communication facilities management and operator interface software, as programmed by the Contractor or User. Modification of the on-board SDC controller database shall be performed on-line using the built-in or HHOT interface. Systems which require the SDC to be removed from service while DDC control sequences are modified shall not be acceptable.

SDC controllers shall utilize true floating point arithmetic capabilities. To accommodate totalization of large totalized values, SDC's with reporting capability shall support the calculation, accumulation and display of values within the range of +/-10 to the 10th power.

2. Database and Memory Back-up

All programming defining the functions to be performed by the SDC, including but not limited to application programs and point database within each SDC, shall be protected from loss due to power failure for a minimum of six months. Systems providing non-volatile memory for these functions are preferred. Systems not providing non-volatile memory shall provide a system rechargeable battery backup system sufficient to provide protection for the specified 6 month period. Systems not in compliance shall provide for uninterrupted power to each SDC.

3. Service Ports

SDC controllers shall be equipped with a minimum of one operator service port for the connection of a HHOT. The service port shall be either a built-in RS-232 data terminal port or an RJ-11 type jack which connects to the manufacturer's standard HHOT.

Connection of a service device, to a service port, shall not cause the SDC controller to lose communications with its peers or other networked device controllers.

The service port shall allow utilization of the same HHOT from any location. The same

HHOT shall be utilized for any SDC, MSDC, AHDC, or UDC Systems which utilize more than one variety of HHOT shall not be acceptable.

4. Display and Readout Capability

The SDC controller shall provide manufacturer's standard display and readout capability.

5. Manual/Auto Control and Notification

The SDC controller shall provide commanded override capability from the HHOT or the built-in operator interface. Such overrides shall be annunciated to the CHS's. Such overrides shall be valid as long as power is applied to the controller.

Manual service overrides, such as Hand/Off/Auto switches, shall be provided as indicated on the drawings. Such overrides shall be located at the controller device location and conform with OSHA Manual lockout regulations, as appropriate, for safety reasons. SDC indication of such manual override actions shall be provided as feedback status indication points shown on the drawings, in conjunction with the application programs within the SDC. Systems which provide built-in H/O/A switching devices with integral feedback shall provide external manual service overrides, as indicated, to comply with OSHA manual lockout regulations. H/O/A switches remotely located at the SDC controller are not acceptable.

6. Adjustments

Every control panel shall provide adjustments for the functions specified. In general, adjustments shall be provided for all set points used by controllers within each control panel. In addition, adjustments shall be provided for throttling ranges, mixed air damper minimum positions, and other items as specified. Adjustments shall be integral to each individual SDC. The built-in operator interfaces shall allow the easy execution of the adjustment through named identifiers within the SDC. From a single SDC user interface, any other SDC shall be accessible and full adjustment capabilities shall be provided.

7. Sensing and Control Outputs Requirements

7.1. Sensing

All sensing inputs shall be provided via industry standard signals. Temperatures, humidities, differential pressure signals, and other signal inputs shall be one of the following types:

0-20 mA

4-20 mA

0-5 VDC

0-12 VDC

1000 ohm platinum (at $0\{SYMBOL 176\}^{\circ}C, 2.62\text{ ohms}/C$)

1000 ohm Balco ($2.2\text{ ohms}/\{SYMBOL 176\}^{\circ}F$)

10 k ohm Thermistor (at $25\{SYMBOL 176\}^{\circ}C/77\{SYMBOL 176\}^{\circ}F$)

Custom, definable input signals (accept sensor inputs from RTD devices,

other than those of the manufacturer).

All signal inputs shall be compatible with the controllers used, and with the requirements for readout of variables in true scaled engineering units as specified.

b). Control Outputs

i. On/Off Outputs

Control panel shall internally provide test points for the circuit driving the equipment contactor, for the purpose of troubleshooting the 120 VAC or 240 VAC circuit to the contactor. All such relays or digital output modules shall provide a pilot light or LED display of the same status. On/Off output modules shall be of the modular construction that can be easily and quickly replaced, on an individual basis, if the module were to be damaged.

i. Modulating Outputs

Modulating outputs shall be industry standard 0-5 VDC, or 0-12 VDC with definable output spans to adapt to industry available control products. Milliamp outputs of 0-20 mA or 4-20 mA are also acceptable. Drive open/Drive closed type modulating outputs are acceptable provided that they also comply with the following requirements.

All modulating outputs shall provide within the control panel, a meter gauge, or display indication via on board display or HHOT, the commanded position signal for the actuating device. This meter, gauge, or display must provide either a 0-100 percent position indication, or read out directly in the engineering unit of the signal being used. Drive open/Drive closed type controllers shall include sufficient components and control algorithms to comply with this requirement. In the case of Drive open/closed technology, position feedback shall be provided to insure positive indication that the control device is at the commanded position.

F. Mechanical System Digital Controllers (Msdc's)

1. General

- a). Controls shall be microprocessor based, Mechanical System Direct Digital Controllers (MSDC's). MSDC's shall be provided for air handling units, central pump systems and other applications as required. MSDC's shall be based on a minimum 16 bit microprocessor working from software program memory which is physically located in the MSDC. The application control program shall be resident within the same enclosure as the input/output circuitry which translates sensor signals. All input/output signal conversion shall be performed through a minimum of a 12 Bit A to D converter. All input/output points shall be

universal in nature allowing their individual function definition to be assigned through the application software. All unused input/output points must be available as universally definable at the owner discretion. If input/output points are not fully universal in nature, unused points must be equal in quantity between Analog Input, Digital Input, Analog Output, Digital Output.

Contractor shall provide a minimum of one MSDC controller per mechanical system, as shown on the drawings.

The BAS contractor shall provide and field install all MSDC's specified under this section. Mechanical Equipment manufacturers desiring to provide MSDC type controls as factory mounted equipment, shall provide a separate bid for their product less all controls, BAS/Temperature Control Contractor.

- b). All input/output signals shall be directly hardwired to the MSDC. Trouble shooting of input/output signals shall be easily executed with a volt-ohm-milli-amp meter (VOM). As a result of this intent, it is specified that power line carrier systems, or other systems which command multiple outputs over a single pair of wires, shall not be used.
- c). MSDC shall be in continuous direct communication with the network which forms the facility wide Building Automation System (BAS). The MSDC's shall communicate with the SDC at a baud rate of not less than 19,200 baud.

2. Non-Volatile Memory

- a). All control sequences programmed into the MSDC shall be stored in non-volatile memory, which is not dependent upon the presence of a battery to be retained. Power failures shall not cause the MSDC memory to be lost, nor shall there be any need for batteries to be recharged or replaced to maintain the integrity of the controller database. The MSDC shall allow for the creation of unique application control strategies. Systems that allow selection of sequences from the library or table are not acceptable.
- b). All control sequences shall be fully field programmable at the MSDC controller, allowing for the creation or editing of an application sequence of operations.
- c). Each MSDC shall be provided with manufacturer's standard built-in Operator Interface.
- d). The MSDC shall allow for internal processing and reporting of user defined Time of Day Schedules, Alarms, Trend Reports, Run Time Totalization, Energy Utilization Reports, Application Program Documentation and interface with a peripheral device such as an autodial/autoanswer modem, a VT-100 Display Terminal, or a serial printer.

Systems not providing the above functionality at the MSDC are not acceptable and shall utilize an SDC in place of the MSDC.

- e). The MSDC shall provide LED indication of transmit/receive communications performance as well as for the proper/improper operation of the controller itself.
- f). The MSDC shall be provided with a battery backed time clock that is capable of maintaining the time of day and calendar for up to thirty days without loss of setting. The battery for the time clock shall be field replaceable by the customer. Integral daily, weekly, holiday and special event scheduling shall be provided, such that all schedules can be custom tailored to the facility. Predefined schedules, with set quantities of on/off cycles are not acceptable.

3. Controller Location

- a). To simplify controls, mechanical service and troubleshooting, the MSDC shall be mounted directly in or on the control compartment of the mechanical system. The MSDC shall be provided in a NEMA 1 enclosure to accommodate direct mounting on the equipment to be controlled. The MSDC shall be constructed in a modular orientation such that service of the field components can be performed quickly and easily. The modular construction should limit the quantities of printed circuit boards to a maximum of three. When required to replace a printed circuit board, it shall not be necessary to disconnect any field wiring. The MSDC shall allow for the creation of, unique, application control strategies. Systems that allow selection of sequences from a library or table are not acceptable. This shall allow all controls maintenance and troubleshooting to be made while at the unit location. MSDC shall be directly wired to sensory devices, staging relays or modulating valves for heating and cooling.
- b). For compatibility to the environment of the mechanical systems, MSDC shall have wide ambient ratings. MSDC shall be rated for service from -40 Deg F (Degrees Fahrenheit) to 140 Deg F.
- c). Contractor shall submit description of location for the MSDC's on all mechanical equipment.

G. Air Handler Digital Controller (AHDC)

1. General

- a). Controls shall be microprocessor based, Air Handler Digital Controllers (AHDC's). AHDC's shall be provided for air handling units, kitchen vent units, make-up air units, and other applications as required. AHDC's shall be based on a minimum 16 bit microprocessor working from software program memory which is physically located in the

AHDC. The application control program shall be resident within the same enclosure as the input/output circuitry which translates the sensor signals. All input/output signal conversion shall be performed through a minimum of a 10 bit A to D converter. All input points shall be universal in nature allowing their individual function definition to be assigned through the application software. All unused input points must be available as universally definable at the discretion of the owner. If the input points are not fully universal in nature, unused points must be equal in quantity between Analog Inputs and Digital Inputs.

Contractor shall provide a minimum of one AHDC controller per air handling system as shown on the drawings.

The BAS contractor shall provide and field install all AHDC's specified under this section. Mechanical equipment manufacturers desiring to provide AHDC type controls as factory mounted equipment, shall provide a separate bid for their products less all controls, actuators, valve assemblies and sensors, which are specified to be provided by the BAS/Temperature control contractor.

- b). All input/output signals shall be directly hardwired to the AHDC. Troubleshooting of input/output signals shall be easily executed with a volt-ohm meter (VOM). As a result of this intent, it is specified that power line carrier systems, or other systems which command multiple outputs over a single pair of wires, shall not be utilized.
- c). AHDC's shall be in continuous direct communication with the network which forms the facility wide Building Automation System. The AHDC's shall communicate with the SDC at a baud rate of not less than 19,200 baud.

2. Non-Volatile Memory

- a). All control sequences programmed into the AHDC shall be stored in non-volatile memory, which is not dependent upon the presence of a battery, to be retained. Power failures shall not cause the AHDC memory to be lost, nor shall there be any need for batteries to be recharged or replaced to maintain the integrity of the controller database. The AHDC shall allow for the creation of unique application control sequences. Systems that only allow selection of sequences from a library or table, are not acceptable.
- b). All control sequences shall be fully programmable at the AHDC, allowing for the creation and editing of an application control sequence, while at the unit.
- c). The AHDC shall be provided with an interface port for the HHOT. The interface port shall allow the HHOT to have full functionality as described. From the interface port, the HHOT shall be able to directly access any AHDC, UDC or VAVDC in the network.

- d). The AHDC shall provide an input/output point trending utility that is capable of accumulating 48 analog point samples and 10 digital point samples, per Input/Output point. Each sample shall be taken on a user defined interval, ranging from 1 second to 255 hours per sample. The digital readings shall be on a change of state occurrence for the digital points. All samples shall be recorded with the engineering units for the value, along with a time and date identifier for each sample taken. The samples shall be protected against loss due to power interruptions through a battery or capacitor backup method for a minimum of 30 days.

Systems unable to provide the above capability shall provide for the individual Input/Output point trending at the SDC. Specifics as to how each AHDC point will be trended, at the SDC, shall be provided in the submittal documents. Included in the explanation shall be the sample intervals, the memory allocation in the SDC and the number of AHDC's per SDC that can be expected.

- e). The AHDC shall provide LED indication of transmit/receive communications performance, as well as for the proper/improper operation of the controller itself.
- f). The AHDC shall be provided with a battery backed time clock that is capable of maintaining the time of day and calendar for up to thirty days, upon loss of power to the AHDC, without loss of setting. The battery for the time clock shall be replaceable by the customer. The AHDC shall be provided with integral time schedules; as a minimum, two seven day schedules with eight on/off periods per day shall be provided. Holiday override of weekly schedules shall be provided for pre-scheduling of holidays, for the year in advance.

3. Controller Location

- a). To simplify controls and mechanical service troubleshooting, the AHDC shall be mounted directly in or on the controls compartment of the air handling system. The AHDC shall be provided in a NEMA 1 enclosure to accommodate direct mounting on the equipment to be controlled. The AHDC shall be constructed in a modular orientation such that service of the failed components can be done quickly and easily. The modular construction should limit the quantities of printed circuit boards to a maximum of two. All logic, control system, power supply and input/output circuitry shall be contained on a single plug-in circuit board. When required to replace a printed circuit board, it shall not be necessary to disconnect any field wiring. This shall allow all controls maintenance and troubleshooting to be made while at the air handling unit. The AHDC shall be directly wired to sensory devices, staging relays or modulating valves for heating and cooling.
- b). For compatibility to the environment of the air handling unit, AHDC's shall have wide ambient ratings. AHDC's shall be rated for service from -40 Deg F (Degrees Fahrenheit) to 140 Deg F.

- c). Contractor shall submit description of location of AHDC's on all mechanical and air handling equipment.

H. Unitary Digital Controller (UDC)

1. General

- a). Controls shall be microprocessor based Unitary Digital Controller (UDC's). UDC's shall be provided for equipment as necessary. UDC's shall be based on a minimum 16 bit microprocessor working from software program memory which is physically located in the UDC. The application control program shall be resident within the same enclosure as the input/output circuitry which translates the sensor signals. All input/output signal conversion shall be performed through a minimum of a 10 bit A to D converter.

Contractor shall provide a minimum of one UDC controller per unitary system as required.

The BAS contractor shall provide and install all UDC's specified under this section. Mechanical equipment manufacturers desiring to provide UDC type controls as factory mounted equipment, shall provide a separate bid for their products less all controls, actuators, valve assemblies and sensors, which are specified to be provided by the BAS/Temperature control contractor.

- b). All input/output signals shall be directly hardwired to the UDC. Troubleshooting of input/output signals shall be easily executed with a volt ohm milli-amp meter (VOMA). As a result of this intent, it is specified that power line carrier systems, or other systems which require multiple outputs over a single pair of wires, shall not be utilized.

- c). UDC's shall be in continuous, direct communication with the network which forms the facility wide building automation system. The UDC's shall communicate with the SDC at a baud rate of not less than 9,600 baud.

2. Non-Volatile Memory

- a). All control sequences programmed into the UDC shall be stored in non-volatile memory, which is not dependent upon the presence of a battery, to be retained. Power failures shall not cause the UDC memory to be lost, nor shall there be any need for batteries to be recharge or replaced to maintain the integrity of the controller database. The UDC shall allow for the creation of unique application control sequences. Systems that allow only selection of sequences from a library or table are not acceptable.
- b). All control sequences shall be fully configurable at the AHDC, allowing

for the creation and change of a sequence while at the unit.

- c). The UDC shall be provided with the ability to interface with the HHOT. The interface port shall be provided at the wall sensor or within the unitary equipment, as specified on the plans. The interface port shall allow the HHOT to have full functionality as described hereinbefore of this specification. From the interface port, the HHOT shall be able to directly access any AHDC, UDC, [or VAVDC] in the network.
- d). The UDC shall provide an input/output point trending utility that is capable of accumulating 48 analog point samples and 10 digital point samples per Input/Output point. Each sample shall be taken on a user defined interval, ranging from 1 second to 255 hours per sample. The digital readings shall be on a change of state occurrence for the digital points. All samples shall be recorded with the engineering units for the value, along with a time and date identifier for each sample taken.

Systems unable to provide the above capability shall provide for the individual input/output point trending at the SDC. Specifics as to how each UDC point will be trended at the SDC, shall be provided in the submittal documents. Included in the explanation shall be the sample intervals, the memory allocation in the SDC and the number of UDC's per SDC that can be expected.

- e). The UDC shall provide LED indication of transmit/receive communication performance, as well as for the proper/improper operation of the controller itself.
3. Controller Location
- a). To simplify controls and mechanical service troubleshooting, the UDC shall be mounted directly in the controls compartment of the unitary system. The UDC shall be provided with a sheet metal or polymeric enclosure that is constructed of material allowing for the direct mounting within the primary air stream, as defined by UL-465. The direct mounting shall allow all controls maintenance and troubleshooting to be made while at the unitary equipment. The UDC shall be directly wired to sensory devices, staging relays or modulating valves for heating and cooling.
 - b). For compatibility to the environment of the unitary equipment, UDC's shall have wide ambient ratings. UDC's shall be rated for service from 32 Deg F (Degrees Fahrenheit) to 140 Deg F.
 - c). Contractor shall submit description of location of UDC's on all mechanical and unitary equipment.

I. Gateway Digital Controller (GDC)

1. General

- a). Controls shall be microprocessor based, Gateway Digital Controllers (GDC's). GDC's shall be provided for the purpose of integrating microprocessor based, communicating, direct digital control systems from vendors other than the primary, selected controls manufacturer. GDC's shall be based on a minimum 16 bit microprocessor working from software program memory which is physically located in the GDC. All communications interface control programs shall be resident within the GDC.

The BAS contractor shall provide and field install all GDC's specified under this section. Any interface requirement beyond a two wire communications wire link, shall be provided by the equipment manufacturer supplying the non-primary or third party microprocessor based, communicating, direct digital controllers.

- b). All GDC's shall exist at the LAN level with the SDC's. The GDC's shall possess all capabilities described under the SDC section while additionally providing the interface to the third party systems described above. The GDC's shall communicate with the third party controllers at the highest possible baud rate offered by the third party system. As a minimum, 9,600 baud communications shall be utilized.

- c). All control sequences programmed into the GDC shall be stored in non-volatile memory, which is not dependent upon the presence of a battery, to be retained. Power failures shall not cause the GDC memory to be lost, nor shall there be any need for batteries to be recharged or replaced to maintain the integrity of the controller database. The GDC shall allow the standard database information from the third party system to be integrated in standard FMCS data formats, allowing for the creation of unique application control sequences. Systems that only allow selection of data and sequences from a library or table, are not acceptable.

- d). Each GDC shall be provided with manufacturer's standard built-in operator interface.

- e). The GDC shall provide Alarming, point trending and Energy report generation capabilities. Alarming points shall be uniquely definable, with multiple alarms assignable to a single point. Such alarm shall be provided with a unique 80 character message. Systems utilizing an alarm message library, shall describe the size of the library and verify how all alarming within the GDC will be guaranteed unique 80 character messages.

The quantities of trended point values shall be limited only by total controller memory space. If necessary, a GDC may be dedicated fully to a trending task, allowing all controller memory to be available for the trend storage. Each unique trend report shall contain a minimum of 4 different points and a minimum of 128 samples per point. Trending frequency for each report shall be operator definable from a sample once a second to a sample once every 24 hours. Trend reports shall be internally formatted by the GDC and shall be reportable directly to a

serial printer, a VT-100 display terminal, a CCS, CHS or any other device capable of receiving a formatted ASCII data file.

The energy reports shall not be limited in quantities only by available memory within the GDC. Each Energy Report shall be fully formatted and reportable to a serial printer, a VT-100 display terminal, a CCS, a CHS or any other device capable of receiving a formatted ASCII data file. As a minimum, each Energy Report shall provide a daily report and a monthly report with summary information such as outside air temperature, outside air humidity, total energy consumed and degree day calculations.

- f). The GDC shall be provided with a battery backed clock that is capable of maintaining the time of day and calendar for up to thirty days, upon loss of power to the GDC, without loss of settings. The battery for the time clock shall be field replaceable by the customer.

2.11. SYSTEM SOFTWARE DESCRIPTION

A. General

1. Contractor shall provide all software for a complete and operational system as described herein. Software shall include manufacturer's standard multi-tasking, multi-user operating system for operator consoles and controllers, network communication software for dial up and hard trunk applications, operator man-machine interface software, control application software and all other software necessary to provide the functions specified herein.
2. System software shall be as manufactured by Siebe Environmental Controls, Johnson Controls, Honeywell, Siemens, Alerton, Reliable Controls, Schneider Electric, Advanced Power, Trane, or approved equal.

2.12. EXCEPTION REPORTING SEQUENCES

A. Alarm/CCS Reports

1. For those digital points indicated on the drawings, the Contractor shall provide a unique change-of-state alarm message of up to 70 characters. The message shall report to all devices assigned to the alarm class.
2. For those points indicated on the drawings which are designated as interrupt priority, the Contractor shall provide an interrupting process display at the CHS location which displays the current conditions for the operator.

In addition, the CHS computer shall automatically send a picture of the process graphic display to the remote locations specified on the drawings as receiving facsimile copies of interrupting alarms.

3. For those points designated in paragraph 3 above, the FMCS shall also send a history log to the system report printer of the immediate prior history of the

points causing the interrupt priority. This log shall contain 1 minutes samples of the previous 15 minutes of operation.

4. For those points on the drawings designed as Hard Facts points, the Contractor shall provide an alarm message to a remote facsimile location designated by the Owner. The FMCS system shall provide at the remote location, a facsimile printout showing location, time/date of alarm and alarm message of the point. For interrupt priority fax alarms, the remote facsimile machine shall receive a hard copy of the interrupt process screen showing on-line dynamic data values of the current conditions.

B. Off Hours Exception Reporting

The Owner shall specify up to five sites to which off hours exceptions shall be auto-dialed and reported. This shall allow the owner to assign off hour exception responses to various facility personnel as necessary. Selection of the sites to be dialed can be programmed by the Owner, and set to change automatically per time of day and day of week.

2.13. MONITORING SYSTEM, SENSORS AND WIRING

A. Sensors and other Devices for Input/Output Summary Schedule:

1. Provide all necessary sensors, relays, panels, conduits and wire for the points indicated in the input/output summary as shown on the contract drawings.
2. Analog sensing elements for remote indication shall be independent of local sensors used for local control loops.
3. Temperature sensors shall be Resistance Temperature Detector (RTD) type of 1000 ohm base. Space (60-90 degrees F); Duct/Well (-30-250 degrees F); Averaging Duct (-30-225 degrees F) or as required under Division 26.
 - a). Space temperature sensors shall be provided with blank commercial type locking satin chrome covers.
 - b). Duct temperature sensors shall be rigid stem or averaging type as specified in the sequence of operation. Water sensors shall be provided with a separable copper, monel or stainless steel well. Outside air wall mounted sensors shall be provided with a sun shield.
 - c). The dew point sensor shall employ a non-reactive organic bobbin material to give precise dew point readings with accuracy of not more than ± 1.5 degrees F. The dew point sensor shall incorporate an integral draft shield as part of the instrument for air velocities in excess of 50 feet per minute. The dew point sensor shall operate over a minimum dew point temperature range suitable to application.
4. Relative humidity sensors shall be capacitance type with 10 percent to 90 percent range. Duct mounted humidity sensors shall be provided with a sampling chamber. Wall mounted sensors shall be provided with covers identical to temperature sensors. Space 10 percent -90 percent RH; Duct 10

percent - 90 percent RH.

5. All wall mounted temperature sensors, humidity sensors, and CO₂ sensors shall be installed with stainless steel wire guard. Set point adjustment shall be achievable without removing the wire guard.
6. Differential and Static Pressure Sensors and Switches
 - a). Fan proof-of-flow switches shall be U.L. listed adjustable set point and differential pressure type. Switches shall be piped to fan discharge except where fans operate at less than one inch WG, they shall be piped across the fan. For fractional horsepower and non-ducted fans, relays or auxiliary contacts may be used. Maximum pressure rating shall be at least 10 inches WG. with .05-12 inch W.C. range.
 - b). Pump proof-of-flow switches shall be U.S. listed adjustable differential pressure or flow type as specified in the sequence of operation or data point summary. Devices shall be 150 psi rated except chilled water flow switches shall be provided with totally sealed vapor tight switch enclosure on 300 psi body. Differential pressure switches shall have valved manifold for servicing, and a range of 3 psi-150 psi.
 - c). Air flow and static pressure analog sensors shall be high accuracy suitable for the low velocity pressures to be encountered, be selected for approximately 50 percent overrange, and have a 4 to 20 ma output. These differential pressure sensors shall be connected to the air flow measuring station with valved lines for testing and calibration, and shall have adjustments for zero and span. 5 inch W.C. range.
 - d). Water flow analog sensors shall be provided complete with flow element and shall be an all solid state precision industrial type with stainless steel meter body, maximum error of no more than .5 percent or span, and 4 to 20 ma output. Sensor shall be rated for 250 psi minimum and installed in strict accordance to the manufacturer's instructions complete with three-valve manifold for calibration and maintenance.
7. Overall system accuracy, including electronic analog sensing elements, shall be as follows:
 - a). Air: Plus or minus 1.0 degrees F temperature, plus or minus 2.5 percent r.h., plus or minus 2.0 percent static pressure.
 - b). Water: Plus or minus 0.7 degrees F over full scale range for water points, plus or minus 1.0 degree F for others.
 - c). Proof of fan or pumps operating status, or alarm conditions shall be through positive feedback from differential pressure switches across fan or pump. Auxiliary dry contacts may be used for proof of fans or pumps if the motors are fractional H.P., and other non-ducted fans.

8. Digital inputs from devices with isolated, dry type contacts (no grounds, no voltage) of either normally open (N.O.) or normally closed (N.C.) configuration shall be provided. Live contact inputs, those that have voltage present, shall be provided with isolating devices to meet dry contact requirements.
9. Liquid flow data shall be received and transmitted by commercial grade instrument similar in quality to Honeywell 411, Rosemount, Foxboro, MAMAC Systems or approved equal, type differential pressure transmitter. Pulse type data sensors shall not be acceptable. Speed response of differential pressure transmitters shall be at least 500 milliseconds. Maximum error signal shall be +/- 1 foot.
10. Start-stop relay module shall contain relays for start-stop function at the remote point, with relays mounted and factory wired to numbered terminal strips.
11. Outage Devices:
 - a). Control Relays: Control relay contacts shall be rated for the application, with a minimum of two sets of Form C contacts, enclosed in a dustproof enclosure. Relays shall have silver-cadmium contacts with a minimum life span rating of one million operations. Operating time shall be 20 milliseconds or less, with release time of 10 milliseconds or less. Relays shall be equipped with coil transient suppression limiting transients to nondamaging levels.
 - b). Time Delay Relays: Time delay relay contacts shall be rated for the application with a minimum of two sets of Form C contacts enclosed in a dustproof enclosure. Relays shall have silver-cadmium contacts with a minimum life span rating of one million operations. Relays shall be equipped with coil transient suppression devices to limit transients to nondamaging levels. Delays contact opening or closing shall be adjustable from one to 60 seconds with a minimum accuracy of plus or minus 2 percent of setting.
 - c). Latching Relays: Latching relay contacts shall be rated for the application with a minimum of two sets of Form C contacts enclosed in a dustproof enclosure. Relays shall have silver-cadmium contacts with a minimum life span rating of one million operations. Operating time shall be 20 milliseconds or less, with release time of 10 milliseconds or less. Relays shall be equipped with coil transient suppression devices to limit transients to nondamaging levels.
 - d). Reed Relays: Reed relays shall be encapsulated in a glass-type container housed in a plastic or epoxy case. Contacts shall be rated for the application. Operating and release times shall be one millisecond or less. Reed relays shall have a minimum life span rating of 10 million operations.
 - e). Contactors: Contactors shall be of the single-coil, electrically operated, mechanically held type. Positive locking shall be obtained without the

use of hooks, latches, or semi-permanent magnets. Contacts shall be double-break silver-to-silver type protected by arcing contacts. Number of contacts and ratings shall be selected for the application. Operating and release times shall be 100 milliseconds or less. Contactors shall be equipped with coil transient suppression devices to limit transients to nondamaging levels.

- f). Solid-State Relays: Input-output isolation shall be greater than 1000 megohms with a breakdown voltage of 1500 V rms or greater at 60 Hz. The contact life shall be 10 million operations or greater. The ambient temperature range shall be minus 20 degrees to plus 140 degrees F. Input impedance shall not be less than 500 ohms. Relays shall be rated for the application. Operating and release times shall be one millisecond or less. Transient suppression shall be provided as an integral part of the relay to limit transients to nondamaging levels.

12. Audible Alarm:

- a). All alarms shall annunciate on the ATC system front end computer and via pagers.

2.14. MAKE-UP WATER FLOW METER/ALARM

- A. In-line T-mounted Flowmeter: Made for installation between pipe flanges; measures flow directly in gallons per minute. As manufactured by Aaliant, Badger, Hersey, Kele, Data Industrial or approved equal.

1. Construction: Stainless steel body, with integral transmitter and direct - reading scale.
2. Pressure rating: 400 psig maximum.
3. Temperature rating: 221 F maximum
4. Display: Two lines; alphanumeric characteristic each. Visual instantaneous rate of flow, with register to indicate total volume in gallons.
5. Output: Two simultaneous outputs; 4 to 20 mA, two-wire, pulse.
6. Transmitter: Universal flow transmitter with pulse output (totalization) to convert digital pulses to totalized gallons.
7. Electronic Housing: NEMA4, 3/4 NPT conduit connection, epoxy coated aluminum.
8. Accuracy: Plus or minus 1 percent of reading.
9. Key Pad: Setting of recalibration, engineering units, data logging sample time, alarms, response time.

- B. Power and control wiring to be furnished and installed under this Section of Division 23.

2.15. FLOW MEASURING STATIONS

- A. Furnish and install an Onicon Model F-1210, Hersey, Kobold or approved equal dual turbine insertion flow sensor complete with hot tap full port ball valve and installation

hardware. The dual turbine element shall have counter rotating axial turbine elements, each with its own rotational sensing system, and an averaging circuit to reduce measurement errors due to swirl and flow profile distortion. Paddle type rotors will not be acceptable. Rotational sensing of each turbine shall be accomplished electronically by sensing impedance change and not with magnetic or photo-electric means. Each sensor shall be individually calibrated and tagged accordingly against the manufacturers primary standards which must be accurate to within 0.1 percent and traceable to the U.S. National Institute of Standards and Technology (NIST).

- B. The sensor shall have a maximum operating pressure of 400 PSI, maximum operating temperature of 220 degrees F (optional 300 degrees F) and a pressure drop of less than 1 PSI at 17 feet per second flow rate. Flow sensor shall have 100:1 turn down ratio. Accuracy shall be ± 2 percent of actual reading from 0.4 feet per second to 20.0 feet per second.
- C. The sensor shall have integral analog outputs of 0-10 VDC and 4-20 mA current output for connection to the Central Control System. The sensor shall also include three integral frequency outputs, (top turbine, bottom turbine, average frequency) for diagnostic purposes and for connection to peripheral equipment (local display, BTU meter, etc.). All outputs shall be linear with flow rate.
- D. The turbine elements shall be made of polypropylene with sapphire jewel bearings and tungsten carbide shafts. The flow sensor shall be constructed of 316 stainless steel with an aluminum electronics enclosure and gasketed cover.
- E. Install flow measuring stations with minimum straight lengths of pipe upstream and downstream from sensor as prescribed by manufacturer's written instructions.
- F. Make electrical connections to power supply and interlock with ATC system.
- G. Calibrate meters to manufacturers requirements.

2.16. FIELD INSTALLED CONDENSATE OVERFLOW SWITCHES

- A. Condensate overflow switches must be tested to comply with U.L. 508.
- B. Interlock condensate overflow switches to shut-down cooling equipment and alarm on ATC system where overflow condition exists.

2.17. CO₂ SENSORS/TRANSMITTER

- A. Furnish and install wall mount CO₂ sensor/transmitters at locations indicated on floor plans. CO₂ sensor/transmitter shall be model CD-W00 as manufactured by Johnson Controls or approved equal.
- B. Measuring Range: 0 to 2,000 ppm CO₂.
- C. Response Time: 1 minute
- D. Output Signal: As required by ATC system

- E. Max power consumption: Less than 2 watts.
- F. Listing: U.L. Listed
- G. Accessories: Mounting Kit, Transformer required.
- H. Where installed in gyms, auxiliary gyms, toilet rooms, locker rooms, cafeteria and corridors install heavy duty stainless steel guards.

2.18. FLOW SWITCHES

- A. Furnish and install piping flow switches at all water cooled equipment (ERV units, VRV compressor units and additionally as shown on the Contract Documents.
- B. Flow switches shall be Vaporproof, single pole double throw type as manufactured by McDonald and Miller or approved equal.
- C. Enclosure shall be NEMA 4X rated for 150psig and suitable for temperatures between 0°F and 150°F with 1 inch MPT connection for upright mounting in horizontal pipe.
- D. Size and select flow switches based on pipe size, insertion depth, pipe material and expected flow rate. Interlock status with ATC system.

PART 3. EXECUTION

3.1. GENERAL

- A. The Automatic Temperature Control System and Central Control and Management System, shall be designed, installed, and commissioned in a turnkey fully implemented and operational manner.

3.2. BMS SPECIFIC REQUIREMENTS

A. Graphic Displays

1. Provide a color graphic system flow diagram display for each new and existing system with all points as indicated on the point list. All terminal unit graphic displays shall be from a standard design library.
2. User shall access the various system schematics via a graphical penetration scheme and/or menu selection.

B. Custom Reports:

1. Provide custom reports as required for this project:

3.3. WORKSTATION INSTALLATION

A. Desktop Workstations Installation:

1. Install workstation(s) at location(s) directed by Owner.
2. Install multiple-receptacle power strip with cord for use in connecting multiple workstation components to a single duplex electrical power receptacle.
3. Install software on workstation(s) and verify software functions properly.
4. Develop Project-specific graphics, trends, reports, logs and historical database.
5. Power each workstation through a dedicated UPS unit. Locate UPS adjacent to workstation.

B. Portable Workstations Installation:

1. Turn over portable workstations to Owner at Substantial Completion.
2. Install software on workstation(s) and verify software functions properly.

C. Color Graphics Application:

1. Use system schematics indicated as starting point to create graphics.
2. Develop Project-specific library of symbols for representing system equipment and products.
3. Incorporate digital images of Project-completed installation into graphics where beneficial to enhance effect.
4. Submit sketch of graphic layout with description of all text for each graphic for Owner's review before creating graphic using graphics software.
5. Seek Owner input in graphics development once using graphics software.
6. Final editing shall be done on-site with Owner's review and feedback.
7. Refine graphics as necessary for Owner acceptance.
8. On receiving Owner acceptance, print a hard copy for inclusion in operation and maintenance manual. Prepare a scanned copy PDF file of each graphic and include with softcopy of BDC system operation and maintenance manual.

3.4. INSTALLATION & SUPERVISION

A. All wiring and tubing shall be properly supported and run in a neat and workmanlike manner. All wiring and tubing exposed and in equipment rooms shall run parallel to or at right angles to the building structure. All piping and wiring within enclosures shall be neatly banded and anchored to prevent restriction to devices and terminals.

B. The control contractor shall be responsible for all electrical installation required for a fully functional control and automation system and not shown on the electrical plans or required by the electrical specifications. All wiring shall be in accordance to all local and national codes.

1. All line voltage wiring, all wiring exposed, and all wiring in equipment rooms shall be installed in conduit in accordance to the electrical specifications.
2. All electric and electronic wiring shall be minimum #20 AWG minimum THHN and shielded if required.
3. All wiring in the central control room shall be concealed in an approved manner.

C. Verify locations of temperature sensors, humidity sensors, CO₂ sensors, and other

exposed control sensors with plans and Owner prior to installation.

- D. The installation and supervision of this project shall be carried out by factory trained personnel who are employed by the Contractor and licensed for this type of work.
- E. Install control units and other hardware in position on permanent walls where not subject to excessive vibration.
- F. Install software in control units and in operator work station. Implement all features of programs to specified requirements and appropriate to sequence of operation.
- G. Install in accordance with manufacturer's instructions.
- H. Check and verify location of space temperature sensors, humidity sensors, CO₂ sensors, and other exposed control sensors with plans and room detail before installation. Align with lighting switches and humidistats.
- I. Mount freeze protection thermostats using flanges and element holders.
- J. Mount outdoor reset thermostats and outdoor sensors indoors, with sensing elements outdoors with sun shield.
- K. Provide separable sockets for liquids and flanges for air bulb elements.
- L. Mount control panels adjacent to associated equipment on vibration free walls or free standing angle iron supports. One cabinet may accommodate more than one system in same equipment room. Provide engraved plastic nameplates for instruments and controls inside cabinet and engraved plastic nameplates on cabinet face.
- M. Install equipment plumb and level.
- N. Install all equipment to be accessible for service and maintenance.

3.5. ACCEPTANCE TESTING

A. Point Verification

To verify end-to-end operation of the system the Contractor shall provide a hard copy of an All Points Summary Listing to the Owner of each part or system to be placed in warranty by the Owner. For CHS systems, the Contractor shall additionally provide a print screen of the process display showing real time dynamic point information for all points on the subsystem(s) to be accepted.

B. Sequence Verification

1. The Contractor shall notify the Owner's representative of systems which perform all specified sequences.
2. The warranty acceptance test shall be of 5 days duration and the system shall perform as follows:

- a). During the five days, the FMCS system shall not report any system diagnostics from the subsystem under test.
- b). The subsystem shall be performance verified as operational using temporary trends of each control loop located in the SDC or MSDC.

During the occupied periods, BAS control loops, under test, shall maintain control of the process variable within the following scales:

Duct Static Pressure	+/-0.3 inch WC
Pump Head Pressure	+/-10 percent of control range
Duct Temperature Loops	+/-2 degrees F
Room Temperature Loops	+/-1degrees F
Pipe Temperature Loops	+/-2 degrees F
Duct Humidity	+/-2x rated error of Humidity Transmitter

The contractor shall provide a hard copy printout of the process variable, process variable set point and control loop output percent for the period of 2 hours prior to occupancy to 2 hours after occupancy with samples taken every 15 minutes.

3.6. COORDINATE WITH TAB AGENCY

- A. Verify that all control components are installed in accordance with project requirements and are functional, including all electrical interlocks, damper sequences, air and water reset, freeze stats and duct smoke detectors.
- B. Verify that all controlling instruments are calibrated and set for design operating conditions prior to commencement of TAB work.
- C. Calibrate sensors after installation, and before the sensor control verification tests are performed. Prove the accuracy of final settings by taking temperature readings. The readings shall be in a typical conditional space for each separately controlled zone.
- D. Allow sufficient time in the project to provide assistance and instruction to the balancing agency in the proper use and setting of control components such as, but not limited to, computers, static pressure controllers, or any other device that may need set points changed so that the testing and balancing work can be performed.
- E. All control sequences, software, equipment, and components shall be started-up by a qualified technician. Start-up report shall be submitted to Engineer prior to the commencement of testing and balancing work. Testing and balancing shall not commence until start-up reports are completed, reviewed by Engineer and forwarded to Testing and Balancing Agency.

3.7. EXAMINATION

- A. Verify existing conditions before starting work.

- B. Verify that systems are ready to receive work.
- C. Beginning of installation means installer accepts existing conditions.
- D. Sequence work to ensure installation of components is complementary to installation of similar components in other systems.
- E. Coordinate installation of system components with installation of mechanical systems equipment such as air handling units and air terminal units.
- F. Verify that conditioned power supply is available to the control units and to the operator work station. Verify that field end devices, wiring, and tubing is installed prior to installation proceeding.

3.8. INTERLOCK REQUIREMENTS

- A. The fan and equipment interlock requirements are as scheduled on the contract drawings.
- B. Furnish and install all necessary relays, transformers, contactors, wiring, conduit, and accessories to perform fan, equipment, and damper interlocks.
- C. Unless otherwise noted, fan interlocks shall be arranged such that dampers associated with fan shall be open when fan starts and close when fan stops.

3.9. SUBMITTALS AT PROJECT CLOSEOUT

- A. Project Record Documents: Record actual locations of components and set points of controls, including changes to sequences made after submission of shop drawings.

3.10. CONNECTIONS

- A. Piping installation requirements are specified in other Division 23 Sections. Drawings indicate general arrangement of piping, fittings, and specialties.
 - 1. Install piping adjacent to machine to allow service and maintenance.
- B. Ground equipment.
 - 1. Tighten electrical connectors and terminals according to manufacturer's published torque-tightening values. If manufacturer's torque values are not indicated, use those specified in UL 486A and UL 486B.
- C. Connect hand-off-auto selection switches to override automatic interlock controls when switch is in hand position.

3.11. FIELD QUALITY CONTROL

- A. Manufacturer's Field Service: Engage a factory-authorized service representative to inspect, test, and adjust field-assembled components and equipment installation, including connections, and to assist in field testing. Report results in writing.

B. Perform the following field tests and inspections and prepare test reports:

1. Operational Test: After electrical circuitry has been energized, start units to confirm proper unit operation. Remove and replace malfunctioning units and retest.
2. Test and adjust controls and safeties.
3. Test calibration of electronic controllers by disconnecting input sensors and stimulating operation with compatible signal generator.
4. Test each point through its full operating range to verify that safety and operating control set points are as required.
5. Test each control loop to verify stable mode of operation and compliance with sequence of operation. Adjust PID actions.
6. Test each system for compliance with sequence of operation.
7. Test software and hardware interlocks.
8. Test all end switches and verify status is reported on the ATC system.

C. DDC Verification:

1. Verify that instruments are installed before calibration, testing, and loop or leak checks.
2. Check instruments for proper location and accessibility.
3. Check instrument installation for direction of flow, elevation, orientation, insertion depth, and other applicable considerations.
4. Check flow instruments. Inspect tag number and line and bore size, and verify that inlet side is identified and that meters are installed correctly.
5. Check pressure instruments, piping slope, installation of valve manifold, and self-contained pressure regulators.
6. Check temperature instruments and material and length of sensing elements.
7. Check control valves. Verify that they are in correct direction.
8. Check DDC system as follows:
 - a). Verify that DDC controller power supply is from emergency power supply, if applicable.
 - b). Verify that wires at control panels are tagged with their service designation and approved tagging system.
 - c). Verify that spare I/O capacity has been provided.

- d). Verify that DDC controllers are protected from power supply surges.
- D. Replace damaged or malfunctioning controls and equipment and repeat testing procedures.
- E. All temperature control and interlock wiring shall be installed in conduit unless otherwise noted on the plans. Power or interlock wiring shall be run in separate conduit from sensor and communications wiring.

3.12. ADJUSTING

A. Calibrating and Adjusting:

1. Calibrate instruments.
2. Make three-point calibration test for both linearity and accuracy for each analog instrument.
3. Calibrate equipment and procedures using manufacturer's written recommendations and instruction manuals. Use test equipment with accuracy at least double that of instrument being calibrated.
4. Control System Inputs and Outputs:
 - a). Check analog inputs at 0, 50, and 100 percent of span.
 - b). Check analog outputs using volt-ohm-milli-amp meter (VOMA) at 0, 50, and 100 percent output.
 - c). Check digital inputs using jumper wire.
 - d). Check digital outputs using ohmmeter to test for contact making or breaking.
 - e). Check resistance temperature inputs at 0, 50, and 100 percent of span using a precision-resistance source.
5. Flow:
 - a). Set differential pressure flow transmitters for 0 and 100 percent values with 3-point calibration accomplished at 0, p50, 90, and 100 percent of span.
 - b). Manually operate flow switches to verify that they make or break contact.
6. Pressure:
 - a). Calibrate pressure transmitters at 0, 50, and 100 percent of span.
 - b). Calibrate pressure switches to make or break contacts, with adjustable differential set at minimum.
7. Temperature:
 - a). Calibrate resistance temperature transmitters at 0, 50, and 100 percent of

- span using a precision-resistance source.
b). Calibrate temperature switches to make or break contacts.

8. Stroke and adjust control valves and dampers.
9. Provide diagnostic and test instruments for calibration and adjustment of system.
10. Provide written description of procedures and equipment for calibrating each type of instrument. Submit procedures review and approval before initiating startup procedures.

- B. Adjust initial temperature and humidity set points.
C. Occupancy Adjustments: When requested within 12 months of date of Substantial Completion, provide on-site assistance in adjusting system to suit actual occupied conditions. Provide up to three visits to Project during other than normal occupancy hours for this purpose.

3.13. ON-SITE ASSISTANCE

- A. Occupancy Adjustments: Within one year of date of Substantial Completion, provide up to three Project site visits, when requested by Owner, to adjust and calibrate components and to assist Owner's personnel in making program changes and in adjusting sensors and controls to suit actual conditions.

3.14. SCHEDULING

- A. Submit spreadsheet to Owner indicating occupied/unoccupied times for each item controlled by ATC system. Incorporate all scheduling requirements into sequence of operation.

3.15. STAGING

- A. Coordinate staging requirements with equipment being controlled. Where multistage units are scheduled or specified, provide all devices, controllers, wiring to control and sequence all stages.

3.16. SEQUENCES OF OPERATION

- A. Refer to Contract Drawings for sequences of operation, control diagrams, and points list.

END OF SECTION

SECTION 23 30 00

HVAC AIR DISTRIBUTION

PART 1 GENERAL

1.1 SUMMARY

- A. For General Mechanical Requirements, see Division 23 Section, "Common Work Results for HVAC" and Division 01, "General Requirements".
- B. The fabrication and installation of all ductwork, together with related equipment, shall comply with the standards of the National Fire Protection Association, as set forth in NFPA Standard No. 90A, as well as with the requirements of the Sheet Metal and Air Conditioning Contractors' National Association, Inc., and the latest edition of the ASHRAE Guide.
- C. All duct sizes shown are net inside clear dimensions. Where internal duct lining is used, increase duct sizes accordingly to provide the indicated net free area. Unless otherwise indicated size runouts, drops, and connections to grilles, registers, diffusers, fans, coils, louvers, filters, and other equipment to the full size of the equipment connection.
- D. Minor changes may be made in duct sizes where required to fit the available space, provided the indicated net free area and approximate aspect ratio are maintained.
- E. Smoothly transition all ductwork to prevent excessive or unnecessary turbulence or pressure loss.
- F. All exposed ductwork in finished areas shall be painted in color as indicated by Architect. All ductwork requiring paint shall be constructed of paint grade galvanized sheet steel with a paintable finish.

1.2 REFERENCES

- A. ASTM A 36 - Structural Steel.
- B. ASTM A 90 - Weight of coating on Zinc-Coated (Galvanized) Iron or Steel Articles.
- C. ASTM A 167 - Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet, and Strip.
- D. ASTM C 916 Type II - Standard Specification for Adhesives for Duct Thermal Insulation.
- E. ASTM A 366 - Steel, Sheet, Carbon, Cold Rolled, Commercial Quality.
- F. ASTM A 480 - General Requirements for Flat-Rolled Stainless and Heat-Resisting Steel Plate, Sheet, and Strip.
- G. ASTM A 525 - General Requirements for Steel Sheet, Zinc-Coated (Galvanized) by the Hot-Dip Process.

- H. ASTM A 527 - Steel Sheet, Zinc-Coated (Galvanized) by Hot-Dip Process, Lock Forming Quality.
- I. ASTM A 568 - Steel, Sheet, Carbon, and High-Strength, Low-Alloy, Hot-Rolled and Cold-Rolled.
- J. ASTM A 569 - Steel, Carbon (0.15 Maximum, Percent), Hot-Rolled Sheet and Strip, Commercial Quality.
- K. ASTM B209 - Aluminum and Aluminum-Alloy Sheet and Plate.
- L. AWS D9.1 - Welding of Sheet Metal.
- M. NFPA 90A - Installation of Air Conditioning and Ventilating Systems.
- N. NFPA 90B - Installation of Warm Air Heating and Air Conditioning Systems.
- O. NFPA 96 - Installation of Equipment for the Removal of Smoke and Grease-Laden Vapors from Commercial Cooking Equipment.
- P. SMACNA - HVAC Air Duct Leakage Test Manual.
- Q. UL 181 - Factory-Made Air Ducts and Connectors.
- R. NFPA 90A - Installation of Air Conditioning and Ventilating Systems.
- S. NFPA 70 - National Electrical Code.
- T. SMACNA - HVAC Duct Construction Standards - Metal and Flexible.
- U. UL 33 - Heat Responsive Links for Fire-Protection Service.
- V. UL 555 - Fire Dampers and Ceiling Dampers.

1.3 PERFORMANCE REQUIREMENTS

- A. No variation of duct configuration or sizes permitted except by written permission. Size round ducts installed in place of rectangular ducts in accordance with ASHRAE Table of Equivalent Rectangular and Round Ducts.

1.4 QUALIFICATIONS

- A. Manufacturer: Company specializing in manufacturing the projects specified in this section with minimum five (5) years documented experience.
- B. Installer: Company specializing in performing the work of this section with minimum five (5) years' experience.

1.5 REGULATORY REQUIREMENTS

- A. Construct ductwork to NFPA- 90A, and NFPA-90B, and NFPA- 96 Standards.

1.6 ENVIRONMENTAL REQUIREMENTS

- A. Do not install duct sealants when temperatures are less than those recommended by sealant manufacturer.
- B. Maintain temperatures during and after installation of duct sealants.

1.7 ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

PART 2 PRODUCTS

2.1 DUCTWORK

- A. Unless otherwise indicated or specified, fabricate ductwork of galvanized sheet steel, stainless steel, or aluminum conforming to Commercial Designation 3003 Temper H14 and Duct Sheet. Duct gages, jointing and reinforcement shall conform to Tables 4, 5, 6 and 7, as applicable, Chapter I of the latest *ASHRAE Guide and Data Book*. Construction details shall conform to Section I and Section II, as applicable, of *Duct Manual and Sheet Metal Construction for Ventilation and Air Conditioning Systems* as published by Sheet Metal and Air Conditioning Contractors Association, Inc.
- B. Erect sheet metal ductwork in a first-class, workmanlike manner secured in place rigidly and permanently. Provide suitable hangers, securely attached to building construction with bolts, clips or inserts. Hangers shall be structural shapes, flat bars, or formed strap hangers; use of wire will not be permitted. Hangers shall not pass through or be inside duct. Support vertical ducts passing through floors by angles riveted to duct and resting either on floor or on brackets secured to building construction. All space around ducts where they pass through any walls, floors, ceilings, or roofs shall be sealed tight with incombustible inert material. Do not arrange ducts so as to impair the effectiveness of fireproofing around structural members. Provide sheet metal flanged collars around exposed ducts passing through walls, floors, or ceilings to provide finished appearance. Seal all duct joints and seams including supply, return, outside air, combustion air, relief air, ventilation air and exhaust ductwork with *Hardcast* Sealing System as manufactured by Hardcast, Inc., Foster, Childers, or approved equal.
- C. Flexible connections of neoprene or other NFPA approved non-inflammable fabric shall be provided in the duct system at all fan inlet and outlet connections.
- D. Provide cut turning vanes in all duct turns where centerline radius is located. Turning vanes shall be air-foil type with extended trailing edges. Fabricate to comply with SMACNA Sheet Metal Construction for Ventilation and Air Conditioning Systems Manual.
- E. Provide duct collars and angle iron framework for mounting of automatic dampers.
- F. Fabricate and support in accordance with SMACNA HVAC Duct Construction Standards

- Metal and Flexible, and as indicated. Provide duct material, gauges, reinforcing, and sealing for operating pressures indicated.

- G. Construct T's, bends, and elbows with radius of not less than 1-1/2 times width of duct on centerline. Where not possible and where rectangular elbows are used, provide air foil turning vanes. Where acoustical lining is indicated, provide turning vanes of perforated metal with glass fiber insulation.
- H. Increase duct sizes gradually, not exceeding 15 degrees divergence wherever possible; maximum 30 degrees divergence upstream of equipment and 45 degrees convergence downstream.
- I. Fabricate continuously welded round and oval duct fittings two gauges heavier than duct gauges indicated in SMACNA Standard. Joints shall be minimum 4-inch (100 mm) cemented slip joint, brazed or electric welded. Prime coat welded joints.
- J. Provide standard 45 degree lateral wye takeoffs unless otherwise indicated where 90 degree conical tee connections may be used.
- K. Fasteners: Rivets, bolts, or sheet metal screws.
- L. Hanger Rods: ASTM A36 - Galvanized steel; threaded both ends, threaded one end, or continuously threaded.

2.2 DUCT SYSTEMS

- A. All supply, return, exhaust, fresh air intake, relief, ventilation, outside air and combustion air ductwork shall be constructed for low pressure service (2 inch W.G.). All exposed round ductwork in finished areas shall be paintable grade, dual wall, constructed for medium pressure service (6 inch W.G.).

2.3 DUCT CONSTRUCTION

- A. Rectangular and/or Round Ductwork (Low Pressure):
 1. Galvanized Steel Ducts: ASTM A525 and ASTM A527 galvanized steel sheet, lock-forming quality, having G-90 Zinc coating in conformance with ASTM A90.
 2. Make allowance for internal duct lining where required. Sizes shown on the drawings are inside clear dimensions.
 3. Determine duct gauges for the longest duct side and use for all four sides. Joints and reinforcing requirements apply to the longest duct side.
 4. Reinforce all ducts to prevent buckling, vibration, or noise as recommended in the referenced construction standards, and as required to suit the installed conditions.
 5. Do not cross break duct which will receive rigid insulation covering.

6. Where tap sizes of divided-flow fittings are not indicated, make branch and main/connection sizes proportional to their respective air flows and maintain uniform transverse velocities in the fitting.
7. Make radius elbows and radius tee connection with throat radius equal to or greater than the width of the duct. Use vaned elbows where shown and where radius elbows will not fit the space, and in all square bends.
8. Turning vanes shall be the air-foil type with extended trailing edges, 36 inch maximum vane length. Where longer vanes are required, use two or more sets of vanes with intermediate runners securely fastened together.
9. Bolt, screw, rivet, or spot weld reinforcing members securely to the duct on not less than 6-inch centers.
10. Where ducts are open-ended without grilles, registers, or other means of stiffening, reinforce and stiffen the open end with standing seams or an angle frame. Provide rolled edges to prevent any exposed sharp edges.
11. Paint all cut ends on galvanized angles, rods, and other uncoated surfaces with aluminum paint.
12. Where ductwork is not painted or otherwise finished, remove all exposed traces of joint sealers, manufacturer's identification and other markings.
13. Aluminum sheet shall be 3003 H14 alloy or duct sheet, 16,000 psi minimum tensile strength, and capable of being formed to a Pittsburgh lock seam.
14. Reinforcing members for aluminum ductwork shall be galvanized steel or aluminum unless otherwise indicated. Where aluminum reinforcing is used, size the member in accordance with ASHRAE recommendations to have rigidity equivalent to listed mild steel angle sizes.
15. Where aluminum ductwork is used, make allowance for increased thermal expansion. Particularly avoid direct contact between aluminum and concrete or masonry walls subject to dampness.
16. Determine duct gauges per SMACNA based on duct size and pressure indicated.

B. Kitchen Range Hood Exhaust Ductwork

1. Exposed Stainless Steel Ducts: ASTM A167, Type 316.
2. The exhaust ductwork serving the kitchen hoods shall comply with NFPA Standard No. 96, International Mechanical Code, State of Delaware Health Department requirements, local Health Department and requirements.
3. The exposed exhaust ductwork shall be Type 316 stainless steel (minimum 18 gauge) No. 4 finish, with all joints and seams welded, ground and polished. All welds shall be liquid tight, continuous external welds. Comply with N.S.F. requirements.

4. Concealed exhaust ductwork shall be constructed of welded carbon steel (minimum 16 gauge).
5. Proper clearance to combustibles shall be maintained as required by Code.
6. All exhaust ducts shall be installed without forming dips or traps that might collect residue. All exhaust duct must slop toward hood at .25 inches per foot. For ducts longer than 75 feet the slope shall be at least 1 inch per foot.
7. Cleanouts shall be located on horizontal sections of ducts not spaced more than 12 feet apart. Cleanouts shall also be located at all vertical risers and all changes in direction. In horizontal sections, the lower edge of the opening shall be not less than 1½ inch from the bottom of the duct. Access panels shall be of the same material and thickness as the duct. Access panels shall have a gasket or sealant that is rated for 1500 degrees F and shall be grease tight. Fasteners used to secure the access panels shall be stainless steel and shall not penetrate duct walls. A sign shall be placed on all access panels stating: *ACCESS PANEL - DO NOT OBSTRUCT*.
8. Dampers, either manual or automatic, shall not be installed in kitchen hood exhaust ducts or kitchen hood exhaust duct systems.
9. Ducts that terminate above the roof shall have the discharge located a minimum of 40 inches above the roof surface.
10. Utilize light to verify that all joints are sealed. Submit results of light testing.

2.4 KITCHEN RANGE HOOD PERFORMED SUPPLY AIR PLENUM

- A. Furnish and install kitchen ventilation hood supply air plenum of the size, arrangement and configuration as indicated on the contract drawings.
- B. Hood is existing but shall have new supply plenum, controls, and fire suppression installed.
- C. Each existing hood shall be provided with a field-installed and approved automatic fire suppression system in accordance with NFPA and International Mechanical Code. The automatic fire suppression system shall bear the label of an approved agency and shall be installed in accordance with the manufacturer's installation instructions.
- D. All hood fire suppression systems shall have automatic actuation. All hood fire suppression systems shall have manual actuation. The manual actuation shall require a maximum force of 40 pounds and a maximum movement of 14 inches to actuate the fire suppression system.
- E. A manual actuation station shall be located at or near a means of egress from the cooking area, a minimum of 10 feet from the kitchen exhaust system. The actuation device shall be located a minimum of 4 ½ feet and a maximum of 5 feet above the floor.
- F. The actuation of the hood fire suppression system shall automatically shut down the fuel

or electrical supply to the cooking equipment. The fuel and electrical supply reset shall be manual. In addition, the actuation of the hood fire suppression system shall automatically de-energize the kitchen hood make-up air unit.

- G. Access shall be provided to all nozzles in the fire suppression system.
- H. The hood fire suppression system shall be tested in accordance with the fire prevention code.
- I. Hood perforated supply plenum shall be Greenheck Model ASP or approved equal. The external air curtain, shall be constructed with a minimum of 18 gauge 400 series stainless steel. Two layers of perforated panels will allow for well distributed low velocity airflow at discharge. External air curtain supply plenums shall supply airflow at a maximum rate of 180 cfm/ft.

2.5 CASINGS

- A. Fabricate casings in accordance with SMACNA - HVAC Duct Construction Standards - Metal and Flexible, and construct for operating pressures indicated.
- B. Mount floor-mounted casings on 4-inch high concrete curbs. At floor, rivet panels on 8-inch centers to angles. Where floors are acoustically insulated, provide liner of 18 gauge galvanized expanded metal mesh supported at 12 inch centers, turned up 12 inches at sides with sheet metal shields.
- C. Reinforce door frames with steel angles tied to horizontal and vertical plenum supporting angles. Install hinged access doors where indicated or required for access to equipment for cleaning and inspection. Provide clear wire glass observation ports, minimum 6 x 6 inch size.
- D. Fabricate acoustic casings with reinforcing turned inward. Provide 16 gauge back facing and 22 gauge perforated front facing with 3/32 inch diameter holes on 5/32 inch centers. Construct panels 2 inches thick, packed with 4.5 lb/cu ft minimum glass fiber media, on inverted channels of 16 gauge.

2.6 AIR TRANSFER OPENINGS

- A. Furnish and install metal sleeves or frames, of the same material as the duct or air terminals attached thereto, in all air transfer openings through walls, partitions, floors and other building construction, extending completely through the opening. Securely fasten the sleeves or frames in place and provide face flanges on both sides. Where grilles or registers are required, attach them to the sleeve or frame, or extend ductwork where shown on the drawings. If no grilles, registers or duct connections are required, furnish and install 1/2 inch x 1/2 inch removable galvanized wire mesh on one face.

2.7 AIR VOLUME CONTROLS

- A. Furnish and install air volume control devices where indicated and where required to adjust and balance air flow in the systems, whether indicated or not. Volume dampers shall be provided in all branch ducts serving air outlets and inlets. For existing air devices install a new volume damper and where required for access, a new access door to

allow access and adjustment.

- B. Air extraction for air outlets and branch ducts shall be the gang-operated vane type, Tuttle & Bailey - *Vectrol*, Type VLC or VLK as appropriate, or approved equal, with suitable adjusting device and means of access.
- C. Manual volume dampers in ductwork shall be factory-assembled units with rigid frame opposed-blade action, and locking quadrant operator. Mark the extended damper shaft and align the operating handle to indicate the blade position. Dampers shall be as manufactured by Ruskin, American Warming and Ventilating, Inc., Arrow, or approved equal. Rectangular dampers shall be Type MD35, with steel channel frame, 16 gauge steel blades, 9 inch maximum blade spacing, low pressure, nylon bearings, galvanized finish with aluminum paint touch up. Round manual balancing dampers shall be Type MDRS25 manufactured by Ruskin, Arrow, American Warming and Ventilating, Inc., or as approved equal. When external insulation is to be applied, provide sheet metal standoffs on all manual volume dampers.
- D. Motor-operated dampers shall be as hereinafter specified under Division 23 Section, "Instrumentation and Controls of HVAC & Plumbing System".
- E. Duct turning vanes shall be Tuttle & Bailey *Ducturns*, or approved equal.
- F. Furnish and install duct collars and angle iron frames for the installation of ATC dampers.
- G. Provide Type 316 stainless steel motor operated dampers for installation in stainless steel ductwork.
- H. Where volume dampers are installed in exposed finished spaces locate damper handle on top of duct.
- I. Where volume dampers are installed above ceilings attach a colored piece of tape so that Test and Balance Engineer can easily locate for air flow adjustment.

2.8 INSTRUMENT TEST PORTS

- A. Furnish and install instrument test ports in the ductwork to allow use of pitot tube length. Equip holes with Ventlok #699 instrument ports. Fittings shall extend beyond duct covering and insulation.
- B. Kitchen hood grease ducts shall be fitted with metal to metal seals for pitot tube access port. Assembly shall consist of stainless steel bolt, toothed lock washer, and nut. Nut shall be welded to grease duct as indicated on contract drawings. Locations of pitot tube access ports shall be coordinated with Test and Balance Engineer prior to installation of the ports.

2.9 DUCT THERMOMETERS

- A. Duct thermometers shall be Dresser Industries, Trerice, Weiss, Weksler, Miljoco, or approved equal direct-mounting filled system dial thermometers. Duct thermometers shall be vapor-actuated, universal-angle dial type, cast aluminum case with 4 ½ inch

diameter, glass lens. Duct thermometers shall include adjustable joint with finish to match case, 180 degree adjustment in vertical plane, 360 degree adjustment in horizontal plane, with locking device. Thermal bulbs shall be copper with phosphor-bronze bourden pressure tube. Movement shall be brass, precision geared. Duct thermometer scales shall be Progressive, satin-faced non-reflective aluminum with permanently etched markings. Each stem shall be copper-plated aluminum or brass for separable socket of length to suit installation.

- B. Where ductwork is installed at a height that would require duct thermometers to be installed 10 feet above finished floor or greater then remote-ready filled - system shall thermometers shall be installed. Connecting tubing shall be bronze, double-braided, armor-over-copper capillary; of length to suite installation.
- C. Duct thermometers shall be furnished and installed at air handling units, 100% outside air units, make-up air units, ducted variable refrigerant volume units, and kitchen make-up air units as follows:

LOCATION	RANGE
Outdoor Air Duct	-40 degrees Fahrenheit to 120 degrees Fahrenheit
Return Air Duct	40 degrees Fahrenheit to 180 degrees Fahrenheit
Mixed Air Plenum	30 degrees Fahrenheit to 180 degrees Fahrenheit
Supply Air Duct	30 degrees Fahrenheit to 180 degrees Fahrenheit

- D. Description: Flanged-fitting bracket for mounting in hole of duct, with threaded end for attaching thermometer.
 1. Extension-Neck Length: Nominal thickness of 2 inches, but not less than thickness of exterior insulation.
 2. Insertion-Neck Length: Nominal thickness of 2 inches, but not less than thickness of insulation lining.

2.10 FLEXIBLE DUCT

- A. Where indicated, flexible ductwork shall be Type SLR-25C as manufactured by General Flex Corporation, or as approved equal, insulated fully, UL listed as Class 1 Air Ducts, Standard 181, NFPA 90A and NFPA 90B with scuff-resistant polyethylene connector jacket and suitable for use in return air plenums.
- B. Limit flexible duct runs to 5 feet maximum. Install flexible ducts, using all recommended fittings, couplings, and accessories. Support ducts with wide straps spaced so that horizontal runs do not sag more than 2-1/2 inches in 5 feet. Internally seal all joints and connections, cover with duct tape, and fasten with metal duct strap clamps. Bends of 180 degrees in flexible duct are prohibited.

2.11 FIRE DAMPERS

- A. Furnish and install automatic fire dampers where indicated, in all 2-hour fire-rated partitions, shafts, slabs, etc., and where required by NFPA Standard No. 90A and by the Fire Marshal. Refer to the architectural drawings for location of all fire-rated walls, shafts and slabs. Fire Dampers shall also be provided at all transfer air devices installed in rated walls at all floor penetrations, and as shown on the contract drawings.
- B. Construction of fire dampers shall conform to requirements of NFPA No. 90A, UL Standard 555 and shall bear UL label. Fire dampers shall be set in frames adequately secured to fire partitions, floors, etc., and installed in strict accordance with UL listing and manufacturer's instructions.
- C. Fire damper shall be Dynamic Type for rectangular ductwork and round ductwork as manufactured by Ruskin, Air Balance, Inc., Arrow, Greenheck, Lloyd Industries, Nailor, or approved equal, multi-leaf accordion type, held open by adequate heavy gauge wires and suitably calibrated fusible links. Vertical dampers (horizontal air flow) shall close by gravity. Horizontal dampers (vertical air flow) shall be closed by suitable and positive spring closing devices.
- D. Damper frames shall provide pocket which shall stop the damper leaves in open position outside of the air stream and shall provide for 100 percent opening connecting to ductwork or grille face. Damper material shall match connecting ductwork.
- E. Provide adequately sized hinged access doors with cam locks for access to all fusible links and for resetting fire dampers. Where applicable, access to fire dampers shall be through registers or grilles. Provide identification on access door indicating fire damper within. Letters shall be not less than 1/2 inch in height.
- F. Submit complete information to the Engineer including installation details. Furnish and install sleeves, angles, break away duct connections, per UL listing.
- G. Furnish to the Owner in a suitable storage container not less than six (6) fusible links of each type, size, and rating used on the project. Where required, furnish Greenheck Type CR, CO, or Type C transition sleeves.

2.12 COMBINATION FIRE/SMOKE DAMPERS WITH INTEGRAL SMOKE DETECTOR

- A. Furnish and install automatic combination fire/smoke dampers with actuators and smoke detectors where shown on plans and as required by NFPA-90A, 92A, 93B, 101 and by the State Regulations. Combination fire/smoke dampers shall be tested, rated, and labeled in accordance with the latest edition of UL Standard 555S. Combination fire/smoke dampers shall be of the low leaking design qualified to UL 555S Leakage Class I. Fire dampers shall have a UL 555 fire rating of 1½ hours and be of low leakage design qualified to UL 555S Leakage Class I. Furnish to the Owner in a suitable storage container not less than six (6) fusible links of each type, size, and rating. Smoke detectors shall be tested, rated and labeled in accordance with the latest edition of UL Standard 268A.
- B. Each damper/actuator combination shall have a UL 555S elevated temperature rating of 350 degrees F minimum and shall be rated to operate at maximum design air flow at its installation location.

- C. Each damper shall be supplied with an appropriate smoke detector installed by the damper manufacturer. Smoke detectors shall be photoelectric type with air duct velocity range of 600 fpm to 4000 fpm and operating temperature range of 23 degrees Fahrenheit to 131 degrees Fahrenheit. Electrical characteristics shall be as scheduled on the contract drawings. Detector shall be factory wired to damper actuator so as to provide single point wiring of the damper. Provide detectors with dry contacts for monitoring on the fire alarm system. Coordinate with Division 26. Provide end switches on damper to allow remote monitoring on fire alarm system, coordinate with Division 26. Furnish end switches to allow monitoring of damper position from a remote test station. Remote test station shall be furnished and installed. Remote test switch shall include controlling switch (double throw switch) and indicator lights.
- D. Each combination fire/damper shall be supplied with an appropriate actuator installed by the damper manufacturer at the time of damper fabrication. Damper actuators shall be electric type and shall be factory wired to smoke detector so as to provide single point wiring of damper. Electrical characteristics shall be as scheduled on the contract drawings.
- E. Combination fire/damper blades shall be of the double skin airfoil type and shall have an equivalent metal thickness of 14 gauge. Combination fire/damper frame shall be galvanized steel furnished into a structural hat channel shape with reinforced covers. Bearings shall be sintered bronze sleeve type, rotating in extended holes in the damper frame.
- F. Blade edge seals shall be silicone rubber designed to inflate and provide a tighter seal against leakage as pressure on either side of the damper increases. Jamb seals shall be stainless steel compression type with silicone rubber backing. Blades shall be completely symmetrical relative to their axle pivot point, presenting identical resistance to air flow in either direction or pressure on either side of the damper.
- G. Combination fire/smoke dampers must be rated for mounting vertically (with blades running horizontally) or horizontally and be UL 555S rated for leakage and air flow in either direction through the damper. Combination fire/damper shall confirm to the following ratings:
1. Leakage: UL 555S Leakage Class I - Leakage rated in both directions.
 2. Pressure: 8 inches w.g. - Differential
 3. Velocity: Operational rated to 4000 FPM with airflow in either direction
 4. Temperature: 350 degrees F with standard actuator
- H. Furnish combination fire/dampers with appropriate galvanized steel sleeves. Where applicable, provide Type R, Type O, or Type C transition sleeve as manufactured by Greenheck or approved equal. Dampers shall be sized to provide 100 percent of the areas of the ductwork in which the damper is installed. Provide stainless steel or aluminum smoke combination fire/dampers when installed in duct systems constructed of these materials, respectively.
- I. Provide adequate sized, hinged, insulated access doors with cam locks for access, inspection of all combination fire/smoke dampers. Where applicable, access to combination fire/smoke dampers shall be through registers, on grilles. Provide identification on access doors indicating combination fire/smoke damper within. Letters

shall not be less than ½- inch in height.

- J. Wiring to fire alarm system shall be provided under Division 26. Installation of combination fire/smoke dampers, duct detectors, and smoke actuators shall be provided under Division 23.
- K. Submit complete information to the Engineer, including installation details. Furnish and install sleeves, angles, actuator, etc., per UL listing. Combination fire/smoke dampers shall be Model FSD-33 as manufactured by Greenheck, Air Balance, Ruskin, Lloyd Industries, Nailor, or approved equal.

2.13 DUCT ACCESS DOORS

- A. Furnish and install adequately sized duct access doors at fire dampers, smoke dampers, air measuring devices, motor-operated dampers, duct smoke detectors, duct coils and other locations where indicated and required for duct access. Doors shall be the continuous piano-hinged type with approved latches and neoprene compression-type gaskets with 1 inch thick fiberglass double skin and shall be Ruskin Model ADH22, Air Balance, Inc., FSA-100 or as approved equal. Stiffen ductwork at door openings. Where doors are installed in insulated ductwork, provide equivalent insulation in the door assembly. Where access doors are installed in the fire-rated partitions, provide *Fire Seal* access doors as manufactured by Air Balance, Inc., or approved equal, UL approved, meeting the rating of the enclosure in which the access door is installed.
- B. Where duct access doors are installed in medium pressure ductwork, they shall be as manufactured by Ruskin, Type ADHF-3, or approved equal, with six latches continuous gasket and insulated core.
- C. For walk-in plenums, provide insulated walk-through access doors, Ruskin Type ADW2, American Air Balance Type WA-100, or as approved equal.
- D. Seal around frame attachment to duct and door to frame with neoprene or foam rubber.

2.14 SPIN-IN FITTINGS

- A. Furnish and install spin-in fittings where indicated on the contract drawings, Model SM-20G, as manufactured by General Environment Corporation, or an approved equal.

2.15 DUCT LINING (LOW PRESSURE DUCTWORK)

- A. All low pressure supply and return ductwork within 10 feet of air handling units, 100% outside air units, and kitchen make-up air units, and as additionally shown on Contract Drawings, shall be lined on the interior for sound attenuation and thermal insulation.
- B. All low pressure ductwork within 10 feet of return [or exhaust] air fans and as additionally shown on Contract Drawings shall be lined on the interior for sound attenuation and thermal insulation.
- C. All internal duct lining for low pressure duct systems shall be provided with an interior galvanized perforated liner.

- D. Provide additional exterior insulation where required and as indicated in Division 23 Section, "HVAC Insulation".
- E. The lining insulation shall be 1 inch thick, 3.0 pcf density, Aeroflex plus Duct Liner Type 300, Owens Corning Quiet R Rotary Duct Liner, Manville, Knauf, or approved equal. The material shall be specifically designed for this application, shall have a black, fire resistant coating, shall meet NFPA Standards 90A and 90B and shall have a UL Fire Hazard Classification of Flame Spread 25 or less and smoke developed of 10 or less. The black-coated surface shall face the air stream.
- F. All exposed edges and the leading edge of all cross joints of the liner shall be coated with the same adhesive used to secure the duct liner to metal surface. All air stream surfaces shall be treated with EPA registered fungicide Foster 40-20. Coating shall meet ASTM D 5590 with 0 growth rating.
- G. The duct liner shall be adhered to the metal with 100 percent coverage of adhesive. Adhesive shall conform to Adhesive and Sealant Council standards for adhesives for duct liner; ASTM C916, Type II (ASC-A-7001-A-1971). Adhesive shall be Foster 85-60, Childers CP-127 or approved equal.
- H. The duct liner shall be additionally secured with mechanical fasteners, which shall compress the duct liner sufficiently to hold it firmly in place. Mechanical fasteners shall conform to Mechanical Fastener Standard MF-1-1971, available from Sheet Metal and Air Conditioning Contractors National Association.
- I. All duct lining shall be installed in complete accordance with the Sheet Metal and Air Conditioning Contractors National Association (SMACNA) Duct Liner Application Standard, First Edition and Green Guard Indoor Air Quality certification program requirements.
- J. Dimensions on drawings indicate inside clear opening of rectangular ductwork. Increase duct dimensions 2 inches each way for accommodating insulation on all shop or field-fabricated rectangular ductwork where lining is specified.

2.16 AIR TERMINAL DEVICES

- A. Furnish and install air supply, return, exhaust devices of sizes and capacities as scheduled on the drawings. Catalog numbers shown are Metalaire, Inc., products for equipment which have been found suitable for the application. Products of Tuttle & Bailey, Anemostat, Division of Hart & Cooley, Carnes, Titus, Price, Nailor, or approved equal will be considered only if performance characteristics including throw, drop, pressure loss, sound pressure level, etc., are equal to or better than the performance characteristics of the specified products. All air devices shall be ADC certified. Ductwork behind registers, grilles and diffusers shall be given two coats of flat black paint. Perimeter of all ceiling diffusers shall be caulked to provide a neat, aesthetic appearance.
- B. Device Schedule:

AIR DEVICE SCHEDULE

AIR DEVICE SCHEDULE		
Device	Accessories	Finish
Supply Diffusers, Lay-in Tile		
Model 5000-A, Rectangular MetalAire Ceiling Diffuser, Throw as Indicated	Integral opposed blade damper	White baked enamel finish
	Removable core	
	Louvered face	
	All aluminum construction	
	Auxiliary panel for lay-in tile installation	
	Adjustable pattern deflector	
Supply Diffuser, Gypboard, Surface Mount		
MetalAire Model 5000-A, Rectangular Ceiling Diffuser, Throw as Indicated (Surface or Duct Mount)	Integral opposed blade damper	White baked enamel finish
	Louver face	
	All aluminum construction	
	Removable core	
	Adjustable pattern deflector	
Supply Register, Sidewall, Floor		
MetalAire Model V4004 Sidewall Supply Register, Throw as Indicated (Surface or Duct Mount)	Integral opposed blade damper	White baked enamel finish
	All aluminum construction	
	22½ inch deflection blades	
	Double deflection spread & drop control	
Return/Exhaust, Transfer Register, Gypboard, Surface Mount		
MetalAire, Model RHD Rectangular Registers (Surface Mount)	Integral opposed blade damper	Off-white baked enamel finish
	45 degree angled deflecting vanes	
	All aluminum construction	

NOT FOR BIDDING PURPOSES

AIR DEVICE SCHEDULE		
Return/Exhaust Register [Sidewall w/filters]		
MetalAire Model SRHF Sidewall Return Register with Filter Housing	All steel construction, for gyms and multipurpose spaces provide heavy duty, 16 gauge	Off white electro- deposition finish
	45 degree angled deflecting vanes	
	Opposed blade dampers	
	Filter housing w/ 1 inch thick disposable filter	
	Hinged core	
	Provide return air filters racks and 1" thick filters where indicated.	
Return/Exhaust, Transfer Register, Lay-in Tile		
MetalAire, Model RHD Rectangular Registers	Integral opposed blade damper	Off-white baked enamel finish
	45 degree angled deflecting vanes	
	All aluminum construction	
	Auxiliary panel for lay-in tile installation	
	Provide return air filters racks and 1" thick filters where indicated.	
Perforated Grilles/Register		
MetalAire, Model RP Perforated Face Grilles/Registers	All aluminum construction	Off-white baked enamel finish
	Opposed Blade Dampers	

- C. Where air terminal devices are installed in duct collars or branches, furnish and install air extractors. Furnish and install control grids, volume dampers, and/or other accessories necessary to ensure uniform air flow across the terminal devices. Accessories shall be of the same material as the terminal device. Install fixed blade terminals so that blades block the normal line of vision. Furnish three (3) of each type of removable key operators.
- D. Contractor shall determine frame and mounting type as per type of ceiling as shown on Architectural drawings.
- E. Noise Criteria: All air devices shall be sized and selected to limit maximum NC (noise criteria) levels to 30.

2.17 LOUVERS (FIXED BLADE)

- A. Furnish and install wall louvers of the size and capacity shown on the contract drawings. Louvers shall be Greenheck Model EHV-901 (high velocity wind driven rain) heavy gauge extruded aluminum stationary type louvers or approved equal. Louvers shall be stationary, dual module type consisting of a "front" louver with J-style blades and a "rear" louver with vertical rain resistant style blades. Louver frame shall be a total depth of 9 inches.
- B. Front louvers shall be drainable type fabricated from heavy gauge 6063-T5 aluminum extrusions of .081 inch nominal wall thickness. Blades shall be positioned at 37 degree and 45 degree angles, approximately 4.25 inches on centers. Rear louver shall be vertical rain resistant style, heavy gauge extruded 6063-T5 aluminum, 0.060 nominal thickness, positioned on approximately 1.5 inch blade spacing. Each louver shall be equipped with a frame and removable rear-mounted screen of flattened aluminum. Each factory assembled louver section shall be designed to withstand wind loadings of 25 psf. Louvers too large for complete factory assembly shall be built up by the installing contractor from factory assembled louver sections.
- C. Louvers shall be tested in accordance with AMCA 550-L, AMCA-540, and AMCA 550 (Certified High Velocity, Rain Resistant, and Impact Resistant Louver).
- D. Louvers shall be supplied with a factory Kynar finish applied after a thorough cleaning and preparation of the metal surface. A total dry film thickness of approximately 1.2 mils shall be provided. Custom color shall be as selected by Architect.
- E. Louvers shall be provided with 1/2 inch x 1/4 inch aluminum bird screens, factory-furnished and installed. Louver performance data shall be A.M.C.A. certified. All louvers shall be caulked weathertight around entire perimeter.

2.18 LOUVER BLANK-OFF PANELS

- A. Insulated, Blank Off Panels: Laminated panels consisting of insulating core surfaced on back and front with metal sheets and attached to back of louver.
1. Thickness: 2 inches (50mm)
 2. Metal Facing Sheets: Aluminum sheet, not less than .032 inch (.81mm) nominal thickness.
 3. Insulating Core: Rigid, glass-fiber-board insulation or extruded-polystyrene foam
 4. Edge Treatment: Trim perimeter edges of blank-off panels with louver manufacturer's standard extruded-aluminum-channel frames, not less than .080 inch (2.03mm) nominal thickness with corners mitered and with same finish as panels.
 5. Seal perimeter joints between panel faces and louver frames with gaskets or sealant.
 6. Panel Finish: Same finish applied to louvers.
 7. Attach blank-off panels with stainless steel sheet metal screws.
 8. Cover all unused openings in louvers.

2.19 INTAKE/RELIEF HOODS

- A. Furnish and install heavy gauge aluminum intake/relief hoods of size, capacity, and

arrangement as shown on Contract Drawings. Intake/relief hoods shall be Greenheck Model FHI for intake or Model FHR for relief as manufactured by Greenheck, ACME Engineering, Cook, Twin City, or approved equal.

- B. Gravity roof ventilators shall be constructed of heavy gauge aluminum or galvanized steel. Hoods shall be constructed of precision formed, arched panels with interlocking seams. Bases shall be constructed so that the curb cap is 8 inches larger than the throat size. Insulated roof curbs shall be furnished as specified and shall be of same manufacturer as roof hood.
- C. Hood support members shall be constructed of galvanized steel and fastened so that the hood can be either removed completely from the base or hinged open. Birdscreens constructed of ½ inch galvanized steel mesh shall be mounted horizontally across the intake/discharge area of the hood. Intake units with throat widths through 42 inches shall ship assembled when throat lengths do not exceed 84 inches. Relief units with throat widths through 48 inches shall ship assembled when throat lengths do not exceed 96 inches.
- D. Motor-operated dampers shall be provided by the ATC Subcontractor and installed by Mechanical Contractor.

2.20 LOUVERED INTAKE RELIEF HOODS

- A. Furnish and install heavy gauge aluminum louvered intake/relief hoods of size, capacity, and arrangement as shown on Contract Drawings. Intake/relief hoods shall be Greenheck Model WIH for intake or Model WRH for relief as manufactured by Greenheck, ACME Engineering, Cook, Twin City, or approved equal.
- B. Louvered gravity roof ventilators shall be constructed of heavy gauge aluminum or galvanized steel. Hoods shall be constructed of precision formed, louvered tiers with interlocking seams. Bases shall be constructed so that the curb cap is 8 inches larger than the throat size. Insulated roof curbs, minimum 12 inches tall, shall be furnished as specified and shall be of same manufacturer as roof hood.
- C. Hood support members shall be constructed of galvanized steel and fastened so that the hood can be either removed completely from the base or hinged open. Birdscreens constructed of ½ inch galvanized steel mesh shall be mounted horizontally across the intake area of the hood. Intake units with throat widths through 42 inches shall ship assembled when throat lengths do not exceed 84 inches.
- D. Motor-operated dampers shall be provided by the ATC Subcontractor and installed by Mechanical Contractor.

2.21 OPEN END DUCTS (OED)

- A. Whether indicated on plans or not, all open-ended ducts shall be provided with a protective screen.
- B. All open-ended ducts shall be furnished with a 12 gauge ½ inch x ½ inch aluminum mesh screen. Screens shall be permanently installed in a removable frame, and the frame shall be attached to the open-ended duct in a neat, workmanship-like manner without any

exposed edges or sharp surfaces.

- C. Screen shall be attached to a ¾ inch x 1/8 inch continuous galvanized perimeter frame. Install duct stiffeners greater than 16 inches in any direction at open-ended ducts.

2.22 DRIP PANS

- A. Furnish and install suitable watertight, aluminum drip pans where water or drain piping is routed over electrical switchgear, transformers, computers, elevator machine equipment, dry storage rooms, etc. Each drip pan shall have a 1 inch copper type M drain piped to discharge where shown on drawings; or, if not shown, to discharge over nearest available open drain. Size and arrangement shall be as approved by Engineer. Sides shall be minimum 1.5 inches deep.
- B. Drain pans shall be of 16 gauge welded construction. Provide drawings of typical drain pan construction for approval before construction. See Submittals in Division 01 Section, "Product Requirements".

2.23 DUCT SEALANTS AND ADHESIVES

- A. All ductwork shall be sealed, including low pressure exhaust systems. Transverse joints and longitudinal seams in duct systems shall be sealed with a duct sealant of the type specified hereinafter in Section 1, 2, or 3 or with a tape sealing system as specified in Section 4. Spiral lockseams are not longitudinal seams and do not require duct sealant. All seams and joints shall require duct sealant suitable for the pressure rating and installation application. All sealants shall exceed 500 hours without becoming brittle under ASTM-D572 test conditions (oxygen bomb), unless specified otherwise. No surface preparation or solvent cleaning shall be necessary to remove light coatings of oil and dust before applying sealant unless specified otherwise. Flanged joints shall be sealed according to Section 5. Construction joints that are not fully welded shall be sealed according to Section 6. Adhesive to secure insulation to metal surfaces shall be that specified in Section 7.
 - 1. Assembly joints to be installed indoors or outdoors shall be sealed with Foster 32-19, Childers CP-146, United Duct Sealer WB, or equivalent, which is a water-based sealant formulated to withstand service temperatures from 20 degrees F to +200 degrees F. Sealant shall have a UL Classification marking with a flame spread of 15 and smoke developed of 0 when applied to inorganic reinforced cement board, both at a coverage of 31 square feet per gallon. Store and apply between 40°F (4°C) and 100°F (38°C); protect from freezing.
 - 2. Assembly joints to be installed indoors shall be sealed with Foster 32-19, Childers CP-146, UNI-GRIP™ duct sealer or equivalent, which is a water-based (vinyl-acrylic polymer) sealant formulated to withstand temperatures from -20 degrees Fahrenheit to +200 degrees Fahrenheit. Surfaces to be sealed should be clean, dry, and free from oil, grease, and dirt. Sealant shall be nonflammable (wet) and fire retardant. Sealant shall have a UL Classification marking with a flame spread of 5 and smoke developed of 5 when applied to 18-gauge galvanized steel and a flame spread of 0 and smoke developed of 0 when applied to inorganic reinforced cement board, both at a coverage of 40 square feet per gallon.

3. Assembly joints shall be sealed with UNI-CAST® tape sealing system or equivalent, which is a combination of an adhesive activator and woven-fiber tape impregnated with a gypsum mineral compound. Modified acrylic/silicone activator (MTA-20 for indoor use) reacts exothermically with the tape to form a hard, airtight seal. Sealant shall be formulated to withstand temperatures from –40 degrees F to +200 degrees Fahrenheit. Combination of tape and MTA-20 adhesive shall have a flame spread and smoke developed of 0. Do not use for outdoors.
 4. Flanged joints to be installed indoors shall be sealed with UNI-GASKET™ flange sealer or equivalent, which has a synthetic elastomer base and is formulated to withstand temperatures from –20 degrees F to +150 degrees F. Sealant shall have a UL Classification marking with a flame spread of 5 and smoke developed of 5 when applied to 18-gauge galvanized steel and a flame spread of 0 and smoke developed of 5 when applied to inorganic reinforced cement board, both at a coverage of 80 square feet per gallon.
 5. Where duct fittings are constructed with standing seam or spot-welded techniques, all construction joints shall be sealed with UNI-WELD™ metal cement or equivalent, which is composed of neoprene rubber, resins, and inert reinforcing material dispersed in a petroleum distillate. Sealant shall be formulated to withstand temperatures from –20 degrees F to +225 degrees F. Sealant shall have a UL Classification marking with a flame spread of 0 and smoke developed of 0 when applied to 18-gauge galvanized steel and a flame spread of 0 and smoke developed of 0 when applied to inorganic reinforced cement board, tested as applied in two 1/8 inch beads 8 inches on center.
 6. Where insulation is to be secured to metal surfaces, the adhesive used shall be Foster 85-60, Childers CP-127, UNI-TACK™ duct liner adhesive or equivalent, which are water-based, vinyl-acrylic copolymer adhesives formulated to withstand temperatures from –20 degrees Fahrenheit to +200 degrees Fahrenheit. Adhesive shall have a UL Classification marking with a flame spread of 0 and smoke developed of 0 when applied to 18-gauge galvanized steel and a flame spread of 0 and smoke developed of 0 when applied to inorganic reinforced cement board, both at a coverage of 267 square feet per gallon. Adhesive shall conform to ASTM C916, Type II.
- B. Manufacturers: Duct Mate, United McGill, MKT Metal Manufacturers, Semco, Elgen, Childers, Foster, or as approved equal.

2.24 AUXILIARY DRIP PANS

- A. Furnish and install suitable watertight, aluminum drip pans for all suspended air handling units, heat pumps, or air handling units installed on upper floor and/or attic. Each drip pan shall have a 1" copper type "M" drain piped to discharge where shown on drawings. Drain pan shall extend 3" beyond sides of air handling unit/heat pump. Sides shall be minimum 1.5" deep.
- B. Drain pans shall be of 16 gauge welded construction. Provide drawings of typical drain pan construction for approval before construction. See Submittals, Division 23 Section, "Common Work Results for HVAC" and Division 01, Section, "General Requirements".

- C. Install U.L. 580 listed condensate float switch in auxiliary drain pan and wire to shut-down unit upon sensing water. All control and interlock wiring to be furnished and installed under Division 23 Section, "Instrumentation & Controls of HVAC & Plumbing Systems".

PART 3 EXECUTION

3.1 DUCT INSTALLATION REQUIREMENTS

- A. Coordinate ductwork with other work and install ducts at proper elevations and locations to maintain indicated ceiling heights and clearances. Provide all elbows, transitions, offsets, connections, and other fittings necessary to fit the work into place or to connect to equipment or diffusers. Method of duct support connection to structure and slabs shall be approved by Structural Engineer, and Shop Drawings shall be submitted.
- B. Substantially support ductwork with structural shapes, flat bars, or formed strap hangers securely attached to the building structure by means of bolts, clamps, or inserts. Support vertical ducts by angles attached to the duct and resting on the floor or supported by brackets or hangers attached to the building structure. Strap hangers shall be 16-gauge minimum galvanized steel formed under the bottom edge of duct. Use square ¼ inch thick washers tight against the bend on upper strap attachments to horizontal surfaces. Place all supports external to the ductwork and out of the air stream. Provide additional supports at coils and other concentrated loads. Arrange supports so that duct weight is not transmitted to ceilings, fans or other equipment.
- C. Prevent direct contact between ductwork and building surfaces or other equipment. Where ducts pass through walls, partitions, floors, ceilings, or roofs, pack and seal the space around the duct with an approved fire-safe inert material. Provide flanged duct escutcheons at all exposed ducts that pass through walls, partitions, floors, and ceilings.
- D. Use galvanized (compatible) corrosion-resistant hangers, supports, brackets, and hardware.
- E. Furnish and install NFPA-approved duct connections where shown and at all connections to fans, air handling units, and similar rotating equipment. Use glass-reinforced neoprene fabric, roll-formed to sheet metal strips or flanges. Support adjacent ductwork to provide sufficient slack in the connection.
- F. See NFPA 90A, and latest publication of SMACNA. Prevent direct contact between ductwork and building surfaces or other equipment. The opening in the construction around the duct shall not exceed one-inch average clearance on all sides. Where ducts pass through walls, partitions, floors, ceilings, or roofs, pack and seal the space around the duct with an approved fire-safe inert material capable of preventing the passage of flame and hot gases sufficiently to ignite cotton waste when subjected to the same NFPA 251 Time-Temperature Conditions required for fire barrier penetration. All exposed duct penetrations shall be finished with a sheet metal field erected flange escutcheon to form a neat appearance.
- G. Coordinate duct installation with the requirements of Division 23 Section, "Vibration Controls for HVAC, Plumbing & Fire Protection Equipment".

- H. Install in accordance with manufacturer's instructions.
- I. Install and seal ducts in accordance with SMACNA *HVAC Duct Construction Standards - Metal and Flexible*.
- J. Duct Sizes are inside clear dimensions. For lined ducts, maintain sizes inside lining.
- K. Provide openings in ductwork where required to accommodate thermometers and controllers. Provide pitot tube openings where required for testing of systems, complete with metal can with spring device or screw to ensure against air leakage. Where openings are provided in insulated ductwork, install insulation material inside a metal ring.
- L. Locate ducts with sufficient space around equipment to allow normal operating and maintenance activities.
- M. Use crimp joints, with or without bead, for joining round duct sizes eight (8) inches and smaller with crimp in direction of air flow.
- N. Use double nuts and lock washers on threaded rod supports.
- O. Set plenum doors 6 to 12 inches (150 to 300 mm) above floor. Arrange door swings so that fan static pressure holds door in closed position.
- P. Provide residue traps in kitchen hood exhaust ducts at base of vertical risers with provisions for clean out. Use welded stainless steel for ductwork exposed to view and welded carbon steel for ducts where concealed. Submit to local Health Department calculations, duct layout, hood layout, sizes for all kitchen hood exhaust, make-up air systems prior to fabrication.
- Q. During construction, provide temporary closures of metal or taped polyethylene on open ductwork to prevent construction dust from entering ductwork systems.

3.2 ACCESSORY INSTALLATION REQUIREMENTS

- A. Install accessories in accordance with manufacturer's instruction, NFPA 90A, and SMACNA *HVAC Duct Construction Standards - Metal and Flexible*.
- B. Provide duct access doors for inspection and cleaning before and after filters, coils, fans, automatic dampers, at fire dampers, combination fire and smoke dampers, duct detectors, air flow monitoring stations, duct-mounted equipment, duct coils and elsewhere as indicated. Provide for cleaning kitchen exhaust ductwork in accordance with NFPA 96. Provide minimum 10 x 10 inch size for hand access, 18 x 18 inch size for shoulder access 20 x 20 inch for kitchen exhaust systems. Review locations prior to fabrication.
- C. Provide duct test holes where required for testing and balancing purposes. Review locations with Test and Balance Engineer prior to installation.
- D. Provide fire dampers, combination fire and smoke dampers and smoke dampers at locations indicated, where ducts and outlets pass through fire-rated components, and where required by authorities having jurisdiction. Install with required perimeter

mounting angles, sleeves, breakaway duct connections, corrosion-resistant springs, bearings, bushings and hinges.

- E. Install smoke dampers and combination fire and smoke dampers in accordance with NFPA 92A. Furnish and install a remote test station and connect to damper end switches.
- F. Demonstrate re-setting of fire dampers to Owner's representative.
- G. Provide flexible connections immediately adjacent to equipment in ducts associated with fans and motorized equipment and supported by vibration isolators. Refer to Division 23 Section, "Vibration Control for HVAC and Plumbing Systems".
- H. Provide balancing dampers at points on supply, return, and exhaust systems where branches are taken from larger ducts as required for air balancing. Install minimum duct widths from duct take-off.
- I. Use splitter dampers only where indicated.
- J. Provide balancing dampers on duct take-off to diffusers, grilles, and registers, regardless of whether dampers are specified as part of the diffuser, grille, or register assembly.
- K. Install diffusers, registers, and grilles to ductwork with airtight construction.
- L. Check location of all air outlets and inlets and make necessary adjustments in position to conform with architectural features, window, and lighting arrangements.
- M. Install duct thermometer support flanges in wall of duct. Attach to duct with screws. Locate duct mounted thermometers, minimum 10 feet downstream of mixing dampers, coils or other devices causing air turbulence.
- N. Install remote - reading duct dial thermometers in control panels with tubing connecting panel and thermometer bulb supported to prevent kinks. Use minimum tubing length. Mount control panel 30 inches above finished floor and label each dial thermometer.
- O. Install duct accessories according to applicable details shown in SMACNA's *HVAC Duct Construction Standards--Metal and Flexible* for metal ducts.
- P. Install volume dampers in lined duct; avoid damage to and erosion of duct liner.
- Q. Provide test holes at fan inlet and outlet and elsewhere as indicated.
- R. Install fire, smoke, and combination fire and smoke dampers according to manufacturer's UL-approved written instructions.
1. Install fusible links in fire dampers. Label access doors according to equipment served.
- S. Adjust duct accessories for proper settings.
- T. Adjust fire and smoke dampers for proper action.

3.3 DUCT LINING INSTALLATION REQUIREMENTS

- A. All portions of duct designated to receive duct liner shall be completely covered with duct liner. Transverse joints shall be neatly butted and there shall be no interruptions or gaps. The black pigmented or mat faced surface of the duct liner shall face the airstream.
- B. Duct liner shall be adhered to the sheet metal with 90 percent coverage of adhesive complying with requirements of ASTM C916. All exposed leading edges and transverse joints shall be factory coated or coated with adhesive during fabrication. Install perforated galvanized inner liner where indicated.
- C. Duct liner shall be additionally secured with mechanical fasteners, either weld-secured or impact-driven, which shall compress the duct liner sufficiently to hold it firmly in place. Adhesive bonded pins are not permitted due to long term adhesive aging characteristics. Spacing of mechanical fasteners with respect to duct liner interior width shall be in accordance with SMACNA HVAC DGS. Maximum spacing for mechanical fasteners shall be as follows:

Velocity = 0 to 2,500 feet per minute (0 to 12.8 m/s):

From transverse end of liner	3 inches (75mm)
Across width of duct	12 inches (300 mm) O.C.
From corners of duct	4 inches (100mm)
Along length of duct	18 inches (450mm) O.C.

Velocity = 2,501 to 5,000 feet per minute (12.8 to 25.4 m/s):

From transverse end of liner	3 inches (75mm)
Across width of duct	6 inches (150mm) O.C.
From corners of duct	4 inches (100mm)
Along length of duct	16 inches (400mm) O.C.

- D. When air velocity exceeds 4,000 fpm (20.3m/s), galvanized sheet metal nosing shall be applied to all leading edges of duct liner.
- E. Acoustical Duct Liner shall be cut to assure overlapping and compressed longitudinal corner joints.
- F. Upon completion of installation of duct liner and before operation is to commence, visually inspect the system and verify that the duct liner insulation has been correctly installed.
- G. Open all system dampers and turn on fans to blow all scraps and other loose pieces of material out of the duct system. Allow for a means of removal of such material.
- H. Check the duct system to ensure that there are no air leaks through joints.

3.4 CLEANING

- A. Clean duct system and force air at high velocity through ducts to remove accumulated dust. To obtain sufficient air, clean half the system at a time. Protect equipment which may be harmed by excessive dirt with temporary filters, or bypass during cleaning.

- B. Clean duct systems with high power vacuum machines. Protect equipment which may be harmed by excessive dirt with filters, or bypass during cleaning. Provide adequate access into ductwork for cleaning purposes.
- C. Ductwork shall be cleaned in accordance with “Duct Cleanliness for New Construction (SMACNA 2000)”, and shall achieve a “Basic” cleanliness level.

3.5 LEAKAGE TESTS

- A. All low pressure sheet metal ductwork shall undergo leakage tests at 2 inch W.G. Tests shall be accomplished under this section and witnessed as specified under Division 23 Section, “Testing, Adjusting, and Balancing for HVAC and Plumbing”.
- B. All medium pressure sheet metal ductwork shall undergo leakage tests at 5 inch W.G. Tests shall be accomplished under this section and witnessed as specified under Division 23 Section, “Testing, Adjusting, and Balancing for HVAC and Plumbing”.
- C. Leakage from each duct system shall not exceed 5 percent for low pressure systems and 1 percent for medium pressure systems of the normal air handling capacity of the system. If the system ductwork is tested in sections, the leakage shall not exceed ½ of 1 percent of the CFM to be handled by that section, and the total leakage of the system shall not exceed 1 percent of the total system CFM. Test pressure shall not exceed the pressure limits of the duct construction as defined in *SMACNA High Pressure Duct Construction Standards*. Repair all leaks which are audible, regardless of the leakage rate of the duct system as a whole, by remaking the entire defective joint or seam. Spot sealing of ducts in place *will not* be acceptable.
- D. All duct accessories, including but not limited to volume dampers, ATC sensors, duct detectors, duct coils shall be installed prior to duct leakage testing.
- E. Submit a complete report of the ductwork leakage tests to the Architect and include final approved copies, notes, and balance reports.

3.6 DUCTWORK IDENTIFICATION

- A. Degrease and clean surfaces to receive adhesive for identification materials.
- B. All ductwork shall be identified with painted background marked with the name of the service with arrows to indicate flow direction. Color Code and System Identification shall comply with ANSI Standards.
- C. Marking shall be plain block letters, stenciled on ductwork (above and below ceilings) and shall be located near each branch connection and at least every ten feet on straight runs of ductwork. Where ductwork is aligned adjacent to each other, markings shall be neatly lined up. All markings shall be located in such a manner as to be easily legible from the floor.
- D. Identify ductwork with plastic nameplates or stenciled painting. Identify with air handling unit identification and area served.
- E. Length of color field for ductwork shall be 32 inches. Lettering shall be minimum 3-1/2

inches high.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 23 31 23

EXISTING HVAC AIR DISTRIBUTION SYSTEM CLEANING

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes cleaning existing HVAC air-distribution ducts, plenums, and system components that are indicated to be re-used under new work.
- B. Under Add Alternate the existing ductwork that is indicated to be re-used shall be cleaned. Install building access panels and duct access panels as required to fully clean the existing ductwork that is indicated to be re-used.
- C. Also degrease exterior surfaces of existing exhaust ductwork indicated to remain to allow duct sealing of the same.

1.3 DEFINITIONS

- A. ASCS: Air systems cleaning specialist.
- B. NADCA: National Air Duct Cleaners Association.

1.4 INFORMATIONAL SUBMITTALS

- A. Qualification Data For an ASCS.
- B. Strategies and procedures plan.
- C. Cleanliness verification report.

1.5 QUALITY ASSURANCE

- A. ASCS Qualifications: A certified member of NADCA.
 - 1. Certification: Employ an ASCS certified by NADCA on a full-time basis.
 - 2. Supervisor Qualifications: Certified as an ASCS by NADCA.
- B. UL Compliance: Comply with UL 181 and UL 181A for fibrous-glass ducts.

- C. Cleaning Conference: Conduct conference at Project site.
 - 1. Review methods and procedures related to HVAC air-distribution system cleaning including, but not limited to, review of the cleaning strategies and procedures plan.

1.6 ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

PART 2 - PRODUCTS (Not Used)

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine existing HVAC air-distribution ducts, plenums, and system components that are indicated to remain to determine appropriate methods, tools, and equipment required for performance of the Work.
- B. Perform "Project Evaluation and Recommendation" according to NADCA ACR 2006.
- C. Prepare written report listing conditions detrimental to performance of the Work.
- D. Proceed with work only after unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Prepare a written plan that includes strategies and step-by-step procedures. At a minimum, include the following:
 - 1. Supervisor contact information.
 - 2. Work schedule including location, times, and impact on occupied areas.
 - 3. Methods and materials planned for each HVAC component type.
 - 4. Required support from other trades.
 - 5. Equipment and material storage requirements.
 - 6. Exhaust equipment setup locations.
- B. Use the existing service openings, as required for proper cleaning, at various points of the HVAC system for physical and mechanical entry and for inspection. Add service openings as required to clean existing ductwork.
- C. Comply with NADCA ACR 2006, "Guidelines for Constructing Service Openings in HVAC Systems" Section.

3.3 CLEANING

- A. Comply with NADCA ACR 2006.
- B. Remove visible surface contaminants and deposits from within the HVAC system.
- C. Systems and Components to Be Cleaned:
 - 1. Existing air devices for that are indicated to remain.
 - 2. Ductwork:
 - a. Existing air ducts, including turning vanes that are indicated to remain.
- D. Collect debris removed during cleaning. Ensure that debris is not dispersed outside the HVAC system during the cleaning process.
- E. Remove existing sound lining within existing ductwork.
- F. Particulate Collection:
 - 1. For particulate collection equipment, include adequate filtration to contain debris removed. Locate equipment downwind and away from all air intakes and other points of entry into the building.
 - 2. HEPA filtration with 99.97 percent collection efficiency for particles sized 0.3 micrometer or larger shall be used where the particulate collection equipment is exhausting inside the building,
- G. Control odors and mist vapors during the cleaning and restoration process.
- H. Mark the position of manual volume dampers and air-directional mechanical devices inside the system prior to cleaning. Return them to their marked position on completion of cleaning.
- I. System components shall be cleaned so that all HVAC system components are visibly clean. On completion, all components must be returned to those settings recorded just prior to cleaning operations.
- J. Clean all air-distribution devices, registers, grilles, and diffusers.
- K. Clean visible surface contamination deposits according to NADCA ACR 2006 and the following:
 - 1. Clean airstream surfaces, and components.
 - 2. Ensure that a suitable operative drainage system is in place prior to beginning wash-down procedures.
 - 3. Clean all airstream components.
- L. Duct Systems:
 - 1. Create service openings in the HVAC system as necessary to accommodate cleaning.

2. Mechanically clean duct systems specified to remove all visible contaminants so that the systems are capable of passing the HVAC System Cleanliness Tests (see NADCA ACR 2006).
- M. Debris removed from the HVAC system shall be disposed of according to applicable Federal, state, and local requirements.
- N. Mechanical Cleaning Methodology:
1. Source-Removal Cleaning Methods: The HVAC system shall be cleaned using source-removal mechanical cleaning methods designed to extract contaminants from within the HVAC system and to safely remove these contaminants from the facility. No cleaning method, or combination of methods, shall be used that could potentially damage components of the HVAC system or negatively alter the integrity of the system.
 - a. Use continuously operating vacuum-collection devices to keep each section being cleaned under negative pressure.
 - b. Cleaning methods that require mechanical agitation devices to dislodge debris that is adhered to interior surfaces of HVAC system components shall be equipped to safely remove these devices. Cleaning methods shall not damage the integrity of HVAC system components or damage porous surface materials such as duct and plenum liners.
 2. Cleaning Mineral-Fiber Insulation Components:
 - a. Fibrous-glass thermal or acoustical insulation elements present in equipment or ductwork shall be thoroughly cleaned with HEPA vacuuming equipment while the HVAC system is under constant negative pressure and shall not be permitted to get wet according to NADCA ACR 2006.
 - b. Cleaning methods used shall not cause damage to fibrous-glass components and will render the system capable of passing the HVAC System Cleanliness Tests (see NADCA ACR 2006).
 - c. Fibrous materials that become wet shall be discarded and replaced.
- O. Antimicrobial Agents and Coatings:
1. Apply antimicrobial agents and coatings if active fungal growth is reasonably suspected or where unacceptable levels of fungal contamination have been verified. Apply antimicrobial agents and coatings according to manufacturer's written recommendations and EPA registration listing after the removal of surface deposits and debris.
 2. When used, antimicrobial treatments and coatings shall be applied after the system is rendered clean.
 3. Apply antimicrobial agents and coatings directly onto surfaces of interior ductwork.
 4. Sanitizing agent products shall be registered by the EPA as specifically intended for use in HVAC systems and ductwork.

3.4 CLEANLINESS VERIFICATION

- A. Verify cleanliness according to NADCA ACR 2006, "Verification of HVAC System Cleanliness" Section.

- B. Verify HVAC system cleanliness after mechanical cleaning and before applying any treatment or introducing any treatment-related substance to the HVAC system, including biocidal agents and coatings.
- C. Perform visual inspection for cleanliness. If no contaminants are evident through visual inspection, the HVAC system shall be considered clean. If visible contaminants are evident through visual inspection, those portions of the system where contaminants are visible shall be re-cleaned and subjected to re-inspection for cleanliness.
- D. Additional Verification:
 - 1. Perform surface comparison testing or NADCA vacuum test.
 - 2. Conduct NADCA vacuum gravimetric test analysis for nonporous surfaces.
- E. Prepare a written cleanliness verification report. At a minimum, include the following:
 - 1. Written documentation of the success of the cleaning.
 - 2. Site inspection reports, initialed by supervisor, including notation on areas of inspection, as verified through visual inspection.
 - 3. Surface comparison test results if required.
 - 4. Gravimetric analysis (nonporous surfaces only).
 - 5. System areas found to be damaged.
- F. Photographic Documentation: Document before and after duct cleaning with digital photographs.

3.5 RESTORATION

- A. Restore and repair HVAC air-distribution equipment, ducts, plenums, and components according to NADCA ACR 2000 "Restoration and Repair of Mechanical Systems" Section.
- B. Restore service opening, capable of future reopening.
- C. Replace fibrous-glass materials that cannot be restored by cleaning or resurfacing.
- D. Replace damaged insulation.
- E. Ensure that closures do not hinder or alter airflow.
- F. New closure materials, including insulation, shall match opened materials and shall have removable closure panels fitted with gaskets and fasteners.
- G. Reseal fibrous-glass ducts.
- H. Label all duct access doors.

END OF SECTION

SECTION 23 81 26

VARIABLE REFRIGERANT VOLUME SPLIT SYSTEMS WITH HEAT RECOVERY
(AIR COOLED SYSTEMS)

PART 1 GENERAL

1.1. RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2. SUMMARY

- A. This Section includes Variable Refrigerant Volume Split Systems with Heat Recovery.
- B. Related Sections include the following:
 - 1. Division 23 Section, "HVAC Piping, Fittings, and Valves" for refrigerant piping materials.
 - 2. Division 23 Section, "HVAC Insulation" for refrigerant pipe insulation requirements.
 - 3. Division 23 Section, "Vibration Controls for HVAC, Plumbing, & Fire Protection Equipment" for isolation materials.
 - 4. Division 23 Section, "Instrumentation & Controls of HVAC & Plumbing Systems" for temperature-control devices, and control wiring and control devices connected to indoor, outdoor and refrigerant distribution devices.
 - 5. Division 26 Section, "Disconnect Switches & Circuit Breakers" and circuit breakers for field installed disconnect switches.

1.3. DEFINITIONS

- A. *BICSI*: Building Industry Consulting Service International.
- B. *EER*: Cooling full load energy efficiency ratio.
- C. *IEER*: Cooling integrated (part load) energy efficiency ratio.
- D. *High Temperature COP*: Heating coefficient of performance at 42°F.
- E. *Low Temperature COP*: Heating coefficient of performance at 17°F.
- F. *SCHE*: Simultaneous cooling and heating efficiency.
- G. *VRV*: Variable Refrigerant Volume

1.4. SUBMITTALS

- A. Product Data: Include manufacturer's technical data for each model indicated, including rated capacities of selected model clearly indicated; dimensions; required clearances;

shipping, installed, and operating weights; furnished specialties; accessories; and installation and startup instructions.

- B. Product data for Variable Refrigerant Volume units specified, including the following:
1. Dimension and plans and elevation drawings including field piping, required clearances and locations of all field connections.
 2. Certified fan-sound power ratings.
 3. Certified coil-performance rating with system operating conditions indicated.
 4. Motor ratings and electrical characteristics plus motor and fan accessories.
 5. Filters with performance characteristics.
 6. Outdoor air cooled heat pump unit.
 7. Summary of all auxiliary utility requirements such as electricity, refrigerant piping, and condensate piping. Summary shall indicate quality and quantity of each required utility.
 8. Branch selector box data.
 9. Refnet data.
 10. ARHI 1230 certification including EER, IFEER, high temperature COP, low temperature COP, and SCHE.
 11. Equipment selections de-rated to reflect scheduled data.
 12. VRV equipment certified installer's certificate.
 13. Wiring material product data and wiring layout for all systems: power, VRV control, control systems, interface to BMS and associated VRV equipment.
- C. Shop Drawings: Detail equipment assemblies and indicate dimensions, weights, loadings, required clearances, method of field assembly, components, and location and size of each field connection. Detail mounting, securing, and flashing of roof curb to roof structure for roof mounted units. Detail mounting and securing to concrete pads for grade mounted systems. Indicate coordinating requirements with roof membrane system or concrete pads and vibration isolation.
- D. Wiring Diagrams: Detail wiring for power, signal, and control systems and differentiate between manufacturer-installed and field-installed wiring.
- E. Field Test Reports: Indicate results of manufacturer's startup and testing requirements. Submit copies of checklists.
- F. Maintenance Data: For equipment to include in the maintenance manuals specified in Division 01.
- G. Warranties: Special warranties specified in this Section.
- H. Install factory certified documents indicating approval to install the VRV equipment.

1.3. SYSTEM DESCRIPTION

- A. Furnish and install where indicated, a variable capacity, heat recovery air conditioning system. System shall be a Variable Refrigerant Volume Series split system as manufactured by Daikin, LG, Mitsubishi, Trane, Samsung, Johnson Controls, or approved equal. The system shall consist of multiple indoor units capable of cooling or heating, branch selector

boxes, refrigerant joints to separate refrigerant flow between units and headers (refnets), a three pipe or two pipe refrigeration distribution system using PID control, and an outdoor unit. The indoor units shall be connected to the outdoor units utilizing the specialized piping joints provided by the equipment manufacturer. The outdoor unit shall be direct expansion (DX), air-cooled heat recovery, multi-zone air-conditioning system with fixed speed and variable speed inverter driven compressors using R-410A refrigerant. The outdoor unit may connect to a connected indoor capacity up to 130% of the outdoor unit capacity. All zones are each capable of operating separately with individual temperature control. A dedicated hot gas pipe shall be provided to provide optimum heating operation performance.

- B. Operation of the system shall permit either individual cooling or heating of each indoor unit simultaneously or all of the indoor units associated with one branch cool/heat selector box. Each indoor unit or group of indoor units shall be able to provide set temperature independently via a BMS interface. Provide all interlock wiring between system controllers and building automation system.
- C. Branch cool/heat selector boxes shall be located as shown on the drawing. The branch selector boxes shall have the capacity to control cooling and heating down stream of the box to each individual heat pump unit. The box shall consist of electronic expansion valves, refrigerant control piping and electronics to facilitate communications between the branch selector box and main processor and between the branch selector box and indoor units. The branch selector box shall control the operational mode of the subordinate indoor units. The use of electronic expansion valves ensure continuous heating during defrost, no heating impact during changeover and reduced sound levels.
- D. Manufacturer shall have five years prior experience making similar equipment as described in this specification.

1.6. QUALITY ASSURANCE

- A. All equipment and systems shall be tested and certified in accordance with AHRI 1230 (Performance Rating of Variable Refrigerant Flow (VRF) Multi-Split Air Conditioning and Heat Pump Equipment) and bear the AHRI certification seal.
- B. Fabricate and label refrigeration system to comply with ASHRAE 15, *Safety Code for Mechanical Refrigeration*.
- C. Listing and Labeling: Provide electrically operated components specified in this Section that are listed and labeled.
 - 1. The Terms *Listed and Labeled*: As defined in the National Electrical Code, Article 100.
 - 2. Listing and Labeling Agency Qualifications: A *Nationally Recognized Testing Laboratory* as defined in OSHA Regulation 1910.7.
- D. Comply with NFPA 70 for components and installation.
- E. The units shall be tested by a Nationally Recognized Testing Laboratory (NRTL), in accordance with ANSI/UL 1995 – Heating and Cooling Equipment and bear the Listed Mark.

- F. The system shall be factory tested for safety and function.
- G. Coordination: Coordinate layout and installation of indoor units, outdoor units, refrigerant piping, branch selector boxes, refnets, and other appurtenances with piping and ductwork and with other installations.
- H. Contractor's certified VRV equipment installer must be on site during installation of VRV system, refrigeration piping, control wiring, system controls and interface to BMS, and associated VRV equipment.
- I. Obtain all necessary permits for low voltage and power wiring for VRV system.

1.7. DELIVERY, STORAGE, AND HANDLING

- A. Deliver outdoor and indoor units as factory assembled units with protective crating and covering.
- B. Coordinate delivery of units in sufficient time to allow movement into building or on to roof as indicated.

1.8. WARRANTY

- A. General Warranty: The special warranty specified in this Article shall not deprive the Owner of other rights the Owner may have under other provisions of the Contract Documents and shall be in addition to, and run concurrent with, other warranties made by the Contractor under requirements of the Contract Documents.
- B. Special Warranty: A written warranty, executed by the manufacturer and signed by the Contractor, agreeing to replace components that fail in materials or workmanship, within the specified warranty period, provided manufacturer's written instructions for installation, operation, and maintenance have been followed.
 - 1. Warranty Period: Compressors and Compressor Motor Contactors: Manufacturers standard, but not less than 6 years after date of Substantial Completion.

1.9. ALTERNATES

- A. Refer to Division 01 Section, "Alternates" for description of work under this section affected by alternates.

PART 2. PRODUCTS

2.1. MANUFACTURERS

- A. Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include the following:
 - 1. Daikin, Samsung, Sanyo, LG, Johnson Controls, Mitsubishi, Trane, Samsung, Fujitsu, or approved equal.

- B. Basis of Design was a Daikin 3-pipe system. All scheduled capacities and efficiencies must be met. Cost of any electrical, piping, design, insulation, additional branch selector boxes, heat recovery boxes, refnets, or other changes associated with other approved manufacturers shall be included in the bid and shall be the responsibility of the Contractor. If manufacturer other than the Basis of Design is utilized and the same requires drains at branch selector boxes, Contractor must provide piping, insulation and if needed to condensate pumps at no additional cost to the Owner. This includes power requirements for condensate pumps.

2.2. OUTDOOR UNITS – AIR COOLED

- A. The outdoor unit is designed specifically for use with variable refrigerant volume system components. The outdoor unit shall be factory assembled and pre-wired with all necessary electronic and refrigerant controls. The refrigeration circuit of the condensing unit shall consist of scroll compressors, motors, fans, condenser coil, electronic expansion valves, solenoid valves, 4-way valve, distribution headers, capillaries, filters, shut off valves, oil separators, service ports, refrigerant regulator and all components for a complete functioning system.
- B. The outdoor unit shall be modular in design and should allow for side-by-side installation with minimum spacing.
- C. The following safety devices shall be included on the outdoor unit; high pressure switch, control circuit fuses, crankcase heaters, fusible plug, high pressure switch, overload relay, inverter overload protector, thermal protectors for compressor and fan motors, over current protection for the inverter and anti-recycling timers.
- D. Unit Cabinet: The outdoor unit shall be completely weatherproof and corrosion resistant. The unit shall be constructed from rust-proofed mild steel panels coated with a baked enamel finish.
- E. Fan: The unit shall have one or more propeller type, direct-drive fan motors that have multiple speed operation via a DC (digitally commutating) inverter. The condensing unit fan motor shall have multiple speed operation of the DC (digitally commutating) inverter type, and be of high external static pressure. A field setting switch to a maximum 0.32 in. WG pressure is available to accommodate field applied duct for indoor mounting of condensing units. The fan shall be a vertical discharge configuration and the motor shall have inherent protection and permanently lubricated bearings and be mounted.
- F. Condenser Coil: The condenser coil shall be manufactured from copper tubes expanded into aluminum fins to form a mechanical bond. The heat exchanger coil shall be of a waffle louver fin and rifled bore tube design to ensure high efficiency performance. The fins are to be covered with an anti-corrosion acrylic resin and hydrophilic film and pipe plates shall be treated with powdered polyester resin for corrosion prevention.

- G. Compressor: Unit shall contain both fixed speed scroll and variable speed inverter scroll compressors. Inverter scroll compressors shall be variable speed (PAM inverter) controlled which shall be capable of changing the speed to follow the variations in total cooling and heating load as determined by the suction gas pressure as measured in the condensing unit. In addition, samplings of evaporator and condenser temperatures shall be made so that the high/low pressures detected are read and calculated. Each non-inverter compressor shall also be of the hermetically sealed scroll type. With each reading, the compressor capacity (IN V frequency or STD ON/OFF) shall be controlled to eliminate deviation from target value. Compressors shall be spring mounted to avoid the transmission of vibration.
- H. Surge Protection: Provide unit with DIN Rail Plug-in Surge Protection for each compressor unit installed for all telecom and control circuits. Surge protection shall be factory or field installed per manufacturer's recommendations. Surge protectors shall be model DLA as manufactured by Citel or approved equal. Units shall be listed in accordance with UL497B.

2.3. BRANCH SELECTOR/HEAT RECOVERY BOX

- A. Branch selector (BS)/heat recovery boxes shall be located as shown on the drawing. The BS/heat recovery box shall be furnished with at least 5 electronic expansion valves (EEV's), refrigerant control piping and electronics to facilitate communications between the BS/heat recovery box and main processor and between the BS/heat recovery box and indoor units. The BS box shall control the operational mode of the subordinate indoor units. The use of five EEV's shall control the direction of refrigerant flow and ensure continuous heating during defrost, no heating impact during changeover and reduced sound levels. The branch selector/heat recovery boxes shall be designed specifically for use with heat recovery system components. These selector/heat recovery boxes shall be factory assembled, wired, and piped and shall be run tested at the factory. Unit Cabinet shall have a galvanized steel plate casing. Each cabinet shall house a liquid gas separator and contain a tube in tube heat exchanger. The unit shall have sound absorption thermal insulation material made of flame and heat resistant foamed polyethylene. Each circuit shall have at least one branch selector/heat recovery box to facilitate simultaneous heating and cooling in the system. Multiple indoor units may be connected to a branch selector/heat recovery box provided they are within the capacity range of the branch selector. The unit electrical power shall be as scheduled on the Contract Drawings. Each branch selector shall support up to four heat pump units, each served by dedicated refrigerant suction and liquid piping. Each heat pump unit shall be able to individually operate in heating or cooling mode.

2.4. INDOOR UNITS

- A. Ceiling Cassette Indoor Unit - The unit shall be completely factory assembled and wired. The casing shall be galvanized sheet with grey heat insulation. This unit shall fit in the ceiling and have the capability of attaching a branch supply duct as well as a fresh air duct. The evaporator fan shall be an assembly with a high performance, fan direct driven by a single motor. The fans shall be statically and dynamically balanced and run on permanently lubricated bearings. The indoor unit shall have an adjustable air outlet system offering 4-way air flow, 3-way air flow, or 2-way air flow. The auto air swing vanes shall automatically swing up and down for uniform air distribution. Return air shall be filtered by a long-life filter to provide approximately, 2500 hours of use in a normal office environment before cleaning. The indoor unit shall be covered with a flat panel which protrudes only 1 inch below the ceiling to provide a neat and clean installation. The coils shall be of

nonferrous construction with smooth plate fins bonded to copper tubing. The tubing shall have inner grooves for high efficiency heat exchange. All tubes joints shall be brazed with phoscopper or silver alloy. The coils shall be pressure tested at the factory. A condensate pan shall extend under the coil and piping. An integral drain pan pump capable of lifting condensate 22 inches shall be provided. An integral booster heater shall not be provided to supplement the unit during the heating mode. The unit electrical power requirements shall be as scheduled on the contract drawings. Furnish with condensate overflow float switch that will shut down unit should a high condensate level condition be sensed.

2.5. CONTROL SYSTEM

- A. The control system shall consist of multiple microprocessors interconnected by a single non-polar two wire multiplex transmission system. Wiring shall be daisy chained from unit to unit direct. NO SPLICES. One microprocessor shall be factory wired and located within each indoor unit. It shall have the capability of sensing return air temperature and indoor coil temperature; receive and process commands from the remote controller. The microprocessor within the wall mounted remote controller shall provide automatic cooling and heating system changeover; display set point and room temperature; a 24 hour on/off timer so that automatic operation can be set on the unit at one hour intervals from one to twenty-four hours; have self-diagnostic function display; check mode for memory of most recent problem; and provide on-off and system/mode function switching. The heating system shall be controlled so that only warm air is discharged whenever the fan speed exceeds the very low (VLO) speed. Normal operation of the remote controller provides individual system control in which one remote controller and one indoor unit are installed in the same room. The control voltage between the indoor units and the outdoor unit shall be 16 volts D.C. 16 VDC shall be generated from the outdoor unit microprocessor board. The system shall be capable of automatic restart when power is restored after power interruption. System shall include twenty function self diagnostics including total hours of compressor run time. Compressor capacity shall be modulated automatically to maintain a constant suction pressure, while varying the refrigerant volume for the needs of the cooling or heating loads. Indoor units shall use PID control to control superheat.
- B. System Controller. Control system shall include a central controller for user interface with system. Controller shall include a Liquid Crystal Display (LCD) touch screen capable of controlling up to 16 outdoor units and 64 indoor unit groups (maximum 128 indoor units).
- C. System Controller shall be able to control the following functions:
1. On/Off selection for each indoor unit group or zone that is defined with several indoor unit groups.
 2. Setpoint adjustment for each indoor unit group or zone.
 3. Fan speed adjustment for each indoor unit group or zone.
 4. Heat/cool/fan mode selection for each indoor unit group or zone.
 5. Automatic changeover and antifreeze/overheat protection.
 6. Forced shutdown terminals.
 7. Priority settings for restriction of local access for start/stop, heat/cool mode and setpoint adjustment (at local remote controllers).
 8. Setpoint limitation in both heating and cooling mode.
 9. Weekly schedule with start-up and shut off times, temperature settings, and operation modes; 16 operations/each day can be set in one schedule, and 8

different schedules are available for special working days, holidays, or period of non-use.

10. Actual time display and setting.
 11. Reset ability for malfunction codes and filter maintenance warning.
 12. Maximum 13 months back up power supply to maintain the memory.
 13. Non systems units (e.g. energy recovery ventilator) can be started/stopped and general alarm/status reported using Digital Input or Digital Input/Output units, including interlock program.
 14. Controller must be BACnet compatible.
- D. Controller shall provide control transformer for 24 VAC supply voltage for controllers as required.
 - E. Provide interface devices as required to interface to Building Automation System. ATC Interface shall allow monitoring of all points indicated on the point list.
 - F. Furnish the controls with the necessary interfaces to communicate via BACnet/IP or LonWorks to a building automation system. Exact protocol to be determined by the ATC subcontractor and VRV installing contractor.
 - G. All inputs and outputs on the manufacturer's controller shall be viewable via the interface.
 - H. All set points and schedules shall be editable via the interface by the building automation system.
 - I. In addition to standard inputs/outputs, provide additional input/outputs as required to accomplish sequence of operation and items listed on point list.
 - J. The manufacturer shall be responsible for assisting and participating in the integration of the equipment into the building automation system and shall provide programming support, testing, verification, and on site personnel as required.

2.6. WIRING

- A. All wiring devices and wire/cable shall be approved for the proposed purpose.
 1. Communication cable shall be indicated for use in the data sheet
 - a). Bacnet
 - b). Lon
 - c). RS-232
 - d). RS-485 for VRV Loop wiring
 2. All wire/cable shall be installed per VRV and wire/cable manufacturers' data sheets.
 3. All wiring devices and wire/cable shall be labeled by UL or approved listing agency.
- B. All installation contractors must have one person on site with five years experience in the trade during the complete installation process.
- C. All wiring shall be installed per National Electric Code, BICSI and all other codes.
- D. All wiring shall be installed in a neat, best and most workmanlike manner using the proper hangers and the protection of wiring in the installed method used.

- E. Installing contractor must supply an electrical permit for record purposes before work begins.
- F. Equipment supplier equipment shall not be installed as a single point of failure by the control contractor.
- G. Equipment manufacturer shall supply control contractor with a pre-wired and tested control NEMA 1 enclosure with gateway, power supply and terminal strips. A complete set of wiring diagrams for the interface must be submitted and included in the O&M manual.
- H. Control panel power shall have a separate 120 volt single phase circuit with no other load on the circuit.

2.7. VRF/VRV SYSTEMS BACNET GATEWAY

- A. The VRF/VRV Systems BACnet™ Gateway shall be capable of monitoring up to 256 indoor units and 64 outdoor units through its embedded web browser. The BACnet Gateway shall be capable of controlling 92 indoor units and 8 outdoor units through its embedded web browser with third-party Building Automation Systems interface. The BACnet Gateway provides multiple energy management schemes and integrates with third-party Building Automation Systems.

2.8. FILTERS

- A. In addition to the washable filters provided with each indoor unit, provide two (2) sets of spare additional washable filters for every indoor unit on the project. Provide correspondence documenting filters have been turned over to Owner at Substantial Completion.

PART 3. EXECUTION

3.1. EXAMINATION

- A. Examine space for compliance with requirements for conditions affecting installation and performance of units. Do not proceed with installation until unsatisfactory conditions have been corrected.

3.2. INSTALLATION

- A. Mount indoor and outdoor units as detailed on contract drawings and according to manufacturer's written instructions.
- B. Install all interlock and control wiring between indoor units, outdoor units thermostats, and condensate pumps.
- C. Supply initial charge of refrigerant and oil as required.
- D. Install indoor ceiling cassettes and ducted units on vibration isolators.

- E. Install outdoor units on concrete pads or on roof curbs as indicated on drawings.
- F. Comb out fins on condensing unit where deformed or bent. Replace or repair broken fins.
- G. Install condensate lift pumps, float switches, alarm, unit shut down wiring and detection block units per manufacturer's recommendations.
- H. For wall mounted units field wire power wiring, alarm circuits, control cable, safety circuit connection, alarm, and condensate pump. Condensate pump shall be powered from indoor unit power wiring. Coordinate condensate pump electrical characteristics with indoor unit electrical characteristics.
- I. Install system controller and interlock all indoor and outdoor units.
- J. Install lockable caps on all outdoor unit refrigerant service valves to prevent tampering.
- K. All final pipe lengths shall be submitted to VRV manufacturer to verify compliance with manufacturer's requirements.
- L. Install all refrigerant piping per manufacturer's requirements without deviation.
- M. Label and identify all indoor units, outdoor units, piping, and branch selector boxes.
- N. Install refnets and Y-fittings with manufacturers' required unobstructed distances upstream and downstream of the same.
- O. Submit pressure test reports and vacuum test reports as informational submittals.
- P. Install all branch selector boxes with manufacturer's required clearances. Also branch selector boxes shall be installed level per manufacturer's requirements.

3.3. CONNECTIONS

- A. Drawings indicate the general arrangement of piping, fittings, and specialties. The following are specific connection requirements:
 1. High/low pressure gas line, liquid and suction lines must be individually insulated between the outdoor and indoor units.
 2. Refrigerant Piping: conform to applicable requirements of Division 23 Section, *HVAC Piping, Fittings, and Valves*.
 3. Install refrigerant piping, refnets, Branch selector boxes, insulation, and control wiring as required by the manufacturer.
 4. Install isolation valves on all three pipes between outdoor unit and branch selector boxes.
 5. Install isolation valves on both pipes at every indoor unit.
- B. Electrical: Conform to applicable requirements in Division 26 Sections.
- C. Ground equipment.

1. Tighten electrical connectors and terminals according to manufacturer's published torque-tightening values. Where manufacturer's torque values are not indicated, use those specified in UL 486A and UL 486B.

3.4. COMMISSIONING AND MANUFACTURER'S FIELD SERVICES

- A. Verify that installation is as indicated and specified. Provide factory authorized start-up and training.
- B. Complete manufacturer's installation and startup checks and perform the following:
 1. Inspect for visible damage to unit casing.
 2. Inspect for visible damage to compressor, air-cooled condenser coil, and fans.
 3. Verify that clearances have been provided for servicing.
 4. Check that labels are clearly visible.
 5. Clean condenser and inspect for construction debris.
 6. Verify wiring is installed per VRF installation manual requirements
 - a). Grounds
 - b). Shielding
 - c). Prior to applying power perform and document end to end continuity test for each wire in the communication cable.
 7. Verify that controls are connected and operable.
 8. Verify that filters are installed.
 9. Adjust vibration isolators.
 10. Verify all piping and branch selector boxes are insulated.
- C. Start unit according to manufacturer's written instructions.
 1. Complete start-up sheets and attach copy with Contractor's startup report.
 2. Start-up unit in close coordination with testing/balancing.
- D. Check and record performance of interlocks and protection devices; verify sequences.
- E. Operate unit for an initial period as recommended or required by manufacturer.
- F. Calibrate thermostats and humidity sensors.
- G. Check internal isolators.
- H. Start refrigeration and measure and record the following:
 1. Coil leaving-air, dry- and wet-bulb temperatures.
 2. Coil entering-air, dry- and wet-bulb temperatures.
 3. Refrigerant suction/discharge pressures.
 4. Indoor and outdoor unit amperage, voltage, and watts.
 5. Fan Rotation and RPM.
 6. Condensate pump operation.
 7. Condensate overflow safety switch operation.
 8. System controller operation.

3.5. DEMONSTRATION

- A. Engage a factory-authorized service representative to train Owner's maintenance personnel as specified below:
1. Review data in the maintenance manuals. Refer to Division 01 Section, *Contract Closeout*.
 2. Review data in the maintenance manuals. Refer to Division 01 Section, *Operation and Maintenance Data*.
 3. Schedule training with Owner, through Architect, with at least 7 days' advance notice.

3.6. TRAINING

- A. The Variable Refrigerant Volume Split System manufacturer shall include in his bid, provisions for additional training at the company's regular school or training center. The VRV manufacturer shall include in his bid all costs associated with sending two (2) individuals to the VRV manufacturer's school for a period of not less than one (1) week. This training is in addition to the aforementioned training required under the General Provisions.
- B. The training time period shall be coordinated with the school system's facility Engineer. The schedule training period shall be arranged at the Owner's convenience.
- C. Cost shall include all training material, instruction books, and two copies of video tape with sound DVD of training session.
- D. Upon completion of the work, the Contractor shall have completely adjusted the entire control system. He shall arrange to instruct the Owner's representative on the operation of the VRV split system for a period of not less than four (4) four (4) hour days. All training shall be by the VRV split system manufacturer and shall utilize specified manuals and as-built documentation.
- E. Engage a factory-authorized service representative to train Owner's maintenance personnel to adjust, operate, and maintain control systems and components.
1. Train Owner's maintenance personnel on procedures and schedules for starting and stopping, troubleshooting, servicing, and maintaining equipment and schedules.
 2. Provide operator training on data display, alarm and status descriptors, requesting data, executing commands, calibrating and adjusting devices, resetting default values, and requesting logs. Include a minimum of 40 hours' dedicated instructor time on-site.
 3. Review data in maintenance manuals. Refer to Division 01 Section, *Contract Closeout*.
 4. Review data in maintenance manuals. Refer to Division 01 Section, *Operation and Maintenance Data*.
 5. Schedule training with Owner, through Architect, with at least seven days' advance notice.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 23 82 22

PACKAGED KITCHEN HOOD VENTILATION CONTROL SYSTEMS

PART 1 - GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes the following:

1. Packaged Kitchen Hood Ventilation Control Systems

- B. Related Sections include the following:

1. Division 23 Section, *Heating, Ventilating, and Air Conditioning* for hood make-up units.
2. Division 23 Section, *Heating, Ventilating, and Air Conditioning* for hood exhaust fans.
3. Division 23 Section, *Instrumentation & Controls of HVAC & Plumbing Systems* for temperature control and contract drawings for sequences of operation.

1.3 SUBMITTALS

- A. Comply with the requirements of Division 01 Section *Submittal Procedures*.

- B. For Approval:

1. Product Data: Include rated capacities, furnished specialties, and accessories.
2. Shop Drawings: Detail equipment assemblies and indicate dimensions, weights, loads, required clearances, method of field assembly, components, and location and size of each field connection. Prepare the following:
 - a. Mounting Details: For securing variable speed drives, temperature sensors, optical sensors, and key pads to kitchen hoods. Indicate coordinating requirements with kitchen hood.
 - b. Wiring Diagrams: Power, signal, and control wiring.
3. Coordination Drawings: Equipment mounting details drawn to scale, on which the following items are shown and coordinated with each other, based on input from installers of the items involved:
 - a. Size and location of variable speed drives, temperature sensors, optical sensors and key pads and methods for anchoring units to kitchen hoods.

- C. For Information:
1. Startup service reports.
 2. Operation and Maintenance Data: For packaged kitchen hood ventilation control systems to include in emergency, operation, and maintenance manuals.

1.4 QUALITY ASSURANCE

- A. Product Options: Drawings performance requirements of packaged kitchen hood ventilation systems are based on the specific system indicated. Refer to Division 01 Section *Product Requirements*.
- B. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.

1.5 COORDINATION

- A. Coordinate supply fan speed control of direct fired H & V units, make-up air units are specified in Division 23.
- B. Coordinate installation of equipment and devices with kitchen hoods. Coordinate exhaust fan and make-up air unit speed control of hood exhaust fans and make-up air units. Hood exhaust fans are specified in Division 23. Hood exhaust fans and make-up air units are specified in Division 23 Section, "Heating, Ventilating, and Air Conditioning Equipment".
- C. Coordinate with Division 23 "Common Work Results for HVAC". Furnish and install motor bearing protective rings at all variable frequency drive motors.

PART 2 - PRODUCTS

2.1 MANUFACTURERS

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
1. Melink Corporation:

2.2 PACKAGED UNITS

- A. Factory assembled, pre-wired, self contained units consist of processors key pads, temperature sensors, optic sensors, air purge units, and variable frequency drives.
- B. The kitchen ventilation control system shall automatically control the speed of the exhaust and make-up air fan(s) to ensure optimal hood performance. The system includes the following: I/O Processor, Keypad, Temperature Sensors, Optic Sensors, Electronic Motor Starters (VFD's which replace magnetic starters for 3-phase motors), and cables.

2.3 I/O PROCESSOR

- A. Processor shall be housed in painted enclosure for durable construction and a smooth finish. The processor shall have the capability of interfacing with up to four (4) pairs of optic sensors, four (4) temperature sensors, four (4) electronic motor starter interfaces plus supply fan command and eight (8) Air purge units. When required provide multiple processors should the quantity of hoods/fans exceed four (4) per processor. The processor shall include the following:
1. Auto Start/Stop Command and Timer function.
 2. Winter Setback Mode.
 3. Comfort Mode: Utilizes cool outside air to keep kitchen comfortable.
 4. Smoke Detection Relay.
 5. Two (2) alarm relays for controlling external devices based on exhaust temperature.
 6. Plug-n-play cables provided for quick and easy installation.
 7. 4-20 milliamp signal output.

2.4 KEYPAD

- A. The Keypad shall provide light and fan operation, 100% sensor bypass capability, system setup (i.e. minimum speed, temperature span) and monitoring (i.e. percent fan speed, temperature level, diagnostics). One keypad shall be capable of controlling up to two (2) I/O Processors.

2.5 TEMPERATURE SENSOR(S)

- A. Temperature sensor(s) shall be mounted in the exhaust duct of each hood to monitor the exhaust air temperature. An analog 4-20 ma signal shall be sent from the I/O Processor to the respective Electronic Motor Starters to automatically adjust fan speed for each hood based on actual heat load. The sensor(s) shall be housed in a stainless steel (304L) housing for durable construction and smooth finish. The stainless steel probe shall be ¼" outside diameter with a .20" wall thickness. The sensor(s) shall be rated for operating temperature of 1000 degrees F.

2.6 OPTIC SENSOR(S)

- A. The optic sensors consist of an Emitter and a Receiver, which get mounted on opposite ends of the kitchen hood. An infrared beam spans the length of the hood to detect any smoke/vapors generated by the cooking appliances. Upon detection, a full "on" signal shall be sent to the I/O processor, which automatically ramps the fan(s) up to 100% speed. The optic sensor(s) shall have the following features:

1. Stainless steel housing (304L) for durable construction and smooth finish.
2. Spring push buttons on housing for easy removal and cleaning.
3. Stainless steel air purge pipe (304L).
4. Air purging capability to prevent fouling of optic lenses.
5. Air straightening channel for optimal effectiveness of air purge.
6. Alignment nuts and springs for easy alignment of Emitter and Receiver.
7. Maximum distance between Emitter and Receiver shall be 45 feet.

2.7 AIR PURGE UNIT(S)

- A. The APU consists of a miniature blower and high efficiency filter mounted on each end of the kitchen hood, over the Optic Sensors. The purpose is to pressurize the Emitter and Receiver housing with clean air to prevent grease vapors from fouling the optic lenses. The APU shall have the following characteristics:
1. Compact and rugged blower construction for easy installation and maximum life.
 2. Permanently lubricated ball bearings to eliminate maintenance.
 3. High efficiency cartridge filter.
 4. Filter bracket for easy replacement of cartridge filter every 2-5 years.

2.8 ELECTRONIC MOTOR STARTERS

- A. The electronic motor starters are variable frequency drives (VFD), which shall be used to control the exhaust and supply fan motors. The VFD modulates the speed of the fan motors by varying the output voltage and frequency based on a signal received from the I/O processor. The VFD will send a feedback signal to the I/O processor in order for the keypad to display the actual speed of the motor. The Electronic motor starters shall have the following characteristics:
1. NEMA 1 Enclosure.
 2. Full across the line bypass/starter.
 3. Soft-Start Capability.
 4. Digital keypad displays output frequency, current, voltage, and allows programming for field modifications.
 5. Protective functions: motor overload, overheating, overcurrent, overvoltage, output shorts, etc.
 6. High and low frequency limiters.
 7. Adjustable torque boost.
 8. Plug-n-play cables provided for quick and easy installation.
 9. Single point power connection.
 10. Coordinate exact size of VFDs based on approved submittals for make-up air units and exhaust fans.
 11. VFDs shall be provided under this Division and shall be remote mounted when shown on the Contract Drawings.

2.9 MOTORS

- A. General requirements for motors are specified in Division 23 Section "Common Work Results for HVAC".
1. Controllers, Electrical Devices, and Wiring: Electrical devices and connections are specified in Division 26 Sections.

PART 3 - EXECUTION

3.1 EXAMINATION

- A. Examine substrates areas and conditions with Installer present for compliance with requirements for installation tolerances and other conditions affecting performance .
- B. Examine roughing-in for hood suppression piping, hood exhaust ductwork systems to verify actual locations of piping connections before equipment installation.
- C. Examine kitchen hoods and ceilings for suitable conditions where variable frequency drives will be installed.
- D. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION

- A. Install packaged kitchen hood ventilation control systems per manufacturer's requirements.
- B. Install interlock wiring between motors and variable frequency drives.
- C. Install processors and variable frequency drives in the utility cabinet.
- D. Install wiring to shunt trip breakers and gas solenoid valves. Interlock with fire alarm system.
- E. Install temperature sensors in exhaust duct collars.
- F. Install optic sensors in the inside ends of each hood with air purge units mounted on top.
- G. Wire system components with pre-in-play cables.
- H. Install controls and equipment shipped by manufacturers for field installation with packaged kitchen hood ventilation control system.
- I. Mount key pads at kitchen hoods.
- J. Install and interlock air flow monitoring station. Interlock with ATC system.

3.3 CONNECTIONS

- A. Install sensors, cabinet, variable speed drives and key pads adjacent to kitchen hoods to allow service and maintenance.
- B. Ground equipment according to Division 26 Section *Grounding and Bonding*.
- C. Connect wiring according to Division 26 Section *Conductors and Cables*.
- D. Interlock packaged kitchen control system with ATC system.

3.4 FIELD QUALITY CONTROL

- A. **Manufacturer's Field Service:** Engage a factory-authorized service representative to inspect, test, and adjust field-assembled components and equipment installation, including connections, and to assist in field testing. Report results in writing.

3.5 STARTUP SERVICE

- A. Engage a factory-authorized service representative to perform startup service.
 - 1. Complete installation and startup checks according to manufacturer's written instructions.

3.6 ADJUSTING

- A. Adjust initial temperature and optic sensor set points.
- B. Set field-adjustable switches and circuit-breaker trip ranges as indicated.
- C. Adjust variable frequency drives and fan speed set points. Coordinate with Test and Balance Engineer.
- D. Adjust pre-set minimum supply fan and exhaust fan air flow rates.

3.7 DEMONSTRATION

- A. Engage a factory-authorized service representative to train Owner's maintenance personnel to adjust, operate, and maintain Packaged Kitchen Hood Ventilation Control Systems. Refer to Division 01 Section, *Closeout Procedures* and *Demonstration and Training*.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 26 05 01

COMMON WORK RESULTS FOR ELECTRICAL

PART 1. GENERAL

1.1 GENERAL

- A. Provide all labor, materials, equipment and services necessary for and incidental to the complete installation and operation of all electrical work.
- B. All work under this Division is subject to the General Conditions and Special Requirements for the entire contract.
- C. Unless otherwise specified, all shop drawings and submissions required under Division 26 shall be made to, and acceptances and approvals made by, the ENGINEER.
- D. Conform to the requirements of all rules, regulations, and codes of local, state, and federal authorities having jurisdiction. Conform to the National Electrical Code and all NECA – National Electrical Installation Standards (NEIS).
- E. Perform the work in a first-class, substantial, and workmanlike manner. Any materials installed which do not present an orderly and neat workmanlike appearance shall be removed and replaced when so directed by the Engineer, at the Contractor's expense.
- F. Coordinate the work of all trades.
- G. Arrange conduit, wiring, equipment, and other work generally as shown, providing proper clearances and access. Carefully examine all contract drawings and fit the work in each location without substantial alteration. Where departures are proposed because of field conditions or other causes, prepare and submit detailed drawings for approval in accordance with "Submittals" specified below. The right is reserved to make reasonable changes in location of equipment, conduit, and wiring up to the time of rough-in or fabrication.
- H. The contract drawings are generally diagrammatic and all offsets, bends, fittings, and accessories are not necessarily shown. Provide all such items as may be required to fit the work to the conditions.
- I. Be responsible for all construction means, methods, techniques, procedures, and phasing sequences used in the work. Furnish all tools, equipment and materials necessary to properly perform the work in a first class, substantial, and workmanlike manner, in accordance with the full intent and meaning of the Contract Documents.
- J. The Contractor shall provide other work and services not otherwise included in the Contract Documents that are customarily forwarded in accordance with generally-accepted construction practices.

1.2 PERMITS, INSPECTIONS, AND FEES:

- A. The Contractor shall obtain and pay for all charges and fees, and deliver all permits, licenses, certificates of inspection, etc., required by the authorities having jurisdiction. Deliver inspection, approval, and other certificates to the Owner prior to final acceptance of the work.
- B. File necessary plans, prepare documents, give proper notices, and obtain necessary approvals.
- C. Permits and fees shall comply with the General Requirements of the Specification.
- D. Notify Inspection Authorities to schedule inspections of work. All work shall be subject to field inspections.
- E. Notify Engineer in advance of scheduled inspections.
- F. An electrical foreman, superintendent or other supervisor shall be in attendance for all scheduled inspections.
- G. The Contractor shall provide an electrical certificate from an independent electrical inspection agency approved by the Owner and the State of Delaware Fire Marshal. The Contractor shall submit certificate prior to final payment invoice. The Contractor shall pay all fees, including filing fees.

1.3 ELECTRICAL WORK UNDER OTHER DIVISIONS:

A. Mechanical Equipment and Systems

1. In general, power wiring and motor starting equipment for mechanical equipment and systems are furnished and installed under Electrical Division 26.
2. Certain mechanical units contain starters, contacts, transformers, fuses, wiring, etc., required for fans, pumps, etc., furnished with the equipment from the factory. When this equipment is supplied from the factory, the Contractor must supply power circuit(s) to the unit and a disconnecting means. Coordinate with Contractor so that one, and only one, set of starters, fuses, switches, etc., is provided and installed.
3. In general, control and interlock equipment for HVAC systems (including associated wiring, conduit, transformers, relays, contacts, etc.) is furnished under Mechanical Divisions. Contractor shall install and connect all such equipment as necessary.
4. Controls, wiring, conduit, transformers, etc., for smoke, fire, and motor-operated dampers are provided by Mechanical. Electrical shall install and connect all such equipment.

B. Architectural Equipment: In general, any electrically operated or controlled equipment furnished under architectural divisions shall be supplied with control wiring, transformers, contacts, etc. Contractor shall provide power circuits to such equipment and install all electrical control equipment related thereto.

C. Carefully review the contract documents and coordinate the electrical work under the various Divisions.

1.4 CONTRACTOR QUALIFICATION:

- A. Any Contractor performing work under this Division shall be fully qualified and acceptable to the Engineer. Submit the following evidence for approval:
 - 1. A list of not less than five (5) comparable projects that the Contractor completed.
 - 2. Letters of reference from not less than three (3) registered professional engineers, contractors, or building owners, explaining Contractor proficiency, quality of work, or other attribute on projects of similar size or substance.
 - 3. Local or State license.
 - 4. Membership in trade or professional organization where required.
 - 5. Copy of Master Electrician's License.
- B. Contractor is any individual, partnership, corporation, or firm performing work by Contract or subcontract on this project.
- C. Acceptance of a subcontractor will not relieve the Contractor of any contractual requirements or his responsibility to supervise and coordinate the various trades.
- D. Supervisory Qualifications: The electrical work on the project shall be under the direct supervision of a licensed Master Electrician.
- E. Qualifications of Installers:
 - 1. For the actual fabrication, installation, and testing of the work, the Contractor shall use only thoroughly trained and experienced personnel who are completely familiar with the requirements of this work and with the installation recommendations of the manufacturers of the specified items.
 - 2. The Electrical Installer shall utilize a full time project foreman in charge of all electrical work. This person shall be fully qualified and experienced in such work and shall be available, on site, at all times during Construction. All problems, questions, coordination, etc., relating to electrical work shall take place through this person to the Architect.

1.4 FIRE SAFE MATERIALS:

- A. Unless otherwise indicated, materials and equipment shall conform to UL, NFPA, or ASTM Standards for Fire Safety with Smoke and Fire Hazard Rating not exceeding flame spread of 25 and smoke developed of 50.

1.5 REFERENCED STANDARDS, CODES, ORDINANCES AND SPECIFICATIONS

- A. Specifications, Codes and Standards listed below are included as part of this specification, latest edition.

ADA	Americans with Disabilities Act
ANSI	American National Standards Institute

ASHRAE	American Society of Heating, Refrigerating and Air Conditioning Engineers
ASME	American Society of Mechanical Engineers
ASTM	American Society for Testing and Materials
IBC	International Building Code
CABO	Council of American Building Officials
FM	Factory Mutual
IEEE	Institute of Electrical and Electronics Engineers
NEC	National Electrical Code
NECA	National Electrical Contractors Association
NEMA	National Electrical Manufacturers Association
NFPA	National Fire Protection Association
OSHA	Occupational Safety & Health Administration
UL	Underwriters Laboratories
	Applicable State and Local Codes

B. All electrical equipment and materials shall comply with the Codes and Standards listed in the latest edition of IEEE Standard 241 *Electric Power Systems in Commercial Buildings*, Chapter 1, Section 1.6, entitled “Codes and Standards”.

C. Comply with all Codes applicable to the work:

1. Bidders shall inform themselves of all local and state codes and regulations.
2. In case of conflict between Contract Documents and governing Codes, the most stringent shall take precedence. Where, in any specific case, different sections of any applicable codes or when Drawings and Specifications specify different materials, methods of Construction, or other requirements, the most restrictive shall govern.
3. Where Contract Documents exceed minimum Code requirements, and are permitted under the Code, the Contract Documents take precedence and shall govern.
4. No extra payment will be allowed for work or changes required by local Code enforcement authorities.

D. Underwriters Laboratories Labels shall apply to all materials and devices, etc., except specified items not covered by existing UL Standards.

E. Conflicts with applicable regulations:

1. Resolve at Contractor's expense.
2. Prepare and submit details of alternate construction:
 - a. Acceptable solution of conflict.
 - b. List of substitute materials:

For approval of inspecting authorities.

For approval of Engineer.

- F. Comply with all NECA's National Electrical Installation Standards (NEIS), including NECA 1-2000 "Standard Practices for Good Workmanship in Electrical Contracting".

1.6 INTERPRETATION OF DOCUMENTS

- A. Any discrepancies between Drawings, Specifications, Drawings and Specifications, or within Drawing and Specifications shall be promptly brought to the attention of the Owner during the bidding period. No allowance shall subsequently be made to the Contractor by reason of his failure to have brought said discrepancies to the attention of the Owner during the bidding period or of any error on the Contractor's part.
- B. The locations of products shown on Drawings are approximate. The Contractor shall place the devices to eliminate all interference with above-ceiling ducts, piping, etc. Where any doubt exists, the exact location shall be determined by the Owner.
- C. All general trades and existing conditions shall be checked before installing any outlets, power wiring, etc.
- D. Equipment sizes shown on the Drawings are estimated. Before installing any wire or conduit, the Contractor shall obtain the exact equipment requirements and install wire, conduit, or other item of the correct size for the equipment actually installed. However, wire and conduit sizes shown on the Drawings shall be taken as a minimum and shall not be reduced without written approval from the Owner.
- E. Where variances occur between the drawings and specifications or within either document itself, the item or arrangement of better quality, greater quality, or higher cost shall be included in the Contract Price. The Engineer will decide on the item and manner in which the work shall be installed.
- F. Contract Drawings are generally diagrammatic and all offsets, fittings, transitions, and accessories are not necessarily shown. Furnish and install all such items as may be required to fit the work to the conditions encountered. Arrange conduits, equipment, and other work generally as shown on the Contract Drawings, providing proper clearance and access. Where departures are proposed because of field conditions or other causes, prepare and submit detailed Shop Drawings for approval in accordance with "submittals" specified below. The right is reserved to make reasonable changes in location of equipment, piping, and ductwork, up to the time of rough-in or fabrication.
- G. Work not specifically outlined, but reasonably incidental to the completion of the work, shall be included without additional compensation from the Owner.

1.5 COORDINATION

- A. Coordinate arrangement, mounting, and support of electrical equipment:

- a. To allow maximum possible headroom unless specific mounting heights that reduce headroom are indicated.
 - b. To provide for ease of disconnecting the equipment with minimum interference to other installations.
 - c. To allow right of way for piping and conduit installed at required slope.
 - d. So connecting raceways, cables, wireways, cable trays, and busways will be clear of obstructions and of the working and access space of other equipment.
- B. Coordinate installation of required supporting devices and set sleeves in cast-in-place concrete, masonry walls, and other structural components as they are constructed.
- C. Coordinate sleeve selection and application with selection and application of firestopping specified in Division 07 Section "Penetration Firestopping."

PART 2. PRODUCTS

2.1 MATERIALS AND EQUIPMENT

- A. Material and equipment installed as a part of the permanent installation shall be new, unless otherwise indicated or specified, and shall be approved by the Underwriters' Laboratories, Inc., for installation in each particular case where standards have been established.
- B. Where material or equipment is identified by proprietary name, model number, and/or manufacturer, furnish the named item or equivalent thereof, subject to acceptance.
- C. Material submissions shall conform to requirements outlined in SUBMITTALS, REVIEW, AND ACCEPTANCE.
- D. The suitability of named item only has been verified. Where more than one Manufacturer is named, only the first named Manufacturer has been verified as suitable. Manufacturers and items other than the first named shall be equal or better in quality and performance to that of specified items, and must be suitable for available space, required arrangement, and application. The Contractor, by providing other than the first named Manufacturer, assumes responsibility for all necessary adjustments and modifications necessary for a satisfactory installation.
- E. The Contractor shall only submit those manufacturers indicated in the Specification. Proposed alternate manufacturers will not be considered unless the specific item indicates "or as approved equal". Submit all data necessary to determine suitability of substituted items for approval.
- F. All items of equipment furnished shall have a service record of at least five (5) years.

2.2 SUBSTITUTIONS

- A. Substituted items or items other than those named shall be equal or better in quality and performance and must be suitable for the available space, required arrangement, and application. Submit any and all data necessary to determine the suitability of substituted items. The Contractor shall be responsible for correct application, placement, and installation of substituted equipment. Cost savings data shall also be submitted with submittal data for substituted items. Total cost savings or a per-unit saving to the Owner shall be clearly indicated. If a substituted item is accepted, all cost savings shall be returned to the Owner as a credit.

- B. Substitutions will not be permitted for specific items of material or equipment where specifically indicated.
- C. For substituted items, clearly list on the first page of the submittal all differences between the specified item and the proposed item. The Contractor shall be responsible for corrective action (or replacement with the specified item) while maintaining the specification requirements if differences have not been clearly indicated in the submittal.
- D. Where the Contractor proposes to use an item of equipment or application other than that specified or detailed on the Drawings, which requires any redesign of the structure, partitions, foundation, HVAC, piping, wiring, or any other part of the mechanical, electrical, or architectural layout, any such redesign and all new drawings and detailing required thereafter shall be prepared by the Contractor at his own expense for review by the Owner representative before any such work is implemented.
- E. All Contractor-proposed changes and revisions shall be at the Contractor's risk and expense. The Contractor shall fully coordinate all revisions, substitutions and changes with other trades. The Contractor shall provide all necessary provisions, including HVAC, ventilation, foundations, access, etc., for a complete, code compliant, and fully functional installation.
- F. Where the Contractor elects to submit a substitution for equipment or materials, he shall:
 1. Submit Shop Drawings that show complete compliance to each statement or requirement of the Specifications.
 2. Submit certified test data from an independent testing laboratory for each product.
 3. Submit one complete working sample of the equipment or materials to be furnished. In cases involving large or heavy items of equipment, the Owner may waive the requirement to submit the sample.
- G. Failure to comply with the above-required submissions shall constitute an automatic rejection of the substitution.

2.3 SUBMITTALS, REVIEW, AND ACCEPTANCE

A. General:

1. The equipment, material, installation, workmanship, arrangement of work, final instruction, and final documentation is subject to review and acceptance. No substitution will be permitted after acceptance of equipment or materials except where such substitution is considered by the Engineer to be in the best interest of the Owner. Submit for review in clear and legible form the following documents:
 - a. Material and Equipment List
 - b. Descriptive Data
 - c. Shop Drawings
 - d. Installation and Coordination Drawings
 - e. Contractor As-Built Drawings
 - f. Owner Instructions and Manuals
 - g. Construction Phasing and Outage Schedule
2. Prepare all submittals specifically for this project and stamp each submittal in a form indicating that the documents have been Contractor reviewed, are complete, and are in

compliance with the requirements of the plans and specifications. Each submittal item shall be clearly identified and numbered. Each submittal shall contain a complete schedule of Manufacturer's part numbers and quantity listings of all supplied components. Each proposed item shall be highlighted and tagged with a star, an arrow, etc., including all options and accessories.

3. Coordinate the installation requirements and any mechanical requirements for the equipment submitted. Submittals will be reviewed for general compliance with design concept in accordance with the contract documents. The Contractor is responsible for the correctness of all submittals. Reviews will not verify dimensions, quantities, or other details.
4. Identify all submittals, indicating the intended application, location, or service of the submitted item. Refer to specification sections or paragraphs where applicable. Clearly indicate the exact type, model number, size, and special features of the proposed item. Clearly list on the first page of the Submittal all differences between the specified item and the proposed item. The Contractor shall be responsible for corrective action (or replacement with the specified item) while maintaining the specification requirements, if differences have not been clearly indicated in the submittal. Submittals of a general nature will not be acceptable.
5. Submit actual operating conditions or characteristics for all equipment where required capacities are indicated. Factory order forms showing only required capacities will not be acceptable. Indicate all options used to meet the specifications. It is not the responsibility of the Engineer or Owner to make selections of factory options other than colors. Submittals lacking proper selection of factory options or special features required by the specification shall be RETURNED WITHOUT REVIEW.
6. Acceptance will not constitute waiver of contract requirements unless deviations are specifically indicated and clearly noted.
7. Documents of general form indicating options shall be clearly marked to show what is specifically proposed for this project.
8. Submittals NOT IN COMPLIANCE with the requirements of this section will be RETURNED WITHOUT REVIEW.

B. Material, Equipment, Manufacturer and Subcontractor List: Within 30 calendar days after the award of contract, submit a complete MATERIAL, EQUIPMENT, MANUFACTURER AND SUBCONTRACTOR LIST for preliminary review. List all proposed materials and equipment, the associated proposed Manufacturer, and any proposed subcontractors. After the receipt of reviewed Material and Equipment List, submit complete Shop Drawings for approval. List all materials and equipment indicating manufacturer, type, class, model, curves, and other general identifying information. Submittals shall be specific for each building as contained in the individual building Specifications and Drawings.

C. Upon approval of the List of Materials, the Contractor shall prepare a complete Master Submittal Register, listing all products and materials that will be submitted for approval. Items shall be listed by referenced specification paragraph in ascending order. This master list shall be included with each submittal, updated to reflect the status of approval for each item, and shall highlight the items pertaining to the submittal. A suggested Submittal Register Format is shown below:

SUBMITTAL REGISTER					
Item/Material	Ref'd Spec. Paragraph	Specified or Substitute	Submittal Date	Status	Remarks

SUBMITTAL REGISTER					

- D. No Shop Drawing Submittals will be considered for approval until the complete List of Subcontractors and the complete List of Materials/Manufacturers and Equipment have been approved.
- E. Descriptive Data: After acceptance of the MATERIAL and EQUIPMENT LIST, submit additional DESCRIPTIVE DATA for all items. Data shall consist of specifications, data sheets, samples, capacity ratings, performance curves, operating characteristics, catalog cuts, dimensional drawings, installation instructions, and any other information necessary to indicate complete compliance with the contract documents. Where several ratings or sizes are shown or available, clearly indicate the exact size or rating relating to the particular device being proposed.
- F. Submit complete descriptive data for all items. Data shall consist of Specifications, data sheets, samples, capacity ratings, performance curves, operating characteristics, catalog cuts, dimensional drawings, wiring diagrams, specific electrical/wiring requirements and connections including control and interlock wiring, installation instructions, and any other information necessary to indicate complete compliance with the Contract Documents. Edit submittal data specifically for application to this project.
- G. Shop Drawings shall be submitted and approved for all materials and equipment prior to installation. If any material and/or equipment is installed prior to receipt by the Contractor of approved Shop Drawings, the Contractor is liable for its replacement at no additional cost to the Owner.
- H. Data submitted shall include information on all materials and equipment to demonstrate compliance with the Contract Drawings and Specifications. Where installation procedures or any part thereof are required to be in accordance with manufacturer's recommendations, furnish printed copies of the recommendations prior to installation. Installation of the item shall not proceed until recommendations are received. Failure to furnish recommendations shall be cause for rejection of the equipment or material.
- I. Any deviation of submitted material or equipment from the Contract Drawings or Specifications shall be clearly marked in red ink on Submittals, and itemized in a transmittal letter, in order to receive consideration for approval.
- J. Approval of material or equipment submittals containing deviations not specifically identified by Contractor shall not relieve the Contractor from compliance with specified requirements.
- K. All major items of mechanical equipment shall be the latest standard catalog products of reputable manufacturers. Where two (2) or more items of the same kind of equipment are required, they shall be the products of a single manufacturer.
- L. Thoroughly review and stamp all submittals to indicate compliance with Contract requirements prior to submission. Coordinate installation requirements and any electrical requirements for equipment submitted. Contractor shall be responsible for correctness of all submittals.

NOT FOR BIDDING PURPOSES

- M. Submittals will be reviewed for general compliance with design concept in accordance with Contract Documents, but dimensions, quantities, or other details will not be verified.
- N. Increase, by the quantity listed below, the number of electrical related Shop Drawings, product data, and samples submitted, to allow for required distribution plus two copies of each submittal required, which will be retained by the Electrical Consulting Engineer.
1. Shop Drawings - Initial Submittal: 1 additional blue- or black-line print.
 2. Shop Drawings - Final Submittal: 1 additional blue- or black-line print.
 3. Product Data: 1 additional copy of each item.
- O. Additional copies may be required by individual sections of these Specifications.
- P. Shop Drawings:
1. Prepare and submit SHOP DRAWINGS AND/OR DIAGRAMS for all specially fabricated items, modifications to standard items, specially designed systems where detailed design is not shown on the contract drawings, or where the proposed installation differs from that shown on the contract drawings.
 2. Shop drawings shall include plans, elevations, sections, mounting details of component parts, point to point interconnection diagrams, elementary diagrams, single line diagrams, and any other drawings necessary to show the fabrication and connection of the complete item or system.
 3. Shop drawings shall be provided for, but not limited to the following items:
 - Basic Electrical Materials
 - Cable - 600 volt
 - Circuit Breakers
 - Conduit and Surface Raceway
 - Contractor and Subcontractor Qualifications
 - Controllers & Control Devices
 - Electrical Connection Coordination Schedule
 - Equipment Connections
 - Equipment Pads
 - Excavation and Backfill
 - Fire Alarm System
 - Firestopping
 - Fuses
 - Ground Conductors, Rods
 - Identification System
 - Material and Equipment List
 - Motor Starters
 - Outlet Boxes
 - Panelboards
 - Receptacles
 - Record and Information Booklet
 - Safety Switches
 - Schedule of Values
 - Sleeves, Hangers, Supports
 - Submittal Schedule
 - Tests and Reports
 - Wiring Devices

Wiring Diagrams

- Q. The Contractor, additionally, shall submit for approval any other shop drawings as required by the Engineer. No item listed above shall be delivered to the site, or installed, until approved. After the proposed materials have been approved, no substitution will be permitted except where approved by the Engineer.
- R. The Contractor shall prepare and submit a Detail Schedule of Values indicating the Contract costs for the major work items. The Contractor shall provide additional detail and information as requested by the Engineer.
- S. The Contractor shall prepare and submit a complete Submittal Schedule. The Schedule shall include a listing of all Submittals, Shop Drawings, and Coordination Drawings.

2.4 COORDINATION DRAWINGS:

- A. Prepare, submit, and use composite installation and coordination drawings to assure proper coordination and installation of the work. Drawings shall include, but not be limited to the following:
 - 1. Telecommunication Rooms indicating data rack assemblies, panels, etc.
 - 2. Electrical Rooms indicating switchboard assemblies, transformers, equipment pads, panels, etc.
 - 3. Mechanical Equipment Rooms, including panels, transformers, starters, equipment, etc.
- B. Draw plans to a scale not less than 1/4 inch equals one foot. Include plans of the proposed work, showing all equipment, major elements, conduit, and wiring in the areas involved. Fully dimension all work, horizontally and vertically. Show coordination with other work including piping, ductwork and other mechanical work, walls, doors, ceilings, columns, beams, joists, and other architectural and structural work.
- C. Identify all equipment and devices on wiring diagrams. Where field connections are shown to factory-wired terminals, furnish manufacturer's literature showing internal wiring.
- D. Prepare, submit, and use scaled layout drawings indicating dimensions, clearances, and actual equipment dimensions. Layout drawing shall include, but not be limited to the following:
 - 1. Pad-mounted equipment and equipment connections.
 - 2. Underground conduits, ductbanks, manholes, handholes, and building penetrations.

2.5 RECORD DRAWINGS:

- A. As the work progresses, record on a set of white prints the installed locations, sizes of electric feeders, equipment, etc. Upon completion of the work, submit one (1) complete set of white prints with "As-Built" information neatly recorded thereon in red ink. Use other colors to distinguish between variations in separate categories of the work. Note related change-order numbers where applicable.
- B. Write step-by-step detailed instructions for turn-on, turn-off, seasonal changeover, and periodic checks of all systems and equipment. Include all precautions and warnings.

- C. Prepare a list of the manufacturers of all major equipment, their local service representative and procedures for obtaining service.
- D. Post one (1) copy of all instructions, lists, charts, and diagrams at the equipment or where indicated, mounted under glass or approved plastic cover.
- E. Furnish to the Owner two (2) copies of the Manufacturer's installation and operations instructions. Include replacement parts lists where applicable. Also include copies of all posted instructions, lists and charts. Assemble the material in one or more heavy duty 8- 1/2" x 11" loose leaf binders with tab separators. Submit for approval before final delivery. Binder shall be labeled on spine and on cover with Project Name.
- F. Deliver all instruction materials to the Owner prior to the formal instruction period.
- G. Deliver two (2) complete sets of all approved submittals to the Owner for filing.
- H. Prepare record documents in accordance with the requirements in the specifications. In addition to the requirements specified, indicate installed conditions for:
 - 1. Major raceway systems, size and location, for both exterior and interior; locations of control devices; distribution and branch electrical circuitry; and circuit breaker size and arrangements.
 - 2. Approved Substitutions, Contract Modifications, and actual equipment and materials installed.
- I. The Contractor shall keep at the site at all times during construction, one set of up-to-date Contract prints for the express purpose of showing any and all changes made during construction. The Contractor shall make the prints showing each change and shall incorporate all changes in "Record/As-Built Drawings" to be submitted to the Engineer upon completion of the project.
- J. The Contractor shall show proof of up-to-date record drawings to the Owner prior to submitting monthly invoice.
- K. The Contractor shall conform to all drawings, including all revisions, addendums, alternates, change orders, deletions, existing conditions, and as-built conditions without extra cost to the Owner.

2.6 DEMONSTRATION AND OPERATING INSTRUCTIONS

- A. Furnish the necessary technicians, skilled workers, and helpers to operate the electrical systems and equipment of the entire project. The Contractor shall provide a minimum of eight (8) hours of system demonstration and eight (8) hours of system operation for each system.
- B. Where specified in technical sections, provide longer periods required for specialized equipment.
- C. Contractor shall provide start-up of all systems in an orderly, organized, and coordinated manner to ensure that all systems are functioning as designed. The Contractor shall provide a detailed start-up, testing, and demonstration plan for all systems in a coordinated manner that is documented in writing at least 45 days prior to system start-up. Start-up, testing and demonstration plans shall include detailed point-by-point checklists that clearly show that systems are, in fact, functioning as designed. Instruct the Owner or designated personnel in operation, maintenance, lubrication, and adjustment of systems and equipment.

- D. The Operating and Maintenance Manual shall be available at the time of the instructions, for use by Instructors and Owner personnel.
- E. Videotape each instruction session, including both the sessions specified above and added sessions required in technical sections for specialized equipment. Provide one complete set of DVD video disks with each Operating and Maintenance Manual.
- F. Schedule the general and specialized instruction periods for a time agreed upon by the Owner and Engineer. All operation training and demonstrations shall be complete prior to Owner acceptance of any given system.

2.7 SLEEVES FOR RACEWAYS AND CABLES

- A. Steel Pipe Sleeves: ASTM A 53/A 53M, Type E, Grade B, Schedule 40, galvanized steel, plain ends.
- B. Sleeves for Rectangular Openings: Galvanized sheet steel.
 - 1. Minimum Metal Thickness:
 - a. For sleeve cross-section rectangle perimeter less than 50 inches (1270 mm) and no side more than 16 inches (400 mm), thickness shall be 0.052 inch (1.3 mm).
 - b. For sleeve cross-section rectangle perimeter equal to, or more than, 50 inches (1270 mm) and 1 or more sides equal to or more than, 16 inches (400 mm), thickness shall be 0.138 inch (3.5 mm).

2.8 SLEEVE SEALS

- A. Description: Modular sealing device, designed for field assembly, to fill annular space between sleeve and raceway or cable.
 - 1. Basis-of-Design product. Subject to compliance with requirements, provide product by one of the following:
 - a. Advance Products & Systems, Inc.
 - b. Campico, Inc.
 - c. Metraflex Co.
 - d. Pipeline Seal and Insulator, Inc.
 - 2. Sealing Elements: EPDM interlocking links shaped to fit surface of cable or conduit. Include type and number required for material and size of raceway or cable.
 - 3. Pressure Plates: Carbon steel. Include two for each sealing element.
 - 4. Connecting Bolts and Nuts: Carbon steel with corrosion-resistant coating of length required to secure pressure plates to sealing elements. Include one for each sealing element.

2.9 GROUT

- A. Nonmetallic, Shrinkage-Resistant Grout: ASTM C 1107, factory-packaged, nonmetallic aggregate grout, noncorrosive, nonstaining, mixed with water to consistency suitable for application and a 30-minute working time.

PART 3. EXECUTION

3.1 EXAMINATION OF SITE, SURVEYS, AND MEASUREMENTS:

- A. Examine the site, determine all conditions and circumstances under which the work must be performed, and make all necessary allowances for same. No additional cost to the Owner shall be permitted for Contractor's failure to do so.
- B. Examine the site and observe the conditions under which the work will be done or other circumstances which will affect the contemplated work. Special attention shall be given to areas where work is to be done in existing buildings. No allowance will be made subsequently in this connection for any error or negligence on the Contractor's part.
- C. The Contractor shall base all measurements, both horizontal and vertical, from established benchmarks. All work shall agree with these established lines and levels. Verify all measurements at the site and check the correctness of same as related to the work.
- D. Any discovery of discrepancy between actual measurements and those indicated which prevents following good practice or the intent of the Drawings and Specifications shall be brought to the attention of the Owner's Representative. Work shall not proceed until receiving instructions from the Owner's Representative.
- E. The Contractor shall follow Drawings in laying out the work and check Drawings of other trades to verify spaces in which work will be installed. Maintain maximum headroom and space conditions at all points. Where headroom or space conditions appear inadequate, the Owner's Representative shall be notified before proceeding with the installation.
- F. To prevent conflict with the work of other trades and for proper execution of the work, the Contractor, as directed by the Owner's Representative, shall make the necessary modifications in the layout as needed, at no extra charge to the Owner.
- G. The Contractor shall be solely responsible for the proper arrangement of his conduit and equipment.
- H. The Engineer shall make all final decisions as to any conditions that require the changing of any work.
- I. The Contractor shall have competent supervision on the site at all times to lay out, check, coordinate, and supervise the installation of all electrical work and be responsible for the accuracy thereof. He shall plan the installation of all electrical work, giving consideration to the work of other trades, to prevent interference.
- J. The Contractor shall determine the location, size, etc., of all chases, sleeve openings, etc., required for the proper installation of the electrical work and see that such are provided. All chases, sleeves, openings, etc., shall be set prior to erection of new work to prevent delay in the progress of other work or trades.
- K. Conditions and/or situations that prevent the proper installation of any equipment or item where shown on the Drawings shall be called to the attention of the Engineer for instructions.

- L. The Contractor shall have equipment shipped or fabricated in sections of suitable size for entering the building and being removed from the finished building in the future, if necessary.
- M. The Contractor shall fully investigate all peculiarities and space limitations for all materials and equipment.
- N. Outlet, pull, and junction boxes and other appliances that require operation, examination, adjustment, servicing or maintenance shall be readily accessible.
- O. The Contractor shall take all field measurements necessary for this work and shall assume responsibility for their accuracy.
- P. The Contractor shall coordinate the electrical work with all other sub-contractors. All work shall be so arranged that there will be no delay in the proper installation and completion of any part or parts of electrical equipment. All electrical work shall be installed in proper sequence with other trades without any unnecessary delay.
- Q. The Drawings are to some extent diagrammatic and indicate the general arrangement of the equipment, the runs of conduit, and the manner of connection.
- R. The Contractor shall confer with all sub-contractors engaged in the construction of the project, regarding the work that may, in any way, affect his installation. Whenever interference occurs, before installing any of the work in question, the Contractor shall consult with all sub-contractors and shall come to an agreement with them as to the exact location and level of his conduit parts of his equipment.
- S. The Contractor shall be responsible for determining exact property lines and area of work. The Contractor shall not install any equipment or conduits outside of the property lines and/or area of work without written direction from the Owner. Any work indicated diagrammatically on the Contract Documents to be installed beyond the property lines and/or area of work shall be verified with the Owner prior to installation.

3.2 GENERAL RESPONSIBILITIES:

- A. The Contractor shall be responsible for systems and related damages possible, and shall hold harmless the Owner, the Architect and his consultants from malfunction of systems and equipment installed under this Contract as defined in the laws of the State of Delaware pertaining to real property for the period of time as defined by such laws.
- B. It is the intent of these Specifications to fully cover without exception all required labor and materials so that the finished work will be delivered to the Owner in a complete and satisfactory working installation. Excavation, wiring, distribution, etc., shall be performed in compliance with the Contract Documents.
- C. Work not specifically outlined, but reasonably incidental to the completion of the work, shall be included without additional compensation from the Owner.
- D. Conflicting points in the Specifications or on the Drawings shall be called to the attention of the Architect prior to the execution of the Contract.

3.3 STORAGE AND PROTECTION OF EQUIPMENT

- A. All electrical equipment to be used in the construction shall be properly stored and protected against the elements. All equipment shall be stored under cover, and shall not be stored at the construction site on the ground, in mud, water, snow, rain, sleet or dust. Large diameter cables may be stored on reels with weatherproof materials. Such weatherproof materials shall be heavy-duty, securely fastened and made impervious to the elements.
- B. Conventional electrical construction materials such as building wire, outlet and junction boxes, wiring devices, conduit, lighting fixtures, fittings, etc., shall be stored in construction buildings, covered trailers or portable covered warehouses. Any equipment subject to damage or corrosion from excessive moisture shall be stored in dry, heated areas. Any equipment containing plastic or material subject to damage caused by excessive heat or sunlight shall be stored to prevent such damage. This includes plastic ducts and lenses.
- C. Switchboard, motor controllers, panelboards, breakers, emergency lighting, and supervisory equipment, if delivered to the construction site before the building is under cover, shall be warehoused and protected as follows: All gear and equipment shall be covered and protected from the elements and other damage and shall be stored in a clean, dry, heated atmosphere under cover.
- D. All gear and equipment delivered to the construction site after the building is under cover shall be protected as described above and in addition shall be provided with auxiliary heat to prevent condensation damage. The gear shall also be protected against damage caused by installation of any building systems and equipment; or damage caused by carelessness of workmen who are installing equipment connected to or adjacent to the above electrical equipment.
- E. Equipment damaged as a result of the above conditions shall be properly repaired at the Contractor's expense or shall be replaced at the Contractor's expense, if, in the opinion of the Engineer the equipment has been damaged to such an extent it cannot operate properly after repairs are made.
- F. All electrical enclosures exposed to construction damages such as paint spots, spackling or plaster spatter, grout splashes, waterproofing compound, tar spots or runs and pipe covering compound splashes, shall be completely covered and protected against damage.
- G. In the event leakage into the building of any foreign material or fluid occurs or may occur, the Contractor shall take all steps as described above to protect any and all equipment.
- H. After connections to electrical equipment are complete and the equipment is ready for operation, all construction debris shall be removed from all enclosures. Such debris includes dust, dirt, wire clippings, tape and insulation removed in order to make the connection.

3.4 ELECTRICAL INSTALLATIONS

- A. General: Sequence, coordinate, and integrate the various elements of electrical systems, materials, and equipment. Comply with the following requirements:
1. Coordinate electrical systems, equipment, materials, and installation with landscape/irrigation contractor(s).
 2. Verify all dimensions by field measurements.
 3. Install systems, materials, and equipment to conform with approved submittal data, including coordination drawings, to greatest extent possible. Conform to arrangements indicated by the Contract Documents, recognizing that portions of the Work are shown only in diagrammatic

form. Where coordination requirements conflict with individual system requirements, refer conflict to the Engineer.

4. Install systems, materials, and equipment level and plumb, parallel and perpendicular to other building systems and components where installed exposed in finished spaces.
5. Install electrical equipment to facilitate servicing, maintenance, and repair or replacement of equipment components. As much as practical, connect equipment for ease of disconnecting, with minimum of interference with other installations. All equipment and disconnects shall maintain proper working space to conform to NEC.
6. Install systems, materials, and equipment giving right-of-way priority to systems that require installation at a specified slope.
7. Arrange for chases, slots and openings in other building components during progress of construction, to allow for electrical installation.
8. Space, coordinate, and integrate installations of electrical materials and equipment for efficient flow of the work.

3.5 SUPERVISION AND COORDINATION:

- A. Provide complete supervision, direction, scheduling and coordination of all work under the contract, including that of subcontractors, using full attention and the best skill. Be responsible for all work and make all subcontractors, suppliers and manufacturers fully aware of all requirements of the contract.
- B. Coordinate the rough-in of all work performed under Divisions Mechanical and Electrical Divisions.
- C. The Contractor shall coordinate all electrical rough-in with approved shop drawings and coordination drawings. Any rough-in installed without complete coordination shall be at the Contractor's risk and expense.
- D. Coordinate the installation of all necessary rough-in of work, sleeves, anchors and supports for conduit, wiring, and other work performed under Mechanical and Electrical Divisions. Coordinate Division 26 work with all trades.
- E. Where a discrepancy exists within the Specifications or drawings or between the Specifications and Drawings, the more stringent (or costly) requirement shall apply until a clarification can be obtained from the Engineer. Failure to clarify such discrepancies with the Engineer will not relieve the Contractor of the responsibility of conforming to the requirements of the Contract.
- F. Failure of the Contractor to obtain a full and complete set of Contract Documents (either before or after bidding) will not relieve the Contractor of the responsibility of complying with the intent of the Contract Documents.
- G. To insure proper electrical coordination between the electrical components supplied under the Electrical Divisions and the equipment supplied under the Mechanical Divisions, a schedule shall be submitted, prior to start of work, for review by the Engineer with the following column headings:

1. Equip. or Item	2. HP or KVA	3. Voltage and Phase	4. Power Factor	5. Capacitor	6. Motor Starter	7. Disconnection.	8. Controls	9. Remarks
-------------------	--------------	----------------------	-----------------	--------------	------------------	-------------------	-------------	------------

Description of Column Headings:

1. List all the approved equipment furnished under Mechanical Division that requires electrical connections and designate the equipment as it appears in the Mechanical Divisions. Indicate the quantity, if more than one, in parentheses of identical equipment being supplied.
 2. Indicate the supplied horsepower of the equipment listed under Column No. 1. If equipment listed has more than one motor, indicate each motor and its respective horsepower. Indicate the kVA rating for all other equipment requiring an electrical connection, unless the electrical connection is for a control circuit only.
 3. Indicate the voltage and phase requirements for equipment listed under Column No. 1. If more than one electrical circuit or voltage is required for the listed equipment, it shall be so indicated. Indicate wiring required for connection, including all phase, neutral, and ground conductors.
 4. Indicate the power factor rating for all motors listed under Column No. 1.
 5. Where a capacitor is to be provided, indicate specification it is supplied under and indicate the KVAR size for any capacitor provided under Division 26.
 6. Where a motor starter is required, indicate the specification division it is supplied under and the type of motor starter; across-the-line, reversible, variable speed, two speed-single winding, etc. Indicate in Column No. 9 if the motor starter provided under Division 26 is not compatible with the motor specified.
 7. Where a disconnect switch is required by the National Electric Code or by the contract documents for the equipment listed under Column No. 1, indicate under which Division the disconnect switch is supplied.
 8. Indicate the Division under which the controls for the equipment listed under Column No. 1 are provided.
 9. Indicate any discrepancies between quantities indicated in the contract documents and what is actually being provided.
- H. The Contractor shall fully coordinate the electrical connections to all equipment prior to installations, with the approved Shop Drawings and the trades involved. Coordination shall include voltage, phases, quantity and size of wiring, device sizes, terminations, rough-in work, and other coordination for a complete installation.
- I. Coordinate the spacing and arrangement of lighting fixtures, diffusers, grilles and access panels in ceilings to establish a symmetrical pattern.
- J. Coordinate light switch locations with door swings prior to rough-in. No switches permitted behind door.
- K. Coordinate electrical work with architectural items and equipment. Typical equipment refers to, but is not limited to, the following:
1. Countertops, Casework and Cabinets.
 2. Fume and Exhaust Hoods.
 3. Kitchen equipment.
 4. Do not install outlets, switches, etc., behind casework, cabinets, etc.
 5. Data, phone, and other low voltage system outlets shall be mounted above the counter tops to match power outlets in the same areas.
 6. Coordinate counter top outlets with drilling of casework/counters.
 7. Coordinate surface raceways and outlets above and below counters with approved casework shop drawings to avoid conflicts with sinks and other appurtenances.

8. Verify lab/kitchen equipment nameplates and connection requirements prior to rough-in.
9. Shop equipment connections, including busways.

L. This Contractor shall make all system connections required to equipment furnished and installed under other divisions. Connections shall be complete in all respects to render this equipment functional to its fullest intent. The Contractor shall make all system connections required to equipment furnished under other Divisions. Circuits shall be extended to all equipment which is incidental to, but not necessarily shown, for equipment specified under other divisions such as magnetic flow meters, AIC panels, liquid level controls, leak detection systems, etc. Connections shall be complete in all respects to render this equipment functional to its fullest extent.

M. Install work with proper clearances and access. Carefully examine all contract drawings and fit the work in each location without substantial alteration. Where departures are proposed or required, submit detailed drawings for acceptance. The right is reserved to make reasonable changes in location of equipment, conduit and wiring up to the time of rough-in or fabrication.

N. It shall be the responsibility of the Contractor to obtain complete instructions for connections.

3.6 GUARANTEE:

A. Guarantee obligations shall be as hereinbefore specified in the GENERAL AND SPECIAL CONDITIONS of these specifications, except as follows:

1. Guarantee the complete electrical system free from all mechanical and electrical defects for the period of two (2) years beginning from the day of final acceptance of the work by the Owner.
2. Also, during the guarantee period, be responsible for the proper adjustments of all systems, equipment and apparatus installed by the Contractor and do all work necessary to ensure efficient and proper functioning of the systems and equipment.
3. Upon receipt of notice from the Owner of failure of any part of the electrical installation during the guarantee period, new replacement parts shall be furnished and installed promptly at no cost.
4. Warranty From the Manufacturer: Contractor shall obtain all warranty papers and records from the Original Equipment Manufacturer according to their warranty policy and deliver the same to the Owner. Contractor shall fulfill all the Original Manufacturer's requirements to validate the warranty as offered by the Original Equipment Manufacturer.

B. Provide 24-hour service for any and all warranty problems experience in the operation of the equipment provided.

C. Any equipment or system in need of warranty work whether during regular hours or on an emergency basis, shall be immediately serviced and repaired. The warranty work and guarantee shall include all parts and labor and shall be furnished at no cost to the Owner.

D. The Contractor shall guarantee to make good any and all defects in his work, exclusive of lamps, which may develop due to defective workmanship or materials, within one year from the date of final acceptance of the work by the Owner.

E. In addition to the warranty and correction of work obligations contained in the General and supplementary Conditions, correct the work of the system as embraced by the Specification, free from

Mechanical and Electrical defects for the warranty period beginning from the day of acceptance of the building by the Engineer for the beneficial use of the Owner.

- F. During the warranty period, take responsibility for the proper adjustments of systems, equipment and apparatus installed and perform work necessary to ensure the efficient and proper functioning of the systems and equipment.
- G. Certain items of equipment hereinafter specified shall be guaranteed for a longer time than the general warranty period. These guarantees shall be strictly adhered to and the Contractor shall be responsible for service or replacement required in connection with guarantee of these items. These guarantees shall commence on the same date as the final acceptance by the Engineer.
- H. Submission of a bid proposal for this Project warrants that the Contractor has reviewed the Contract Documents and has found them free from ambiguities and sufficient for the construction and proper operation of systems installed for this project. If discrepancies are found, have them clarified by Addendum.
- I. It is possible that certain areas of the building or certain systems will be accepted at a time different than as specified. The date of acceptance by the Architect for beneficial use of the Owner for these building areas or systems will be adjusted accordingly.

3.7 SCHEDULING OF WORK:

- A. The Contractor shall not be permitted to do any work in any area of any occupied building during normal hours, except in areas specifically assigned.
- B. Coordination of work by the Contractor is essential such that power outages are kept to a minimum in quantity and duration. All required outages shall be approved by the Owner for optimum time scheduling. Written notice of not less than 15 calendar days shall precede all power outages.

3.8 TEMPORARY FACILITIES:

- A. General: Refer to the Division 1 Sections for general requirements on temporary facilities.
- B. Remove all temporary power installations and connections after permanent power is established and/or prior to completion of the project.

3.9 DEMONSTRATION:

- A. As a part of this contract, the Contractor shall provide for the services of equipment manufacturers or their established representatives to demonstrate to selected maintenance personnel the correct operation, safety and maintenance of all electrical equipment under this contract.

3.10 PAINTING AND FINISHES:

- A. Provide protective finishes on all materials and equipment. Use coated or corrosion-resistant materials, hardware and fittings throughout the work. Paint bare, untreated ferrous surfaces with rust-inhibiting paint. All exterior components including supports, hangers, nuts, bolts, washers, vibration isolators, etc., shall be galvanized or stainless steel.
- B. Clean surfaces prior to application of coatings, paint, or other finishes.

- C. Provide factory-applied finishes where specified. Unless otherwise indicated factory-applied paints shall be baked enamel with proper pre-treatment.
- D. Protect all finishes and restore any finishes damaged as a result of work under Division 26 to their original condition.
- E. The preceding requirements apply to all work, whether exposed or concealed.
- F. Remove all construction marking and writing from exposed equipment, conduit, and building surfaces. Do not paint manufacturer's labels or tags.
- G. All exposed conduit, etc., shall be painted, except in electrical rooms, mechanical rooms, storage rooms, and crawl spaces. Colors shall be selected by the Architect and conform to ANSI Standards.
- H. Submit color of factory-finished equipment for approval prior to ordering.

3.11 PROTECTION OF WORK:

- A. Protect work, material and equipment from weather and construction operations before and after installation. Properly store and handle all materials and equipment.
- B. Cover temporary openings in conduit and equipment to prevent the entrance of water, dirt, debris, or other foreign matter.
- C. Cover or otherwise protect all finishes.
- D. Replace damaged materials, devices, finishes and equipment.

3.12 OPERATION OF EQUIPMENT:

- A. Clean all systems and equipment prior to initial operation for testing, retesting, or other purposes. Set, adjust, and test all equipment in accordance with manufacturer's instructions. Do not operate equipment unless all proper safety devices or controls are operational. Provide all maintenance and service for equipment that is authorized for operation during construction.
- B. Where specified, or otherwise required, provide the services of the manufacturer's factory-trained servicemen or technicians to start up the equipment.
- C. Do not use electrical systems for temporary services during construction unless authorized in writing by the Owner. Where such authorization is granted, temporary use of equipment shall in no way limit or otherwise affect warranties or guaranty period of the work.
- D. Upon completion of work, clean and restore all equipment to new conditions; replace expendable items such as filters.

3.13 TESTING AND ADJUSTMENT

- A. Perform all tests which are specified or required to demonstrate that the work is installed and operating properly. Where formal tests are required, give proper notices and perform all necessary preliminary tests to assure that the work is complete and ready for final test.

- B. Adjust all systems, equipment and controls to operate in a safe, efficient and stable manner.
- C. On all circuits, 600 volts or less, provide circuits that are free from ground faults, short circuits and open circuits.
- D. Other tests of a specific nature for special equipment shall be as specified under the respective equipment.

3.14 IDENTIFICATIONS, ELECTRICAL DIAGRAMS AND OPERATING INSTRUCTIONS:

- A. Contractor shall submit for approval schematic diagrams of each electrical system installed in the building. Diagrams shall indicate device location, service, type, make, model number and the identification number of each device in the particular system. Following approval by all authorities, the diagrams shall be framed, mounted under glass and hung in each Main Equipment Room where directed. Contractor shall deliver the tracing or sepia from which the diagrams were reproduced to the Owner.
- B. All equipment shall be plainly tagged.
- C. All items of equipment, including motor starters, panels, etc., shall be furnished with white letters and numbers on black plastic identification plates or aluminum letters and numbers on black engraved aluminum identification plates. Lettering shall be a minimum of 1/4" high. Identification plates shall be securely affixed to each piece of equipment, starter, panels, etc., by screws or adhesive (Tuff-Bond #TB2 or as approved equal). Pressure sensitive tape backing is prohibited.
- D. Provide three (3) copies of operating and maintenance instructions for all principal items of equipment furnished. This material shall be bound as a volume of the "Record and Information Booklet" as hereinafter specified.
- E. Provide at least 24 hours of straight time instruction to the operating personnel. This instruction period shall consist of not less than three (3) consecutive 8-hour days. Time of instruction shall be designated by the Owner. Provide two VHS video taped copies of all instructional periods/demonstrations.

3.15 RECORD DRAWINGS AND SPECIFICATIONS:

- A. Upon completion of the Electrical installations, the Contractor shall deliver to the Engineer one complete set of prints of the Electrical Contract Drawings which shall be legibly marked in red pencil to show all Addenda, approved Shop Drawings, Change Orders, changes and departures of the installation as compared with the original design. They shall be suitable for use in preparation of Record Drawings.
- B. The Contractor shall provide a record specification including all Addenda and other modifications. Record substantial variations in actual work performed. Identify all substitutions.

3.16 RECORD AND INFORMATION BOOKLET:

- A. The Contractor shall have prepared three (3) copies of the Record and Information Booklet and deliver these copies of the booklet to the Owner. The booklet shall be as specified herein. The booklet must be approved and will not be accepted as final until so stamped.

- B. The booklet shall be bound in a three-ring loose-leaf binder similar to "National" No. 3881 with the following title lettered on the front and on the spine of the binder: "Record and Information Booklet (insert name of the project)". No sheets larger than 8-1/2" x 11" shall be used, except sheets that may be neatly folded to 8-1/2" x 11" and used as a pull-out. An Index will include the section tabs for each subject included. If more than one binder is required, print covers and spines with Volume numbers. Include in the front of every binder an index to all binders.
1. Internally subdivide the binder contents with permanent page dividers, logically organized as described below; with tab titling clearly printed under reinforced laminated plastic tabs.
 2. Contents: Prepare a Table of Contents for each volume, with each product or system description identified, typed on white paper.
 3. Part 1: Directory, listing names, addresses, and telephone numbers of Electrical Engineers; Contractor; Electrical Subcontractors; and major Electrical equipment suppliers. Provide sales and service representative names and phone numbers of all equipment.
 4. Part 2: Operation and Maintenance Instructions, arranged by Specification Section. For each category, identify names, addresses, and telephone numbers of Subcontractors and suppliers. Identify the following:
 - a. Significant design criteria.
 - b. List of equipment. Complete record of material list. Catalog brochures and product data for all components. Include all submitted comments, and corrected catalog data and shop drawings on each piece of equipment and each system.
 - c. Parts list for each component, including recommended spare parts list. Include motor starter overload schedules.
 - d. Operating instructions, including sequence of operation.
 - 1) Description of function, normal operating characteristics and limitations, engineering data and tests, and complete nomenclature and commercial numbers of replacement parts. Provide a description of each system installed.
 - 2) Manufacturer's printed operating procedures to include start-up, break-in, and routine and normal operating instructions; control, stopping.
 - e. Maintenance instructions for equipment and systems. Detailed checkout procedures to insure operation of systems and gear, including recommended cleaning methods and materials and special precautions identifying detrimental agents.
 - f. Servicing, diagnostic and troubleshooting instructions and procedures for systems and major equipment.
 - g. Recommended preventative maintenance program, including a list of items requiring inspection and servicing. Provide Chart Form indicating time and type of routine and preventative maintenance of electrical equipment, etc. The chart shall also indicate tag number, model number of equipment, location and service.
 - 1) For replacement items, indicate type, size and quantity of the replaceable items.
 - 2) Provide lubrication schedule, including type, grade, temperature range and frequency.
 - 3) Provide a list of each type of lighting fixture lamp used, lamp fixture used, and source.
 - 4) Include estimated mean time between failures for major parts.
 - h. Wiring Diagrams, Block Diagrams, and Assembly Drawings.
 - i. Panelboard Circuit Directory for each panelboard, including Panel Name, Panel Location, Panel Ratings, spare circuit breakers, spaces for additional circuit breakers.
 - j. List of equipment keys turned over to the Owner.
 5. Part 3: Project Documents and Certificates, including the following:

- a. Shop Drawings and Product Data. Record Documents of the systems.
 - b. Photocopies of certificates.
 - c. Photocopies of Manufacturers' and Contractors' warranties, guarantees.
 - d. Test Reports: Copies of the approved results of all tests required under all sections of specifications.
 - e. Inspection Certificates.
 - f. Manufacturer's Conformance Certificates.
6. Provide one copy (DVD video disk) of video instruction session with each booklet set. Label video disk with all pertinent information.
 7. Submit one copy of completed volumes in final form 15 days prior to final Inspection. This copy will be returned with Engineer comments. Revise content of documents as required prior to final submittal.
 8. Submit final volumes revised, within ten days after final inspection.
- C. Upon completion of the project, the Contractor shall furnish the Owner a complete list of suppliers of equipment for parts and maintenance purposes. The list shall include the name, address, and telephone number of the parts and maintenance firm on a single 8-1/2" x 11" sheet of paper.
- D. This item shall include the furnishing of a complete list of equipment installed on the project, including the Manufacturer's name, the make and model number of the equipment, and address and telephone number of the nearest supplier who stocks maintenance and/or replacement parts. The list should be submitted along with as-built drawings and be typed in an organized manner.
- 3.17 INSTALLATION AND COORDINATION DRAWINGS:
- A. In congested areas, prepare, submit, and use composite installation and coordination drawings to assure proper coordination and installation of work. Drawings shall include, but not be limited, to the following: Complete Electrical Drawings showing coordination with lights, electrical equipment, mechanical, plumbing, HVAC, structural, and architectural elements and provision for access.
 - B. Draw plans to a scale not less than 3/8-inch equals one foot. Include plans, sections, and elevations of proposed work, showing all equipment and conduit in areas involved. Fully dimension all work including lighting fixtures, conduits, pullboxes, panelboards, and other electrical work, walls, doors, ceilings, columns, beams, joists, mechanical equipment, and other architectural and structural work.
 - C. Identify all equipment and devices on wiring diagrams and schematics. Where field connections are shown to factory-wired terminals, include manufacturer's literature showing internal wiring.
- 3.18 CUTTING AND PATCHING
- A. The cutting of walls, floors, partitions, etc., for the passage and/or accommodation of conduits, etc., the closing of superfluous openings and the removal of all debris caused by said work under this contract shall be performed by and at the expense of the Contractor.
 - B. No cutting of any structure or finishes shall be done until the condition requiring such cutting has been examined and approved by the Architect.
 - C. All surfaces disturbed as a result of such cutting shall be restored under this division to match original work and all materials used for any patching, mending or finishing must conform to the class of materials originally installed.

- D. Openings through precast planks for the passage of hanger rods, conduits, outlet boxes, etc., shall be drilled with power driven carbide tip drills. This drilling shall be done by the trades needing the openings and shall be in accordance with Architect's instructions. No reinforcing bars shall be cut without specific approval of the Structural Engineer.

3.19 WATERPROOFING

- A. Coordinate the work to minimize penetration of waterproof construction, including roofs, exterior walls and interior waterproof construction. Where such penetrations are necessary, furnish and install all necessary sleeves, flashings, fittings, and caulking to make penetrations absolutely watertight.
- B. Where conduits or other openings penetrate roofs, flash pipe with Stoneman "Stormite" or approved equal, roof flashing assemblies, with 4-pound lead, 6 inch skirt, and caulked counterflashing sleeve similar to No. 1000-4.
- C. Furnish and install pitch pockets where required.
- D. Furnish and install conduit sleeves specifically designed for application to the particular roof construction, and install in accordance with the manufacturer's instructions, the National Roofing Contractors' Association, and as required by other divisions of this specification. The Contractor shall be responsible for sleeve sizes and locations.

3.20 SLEEVE INSTALLATION FOR ELECTRICAL PENETRATIONS

- A. Electrical penetrations occur when raceways, cables, wireways, cable trays, or busways penetrate concrete slabs, concrete or masonry walls, or fire-rated floor and wall assemblies.
- B. Concrete Slabs and Walls: Install sleeves for penetrations unless core-drilled holes or formed openings are used. Install sleeves during erection of slabs and walls.
- C. Use pipe sleeves unless penetration arrangement requires rectangular sleeved opening.
- D. Fire-Rated Assemblies: Install sleeves for penetrations of fire-rated floor and wall assemblies unless openings compatible with firestop system used are fabricated during construction of floor or wall.
- E. Cut sleeves to length for mounting flush with both surfaces of walls.
- F. Extend sleeves installed in floors 2 inches (50 mm) above finished floor level.
- G. Size pipe sleeves to provide 1/4-inch (6.4-mm) annular clear space between sleeve and raceway or cable, unless indicated otherwise.
- H. Seal space outside of sleeves with grout for penetrations of concrete and masonry
 1. Promptly pack grout solidly between sleeve and wall so no voids remain. Tool exposed surfaces smooth; protect grout while curing.
- I. Interior Penetrations of Non-Fire-Rated Walls and Floors: Seal annular space between sleeve and raceway or cable, using joint sealant appropriate for size, depth, and location of joint. Comply with requirements in Division 07 Section "Joint Sealants".

- J. Fire-Rated-Assembly Penetrations: Maintain indicated fire rating of walls, partitions, ceilings, and floors at raceway and cable penetrations. Install sleeves and seal raceway and cable penetration sleeves with firestop materials. Comply with requirements in Division 07 Section "Through-Penetration Firestop Systems."
- K. Roof-Penetration Sleeves: Seal penetration of individual raceways and cables with flexible boot-type flashing units applied in coordination with roofing work.
- L. Aboveground, Exterior-Wall Penetrations: Seal penetrations using steel or cast-iron pipe sleeves and mechanical sleeve seals. Select sleeve size to allow for 1-inch (25-mm) annular clear space between pipe and sleeve for installing mechanical sleeve seals.
- M. Underground, Exterior-Wall Penetrations: Install cast-iron pipe sleeves. Size sleeves to allow for 1-inch (25-mm) annular clear space between raceway or cable and sleeve for installing mechanical sleeve seals.

3.21 SLEEVE-SEAL INSTALLATION

- A. Install to seal exterior wall penetrations.
- B. Use type and number of sealing elements recommended by manufacturer for raceway or cable material and size. Position raceway or cable in center of sleeve. Assemble mechanical sleeve seals and install in annular space between raceway or cable and sleeve. Tighten bolts against pressure plates that cause sealing elements to expand and make watertight seal.

3.22 FIRESTOPPING

- A. Apply firestopping to penetrations of fire-rated floor and wall assemblies for electrical installations to restore original fire-resistance rating of assembly. Firestopping materials and installation requirements are specified in Division 26 Section "Electrical Firestopping."

END OF SECTION

SECTION 26 05 02

ELECTRICAL DEMOLITION FOR REMODELING

PART 1. GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections apply to this Section.

1.2 SCOPE

- A. Electrical demolition shall be carried out per the Contract Documents.
- B. Provide all cutting and patching for electrical construction.
- C. Provide temporary service and provisions to maintain existing systems.

PART 2. PRODUCTS

2.1 MATERIALS AND EQUIPMENT

- A. Materials and equipment for patching and extending work: As specified in individual sections.

PART 3. EXECUTION

3.1 EXAMINATION

- A. The Contractor shall examine the site, determine all conditions and circumstances and gather all data and information required for the work. Field investigations include, but are not limited to, performing surveys, opening of equipment enclosures, and other work as required to maintain existing systems.
- B. The Contractor shall survey all new and existing wiring, circuitry, cabling, equipment and devices. Data gathering shall include, but not be limited to, equipment nameplate information, ratings, voltage, wiring configurations, conductor lengths, conductor routing, conductor sizes, equipment connections, and other information as required to maintain existing systems.

- C. The Contractor shall provide complete field investigations to determine existing and new conductor, cable, and conduit routing, points of connections, and tracing of existing systems.
- D. Verify that field measurements and circuiting arrangements are as shown on the Drawings.
- B. Verify that abandoned wiring and equipment serve only abandoned facilities.
- C. Demolition Drawings are based on casual field observation. Report discrepancies to the Owner, Engineer before disturbing existing installation.
- D. Beginning of demolition means installer accepts existing conditions.

3.2 PREPARATION

- A. Disconnect electrical systems in walls, floors, and ceilings scheduled for removal.
- B. Coordinate utility service outages with the Owner, Architect and Engineer. Also, coordinate utility service outages with Utility Company.

3.3 CONNECTIONS AND ALTERATIONS TO EXISTING SYSTEMS

- A. Keep all existing electrical systems in operation during the progress of the work. Provide temporary electrical connections to systems of equipment, etc., where necessary to maintain continuous operation until the new systems and equipment are ready for operation.
- B. When existing electrical work is removed, remove all conduit, ducts, supports, etc. to a point below the finished floors or behind finished walls and cap. Such points shall be far enough behind finished surfaces to allow for the installation of the normal thickness of finished material.
- C. When the work specified hereunder connects to any existing equipment, conduit, wiring, etc., perform all necessary alterations, cuttings, fittings, etc., of the existing work as may be necessary or required to make satisfactory connections between the new and existing work and leave the complete work in a finished and workmanlike condition.
- D. When the work specified under other divisions necessitates relocation of existing equipment, conduits, wiring, etc., perform all work and make all necessary changes to existing work as may be required to leave the completed work in a finished and workmanlike condition.
- E. Contractor shall be responsible for removing and replacing existing ceiling tile within the lay-in ceiling areas as required. Contractor shall provide all necessary cutting and fitting of bushed holes for cable passage through tiles. Any tiles damaged during the Contract shall be replaced with like kind at no cost to the Owner.
- F. Provide temporary wiring and connections to maintain existing systems in service during construction. When work must be performed on energized equipment or circuits, use personnel experienced in such operations. In particular, all security and safety systems must

be maintained in operation at all times as required by the Owner. This includes security and safety lighting.

- G. Existing Electrical Service: Disable system only to make switchovers and connections. Obtain permission from Owner, Architect/Engineer and other trades at the site at least 24 hours before partially or completely disabling system. Minimize outage duration. Make temporary connections to maintain service in areas adjacent to work area.
- H. Trace all circuits and controls to be disconnected to ensure that vital services to other areas are not interrupted.

3.4 PROTECTION

- A. Provide protection for all existing and new cabling. Provide inner duct, conduit or other suitable means of protection to prevent damage to cables located in renovated areas.
- B. Damage to wiring, cabling or equipment shall be repaired by skilled mechanics for the trade involved at no additional contract amount.
- C. Fixtures, materials and equipment shall be protected at all times. The Contractor shall make good any damage caused either directly or indirectly by his workmen. Conduit openings shall be closed with caps or plugs during installation. Fixtures and equipment shall be tightly covered and protected against dirt, water and chemical or other injury. At the completion of all work, the fixtures, materials and equipment shall be thoroughly cleaned and turned over in a condition satisfactory to the Owner.
- D. Damage: Where wiring, raceways, lighting fixtures, devices or equipment to remain is inadvertently damaged or disturbed, cut out and remove damaged section and provide new of equal or capacity or quality.

3.5 ELECTRICAL DEMOLITION

- A. Remove from the premises and dispose of all existing wiring, conduit, material, fixtures, devices, equipment, etc., not required for re-use or re-installation.
- B. Deliver on the premises where directed existing material and equipment which is removed and is desired by the Owner or is indicated to remain the property of the Owner.
- C. All other equipment and materials which are removed shall become the property of the Contractor and shall be removed by him from the premises.
- D. Where electrical equipment is removed, also remove all wiring back to source panelboard or switch or to last remaining device on the same circuit. All conduit, hangers, supports, etc., shall also be removed unless otherwise noted. Such conduit may remain to be reused for new work provided said conduit is of the proper size and type as that specified and in a condition acceptable to Engineer and Owner.

- E. Any conduit abandoned in concrete slabs, walls, or other inaccessible locations shall be left empty except for a nylon pull wire. Ends shall be capped with push plugs for future use.
- F. Where an existing system is indicated to be removed, the Contractor shall provide complete removal of entire system including all wiring, conduit, and connected/associated fixtures and devices. The system shall be removed in its entirety unless otherwise noted.

3.6 EXISTING CONDUIT WORK

- A. Remove all abandoned raceway, including abandoned raceway above accessible ceiling finishes. Cut raceway flush with walls and floors, and patch surfaces. Remove conduit back to point of penetration/exposure.
- B. Remove concealed abandoned raceway to its source.
- C. Abandoned Work: buried electrical work abandoned in place shall be cut out approximately 2 inches beyond the face of adjacent construction, capped and the adjacent surface patched to match the existing finish.
- D. Disconnect abandoned outlets and remove devices. Remove abandoned outlets if raceway servicing them is abandoned and removed. Provide blank cover for abandoned outlets that are not removed.
- E. Ensure access to existing boxes and other installations which remain active and which require access. Modify installation or provide access panel as appropriate.
- F. Extend existing raceway and box installations using materials and methods compatible with existing electrical installations, or as specified.
- G. Clean and repair existing raceway and boxes that remain or are to be reinstalled.
- H. Remove all abandoned wiring from existing conduits and ductbanks. Abandoned wiring that cannot be removed shall be tagged at each end as "Abandoned".
- I. Contractor shall provide all cutting and patching required to connect to and extend existing conduits, wiring, circuits, etc.

3.7 EXISTING WIRING AND CABLING WORK

- A. Remove all abandoned and unused wire and cable, including abandoned wire and cable above accessible ceiling finishes. Patch surfaces where removed cables pass through building finishes. Remove abandoned and unused cabling and wiring back to the source.
- B. Disconnect abandoned circuits and remove circuit wire and cable. Remove abandoned boxes if wire and cable servicing them is abandoned and removed. Provide blank cover for abandoned boxes that are not removed.

- C. Ensure access to existing wiring connections which remain active and which require access. Modify installation or provide access panel as appropriate.
- D. Extend existing circuits using materials and methods compatible with existing electrical installations or as specified.
- E. Clean and repair existing wire and cable that remain or is to be reinstalled.
- F. Provide supports for all wiring and cabling to remain as required by NEC.
- G. Contractor shall provide field services for racking out of all existing circuits to be maintained. Contractor shall locate, trace and label, all existing circuits being re-used.

3.8 DEMOLITION AND EXTENSION OF EXISTING ELECTRICAL WORK

- B. Demolish and extend existing electrical work to meet all requirements of these specifications.
- C. If certain raceways and boxes are abandoned but not scheduled for removal, those items must be shown on the As-Built Drawings.
- D. Remove, relocate, and extend existing installations to accommodate new construction.
- E. Remove abandoned wiring to source of supply.
- F. Disconnect and remove abandoned luminaires. Remove brackets, stems, hangers, and other accessories.
- G. Repair adjacent construction and finishes damaged during demolition and extension work.
- H. Maintain access to existing electrical installations which remain active. Modify installation or provide access panel as appropriate.
- I. Extend existing installations using materials and methods (compatible with existing electrical installations, or) as specified. This includes the extension of the circuit from the last active device to the next device in the system to be activated.

3.9 CLEANING AND REPAIR

- A. The Consultant shall show, on the drawings, all items to be cleaned or repaired.
- B. Clean and repair existing equipment and materials that remain or are to be reused.
- C. Panelboards: Clean exposed surfaces and check tightness of electrical connections. Replace damaged circuit breakers and provide closure plates for vacant positions. Provide typed circuit

directory showing revised circuiting arrangement. Trace existing circuits to determine exact location and type of load served by each circuit breaker.

D. Provide new labels on all existing electrical equipment being re-used.

3.10 INSTALLATION

A. Install relocated materials and equipment under the provisions of other sections.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 26 05 19

LOW-VOLTAGE ELECTRICAL POWER CONDUCTORS AND CABLES

PART 1. GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes the following:
 - 1. Building wires and cables rated 600 V and less.
 - 2. Connectors, splices, and terminations rated 600 V and less.

1.3 SUBMITTALS

- A. Product Data: For each type of product indicated.
- B. Qualification Data: For testing agency.
- C. Field quality-control test reports.

1.4 QUALITY ASSURANCE

- A. Testing Agency: Engage a qualified independent testing agency to perform field quality-control testing.

PART 2. PRODUCTS

2.1 CONDUCTORS AND CABLES

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 - 1. Alcan Products Corporation; Alcan Cable Division.
 - 2. American Insulated Wire Corp.; a Leviton Company.
 - 3. General Cable Corporation.
 - 4. Senator Wire & Cable Company.
 - 5. Southwire Company.
- B. Copper Conductors: Comply with NEMA WC 70.

- C. Conductor Insulation: Comply with NEMA WC 70 for Types THHN-THWN, XHHW, USE, and SO.
- D. Multiconductor Cable: Comply with NEMA WC 70/ICEA S-95-658 for metal-clad cable, Type MC, with ground wire.

2.2 CONNECTORS AND SPLICES

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following.
 1. AFC Cable Systems, Inc.
 2. Hubbell Power Systems, Inc.
 3. O-Z/Gedney; EGS Electrical Group LLC.
 4. 3M; Electrical Products Division.
 5. Tyco Electronics Corp.
- B. UL-listed, factory-fabricated wiring connectors of size, ampacity rating, material, type, and class for application and service indicated. Comply with Project's installation requirements and as specified in Part 3 "Wire and Insulation Applications" Article.
- C. Split Bolt Connectors: Not Acceptable.
- D. Solderless Pressure Connectors: High copper alloy terminal. May be used only for cable termination to equipment pads or terminals. Not approved for splicing.
- E. Spring Wire Connectors: Solderless spring type pressure connector with insulating covers for copper wire splices and taps. Use for conductor sizes 10 AWG and smaller.
- F. All wire connectors used in underground or exterior pull boxes shall be gel-filled twist connectors or a connector designed for damp and wet locations.
- G. Mechanical Connectors: Bolted type tin-plated; high conductivity copper alloy; spacer between conductors; beveled cable entrances.
- H. Compression (crimp) Connectors: Long barrel; seamless, tin-plated electrolytic high conductivity copper tubing, internally beveled barrel ends. Connector shall be clearly marked with the wire size and type and proper number and location of crimps.
- I. Heat shrinkable tubing shall meet the requirements of ANSI C119.1-1986 for buried connections to 90°C and shall be material flame-retarded per IEEE 383 "Vertical Tray Flame Test". Motor connection kits shall consist of heat-shrinkable, polymeric insulating material over the connection area and a high dielectric strength mastic to seal the ends against ingress of moisture and contamination. Motor connection kits shall accommodate a range of cable sizes for both in-line and stub-type configurations. Connection kits shall be independent of cable manufacturer's tolerances.
- J. Wire Nut Connectors:
 1. Wire nuts install in wet locations, exterior, etc., shall be self-contained, waterproof and corrosion-proof units incorporating prefilled silicone grease to block out moisture and air.

2. Connectors shall be UL listed appropriately sized according to manufacturer's recommendation for the suitable wire sizes and voltage rating (600 volt minimum).
3. Connectors body shall have a color-coded outer shell.
4. Connectors shall be as manufactured by King Technology or approved equal.

2.3 SYSTEM DESCRIPTION

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70 by a qualified testing agency, and marked for intended location and application.
- B. Comply with NFPA 70.

PART 3. EXECUTION

3.1 CONDUCTOR MATERIAL APPLICATIONS

- A. Feeders: Copper. Solid for No. 10 AWG and smaller; stranded for No. 8 AWG and larger.
- B. Branch Circuits: Copper. Solid for No. 10 AWG and smaller; stranded for No. 8 AWG and larger.

3.2 CONDUCTOR INSULATION AND MULTICONDUCTOR CABLE APPLICATIONS AND WIRING METHODS

- A. Service Entrance: Type THHN-THWN, single conductors in raceway.
- B. Feeders Concealed in Ceilings, Walls, Partitions, and Crawlspace: Type THHN-THWN, single conductors in raceway.
- C. Feeders Concealed in Concrete, below Slabs-on-Grade, and Underground: Type RHW, single conductors in raceway.
- D. Exposed Branch Circuits, Including in Crawlspace: Type THHN-THWN, single conductors in raceway.
- E. Branch Circuits Concealed in Ceilings, Walls, and Partitions: Type THHN-THWH, single conductors in raceway, except the last 10' from a junction box to recessed lighting fixture may be type MC cable.
- F. Branch Circuits Concealed in Concrete, below Slabs-on-Grade, and Underground: Type THHN-THWN, single conductors in raceway.
- G. Conductors shall be rated 75 deg C in wet locations and 90 deg C in dry locations.

3.3 INSTALLATION OF CONDUCTORS AND CABLES

- A. Conceal cables in finished walls, ceilings, and floors, unless otherwise indicated.

- B. Complete raceway installation between conductor and cable termination points according to Division 26 "Raceways and Boxes for Electrical Systems" prior to pulling conductors and cables.
- C. Use manufacturer-approved pulling compound or lubricant where necessary; compound used must not deteriorate conductor or insulation. Do not exceed manufacturer's recommended maximum pulling tensions and sidewall pressure values.
- D. Use pulling means, including fish tape, cable, rope, and basket-weave wire/cable grips, that will not damage cables or raceway.
- E. Install exposed cables parallel and perpendicular to surfaces of exposed structural members, and follow surface contours where possible.
- F. Support cables according to Section 260429, "Hangers and Supports for Electrical Systems."
- G. Identify and color-code conductors and cables according to Section 260553, "Identification for Electrical Systems."

3.4 CONNECTIONS

- A. Tighten electrical connectors and terminals according to manufacturer's published torque-tightening values. If manufacturer's torque values are not indicated, use those specified in UL 486A and UL 486B.
- B. Make splices and taps that are compatible with conductor material and that possess equivalent or better mechanical strength and insulation ratings than unspliced conductors.
- C. Wiring at Outlets: Install conductor at each outlet, with at least 12 inches (300 mm) of slack.
- A. Joints of #10 AWG and smaller shall be made with properly insulated solderless type pressure connectors. Where stranded conductors or multiple solid conductors are connected to terminals, solderless lugs manufactured by Thomas and Betts Company or equivalent shall be used.
- B. Joints of #8 AWG and larger in power and lighting circuits shall be of the type indented into the conductor by means of a hand or hydraulic pressure tool. Connectors shall be Burndy "Hydent", TeB "St Kon", or equivalent. Connectors for control wiring shall be Burndy "Hy-Lug", or equivalent.
- C. All circuits for exterior electric work shall be #10 AWG (minimum) and contain an extra #10 AWG (minimum) copper ground conductor. All exterior wiring shall be installed in conduit as specified above, unless otherwise noted as larger on the Drawings.

SLEEVE INSTALLATION FOR ELECTRICAL PENETRATIONS

- A. Coordinate sleeve selection and application with selection and application of firestopping specified in Division 26 Section "Electrical Firestopping," and "Basic Electrical Materials and Methods".

3.6 SLEEVE-SEAL INSTALLATION

- A. Install to seal underground exterior-wall penetrations according to Division 26 Section, "Basic Electrical Materials and Methods".

3.7 FIRESTOPPING

- A. Apply firestopping to electrical penetrations of fire-rated floor and wall assemblies to restore original fire-resistance rating of assembly according to Division 7 Section "Through Penetration Firestop System."

3.8 FIELD QUALITY CONTROL

- A. Testing Agency: Engage a qualified testing agency to perform tests and inspections and prepare test reports.
- B. Perform tests and inspections and prepare test reports.
- C. Tests and Inspections:
 - 1. After installing conductors and cables and before electrical circuitry has been energized, test service entrance and feeder conductors, and conductors feeding the mechanical equipment and services for compliance with requirements.
 - 2. Perform each visual and mechanical inspection and electrical test stated in NETA Acceptance Testing Specification. Certify compliance with test parameters.
- D. Measure tightness of bolted connections and compare torque measurements with manufacturer's recommended values.
- E. Verify continuity of each branch circuit conductor.
- F. Demonstration: Subject to wire and cable hook-ups, energize circuit and demonstrate functioning in accordance with requirements. Where necessary, correct malfunctioning units, and then retest to demonstrate compliance.
- G. Test Reports: Prepare a written report to record the following:
 - 1. Test procedures used.
 - 2. Test results that comply with requirements.
 - 3. Test results that do not comply with requirements and corrective action taken to achieve compliance with requirements.
- H. Remove and replace malfunctioning units and retest as specified above.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 26 05 26

GROUNDING AND BONDING FOR ELECTRICAL SYSTEMS

PART 1. GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes grounding and bonding systems and equipment.
- B. Section includes grounding and bonding systems and equipment, plus the following special applications:
 - 1. Underground distribution grounding.

1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product indicated.

1.4 INFORMATIONAL SUBMITTALS

- A. As-Built Data: Plans showing dimensioned as-built locations of grounding features specified in "Field Quality Control" Article, including the following:
 - 1. Test wells.
 - 2. Ground rods.
 - 3. Ground rings.
 - 4. Grounding arrangements and connections for separately derived systems.
- B. Qualification Data: For testing agency and testing agency's field supervisor.
- C. Field quality-control reports.

1.5 CLOSEOUT SUBMITTALS

- A. Operation and Maintenance Data: For grounding to include in emergency, operation, and maintenance manuals.

1. In addition to items specified in Division 01 Section "Operating, Maintenance, Project Data," include the following:
 - a. Instructions for periodic testing and inspection of grounding features at test wells, ground rings, grounding connections for separately derived systems based on NETA MTS.
 - 1) Tests shall determine if ground-resistance or impedance values remain within specified maximums, and instructions shall recommend corrective action if values do not.
 - 2) Include recommended testing intervals.

1.6 QUALITY ASSURANCE

- A. Testing Agency Qualifications: Member company of NETA or an NRTL.
 1. Testing Agency's Field Supervisor: Certified by NETA to supervise on-site testing.
- B. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- C. Comply with UL 467 for grounding and bonding materials and equipment.


PART 2. PRODUCTS

2.1 MANUFACTURERS

- A. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 1. Burndy; Part of Hubbell Electrical Systems.
 2. Dossert AF Telecommunications LLC.
 3. ERICO International Corporation.
 4. Fushi Copperweld Inc.
 5. Galvan Industries, Inc.; Electrical Products Division, LLC.
 6. Harger Lightning and Grounding.
 7. ILSCO.
 8. O-Z/Gedney; A Brand of the EGS Electrical Group.
 9. Robbins Lightning, Inc.

2.2 SYSTEM DESCRIPTION

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- B. Comply with UL 467 for grounding and bonding materials and equipment.



2.3 CONDUCTORS

- A. Insulated Conductors: Copper wire or cable insulated for 600 V unless otherwise required by applicable Code or authorities having jurisdiction.
- B. Bare Copper Conductors:
 - 1. Solid Conductors: ASTM B 3.
 - 2. Stranded Conductors: ASTM B 8.
 - 3. Tinned Conductors: ASTM B 33.
 - 4. Bonding Cable: 28 kcmil, 14 strands of No. 17 AWG conductor, 1/4 inch (6.3 mm) in diameter, unless otherwise noted.
 - 5. Bonding Conductor: No. 4 or No. 6 AWG, stranded conductor, unless otherwise noted.
 - 6. Bonding Jumper: Copper tape, braided conductors terminated with copper ferrules; 1-5/8 inches (41 mm) wide and 1/16 inch (1.6 mm) thick.
- C. Grounding Bus: Pre-drilled rectangular bars of annealed copper [1 1/2 by 4 inches (6.3 by 100 mm)] in cross section, unless otherwise indicated, with 9/32-inch (7.1 mm) holes spaced 1-1/8 inches (28 mm) apart. Stand-off insulators for mounting shall comply with UL 891 for use in switchboards, 600 V and shall be Lexan or PVC, impulse tested at 5000 V.

2.4 CONNECTORS

- A. Listed and labeled by an NRTL acceptable to authorities having jurisdiction for applications in which used and for specific types, sizes, and combinations of conductors and other items connected.
- B. Bolted Connectors for Conductors and Pipes: Copper or copper alloy.
- C. Welded Connectors: Exothermic welding kits of types recommended by kit manufacturer for materials being joined and installation conditions.
- D. Bus-Bar Connectors: Mechanical type, cast silicon bronze, solderless exothermic-type wire terminals, and long barrel, two-bolt connection to ground bus bar.

2.5 GROUNDING ELECTRODES

- A. Ground Rods: Copper-clad steel, 3/4 inch by 10 feet (19 mm by 3 m).

PART 3. EXECUTION

3.1 APPLICATIONS

- A. Conductors: Install solid conductor for No. 10 AWG and smaller, and stranded conductors for No. 8 AWG and larger unless otherwise indicated.

- B. Underground Grounding Conductors: Install bare tinned-copper conductor, No. 4/0 AWG minimum.
 - 1. Bury at least 24 inches (600 mm) below grade.
- C. Grounding Bus: Install in electrical equipment rooms, in rooms housing service equipment, and elsewhere as indicated.
 - 1. Install bus horizontally, on insulated spacers 2 inches (50 mm) minimum from wall, 6 inches (150 mm) above finished floor unless otherwise indicated.
- D. Conductor Terminations and Connections:
 - 1. Pipe and Equipment Grounding Conductor Terminations: Bolted connectors.
 - 2. Underground Connections: Welded connectors except at test wells and as otherwise indicated.
 - 3. Connections to Ground Rods at Test Wells: Bolted connectors.
 - 4. Connections to Structural Steel: Welded connectors.

3.2 GROUNDING AT THE SERVICE

- A. Equipment grounding conductors and grounding electrode conductors shall be connected to the ground bus. Install a main bonding jumper between the neutral and ground buses.

3.3 GROUNDING SEPARATELY DERIVED SYSTEMS

- A. Generator: Install grounding electrode(s) at the generator location. The electrode shall be connected to the equipment grounding conductor and to the frame of the generator.

3.4 GROUNDING UNDERGROUND DISTRIBUTION SYSTEM COMPONENTS

- A. Comply with IEEE C2 grounding requirements.
- B. Pad-Mounted Transformers and Switches: Install four ground rods and ground ring around the pad. Ground pad-mounted equipment and noncurrent-carrying metal items associated with substations by connecting them to underground cable and grounding electrodes. Install tinned-copper conductor not less than No. 4/0 AWG for ground ring and for taps to equipment grounding terminals. Bury ground ring not less than 6 inches (150 mm) from the foundation.
- C. Grounding Manholes and Handholes: Install a driven ground rod through manhole or handhole floor, close to wall, and set rod depth so 4 inches (100 mm) will extend above finished floor. If necessary, install ground rod before manhole is placed and provide No. 1/0 AWG bare, tinned-copper conductor from ground rod into manhole through a waterproof sleeve in manhole wall. Protect ground rods passing through concrete floor with a double wrapping of pressure-sensitive insulating tape or heat-shrunk insulating sleeve from 2 inches (50 mm) above to 6 inches (150 mm) below concrete. Seal floor opening with waterproof, nonshrink grout.

3.5 EQUIPMENT GROUNDING

- A. Install insulated equipment grounding conductors with all feeders and branch circuits.
- B. Air-Duct Equipment Circuits: Install insulated equipment grounding conductor to duct-mounted electrical devices operating at 120 V and more, including air cleaners, heaters, dampers, humidifiers, and other duct electrical equipment. Bond conductor to each unit and to air duct and connected metallic piping.
- C. Water Heater, Heat-Tracing, and Antifrost Heating Cables: Install a separate insulated equipment grounding conductor to each electric water heater and heat-tracing cable. Bond conductor to heater units, piping, connected equipment, and components.

3.6 INSTALLATION

- A. Grounding Conductors: Route along shortest and straightest path possible unless otherwise indicated or required by Code. Avoid obstructing access or placing conductors where they may be subjected to strain, impact, or damage.
- B. Ground Rods: Drive rods until tops are 2 inches (50 mm) below finished floor or final grade unless otherwise indicated.
 - 1. Interconnect ground rods with grounding electrode conductor below grade and as otherwise indicated. Make connections without exposing steel or damaging coating if any.
 - 2. For grounding electrode system not detailed on the drawings, install at least three rods spaced at least one-rod length from each other and located at least the same distance from other grounding electrodes, and connect to the service grounding electrode conductor.
- C. Test Wells: Ground rod driven through drilled hole in bottom of handhole. Handholes are specified in Division 26 Section "Underground Ducts and Raceways for Electrical Systems," and shall be at least 12 inches (300 mm) deep, with cover.
 - 1. Test Wells: Install at least one test well for each service unless otherwise indicated. Install at the ground rod electrically closest to service entrance. Set top of test well flush with finished grade or floor. Provide all test wells with twist lock cover, Hanger# BAW910 or approved equal.
- D. Bonding Straps and Jumpers: Install in locations accessible for inspection and maintenance except where routed through short lengths of conduit.
 - 1. Bonding to Structure: Bond straps directly to basic structure, taking care not to penetrate any adjacent parts.
 - 2. Bonding to Equipment Mounted on Vibration Isolation Hangers and Supports: Install bonding so vibration is not transmitted to rigidly mounted equipment.
 - 3. Use exothermic-welded connectors for outdoor locations; if a disconnect-type connection is required, use a bolted clamp.
- E. Grounding and Bonding for Piping:

1. Metal Water Service Pipe: Install insulated copper grounding conductors, in conduit, from building's main service equipment, or grounding bus, to main metal water service entrances to building. Connect grounding conductors to main metal water service pipes; use a bolted clamp connector or bolt a lug-type connector to a pipe flange by using one of the lug bolts of the flange. Where a dielectric main water fitting is installed, connect grounding conductor on street side of fitting. Bond metal grounding conductor conduit or sleeve to conductor at each end.
 2. Water Meter Piping: Use braided-type bonding jumpers to electrically bypass water meters. Connect to pipe with a bolted connector.
 3. Bond each aboveground portion of gas piping system downstream from equipment shutoff valve.
- F. Grounding for Steel Building Structure: Install a driven ground rod at base of each corner column and at intermediate exterior columns at distances not more than 40 feet (18 m) apart.
- G. Concrete-Encased Grounding Electrode (Ufer Ground): Fabricate according to NFPA 70; use a minimum of 20 feet (6 m) of bare copper conductor not smaller than No. 4 AWG.
1. If concrete foundation is less than 20 feet (6 m) long, coil excess conductor within base of foundation.
 2. Bond grounding conductor to reinforcing steel in at least four locations and to anchor bolts. Extend grounding conductor below grade and connect to building's grounding grid or to grounding electrode external to concrete.

3.7 FIELD QUALITY CONTROL

- A. Testing Agency: Engage a qualified testing agency to perform tests and inspections.
- B. Perform tests and inspections.
- C. Tests and Inspections
 1. After installing grounding system but before permanent electrical circuits have been energized, test for compliance with requirements.
 2. Inspect physical and mechanical condition. Verify tightness of accessible, bolted, electrical connections with a calibrated torque wrench according to manufacturer's written instructions.
 3. Test completed grounding system at each location where a maximum ground-resistance level is specified, at service disconnect enclosure grounding terminal, at ground test wells, and at individual ground rods. Make tests at ground rods before any conductors are connected.
 - a. Measure ground resistance no fewer than two full days after last trace of precipitation and without soil being moistened by any means other than natural drainage or seepage and without chemical treatment or other artificial means of reducing natural ground resistance.
 - b. Perform tests by fall-of-potential method according to IEEE 81.

4. Prepare dimensioned Drawings locating each test well, ground rod and ground-rod assembly, and other grounding electrodes. Identify each by letter in alphabetical order, and key to the record of tests and observations. Include the number of rods driven and their depth at each location, and include observations of weather and other phenomena that may affect test results. Describe measures taken to improve test results.
- D. Grounding system will be considered defective if it does not pass tests and inspections.
 - E. Prepare test and inspection reports.
 - F. Report measured ground resistances that exceed the following values:
 1. Power and Lighting Equipment or System with Capacity of 500 kVA and Less: 10 ohms.
 2. Power and Lighting Equipment or System with Capacity of 500 to 1000 kVA: 5 ohms.
 3. Substations and Pad-Mounted Equipment: 5 ohms.
 4. Manhole Grounds: 10 ohms.
 - G. Excessive Ground Resistance: If resistance to ground exceeds specified values, notify Architect promptly and include recommendations to reduce ground resistance.

END OF SECTION

NOT FOR BIDDING PURPOSES

NOT FOR BIDDING PURPOSES

SECTION 26 05 28

ELECTRICAL FIRESTOPPING

PART 1. GENERAL

1.1 SUMMARY

- A. Section includes:
1. Through-penetration firestopping in fire rated construction.
 2. Through-penetration smoke-stopping in smoke partitions.
- B. Related items: Raceway seals and manufactured electrical devices: Refer to Section 16100.

1.2 REFERENCES

- A. Underwriters Laboratories
1. UL Fire Resistance Directory
 - a. Through-penetration firestop devices (XICR)
 - b. Fire resistance rating (BXUV)
 - c. Through-penetration firestop systems (XHEZ)
 - d. Fill, void, or cavity material (XKHW)
 - B. American Society for Testing and Materials Standards: ASTM E 814-88: Standard Test Method for Fire Tests of Through-Penetration Firestops.

1.3 DEFINITIONS

- A. Assembly: Particular arrangement of materials specific to given type of construction described or detailed in reference documents.
- B. Barriers: Time-rated fire walls, smoke barrier walls, time rated ceiling/floor assemblies and structural floors
- C. Firestopping: Methods and materials applied in penetrations and unprotected openings to limit spread of heat, fire, gasses and smoke.
- D. Penetration: Opening or foreign material passing through or into barrier or structural floor such that full thickness of rated materials is not obtained.
- E. System: Specific products and applications, classified and numbered by Underwriters Laboratories, Inc. to close specific barrier penetrations.
- F. Sleeve: Metal fabrication or pipe section extended through thickness of barrier and used to permanently guard penetration. Sleeves are described as part of penetrating system in other sections and may or may not be required.

1.4 SYSTEM DESCRIPTION

A. Design Requirements

1. Fire-rated construction: Maintain barrier and structural floor fire resistance ratings including resistance to cold smoke at all penetrations, connections with other surfaces or types of construction, at separations required to permit building movement and sound or vibration absorption.
2. Smoke barrier construction: Maintain barrier and structural floor resistance to cold smoke at all penetrations, connections with other surfaces and types of construction, and at all separations required to permit building movement and sound or vibration absorption.

1.5 SUBMITTALS

- A. Submit in accordance with Section 16010, unless otherwise indicated.
- B. Product data: Manufacturer's specifications and technical data including the following:
 1. Detailed specification of construction and fabrication.
 2. Manufacturer's installation instructions.
- C. Shop drawings: Indicate dimensions, description of materials and finishes, general construction, specific modifications, component connections, anchorage methods, hardware, and installation procedures, plus the following specific requirements:
 1. Details of each proposed assembly identifying intended products and applicable UL system number, or UL classified devices.
 2. Manufacturer or manufacturer's representative shall provide qualified engineering judgment and drawings relating to non-standard applications as needed.
- D. Quality control submittals: Statement of qualifications.
- E. Applicator's qualifications statement: List past projects indicating required experience.

1.6 QUALITY ASSURANCE

- A. Installer's qualifications: Fire experienced in installation or application of systems similar in complexity to those required for this project, plus the following:
 1. Acceptable to or licensed by manufacturer, State or local authority where applicable.
 2. At least 2 years' experience with systems.
 3. Successfully completed at least 5 comparable scale projects using this system.

- B. Local and State regulatory requirements: Submit forms or acceptance for proposed assemblies not conforming to specific UL Firestop System numbers, or UL classified devices.
- C. Materials shall have been tested to provide fire rating at least equal to that of the construction.
- D. Manufacturer shall be a member of the International Firestop Council (IFC).

1.7 DELIVERY, STORAGE, AND HANDLING

- A. Packing and shipping:
 - 1. Deliver products in original unopened packaging with legible manufacturer's identification.
 - 2. Coordinate delivery with scheduled installation date, allow minimum storage at site.
- B. Storage and protection: Store materials in a clean, dry, ventilated location. Protect from soiling, abuse, moisture and freezing when required. Follow manufacturer's instructions.

1.8 PROJECT CONDITIONS

- A. Existing conditions:
 - 1. Verify existing conditions and substrate before starting work. Correct unsatisfactory conditions before proceeding.
 - 2. Proceed with installation only after penetrations of the substrate and supporting brackets have been installed.
- B. Environmental requirements:
 - 1. Furnish adequate ventilation if using solvent.
 - 2. Furnish forced air ventilation during installation if required by manufacturer.
 - 3. Keep flammable materials away from sparks or flame.
 - 4. Provide masking and drop cloths to prevent contamination of adjacent surfaces by firestopping materials.

1.9 GUARANTEE

- A. Submit copies of written guarantee agreeing to repair or replace joint sealers which fall in joint adhesion, extrusion resistance, migration resistance, or general durability or appear to deteriorate in any other manner not clearly specified by submitted manufacturer's data as an inherent quality of the material for the exposure indicated. The guarantee period shall be two year from date of substantial completion unless otherwise noted.

PART 2. PRODUCT

2.1 MANUFACTURERS

- A. Subject to compliance with requirements, manufacturers offering products that may be incorporated into the work include, but are not limited to, the following:
1. Hilti.
 2. Nelson.

2.2 THROUGH-PENETRATION FIRESTOPPING OF FIRE-RATED CONSTRUCTION

- A. Systems of devices listed in the UL Fire Resistance Directory under categories XLCR and XHEZ may be used, providing that it conforms to the construction type, penetration type, annular space requirements and fire rating involved in each separate instance, and that the system be symmetrical for wall applications. Systems or devices must be asbestos-free.
1. Additional requirements: Withstand the passage of hot smoke either as an inherent property of the system, or by the use of a separate product included as a part of the UL system or device, and designed to perform this function.
 2. Acceptable manufacturers and products:
 - a. Those listed in the UL Fire Resistance directory for the UL System involved and as further defined in the Systems and Applications Schedule in Part 3.6 of this section.
 - b. All firestopping products must be from a single manufacturer. All trades shall use products from the same manufacturer unless otherwise noted.

2.3 SMOKE-STOPPING AT SMOKE PARTITIONS

- A. Through-penetration smoke stopping: Any system complying with the requirements for through-penetration fire stopping in fire-rated construction, as specified in The Systems and Applications Schedule in Part 3.6 of this section, is acceptable, provided that the system includes the specified smoke seal or will provide a smoke seal. The length of time of the fire resistance may be disregarded.

2.4 ACCESSORIES

- A. Fill, void or cavity materials: As classified under category XHHW in the UL Fire Resistance Directory.
- B. Forming materials: As classified under category XHKU in the UL Fire Resistance Directory.
- C. Sleeves: Minimum 24 MSG galvanized steel, 12" diameter or smaller steel pipe. Sleeve shall project 1/2" from each surface of the floor/wall. Size as recommended by firestop manufacturer.

PART 3. EXECUTION

3.1 EXAMINATION

- A. Verification of conditions: Examine areas and conditions under which work is to be performed and identify conditions detrimental to proper or timely completion.
 - 1. Verify barrier penetrations are properly sized and in suitable condition for application of materials.
 - 2. Do not proceed until unsatisfactory conditions have been corrected.

3.2 PREPARATION

- A. Clean surfaces to be in contact with penetration seal materials of dirt, grease, or loose materials, rust, or other substances that may affect proper fitting, adhesion, or the required fire resistance.

3.3 INSTALLATION

- A. Install penetration seal materials in accordance with printed instructions of the UL Fire Resistance Directory and in accordance with manufacturer's instruction.
- B. Seal holes or voids made by penetrations to ensure an effective smoke barrier.
- C. Protect materials from damage on surfaces subject to traffic.
- D. When large openings are created in walls or floors to permit installation of conduits, cable tray, or other items, close unused portions of opening with firestopping materials tested for the application. See UL Fire Resistance Directory or Paragraph 2.2 of this document.
- E. Install smoke stopping as specified for firestopping.
- F. Provide sleeves the full thickness of the assembly being penetrated and cut sleeves to a length of 1" more than the overall thickness of the penetration, or as recommended by the firestop manufacturer.
- G. All holes and voids shall be sealed the same day they are made.

3.4 FIELD QUALITY CONTROL

- A. Examine penetration sealed areas to ensure proper installation before concealing or enclosing areas.
- B. Keep areas of work accessible until inspection by applicable code authorities.
- C. Perform under this section patching and repairing of firestopping caused by cutting or penetration by other trades.

3.5 ADJUSTING AND CLEANING

- A. Clean up spills of liquid components.

B. Neatly cut and trim materials as required.

C. Remove equipment, materials and debris, leaving area in undamaged, clean condition.

3.6 SYSTEMS AND APPLICATION SCHEDULES*

SEE NEXT PAGE.

NOT FOR BIDDING PURPOSES

PENETRATING ITEM	CONCRETE	GYPSUM	WOOD FLOOR/CEILING
Metal Pipe	CAJ1001 CP25S/L, CP25N/S CAJ1006 CS-195+, FS-195+ CAJ1007 FS-195+, 1" & 2" Wide CAJ1009 2000, 2000+, 2003 CAJ1010 2000, 2000+, 2003 CAJ1012 2000, 2000+, 2003 CAJ1013 2000, 2000+, 2003 CAJ1014 2000, 2000+, 2003 CAJ1015 2000, 2000+, 2003 CAJ1017 FD 150 CAJ1021 FD 150 CAJ1027 MPS-2+ CAJ1044 CP 25WB+ CAJ1052 CP 25S/L, CP 25N/S CAJ1058 2000, 2000+, 2003 CAJ1060 2000, 2000+, 2003 CAJ1063 2000, 2000+, 2003 CAJ1066 CP 25N/S, CP 25S/L, CP 25WB+ CAJ1091 CP 25N/S, CP 25S/L, CP 25WB+ CAJ1092 CP 25WB+ CAJ1102 FS-195+ CAJ1100 CP 25S/L, CP 25N/S CAJ1175 CP 25WB+ CAJ1176 CP 25WB+ CAJ1188 2000+ CBJ1020 CS-195+, FS-195+ CBJ1021 CS-195+, MPS-2+ CBJ1031 2001 CBJ1032 2001 FA1002 CP 25WB+ WJ1010 CP 25WB+ WJ1023 2001	WL1001 CP 25 WL1002 FS-195+ WL1003 CP 25WB+, CP 25N/S WL1008 2000+ WL1009 2000+ WL1010 2000+ WL1016 CP 25WB+ WL1017 CP 25WB+, CP 25N/S WL1022 CP 25WB+, CP 25N/S WL1026 FD 150 WL1027 CS-195+, FS-195+ WL1067 CP 25N/S WL1073 CP 25WB+ WL1080 MPS-2+ WL1082 2000+	FC1002 CP 25 FC1003 2000, 2000+, 20003 FC1006 CP 25WB+

NOT FOR BIDDING PURPOSES

PENETRA TING ITEM	CONCRETE	GYPSUM	WOOD FLOOR/ CEILING
Non- Metallic	CAJ2001 FS-195+, 1" & 2" WIDE, PPD'S CAJ2002 FS-195+ CAJ2003 CS-195+, FS-195+ CAJ2005 FS-195+ CAJ2006 FS-195+ CAJ2013 FS-195+ CAJ2019 2000, 2000+, 2003 CAJ2027 FS-195+, CP 25N/S, CP 25S/L, CP 25WB+ CAJ2028 FS-195, MPS-2+ CAJ2029 FS-195+, PPD'S CAJ2030 CS-195+, FS-195+ CAJ2040 FS-195+, CP 25WB+ CAJ2044 FS-195+, CP 25N/S, CP 25S/L CP 25 WB+ CAJ2090 FS-195+ CAJ2177 FS-195+, PPD'S FA2001 FS-195+, PPD'S FS2002 CS-195+, FS-195+, MPS-2+, PPD'S FA2011 FS-195+ WJ2012 FS-195+ 1" WIDE	WL2002 FS-195+, PPD'S WL2003 FS-195+ WL2004 FS-195+ WL2005 FS-195+ 4' WIDE WL2006 FS-195+ WL2013 FS-195+ WL2031 CS-195+, FS- 195+ WL2032 CS-195+, FS- 195+ WL2033 FS-195+ WL2073 FS-195+ 1" WIDE	FC2002 FS-195+, PPD'S FC2007 FS-195+ PPD'S FC2008 FS-195+ FC2009 FS-195+, PPD'S FC2024 FS-195+ FC2026 FS-195+ FC2028 FS-195+, 1' & 2" WIDE, PPD'S
Insulated Cable	CAJ3001 CP 25N/S, CP 25S/L CAJ3005 CS 195+, FS-195+ CAJ3007 2001 CAJ3009 2000, 2000+, 2003 CAJ3010 2000, 2000+, 2003 CAJ3011 2001 CAJ3014 FD 150 CAJ3015 FD 150 CAJ3021 MPS-2+ CAJ3029 2000, 2000+, 2003 CAJ3030 CP 25WB+ CAJ3031 CP 25N/S, CP 25S/L CAJ3041 2000, 2000+, 2003 CAJ3044 CS-195+, FS-195+	WL3001 CP 25, MPS-2+ WL3008 2000+ WL3009 2000+ WL3015 CP 25WB+, CP 25N/S WL3022 2000+ WL3030 FS-195+ WL3031 MPS-2+ WL3032 CP 25WB+ WL3041 2000+ WL3051 CP 25N/S WL3056 CP25N/S WL3062 CP 25WB+	FC3001 CP 25S/L, CP 25N/S FC3002 2000+ FC3003 2000, 2000+, 2003 FC3007 CP 25WB+, MPS-2+ FC3008 FS-195+

NOT FOR BIDDING PURPOSES

PENETRATING ITEM	CONCRETE	GYPSUM	WOOD FLOOR/CEILING
	CAJ3058 FS-195+, MPS-2+ CAJ3071 CP 25N/S, CP 25S/L CAJ3074 CP 25N/S, CP 25S/L CAJ3075 2001 CAJ3080 CP 25WB+ CBJ3016 CS-195+, FS-195+ CBJ3017 CS-195+, MPS-2+ FA3001 CP 25WB+ FB3004 CS-195+, MP WJ3015 2001 WJ3016 2001		
Mixed Penetrating Items Combos	CAJ8001 CS-195+ FS-195+ CAJ8003 2000, 2000+, 20003 CAJ8004 2000, 2000+, 20003 CAJ8006 2001 CAJ8013 FS-195+, CP 25 CBJ8004 CS-195, FS-195 CBJ8005 CS-195, MPS-2+ CBJ8008 2001 FA8001 FS-195+, CP 25WB+	WL8002 CS-195+, FS-195+	

* Underwriter's Laboratories, Inc., Fire Resistance Directory.

END OF SECTION

NOT FOR BIDDING PURPOSES

NOT FOR BIDDING PURPOSES

SECTION 26 05 29

HANGERS AND SUPPORTS FOR ELECTRICAL SYSTEMS

PART 1. GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes the following:

1. Hangers and supports for electrical equipment and systems.
2. Construction requirements for concrete bases.

- B. Related Sections include the following:

1. Metal Fabrications – For requirements for miscellaneous metal items involved in supports and fastenings.
2. Joint Sealants – For requirements for firestopping at sleeves through walls and floors that are fire barriers.

1.3 DEFINITIONS

- A. EMT: Electrical metallic tubing.
- B. IMC: Intermediate metal conduit.
- C. RMC: Rigid metal conduit.

1.4 PERFORMANCE REQUIREMENTS

- A. Design supports for multiple raceways capable of supporting combined weight of supported systems and its contents.
- B. Design equipment supports capable of supporting combined operating weight of supported equipment and connected systems and components.
- C. Rated Strength: Adequate in tension, shear, and pullout force to resist maximum loads calculated or imposed for this Project, with a minimum structural safety factor of five times the applied force.

1.5 SUBMITTALS

- A. Product Data: For the following:
 - 1. Steel slotted support systems.

1.6 QUALITY ASSURANCE

- A. Comply with NFPA 70.

1.7 COORDINATION

- A. Coordinate size and location of concrete bases. Cast anchor-bolt inserts into bases. Concrete, reinforcement, and formwork requirements are specified in Division 02.
- B. Coordinate installation of roof curbs, equipment supports, and roof penetrations. These items are specified in Division 07 Section "Roof Accessories" and Division 23.

PART 2. PRODUCTS

2.1 SUPPORT, ANCHORAGE, AND ATTACHMENT COMPONENTS

- A. Steel Slotted Support Systems: Comply with MFMA-4, factory-fabricated components for field assembly.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Allied Tube & Conduit.
 - b. Cooper B-Line, Inc.; a division of Cooper Industries.
 - c. EPSCO International Corporation.
 - d. US Metals Corp.
 - e. Thomas & Betts Corporation.
 - f. Unistrut; Tyco International, Ltd.
 - g. Wesanco, Inc.
 - 2. Metallic Coatings: Hot-dip galvanized after fabrication and applied according to MFMA-4.
 - 3. Painted Coatings: Manufacturer's standard painted coating applied according to MFMA-4.
 - 4. Channel Dimensions: Selected for applicable load criteria.
- B. Raceway and Cable Supports: As described in NECA 1 and NECA 101.
- C. Conduit and Cable Support Devices: Steel and malleable-iron hangers, clamps, and associated fittings, designed for types and sizes of raceway or cable to be supported.

- D. Support for Conductors in Vertical Conduit: Factory-fabricated assembly consisting of threaded body and insulating wedging plug or plugs for non-armored electrical conductors or cables in riser conduits. Plugs shall have number, size, and shape of conductor gripping pieces as required to suit individual conductors or cables supported. Body shall be malleable iron.
- E. Structural Steel for Fabricated Supports and Restraints: ASTM A 36/A 36M, steel plates, shapes, and bars; black and galvanized.
- F. Mounting, Anchoring, and Attachment Components: Items for fastening electrical items or their supports to building surfaces include the following:
1. Powder-Actuated Fasteners: Threaded-steel stud, for use in hardened portland cement concrete, steel, or wood, with tension, shear, and pullout capacities appropriate for supported loads and building materials where used.
 - a. Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 - 1) Hilti Inc.
 - 2) ITW Ramset/Red Head; a division of Illinois Tool Works, Inc.
 - 3) MKT Fastening, LLC.
 - 4) Simpson Strong-Tie Co., Inc., Ramset Fastening Systems Unit.
 2. Mechanical-Expansion Anchors: Insert-wedge-type, zinc-coated steel, for use in hardened portland cement concrete with tension, shear, and pullout capacities appropriate for supported loads and building materials in which used.
 - a. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 - 1) Cooper H-Line, Inc.; a division of Cooper Industries.
 - 2) Empire Tool and Manufacturing Co., Inc.
 - 3) Hilti Inc.
 - 4) ITW Ramset/Red Head; a division of Illinois Tool Works, Inc.
 - 5) MKT Fastening, LLC.
 3. Concrete Inserts: Steel or malleable-iron, slotted support system units similar to MSS Type 18; complying with MFMA-4 or MSS SP-58.
 4. Clamps for Attachment to Steel Structural Elements: MSS SP-58, type suitable for attached structural element.
 5. Through Bolts: Structural type, hex head, and high strength. Comply with ASTM A 325.
 6. Toggle Bolts: All-steel springhead type.
 7. Hanger Rods: Threaded steel.

2.2 FABRICATED METAL EQUIPMENT SUPPORT ASSEMBLIES

- A. Description: Welded or bolted, structural-steel shapes, shop or field fabricated to fit dimensions of supported equipment.

- B. Materials: Comply with requirements in Division 05 Section "Metal Fabrications" for steel shapes and plates.
- C. Submit structural calculations for load and strength of each component and detailing of each assembly.

PART 3. EXECUTION

3.1 APPLICATION

- A. Comply with NECA 1 and NECA 101 for application of hangers and supports for electrical equipment and systems except if requirements in this Section are stricter.
- B. Maximum Support Spacing and Minimum Hanger Rod Size for Raceway: Space supports for EMT, IMC, and RMC as required by NFPA 70. Minimum rod size shall be 1/4 inch (6 mm) in diameter.
- C. Multiple Raceways or Cables: Install trapeze-type supports fabricated with steel slotted or other support system, sized so capacity can be increased by at least 25 percent in future without exceeding specified design load limits.
 1. Secure raceways and cables to these supports with two-bolt conduit clamps.

3.2 SUPPORT INSTALLATION

- A. Comply with NECA 1 and NECA 101 for installation requirements except as specified in this Article.
- B. Strength of Support Assemblies: Where not indicated, select sizes of components so strength will be adequate to carry present and future static loads within specified loading limits. Minimum static design load used for strength determination shall be weight of supported components plus 200 lb (90 kg).
- C. Mounting and Anchorage of Surface-Mounted Equipment and Components: Anchor and fasten electrical items and their supports to building structural elements by the following methods unless otherwise indicated by code:
 1. To Wood: Fasten with lag screws or through bolts.
 2. To New Concrete: Bolt to concrete inserts.
 3. To Masonry: Approved toggle-type bolts on hollow masonry units and expansion anchor fasteners on solid masonry units.
 4. To Existing Concrete: Expansion anchor fasteners.
 5. To Steel: Beam clamps (MSS Type 19, 21, 23, 25, or 27) complying with MSS SP-69.
 6. To Light Steel: Sheet metal screws.
 7. Items Mounted on Hollow Walls and Nonstructural Building Surfaces: Mount cabinets, panelboards, disconnect switches, control enclosures, pull and junction boxes, transformers, and other devices on slotted-channel racks attached to substrate.

- D. Drill holes for expansion anchors in concrete at locations and to depths that avoid reinforcing bars.

3.3 INSTALLATION OF FABRICATED METAL SUPPORTS

- A. Comply with installation requirements in Division 05 Section "Metal Fabrications" for site-fabricated metal supports.
- B. Cut, fit, and place miscellaneous metal supports accurately in location, alignment, and elevation to support and anchor electrical materials and equipment.
- C. Field Welding: Comply with AWS D1.1/D1.1M.

3.4 CONCRETE BASES

- A. Construct concrete bases of dimensions indicated but not less than 4 inches (100 mm) larger in both directions than supported unit, and so anchors will be a minimum of 10 bolt diameters from edge of the base.
- B. Use 3000-psi (20.7-MPa), 28-day compressive-strength concrete. Concrete materials, reinforcement, and placement requirements are specified in Section 033000 "Cast-in-Place Concrete."
- C. Anchor equipment to concrete base as follows:
 - 1. Place and secure anchorage devices. Use supported equipment manufacturer's setting drawings, templates, diagrams, instructions, and directions furnished with items to be embedded.
 - 2. Install anchor bolts to elevations required for proper attachment to supported equipment.
 - 3. Install anchor bolts according to anchor-bolt manufacturer's written instructions.

3.5 PAINTING

- A. Touchup: Clean field welds and abraded areas of shop paint. Paint exposed areas immediately after erecting hangers and supports. Use same materials as used for shop painting. Comply with SSPC-PA 1 requirements for touching up field-painted surfaces.
 - 1. Apply paint by brush or spray to provide minimum dry film thickness of 2.0 mils (0.05 mm).
- B. Galvanized Surfaces: Clean welds, bolted connections, and abraded areas and apply galvanizing-repair paint to comply with ASTM A 780.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 26 05 33

RACEWAYS AND BOXES FOR ELECTRICAL SYSTEMS

PART 1. GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This Section includes raceways, fittings, boxes, enclosures, and cabinets for electrical wiring.
- B. Related Requirements: Section 16 "Underground Ducts and Raceways for Electrical Systems" for exterior ductbanks, manholes, and underground utility construction.

1.3 DEFINITIONS

- A. EMT: Electrical metallic tubing.
- B. FMC: Flexible metal conduit.
- C. IMC: Intermediate metal conduit.
- D. LFMC: Liquidtight flexible metal conduit.
- E. LFNC: Liquidtight flexible nonmetallic conduit.
- F. RNC: Rigid nonmetallic conduit.

1.4 SUBMITTALS

- A. Product Data: For surface raceways, wireways and fittings, floor boxes, hinged-cover enclosures, and cabinets.
- B. Shop Drawings: For the following raceway components. Include plans, elevations, sections, details, and attachments to other work.
 - 1. Custom enclosures and cabinets.
- C. Coordination Drawings: Conduit routing plans, drawn to scale, on which the following items are shown and coordinated with each other, based on input from installers of the items involved:
 - 1. Structural members in the paths of conduit groups with common supports.

2. HVAC and plumbing items and architectural features in the paths of conduit groups with common supports.

D. Source quality-control test reports.

1.5 QUALITY ASSURANCE

- A. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, Article 100, by a testing agency acceptable to authorities having jurisdiction, and marked for intended use.
- B. Comply with NFPA 70.

PART 2. PRODUCTS

2.1 METAL CONDUIT AND TUBING

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 1. AFC Cable Systems, Inc.
 2. Allied Tube & Conduit; a Tyco International Ltd. Co.
 3. Electri-Flex Co.
- B. Rigid Steel Conduit: ANSI C80.1
- C. IMC: ANSI C80.6.
- D. PVC-Coated Steel Conduit: PVC coated rigid steel conduit
 1. Comply with NEMA RN 1.
 2. Coating Thickness: 0.040 inch (1 mm), minimum.
- E. EMT: ANSI C80.5.
- F. FMC: Zinc-coated steel.
- G. LFMC: Flexible steel conduit with PVC jacket.
- H. Fittings for Conduit (Including all Types and Flexible and Liquidtight), EMT, and Cable: NEMA FB 1; listed for type and size raceway with which used, and for application and environment in which installed.
 1. Conduit Fittings for Hazardous (Classified) Locations: Comply with UL 886.
 2. Fittings for EMT: Steel or die-cast or compression type.
 3. Expansion Fittings: PVC or steel to match conduit type, complying with UL 651, rated for environmental conditions where installed, and including flexible external bonding jumper.

- I. Joint Compound for Rigid Steel Conduit or IMC: Listed for use in cable connector assemblies, and compounded for use to lubricate and protect threaded raceway joints from corrosion and enhance their conductivity.

2.2 NONMETALLIC CONDUIT AND TUBING

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 - 1. AFC Cable Systems, Inc.
 - 2. Anamet Electrical, Inc.; Anaconda Metal Hose.
 - 3. Aruco Corporation.
 - 4. Electri-Flex Co.
- B. RNC: NEMA TC 2, Type EPC-40-PVC, unless otherwise indicated.
- C. LFNC: UL 1660.
- D. Fittings for RNC: NEMA TC 3; match to conduit or tubing type and material.
- E. Fittings for LFNC: UL 514B.

2.3 METAL WIREWAYS AND AUXILIARY GUTTERS

- A. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 - 1. Cooper B-Line, Inc.
 - 2. Hoffman.
 - 3. Mono-Systems, Inc.
 - 4. Square D.
- B. Description: Steel metal, complying with UL 870 and NEMA 250, Type 1 unless otherwise indicated, and sized according to NFPA 70.
 - 1. Metal wireways installed outdoors shall be listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- C. Fittings and Accessories: Include covers, couplings, offsets, elbows, expansion joints, adapters, hold-down straps, end caps, and other fittings to match and mate with wireways as required for complete system.
- D. Wireway Covers: Hinged type unless otherwise indicated.
- E. Finish: Manufacturer's standard enamel finish.

2.4 SURFACE RACEWAYS

- A. Listing and Labeling: Surface raceways shall be listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- B. Surface Metal Raceways: Galvanized steel, dual compartment type with snap-on covers complying with UL 5. Manufacturer's standard enamel finish in color selected by Architect. Provide devices in multi-outlet assembly as indicated on the drawings. Provide all components, fittings, etc. required for a complete installation.
 - 1. Manufacturers: Subject to compliance with requirements, provide products by one of the following:
 - a. Wiremold / Legrand
 - b. Mono-Systems, Inc.
 - c. Panduit Corp.
 - d. Hubbell.

2.5 BOXES, ENCLOSURES, AND CABINETS

- A. Available Manufacturers: Subject to compliance with requirements, manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:
 - 1. Cooper Crouse-Hinds; Div. of Cooper Industries, Inc.
 - 2. Erickson Electrical Equipment Company.
 - 3. Hoffman.
 - 4. O-Z/Gedney; a unit of General Signal.
 - 5. Spring City Electrical Manufacturing Company.
 - 6. Thomas & Betts Corporation.
 - 7. Walker Systems, Inc.; Wiremold Company (The).
- B. Sheet Metal Outlet and Device Boxes: NEMA OS 1.
- C. Cast-Metal Outlet and Device Boxes: NEMA FB 1, aluminum, Type FD, with gasketed cover.
- D. Nonmetallic Outlet and Device Boxes: NEMA OS 2.
- E. Small Sheet Metal Pull and Junction Boxes: NEMA OS 1.
- F. Cast-Metal Access, Pull, and Junction Boxes: NEMA FB 1, cast aluminum with gasketed cover.
- G. Box extensions used to accommodate new building finishes shall be of same material as recessed box.
- H. Device Box Dimensions: 4 inches square by 2-1/8 inches deep (100 mm square by 60 mm deep).
- I. Gangable boxes are allowed.
- J. Hinged-Cover Enclosures: NEMA 250, Type 1, with continuous-hinge cover with flush latch, unless otherwise indicated.

1. Metal Enclosures: Steel, finished inside and out with manufacturer's standard enamel.
2. Interior Panels: Steel; all sides finished with manufacturer's standard enamel.

K. Cabinets:

1. NEMA 250, Type 1, galvanized-steel box with removable interior panel and removable front, finished inside and out with manufacturer's standard enamel.
2. Hinged door in front cover with flush latch and concealed hinge.
3. Key latch to match panelboards.
4. Metal barriers to separate wiring of different systems and voltage.
5. Accessory feet where required for freestanding equipment.

PART 3. EXECUTION

3.1 RACEWAY APPLICATION

A. Outdoors: Apply raceway products as specified below, unless otherwise indicated:

1. Exposed Conduit: Rigid steel conduit.
2. Concealed Conduit, Aboveground: Rigid steel conduit.
3. Underground Conduit: RNC, Type EPC-40-PVC, direct buried, unless otherwise noted.
4. Connection to Vibrating Equipment (Including Transformers and Hydraulic, Pneumatic, Electric Solenoid, or Motor-Driven Equipment): LFMC
5. Boxes and Enclosures, Aboveground: NEMA 250, Type 3R.

B. Comply with the following indoor applications, unless otherwise indicated:

1. Exposed, Not Subject to Physical Damage: EMT.
2. Exposed, Not Subject to Severe Physical Damage: EMT.
3. Exposed and Subject to Severe Physical Damage: Rigid steel conduit. Includes raceways in the following locations:
 - a. Loading dock.
 - b. Corridors used for traffic of mechanized carts, forklifts, and pallet-handling units.
 - c. Mechanical rooms to 8' AFF.
4. Concealed in Ceilings and Interior Walls and Partitions: EMT.
5. Connection to Vibrating Equipment (Including Transformers and Hydraulic, Pneumatic, Electric Solenoid, or Motor-Driven Equipment): LFMC.
6. Damp or Wet Locations: Rigid steel conduit.
7. Boxes and Enclosures: NEMA 250, Type 1, except use NEMA 250, Type 4X, stainless steel in damp or wet locations.

C. Minimum Raceway Size: 3/4-inch (21-mm) trade size.

D. Raceway Fittings: Compatible with raceways and suitable for use and location.

1. Rigid and Intermediate Steel Conduit: Use threaded rigid steel conduit fittings, unless otherwise indicated.
2. EMT: Use compression, steel fittings. Comply with NEMA FB 2.10.

3. Flexible Conduit: Use only fittings listed for use with flexible conduit. Comply with NEMA FB 2.20.
- E. Install surface raceways only in finished spaces where concealment of conduit in existing walls is not feasible.

3.2 INSTALLATION

- A. Comply with NECA 1 for installation requirements applicable to products specified in Part 2 except where requirements on Drawings or in this Article are stricter.
- B. Keep raceways at least 6 inches (150 mm) away from parallel runs of flues and steam or hot-water pipes. Install horizontal raceway runs above water and steam piping.
- C. Complete raceway installation before starting conductor installation.
- D. Support raceways as specified in Division 26 Section "Hangers and Supports for Electrical Systems."
- E. Arrange stub-ups so curved portions of bends are not visible above the finished slab.
- F. Install no more than the equivalent of three 90-degree bends in any conduit run except for communications conduits, for which fewer bends are allowed.
- G. Conceal conduit and EMT within accessible ceilings space unless otherwise indicated. Install conduits parallel or perpendicular to building lines.
- H. Support conduit within 12 inches (300 mm) of enclosures to which attached.
- I. Stub-ups to Above Recessed Ceilings:
 1. Use EMT, or RMC for raceways.
 2. Use a conduit bushing or insulated fitting to terminate stub-ups not terminated in hubs or in an enclosure.
- J. Threaded Conduit Joints, Exposed to Wet, Damp, Corrosive, or Outdoor Conditions: Apply listed compound to threads of raceway and fittings before making up joints. Follow compound manufacturer's written instructions.
- K. Raceway Terminations at Locations Subject to Moisture or Vibration: Use insulating bushings to protect conductors, including conductors smaller than No. 4 AWG.
- L. Install raceways square to the enclosure and terminate at enclosures with locknuts. Install locknuts hand tight plus 1/4 turn more.
- M. Do not rely on locknuts to penetrate nonconductive coatings on enclosures. Remove coatings in the locknut area prior to assembling conduit to enclosure to assure a continuous ground path.
- N. Cut conduit perpendicular to the length. For conduits 2-inch (53-mm) trade size and larger, use roll cutter or a guide to make cut straight and perpendicular to the length.

- O. Install pull wires in empty raceways. Use polypropylene or monofilament plastic line with not less than 200-lb (90-kg) tensile strength. Leave at least 12 inches (300 mm) of slack at each end of pull wire. Cap underground raceways designated as spare above grade alongside raceways in use.
- P. Surface Raceways:
1. Install surface raceway with a minimum 2-inch (50-mm) radius control at bend points.
 2. Secure surface raceway with screws or other anchor-type devices at intervals not exceeding 48 inches (1200 mm) and with no less than two supports per straight raceway section. Support surface raceway according to manufacturer's written instructions. Tape and glue are not acceptable support methods.
 3. Two-hole straps are required.
- Q. Install raceway sealing fittings at suitable, approved, and accessible locations and fill them with listed sealing compound. For concealed raceways, install each fitting in a flush steel box with a blank cover plate having a finish similar to that of adjacent plates or surfaces. Install raceway sealing fittings at the following points:
1. Where conduits pass from warm to cold locations, such as boundaries of refrigerated spaces.
 2. Where otherwise required by NFPA 70.
- R. Expansion-Joint Fittings for RNC: Install in each run of aboveground conduit that is located where environmental temperature change may exceed 30 deg F (17 deg C), and that has straight-run length that exceeds 25 feet (7.6 m).
1. Install expansion-joint fittings for each of the following locations, and provide type and quantity of fittings that accommodate temperature change listed for location:
 - a. Outdoor Locations Not Exposed to Direct Sunlight: 125 deg F (70 deg C) temperature change.
 - b. Outdoor Locations Exposed to Direct Sunlight: 155 deg F (86 deg C) temperature change.
 - c. Indoor Spaces: Connected with the Outdoors without Physical Separation: 125 deg F (70 deg C) temperature change.
 - d. Attics: 135 deg F (75 deg C) temperature change.
 2. Install fitting(s) that provide expansion and contraction for at least 0.00041 inch per foot of length of straight run per deg F (0.06 mm per meter of length of straight run per deg C) of temperature change.
 3. Install each expansion-joint fitting with position, mounting, and piston setting selected according to manufacturer's written instructions for conditions at specific location at the time of installation.

3.3 SLEEVE AND SLEEVE-SEAL INSTALLATION FOR ELECTRICAL PENETRATIONS

- A. Install sleeves and sleeve seals at penetrations of exterior floor and wall assemblies. Comply with requirements in Division 26 Section "Basic Electrical Materials and Methods."

3.4 FIRESTOPPING

- A. Apply firestopping to electrical penetrations of fire-rated floor and wall assemblies to restore original fire-resistance rating of assembly. Firestopping materials and installation requirements are specified in Division 26 Section "Electrical Firestopping."

3.5 PROTECTION

- A. Provide final protection and maintain conditions that ensure coatings, finishes, and cabinets are without damage or deterioration at time of Substantial Completion.
 - 1. Repair damage to galvanized finishes with zinc-rich paint recommended by manufacturer.
 - 2. Repair damage to PVC or paint finishes with matching touchup coating recommended by manufacturer.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 26 05 53

IDENTIFICATION FOR ELECTRICAL SYSTEMS

PART 1. GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section Includes:
 - 1. Identification for raceways.
 - 2. Identification of power and control cables.
 - 3. Identification for conductors.
 - 4. Underground-line warning tape.
 - 5. Warning labels and signs.
 - 6. Instruction signs.
 - 7. Equipment identification labels.
 - 8. Miscellaneous identification products.

1.3 SUBMITTALS

- A. Product Data: For each electrical identification product indicated.

1.4 QUALITY ASSURANCE

- A. Comply with ANSI A13.1 and IEEE C2.
- B. Comply with NFPA 70.
- C. Comply with 29 CFR 1910.144 and 29 CFR 1910.145.
- D. Comply with ANSI Z535.4 for safety signs and labels.
- E. Adhesive-attached labeling materials, including label stocks, laminating adhesives, and inks used by label printers, shall comply with UL 969.

1.5 COORDINATION

- A. Coordinate identification names, abbreviations, colors, and other features with requirements in other Sections requiring identification applications, Drawings, Shop Drawings, manufacturer's

wiring diagrams, and the Operation and Maintenance Manual; and with those required by codes, standards, and 29 CFR 1910.145. Use consistent designations throughout Project.

- B. Coordinate installation of identifying devices with completion of covering and painting of surfaces where devices are to be applied.
- C. Coordinate installation of identifying devices with location of access panels and doors.
- D. Install identifying devices before installing acoustical ceilings and similar concealment.

PART 2. PRODUCTS

2.1 POWER RACEWAY IDENTIFICATION MATERIALS

- A. Comply with ANSI A13.1 for minimum size of letters for legend and for minimum length of color field for each raceway size.
- B. Colors for Raceways Carrying Circuits at 600 V or Less:
 1. Black letters on an orange field for normal feeders, black letters on a yellow field for emergency feeders.
 2. Legend: Indicate voltage and system or service type.
- C. Snap-Around Labels for Raceways Carrying Circuits at 600 V or Less: Slit, pretensioned, flexible, preprinted, color-coded acrylic sleeve, with diameter sized to suit diameter of raceway or cable it identifies and to stay in place by gripping action.

2.2 POWER AND CONTROL CABLE IDENTIFICATION MATERIALS

- A. Comply with ANSI A13.1 for minimum size of letters for legend and for minimum length of color field for each cable size.
- B. Snap-Around Labels: Slit, pretensioned, flexible, preprinted, color-coded acrylic sleeve, with diameter sized to suit diameter of cable it identifies and to stay in place by gripping action.

2.3 CONDUCTOR IDENTIFICATION MATERIALS

- A. Color-Coding Conductor Tape: Colored, self-adhesive vinyl tape not less than 3 mils (0.08 mm) thick by 1 to 2 inches (25 to 50 mm) wide.

2.4 UNDERGROUND-LINE WARNING TAPE

- A. Tape:
 1. Recommended by manufacturer for the method of installation and suitable to identify and locate underground electrical and communications utility lines.
 2. Printing on tape shall be permanent and shall not be damaged by burial operations.

3. Tape material and ink shall be chemically inert, and not subject to degrading when exposed to acids, alkalis, and other destructive substances commonly found in soils.

B. Color and Printing:

1. Comply with ANSI Z535.1 through ANSI Z535.5.
2. Inscriptions for Red-Colored Tapes: ELECTRIC LINE, HIGH VOLTAGE.
3. Inscriptions for Orange-Colored Tapes: TELEPHONE CABLE, CATV CABLE, COMMUNICATIONS CABLE, OPTICAL FIBER CABLE.

C. Tag:

1. Multilayer laminate consisting of high-density polyethylene scrim coated with pigmented polyolefin, bright-colored, continuous-printed on one side with the description of the utility, compounded for direct-burial service.
2. Thickness: 12 mils (0.3 mm).
3. Weight: 36.1 lb/1000 sq. ft. (17.6 kg/100 sq. m).
4. 3-Inch (75-mm) Tensile According to ASTM D 882: 400 lbf (1780 N), and 11,500 psi (79.2 MPa).

2.5 WARNING LABELS AND SIGNS

A. Comply with NFPA 70 and 29 CFR 1910.145

B. Baked-Enamel Warning Signs:

1. Preprinted aluminum signs, punched or drilled for fasteners, with colors, legend, and size required for application.
2. 1/4-inch (6.4-mm) grommets in corners for mounting.
3. Nominal size, 7 by 10 inches (180 by 250 mm).

C. Metal-Backed, Butyrate Warning Signs:

1. Weather-resistant, nonfading, preprinted, cellulose-acetate butyrate signs with 0.0396-inch (1-mm) galvanized-steel backing; and with colors, legend, and size required for application.
2. 1/4-inch (6.4-mm) grommets in corners for mounting.
3. Nominal size, 10 by 14 inches (250 by 360 mm).

D. Warning label and sign shall include, but are not limited to, the following legends:

1. Multiple Power Source Warning: "DANGER - ELECTRICAL SHOCK HAZARD - EQUIPMENT HAS MULTIPLE POWER SOURCES."
2. Workspace Clearance Warning: "WARNING - OSHA REGULATION - AREA IN FRONT OF ELECTRICAL EQUIPMENT MUST BE KEPT CLEAR FOR 36 INCHES (915 MM)."

2.6 EQUIPMENT IDENTIFICATION LABELS

- A. Engraved, Laminated Acrylic or Melamine Label: Punched or drilled for screw mounting. White letters on a dark-gray background. Minimum letter height shall be 3/8 inch (10 mm).

- B. Stenciled Legend: In nonfading, waterproof, black ink or paint. Minimum letter height shall be 1 inch (25 mm).

2.7 CABLE TIES

- A. General-Purpose Cable Ties: Fungus inert, self extinguishing, one piece, self locking, Type 6/6 nylon.

1. Minimum Width: 3/16 inch (5 mm).
2. Tensile Strength at 73 deg F (23 deg C), According to ASTM D 638: 12,000 psi (82.7 MPa).
3. Temperature Range: Minus 40 to plus 185 deg F (Minus 40 to plus 85 deg C).
4. Color: Black except where used for color-coding.

- B. UV-Stabilized Cable Ties: Fungus inert, designed for continuous exposure to exterior sunlight, self extinguishing, one piece, self locking, Type 6/6 nylon.

1. Minimum Width: 3/16 inch (5 mm).
2. Tensile Strength at 73 deg F (23 deg C), According to ASTM D 638: 12,000 psi (82.7 MPa).
3. Temperature Range: Minus 40 to plus 185 deg F (Minus 40 to plus 85 deg C).
4. Color: Black.

- C. Plenum-Rated Cable Ties: Self extinguishing, UV stabilized, one piece, self locking.

1. Minimum Width: 3/16 inch (5 mm).
2. Tensile Strength at 73 deg F ((23 deg C)), According to ASTM D 638: 7000 psi (48.2 MPa).
3. UL 94 Flame Rating: V-0.
4. Temperature Range: Minus 50 to plus 284 deg F (Minus 46 to plus 140 deg C).
5. Color: Black.

2.8 MISCELLANEOUS IDENTIFICATION PRODUCTS

- A. Paint: Comply with requirements in painting Sections for paint materials and application requirements. Select paint system applicable for surface material and location (exterior or interior).
- B. Fasteners for Labels and Signs: Self-tapping, stainless-steel screws or stainless-steel machine screws with nuts and flat and lock washers.

PART 3. EXECUTION

3.1 INSTALLATION

- A. Verify identity of each item before installing identification products.
- B. Location: Install identification materials and devices at locations for most convenient viewing without interference with operation and maintenance of equipment.

- C. Apply identification devices to surfaces that require finish after completing finish work.
- D. Self-Adhesive Identification Products: Clean surfaces before application, using materials and methods recommended by manufacturer of identification device.
- E. Attach signs and plastic labels that are not self-adhesive type with mechanical fasteners appropriate to the location and substrate.
- F. System Identification Color-Coding Bands for Raceways and Cables: Each color-coding band shall completely encircle cable or conduit. Place adjacent bands of two-color markings in contact, side by side. Locate bands at changes in direction, at penetrations of walls and floors, at 50-foot (15-m) maximum intervals in straight runs, and at 25-foot (7.6-m) maximum intervals in congested areas.
- G. Cable Ties: For attaching tags. Use general-purpose type, except as listed below:
 - 1. Outdoors: UV-stabilized nylon.
 - 2. In Spaces Handling Environmental Air: Plenum rated.
- H. Underground-Line Warning Tape: During backfilling of trenches install continuous underground-line warning tape directly above line at 6 to 8 inches (150 to 200 mm) below finished grade. Use multiple tapes where width of multiple lines installed in a common trench or concrete envelope exceeds 16 inches (400 mm) overall.
- I. Painted Identification: Comply with requirements in painting Sections for surface preparation and paint application.

3.2 IDENTIFICATION SCHEDULE

- A. Accessible Raceways and Metal-Clad Cables, 600 V or Less, for Service, Feeder, and Branch Circuits More Than 50% and 120 V to ground: Identify with snap around label applied in bands. Install labels at 10-foot (3-m) maximum intervals.
- B. Accessible Raceways and Cables within Buildings: Identify the covers of each junction and pull box of the following systems with self-adhesive vinyl labels with the wiring system legend and system voltage. System legends shall be as follows:
 - 1. Emergency Power - Yellow.
 - 2. Power - Orange.
 - 3. Fire Alarm System - Red.
 - 4. Security System - Blue and Yellow.
 - 5. Mechanical and Electrical Supervisory System - Green and Blue.
 - 6. Telecommunications Systems - Green and Yellow.
 - 7. Control Wiring - Green and Red.
- C. Power-Circuit Conductor Identification, 600 V or Less: For conductors in vaults, pull and junction boxes, manholes, and handholes, use color-coding conductor tape to identify the phase.
 - 1. Color-Coding for Phase and Voltage Level Identification, 600 V or Less: Use colors listed below for ungrounded service, feeder, and branch-circuit conductors.
 - a. Color shall be factory applied or field applied for sizes larger than No. 8 AWG, if authorities having jurisdiction permit.

- b. Colors for 208/120-V Circuits:
 - 1) Phase A: Black.
 - 2) Phase B: Red.
 - 3) Phase C: Blue.
 - c. Colors for 480/277-V Circuits:
 - 1) Phase A: Brown.
 - 2) Phase B: Orange.
 - 3) Phase C: Yellow.
 - d. All control wiring shall be color coded when using wires of different color from the type used to designate phase wires.
 - e. Field-Applied, Color-Coding Conductor Tape: Apply in half-lapped turns for a minimum distance of 6 inches (150 mm) from terminal points and in boxes where splices or taps are made. Apply last two turns of tape with no tension to prevent possible unwinding. Locate bands to avoid obscuring factory cable markings.
 - f. All emergency wiring shall have the same color-coding, but shall be clearly identified as emergency in all outlets, fixtures, etc.
- D. Power-Circuit Conductor Identification, More than 600 V: For conductors in vaults, pull and junction boxes, manholes, and handholes, use nonmetallic plastic tag holder with adhesive-backed phase tags, and a separate tag with the circuit designation.
- E. Install instructional sign including the color-code for grounded and ungrounded conductors using adhesive-film-type labels.
- F. Control-Circuit Conductor Identification: For conductors and cables in pull and junction boxes, manholes, and handholes, use self-adhesive vinyl labels with the conductor or cable designation, origin, and destination.
- G. Control-Circuit Conductor Termination Identification: For identification at terminations provide self-adhesive vinyl labels with the conductor designation.
- H. Conductors to Be Extended in the Future: Attach marker tape to conductors and list source.
- I. Auxiliary Electrical Systems Conductor Identification: Identify field-installed alarm, control, and signal connections.
- 1. Identify conductors, cables, and terminals in enclosures and at junctions, terminals, and pull points. Identify by system and circuit designation.
 - 2. Use system of marker tape designations that is uniform and consistent with system used by manufacturer for factory-installed connections.
 - 3. Coordinate identification with Project Drawings, manufacturer's wiring diagrams, and the Operation and Maintenance Manual.
- J. Locations of Underground Lines: Identify with underground-line warning tape for power, lighting, communication, and control wiring and optical fiber cable.
- 1. Limit use of underground-line warning tape to direct-buried cables.
 - 2. Install underground-line warning tape for both direct-buried cables and cables in raceway.
- K. Workspace Indication: Install floor marking tape to show working clearances in the direction of access to live parts. Workspace shall be as required by NFPA 70 and 29 CFR 1926.403 unless

otherwise indicated. Do not install at flush-mounted panelboards and similar equipment in finished spaces.

- L. Warning Labels for Indoor Cabinets, Boxes, and Enclosures for Power and Lighting: Baked-enamel warning signs or Metal-backed, butyrate warning signs.
1. Comply with 29 CFR 1910.145.
 2. Identify system voltage with black letters on an orange background.
 3. Apply to exterior of door, cover, or other access.
 4. For equipment with multiple power or control sources, apply to door or cover of equipment including, but not limited to, the following:
 - a. Power transfer switches.
 - b. Controls with external control power connections.
- M. Operating Instruction Signs: Install instruction signs to facilitate proper operation and maintenance of electrical systems and items to which they connect. Install instruction signs with approved legend where instructions are needed for system or equipment operation.
- N. Emergency Operating Instruction Signs: Install instruction signs with white legend on a red background with minimum 3/8-inch- (10-mm-) high letters for emergency instructions at equipment used for power transfer.
- O. Equipment Identification Labels: On each unit of equipment, install unique designation label that is consistent with wiring diagrams, schedules, and the Operation and Maintenance Manual. Apply labels to disconnect switches and protection equipment, central or master units, control panels, control stations, terminal cabinets, and racks of each system. Systems include power, lighting, control, communication, signal, monitoring, and alarm systems unless equipment is provided with its own identification.
1. Labeling Instructions:
 - a. Indoor Equipment: Engraved, laminated acrylic or melamine label. Unless otherwise indicated, provide a single line of text with 1/2-inch- (13-mm-) high letters on a 1/2-inch- (38-mm-) high label; where two lines of text are required, use labels 2 inches (50 mm) high.
 - b. Outdoor Equipment: Engraved, laminated acrylic or melamine label.
 - c. Elevated Components: Increase sizes of labels and letters to those appropriate for viewing from the floor.
 - d. Unless provided with self-adhesive means of attachment, fasten labels with appropriate mechanical fasteners that do not change the NEMA or NRTL rating of the enclosure.
 2. Equipment to Be Labeled:
 - a. Panelboards: Typewritten directory of circuits in the location provided by panelboard manufacturer. Panelboard identification shall be engraved, laminated acrylic or melamine label, "Panel (designation), Served from (designation)."
 - b. Enclosures and electrical cabinets.
 - c. Access doors and panels for concealed electrical items.
 - d. Switchgear.
 - e. Switchboards.
 - f. Transformers: Label that includes tag designation shown on Drawings for the transformer, feeder, and panelboards or equipment supplied by the secondary.
 - g. Substations.
 - h. Emergency system boxes and enclosures.

- i. Motor-control centers.
- j. Enclosed switches.
- k. Enclosed circuit breakers.
- l. Enclosed controllers.
- m. Variable-speed controllers.
- n. Push-button stations.
- o. Power transfer equipment.
- p. Contactors.
- q. Remote-controlled switches, dimmer modules, and control devices.
- r. Battery-inverter units.
- s. Battery racks.
- t. Power-generating units.
- u. Monitoring and control equipment.
- v. UPS equipment.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 26 24 16

PANELBOARDS

PART 1. GENERAL

1.1. RELATED DOCUMENTS

- A. Drawings and general provision of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2. SUMMARY

- A. This Section includes distribution panelboards, lighting and power panelboards and fusible circuit breaker panelboards with associated auxiliary equipment rated 600 V and less.
- B. Related Sections include the following:
 - 1. Division 26 Section "Common Work Results for Electrical" for general materials and installation methods.
 - 2. Division 26 Section "Electrical Identification" for labeling materials.

1.3. SUBMITTALS

- A. Product Data: For each type of panelboard, accessory item, and component specified.
- B. Shop Drawings: For panelboards. Include dimensioned plans, sections, and elevations. Show tabulations of installed devices, major features, and voltage rating. Include the following:
 - 1. Enclosure type with details for types other than NEMA 250, Type 1.
 - 2. Bus configuration and current ratings.
 - 3. Short-circuit current rating of panelboard.
 - 4. Features, characteristics, ratings, and factory settings of individual protective devices and auxiliary components.
 - 5. Wiring Diagrams: Details of schematic diagram including control wiring and differentiating between manufacturer-installed and field-installed wiring.
- C. Qualification Data: For firms and persons specified in *Quality Assurance* Article.
- D. Seismic Qualification Certificates: Submit certification that panelboards, overcurrent protective devices, accessories, and components will withstand seismic forces defined in Section 260548 "Seismic Controls for Electrical Systems." Include the following:

1. Basis for Certification: Indicate whether withstand certification is based on actual test of assembled components or on calculation.
 2. Dimensioned Outline Drawings of Equipment Unit: Identify center of gravity and locate and describe mounting and anchorage provisions.
 3. Detailed description of equipment anchorage devices on which the certification is based and their installation requirements.
- E. Field Test Reports: Indicate and interpret test results for compliance with performance requirements.
- F. Panelboard Schedules: For installation in panelboards. Submit final versions after load balancing.
- G. Maintenance Data: For panelboard components to include in the Operation and Maintenance Manuals specified in Division 01.
- H. Project Record Data: Record actual locations of products, indicated actual branch circuit arrangement.

1.4. QUALITY ASSURANCE

- A. Testing Agency Qualifications: In addition to the requirements specified in Division 01 Section *Quality Control* an independent testing agency shall meet OSHA criteria for accreditation of testing laboratories, Title 29, Part 1907, or shall be a full member company of the International Electrical Testing Association.
1. Testing Agency Field Supervisor: Person currently certified by the International Electrical Testing Association or National Institute for Certification in Engineering Technologies, to supervise on-site testing specified in Part 3 of this Section.
- B. Listing and Labeling: Provide products specified in this Section that are listed and labeled.
1. The Terms *Listed* and *Labeled*: As defined in the National Electrical Code, Article 100.
 2. Listing and Labeling Agency Qualifications: A *Nationally Recognized Testing Laboratory* as defined in OSHA Regulation 1910.7.
- C. Comply with NFPA 70, *National Electrical Code*.
- D. Comply with NEMA AB1, *Molded Case Circuit Breakers*.
- E. Comply with NEMA PB1, *Panelboards*.
- F. Comply with NEMA PB1.1, *Instructions for Safe Installation, Operation & Maintenance of Panelboards Rated 600 Volts or Less*.

1.5. EXTRA MATERIALS

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 - 1. Keys: 2 spares of each type for panelboard cabinet lock.
 - 2. Circuit Breakers Including GFCI and Ground Fault Equipment Protection (GFEP) Types: Two spares for each panelboard.
 - 3. Fuses for Fused Switches: Equal to 10 percent of quantity installed for each size and type, but no fewer than three of each size and type.
 - 4. Fuses for Fused Power-Circuit Devices: Equal to 10 percent of quantity installed for each size and type, but no fewer than three of each size and type.

1.6. DELIVERY, STORAGE, AND HANDLING

- A. Remove loose packing and flammable materials from inside panelboards; install temporary electric heating (250 W per panelboard) to prevent condensation.
- B. Handle and prepare panelboards for installation according to NEMA PB 1.

1.7. PROJECT CONDITIONS

- A. Environmental Limitations:
 - 1. Do not deliver or install panelboards until spaces are enclosed and weathertight, wet work in spaces is complete and dry, work above panelboards is complete, and temporary HVAC system is operating and maintaining ambient temperature and humidity conditions at occupancy levels during the remainder of the construction period.
 - 2. Rate equipment for continuous operation under the following conditions unless otherwise indicated:
 - a). Ambient Temperature: Not exceeding 23 deg F (minus 5 deg C) to plus 104 deg F (plus 40 deg C).
 - b). Altitude: Not exceeding 6600 feet (2000 m).
- B. Service Conditions: NEMA PB 1, usual service conditions, as follows:
 - 1. Ambient temperatures within limits specified.
 - 2. Altitude not exceeding 6600 feet (2000 m).

1.8. COORDINATION

- A. Coordinate layout and installation of panelboards and components with other construction that penetrates walls or is supported by them, including electrical and other types of equipment, raceways, piping, encumbrances to workspace clearance requirements, and adjacent surfaces. Maintain required workspace clearances and required clearances for equipment access doors and panels.

PART 2. PRODUCTS

2.1. GENERAL REQUIREMENTS FOR PANELBOARDS

- A. Enclosures: Flush- and surface-mounted cabinets. Piano hinged doors and covers.
1. Rated for environmental conditions at installed location.
 - a). Indoor Dry and Clean Locations: NEMA 250, Type 1.
 - b). Outdoor Locations: NEMA 250, Type 4.
 - c). Kitchen Wash-Down Areas: NEMA 250, Type 4X, stainless steel.
 - d). Other Wet or Damp Indoor Locations: NEMA 250, Type 4.
 2. Hinged Front Cover: Entire front trim piano hinged to box and with piano hinged door within hinged trim cover.
 3. Finishes:
 - a). Panels and Trim: Steel, factory finished immediately after cleaning and pretreating with manufacturer's standard two-coat, baked-on finish consisting of prime coat and then a topcoat.
 - b). Back Boxes: Same finish as panels and trim.
 4. Directory Card: Inside panelboard door, mounted in metal frame with transparent protective cover.
 5. Multiple-Section Panelboards shall consist of two or more cabinets with identical interiors mounted under separate trims. Cabinets, trim, and doors shall be of the same size. Main lugs and busses of each section shall be rated as indicated on the Drawings. Where main breakers are indicated in multi-section panelboards, the main breaker shall be contained in one section with through-feed lugs and sub-feed cables installed within panel, equal to the incoming feeder size. All busses and lugs shall have ampere capacity equal to or greater than the main breaker ampere rating. Loads shall be divided as evenly as practical between the sections, in addition to being balanced over the phases.
- B. Incoming Mains Location: Top and bottom.
- C. Phase, Neutral, and Ground Buses:
1. Material: Hard-drawn copper, 98 percent conductivity.
 2. Equipment Ground Bus: Adequate for feeder and branch-circuit equipment grounding conductors; bonded to box.
 3. Isolated Ground Bus: Adequate for branch-circuit isolated ground conductors; insulated from box.
 4. Extra-Capacity Neutral Bus: Neutral bus rated 200 percent of phase bus and UL listed as suitable for nonlinear loads.
- D. Conductor Connectors: Suitable for use with conductor material and sizes.

1. Material: Hard-drawn copper, 98 percent conductivity.
 2. Main and Neutral Lugs: Compression type.
 3. Ground Lugs and Bus-Configured Terminators: Compression type.
 4. Feed-Through Lugs: Compression type, suitable for use with conductor material. Locate at opposite end of bus from incoming lugs or main device.
 5. Subfeed (Double) Lugs: Compression type suitable for use with conductor material. Locate at same end of bus as incoming lugs or main device.
 6. Extra-Capacity Neutral Lugs: Rated 200 percent of phase lugs mounted on extra-capacity neutral bus.
- E. Service Equipment Label: NRTL labeled for use as service equipment for panelboards or load centers with one or more main service disconnecting and overcurrent protective devices.
- F. Future Devices: Mounting brackets, bus connections, filler plates, and necessary appurtenances required for future installation of devices.
- G. Panelboard Short-Circuit Current Rating: Fully rated to interrupt symmetrical short-circuit current available at terminals..

2.2. LIGHTING AND APPLIANCE PANELBOARDS

- A. Basis-of-Design Product: Subject to compliance with requirements, provide Square D; a brand of Schneider Electric or comparable product by one of the following:
1. Eaton Corp.; Cutler-Hammer.
 2. Siemens Energy & Automation, Inc.
- B. Panelboards: NEMA PB-1, lighting and appliance branch-circuit type.
- C. Mains: Circuit breaker or lugs only, as indicated.
- D. Branch Overcurrent Protective Devices: Bolt-on circuit breakers, replaceable without disturbing adjacent units.
- E. Doors: Piano hinged doors and covers. Concealed hinges; secured with flush latch with tumbler lock; keyed alike.
- F. Column-Type Panelboards: Narrow gutter extension, with cover, to overhead junction box equipped with ground and neutral terminal buses.

2.3. DISCONNECTING AND OVERCURRENT PROTECTIVE DEVICES

- A. Basis-of-Design Product: Subject to compliance with requirements, provide Square D; a brand of Schneider Electric or comparable product by one of the following:
1. Eaton Corp.; Cutler-Hammer.
 2. Siemens Energy & Automation, Inc.

B. Molded-Case Circuit Breaker (MCCB): Comply with UL 489, with interrupting capacity to meet available fault currents.

1. Thermal-Magnetic Circuit Breakers: Inverse time-current element for low-level overloads, and instantaneous magnetic trip element for short circuits. Adjustable magnetic trip setting for circuit-breaker frame sizes 100A through 225A, field adjustable short-time and continuous current setting for frame sizes 250A and larger.

- a. Adjustable Instantaneous-Trip Circuit Breakers: Magnetic trip element with front-mounted, field-adjustable trip setting.
- b. GFCI Circuit Breakers: Single- and two-pole configurations with Class A ground-fault protection (6-mA trip).
- c. Ground-Fault Equipment Protection (GFEP) Circuit Breakers: Class B ground-fault protection (30-mA trip).
- d. Arc-Fault Circuit Interrupter (AFCI) Circuit Breakers: Comply with UL 1699; 120/240-V, single-pole configuration.
- e. Molded-Case Circuit-Breaker (MCCB) Features and Accessories:

- 1). Standard frame sizes, trip ratings, and number of poles.
- 2). Lugs: Compression style, suitable for number, size, trip ratings, and conductor material.
- 3). Application Listing: Appropriate for application; Type SWD for switching fluorescent lighting loads; Type HID for feeding fluorescent and high-intensity discharge (HID) lighting circuits.
- 4). Shunt Trip: 120 -V trip coil energized from separate circuit, set to trip at 55 percent of rated voltage.
- 5). Under-voltage Trip: Set to operate at 35 to 75 percent of rated voltage without intentional time delay.
- 6). Auxiliary Contacts: One SPDT switch with "a" and "b" contacts; "a" contacts mimic circuit-breaker contacts and "b" contacts operate in reverse of circuit-breaker contacts.
- 7). Multipole units enclosed in a single housing or factory assembled to operate as a single unit.
- 8). Handle Padlocking Device: Fixed attachment, for locking circuit-breaker handle in on or off position.
- 9). Handle Clamp: Loose attachment, for holding circuit-breaker handle in on position.

24. ACCESSORY COMPONENTS AND FEATURES

- A. Accessory Set: Include tools and miscellaneous items required for overcurrent protective device test, inspection, maintenance, and operation per manufacturer's recommendations.
- B. Portable Test Set: Provide for testing functions of solid-state trip devices without removing from panelboard. Include relay and meter test plugs suitable for testing panelboard meters and switchboard class relays.

PART 3. EXECUTION

3.1. INSTALLATION

- A. Install panelboards and accessory items according to NEMA PB 1.1.
- B. Mounting: Plumb and rigid without distortion of box. Mount flush panelboards uniformly flush with wall finish.
- C. Install filler plates in unused spaces.
- D. Wiring in Panelboard Gutters: Arrange conductors into groups and bundle and wrap with wire ties after completing load balancing.
- E. Two or three pole circuit breakers shall be common trip type. Single pole breakers with handle ties will not be permitted.
- F. Tandem circuit breakers will not be permitted.
- G. Multiple-section panelboards, as required by number of branch circuit breakers, shall consist of two or more cabinets with identical interiors mounted under separate trims. Cabinets, trims, and doors shall be the same size. Main lugs and busses of each section shall be rated as indicated on the Drawings. Where main breakers are indicated in multi-section panelboards the main breaker shall be contained in one section with feed-through lugs and sub-feed cables installed within panel, equal to the incoming feeder size. All buses and lugs shall have ampere capacity equal to or greater than the main breaker ampere rating. Loads shall be divided as evenly as practical between the sections in addition to being balanced over the phases.
- H. Provide ground buses in panelboards as indicated on the Drawings. Ground bus shall be similar in all respects to neutral bus.
- I. Ground Fault Protection: Install panelboard ground fault circuit interrupter devices in accordance with installation guidelines of NEMA 289, *Application Guide for Ground Fault Circuit Interrupters*.
- J. Branch circuit breakers (or switches) serving clocks, telephone and communications equipment, refrigerators, exit signs, fire alarm system controls, etc., shall be equipped with lock clips to prevent accidental operation.
- K. Branch circuit breakers serving electric water coolers shall be GFCI type for personnel protection (5mA).
- L. Branch circuit breakers serving vending machines shall be GFCI type for personnel protection (5mA).
- M. Branch circuit breakers serving receptacles and appliances located under kitchen ventilation hoods shall be equipped with shunt-trip mechanisms.

- N. Height: Six-feet, six-inches to top of panelboard; install panelboards taller than 6 feet with bottom no more than 4 inches above the floor. Top breaker maximum height not to exceed 6 feet 8 inches.
- O. Do not energize or connect service-entrance equipment and panelboards to their sources until surge protective devices are properly installed and connected.

3.2. IDENTIFICATION

- A. Identify field-installed wiring and components and provide warning signs as specified in Division 26 Section "Electrical Identification".
- B. Panelboard Nameplates: Label each panelboard with engraved laminated-plastic or metal nameplates mounted with corrosion-resistant screws.
- C. Device Nameplates: Label each branch circuit device on distribution panelboards with a nameplate complying with requirements for identification specified in Section 260553 "Identification for Electrical Systems."
- D. Panelboard Circuit Directories: Provide a typed written directory, indicating plainly what each branch circuit of the panelboard serves and where. Provide additional information as required by NEC. Spaces and spare breakers shall be written in pencil. Copying of Contract Drawing Panel Schedules and Descriptions shall not be acceptable. Circuit directory shall reflect final circuit connections, loads and locations after balancing of panelboard loads.

3.3. GROUNDING

- A. Make equipment grounding connections for panelboards as indicated.
- B. Provide ground continuity to main electrical ground bus as indicated.

3.4. CONNECTIONS

- A. Tighten electrical connectors and terminals, including grounding connections, according to manufacturer's published torque-tightening values. Where manufacturer's torque values are not indicated, use those specified in UL 486A and UL 486B.
- B. Neutral and ground conductors shall be isolated and terminated only at their respective bus bars. There shall only be one neutral-ground connection in service-entrance equipment by means of a removable main bonding jumper. Neutral and ground terminations at one bus bar shall not be acceptable.

3.5. FIELD QUALITY CONTROL

- A. Prepare for acceptance tests as follows:

1. Make insulation-resistance tests of each panelboard bus, component, and connecting supply, feeder, and control circuits.
 2. Make continuity tests of each circuit.
 3. Provide set of Contract Documents to test organization. Include full updating on final system configuration and parameters where they supplement or differ from those indicated in the original Contract Documents.
- B. Testing Agency: Provide services of a qualified independent testing agency to perform specified testing.
- C. Testing: After installing panelboards and after electrical circuitry has been energized, demonstrate product capability and compliance with requirements.
1. Procedures: Perform each visual and mechanical inspection and electrical test stated in NETA ATS, Section 7.5 for switches and Section 7.6 for molded-case circuit breakers. Certify compliance with test parameters.
 2. Correct malfunctioning units on-site, where possible, and retest to demonstrate compliance; otherwise, remove and replace with new units, and retest.
 3. Reports by Testing Organization: Report written reports of tests and observations. Report defective materials and workmanship and unsatisfactory test results. Include records of repairs and adjustments made.
 4. Labeling: Upon satisfactory completion of tests and related effort, apply a label to tested components indicating results of tests and inspections, responsible organization and person, and date.
 5. Protective Device Ratings and Settings: Verify indicated ratings and settings to be appropriate for final system configuration and parameters. Where discrepancies are found, recommend final protective device ratings and settings. Use accepted ratings or settings to make the final system adjustments.
- D. Visual and Mechanical Inspection: Include the following inspections and related work:
1. Inspect for defects and physical damage, labeling, and nameplate compliance with requirements of up-to-date drawings and panelboard schedules.
 2. Exercise and perform operational tests of all mechanical components and other operable devices in accordance with manufacturer's instruction manual.
 3. Check panelboard mounting, area clearances, and alignment and fit of components.
 4. Check tightness of bolted electrical connections with calibrated torque wrench. Refer to manufacturer's instructions for proper torque values.

5. Perform visual and mechanical inspection and related work for over-current protective devices.
 6. Verify that all neutral conductors are bonded to the system ground at the service-entrance prior to installation of the surge protective device.
 7. Verify that neutral-ground bonds do not exist at locations that are not service entrances or separately derived power sources.
- E. Electrical Tests: Include the following items performed in accordance with manufacturer's instructions:
1. Insulation resistance test of buses and portions of control wiring that is disconnected from solid-state devices. Insulation resistance less than 100 megohms is not acceptable.
 2. Ground resistance test on system and equipment ground connections.
 3. Test main and subfeed over-current protective devices.
 4. Test phase loss relay(s) at panelboards to verify that phase loss relays are fully operational.
- F. Retest: Correct deficiencies identified by tests and observations and provide retesting of panelboards by testing organization. Verify by the system tests that the total assembly meets specified requirements.

3.6. ADJUSTING

- A. Adjust moving parts and operable component to function smoothly, and lubricate as recommended by manufacturer.
- B. Set field-adjustable circuit-breaker trip ranges as specified in Section 260573 "Overcurrent Protective Device Coordination Study."
- C. Load Balancing: After Substantial Completion, but not more than 60 days after Final Acceptance, measure load balancing and make circuit changes.
 1. Measure as directed during period of normal system loading.
 2. Perform load-balancing circuit changes outside normal occupancy/working schedule of the facility and at time directed. Avoid disrupting critical 24-hour services such as fax machines and on-line data processing, computing, transmitting, and receiving equipment.
 3. After circuit changes, recheck loads during normal load period. Record all load readings before and after changes and submit test records.
 4. Tolerance: Difference exceeding 20 percent between phase loads, within a panelboard, is not acceptable. Rebalance and recheck as necessary to meet this minimum requirement.

3.7. PROTECTION

- A. Temporary Heating: Apply temporary heat to maintain temperature according to manufacturer's written instructions.

3.8. CLEANING

- A. On completion of installation, inspect interior and exterior of panelboards. Remove paint splatters and other spots, dirt, and debris. Touch up scratches and mars of finish to match original finish.

END OF SECTION

NOT FOR BIDDING PURPOSES

NOT FOR BIDDING PURPOSES

NOT FOR BIDDING PURPOSES

SECTION 26 27 26

WIRING DEVICES

PART 1. GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

A. Section Includes:

1. Receptacles, receptacles with integral GFCI, and associated device plates.
2. Weather-resistant receptacles.
3. Wall-switch.

1.3 DEFINITIONS

- A. EMI: Electromagnetic interference.
- B. GFCI: Ground-fault circuit interrupter.
- C. Pigtail: Short lead used to connect a device to a branch-circuit conductor.
- D. RFI: Radio-frequency interference.
- E. TVSS: Transient voltage surge suppressor.
- F. UTP: Unshielded twisted pair.

1.4 ADMINISTRATIVE REQUIREMENTS

A. Coordination:

1. Receptacles for Owner-Furnished Equipment: Match plug configurations.
2. Cord and Plug Sets: Match equipment requirements.

1.5 ACTION SUBMITTALS

- A. Product Data: For each type of product.

- B. Shop Drawings: List of legends and description of materials and process used for premarking wall plates.

1.6 INFORMATIONAL SUBMITTALS

- A. Field quality-control reports.

1.7 CLOSEOUT SUBMITTALS

- A. Operation and Maintenance Data: For wiring devices to include in all manufacturers' packing-label warnings and instruction manuals that include labeling conditions.

1.8 MAINTENANCE MATERIAL SUBMITTALS

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 1. Floor Service-Outlet Assemblies: One for every 10, but no fewer than one .

PART 2. PRODUCTS

2.1 MANUFACTURERS

- A. Manufacturers' Names: Shortened versions (shown in parentheses) of the following manufacturers' names are used in other Part 2 articles:
 1. Hubbell Incorporated; Wiring Device-Kellems (Hubbell).
 2. Leviton Mfg. Company Inc. (Leviton).
 3. Pass & Seymour LeGrand (Pass & Seymour).
- B. Source Limitations: Obtain each type of wiring device and associated wall plate from single source from single manufacturer.

2.2 GENERAL WIRING-DEVICE REQUIREMENTS

- A. Wiring Devices, Components, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- B. Comply with NFPA 70.
- C. Devices that are manufactured for use with modular plug-in connectors may be substituted under the following conditions:
 1. Connectors shall comply with UL 2459 and shall be made with stranding building wire.
 2. Devices shall comply with the requirements in this Section.

2.3 STRAIGHT-BLADE RECEPTACLES

- A. Convenience Receptacles, 125 V, 20 A: Comply with NEMA WD 1, NEMA WD 6 Configuration 5-20R, UL 498, and FS W-C-596.
1. Products: Subject to compliance with requirements, provide one of the following:
 - a. Hubbell; HBL5351 (single), HBL5352 (duplex).
 - b. Leviton; 5891 (single), 5352 (duplex).
 - c. Pass & Seymour; 5361 (single), 5362 (duplex).

2.4 GFCI RECEPTACLES

A. General Description:

1. Straight blade, non-feed-through type.
2. Comply with NEMA WD 1, NEMA WD 6, UL 498, UL 943 Class A, and FS W-C-596.
3. Include indicator light that shows when the GFCI has malfunctioned and no longer provides proper GFCI protection.

B. Duplex GFCI Convenience Receptacles, 125 V, 20 A:

1. Products: Subject to compliance with requirements provide one of the following:
 - a. Hubbell; GFR5352L.
 - b. Pass & Seymour; 2095.
 - c. Leviton; 7590.

2.5 TOGGLE SWITCHES

A. Comply with NEMA WD 1, UL 20, and FS W-S-896.

B. Switches, 120/277 V, 20 A:

1. Products: Subject to compliance with requirements, provide one of the following:
 - a. Single Pole:
 - i. Hubbell; HBL1221.
 - ii. Leviton; 1221-2.
 - iii. Pass & Seymour; CSB20AC1.
 - b. Three Way:
 - i. Hubbell; HBL1223.
 - ii. Leviton; 1223-2.
 - iii. Pass & Seymour; CSB20AC3.

C. Single-Pole, Double-Throw, Momentary-Contact, Center-off Switches: 120/277 V, 20 A; for use with mechanically held lighting contactors.

1. Products: Subject to compliance with requirements, provide one of the following:
 - a. Hubbell; HBL1557.
 - b. Leviton; 1257.

- c. Pass & Seymour; 1251.

2.6 WALL PLATES

- A. Single and combination types shall match corresponding wiring devices.
1. Plate-Securing Screws: Metal with head color to match plate finish.
 2. Material for Finished Spaces: Steel with white baked enamel, suitable for field painting, 0.035-inch- (1-mm-) thick, satin-finished, Type 302 stainless steel.
 3. Material for Unfinished Spaces: Galvanized steel.
 4. Material for Damp Locations: Cast aluminum with spring-loaded lift covers, and listed and labeled for use in wet and damp locations.
- B. Wet-Location, Weatherproof Cover Plates: NEMA 250, complying with Type 3R, weather-resistant, die-cast aluminum with lockable cover.

2.7 FINISHES

- A. Device Color:
1. Wiring Devices Connected to Normal Power System: Brown unless otherwise indicated or required by NFPA 70 or device listing.

PART 3. EXECUTION

3.1 INSTALLATION

- A. Comply with NECA 1, including mounting heights listed in that standard, unless otherwise indicated.
- B. Coordination with Other Trades:
1. Protect installed devices and their boxes. Do not place wall finish materials over device boxes and do not cut holes for boxes with routers that are guided by riding against outside of boxes.
 2. Keep outlet boxes free of plaster, drywall joint compound, mortar, cement, concrete, dust, paint, and other material that may contaminate the raceway system, conductors, and cables.
 3. Install device boxes in brick or block walls so that the cover plate does not cross a joint unless the joint is troweled flush with the face of the wall.
 4. Install wiring devices after all wall preparation, including painting, is complete.
- C. Conductors:
1. Do not strip insulation from conductors until right before they are spliced or terminated on devices.
 2. Strip insulation evenly around the conductor using tools designed for the purpose. Avoid scoring or nicking of solid wire or cutting strands from stranded wire.

3. The length of free conductors at outlets for devices shall meet provisions of NFPA 70, Article 300, without pigtails.
4. Existing Conductors:
 - a. Cut back and pigtail, or replace all damaged conductors.
 - b. Straighten conductors that remain and remove corrosion and foreign matter.
 - c. Pigtailing existing conductors is permitted, provided the outlet box is large enough.

D. Device Installation:

1. Replace devices that have been in temporary use during construction and that were installed before building finishing operations were complete.
2. Keep each wiring device in its package or otherwise protected until it is time to connect conductors.
3. Do not remove surface protection, such as plastic film and smudge covers, until the last possible moment.
4. Connect devices to branch circuits using pigtails that are not less than 6 inches (152 mm) in length.
5. When there is a choice, use side wiring with binding-head screw terminals. Wrap solid conductor tightly clockwise, two-thirds to three-fourths of the way around terminal screw.
6. Use a torque screwdriver when a torque is recommended or required by manufacturer.
7. When conductors larger than No. 12 AWG are installed on 15- or 20-A circuits, splice No. 12 AWG pigtails for device connections.
8. Tighten unused terminal screws on the device.
9. When mounting into metal boxes, remove the fiber or plastic washers used to hold device-mounting screws in yokes, allowing metal-to-metal contact.

E. Receptacle Orientation:

1. Install ground pin of vertically mounted receptacles up, and on horizontally mounted receptacles to the left.

F. Device Plates: Do not use oversized or extra-deep plates. Repair wall finishes and remount outlet boxes when standard device plates do not fit flush or do not cover rough wall opening.

G. Arrangement of Devices: Unless otherwise indicated, mount flush, with long dimension vertical and with grounding terminal of receptacles on top. Group adjacent switches under single, multi-opening wall plates.

H. Adjust locations of floor service outlets to suit arrangement of partitions and furnishings.

3.2 GFCI RECEPTACLES

- A. Install non-feed-through-type GFCI receptacles where protection of downstream receptacles is not required.

3.3 IDENTIFICATION

- A. Comply with Division 26 Section "Identification for Electrical Systems."
- B. Identify each receptacle with panelboard identification and circuit number. Use hot, stamped, or engraved machine printing with black-filled lettering on face of plate, and durable wire markers or tags inside outlet boxes.

3.4 FIELD QUALITY CONTROL

- A. Perform the following tests and inspections:
 - 1. Test Instruments: Use instruments that comply with UL 1436.
 - 2. Test Instrument for Convenience Receptacles: Digital wiring analyzer with digital readout or illuminated digital-display indicators of measurement.
- B. Tests for Convenience Receptacles:
 - 1. Line Voltage: Acceptable range is 105 to 132 V.
 - 2. Percent Voltage Drop under 15-A Load: A value of 6 percent or higher is unacceptable.
 - 3. Ground Impedance: Values of up to 2 ohms are acceptable.
 - 4. GFCI Trip: Test for tripping values specified in UL 1436 and UL 943.
 - 5. Using the test plug, verify that the device and its outlet box are securely mounted.
 - 6. Tests shall be diagnostic, indicating damaged conductors, high resistance at the circuit breaker, poor connections, inadequate fault current path, defective devices, or similar problems. Correct circuit conditions, remove malfunctioning units and replace with new ones, and retest as specified above.
- C. Wiring device will be considered defective if it does not pass tests and inspections.
- D. Prepare test and inspection reports.

END OF SECTION

SECTION 26 28 13

FUSES

PART 1. GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

A. Section Includes:

1. Cartridge fuses rated 600-V ac and less for use in control circuits, enclosed switches, and enclosed controllers.
2. Spare-fuse cabinets.

1.3 ACTION SUBMITTALS

- A. Product Data: For each type of product indicated. Include construction details, material, dimensions, descriptions of individual components, and finishes for spare-fuse cabinets. Include the following for each fuse type indicated:

1. Ambient Temperature Adjustment Information: If ratings of fuses have been adjusted to accommodate ambient temperatures, provide list of fuses with adjusted ratings.
 - a. For each fuse having adjusted ratings, include location of fuse, original fuse rating, local ambient temperature, and adjusted fuse rating.
 - b. Provide manufacturer's technical data on which ambient temperature adjustment calculations are based.
2. Dimensions and manufacturer's technical data on features, performance, electrical characteristics, and ratings.
3. Current-limitation curves for fuses with current-limiting characteristics.
4. Time-current coordination curves (average melt) and current-limitation curves (instantaneous peak let-through current) for each type and rating of fuse.
5. Coordination charts and tables and related data.
6. Fuse sizes for elevator feeders and elevator disconnect switches.

1.4 CLOSEOUT SUBMITTALS

- A. Operation and Maintenance Data: For fuses to include in emergency, operation, and maintenance manuals. In addition to items specified in Section 017823 "Operation and Maintenance Data," include the following:

1. Ambient temperature adjustment information.
2. Current-limitation curves for fuses with current-limiting characteristics.
3. Time-current coordination curves (average melt) and current-limitation curves (instantaneous peak let-through current) for each type and rating of fuse.
4. Coordination charts and tables and related data.

1.5 MAINTENANCE MATERIAL SUBMITTALS

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 1. Fuses: Equal to 10 percent of quantity installed for each size and type, but no fewer than three of each size and type.

1.6 QUALITY ASSURANCE

- A. Source Limitations: Obtain fuses, for use within a specific product or circuit, from single source from single manufacturer.
- B. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- C. Comply with NEMA FU 1 for cartridge fuses.
- D. Comply with NFPA 70.
- E. Comply with UL 248-11 for plug fuses.

1.7 PROJECT CONDITIONS

- A. Where ambient temperature to which fuses are directly exposed is less than 40 deg F (5 deg C) or more than 100 deg F (38 deg C), apply manufacturer's ambient temperature adjustment factors to fuse ratings.

1.8 COORDINATION

- A. Coordinate fuse ratings with utilization equipment nameplate limitations of maximum fuse size and with system short-circuit current levels.

PART 2. PRODUCTS

2.1 MANUFACTURERS

- A. Manufacturers: Subject to compliance with requirements, provide products by one of the following:

1. Cooper Bussmann, Inc.
2. Edison Fuse, Inc.
3. Ferraz Shawmut, Inc.
4. Littelfuse, Inc.

2.2 CARTRIDGE FUSES

- A. Characteristics: NEMA FU 1, nonrenewable cartridge fuses with voltage ratings consistent with circuit voltages.

2.3 SPARE-FUSE CABINET

- A. Characteristics: Wall-mounted steel unit with full-length, recessed piano-hinged door and key-coded cam lock and pull.
 1. Size: Adequate for storage of spare fuses specified with 15 percent spare capacity minimum.
 2. Finish: Gray, baked enamel.
 3. Identification: "SPARE FUSES" in 1-1/2-inch- (38 mm-) high letters on exterior of door.
 4. Fuse Pullers: For each size of fuse, where applicable and available, from fuse manufacturer.

PART 3. EXECUTION

3.1 EXAMINATION

- A. Examine fuses before installation. Reject fuses that are moisture damaged or physically damaged.
- B. Examine holders to receive fuses for compliance with installation tolerances and other conditions affecting performance, such as rejection features.
- C. Examine utilization equipment nameplates and installation instructions. Install fuses of sizes and with characteristics appropriate for each piece of equipment.
- D. Evaluate ambient temperatures to determine if fuse rating adjustment factors must be applied to fuse ratings.
- E. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 FUSE APPLICATIONS

- A. Cartridge Fuses:
 1. Feeders: Class J, time delay.
 2. Motor Branch Circuits: Class RK1, time delay.
 3. Other Branch Circuits: Class RK1, time delay.
 4. Control Circuits: Class CC, time delay.

3.3 INSTALLATION

- A. Install fuses in fusible devices. Arrange fuses so rating information is readable without removing fuse.
- B. Install spare-fuse cabinet(s).

3.4 IDENTIFICATION

- A. Install labels complying with requirements for identification specified in Section 260553 "Identification for Electrical Systems" and indicating fuse replacement information on inside door of each fused switch and adjacent to each fuse block, socket, and holder.

END OF SECTION

NOT FOR BIDDING PURPOSES

SECTION 26 28 16

ENCLOSED SWITCHES AND CIRCUIT BREAKERS

PART 1. GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and other Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

A. Section Includes:

1. Fusible switches.
2. Nonfusible switches.
3. Receptacle switches.
4. Shunt trip switches.
5. Molded-case circuit breakers (MCCBs).
6. Enclosures.

1.3 DEFINITIONS

- A. NC: Normally closed.
- B. NO: Normally open.
- C. SPDT: Single pole, double throw.

1.4 PERFORMANCE REQUIREMENTS

- A. Seismic Performance: Enclosed switches and circuit breakers shall withstand the effects of earthquake motions determined according to ASCE/SEI 7.

The term "withstand" means "the unit will remain in place without separation of any parts from the device when subjected to the seismic forces specified and the unit will be fully operational after the seismic event."

1.5 ACTION SUBMITTALS

- A. Product Data: For each type of enclosed switch, circuit breaker, accessory, and component indicated. Include dimensioned elevations, sections, weights, and manufacturers' technical data on features, performance, electrical characteristics, ratings, accessories, and finishes.

1. Enclosure types and details for types other than NEMA 250, Type 1.
 2. Current and voltage ratings.
 3. Short-circuit current ratings (interrupting and withstand, as appropriate).
 4. Detail features, characteristics, ratings, and factory settings of individual overcurrent protective devices, accessories, and auxiliary components.
 5. Include time-current coordination curves (average melt) for each type and rating of overcurrent protective device; include selectable ranges for each type of overcurrent protective device.
- B. Shop Drawings: For enclosed switches and circuit breakers. Include plans, elevations, sections, details, and attachments to other work.
1. Wiring Diagrams: For power, signal, and control wiring.

1.6 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For qualified testing agency.
- B. Seismic Qualification Certificates: For enclosed switches and circuit breakers, accessories, and components, from manufacturer.
1. Basis for Certification: Indicate whether withstand certification is based on actual test of assembled components or on calculation.
 2. Dimensioned Outline Drawings of Equipment Unit: Identify center of gravity and locate and describe mounting and anchorage provisions.
 3. Detailed description of equipment anchorage devices on which the certification is based and their installation requirements.
- C. Field quality-control reports.
1. Test procedures used.
 2. Test results that comply with requirements.
 3. Results of failed tests and corrective action taken to achieve test results that comply with requirements.

1.7 CLOSEOUT SUBMITTALS

- A. Operation and Maintenance Data: For enclosed switches and circuit breakers to include in emergency, operation, and maintenance manuals. In addition to items specified in Section 017823 "Operation and Maintenance Data," include the following:
1. Manufacturer's written instructions for testing and adjusting enclosed switches and circuit breakers.
 2. Time-current coordination curves (average melt) for each type and rating of overcurrent protective device; include selectable ranges for each type of overcurrent protective device.

1.8 MAINTENANCE MATERIAL SUBMITTALS

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 - 1. Fuses: Equal to 10 percent of quantity installed for each size and type, but no fewer than three of each size and type.
 - 2. Fuse Pullers: Two for each size and type.

1.9 QUALITY ASSURANCE

- A. Testing Agency Qualifications: Member company of NETA or an NRTL.
 - 1. Testing Agency's Field Supervisor: Currently certified by NETA to supervise on-site testing.
- B. Source Limitations: Obtain enclosed switches and circuit breakers, overcurrent protective devices, components, and accessories, within same product category, from single source from single manufacturer.
- C. Product Selection for Restricted Space: Drawings indicate maximum dimensions for enclosed switches and circuit breakers, including clearances between enclosures, and adjacent surfaces and other items. Comply with indicated maximum dimensions.
- D. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- E. Comply with NFPA 70.

1.10 PROJECT CONDITIONS

- A. Environmental Limitations: Rate equipment for continuous operation under the following conditions unless otherwise indicated:
 - 1. Ambient Temperature: Not less than minus 22 deg F (minus 30 deg C) and not exceeding 104 deg F (40 deg C).
 - 2. Altitude: Not exceeding 6600 feet (2010 m).

1.11 COORDINATION

- A. Coordinate layout and installation of switches, circuit breakers, and components with equipment served and adjacent surfaces. Maintain required workspace clearances and required clearances for equipment access doors and panels.

PART 2. PRODUCTS

2.1 FUSIBLE SWITCHES

- A. Basis-of-Design Product: Subject to compliance with requirements, provide Square D; a brand of Schneider Electric or comparable product by one of the following:
1. Siemens Energy & Automation, Inc.
 2. General Electric Company – GE Commercial & Industrial Electrical Distribution.
 3. Eaton Electrical, Inc.; Cutler-Hammer Business Unit.
- B. Type HD, Heavy Duty, Single Throw, 600-V ac, 1200 A and Smaller: UL 98 and NEMA KS 1, horsepower rated, with clips or bolt pads to accommodate specified fuses, lockable handle with capability to accept three padlocks, and interlocked with cover in closed position.
1. Siemens Energy & Automation, Inc.
 2. General Electric Company – GE Commercial & Industrial Electrical Distribution.
 3. Eaton Electrical, Inc.; Cutler-Hammer Business Unit.
- C. Type HD, Heavy Duty, Double Throw, 600-V ac, 1200 A and Smaller: UL 98 and NEMA KS 1, horsepower rated, with clips or bolt pads to accommodate specified fuses, lockable handle with capability to accept three padlocks, and interlocked with cover in closed position.
- D. Accessories:
1. Equipment Ground Kit: Internally mounted and labeled for copper and aluminum ground conductors.
 2. Neutral Kit: Internally mounted, insulated, capable of being grounded and bonded; labeled for copper and aluminum neutral conductors.
 3. Class R Fuse Kit: Provides rejection of other fuse types when Class R fuses are specified.
 4. Auxiliary Contact Kit: One NO/NC (Form "C") auxiliary contact(s), arranged to activate before switch blades open.
 5. Hookstick Handle: Allows use of a hookstick to operate the handle.
 6. Lugs: Compression type, suitable for number, size, and conductor material.
 7. Service-Kit Switches: Labeled for use as service equipment.
 8. Accessory Control Power Voltage: Remote mounted and powered 120-V ac. Provide as required with auxiliary conduit kit.

2.2 NONFUSIBLE SWITCHES

- A. Basis-of-Design Product: Subject to compliance with requirements, provide Square D; a brand of Schneider Electric or comparable product by one of the following:
1. Siemens Energy & Automation, Inc.
 2. General Electric Company – GE Commercial & Industrial Electrical Distribution.
 3. Eaton Electrical, Inc.; Cutler-Hammer Business Unit.

- B. Type HD, Heavy Duty, Single Throw, 600-V ac, 1200 A and Smaller: UL 98 and NEMA KS 1, horsepower rated, lockable handle with capability to accept three padlocks, and interlocked with cover in closed position.
- C. Accessories:
 - 1. Equipment Ground Kit: Internally mounted and labeled for copper and aluminum ground conductors.
 - 2. Neutral Kit: Internally mounted; insulated, capable of being grounded and bonded; labeled for copper and aluminum neutral conductors.
 - 3. Auxiliary Contact Kit: One NO/NC (Form "C") auxiliary contact(s), arranged to activate before switch blades open.
 - 4. Hookstick Handle: Allows use of a hookstick to operate the handle.
 - 5. Lugs: Compression type, suitable for number, size, and conductor material.
 - 6. Accessory Control Power Voltage: Remote mounted and powered, 120-V ac. Provide as required with auxiliary conduit kit.

2.3 RECEPTACLE SWITCHES

- A. Basis-of-Design Product: Subject to compliance with requirements, provide Square D; a brand of Schneider Electric or comparable product by one of the following:
 - 1. Siemens Energy & Automation, Inc.
 - 2. General Electric Company – GE Commercial & Industrial Electrical Distribution.
 - 3. Eaton Electrical, Inc.; Cutler-Hammer Business Unit.
- B. Type HD, Heavy-Duty, Single-Throw Nonfusible Switch: 600-V ac, UL 98 and NEMA KS 1; horsepower rated, lockable handle with capability to accept three padlocks; interlocked with cover in closed position.
- C. Interlocking Linkage: Provided between the receptacle and switch mechanism to prevent inserting or removing plug while switch is in the on position, inserting any plug other than specified, and turning switch on if an incorrect plug is inserted or correct plug has not been fully inserted into the receptacle.
- D. Receptacle: Polarized, three-phase, four-wire receptacle (fourth wire connected to enclosure ground lug)

2.4 SHORT TRIP SWITCHES

- A. Subject to compliance with requirements, provide product by one of the following:
 - 1. Cooper Bussmann, Inc.
 - 2. Ferraz Shawmut, Inc.
 - 3. Littelfuse, Inc.
- B. General Requirements: Comply with ASME A17.1, UL 50, and UL 98, with 200-kA interrupting and short-circuit current rating when fitted with Class J fuses.

- C. Switches: Three-pole, horsepower rated, with integral shunt trip mechanism and Class J fuse block; lockable handle with capability to accept three padlocks; interlocked with cover in closed position.
- D. Control Circuit: 120-V ac; obtained from integral control power transformer, with primary and secondary fuses, with a control power transformer of enough capacity to operate shunt trip, connected pilot, and indicating and control devices.
- E. Accessories:
 - 1. Oiltight key switch for key-to-test function.
 - 2. Oiltight red ON pilot light.
 - 3. Mechanically interlocked auxiliary contacts that change state when switch is opened and closed.
 - 4. Form C alarm contacts that change state when switch is tripped.
 - 5. Three-pole, double-throw, fire-safety and alarm relay; 120-V ac coil voltage.
 - 6. Three-pole, double-throw, fire-alarm voltage monitoring relay, complying with NFPA 72.

2.5 MOLDED-CASE CIRCUIT BREAKERS

- A. Basis-of-Design Product: Subject to compliance with requirements, provide Square D; a brand of Schneider Electric or comparable product by one of the following:
 - 1. Siemens Energy & Automation, Inc.
 - 2. General Electric Company – GE Commercial & Industrial Electrical Distribution.
 - 3. Eaton Electrical, Inc.; Cutler-Hammer Business Unit.
- B. General Requirements: Comply with UL 489, NEMA AB 1, and NEMA AB 3, with interrupting capacity to comply with available fault currents.
- C. Thermal-Magnetic Circuit Breakers: Inverse time-current element for low-level overloads and instantaneous magnetic trip element for short circuits. Adjustable magnetic trip setting for circuit-breaker frame sizes 250A and larger.
- D. Adjustable, Instantaneous-Trip Circuit Breakers: Magnetic trip element with front-mounted, field-adjustable trip setting.
- E. Ground-Fault, Circuit-Interrupter (GFCI) Circuit Breakers: Single- and two-pole configurations with Class A ground-fault protection (6-mA trip).
- F. Ground-Fault, Equipment-Protection (GFEP) Circuit Breakers: With Class B ground-fault protection (30-mA trip).
- G. Features and Accessories:
 - 1. Lugs: Compression type, suitable for number, size, trip ratings, and conductor material.
 - 2. Application Listing: Appropriate for application; Type SWD for switching fluorescent lighting loads; Type HID for feeding fluorescent and high-intensity discharge lighting circuits.
 - 3. Shunt Trip: Trip coil energized from separate circuit, with coil-clearing contact.

4. Auxiliary Contacts: One SPDT switch with "a" and "b" contacts; "a" contacts mimic circuit-breaker contacts, "b" contacts operate in reverse of circuit-breaker contacts.
5. Accessory Control Power Voltage: Remote mounted and powered; 120-V ac.

2.6 ENCLOSURES

- A. Enclosed Switches and Circuit Breakers: NEMA AB 1, NEMA KS 1, NEMA 250, and BL 50, to comply with environmental conditions at installed location.
 1. Indoor, Dry and Clean Locations: NEMA 250, Type 1.
 2. Outdoor Locations: NEMA 250, Type 3R.
 3. Kitchen Wash-Down Areas: NEMA 250, Type 4X, stainless steel.
 4. Other Wet or Damp, Indoor Locations: NEMA 250, Type 4X, stainless steel.
 5. Indoor Locations Subject to Dust, Falling Dirt, and Dripping Noncorrosive Liquids: NEMA 250, Type 12.
 6. Hazardous Areas Indicated on Drawings: NEMA 250, Type 9.

PART 3. EXECUTION

3.1 EXAMINATION

- A. Examine elements and surfaces to receive enclosed switches and circuit breakers for compliance with installation tolerances and other conditions affecting performance of the Work.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION

- A. Install individual wall-mounted switches and circuit breakers with tops at uniform height unless otherwise indicated.
- B. Temporary Lifting Provisions: Remove temporary lifting eyes, channels, and brackets and temporary blocking of moving parts from enclosures and components.
- C. Install fuses in fusible devices.
- D. Comply with NECA 1.

3.3 IDENTIFICATION

- A. Comply with requirements in Section 260553 "Identification for Electrical Systems."
 1. Identify field-installed conductors, interconnecting wiring, and components; provide warning signs.
 2. Label each enclosure with engraved metal or laminated-plastic nameplate.

3.4 FIELD QUALITY CONTROL

- A. Testing Agency: Engage a qualified testing agency to perform tests and inspections.
- B. Perform tests and inspections.
 - 1. Manufacturer's Field Service: Engage a factory-authorized service representative to inspect components, assemblies, and equipment installations, including connections, and
- C. Acceptance Testing Preparation:
 - 1. Test insulation resistance for each enclosed switch and circuit breaker, component, connecting supply, feeder, and control circuit.
 - 2. Test continuity of each circuit.
- D. Tests and Inspections:
 - 1. Perform each visual and mechanical inspection and electrical test stated in NETA Acceptance Testing Specification. Certify compliance with test parameters.
 - 2. Correct malfunctioning units on-site, where possible, and retest to demonstrate compliance; otherwise, replace with new units and retest.
 - 3. Test and adjust controls, remote monitoring, and safeties. Replace damaged and malfunctioning controls and equipment.
- E. Enclosed switches and circuit breakers will be considered defective if they do not pass tests and inspections.
- F. Prepare test and inspection reports including a certified report that identifies enclosed switches and circuit breakers and that describes scanning results. Include notation of deficiencies detected, remedial action taken, and observations after remedial action.

3.5 ADJUSTING

- A. Adjust moving parts and operable components to function smoothly, and lubricate as recommended by manufacturer.
- B. Set field-adjustable circuit-breaker trip ranges as specified in Section 260573 "Overcurrent Protective Device Coordination Study."

END OF SECTION

SECTION 26 29 13

ENCLOSED CONTROLLERS

PART 1. GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. Section includes the following enclosed controllers rated 600 V and less:
 - 1. Full-voltage manual.
 - 2. Full-voltage magnetic.
- B. Related Section:
 - 1. Division 23 for Variable-Frequency Motor Controllers for general-purpose, ac, adjustable-frequency, pulse-width-modulated controllers for use on variable torque loads in ranges up to 200 hp.

1.3 DEFINITIONS

- A. CPT: Control power transformer.
- B. MCCB: Molded-case circuit breaker.
- C. MCP: Motor circuit protector.
- D. N.C.: Normally closed.
- E. N.O.: Normally open.
- F. OCPD: Overcurrent protective device.

1.4 PERFORMANCE REQUIREMENTS

- A. Seismic Performance: Enclosed controllers shall withstand the effects of earthquake motions determined according to ASCE/SEI 7.
 - 1. The term "withstand" means "the unit will remain in place without separation of any parts from the device when subjected to the seismic forces specified and the unit will be fully operational after the seismic event."

1.5 ACTION SUBMITTALS

- A. Product Data: For each type of enclosed controller. Include manufacturer's technical data on features, performance, electrical characteristics, ratings, and enclosure types and finishes.
- B. Shop Drawings: For each enclosed controller. Include dimensioned plans, elevations, sections, details, and required clearances and service spaces around controller enclosures.
 - 1. Show tabulations of the following:
 - a. Each installed unit's type and details.
 - b. Factory-installed devices.
 - c. Nameplate legends.
 - d. Short-circuit current rating of integrated unit.
 - e. Features, characteristics, ratings, and factory settings of individual OCPDs in combination controllers.
 - 2. Wiring Diagrams: For power, signal, and control wiring.

1.6 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For qualified testing agency.
- B. Seismic Qualification Certificates: For enclosed controllers, accessories, and components, from manufacturer.
 - 1. Basis for Certification: Indicate whether withstand certification is based on actual test of assembled components or on calculation.
 - 2. Dimensioned Outline Drawings of Equipment Unit: Identify center of gravity and locate and describe mounting and anchorage provisions.
 - 3. Detailed description of equipment anchorage devices on which the certification is based and their installation requirements.
- C. Field quality-control reports.
- D. Load-Current and List of Settings of Adjustable Overload Relays: Compile after motors have been installed and arrange to demonstrate that switch settings for motor running overload protection suit actual motors to be protected.

1.7 CLOSEOUT SUBMITTALS

- A. Operation and Maintenance Data: For enclosed controllers to include in emergency, operation, and maintenance manuals. In addition to items specified in Section 017823 "Operation and Maintenance Data," include the following:
 - 1. Routine maintenance requirements for enclosed controllers and installed components.
 - 2. Manufacturer's written instructions for setting field-adjustable overload relays.

1.8 MATERIALS MAINTENANCE SUBMITTALS

- A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.
 - 1. Control Power Fuses: Equal to 10 percent of quantity installed for each size and type, but no fewer than two of each size and type.
 - 2. Indicating Lights: Two of each type and color installed.

1.9 QUALITY ASSURANCE

- A. Testing Agency Qualifications: Member company of NETA or an NRTL.
 - 1. Testing Agency's Field Supervisor: Currently certified by NETA to supervise on-site testing.
- B. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.
- C. Comply with NFPA 70.
- D. IEEE Compliance: Fabricate and test enclosed controllers according to IEEE 344 to withstand seismic forces defined in Section 260548.16 "Seismic Controls for Electrical Systems."

1.10 DELIVERY, STORAGE, AND HANDLING

- A. Store enclosed controllers indoors in clean, dry space with uniform temperature to prevent condensation. Protect enclosed controllers from exposure to dirt, fumes, water, corrosive substances, and physical damage.
- B. If stored in areas subject to weather, cover enclosed controllers to protect them from weather, dirt, dust, corrosive substances, and physical damage. Remove loose packing and flammable materials from inside controllers; install temporary electric heating, with at least 250 W per controller.

1.11 PROJECT CONDITIONS

- A. Environmental Limitations: Rate equipment for continuous operation under the following conditions unless otherwise indicated:
 - 1. Ambient Temperature: Not less than minus 22 deg F (minus 30 deg C) and not exceeding 104 deg F (40 deg C).
 - 2. Altitude: Not exceeding 6600 feet (2010 m).

1.12 COORDINATION

- A. Coordinate layout and installation of enclosed controllers with other construction including conduit, piping, equipment, and adjacent surfaces. Maintain required workspace clearances and required clearances for equipment access doors and panels.

NOT FOR BIDDING PURPOSES

- B. Coordinate installation of roof curbs, equipment supports, and roof penetrations.

PART 2. PRODUCTS

2.1 FULL-VOLTAGE CONTROLLERS

- A. General Requirements for Full-Voltage Controllers: Comply with NEMA ICS 2, general purpose, Class A.
- B. Fractional Horsepower Manual Controllers: "Quick-make, quick-break" toggle or push-button action; marked to show whether unit is off, on, or tripped.
1. Basis-of-Design Product: Subject to compliance with requirements, provide Square D; a brand of Schneider Electric or comparable product by one of the following:
 - a. Siemens Energy & Automation, Inc.
 - b. General Electric Company, GE Commercial & Industrial Electrical Distribution.
 - c. Eaton Electrical, Inc.; Cutler-Hammer Business Unit.
 2. Configuration: Nonreversing.
 3. Overload Relays: Inverse-time-current characteristics; NEMA ICS 2, Class 10 tripping characteristics; heaters matched to nameplate full-load current of actual protected motor; external reset push button; bimetallic type.
 4. Surface mounting.
 5. Red pilot light.
 6. Hand-Off-Automatic Selector Switch
- C. Magnetic Controllers: Full voltage, across the line, electrically held.
1. Basis-of-Design Product: Subject to compliance with requirements, provide Square D; a brand of Schneider Electric or comparable product by one of the following:
 - a. Eaton Electrical Inc.; Cutler-Hammer Business Unit.
 - b. Siemens Energy & Automation, Inc.
 2. Configuration: Nonreversing.
 3. Contactor Coils: Pressure-encapsulated type.
 - a. Operating Voltage: Depending on contactor NEMA size and line-voltage rating, manufacturer's standard matching control power or line voltage.
 4. Power Contacts: Totally enclosed, double-break, silver-cadmium oxide; assembled to allow inspection and replacement without disturbing line or load wiring.
 5. Control Circuits: 120-V ac; obtained from integral CPT, with primary and secondary fuses, with CPT of sufficient capacity to operate integral devices and remotely located pilot, indicating, and control devices.
 - a. CPT Spare Capacity: 50 VA.

6. Solid-State Overload Relay:

- a. Switch or dial selectable for motor running overload protection.
- b. Sensors in each phase.
- c. Class 10/20 selectable tripping characteristic selected to protect motor against voltage and current unbalance and single phasing.

D. Combination Magnetic Controller: Factory-assembled combination of magnetic controller, OCPD, and disconnecting means.

1. Basis-of-Design Product: Subject to compliance with requirements, provide Square D; a brand of Schneider Electric or comparable product by one of the following:
 - a. Siemens Energy & Automation, Inc.
 - b. General Electric Company, GE Commercial & Industrial Electrical Distribution.
 - c. Eaton Electrical, Inc.; Cutler-Hammer Business Unit.
2. Auxiliary Contacts: N.O./N.C., arranged to activate before switch blades open.
3. Nonfusible Disconnecting Means:
 - a. NEMA KS 1, heavy-duty, horsepower-rated, nonfusible switch.
 - b. Lockable Handle: Accepts three padlocks and interlocks with cover in closed position.

2.2 ENCLOSURES

A. Enclosed Controllers: NEMA ICS 6, to comply with environmental conditions at installed location.

1. Dry and Clean Indoor Locations: Type 1.
2. Outdoor Locations: Type 3R.
3. Kitchen Wash-Down Areas: Type 4X stainless steel.
4. Other Wet or Damp Indoor Locations: Type 4X stainless steel.
5. Indoor Locations Subject to Dust, Falling Dirt, and Dripping Noncorrosive Liquids: Type 12.
6. Hazardous Areas Indicated on Drawings: Type 9.

2.3 ACCESSORIES

A. General Requirements for Control Circuit and Pilot Devices: NEMA ICS 5; factory installed in controller enclosure cover unless otherwise indicated.

1. Push Buttons, Pilot Lights, and Selector Switches: Heavy-duty type.
 - a. Push Buttons: types; maintained as indicated.
 - b. Pilot Lights: LED type; Red for “power available”, green for “running”; push to test.

- B. Control Relays: Two (2) N.O./N.C. auxiliary contacts, and adjustable solid-state time-delay relays as required by automation and control sequences.
- C. Phase-Failure, Phase-Reversal, and Undervoltage and Overvoltage Relays: Solid-state sensing circuit with isolated output contacts for hard-wired connections. Provide adjustable undervoltage, overvoltage, and time-delay settings, with automatic reset. Provide ICM Control ICM450 or approved equal, in a separate enclosure (NEMA rating to match controller).
- D. Sun shields installed on fronts, sides, and tops of enclosures installed outdoors and subject to direct and extended sun exposure.
- E. Cover gaskets for Type 1 enclosures.
- F. Terminals for connecting power factor correction capacitors to the line side of overload relays.
- G. Hand-Off-Automatic Selector Switch, NEMA ICS2, heavy-duty type.

PART 3. EXECUTION

3.1 EXAMINATION

- A. Examine areas and surfaces to receive enclosed controllers, with Installer present, for compliance with requirements and other conditions affecting performance of the Work.
- B. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION

- A. Wall-Mounted Controllers: Install enclosed controllers on walls with tops at uniform height unless otherwise indicated, and by bolting units to wall or mounting on lightweight structural-steel channels bolted to wall. For controllers not at walls, provide freestanding racks complying with Section 260519 "Hangers and Supports for Electrical Systems."
- B. Temporary Lifting Provisions: Remove temporary lifting eyes, channels, and brackets and temporary blocking of moving parts from enclosures and components.
- C. Install fuses in control circuits if not factory installed. Comply with requirements in Section 262813 "Fuses."
- D. Install heaters in thermal overload relays. Select heaters based on actual nameplate full-load amperes after motors have been installed.
- E. Install, connect, and fuse thermal-protector monitoring relays furnished with motor-driven equipment.
- F. Install power factor correction capacitors. Connect to the line side of overload relays. If connected to the load side of overload relays, adjust overload heater sizes to accommodate the reduced motor full-load currents.

- G. Comply with NECA 1.

3.3 IDENTIFICATION

- A. Identify enclosed controllers, components, and control wiring. Comply with requirements for identification specified in Section 260553 "Identification for Electrical Systems."
 - 1. Identify field-installed conductors, interconnecting wiring, and components; provide warning signs.
 - 2. Label each enclosure with engraved nameplate.
 - 3. Label each enclosure-mounted control and pilot device.

3.4 CONTROL WIRING INSTALLATION

- A. Install wiring between enclosed controllers and remote devices.
- B. Bundle, train, and support wiring in enclosures.
- C. Connect selector switches and other automatic-control selection devices where applicable.
 - 1. Connect selector switches to bypass only those manual- and automatic-control devices that have no safety functions when switches in manual-control position.
 - 2. Connect selector switches with enclosed-controller circuit in both manual and automatic positions for safety-type control devices such as low- and high-pressure cutouts, high-temperature cutouts, and motor overload protectors.

3.5 FIELD QUALITY CONTROL

- A. Testing Agency: Engage a qualified testing agency to perform tests and inspections.
- B. Acceptance Testing Preparation:
 - 1. Test insulation resistance for each enclosed controller, component, connecting supply, feeder, and control circuit.
 - 2. Test continuity of each circuit.
- C. Tests and Inspections:
 - 1. Inspect controllers, wiring, components, connections, and equipment installation. Test and adjust controllers, components, and equipment.
 - 2. Test insulation resistance for each enclosed-controller element, component, connecting motor supply, feeder, and control circuits.
 - 3. Test continuity of each circuit.
 - 4. Verify that voltages at controller locations are within plus or minus 10 percent of motor nameplate rated voltages. If outside this range for any motor, notify Construction Manager before starting the motor(s).
 - 5. Test each motor for proper phase rotation.
 - 6. Perform each electrical test and visual and mechanical inspection stated in NETA Acceptance Testing Specification. Certify compliance with test parameters.

7. Correct malfunctioning units on-site, where possible, and retest to demonstrate compliance; otherwise, replace with new units and retest.
 8. Test and adjust controls, remote monitoring, and safeties. Replace damaged and malfunctioning controls and equipment.
- D. Enclosed controllers will be considered defective if they do not pass tests and inspections.
- E. Prepare test and inspection reports including a certified report that identifies enclosed controllers and that describes scanning results. Include notation of deficiencies detected, remedial action taken, and observations after remedial action.

3.6 ADJUSTING

- A. Set field-adjustable switches, auxiliary relays, time-delay relays, timers, and overload-relay pickup and trip ranges.
- B. Set the taps on reduced-voltage autotransformer controllers at 50 percent.
- C. Set field-adjustable switches and program microprocessors for required start and stop sequences in reduced-voltage solid-state controllers.

3.7 PROTECTION

- A. Temporary Heating: Apply temporary heat to maintain temperature according to manufacturer's written instructions until enclosed controllers are ready to be energized and placed into service.
- B. Replace controllers whose interiors have been exposed to water or other liquids prior to Substantial Completion.

3.8 DEMONSTRATION

- A. Train Owner's maintenance personnel to adjust, operate, and maintain enclosed controllers.

END OF SECTION

SECTION 28 31 11

FIRE ALARM SYSTEM

PART 1. GENERAL

1.1 RELATED DOCUMENTS

- A. Drawings and general provisions of the Contract, including General and Supplementary Conditions and Division 01 Specification Sections, apply to this Section.

1.2 SUMMARY

- A. This specification provides the requirements for the installation, programming and configuration of an extension of the existing Fire Alarm System. The system shall include, but not be limited to: Fire Alarm Control Panel, Automatic and Manually activated alarm Initiating and Indicating Peripheral Devices and Appliances, conduit, wire and accessories required to furnish a complete and operational Fire Alarm System. System shall include, but not be limited to, the following:
1. System smoke detectors.
 2. Heat detectors.
 3. Carbon monoxide detectors.
 4. Notification appliances.
 5. Addressable interface devices.
- B. The system shall include all wiring, raceways, pull boxes, terminal cabinets, outlet and mounting boxes, alarm initiating devices, alarm indicating devices, and control equipment, and all other accessories and miscellaneous items required for an operating system.
- C. The Fire Alarm System supplied under this specification shall be a microprocessor-based network system. All Control Panel Assemblies and connected Field Appliances shall be both designed and manufactured by the same company, and shall be tested and cross-listed as compatible to ensure that a fully functioning Life Safety System is designed and installed.
- D. Existing system devices shall be re-used and maintained fully operational unless otherwise noted. Reconnect and reprogram existing system circuits/devices as required, including interface with security system for system monitoring at Pulaski Highway facility, for a fully functional system.
- E. Test system prior to performing any modifications and report any defects, etc. to the owner in writing. Any defects, malfunctions of the system not reported in advance of performing work shall be the responsibility of the contractor to correct.
- F. All related work specified in other sections shall be properly coordinated with the fire alarm equipment.

1.3 REFERENCES

- A. The system, equipment, installation, and operation shall comply with the current provisions of the following standards and publications:
1. National Electric Code, Article 70.
 2. National Fire Protection Association Standards:
 - a. NFPA72 National Fire Alarm Code
 - b. NFPA 90A Air Conditioning & Ventilation Systems
 - c. NFPA101 Life Safety Code
 3. Local and State Building Codes.
 4. Local Authorities Having Jurisdiction.
 5. Underwriters Laboratories Inc.: The system and all components shall be listed by Underwriters Laboratories Inc. for use in fire protective signaling system under the following standards as applicable:
 - a. UL 864/UOJZ, APOU - Control Units for Fire Protective Signaling Systems.
 - b. UL 268 - Smoke Detectors for Fire Protective Signaling Systems.
 - c. UL 268A - Smoke Detectors for Duct Applications.
 - d. UL 217 - Smoke Detectors Single Station.
 - e. UL 521 - Heat Detectors for Fire Protective Signaling Systems.
 - f. UL 228 - Door Holders for Fire Protective Signaling Systems.
 - g. UL 464 - Audible Signaling Appliances.
 - h. UL 1638 - Visual Signaling Appliances.
 - i. UL 38 - Manually Activated Signaling Boxes.
 - j. UL 346 - Waterflow Indicators for Fire Protective Signaling Systems.
 - k. UL 1971 - Standard for Signaling Devices for the Hearing Impaired.
 - l. UL 1481 - Power Supplies for Fire Protective Signaling Systems.
 - m. UL 1711 - Amplifiers for Fire Protective Signaling Systems.
 - n. UL Fire Protection Equipment Directory.
 - o. UL Electrical Construction Materials Directory.
 6. Americans with Disabilities Act (ADA)
 7. International Standards Organization (ISO)
 - a. ISO-9000
 - b. ISO-9001
 8. Factory Mutual Approval Guide.
 9. State of Delaware Fire Prevention Code.
 10. American Insurance Association Fire Protection Code (Article 14).
 11. Delaware Occupational Safety & Health Act.
 12. International Building Code (IBC).

1.4 DEFINITIONS

- A. FACP: Fire Alarm Control Panel.
- B. HLI: High Level Interface.
- C. NICET: National Institute for Certification in Engineering Technologies.

1.5 ACTION SUBMITTALS

- A. Product Data: For each type of product, including furnished options and accessories.
1. Include construction details, material descriptions, dimensions, profiles, and finishes.
 2. Include rated capacities, operating characteristics, and electrical characteristics.
- B. Shop Drawings: For fire-alarm system.
1. Comply with recommendations and requirements in the "Documentation" section of the "Fundamentals" chapter in NFPA 72.
 2. Include plans, elevations, sections, details, and attachments to other work.
 3. Include details of equipment assemblies. Indicate dimensions, weights, loads, required clearances, method of field assembly, components, and locations. Indicate conductor sizes, indicate termination locations and requirements, and distinguish between factory and field wiring.
 4. Detail assembly and support requirements.
 5. Include voltage drop calculations for notification-appliance circuits.
 6. Include battery-size calculations.
 7. Include input/output matrix.
 8. Include statement from manufacturer that all equipment and components have been tested as a system and meet all requirements in this Specification and in NFPA 72.
 9. Include performance parameters and installation details for each detector.
 10. Verify that each duct detector is listed for complete range of air velocity, temperature, and humidity possible when air-handling system is operating.
 11. Include plans, sections, and elevations of heating, ventilating, and air-conditioning ducts, drawn to scale; coordinate location of duct smoke detectors and access to them.
 - a. Show critical dimensions that relate to placement and support of sampling tubes, detector housing, and remote status and alarm indicators.
 - b. Locate detectors according to manufacturer's written recommendations.
 12. Include voice/alarm signaling-service equipment rack or console layout, grounding schematic, amplifier power calculation, and single-line connection diagram.
 13. Include floor plans to indicate final outlet locations showing address of each addressable device. Show size and route of cable and conduits and point-to-point wiring diagrams.
 14. Submit wiring diagrams for all equipment connected to fire alarm system. Examples are monitoring of hood extinguishing systems, sprinkler systems, HVAC control, damper control, elevator recall and elevator power shunt trip of the elevator system control.
- C. General Submittal Requirements:
1. Submittals shall be approved by authorities having jurisdiction prior to submitting them to Architect.
 - a. Secure permits and approvals prior to installation.
 - b. Prior to commencement and after completion of work, notify Authorities Having Jurisdiction.
 - c. Submit letter of approval for installation before requesting acceptance of system.
 2. Shop Drawings shall be prepared by persons with the following qualifications:
 - a. Trained and certified by manufacturer in fire-alarm system design.
 - b. NICET-certified, fire-alarm technician; Level III minimum.
 - c. Licensed or certified by authorities having jurisdiction.

1.6 INFORMATIONAL SUBMITTALS

- A. Qualification Data: For Installer.
- B. Seismic Qualification Certificates: For fire-alarm control unit, accessories, and components, from manufacturer.
 - 1. Basis for Certification: Indicate whether withstand certification is based on actual test of assembled components or on calculation.
 - 2. Dimensioned Outline Drawings of Equipment Unit: Identify center of gravity and locate and describe mounting and anchorage provisions.
 - 3. Detailed description of equipment anchorage devices on which the certification is based and their installation requirements.
- C. Field quality-control reports.

1.7 WARRANTY

- A. For materials and workmanship for a period of two years from final system acceptance.

1.8 CLOSEOUT SUBMITTALS

- A. Operation and Maintenance Data: For fire-alarm systems and components to include in emergency, operation, and maintenance manuals.
 - 1. In addition to items specified in Division 01 "Operation and Maintenance Data," include the following and deliver copies to authorities having jurisdiction:
 - a. Comply with the "Records" section of the "Inspection, Testing and Maintenance" chapter in NFPA 72.
 - b. Provide Fire Alarm and Emergency Communications System Record of Completion Documents according to the "Completion Documents" Article in the "Documentation" section of the "Fundamentals" chapter in NFPA 72.
 - c. Complete wiring diagrams showing connections between all devices and equipment. Each conductor shall be numbered at every junction point with indication of origination and termination points.
 - d. Riser diagram.
 - e. Device addresses.
 - f. Record copy of site-specific software.
 - g. Provide "Inspection and Testing Form" according to the "Inspection, Testing and Maintenance" chapter in NFPA 72, and include the following:
 - 1) Equipment tested.
 - 2) Frequency of testing of installed components.
 - 3) Frequency of inspection of installed components.
 - 4) Requirements and recommendations related to results of maintenance.
 - 5) Manufacturer's user training manuals.
 - h. Manufacturer's required maintenance related to system warranty requirements.
 - i. Abbreviated operating instructions for mounting at fire-alarm control unit and each annunciator unit.

B. Software and Firmware Operational Documentation:

1. Software operating and upgrade manuals.
2. Program Software Backup: On magnetic media or compact disk, complete with data files. A total of two copies shall be provided; one read only type and one writeable type.
3. Device address list.
4. Printout of software application and graphic screens.
5. All passcode information required to make alternations to the Fire Alarm Control Panel.

1.9 MAINTENANCE MATERIAL SUBMITTALS

A. Furnish extra materials that match products installed and that are packaged with protective covering for storage and identified with labels describing contents.

1. Lamps for Remote Indicating Lamp Units: Quantity equal to 10 percent of amount installed, but no fewer than one unit.
2. Smoke Detectors, Fire Detectors: Quantity equal to 10 percent of amount of each type installed, but no fewer than one unit of each type.
3. Detector Bases: Quantity equal to two percent of amount of each type installed, but no fewer than one unit of each type.
4. Keys and Tools: One extra set for access to locked or tamperproofed components.
5. Audible and Visual Notification Appliances: One of each type installed.
6. Fuses: Two of each type installed in the system. Provide in a box or cabinet with compartments marked with fuse types and sizes.

1.10 QUALITY ASSURANCE

- A. Installer Qualifications: Personnel shall be trained and certified by manufacturer for installation of units required for this Project.
- B. Installer Qualifications: Installation shall be by personnel certified by NICET as fire-alarm Level III technician.
- C. NFPA Certification: Obtain certification according to NFPA 72 by a UL-listed alarm company.

1.11 PROJECT CONDITIONS

- A. Use of Devices during Construction: Protect devices during construction unless devices are placed in service to protect the facility during construction.

1.12 WARRANTY

- A. Special Warranty: Manufacturer agrees to repair or replace fire-alarm system equipment and components that fail in materials or workmanship within specified warranty period.
 1. Warranty Extent: All equipment and components not covered in the Maintenance Service Agreement.

2. Warranty Period: Five years from date of Substantial Completion.

PART 2. PRODUCTS

2.1 SYSTEM DESCRIPTION

- A. Source Limitations for Fire-Alarm System and Components: Components shall be compatible with, and operate as one system. Provide system manufacturer's certification that all components provided have been tested as, and will operate as, a system.
- B. Noncoded, UL-certified addressable system, with multiplexed signal transmission and horn/strobe evacuation.
- C. Automatic sensitivity control of certain smoke detectors.
- D. All components provided shall be listed for use with the selected system.
- E. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.

2.2 SYSTEMS OPERATIONAL DESCRIPTION

- A. Fire-alarm signal initiation shall be by one or more of the following devices and systems:
 1. Manual stations.
 2. Heat detectors.
 3. Smoke detectors.
 4. Automatic sprinkler system water flow.
 5. Fire-extinguishing system operation.
 6. Dry system pressure flow switch.
- B. Fire-alarm signal shall initiate the following actions:
 1. Continuously operate alarm notification appliances, including voice evacuation notices.
 2. Identify alarm and specific initiating device at fire-alarm control unit, connected network control panels, and remote annunciators.
 3. Transmit an alarm signal to the remote alarm receiving station.
 4. Unlock electric door locks in designated egress paths.
 5. Release fire and smoke doors held open by magnetic door holders.
 6. Activate voice/alarm communication system.
 7. Switch heating, ventilating, and air-conditioning equipment controls to fire-alarm mode.
 8. Close smoke dampers in air ducts of designated air-conditioning duct systems.
 9. Activate emergency shutoffs for gas and fuel supplies.
 10. Record events in the system memory.
 11. Indicate device in alarm on the graphic annunciator.
- C. Supervisory signal initiation shall be by one or more of the following devices and actions:

1. Valve supervisory switch.
2. High- or low-air-pressure switch of a dry-pipe or preaction sprinkler system.
3. Duct smoke detectors.
4. Independent fire-detection and -suppression systems.
5. User disabling of zones or individual devices.
6. Loss of communication with any panel on the network.

D. System trouble signal initiation shall be by one or more of the following devices and actions:

1. Open circuits, shorts, and grounds in designated circuits.
2. Opening, tampering with, or removing alarm-initiating and supervisory signal-initiating devices.
3. Loss of communication with any addressable sensor, input module, relay control module, remote annunciator, printer interface, or Ethernet module.
4. Loss of primary power at fire-alarm control unit.
5. Ground or a single break in internal circuits of fire-alarm control unit.
6. Abnormal ac voltage at fire-alarm control unit.
7. Break in standby battery circuitry.
8. Failure of battery charging.
9. Abnormal position of any switch at fire-alarm control unit or annunciator.
10. Voice signal amplifier failure.

E. System Supervisory Signal Actions:

1. Identify specific device initiating the event at fire-alarm control unit, connected network control panels, and remote annunciator.
2. After a time delay of 200 seconds, transmit a trouble or supervisory signal to the remote alarm receiving station.
3. Transmit system status to building management system.
4. Display system status on graphic annunciator.

2.3 PERFORMANCE REQUIREMENTS

A. Seismic Performance - Fire-alarm control unit and raceways shall withstand the effects of earthquake motions determined according to ASCE/SEI 7.

1. The term "withstand" means "the unit will remain in place without separation of any parts from the device when subjected to the seismic forces specified and the unit will be fully operational after the seismic event."

2.4 SYSTEM SMOKE DETECTORS

A. General Requirements for System Smoke Detectors:

1. Comply with UL 268; operating at 24-V dc, nominal.
2. Detectors shall be two-wire type.
3. Integral Addressable Module: Arranged to communicate detector status (normal, alarm, or trouble) to fire-alarm control unit.

4. Base Mounting: Detector and associated electronic components shall be mounted in a twist-lock module that connects to a fixed base. Provide terminals in the fixed base for connection to building wiring.
5. Self-Restoring: Detectors do not require resetting or readjustment after actuation to restore them to normal operation.
6. Integral Visual-Indicating Light: LED type, indicating detector has operated and power-on status.
7. Remote Control: Unless otherwise indicated, detectors shall be digital-addressable type, individually monitored at fire-alarm control unit for calibration, sensitivity, and alarm condition and individually adjustable for sensitivity by fire-alarm control unit.
 - a. Multiple levels of detection sensitivity for each sensor.
 - b. Sensitivity levels based on time of day.

B. Duct Smoke Detectors: Photoelectric type complying with UL 268A.

1. Detector address shall be accessible from fire-alarm control unit and shall be able to identify the detector's location within the system and its sensitivity setting.
2. An operator at fire-alarm control unit, having the designated access level, shall be able to manually access the following for each detector:
 - a. Primary status.
 - b. Device type.
 - c. Present average value.
 - d. Present sensitivity selected.
 - e. Sensor range (normal, dirty, etc.)
3. Weatherproof Duct Housing Enclosure: NEMA 250, Type 4X; NRTL listed for use with the supplied detector for smoke detection in HVAC system ducts.
4. Each sensor shall have multiple levels of detection sensitivity.
5. Sampling Tubes: Design and dimensions as recommended by manufacturer for specific duct size, air velocity, and installation conditions where applied.
6. Relay fan shut down: Fully programmable relay related to interrupt fan motor-control circuit.

2.5 CARBON MONOXIDE DETECTORS

- A. Provide carbon monoxide detector listed for connection to fire-alarm system.

1. Mounting: Adapter plate for outlet box mounting.
2. Testable by introducing test carbon monoxide into the sensing cell.
3. Detector shall provide alarm contacts and trouble contacts.
4. Detector shall send trouble alarm when nearing end-of-life, power supply problems, or internal faults.
5. Comply with UL 2075.
6. Locate, mount, and wire according to manufacturer's written instructions.
7. Provide means for addressable connection to fire-alarm system.
8. Test button simulates an alarm condition

2.6 ADDRESSABLE INTERFACE DEVICE

A. General:

1. Include address-setting means on the module.
2. Store an internal identifying code for control panel use to identify the module type.
3. Listed for controlling HVAC fan motor controllers.

B. Monitor Module: Microelectronic module providing a system address for alarm-initiating devices for wired applications with normally open contacts. Provide for all sprinkler flow and tamper switches, and as required.

C. Integral Relay: Capable of providing a direct signal to elevator controller to initiate elevator recall, to circuit-breaker shunt trip for power shutoff, etc.

1. Allow the control panel to switch the relay contacts on command.
2. Have a minimum of two normally open and two normally closed contacts available for field wiring.

D. Control Module:

1. Operate notification devices.
2. Operate solenoids for use in sprinkler service.
3. Mute sound system(s).
4. Unlock security doors.

2.7 REMOTE TEST/INDICATING STATION

- A. Provide keyed test switch with LED indicating light for each duct detector. Locate 12" below accessible ceiling.

PART 3. EXECUTION

3.1 EXAMINATION

- A. Examine areas and conditions for compliance with requirements for ventilation, temperature, humidity, and other conditions affecting performance of the Work.

1. Verify that manufacturer's written instructions for environmental conditions have been permanently established in spaces where equipment and wiring are installed, before installation begins.
- B. Examine roughing-in for electrical connections to verify actual locations of connections before installation.
- C. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 EQUIPMENT INSTALLATION

- A. Comply with NFPA 72, NFPA 101, and requirements of authorities having jurisdiction for installation and testing of fire-alarm equipment. Install all electrical wiring to comply with requirements in NFPA 70 including, but not limited to, Article 760, "Fire Alarm Systems."
 1. Devices placed in service before all other trades have completed cleanup shall be replaced.
 2. Devices installed but not yet placed in service shall be protected from construction dust, debris, dirt, moisture, and damage according to manufacturer's written storage instructions.
- B. Install wall-mounted equipment, with tops of cabinets not more than 78 inches (1980 mm) above the finished floor.
- C. Smoke- or Heat-Detector Spacing:
 1. Comply with the "Smoke-Sensing Fire Detectors" section in the "Initiating Devices" chapter in NFPA 72, for smoke detector spacing.
 2. Comply with the "Heat-Sensing Fire Detectors" section in the "Initiating Devices" chapter in NFPA 72, for heat-detector spacing.
 3. Smooth ceiling spacing shall not exceed 30 feet (9 m).
 4. Spacing of detectors for irregular areas, for irregular ceiling construction, and for high ceiling areas shall be determined according to Annex A in NFPA 72.
 5. HVAC: Locate detectors not closer than 36 inches (910 mm) from air-supply diffuser or return-air opening.
 6. Lighting Fixtures: Locate detectors not closer than 12 inches (300 mm) from any part of a lighting fixture and not directly above pendant mounted or indirect lighting.
- D. Install a cover on each smoke detector that is not placed in service during construction. Cover shall remain in place except during system testing. Remove cover prior to system turnover.
- E. Duct Smoke Detectors: Comply with NFPA 72 and NFPA 90A. Install sampling tubes so they extend the full width of duct. Tubes more than 36 inches (9100 mm) long shall be supported at both ends.
- F. Remote Status and Alarm Indicators: Install in a visible location near each smoke detector, sprinkler water-flow switch, and valve-tamper switch that is not readily visible from normal viewing position.
- G. Device Location-Indicating Lights: Locate in public space near the device they monitor.

3.3 PATHWAYS

- A. Pathways above recessed ceilings and in non-accessible locations may be routed exposed.
 - 1. Exposed pathways located less than 96 inches (2440 mm) above the floor shall be installed in EMT.
- B. Pathways shall be installed in EMT.
- C. Exposed EMT shall be painted red enamel.

3.4 CONNECTIONS

- A. For fire-protection systems related to doors in fire-rated walls and partitions and to doors in smoke partitions, comply with requirements in Division 08 "Door Hardware." Connect hardware and devices to fire-alarm system.
 - 1. Verify that hardware and devices are listed for use with installed fire-alarm system before making connections.
- B. Make addressable connections with a supervised interface device to the following devices and systems. Install the interface device less than 36 inches (910 mm) from the device controlled. Make an addressable confirmation connection when such feedback is available at the device or system being controlled.
 - 1. Smoke dampers in air ducts or designated HVAC duct systems.
 - 2. Magnetically held-open doors.
 - 3. Electronically locked doors and access gates.
 - 4. Alarm-initiating connections to activate emergency shutoffs for gas and fuel supplies.
 - 5. Supervisory connections at valve supervisory switches.
 - 6. Supervisory connections at low-air-pressure switch of each dry-pipe sprinkler system.
 - 7. Data communication circuits for connection to building management system.
- C. Each addressable analog loop shall be circuited as shown on the drawings but device loading is not to exceed 80% of loop capacity in order to leave space for future devices.
- D. Where it is necessary to interface conventional initiating devices, provide intelligent input modules to supervise Class B zone wiring.

3.5 IDENTIFICATION

- A. Identify system components, wiring, cabling, and terminals. Comply with requirements for identification specified in Section 16075 "Identification for Electrical Systems."
- B. Install framed instructions in a location visible from fire-alarm control unit.

3.6 GROUNDING

- A. Ground fire-alarm control unit and associated circuits; comply with IEEE 1100. Install a ground wire from main service ground to fire-alarm control unit.
- B. Ground shielded cables at the control panel location only. Insulate shield at device location.

3.7 FIELD QUALITY CONTROL

- A. Field tests shall be witnessed by authorities having jurisdiction.
- B. Manufacturer's Field Service: Engage a factory-authorized service representative to test and inspect components, assemblies, and equipment installations, including connections.
- C. Perform tests and inspections.
- D. Perform the following tests and inspections with the assistance of a factory-authorized service representative:
 - 1. Visual Inspection: Conduct visual inspection prior to testing.
 - a. Inspection shall be based on completed record drawings and system documentation that is required by the "Completion Documents, Preparation" table in the "Documentation" section of the "Fundamentals" chapter in NFPA 72.
 - b. Comply with the "Visual Inspection, Frequencies" table in the "Inspection" section of the "Inspection, Testing and Maintenance" chapter in NFPA 72; retain the "Initial/Reacceptance" forms and list only the installed components.
 - 2. System Testing: Comply with the "Test Methods" table in the "Testing" section of the "Inspection, Testing and Maintenance" chapter in NFPA 72.
 - 3. Test audible appliances for the public operating mode according to manufacturer's written instructions. Perform the test using a portable sound-level meter complying with Type 2 requirements in ANSI S1.4.
 - 4. Test audible appliances for the private operating mode according to manufacturer's written instructions.
 - 5. Test visible appliances for the public operating mode according to manufacturer's written instructions.
 - 6. Factory-authorized service representative shall prepare the "Fire Alarm System Record of Completion" in the "Documentation" section of the "Fundamentals" chapter in NFPA 72 and the "Inspection and Testing Form" in the "Records" section of the "Inspection, Testing and Maintenance" chapter in NFPA 72.
- E. Reacceptance Testing: Perform reacceptance testing to verify the proper operation of added or replaced devices and appliances.
- F. Fire-alarm system will be considered defective if it does not pass tests and inspections.
- G. Prepare test and inspection reports.
- H. Maintenance Test and Inspection: Perform tests and inspections listed for weekly, monthly, quarterly, and semiannual periods. Use forms developed for initial tests and inspections.

- I. Annual Test and Inspection: One year after date of Substantial Completion, test fire-alarm system complying with visual and testing inspection requirements in NFPA 72. Use forms developed for initial tests and inspections.

3.8 MAINTENANCE SERVICE

- A. Initial Maintenance Service: Beginning at Substantial Completion, maintenance service shall include 12 months' full maintenance by skilled employees of manufacturer's designated service organization. Include preventive maintenance, repair or replacement of worn or defective components, lubrication, cleaning, and adjusting as required for proper operation. Parts and supplies shall be manufacturer's authorized replacement parts and supplies.
 1. Include visual inspections according to the "Visual Inspection Frequencies" table in the "Testing" paragraph of the "Inspection, Testing and Maintenance" chapter in NFPA 72.
 2. Perform tests in the "Test Methods" table in the "Testing" paragraph of the "Inspection, Testing and Maintenance" chapter in NFPA 72.
 3. Perform tests per the "Testing Frequencies" table in the "Testing" paragraph of the "Inspection, Testing and Maintenance" chapter in NFPA 72.

3.9 SOFTWARE SERVICE AGREEMENT

- A. Comply with UL 864.
- B. Technical Support: Beginning at Substantial Completion, service agreement shall include software support for two years.
- C. Upgrade Service: At Substantial Completion, update software to latest version. Install and program software upgrades that become available within two years from date of Substantial Completion. Upgrading software shall include operating system and new or revised licenses for using software.
 1. Upgrade Notice: At least 30 days to allow Owner to schedule access to system and to upgrade computer equipment if necessary.

3.10 DEMONSTRATION

- A. Engage a factory-authorized service representative to train Owner's maintenance personnel to adjust, operate, and maintain fire-alarm system.

END OF SECTION

NOT FOR BIDDING PURPOSES